

BOOK 4704

Form 4-679  
(January 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

DEPENDENT RESURVEY

North, East and West Boundaries

and

Subdivisional Lines

Township 16 North, Range 26 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

## EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Paul G. Bauer, Cadastral Surveyor

Under special instructions dated March 13, 19 63, which provided for the surveys included under Group Number 389, approved March 18, 1963, and assignment instructions dated November 26, 19 63.

Survey commenced November 27, 19 63

Survey completed January 29, 19 64

1A

# BOOK 4704 INDEX DIAGRAM

Township 16 North, Range 26 East

		1	2	3	3	4	4		
		49( $\frac{1}{4}$ )	48( $\frac{1}{4}$ )	39( $\frac{1}{4}$ )	33( $\frac{1}{4}$ )	27( $\frac{1}{4}$ )	20( $\frac{1}{4}$ )		
13		6 48	5 39	4 33	3 26	2 19	1		9
		47	47	38	32	25	19		
12		7 46	8 38	9 31	10 25	11 18	12		8
		46	45	37	31	24	18		
11		18 45	17 37	16 30	15 23	14 17	13		7
		44	44	36	30	23	17		
11		19 43	20 36	21 29	22 22	23 16	24		7
		42	42	35	29	22	15		
10		30 41	29 34	28 28	27 21	26 15	25		6
		41	40	34	28	21	14		
9		31 40	32 33	33 27	34 20	35 13	36		5

BOOK 4701  
Township 16 North, Range 26 East  
Gila and Salt River Meridian, Arizona

CHAINS

The south boundary was surveyed by O. D. Wheeler in 1882 and was currently resurveyed under this same Group for T15N, R26E. The north boundary, (the Fourth Standard Parallel North), the east and west boundaries and the subdivisional lines were surveyed in 1882 by H. A. Coe.

The following notes are those of a dependent resurvey of the north boundary (the Fourth Standard Parallel North), the east and west boundaries, and the subdivisional lines of Township 16 North, Range 26 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions, dated March 13, 1963.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top. Original corner monuments were deposited alongside the new monuments unless described otherwise.

The geographic position of the southeast corner of the township is: Latitude, 34°44'52.0" North and Longitude, 109°31'32.9" West.

The magnetic declination was found to be 14° East.

---

Dependent Resurvey  
Fourth Standard Parallel North  
through Range 26 East

---

Reestablishment of the Survey in 1882  
by H. A. Coe

---

The standard township cor. of T17N, R25&26E, monumented by a 3"x 3"x 3" cedar post, firmly set and plainly mkd. with 6 notches on each edge.

At the cor. point

Set the iron post 22 ins. in the ground, cap mkd.

SC  
T17N  
R25E R26E  
S36 | S31  
1963

The cor. is located in a N-S fence line, 0.04 lks. south of fence bearing West.

N. 89°08' E., along the S. bdy. of sec. 31.

Over nearly level grass land.

15.50 Track road, bears N. 35°E., and S. 35° W.

34.40 Track road, bears NE. and SW.

CHAINS

40.59

Point for the Standard  $\frac{1}{4}$  sec. cor. of sec. 31 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, mound with stone to top, cap mkd.

SC  
T17N R26E  
 $\frac{1}{4}$  S31  
-----  
1963

81.17

Point for the standard corner of secs. 31 and 32 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground and in a collar of stone, cap mkd.

SC  
T17N R26E  
S31|S32  
-----  
1963

Land, nearly level range land.  
Soil, sandy clay loam.  
No timber; undergrowth, yellow brush.

---

N. 89°08' E., along the S. bdy. of sec. 32.

Over nearly level range land.

40.59

Point for the Standard  $\frac{1}{4}$  sec. cor. of sec. 32, at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground and in a collar of stone, cap mkd.

SC  
T17N R26E  
 $\frac{1}{4}$  S32  
-----  
1963

47.40

Wash, 20 lks. wide, 2 ft. deep, drains S. 10° W.

81.17

Point for the Standard cor. of secs. 32 and 33 at proportionate dist.; unable fo find any evidence of the original cor.

Set the iron post 22 ins. in the ground and in a collar of stone, cap mkd.

SC  
T17N R26E  
S32|S33  
-----  
1963

Land, nearly level.  
Soil, sandy clay loam.  
No timber; undergrowth, yellow brush.

---

LOG# 4704

Resurvey, 4th Stan. Par. North, R26E, Arizona

3.

CHAINS	
	<p>N. 89°08' E., along the S. bdy. of sec. 33.</p> <p>Over nearly level grass land.</p>
40.59	<p>Point for the Standard <math>\frac{1}{4}</math> sec. cor. of sec. 33, at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, and in a collar of stone, cap mkd.</p> <p style="text-align: center;">SC T17N R26E <math>\frac{1}{4}</math> S33 ----- 1963</p>
42.10	<p>Wash, 100 lks. wide, 4 ft. deep, drains S. 55° W.</p>
75.20	<p>Track road bears S. 30° W. and N. 20° E.</p>
81.17	<p>Point for the Standard cor. of secs. 33 and 34 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground and in a collar of stone, cap mkd.</p> <p style="text-align: center;">SC T17N R26E S33 S34 ----- 1963</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, scattered yellow brush.</p> <hr/> <p>N. 89°08' E., along the S. bdy. of sec. 34.</p> <p>Over nearly level grass land.</p>
40.59	<p>Point for the Standard <math>\frac{1}{4}</math> sec. cor. of sec. 34 at proportionate dist.; unable to locate any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">SC T17N R26E <math>\frac{1}{4}</math> S34 ----- 1963</p>
81.17	<p>Point for the Standard cor. of secs. 34 and 35 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">SC T17N R26E S34 S35 ----- 1963</p> <p>Raise a mound of stone N. of the cor.</p>

BOOK 4704

4

Resurvey, 4th Stan, Par. North, R26E, Arizona

4.

CHAINS

Land, nearly level.  
Soil, sandy clay loam.  
No timber; undergrowth, yellow brush and sage.

---

N. 89°08' E., along the S. bdy. of sec. 35.

Over nearly level grass land.

3.30 Fence, bears S. 80° W. and N. 80° E.

14.50 Enter low rolling clay hills.

40.59 Point for the Standard  $\frac{1}{4}$  sec. cor. of sec. 35 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.

SC  
T17N R26E  
 $\frac{1}{4}$  S35  
-----  
1963

48.50 Blade road, bears S. and N. 10° W.

63.10 Wash, 20 lks. wide, 2 ft. deep, drains S. 80° W.

81.17 Point for the Standard cor. of secs. 35 and 36 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

SC  
T17N R26E  
S35|S36  
-----  
1963

Raise a mound of stone N. of the cor.

Land, gently rolling.  
Soil, clay loam and sand.  
No timber; scattered yellow brush.

---

N. 89°08' E., along the S. bdy. of sec. 36.

Over gently rolling range land.

12.10 Fence, 5 strand barbed wire, bears N. 8°15' E. and S. 8°15' W.

23.30 Wash, 5 lks. wide, 2 ft. deep, drains SW.

40.59 Point for the Standard  $\frac{1}{4}$  sec. cor. of sec. 36 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

SC  
T17N R26E  
 $\frac{1}{4}$  S36  
-----  
1963

CHAINS	
	Raise a mound of stone N. of the cor.
	Asc. over steep, barren clay hills.
55.00	Enter scattered timber.
60.60	Rim of bluff, bears SW. and NE.; desc. over gentle E. slope, along old fence line.
78.96	Fence, bears N. 9°10' E., and S. 6°45' E.
81.17	The Standard Cor. of T17N, Rs26&27E, monumented by an iron post as described in the survey notes of T16N, R28E, resurveyed under Group No. 390, Arizona.
	Land, sandy and clay loam. Timber, scattered juniper on E. 25.00 chs. Undergrowth, yellow brush.
<hr/> <p>Dependent Resurvey of the East Boundary Township 16 North, Range 26 East</p> <hr/> <p>Reestablishment of the Survey in 1882 by H. A. Coe</p> <hr/>	
	From the cor. of Ts15 and 16N, Rs26 and 27E, monumented by an iron post as described in the field notes of T15N, R26E, recently resurveyed under this same Group.
	N. 1°06' W., bet. secs. 31 and 36.
	Over rolling land through moderate timber.
9.00	Road, bears N. 48°05' E. and S. 48°05' W.
20.50	Desc. over N. slope.
34.80	Wash, 20 lks. wide, 2 ft. deep, drains N. 40° W.
40.22	Point for the ¼ sec. cor. of secs. 31 and 36 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 20 ins. in the ground, cap mkd.
	<p>T16N R26E R27E ¼ S36   S31 1963</p>
	from which
	<p>A juniper, 7 ins. diam., bears N. 13°45' E., 30 lks. dist., mkd. T16NR27E¼S31BT</p>
	Raise a mound of stone West of the cor.
	Desc. over rolling land, NW. drainage and exposure.
80.45	Point for the cor. of secs. 25, 30, 31 and 36 at proportionate dist.; unable to find any evidence of the original cor.

6

CHAINS

Set the iron post 20 ins. in the ground, cap mkd.

T16N  
R26E R27E  
S25 | S30  
S36 | S31  
1963

Raise a mound of stone West of the cor.

Cor. is located in basin bearing N. 60° W. and S. 60° E.

Land, rolling.  
Soil, clay loam.  
Timber, moderate to scattered juniper.  
Undergrowth, sagebrush.

N. 1°06' W., bet. secs. 25 and 30.

Over rolling land.

26.90 Track road, bears N. 40° E. and S. 40° W.

40.22 Point for the 1/4 sec. cor. of secs. 25 and 30 at proportionate dist.; unable to locate any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N  
R26E R27E  
<sup>1/4</sup>  
S25 | S30  
1964

Raise a mound of stone West of cor.

Continue over nearly level valley through widely scattered timber.

77.40 Fence, 3 strand barbed wire, bears S. 89°30' E. and N. 89°30' W.

80.45 Point for the cor. of secs. 19, 24, 25 and 30 at proportionate dist.; unable to locate any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N  
R26E R27E  
S24 | S19  
S25 | S30  
1964

Deposit glass in the hole dug for iron post.

Land, rolling.  
Soil, clay loam and sandy.  
Timber, scattered junipers.  
Undergrowth, sage and yellow brush.

CHAINS	
	<p>N. 1°06' W., bet. secs. 19 and 24.</p> <p>Over rolling land through scattered timber.</p>
17.60	<p>Wash, 80 lks. wide, 10 ft. banks, drains irregularly S. 50° W.; cont. over valley floor.</p>
40.22	<p>Point for the ¼ sec. cor. of secs. 19 and 24 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E R27E ¼ S24 S19 1964</p> </div> <p>Raise a mound of stone West of the cor.</p>
62.80	<p>Wash, 60 lks. wide, 4 ft. deep, drains S. 60° W.; asc. over clay hills facing S.</p>
80.45	<p>Point for the cor. of secs. 13, 18, 19 and 24 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 18 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E R27E S13 S18 S24 S19 1963</p> </div> <p>The cor. is located on E. slope of clay spur sloping S. 30° E.</p> <p>No accessories available.</p> <p>Land, rolling and broken. Soil, sandy and clay loam. Timber, widely scattered juniper. Undergrowth, scattered shadscale and brush.</p> <hr/> <p>N. 1°06' W., bet. secs. 13 and 18.</p> <p>Asc. over broken clay hills.</p>
12.40	<p>N. side of valley, bears E. and W.; thence over rolling land through scattered timber.</p>
35.90	<p>Rim, bears S. 70° W. and N. 70° E.; leave timber, desc. over barren N. slope.</p>
40.22	<p>Point for the ¼ sec. cor. of secs. 13 and 18 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E R27E ¼ S13 S18 1963</p> </div>

8

CHAINS

Deposit glass in the hole dug for iron post.

60.60 Desc. over gentle N. slope, through scattered timber.

76.00 Wash, 30 lks. wide, 5 ft. banks, drains S. 85° W.; asc. over gentle S. slope.

80.45 Point for the cor. of secs. 7, 12, 13 and 18 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N  
R26E R27E  
S12|S7  
S13|S18  
1963

Deposit glass in the hole dug for iron post.

Land, rolling, slightly broken.  
Soil, clay loam.  
Timber, widely scattered junipers.  
Undergrowth, shadscale and brush.

N. 1°06' W., bet. secs. 7 and 12.

Over gently rolling land; asc. gentle S. slope.

7.20 Low rim, bears N. 70° E. and S. 70° W.; enter scattered timber.

40.22 Point for the 1/2 sec. cor. of secs. 7 and 12 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N  
R26E R27E  
1/2  
S12|S7  
1963

74.30 Old fence, bears N. 88°20' W.

80.45 Point for the cor. of secs. 1, 6, 7 and 12 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N  
R26E R27E  
S1|S6  
S12|S7  
1963

Deposit glass in the hole dug for iron post.

Land, rolling.  
Soil, clay loam and sandy.  
Timber, scattered junipers.  
Undergrowth, yellow brush and sage.

BOOK 6724

Resurvey, E. Bdy., T16N, R26E, Arizona

CHAINS

N. 1°06' W., bet. secs. 1 and 6.

Over gently rolling land.

5.44 Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 1 and 6 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T17N	
S36	
S 1	S 6
R26E	R27E
T16N	
CC	
1963	

from which

The Standard Township Cor. of T17N, Rs26&27E, bears N. 89°09' E., 2.26 chs. dist.

South gate post in N-S fence line bears N. 23° E .05 lks. dist.

Cor. is in old E-W fence line.

Raise a mound of stone South of the cor.

Land, rolling.  
Soil, sandy clay.  
Timber, scattered junipers.  
Undergrowth, yellow brush and sage.

---

Dependent Resurvey of the West Boundary  
Township 16 North, Range 26 East

---

Reestablishment of the Survey in 1882  
by H. A. Coe

---

From the cor. of Ts15&16N, Rs25&26E, an iron post as described in the field notes of T15N, R26E, recently resurveyed under this same Group.

N. 1°27' W., bet. secs. 31 and 36.

Over gently rolling grass land.

25.20 Wash, 100 lks. wide, 2 ft. deep, drains N. 85° W. circling to S.

38.41 Point selected for the witness ¼ sec. cor. of secs. 31 and 36.

Set the iron post 20 ins. in the ground, cap mkd.

T16N	
R25E R26E	
¼	
WC	
S36	S31
1963	

CHAINS

Raise a mound of stone West of the cor.

39.81 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 36 at proportionate dist., falls in same wash as one at 25.20 - E. drainage. Unable to find any evidence of the original cor.

52.40 Same wash, drains S. 30° W.

79.62 Point for the cor. of secs. 25, 30, 31 and 36 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N  
R25E R26E  
S25|S30  
S36|S31  
1963

from which

N-S fence line bears West, 8.41 chs. dist.

Raise a mound of stone West of the cor.

Land, gently rolling.  
Soil, sandy clay loam.  
No timber; undergrowth, scattered yellow brush and sage.

N. 1°27' W., bet. secs. 25 and 30.

Over nearly level grass land.

35.80 Wash, 15 lks. wide, 2 ft. deep, drains SE.

39.81 Point for the  $\frac{1}{4}$  sec. cor. of secs. 25 and 30 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N  
R25E R26E  
 $\frac{1}{4}$   
S25|S30  
1963

Raise a mound of stone West of the cor.

79.62 Point for the cor. of secs. 19, 24, 25 and 30 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N  
R25E R26E  
S24|S19  
S25|S30  
1963

from which

N-S fence line, bears West, 6.67 chs. dist.

CHAINS	
	<p>Raise a mound of stone West of the cor.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, scattered yellow brush.</p>
	<p>N. 1°27' W., bet. secs. 19 and 24.</p>
	<p>Over nearly level grass land.</p>
18.70	<p>Crest of low rise, bears E. and W.</p>
39.81	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 24 at proportionate dist.; unable to find any evidence of the original cor.</p>
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R25E R26E <math>\frac{1}{4}</math> S24 S19 1963</p>
	<p>Raise a mound of stone West of the cor.</p>
54.30	<p>Wash, 5 lks. wide, 1 ft. deep, drains S. 75° E.</p>
79.62	<p>Point for the cor. of secs. 13, 18, 19 and 24 at proportionate dist.; unable to find any evidence of the original cor.</p>
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R25E R26E S13 S18 S24 S19 1963</p>
	<p>from which</p>
	<p style="text-align: center;">N-S fence line, bears West, 6.06 chs. dist.</p>
	<p>Raise a mound of stone West of the cor.</p>
	<p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, scattered brush.</p>
	<p>N. 1°27' W., bet. secs. 13 and 18.</p>
	<p>Over gently rolling range land.</p>
39.81	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 18 at proportionate dist.; unable to locate any evidence of the original cor.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R25E R26E <math>\frac{1}{4}</math> S13 S18 1963</p>

BOOK 4704

Resurvey, W. Bdy., T16N, R26E, Arizona

12.

12

CHAINS

Raise a mound of stone West of the cor.

76.60 Desc. over gentle N. slope.

79.62 Point for the cor. of secs. 7, 12, 13 and 18 at proportionate dist.; unable to locate any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N  
R25E R26E  
S12|S7  
S13|S18  
1963

from which

N-S fence line bears W., 3.00 chs. dist.

Raise a mound of stone West of the cor.

Land, gently rolling.  
Soil, sandy clay loam.  
No timber, scattered brush.

N. 1°27' W., bet. secs. 7 and 12.

Over gently rolling range land.

9.90 Dim track road, bears NW. and SE.

12.50 Approximate dist. to fence, bears N. 47°40' E. and S. 47°40' W. about 2.50 chs., thence S.

39.81 Point for the 1/2 sec. cor. of secs. 7 and 12 at proportionate dist.; unable to locate any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N  
R25E R26E  
1/2  
S12|S7  
1963

Raise a mound of stone West of the cor.

40.10 Road, bears N. 15° E. and S. 15° W. (approximate dist.)

74.60 Track road bears NE. and SW. (approximate dist.)

79.62 Point for the cor. of secs. 1, 6, 7 and 12 at proportionate dist.; unable to locate any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N  
R25E R26E  
S1|S6  
S12|S7  
1963

BOOK 4704

Resurvey, W. Bdy., T16N, R26E, Arizona

13.

CHAINS

Raise a mound of stone West of the cor.  
 Land, gently rolling.  
 Soil, sandy clay loam.  
 No timber, undergrowth, sage and yellow brush.

N. 1°27' W., bet. secs. 1 and 6.

Desc. over gentle N. slope.

18.60 Dim track road, bears NE. and SW.

32.00 Wash on bend, 250 lks. wide, 3 ft. deep, drains south about 3.00 chs., thence S. 60° W.

59.82 Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 1 and 6 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T17N R25E  
 S36  
 S 1 | S 6  
 R25E R26E  
 T16N.  
 CC  
 1963

from which

The Standard Township Cor. of T17N, Rs25&26E bears S. 88°55' E., 32.03 chs. dist.

The Standard Township Cor. of T17N, Rs24&25E bears N. 88°55' W., 440.03 chs. dist., monumented by a 3-inch iron post as described in the official record.

Raise a mound of stone South of the closing cor.

Land, gently rolling.  
 Soil, sandy clay loam.  
 No timber; undergrowth, sage and yellow brush.

Dependent Resurvey of the Subdivisional Lines  
 Township 16 North, Range 26 East

Reestablishment of the Survey in 1882  
 by H. A. Coe

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the township, monumented by an iron post as described in the field notes of T15N, R26E, recently resurveyed under this same Group.

N. 1°23' W., bet. secs. 35 and 36.

Desc. over rolling clay hills putting West, scattered timber.

CHAINS	
11.60	Desc. over N. slope.
16.80	Wash, 6 lks. wide, 1 ft. deep, drains NW.; thence over valley floor.
40.20	Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R26E  <math>\frac{1}{4}</math>  S35   S36  1964</p>
	Raise a mound of stone West of the cor.
48.30	Leave timber.
53.40	West edge of stock ponds.
60.50	Track road, bears S. 55° W. and N. 60° E.
73.00	Small gully, drains NW.
80.40	Point for the cor. of secs. 25, 26, 35 and 36 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R26E  <u>S26   S25</u>  S35   S36  1964</p>
	Raise a mound of stone West of the cor.
	<p>Land, rolling clay hills on S. 15 chs., gently rolling grassland on remainder.  Soil, clay and sandy clay loam.  Timber, scattered juniper on S. 48.00 chs.  Undergrowth, low sage and yellow brush.</p>
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the township.
	S. 83°41' W., bet. secs. 25 and 36.
	Over gently rolling grass land, through widely scattered timber.
10.50	Wash, 100 lks. wide, 1 ft. deep, drains N.
19.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 30° W.
40.25	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p style="text-align: center;">T16N R26E  <math>\frac{1}{4}</math> <math>\frac{S 25}{S 36}</math>  1964</p>

BOOK 4704

Dep. Resurvey, Subdivision, T16N, R26E, Arizona

CHAINS	
	Raise a mound of stone N. of the cor.
48.10	Track road, bears NE. and SW.
60.00	Leave widely scattered timber.
80.50	The cor. of secs. 25, 26, 35 and 36.  Land, gently rolling grass land. Soil, clay loam. Timber, widely scattered juniper on E. 60 chs. Undergrowth, low sage and yellow brush.
	N. 1°06' W., bet. secs. 25 and 26.  Over nearly level grass land.
39.30	Small wash, drains W.
40.20	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26 at proportionate dist.; unable to find any evidence of the original cor.  Set the iron post 22 ins. in the ground, cap mkd.
	T16N R26E $\frac{1}{4}$ S26   S25 1964
	Raise a mound of stone West of the cor.
46.20	Wash, 60 lks. wide, 3 ft. deep, drains S. 65° W.
57.80	Wash, 200 lks. wide, 4 ft. banks, drains S. 65° W.
79.50	Wash, 10 lks. wide, 2 ft. deep, drains W.
80.40	Point for the cor. of secs. 23, 24, 25 and 26 at proportionate dist.; unable to find any evidence of the original cor.  Set the iron post 22 ins. in the ground, cap mkd.
	T16N R26E S23   S24 S26   S25 1964
	Raise a mound of stone West of the cor.  Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, yellow brush and sage.
	From the cor. of secs. 19, 24, 25 and 30 on the east bdy. of the township.  S. 83°38' W., bet. secs. 24 and 25.  Over nearly level grass land through scattered timber.
24.00	Fence, 3 strand barbed wire, bears S. 75° E. and N. 75° W. about 3.00 chs. to fence cor., thence North.

CHAINS

40.22

Point for the  $\frac{1}{4}$  sec. cor. of secs. 24 and 25 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4}$   $\frac{S\ 24}{S\ 25}$   
 1964

Raise a mound of stone North of the cor.

43.10

Wash, 65 lks. wide, 4 ft. banks, drains S. 60° W.

80.44

The cor. of secs. 23, 24, 25 and 26.

Land, gently rolling.  
 Soil, clay loam.  
 Timber, widely scattered juniper.  
 Undergrowth, yellow brush and sage.

---

N. 1°31' W., bet. secs. 23 and 24.

Over gently rolling land through widely scattered timber.

5.10

Wash, 30 lks. wide, 2 ft. deep, drains S. 65° W.

40.20

Point for the  $\frac{1}{4}$  sec. cor. of secs. 23 and 24 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.

T16N R26E  
 $\frac{1}{4}$   $\frac{S23|S24}{S23|S24}$   
 1964

44.10

Leave valley, bears irregularly E. and W.; asc. over broken clay hills.

61.40

Top of ridge, bears S. 80° W. and N. 80° E.; thence over clay basin.

69.80

Top of small knoll.

80.40

Point for the cor. of secs. 13, 14, 23 and 24 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T16N R26E  
 $\frac{S14|S13}{S23|S24}$   
 1964

Land,  $S\frac{1}{2}$  grassland,  $N\frac{1}{2}$  clay hills.  
 Soil, sandy clay loam  $S\frac{1}{2}$ , clay on  $N\frac{1}{2}$ .  
 Timber, widely scattered juniper.  
 Undergrowth, scattered yellow brush and shadscale.

---

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the township.</p> <p>S. 83°30' W., bet. secs. 13 and 24.</p> <p>Over steep broken clay hills.</p>
40.55	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E</p> <p><math>\frac{1}{4}</math> <math>\frac{S\ 13}{S\ 24}</math></p> <p>1964</p> </div>
81.10	<p>Continue over broken clay hills.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, broken clay hills.</p> <p>Soil, clay.</p> <p>No timber; undergrowth, scattered shadscale.</p>
29.40	<p>N. 1°07' W., bet. secs. 13 and 14.</p> <p>Over clay basin.</p> <p>Wash, 50 lks. wide, 1 ft. deep, drains N. 80° W.</p>
40.20	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 14 at proportionate dist.; unable to locate any evidence of the original cor.</p> <p>Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E</p> <p><math>\frac{1}{4}</math></p> <p>S14   S13</p> <p>1964</p> </div>
53.70	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 75° W.</p>
64.70	<p>Wash, 100 lks. wide, 1 ft. deep, drains S. 60° W.</p>
80.40	<p>Point for the cor. of secs. 11, 12, 13 and 14 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E</p> <p>S11   S12</p> <p>S14   S13</p> <p>1964</p> </div>
	<p>Raise a mound of stone West of the cor.</p> <p>Deposit glass in the hole dug for iron post.</p>

CHAINS

Land, rolling, slightly broken clay hills.  
Soil, clay loam.  
No timber; undergrowth, shadscale, brush.

From the cor. of secs. 7, 12, 13 and 18 on the east bdy. of the township.

S. 83°29' W., bet. secs. 12 and 13.

Over gently rolling land through moderate timber.

21.20 Wash, 10 lks. wide, 5 ft. banks, drains S. circling SW.

40.53 Point for the ¼ sec. cor. of secs. 12 and 13 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N R26E  
¼  $\frac{S\ 12}{S\ 13}$   
1964

Raise a mound of stone North of the cor.

Continue over rolling grass land through scattered timber.

51.50 Rim, bears NW. and S. about 3.90 chs.; desc. over rolling clay hills.

81.06 The cor. of secs. 11, 12, 13 and 14.

Land, rolling.  
Soil, sandy and clay loam.  
Timber, moderate to scattered juniper.  
Undergrowth, yellow brush and sage.

N. 1°03' W., bet. secs. 11 and 12.

Over gently rolling land.

23.70 Desc. over gentle N. slope.

31.10 Wash, 15 lks. wide, 1 ft. deep, drains S. 70° W.

36.70 Rim, bears NE. and SW.; enter clay hills.

40.20 Point for the ¼ sec. cor. of secs. 11 and 12 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N R26E  
¼  $\frac{S11}{S12}$   
1964

Desc. over broken and rolling clay hills.

73.70 Leave clay hills; thence over gently rolling land.

CHAINS	
76.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.
80.40	Point for the cor. of secs. 1, 2, 11 and 12 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T16N R26E  <math>\frac{S\ 2}{S\ 11} \mid \frac{S\ 1}{S\ 12}</math>                      1964</p>
	Raise a mound of stone West of the cor.
	Land, rolling and broken. Soil, clay and sandy clay. No timber; undergrowth, shadscale and yellow brush.
	<hr/>
	From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the township.
	S. 83°25' W., bet. secs. 1 and 12.
	Desc. over gentle W. slope.
2.20	Draw, drains SW.; asc. gentle E. slope through scattered timber.
28.90	Valley rim, bears NE. and SW.; desc. over broken barren clay hills.
35.20	Fence, barbed wire, bears NW. and East.
40.48	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T16N R26E  <math>\frac{1}{4} \frac{S\ 1}{S\ 12}</math>                      1964</p>
	Raise a mound of stone North of the cor.
44.60	Fence line, bears N. 89°28' W.
61.40	Leave clay hills, enter nearly level grassland.
80.96	The cor. of secs. 1, 2, 11 and 12.
	Land, rolling and broken. Soil, clay and sand. Timber, widely scattered juniper. Undergrowth, yellow brush and shadscale.
	<hr/>
	N. 2°57' W., bet. secs. 1 and 2.
	Over gently rolling grassland.
4.30	Fence, barbed wire, bears N. 89°28' W. and S. 89°28' E.

## CHAINS

13.55

Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 1 and 2 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T17N R26E  
S35  
-----  
S 2 | S 1  
T16N R26E  
CC  
1963

from which

The Standard Cor. of secs. 35 and 36 bears  
N. 89°08' E., 2.13 chs. dist.

Raise a mound of stone South of the closing cor.

Land, gently rolling.  
Soil, sandy clay loam.  
Timber, widely scattered juniper.  
Undergrowth, yellow brush.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 1 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 22 ins. in the ground, cap mkd.

-----  
 $\frac{1}{4}$  S1  
T16N R26E  
1963

from which

The Standard  $\frac{1}{4}$  Sec. Cor. of sec. 36 bears N. 89°08'  
E., 2.20 chs. dist.

Raise a mound of stone South of the  $\frac{1}{4}$  sec. cor. of sec. 1.

From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post as described in the field notes of T15N, R26E, recently resurveyed under this same Group.

N. 1°14' W., bet. secs. 34 and 35.

Over rolling clay hills.

3.60

Leave clay hills; enter gently rolling grassland.

40.10

Point for the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, and in a collar of stone, cap mkd.

CHAINS	
	T16N R26E $\frac{1}{4}$ S34   S35 1964
48.30	Track road, bears E. and W.
70.70	Wash, 90 lks. wide, 3 ft. deep, drains S. 55° W.
80.20	Point for the cor. of secs. 26, 27, 34 and 35 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T16N R26E S27   S26 S34   S35 1964
	Raise a mound of stone West of the cor.
	Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, low sage and yellow brush.
	From the cor. of secs. 25, 26, 35 and 36.
	S. 83°36' W., bet. secs. 26 and 35.
	Over nearly level grassland.
40.26	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T16N R26E $\frac{1}{4}$ S 26 $\frac{1}{4}$ S 35 1964
	Raise a mound of stone North of the cor.
59.30	Wash, 40 lks. wide, 3 ft. deep, drains irregularly SW.
80.52	The cor. of secs. 26, 27, 34 and 35.
	Land, nearly level grassland. Soil, sandy clay loam. No timber; undergrowth, scattered yellow brush and sage.
	N. 1°22' W., bet. secs. 26 and 27.
	Over nearly level grassland.
23.00	Wash, 50 lks. wide, 4 ft. deep, drains S. 60° W.
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27 at proportionate dist.; unable to find any evidence of the original cor.
80.18	Point for the cor. of secs. 22, 23, 26, and 27 at proportionate dist.; unable to find any evidence of original cor.

CHAINS

Set the iron post 18 ins. in the ground, and in a collar of stone, cap mkd.

T16N R26E  
 $\frac{S22}{S27} | \frac{S23}{S26}$   
 1963

Land, nearly level on S  $\frac{1}{2}$ , broken clay hills on N  $\frac{1}{2}$ .  
 Soil, sandy and clay.  
 Timber, widely scattered juniper S  $\frac{1}{2}$  mile.  
 Undergrowth, yellow brush and sage.

From the cor. of secs. 23, 24, 25 and 26.

S. 83°28' W., bet. secs. 23 and 26.

Over nearly level land through widely scattered timber.

.90 Wash, 60 lks. wide, 3 $\frac{1}{2}$  ft. deep, drains S. 55° W.

40.46 Point for the  $\frac{1}{4}$  sec. cor. of secs. 23 and 26 at proportionatedist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4} \frac{S 23}{S 26}$   
 1964

Raise a mound of stone North of the cor.

Leave valley, bears NE. and SW.; asc. over steep, broken clay hills.

80.92 The cor. of secs. 22, 23, 26 and 27.

Land, nearly level on E  $\frac{1}{2}$  mile, broken on remainder.  
 Soil, sandy and clay loam.  
 Timber, very widely scattered junipers.  
 Undergrowth, yellow brush and sage.

N. 1°23' W., bet. secs. 22 and 23.

Over broken clay hills.

1.80 Enter small basin.

13.30 Asc. over broken clay hills.

40.09 Point for the  $\frac{1}{4}$  sec. cor. of secs. 22 and 23 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4} \frac{S22}{S23}$   
 1964

CHAINS	
63.60	Rim, bears N. 70° E. and S. 70° W.; thence over mesa top through scattered timber.
80.18	Point for the cor. of secs. 14, 15, 22 and 23 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 22 ins. in the ground, cap mkd.
	<p>T16N R26E  <math>\frac{S15}{S22}   \frac{S14}{S23}</math>                      1964</p>
	Raise a mound of stone West of the cor.
	<p>Land, rolling and broken.                      Soil, clay loam.                      Timber, scattered juniper on mesa.                      Undergrowth, yellow brush and shadscale.</p>
	From the cor. of secs. 13, 14, 23 and 24.
	S. 83°18' W., bet. secs. 14 and 23.
	Over low rolling clay hills, N. drainage and exposure.
23.60	Small wash, drains N.
35.20	Small wash, drains N.
40.35	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23 at proportionate dist.; unable to locate any evidence of the original cor.
	Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.
	<p>T16N R26E  <math>\frac{1}{4} \frac{S-14}{S-23}</math>                      1964</p>
51.20	Enter scattered timber.
62.70	Rim, bears N. and S.; thence over nearly level mesa through scattered timber and low brush.
80.70	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, rolling and slightly broken.                      Soil, clay.                      Timber, scattered junipers.                      Undergrowth, yellow brush and sage.</p>
	N. 1° W., bet. secs. 14 and 15.
	Over nearly level land, through scattered juniper.
18.70	Mesa rim, bears E. and W.; desc. over steep barren N. slope.
27.30	Wash, 150 lks. wide, 3 ft. banks, drains N. 30° W. for about 15 chs., thence westerly.

CHAINS

- 40.09 Point for the  $\frac{1}{4}$  sec. cor. of secs. 14 and 15 at proportionate dist.; unable to find any evidence of the original cor.  
  
Set the iron post 22 ins. in the ground, cap mkd.  
  

T16N R26E  
 $\frac{1}{4}$   
S15 | S14  
1964

Raise a mound of stone West of the cor.
- 45.40 Asc. steep S. slope.
- 61.20 Ridge top, bears E. and W.; desc. steep N. slope.
- 77.00 Wash, 80 lks. wide, 3 ft. deep, drains W.; asc. S. slope.
- 80.18 Point for the cor. of secs. 10, 11, 14 and 15 at proportionate dist.; unable to find any evidence of the original cor.  
  
Set the iron post 20 ins. in the ground, cap mkd.  
  

T16N R26E  
S10 | S11  
S15 | S14  
1964

Raise a mound of stone West of the cor

Land, rolling and broken.  
Soil, clay.  
Timber, scattered juniper on S. 13.00 chs.  
Undergrowth, shadscale and yellow brush.

---

From the cor. of secs. 11, 12, 13 and 14.  
S. 83°05' W., bet. secs. 11 and 14.  
Over rolling and broken clay hills.
- 26.40 Leave clay hills; continue over gently rolling grass land through scattered timber.
- 40.27 Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 and 14 at proportionate dist.; unable to find any evidence of the original cor.  
  
Set the iron post 24 ins. in the ground, cap mkd.  
  

T16N R26E  
 $\frac{1}{4}$  S 11  
S 14  
1964

Raise a mound of stone N. of the cor.
- 64.30 Wash, 30 lks. wide, 2 ft. deep, drains irregularly W.
- 74.40 Same wash.
- 75.80 Same wash.

CHAINS	
79.50	Same wash, drains S. circling West.
80.54	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling, slightly broken. Soil, clay and sandy clay loam. Timber, scattered to widely scattered juniper. Undergrowth, yellow brush and sage.</p>
	<hr/> <p>N. 1°28' W., bet. secs. 10 and 11.</p> <p>Asc. over S. slope.</p>
17.10	Gully, drains SW.
30.70	Rim, bears NE. and SW.; desc. over clay hills.
40.09	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 11 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R26E <math>\frac{1}{4}</math> S10   S11 1964</p>
55.70	Leave clay hills, enter nearly level grassland.
79.20	Wash, 10 lks. wide, 1 ft. deep, drains irregularly NW.
80.18	<p>Point for the cor. of secs. 2, 3, 10 and 11 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R26E S3   S2 S10   S11 1964</p>
	<p>Raise a mound of stone West of the cor.</p> <p>Land, gently rolling and broken. Soil, clay loam and sandy. No timber; undergrowth, shadscale and yellow brush.</p>
	<hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 83° W., bet. secs. 2 and 11.</p> <p>Over gently rolling land through scattered undergrowth.</p>
9.30	Small wash, drains NW.
37.00	Wash, 20 lks. wide, 1 ft. deep, drains irregularly NW.
40.57	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 11 at proportionate dist.; unable to find any evidence of the original cor.</p>

26

CHAINS

Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.

T16N R26E

$\frac{1}{4}$   $\frac{S \ 2}{S \ 11}$   
1964

from which

A mining claim cor. - Remote West cor. No. 3 SE, and Remote East cor. No. 4 SW., bears S. 25°45' E., 5.45 chs. dist., monumented by a 4x4x4-inch post. From this claim cor. Remote West No. 4 SW. bears S. 84°19' W., 10.02 chs. dist., monumented by a 4x4x4-inch wood post.

Thence, over low rolling clay hills.

65.30 Crest of clay knoll.

74.80 Leave clay hills, enter nearly level grassland.

81.14 The cor. of secs. 2, 3, 10 and 11.

Land, gently rolling.

Soil, clay loam.

No timber; undergrowth, yellow brush.

N. 3°25' W., bet. secs. 2 and 3.

Over gently rolling grassland.

3.20 Wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.

15.00 Fence, bears E. and W.

21.20 Old E-W fence line.

22.25 Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 2 and 3 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T17N R26E

S34

S 3 | S 2

T16N R26E

1963

from which

The Standard Cor. of secs. 34 and 35, T17N, R26E, bears N. 89°08' E., 2.10 chs. dist.

Raise a mound of stone S. of the closing cor.

Land, gently rolling.

Soil, sandy clay loam.

No timber; undergrowth, yellow brush.

CHAINS

The point for the  $\frac{1}{4}$  sec. cor. of secs. 2 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.

$\frac{1}{4}$  S 2  
 T16N R26E  
 1963

from which

The Standard  $\frac{1}{4}$  Sec. Cor. of sec. 35 bears  
 N.  $89^{\circ}08'$  E., 2.11 chs. dist.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township, monumented by an iron post as described in the field notes of T15N, R26E, recently resurveyed under this same Group.

N.  $1^{\circ}41'$  W., bet. secs. 33 and 34.

Over nearly level grass land.

15.90 Wash, 20 lks. wide, 2 ft. deep, drains West about 3.00 chs. to main wash.

21.60 Wash, 20 lks. wide, 3 ft. deep, drains S.  $65^{\circ}$  W.

37.40 Bladed road, bears S.  $55^{\circ}$  W. and N.  $55^{\circ}$  E.

39.99 Point for the  $\frac{1}{4}$  sec. cor. of secs. 33 and 34 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4}$   
 S33 | S34  
 1964

Raise a mound of stone West of the cor.

42.70 Wash, 100 lks. wide, 4 ft. banks, drains S.  $65^{\circ}$  W.

79.98 Point for the cor. of secs. 27, 28, 33 and 34 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
 S28 | S27  
 S33 | S34  
 1964

Raise a mound of stone West of the cor.

Land, nearly level.

Soil, sandy clay loam.

No timber; undergrowth, yellow brush.

CHAINS		
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 83°33' W., bet. secs. 27 and 34.</p> <p>Over nearly level grass land.</p>	
30.20	Fence, barbed wire, bears N. and S.	
36.30	Wash, 100 lks. wide, 4 ft. banks, drains south circling to S. 60° W.	
40.07	<p>Point for the ¼ sec. cor. of secs. 27 and 34 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E</p> <p>¼ <math>\frac{S\ 27}{S\ 34}</math></p> <p>1964</p> </div> <p>Raise a mound of stone North of the cor.</p>	
56.40	Asc. over broken clay hills.	
77.90	Crest of main spur, slopes SW. about 4.50 chs.	
80.14	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, gently rolling to broken.</p> <p>Soil, sandy clay and clay loam.</p> <p>Timber, widely scattered junipers.</p> <p>Undergrowth, yellow brush.</p>	
	<hr/> <p>N. 1°19' W., bet. secs. 27 and 28.</p> <p>Over gently rolling land, low undergrowth.</p>	
6.90	Small wash, drains SW.	
39.98	<p>Point for the ¼ sec. cor. of secs. 27 and 28 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E</p> <p>¼ <math>\frac{S28}{S27}</math></p> <p>1964</p> </div> <p>Deposit glass in the hole dug for iron post.</p>	
47.20	Wash, 90 lks. wide, 1 ft. deep, drains SW.	
67.90	Wash, 35 lks. wide, 3 ft. deep, drains SW.	
77.30	Asc. over broken clay hills.	
79.96	<p>Point for the cor. of secs. 21, 22, 27 and 28 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p>	

CHAINS	
	<p style="text-align: center;">T16N R26E  <math>\frac{S21}{S28}   \frac{S22}{S27}</math>                      1964</p> <p>Raise a mound of stone West of the cor.</p> <p>Land, gently rolling to broken.                      Soil, sandy clay and clay loam.                      No timber; undergrowth, yellow brush and shadscale.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 83°24' W., bet. secs. 22 and 27.</p> <p>Over steep, broken clay hills.</p>
16.80	Wash, 60 lks. wide, 1 ft. deep, drains irregularly S. 70° W.; leave clay hills, thence over nearly level land bearing NE. and SW.
35.20	Enter clay hills.
40.04	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 22 and 27 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R26E  <math>\frac{1}{4} \frac{S 22}{S 27}</math>                      1964</p> <p>Deposit glass in the hole dug for iron post.</p>
52.50	Leave clay hills; enter nearly level grass land.
76.70	Wash, 70 lks. wide, 1 ft. deep, drains irregularly South; enter clay hills.
80.08	<p>The cor. of secs. 21, 22, 27 and 28.</p> <p>Land, gently rolling and broken.                      Soil, clay loam.                      No timber; undergrowth, yellow brush.</p> <hr/> <p>N. 1°53' W., bet. secs. 21 and 22.</p> <p>Over steep, broken clay hills.</p>
39.99	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 22, at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R26E  <math>\frac{1}{4}</math>  <math>\frac{S21}{S22}</math>                      1964</p> <p>Raise a mound of stone West of the cor.</p>

CHAINS		
40.90	Rim, bears E. and W.; thence over nearly level mesa top through scattered timber.	
53.60	Rim, bears NE. and SW.; desc. over broken clay hills.	
57.30	Draw, near head, drains W.	
68.70	Broken spur, slopes W.; desc. along broken E. slope.	
79.98	Point for the cor. of secs. 15, 16, 21 and 22 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	<p>T16N R26E  S16   S15  S21   S22  1964</p>	
	<p>Land, rolling and broken.  Soil, clay loam.  Timber, scattered juniper on mesa top.  Undergrowth, yellow brush.</p>	
	From the cor. of secs. 14, 15, 22 and 23.	
	S. 83°17' W., bet. secs. 15 and 22.	
	Over nearly level mesa top through scattered timber.	
40.37	Point for the ¼ sec. cor. of secs. 15 and 22 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 20 ins. in the ground and in a collar of stone, cap mkd.	
	<p>T16N R26E  ¼ S 15  S 22  1964</p>	
60.20	Mesa rim, bears NE. and SW.; desc. over rolling clay hills.	
80.74	The cor. of secs. 15, 16, 21 and 22.	
	<p>Land, nearly level on E. 60.00 chs., broken clay hills on remainder.  Soil, sandy clay loam.  Timber, scattered juniper on mesa top.  Undergrowth, sage and yellow brush.</p>	
	N. 1°25' W., bet. secs. 15 and 16.	
	Over gently rolling grass land.	
18.90	Low ridge, bears E. and W.	
36.70	Wash, 180 lks. wide, 3 ft. deep, drains S. 70° W.	
39.99	Point for the ¼ sec. cor. of secs. 15 and 16 at proportionate dist.; unable to locate any evidence of the original cor.	

CHAINS		
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R26E  <math>\frac{1}{4}</math>                      S16   S15                      1964</p>	
	<p>Raise a mound of stone West of the cor.</p>	
50.60	<p>Enter clay hills.</p>	
71.80	<p>Flat topped spur, slopes W.; desc.</p>	
72.90	<p>Leave clay hills, enter gently rolling grassland.</p>	
79.98	<p>Point for the cor. of secs. 9, 10, 15 and 16 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R26E                      S 9   S10                      S16   S15                      1964</p>	
	<p>Raise a mound of stone West of the cor.</p> <p>Land, rolling and broken.                      Soil, clay loam.                      No timber; undergrowth, yellow brush.</p>	
	<hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 83°12' W., bet. secs. 10 and 15.</p> <p>Over rolling clay hills.</p>	
40.67	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 15 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T16N R26E  <math>\frac{1}{4}</math> S 10                      S 15                      1964</p>	
65.30	<p>Leave clay hills, bears NE. and SW.; thence over nearly level grass land.</p>	
81.34	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling and broken.                      Soil, clay loam.                      No timber; undergrowth, yellow brush.</p>	
	<hr/> <p>N. 1°36' W., bet. secs. 9 and 10.</p> <p>Over nearly level grass land.</p>	

CHAINS

39.99 Point for the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4}$   
 S9 | S10  
 1964

Raise a mound of stone West of the cor.

73.90 Wash, 50 lks. wide, 3 ft. deep, drains S. 75° W.

79.98 Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
S4 | S3  
S9 | S10  
 1964

Raise a mound of stone West of the cor.

Land, nearly level.

Soil, sandy clay loam

No timber; undergrowth, yellow brush and sage.

From the cor. of secs. 2, 3, 10 and 11.

S. 83°06' W., bet. secs. 3 and 10.

Over nearly level grass land.

1.00 Wash, 20 lks. wide, 1 ft. deep, drains irregularly NW.

40.73 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 10 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 20 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4}$  S 3  
S 10  
 1964

Raise a mound of stone N. of the cor.

60.50 Wash, 40 lks. wide, 2 ft. deep, drains SW. curving to NW.

62.50 Same wash, drains NW. curving SW.

64.30 Same wash, drains irregularly SW.

81.46 The cor. of secs. 3, 4, 9 and 10.

Land, nearly level.

Soil, sandy clay loam.

No timber; undergrowth, scattered yellow brush.

CHAINS

N. 2°56' W., bet. secs. 3 and 4.

Over nearly level grass land.

25.50 Fence, barbed wire, bears E. and W.

30.82 Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 3 and 4 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground and in a collar of stone, cap mkd.

T17N R26E  
    S33      
 S 4 | S 3  
 T16N R26E  
 CC  
 1963

from which

The Standard Cor. of secs. 33 and 34, T17N, R26E, bears N. 89°09' E., 2.05 chs. dist.

Land, nearly level.  
 Soil, sandy clay loam.  
 No timber; undergrowth, yellow brush.

The point for the ¼ sec. cor. of sec. 3 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 20 ins. in the ground, cap mkd.

    ¼ S3      
 T16N R26E  
 1963

from which

The standard ¼ sec. cor. of sec. 34, T17N, R26E, bears N. 89°08' E., 2.07 chs. dist.

Raise a mound of stone S. of the ¼ sec. cor. of sec. 3.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, monumented by an iron post as described in the field notes of T15N, R26E, recently surveyed under this same Group.

N. 1°36' W., bet. secs. 32 and 33.

Over nearly level grass land, low undergrowth.

9.70 Wash, 100 lks. wide, 2 ft. deep, drains irregularly S. 20° W. from irregularly North.

30.50 Same wash, drains from N. 15° W.

32.40 Track road, bears irregularly East and West.

39.87 Point for the ¼ sec. cor. of secs. 32 and 33 at proportionate dist.; unable to find any evidence of the original cor.

CHAINS

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4}$   
 S32|S33  
 1964

Raise a mound of stone West of the cor.

45.20 Same wash, drains from NE.

79.74 Point for the cor. of secs. 28, 29, 32 and 33 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
S29|S28  
S32|S33  
 1964

Raise a mound of stone West of the cor.

Land, nearly level.

Soil, sandy clay loam.

No timber; undergrowth, yellow brush and sage.

From the cor. of secs. 27, 28, 33 and 34.

S. 83°31' W., bet. secs. 28 and 33.

Over low rolling clay land.

2.00 Enter nearly level grass land.

5.60 Small wash, drains SW.

40.03 Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 33 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 23 ins. in the ground, cap mkd.

T16N R26E  
 $\frac{1}{4}$  S 28  
S 33  
 1964

Raise a mound of stone N. of the cor.

56.70 Wash, 80 lks. wide, 3 ft. deep, drains SW.

80.06 The cor. of secs. 28, 29, 32 and 33.

Land, gently rolling.

Soil, sandy clay loam.

No timber; undergrowth, sage and yellow brush.

N. 1°45' W., bet. secs. 28 and 29.

Over gently rolling land.

29.60 Leave valley; asc. over broken clay hills.

CHAINS	
39.87	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 28 and 29, at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T16N R26E <math>\frac{1}{4}</math> S29   S28 1964</p>
41.00	Enter nearly level land.
61.00	Asc. over steep, broken clay hills.
79.74	<p>Point for the cor. of secs. 20, 21, 28 and 29 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T16N R26E S20   S21 S29   S28 1964</p>
	<p>Deposit glass in the hole dug for iron post.</p> <p>Land, rolling and broken. Soil, clay loam. No timber; undergrowth, sage and yellow brush.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 83°21' W., bet. secs. 21 and 28.</p> <p>Over clay hills.</p>
2.20	Enter nearly level grass land.
13.90	Wash, 25 lks. wide, 1 ft. deep, drains S. 10° E.
22.40	Enter clay hills.
40.33	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 21 and 28 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 18 ins. in the ground and in a collar of stone, cap mkd.</p> <p style="text-align: center;">T16N R26E <math>\frac{1}{4}</math> S 21 S 28 1964</p>
80.66	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling and broken. Soil, clay loam. No timber; undergrowth, brush and shadscale.</p>

CHAINS	
	N. 1°44' W., bet. secs. 20 and 21.
	Over rolling clay hills.
18.20	Spur, slopes West.
26.00	Enter nearly level land, bears NE. and SW.
39.87	Point for the ¼ sec. cor. of secs. 20 and 21 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 18 ins. in the ground and in a collar of stone, cap mkd.
	T16N R26E ¼ S20   S21 1964
68.00	East slope of clay hill.
79.74	Point for the cor. of secs. 16, 17, 20 and 21 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 20 ins. in the ground, cap mkd.
	T16N R26E S17   S16 S20   S21 1964
	Raise a mound of stone West of the cor.
	Land, rolling and broken. Soil, clay loam. No timber; undergrowth, yellow brush, sage and shadscale.
	From the cor. of secs. 15, 16, 21 and 22.
	S. 83°10' W., bet. secs. 16 and 21.
	Over rolling clay hills.
10.00	Leave clay hills, enter nearly level grass land.
40.25	Point for the ¼ sec. cor. of secs. 16 and 21 at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 21 ins. in the ground, cap mkd.
	T16N R26E ¼ S16 S21 1964
	Raise a mound of stone North of the corner.
61.20	Line follows along S. side of large wash draining irregularly West.
80.50	The cor. of secs. 16, 17, 20 and 21.

BOOK 4704

Dep. Resurvey, Subdivision, T16N, R26E, Arizona

37.

CHAINS

Land, rolling to nearly level.  
Soil, clay loam.  
No timber; undergrowth, shadscale and yellow brush.

N. 1°34' W., bet. secs. 16 and 17.

Over nearly level grassland.

3.20 Wash, 150 lks. wide, 3 ft. deep, drains S. 60° W.

26.10 Wash, 50 lks. wide, 1 ft. deep, drains SW.

39.87 Point for the 1/4 sec. cor. of secs. 16 and 17 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
1/4  
S17 | S16  
1964

Raise a mound of stone West of the cor.

79.74 Point for the cor. of secs. 8, 9, 16 and 17 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 23 inches in the ground, cap mkd.

T16N R26E  
S8 | S9  
S17 | S16  
1964

Raise a mound of stone West of the cor.

Land, nearly level.  
Soil, sandy clay loam.  
No timber; undergrowth, sage and yellow brush.

From the cor. of secs. 9, 10, 15 and 16.

S. 83°01' W., bet. secs. 9 and 16.

Over nearly level grass land.

28.60 Wash, 35 lks. wide, 1 ft. deep, drains NW.

40.38 Point for the 1/4 sec. cor. of secs. 9 and 16 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
1/4 S 9  
S 16  
1964

Raise a mound of stone North of the cor.

CHAINS		
75.60	Track road, bears NE. and SW.	
80.76	The cor. of secs. 8, 9, 16 and 17.	
	Land, nearly level grass land. Soil, clay loam. No timber; undergrowth, sage and yellow brush.	
	N. 1°32' W., bet. secs. 8 and 9.	
	Over nearly level grass land.	
23.90	Wash, 20 lks. wide, 2 ft. deep, drains irregularly W.	
39.87	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T16N R26E $\frac{1}{4}$ S 8   S 9 1964	
	Raise a mound of stone West of the cor.	
48.00	Wash, 40 lks. wide, 3 ft. deep, drains N. 80° W.	
79.74	Point for the cor. of secs. 4, 5, 8 and 9 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 22 ins. in the ground, cap mkd.	
	T16N R26E S 5   S 4 S 8   S 9 1964	
	Raise a mound of stone West of the cor.	
	Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, yellow brush.	
	From the cor. of secs. 3, 4, 9 and 10.	
	S. 82°52' W., bet. secs. 4 and 9.	
	Over nearly level land.	
23.30	Track road, bears S. 30° W. and N. 30° E.	
40.35	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 24 ins. in the ground, cap mkd.	
	T16N R26E $\frac{1}{4}$ S 4 S 9 1964	

CHAINS

80.70 Raise a mound of stone North of the cor.  
 The cor. of secs. 4, 5, 8 and 9.  
 Land, nearly level range.  
 Soil, sandy clay.  
 No timber; undergrowth, yellow brush and sage.

---

13.30 N. 3°02' W., bet. secs. 4 and 5.  
 Over gently rolling range land.

36.30 Wash, 60 lks. wide, 1 ft. deep, drains SW.

39.67 Fence, barbed wire, bears E. and W.  
 Intersect the Fourth Standard Parallel North.  
 Point for the closing cor. of secs. 4 and 5 at proportionate dist.; unable to find any evidence of the original cor.  
 Set the iron post 23 inches in the ground and in a collar of stone, cap mkd.

T17N  
 S32  
 ———  
 S 5 | S 4  
 T16N R26E  
 CC  
 1963

from which  
 the Standard Corner of secs. 32 and 33, T17N, R26E, bears N. 89°08' E., 1.47 chs. dist.

Land, nearly level.  
 Soil, sandy clay loam.  
 No timber; undergrowth, yellow brush and sage.

The point for the ¼ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing corners.  
 Set the iron post 22 ins. in the ground, cap mkd.

¼ S4  
 T16N R26E  
 1963

from which  
 The Standard ¼ Sec. Cor. of sec. 33, T17N, R26E, bears N. 89°08' E. 1.76 chs. dist.

Deposit glass in hole dug for iron post.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township, monumented by an iron post as described in the field notes of T15N, R26E, recently resurveyed under this same Group.

## CHAINS

N. 1°58' W., bet. secs. 31 and 32.

Over gently rolling land through low sage.

24.00 Asc. over S. slope.

39.75 Point for the  $\frac{1}{4}$  sec. cor. of secs. 31 and 32 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N R26E

$\frac{1}{4}$   
S31|S32  
1964

from which

A pond, bears N. 78°22' E., 62.41 chs. dist.

Raise a mound of stone West of the cor.

45.50 Crest of ridge, bears NE. and SW.

55.50 Enter low rolling clay hills, scattered petrified wood.

73.00 Leave clay hills; enter gently rolling land.

79.50 Point for the cor. of secs. 29, 30, 31 and 32 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E

S30|S29  
S31|S32  
1964

Raise a mound of stone West of the cor.

Land, gently rolling.

Soil, sandy and clay.

No timber; undergrowth, yellow brush.

From the cor. of secs. 28, 29, 32 and 33.

S. 83°34' W., bet. secs. 29 and 32.

Asc. over gently rolling range land.

33.30 Low rise, bears N. and S.

38.50 Fence, barbed wire, bears N. 15° W. and S. 15° E.

40.34 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, cap mkd.

T16N R26E

$\frac{1}{4}$   $\frac{S 29}{S 32}$   
1964

Raise a mound of stone North of the corner.

CHAINS		
46.30	Wash, 20 lks. wide, 2 ft. deep, drains S. 10° E.	
64.30	Asc. over broken clay hills.	
72.40	Crest of main spur, slopes SW. about 5.00 chs. to end.	
73.10	Enter gently rolling land.	
80.68	The cor. of secs. 29, 30, 31 and 32.	
	Land, rolling. Soil, sand and clay loam. No timber; undergrowth, yellow brush and sage.	
	S. 83°45' W., bet. secs. 30 and 31.	
	Over gently rolling land, few low clay hills.	
40.14	Point for the ¼ sec. cor. of secs. 30 and 31 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 20 ins. in the ground and in a collar of stone, cap mkd.	
	T16N R26E ¼ $\frac{S\ 30}{S\ 31}$ 1964	
79.80	Crest of low ridge, bears NE. and SW.	
96.80	Wash, 200 lks. wide, 3 ft. deep, drains S. about 10.00 chs., thence SW.	
115.35	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the township.	
	Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, yellow brush and sage.	
	From the cor. of secs. 29, 30, 31 and 32.	
	N. 1°37' W., bet. secs. 29 and 30.	
	Over gently rolling grassland.	
10.10	Track road, bears NW. and SE.	
27.00	Wash, 10 lks. wide, 1 ft. deep, drains irregularly West.	
37.10	Wash, 10 lks. wide, 1 ft. deep, drains irregularly West.	
39.74	Point for the ¼ sec. cor. of secs. 29 and 30 at proportionate dist.; unable to find any evidence of the original cor.	
	Set the iron post 22 ins. in the ground, cap mkd.	

CHAINS

T16N R26E

$\frac{1}{2}$   
S30|S29  
1964

Raise a mound of stone West of the cor.

45.30 Crest of low ridge, bears E. and S. 60° W.

58.10 Wash, 30 lks. wide, 1 ft. deep, drains SW.

79.48 Point for the cor. of secs. 19, 20, 29 and 30 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E

S19|S20  
S30|S29  
1964

Raise a mound of stone West of the cor.

Land, gently rolling.  
Soil, clay loam and shallow sand.  
No timber; undergrowth, yellow brush and sage.

From the cor. of secs. 20, 21, 28 and 29.

S. 83°24' W., bet. secs. 20 and 29.

Over steep, broken clay hills.

40.00 Enter gently rolling land.

40.26 Point for the  $\frac{1}{4}$  sec. cor. of secs. 20 and 29 at proportionate dist.; unable to find any remaining evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E

$\frac{1}{4}$   $\frac{S 20}{S 29}$   
1964

Raise a mound of stone N. of the cor.

80.52 The cor. of secs. 19, 20, 29 and 30.

Land, clay hills on E  $\frac{1}{2}$ , gently rolling on remainder.  
Soil, shallow sand and clay.  
No timber; undergrowth, yellow brush.

S. 83°49' W., bet. secs. 19 and 30.

Over gently rolling grassland.

7.30 Track road, bears N. 30° E. and S. 20° W.

40.23 Point for the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

CHAINS	
	T16N R26E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{19}{30}$ 1964
	Raise a mound of stone North of the cor.
46.10	Wash, 340 lks. wide, 3 ft. deep, drains irregularly SW.
70.50	Low spur, slopes South.
93.00	Gully, drains S.
114.98	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the township.
	Land, gently rolling. Soil, clay loam. No timber; undergrowth, yellow brush and sage.
	From the cor. of secs. 19, 20, 29 and 30.  N. 1°47' W., bet. secs. 19 and 20.  Over gently rolling grass land.
20.40	Wash, 30 lks. wide, 2 ft. deep, drains irregularly W.
26.00	Track road, bears NE. and SW.
39.75	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T16N R26E $\frac{1}{4}$ $\frac{S19}{S20}$ 1964
	Raise a mound of stone West of the cor.
65.30	Wash, 170 lks. wide, 4 ft. deep, drains S. 55° W.
69.10	Gulley, 30 lks. wide, 4 ft. deep, drains SW. to main wash.
79.50	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; unable to find any evidence of the original cor.
	Set the iron post 24 ins. in the ground, cap mkd.
	T16N R26E $\frac{S18}{S19}$ $\frac{S17}{S20}$ 1964
	from which
	A windmill bears N. 45°31' E., 35.54 chs. dist.

CHAINS	
	<p>Raise a mound of stone West of the cor.</p> <p>Land, gently rolling. Soil, sandy clay. No timber; undergrowth, yellow brush and sage.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 83°13' W., bet. secs. 17 and 20.</p> <p>Over nearly level grass land.</p> <p>9.00 Wash, 250 lks. wide, 3 ft. deep, drains S. 60° W.</p> <p>16.00 Center of earthen dam, bears NE. and SW.</p> <p>40.29 Point for the ¼ sec. cor. of secs. 17 and 20 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E</p> <p>¼ <math>\frac{S\ 17}{S\ 20}</math></p> <p>1964</p> </div> <p>Raise a mound of stone N. of the cor.</p> <p>53.50 Dike, bears N. and S.</p> <p>63.70 Gully, 30 lks. wide, 5 ft. deep, drains SW.</p> <p>80.58 The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, yellow brush and sage.</p> <hr/> <p>S. 83°52' W., bet. secs. 18 and 19.</p> <p>Over gently rolling grass land.</p> <p>34.00 Crest of low rise, bears N. and S.</p> <p>40.27 Point for the ¼ sec. cor. of secs. 18 and 19 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <div style="text-align: center;"> <p>T16N R26E</p> <p>¼ <math>\frac{S\ 18}{S\ 19}</math></p> <p>1964</p> </div> <p>Raise a mound of stone N. of the cor.</p> <p>69.30 Wash, 30 lks. wide, 3 ft. deep, drains South.</p> <p>114.48 The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the township.</p>

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, yellow brush and sage.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p>
	<p>N. 1°51' W., bet. secs. 17 and 18.</p>
	<p>Over nearly level grass land.</p>
30.00	<p>Crest of low ridge, bears E. and W.</p>
39.75	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 18 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R26E <math>\frac{1}{4}</math> S18   S17 1964</p>
	<p>Raise a mound of stone West of the cor.</p>
79.50	<p>Point for the cor. of secs. 7, 8, 17 and 18 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R26E S 7   S 8 S18   S17 1964</p>
	<p>Raise a mound of stone West of the cor.</p>
	<p>Land, nearly level. Soil, clay and sand. No timber; undergrowth, yellow brush and sage.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p>
	<p>S. 83°05' W., bet. secs. 8 and 17.</p>
	<p>Over nearly level range land.</p>
40.48	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 8 and 17 at proportionate dist.; unable to find any evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R26E <math>\frac{1}{4}</math> S 8 S 17 1964</p>
	<p>Raise a mound of stone N. of the cor.</p>
58.10	<p>Gully, 30 lks. wide, 3 ft. deep, drains North.</p>
80.96	<p>The cor. of secs. 7, 8, 17 and 18.</p>

CHAINS		
	<p>Land, nearly level. Soil, clay and sand. No timber; undergrowth, yellow brush and sage.</p>	
	<p>S. 83°55' W., bet. secs. 7 and 18.</p>	
	<p>Over gently rolling grassland.</p>	
40.35	<p>Point for the ¼ sec. cor. of secs. 7 and 18 at proportionate dist.; unable to find any evidence of the original cor.</p>	
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T16N R26E  <math>\frac{1}{4}</math> <math>\frac{S 7}{S 18}</math>                      1964</p>	
	<p>Raise a mound of stone North of the cor.</p>	
60.40	<p>Low ridge, bears N. 10° W. and South.</p>	
113.96	<p>The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the township</p>	
	<p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, yellow brush and sage.</p>	
	<p>From the cor. of secs. 7, 8, 17 and 18.</p>	
	<p>N. 1°30' W., bet. secs. 7 and 8.</p>	
	<p>Over nearly level grass land.</p>	
39.74	<p>Point for the ¼ sec. cor. of secs. 7 and 8 at proportionate dist.; unable to find any evidence of the original cor.</p>	
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T16N R26E  <math>\frac{1}{4}</math> S 7   S 8                      1964</p>	
	<p>Raise a mound of stone West of the cor.</p>	
52.70	<p>Wash, 10 lks. wide, 3 ft. deep, drains N. 30° W.</p>	
67.80	<p>Wash, 200 lks. wide, 4 ft. banks, drains irregularly West.</p>	
79.48	<p>Point for the cor. of secs. 5, 6, 7 and 8 at proportionate dist.; unable to find any evidence of the original cor.</p>	
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T16N R26E                      S 6   S 5                      S 7   S 8                      1964</p>	

CHAINS	
	<p>Raise a mound of stone West of the cor.</p>
	<p>Land, nearly level.</p>
	<p>Soil, sandy clay loam.</p>
	<p>No timber; undergrowth, scattered yellow brush.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>
	<p>S. 82°53' W., bet. secs. 5 and 8.</p>
	<p>Over nearly level grass land.</p>
2.40	<p>Wash, 70 lks. wide, 4 ft. deep, drains irregularly SW.</p>
40.45	<p>Point for the ¼ sec. cor. of secs. 5 and 8 at proportionate dist.; unable to find any evidence of the original cor.</p>
	<p>Set the iron post 23 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R26E</p>
	<p style="text-align: center;">¼ <math>\frac{S \ 5}{S \ 8}</math></p>
	<p style="text-align: center;">1964</p>
	<p>Raise a mound of stone North of the cor.</p>
80.90	<p>The cor. of secs. 5, 6, 7 and 8.</p>
	<p>Land, nearly level.</p>
	<p>Soil, sandy clay loam.</p>
	<p>No timber; undergrowth, scattered yellow brush.</p>
	<p>S. 83°59' W., bet. secs. 6 and 7.</p>
	<p>Over nearly level range land.</p>
11.10	<p>Fence, 5 strand barbed wire, bears N. 32°10' E. and S. 32°10' W.</p>
40.54	<p>Point for the ¼ sec. cor. of secs. 6 and 7 at proportionate dist.; unable to find any evidence of the original cor.</p>
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T16N R26E</p>
	<p style="text-align: center;">¼ <math>\frac{S \ 6}{S \ 7}</math></p>
	<p style="text-align: center;">1964</p>
	<p>Raise a mound of stone North of the cor.</p>
44.80	<p>Wash, 120 lks. wide, 3 ft. deep, drains NW.</p>
82.90	<p>Fence, barbed wire, bears N. and S.</p>
101.20	<p>Bladed road, bears N. 15° E. and S. 15° W.</p>
107.50	<p>Track road, bears NE. and SW.</p>
113.83	<p>The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the township.</p>

CHAINS

Land, gently rolling.  
Soil, sandy clay loam.  
No timber; undergrowth, yellow brush and sage.

---

From the cor. of secs. 5, 6, 7 and 8.

N. 3°02' W., bet. secs. 5 and 6.

Over nearly level grass land.

8.90 Old E-W fence line.

11.90 Wash, 10 lks. wide, 3 ft. deep, drains SW.

39.78 Point for the ¼ sec. cor. of secs. 5 and 6 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 24 ins. in the ground, cap mkd.

T16N R26E  
          ½  
          S 6 | S 5  
          1964

Raise a mound of stone West of the cor.

47.00 Fence, barbed wire, bears N. 89°30' W. and S. 89°30' E.

48.49 Intersect the Fourth Standard Parallel North.

Point for the closing cor. of secs. 5 and 6 at proportionate dist.; unable to find any evidence of the original cor.

Set the iron post 22 ins. in the ground, and in a collar of stone, cap mkd.

T17N  
S31  
-----  
S 6 | S 5  
T16N R26E  
CC  
1963

from which

The Standard Cor. of secs. 31 and 32, T17N, R26E,  
bears N. 89°08' E., 1.07 chs. dist.

Land, nearly level.  
Soil, sandy clay loam.  
No timber; undergrowth, yellow brush.

---

The point for the ¼ sec. cor. of sec. 5 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 18 ins. in the ground and in a collar of stone, cap mkd.

-----  
¼ S 5  
T16N R26E  
1963

COOK 4704

Dep. Resurvey, Subdivision, T16N, R26E, Arizona 49.

CHAINS

from which

The Standard  $\frac{1}{4}$  Sec. Cor. of sec. 32, T17N, R26E, bears N.  $89^{\circ}08'$  E., 1.27 chs. dist.

The point for the  $\frac{1}{4}$  sec. cor. of sec. 6 is on the N. bdy. at a proportionate dist. in longitude West of the closing cor. of secs. 5 and 6, based on the theoretical position as shown on the official plat.

Set the iron post 24 ins. in the ground and in a collar of stone, cap mkd.

$\frac{1}{4}$  S6  
T16N R26E  
1963

from which

The Standard  $\frac{1}{4}$  Sec. Cor. of sec. 31 bears N.  $89^{\circ}08'$  E., 1.08 chs. dist.

General Description

The land in Township 16 North, Range 26 East, Gila and Salt River Meridian, varies from nearly level range land to broken clay hills. The soil is shallow sand, clay and clay hard-pan. Scattered to moderate junipers are found within the area, mostly along the eastern part of the township, with native bunch grass and yellow brush the predominating undergrowth.

There are several stock ponds, dikes and a windmill within the township, which afford a continued water supply for the grazing of livestock, the primary interest at present. Exploratory mineral drilling has been done recently in the close vicinity of the  $\frac{1}{4}$  sec. cor. of secs. 2 and 11.

The township is easily accessible from east, west or north, with roads leading to the ponds in the area.



BOOK 4704  
CERTIFICATE OF SURVEY

We Boyd S. Owens  
X, Paul G. Bauer, HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 13 day of March, 1963,  
We

X have dependently resurveyed the north boundary (Fourth Standard Parallel North), the east and west boundaries, and the subdivisional lines of Township 16 North, Range 26 East

of the Gila and Salt River Meridian, in the State of Arizona, which  
Us Our  
are represented in the foregoing field notes as having been executed by ~~me~~ and under ~~my~~ direction;  
and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 28, 1964  
(Date)

*Boyd S Owens*  
(Cadastral Surveyor)

April 28, 1964  
(Date)

*Paul G. Bauer*  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL  
Bureau of Land Management

The foregoing field notes of the dependent resurvey of the north boundary (Fourth Standard Parallel North), the east and west boundaries, and the subdivisional lines of Township 16 North, Range 26 East, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens and Paul G. Bauer, Cadastral Surveyors, having been critically examined and found correct, are hereby approved. Washington, D.C.

AUG 31 1964  
(Date)

*E. L. Lemington*  
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

\_\_\_\_\_  
(Date)

\_\_\_\_\_  
(Chief, Division of Engineering)