

Form 4-679
(January 1963)

BOOK 4721
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

REMONUMENTED

CADASTRAL SURVEY CORNERS

Township 15 North, Range 7 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated April 23, 19 64, which provided for the surveys
included under Group Number 415, approved April 23, 1964,
and assignment instructions dated May 15, 19 64.

Survey commenced May 18, 19 64

Survey completed June 26, 19 64

1A

BOOK 4721 INDEX DIAGRAM

Township 15 North, Range 7 East,

6	5	4	3	2	1
				3	2 3
7	8	9	10	11	2 12
				3	1
13	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1

BOOK 4721

Township 15 North Range 7 East,
Gila and Salt River Meridian, Arizona

16

CHAINS

The boundaries and subdivisional lines of fractional Township 15 North, Range 7 East, were surveyed in 1902 by Girard and Latimer.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 23, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The Assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, Township 15 North, Range 7 East, Arizona

The cor. of secs. 7, 12, 13 and 18, Tps. 15 N., Rs. 7 and 8 E., is monumented by a malpais stone, 20 x 15 x 10 ins., firmly set, mkd. with 2 notches on N. and 4 notches on S., with scattered mound of stones W., from which, the remaining original bearing trees

A split juniper, 24 ins. diam., bears S. 36° W., 222 lks. dist. This tree is in railed area and considerably cut and marred in attempt to push over. No mks. legible.

A ponderosa pine, 30 ins. diam., bears N. 72° W., 254 lks. dist., mkd. T15N R7E S12 BT. (Note: record is N. 72° W., 245 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T15N
R7E R8E
S12 | S7
S13 | S18
1964

Bury the original cor. stone alongside the iron post.

Rebuild a large mound of stones W. of the iron post.

No other bearing trees available.

The ¼ sec. cor. of secs. 12 and 13, is monumented by a malpais stone, 20 x 12 x 8 ins., firmly set, mkd. ¼ on N., from which, the original bearing trees

A juniper, 18 ins. diam., bears S. 20° E., 92 lks. dist., mkd. ¼ S13 BT. (Note: record is S. 25° E., 100 lks. dist.)

A ponderosa pine, 16 ins. diam., bears N. 30° W., 80 lks. dist., scribe marks grown over, remarked T15N R7E ¼ S12 BT.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R7E

¼ S12
 S13
 1964

Raise a mound of stones N. of the iron post and deposit the original cor. stone in the mound.

The ¼ sec. cor. of secs. 11 and 12, is monumented by a malpais stone, 24 x 10 x 10 ins., firmly set, mkd. ¼ on W., with a mound of stones W., from which, the remains of the original bearing trees

A dead pine (juniper called for), 24 ins. diam., bears S. 2°45' E., 255 lks. dist., mkd. ¼ S12 BT.

A pine, 16 ins. diam., bears S. 49°15' W., 307 lks. dist., is dead and fallen.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R7E

¼
 S11 | S12
 1964

from which

A alligator juniper, 6 ins. diam., bears N. 29°45' W., 165 lks. dist., mkd. T15N R7E ¼ S11 BT.

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

The cor. is located on old E-W fence line.

The cor. of secs. 1, 2, 11 and 12, is monumented by a malpais stone, 20 x 16 x 4 ins., firmly set, mkd. with 5 notches on S. and 1 notch on E., from which, the remains of the original bearing trees

A juniper, 36 ins. diam., bears S. 2°15' E., 209 lks. dist., mkd. T15N R7E S12 BT.

The other original bearing trees (oaks) have died and fallen.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R7E

S2 | S1
 S11 | S12
 1964

from which

CHAINS

A juniper, 6 ins. diam., bears N. 20°30' E.,
 54 lks. dist., mkd. T15N R7E S1 BT.

A oak, 6 ins. diam., bears S. 77°30' W.,
 147 lks. dist., mkd. S11 BT.

Bury the original cor. stone alongside the iron post.

Raise a mound of stones W. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, is monumented by a malpais stone, 18 x 16 x 4 ins., firmly set, mkd. $\frac{1}{4}$ on N., with a large mound of stones W. The original bearing trees have recently been railed out. Bearings and dist. to stump holes check.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound with stones to top, with brass cap mkd.

T15N R7E
 $\frac{1}{4}$ $\frac{S1}{S12}$
 1964

Deposit the original cor. stone in the mound alongside the iron post.

Raise a mound of stones N. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, is monumented by a malpais stone in place, 34 x 28 x 13 ins., plainly mkd. $\frac{1}{4}$ and a cross at the cor. point, from which, the original bearing trees

A juniper, 15 ins. diam., bears S. 52° E., 166 lks. dist., mkd. $\frac{1}{4}$ S14 BT. (I reopen the partly grown over blaze.)

A juniper, 24 ins. diam., bears N. 47° W., 48 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

As the cor. stone is well mkd. with no signs of deterioration, I do not remonument this cor.

Raise a large mound of stones N. of the orig. cor. stone.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, is monumented by a malpais stone, 20 x 10 x 18 ins., firmly set, mkd. $\frac{1}{4}$ on N., from which, the original bearing trees

A juniper, 14 ins. diam., bears N. 34° E., 133 lks. dist., mkd. $\frac{1}{4}$ S2 BT. (Note: 132 lks. dist. called for in record.)

A juniper, 14 ins. diam., bears S. 27° W., 149 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

At the cor point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound with stones to top, with brass cap mkd.

T15N R7E
 $\frac{1}{4}$ $\frac{S2}{S11}$
 1964

6

BOOK 4721

CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23 day of April, 1964, I have remonumented cadastral survey corners in Township 15 North, Range 7 East,

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 24, 1965

(Date)

Boyd S. Owens

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date FEB 25 1965

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 15 North, Range 7 East, of the Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUL 6 1965

(Date)

[Signature]

(Chief, Division of Engineering)

NE

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~

, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)