

Form 4-679
(January 1963)

BOOK 4727
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

REMONUMENTED

CADASTRAL SURVEY CORNERS

Township 13 North, Range 5 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated April 23, 19 64, which provided for the surveys
included under Group Number 415, approved April 23, 1964,
and assignment instructions dated May 15, 19 64.

Survey commenced May 18, 19 64

Survey completed June 26, 19 64

BOOK 4727

INDEX DIAGRAM

Township 13 North, Range 5 East,

2 6	5 5	4	3	2	1
7	8 5	9 4	10 3	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

CHAINS

The south boundary (the Third Standard Parallel North), part of the east, west and north boundaries, and a portion of the subdivisional lines were surveyed in 1873 by C. B. Foster. The subdivision within the Camp Verde Garden Reservation was surveyed in 1887 by C. H. Wallace. That portion of land within the abandoned Camp Verde Military Reservation was resurveyed in 1892 by D. Drummond. A portion of the boundaries and subdivisional lines was resurveyed in 1916 by Wm. H. Richards. Part of the subdivisional lines were resurveyed in 1923 by B. J. Kinsey and Ty White, who also amended a portion of the Third Standard Parallel North and surveyed part of the west boundary.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 23, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, Township 13 North, Range 5 East, Arizona

The cor. of secs. 13 and 24 on the E. bdy. of the Tp. is monumented by a malpais stone 14x8x6 ins., firmly set, mkd. with 3 notches on the N. and S., with a mound of stones W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T13N
R5E R6E
S13
S24
1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone W. of the iron post.

A fence bearing N. and S. bears W., 4 lks. dist.

The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp. is monumented by a malpais stone 24x14x6 ins., firmly set, mkd. with 5 notches on S. and 1 notch on N.

At the cor. point

CHAINS

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T13N
R4E R5E
S 1 | S 6
S12 | S 7
1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stone W. of the iron post.

A telephone pole bears East, 6½ lks. dist.

A fence cor. bears N., 2 lks. dist., from which fences bear N., E. and W.

The ¼ sec. cor. of secs. 1 and 6 on the W. bdy. of the Tp. is monumented by a malpais stone 24x14x6 ins., firmly set, mkd. ¼ on W. face.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.

T13N
R4E R5E
¼
S 1 | S 6
1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stone W. of the iron post.

The cor. of secs. 13, 14, 23 and 24 is monumented by a malpais stone 14x10x8 ins., set in a mound of stone with an old squared stake lying alongside. The stone is mkd. with 3 notches on S. and 1 notch on E.; unable to read mks. on squared stake.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E
S14 | S13
S23 | S24
1964

Deposit the original cor. stone in a mound of stone W. of the iron post.

A N-S fence bears E., 5 lks. dist.

The ¼ sec. cor. of secs. 13 and 24 is monumented by a malpais stone 12x8x3 ins., firmly set with piece of old wooden stake alongside, mkd. with ¼ on N. face.

CHAINS

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E
 $\frac{1}{4}$ $\frac{S13}{S24}$
 1964

Bury the original cor. stone alongside the iron post.

Raise a mound of stone N. of the iron post.

The cor. of secs. 14, 15, 22 and 23 is monumented by a malpais stone 14x12x10 ins., firmly set with piece of old wooden stake alongside, stone mkd. with 3 notches on the S. and 2 notches on the E., with a mound of stone N.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E
 $\frac{S15}{S22}$ | $\frac{S14}{S23}$
 1964

Bury the original corner stone alongside the iron post.

Raise a mound of stone W. of the iron post.

A road bearing N. and S., bears W., 1.00 chain dist.

The cor. of secs. 10, 11, 14 and 15 is monumented by a limestone 14x12x8 ins., firmly set, mkd. with 4 notches on S. and 2 notches on E., with a mound of stones W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E
 $\frac{S10}{S15}$ | $\frac{S11}{S14}$
 1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

The cor. is located under fence bearing W. and SE.

The ¼ sec. cor. of secs. 10 and 11 is monumented by a limestone 14x12x6 ins., firmly set in a mound of stones, mkd. ¼ on W.

BOOK 4727

Remonumentation, Township 13 North, Range 5 East, Arizona

4

4.

CHAINS

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound with stones to top, brass cap mkd.

T13NR5E

¼

S10|S11

1964

Deposit the original cor. stone alongside the iron post.

The cor. of secs. 15, 16, 21 and 22 is monumented by a malpais stone 20x14x10 ins., firmly set in a collar of stones with old wooden stake alongside, stone mkd. with 3 notches on S. and E. edges, with a mound of stones W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground and in a collar of stone, brass cap mkd.

T13NR5E

S16|S15

S21|S22

1964

Deposit the mkd. stone and old stake alongside the iron post.

Rebuild the original mound of stones W. of the iron post.

Fence cor. bears SE., 8 lks. dist., from which fences bear N. and E.

The cor. of secs. 9, 10, 15 and 16 is monumented by a cobblestone 15x10x8 ins., firmly set, mkd. with 4 notches on S. and 3 notches on E., with a mound of stones W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E

S 9|S10

S16|S15

1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone W. of the iron post.

The ¼ sec. cor. of secs. 9 and 10 is monumented by a granite stone 10x10x10 ins., firmly set, mkd. ¼ on W. face, with a mound of stones W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound with stones to top, brass cap mkd.

CHAINS

T13NR5E

$\frac{1}{4}$

S 9 | S10

1964

Deposit the original cor. stone alongside the iron post.

The cor. of secs. 3, 4, 9 and 10 is monumented by a limestone 16x8x8 ins., firmly set, mkd. with 5 notches on the S. and 3 notches on the E., with a mound of stones W.

At the cor. point

Set and iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E

S 4 | S 3

S 9 | S10

1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone W. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9 is monumented by a limestone 18x12x4 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, with a mound of stones W.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E

$\frac{1}{4}$

S 8 | S 9

1964

Bury the original cor. stone alongside the iron post.

Rebuild the original mound of stone W. of the iron post.

The cor. is located on a N-S fence line, about 150 lks. north of jog in dirt road bearing E. and W.

A utility line parallels the fence.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 5 is monumented by a limestone 12x8x4 ins., firmly set in a mound of stones, mkd. $\frac{1}{4}$ on W. face.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.

T13NR5E

$\frac{1}{4}$

S 5 | S 4

1964

BOOK 4727

Remonumentation, Township 13 North, Range 5 East, Arizona

6

6.

CHAINS

Bury the original cor. stone alongside the iron post.

Raise a mound of stones W. of the iron post.

A fence cor. bears NE., 5 lks. dist., from which fences bear N., S. and W.

The center of cattle guard on oiled road bearing E. and W. bears north, 109 lks. dist.

The cor. is at the NW. end of an air strip.

BOOK 4727
CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 23 day of April, 1964,
I have remonumented cadastral survey corners in Township 13 North,
Range 5 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 24, 1965

(Date)

Boyd S. Owens

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in
Township 13 North, Range 5 East, of the Gila and Salt River Meridian,
Arizona,

executed by Boyd S. Owens, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JUL 6 1965

(Date)

E. E. Pennington

(Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~_____~~, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)