

Form 4-679
(January 1963)

BOOK 4735
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

REMONUMENTED

CADASTRAL SURVEY CORNERS

Township 23 North, Range 1 West

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Cadastral Surveyor

Under special instructions dated June 22, 19 64, which provided for the surveys
included under Group Number 417, approved June 22, 1964,
and assignment instructions dated August 27, 19 64.

Survey commenced September 6, 19 64

Survey completed October 27, 19 64

1A

BOOK 4735

BOOK 4735 INDEX DIAGRAM

Township 23 North, Range 1 West,
9 7

6	5	4	3	2	1	6
7	8	9	10	11	12	5
18	17	16	15	14	13	5
19	20	21	22	23	24	4
30	29	28	27	26	25	4
31	32	33	34	35	36	3
						3
						2
						1
						1

CHAINS

The North, South, East and West boundaries and Sub-divisional lines were surveyed in 1884 by J. T. Smith. The North boundary was resurveyed in 1916 by Davis Thompson.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b), dated October 16, 1958.

The approval of the Special Instructions on June 22, 1964 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The Assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, T. 23 N., R. 1 W., Arizona

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, T. 23 N., R. 1 E. and R. 1 W., is monumented by a malpais stone, 8 x 12 x 12 ins., loosely set in a scattered mound of stones, mkd. $\frac{1}{4}$ on the W., from which the original bearing tree

A juniper, 12 ins. diam., bears S. 63° W.,
7 lks. dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, with a mound of stones with 4 ft. base to the top, with brass cap mkd.

T23N
R1W R1E
 $\frac{1}{4}$
S36|S31
1964

from which

A pinon, 7 ins. diam., bears N. 75 $\frac{1}{2}$ ° E.,
18 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Bury the original cor. stone alongside the iron post.

Cor. is on a gentle N. slope and in a N. and S. fence, with the Santa Fe railroad tracks about 25 chs. N.

The cor. of secs. 25, 30, 31 and 36, T. 23 N., R. 1 E., and R. 1 W., is monumented by a limestone, 10 x 16 x 20 ins., firmly set in a collar of stones, mkd. with 5 notches on the N. and 1 notch on the S., from which the original bearing trees

A pinon, 10 ins. diam., bears N. 89° E.,
17 lks. dist., mkd. with an overgrown blaze.

A pinon, 12 ins. diam., bears N. 86° W.,
50 lks. dist., blaze mostly grown over with
parts of scribe mks. visible.

CHAINS

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N
R1W R1E
S25|S30
S36|S31
1964

from which

A pinon, 8 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ E.,
27 lks. dist., mkd. T23N R1E S30 BT.

A juniper, 8 ins. diam., bears S. 27° E.,
98 lks. dist., mkd. T23N R1E S31 BT.

A juniper, 12 ins. diam., bears S. 22° W.,
41 lks. dist., mkd. T23N R1W S36 BT.

A juniper, 8 ins. diam., bears N. 54° W.,
71 lks. dist., mkd. T23N R1W S25 BT.

Build a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle SW. slope and 5 lks. E. of a N. and S. fence, with the Santa Fe railroad tracks about 15 chs. S.

The point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, T. 23 N., R. 1 E. and R. 1 W., is reestablished from the original bearing tree by record bearing and distance.

A pinon, 16 ins. diam., bears N. 8° W.,
72 lks. dist., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N
R1W R1E
 $\frac{1}{4}$
S25|S30
1964

from which

A pinon, 10 ins. diam., bears N. 67° E.,
47 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

A juniper, 6 ins. diam., bears N. 48° W.,
114 lks. dist., mkd. $\frac{1}{4}$ S25 BT.

Build a small mound of stones to the W. of the iron post.

Cor. is on a NW. slope, 11 lks, E. of a N. and S. fence.

CHAINS

The cor. of secs. 19, 24, 25 and 30, is monumented by a malpais stone, 12 x 12 x 16 ins., loosely set, mkd. with 4 notches on the N. and 2 notches on the S., with a mound of stones to the E.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N
R1W R1E
S24 | S19
S25 | S30
1964

from which

A juniper, 8 ins. diam., bears S. 56½° E.,
42 lks. dist., mkd. T23N R1E S30 BT.

A juniper, 14 ins. diam., bears S. 19½° W.,
81 lks. dist., mkd. T23N R1W S25 BT.

A juniper, 12 ins. diam., bears N. 60° W.,
201 lks. dist., mkd. T23N R1W S24 BT.

Build a mound of stones to the W. of the iron post.

Bury the original corner stone in the mound of stones to the W. of the iron post.

Cor. is on a rocky S. slope, 9 lks. W. of a N. and S. fence.

The ¼ sec. cor. of secs. 19 and 24, T. 23 N., R. 1 E. and R. 1 W., is monumented by a malpais stone, 8 x 8 x 14 ins., set in a mound of stones, mkd. ¼ on the W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N
R1W R1E
¼
S24 | S19
1964

from which

A juniper, 4 ins. diam., bears N. 53½° E.,
29 lks. dist., mkd. X BT.

A juniper, 12 ins. diam., bears S. 89½° W.,
83 lks. dist., mkd. ¼ S24 BT.

Build a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle E. slope and in a N. and S. fence.

CHAINS

The point for the cor. of secs. 13, 18, 19 and 24, T. 23 N., R. 1 E. and R. 1 W., is reestablished by using record bearing and distance from the original bearing tree

A juniper, 20 ins. diam., bears N. 45° E.,
40 lks. dist., mkd. T23N R1E S18 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N
R1W R1E
S13 | S18
S24 | S19
1964

from which

A juniper, 7 ins. diam., bears S. 49½° E.,
72 lks. dist., mkd. S.19 BT

A pinon, 10 ins. diam., bears S. 72° W.,
34 lks. dist., mkd. T23N R1W, S24 BT.

A juniper, 14 ins. diam., bears N. 32½° W., 83 lks. dist., mkd. T23N R1W. S13 BT.

Build a mound of stones to the W. of the iron post.

Cor. is on top of a hill sloping E. and 7 lks. E. of a N. and S. fence.

The ¼ sec. cor. of secs. 13 and 18, T 23 N., R. 1 E. and R. 1 W., is monumented by a malpais stone, 6 x 8 x 18 ins., set in a small mound of stones, mkd. ¼ on the W.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T23N
R1W R1E
¼
S13 | S18
1964.

from which

A juniper, 11 ins. diam., bears S. 74° E.,
98 lks. dist., mkd. ¼ S18 BT.

A pinon, 9 ins. diam., bears S. 60° W.,
84 lks. dist., mkd. ¼ S13 BT.

Bury the original corner stone alongside the iron post.

Cor. is on a NW. slope among thick juniper and pinon trees and is in a N. and S. fence.

CHAINS

The cor. of secs. 7, 12, 13 and 18, T. 23 N., R. 1 E. and R. 1 W., is monumented by a malpais stone, 6 x 10 x 14 ins.; set in a mound of stones, mkd. with 4 notches on the S. and 2 notches on the N., from which the remains of the original bearing trees

A pinon, 14 ins. diam., bears S. 87° W.,
92 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N
R1W R1E
S12|S7
S13|S18
1964

from which

A pinon, 5 ins. diam., bears S. 18° E.,
87 lks. dist., mkd. S.18 BT.

A pinon, 6 ins. diam., bears S. 53½° W.,
95 lks. dist., mkd. T23N R1W S13 BT.

A juniper, 14 ins. diam., bears N. 20° W.,
31 lks. dist., mkd. T23N R1W S12 BT.

Build a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is in a nearly level area and in a N. and S. fence.

The ¼ sec. cor. of secs. 7 and 12, T. 23 N., R. 1 E., and R. 1 W., is monumented by a malpais stone, 4 x 9 x 14 ins., set in a small mound of stones, mkd. ¼ on the W., from which the original bearing tree

A juniper, 14 ins. diam., bears S. 81½° E.,
31 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23N
R1W R1E
¼
S12|S7
1964

from which

A juniper, 8 ins. diam., bears S. 33½° E.,
63 lks. dist., mkd. ¼ S7 BT.

A juniper, 16 ins. diam., bears N. 57° W.,
48 lks. dist., mkd. ¼ S12 BT.

6.

CHAINS

Build a mound of stones to the W. of the iron post.
 Bury the original corner stone alongside the iron post.
 Cor. is in almost level area and is 6 lks. E. of a
 N. and S. fence with a track road 75 lks. W.

The cor. of secs. 1, 6, 7 and 12, T. 23 N., R. 1 E. and
 R. 1 W., is monumented by a malpais stone, 6 x 10 x 14
 ins., set in a small mound of stones, mkd. with 5
 notches on the S. and 1 notch on the N., from which the
 original bearing trees

A juniper, 14 ins. diam., bears S. 20° E.,
 30 lks. dist., mkd. T23N R1E S7 BT.

A juniper, 14 ins. diam., bears S. 54½° W.,
 38 lks. dist., mkd. T23N R1W. S12 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

T23N
 R1W R1E
 S1 | S6
 S12 | S7
 1964

from which

A juniper, 16 ins. diam., bears N. 75½° E.,
 80 lks. dist., mkd. T23N R1E S6 BT.

A juniper, 8 ins. diam., bears N. 41½° W.,
 32 lks. dist., mkd. T23N R1W S1 BT.

Build a mound of stones to the W. of the iron post.
 Bury the original corner stone alongside the iron post.
 Cor. is in nearly level area and 11 lks. W. of a fence
 cor. from which fences bear N., S. and E. and with a
 track road 100 lks. W., bearing N. and S.

The ¼ sec. cor. on the N. Bdy. of sec. 1, T. 23 N.,
 R. 1 W., is monumented by a limestone, 8 x 16 x 20 ins.,
 mkd. ¼ on the N., with a mound of stones to the N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
 in the ground, with brass cap mkd.

¼ S1
 T23N R1W
 1964

from which

A pinon, 8 ins. diam., bears S. 34° E., 13 lks.
 dist., mkd. ¼ S1 BT.

A pinon, 6 ins. diam., bears S. 27° W.,
 64 lks. dist., mkd. ¼ S1 BT.

CHAINS

Build a mound of stones to the S. of the iron post.
 Bury the original corner stone alongside the iron post.
 Cor. is on a steep W. slope among thick juniper and pinon trees and is in an E. and W. fence with a deep wash 4 chs. wide, draining SW.

At the cor. of secs. 1, 2, 35 and 36, Tps. 23 and 24 N., R. 1 W., is monumented by a malpais stone, 8 x 10 x 14 ins., firmly set, mkd. with 5 notches on the W. and 1 notch on the E., with a mound of stones to the NW., from which the original bearing trees

A pinon, 8 ins. diam., bears S. 40° E., 45 lks. dist., tree is dead and has fallen, mkd. T23N R1W S1 BT.

A juniper, 20 ins. diam., bears S. 45° W., 29 lks. dist., mkd. T23N R1W S2 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, with a mound of stones with 4 ft. base to the top, with brass cap mkd.

T24N R1W
 S35 | S36
 S2 | S1
 T23N
 1964

from which

A pinon, 10 ins. diam., bears N. 51° E., 111 lks. dist., mkd. T24N R1W S36 BT.

A juniper, 6 ins. diam., bears S. 46° E., 30 lks. dist., mkd. T23N R1W S1 BT.

A juniper, 16 ins. diam., bears N. 42° W., 107 lks. dist., mkd. T24N R1W S35 BT.

Bury the original corner stone alongside the iron post.

Cor. is on a rocky SW. slope and in an E. and W. fence, among moderate juniper and pinon trees.

The ¼ sec. cor. on the N. Bdy of sec. 2, T. 23 N., R. 1 W., is monumented by a limestone, 8 x 10 x 12 ins., firmly set, mkd. ¼ on the N., with a mound of stones to the N., from which the original bearing trees

A pinon, 12 ins. diam., bears S. 67½° E., 25 lks. dist., mkd. ¼ S2 BT.

A pinon, 6 ins. diam., bears S. 25° W., 104 lks. dist., mkd. ¼ S2 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

CHAINS

1/2 S2
T23N R1W
1964

Build a mound of stones to the S. of the iron post.
Bury the original cor. stone alongside the iron post.
Cor. is on a gentle SW. slope among medium juniper and pinon trees and is in an E. and W. fence.

The cor. of secs. 4 and 5 on the N. Bdy. of T. 23 N., R. 1 W., is monumented by a limestone, 8 x 10 x 16 ins., firmly set, mkd. with 4 notches on the E. and 2 notches on the W.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S5 | S4
T23N R1W
1964

from which

A juniper, 5 ins. diam., bears S. 33 1/2° E., 98 lks. dist., mkd. X BT.

A juniper, 6 ins. diam., bears S. 11° W., 95 lks. dist., mkd. T23N R1W S5 BT.

Bury the original corner stone alongside the iron post.

Cor. is on a gradual NW. slope in an E. and W. fence.

The 1/2 sec. cor. on the N. Bdy. of sec. 5, T. 23 N., R. 1 W., is monumented by a limestone, 7 x 9 x 11 ins., set in a mound of stones, mkd. 1/2 on the N.

At the cor. point

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

1/2 S5
T23N R1W
1964

from which

A juniper, 5 ins. diam., bears S. 83° W., 34 lks. dist., mkd. 1/2 S5 BT.

Bury the original corner stone alongside the iron post.

Cor. is on a S. slope in an E. and W. fence with a small draw, 110 lks. W., draining SE.

BOOK 4735

Remonumentation, T. 23 N., R. 1 W., Arizona

9.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, Tps. 23 and 24 N., R. 1 W., is monumented by a limestone, 12 x 14 x 20 ins., firmly set, mkd. $\frac{1}{4}$ on the N., from which the orig. bearing trees

A juniper, 14 ins. diam., bears S. 41° E., 87 lks. dist., mkd. $\frac{1}{4}$ S BT.

A juniper, 14 ins. diam., bears S. 11° W., 89 lks. dist., mkd. X S36 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T24N R1W

$\frac{1}{4}$ S31
S6

T23N
1964

from which

A juniper, 20 ins. diam., bears N. 56° E., 145 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle E. slope in an E. and W. fence and among moderate juniper and pinon trees.

11
BOOK 4735
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day of June, 1964, I have remonumented cadastral survey corners in Township 23 North, Range 1 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 24, 1965
(Date)

Wallace R Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date **FEB 25 1965**

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 23 North, Range 1 West, of the Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUL 2 1965
(Date)

E. E. Livingston
(Chief, Division of Engineering) *NES*

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~_____~~, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)