

1A

BOOK 4736
INDEX DIAGRAM

Township 28 North, Range 4 East,

6	2 5 1 2	4 3	3	2	1
7	1 8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

CHAINS

The North boundary was surveyed in 1899 by W. O. Secor. The East, West and South boundaries and Subdivisional lines were surveyed in 1900 by L. Wolfly.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 22, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The Assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open site Dietzgen compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, T. 28 N., R. 4 E., Arizona

The point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8 was established by using record bearing and distance from the original bearing trees.

A pinon, 10 ins. diam., bears N. $44\frac{1}{2}^\circ$ E., 15 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A pinon, 10 ins. diam., bears S. 48° W., 8 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28NR4E

$\frac{1}{4}$
S7 | S8
1964

Found a wooden post, 3 ft. long, 4 ins. square, lying loose on the ground, mkd. $\frac{1}{4}$ S7 with other faint marks. Bury the cor. post alongside the iron post.

Cor. is in nearly level area among thick juniper and pinon.

The cor. of secs. 5, 6, 7 and 8 is monumented by a limestone, 10 x 12 x 24 ins., loosely set, mkd. with 5 notches on the S. and E., from which the original bearing trees

A pinon, 8 ins. diam., bears N. 17° E., 15 lks. dist., mkd. T28N R4E S5 BT.

A pinon, 6 ins. diam., bears S. 17° E., 27 lks. dist., mkd. T28N R4E S8 BT.

CHAINS

brass cap mkd.

T28NR4E
 $\frac{1}{4}$ $\frac{S5}{S8}$
 1964

from which

A pine, 12 ins. diam., bears N. 55° E.,
 54 lks. dist., mkd. $\frac{1}{4}$ S5 BT

A pinon, 8 ins. diam., bears S. 24° W.,
 13 lks. dist., mkd. $\frac{1}{4}$ S8 BT

Bury the original corner stone alongside the iron post.

Cor. is on the SE. side of a spur sloping SW.

The cor. of secs. 4, 5, 8 and 9 is monumented by a limestone 7 x 16 x 18 ins., firmly set, mkd. with 4 notches on the E. and 5 notches on the S., from which the original bearing trees

A pinon, 14 ins. diam., bears N. 51 $\frac{1}{2}$ ° E.,
 63 lks. dist., mkd. T28N R4E S4 BT

A pinon, 14 ins. diam., bears S. 70° E.,
 67 lks. dist., mkd. T28N R4E S9 BT

A pinon, 8 ins. diam., bears S. 21 $\frac{3}{4}$ ° W.,
 28 lks. dist., mkd. T28N R4E S8 BT

A pinon, 16 ins. diam., bears N. 33 $\frac{1}{2}$ ° W.,
 52 lks. dist., mkd. T28N R4E S5 BT

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T28NR4E
 $\frac{S5}{S8}$ | $\frac{S4}{S9}$
 1964

Bury the original corner stone alongside the iron post.

Cor. is in nearly level area among thick juniper and pinon trees.

2

CHAINS

A fallen pinon, 10 ins. diam., bears S. 62° W.,
24 lks. dist., mkd. T28N R4E S7 BT.

A juniper, 14 ins. diam., bears N. 69° W.,
23 lks. dist., mkd. T28N R4E S6 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins.
in the ground, with a mound of stones with 3½ ft. base
to the top, with brass cap mkd.

T28N R4E
S6 | S5
S7 | S8
1964

from which

A pinon, 7 ins. diam., bears N. 55° E.,
26 lks. dist., mkd. S5 BT.

A pinon, 6 ins. diam., bears S. 45° E.,
54 lks. dist., mkd. S8 BT.

A pinon, 4 ins. diam., bears S. 32° W.,
14 lks. dist., mkd. BT.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle SW. slope, 3 chs. E. of a draw
draining SE.

The ¼ sec. cor. of secs. 5 and 6 is monumented by a
limestone, 10 x 14 x 16 ins., firmly set, mkd. ¼ S
on the W., from which the original bearing trees

A pinon, 10 ins. diam., bears S. 26° E.,
20 lks. dist., mkd. ¼ S5 BT.

A pinon, 14 ins. diam., bears S. 83° W.,
10 lks. dist., mkd. ¼ S6 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins.
in the ground, with a mound of stones with 3½ ft. base
to the top, with brass cap mkd.

T28NR4E
¼
S6 | S5
1964

Bury the orig. corner stone alongside the iron post.

Cor. is on a gentle E. slope among thick juniper and
pinon trees.

The ¼ sec. cor. of secs. 5 and 8 is monumented by a
limestone, 12 x 14 x 22 ins., firmly set, mkd. ¼ S on
the N.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins.
in the ground, with a mound of stones to the top, with

5

BOOK 4736

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day of June, 1964, I have remonumented cadastral survey corners in Township 28 North, Range 4 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 24, 1965
(Date)

Wallace R. Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 28 North, Range 4 East, of the Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUL 2 1965
(Date)

E. B. Pennington
(Chief, Division of Engineering) *MES*

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
_____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)