

BOOK 4737

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Remonumented

Cadastral Survey Corners

Township 30 North, Range 2 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Cadastral Surveyor

Under special instructions dated June 22, 19 64, which provided for the surveys

included under Group Number 417, approved June 22, 1964,

and assignment instructions dated August 27, 19 64.

Survey commenced September 6, 19 64

Survey completed October 27, 19 64

1A

BOOK 4737 INDEX DIAGRAM

Township 30 North, Range 2 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	5 14	5 13
					4 4
19	20	21	22	23	3 24
					3
30	29	28	27	26	25
31	32	33	34	35	36

CHAINS

The north, south and west boundaries and subdivisional lines were surveyed in 1900 by F. B. Jacobs. The east boundary was surveyed in 1900 by J. B. Pope.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 22, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, Township 30 North, Range 2 East, Arizona

The cor. of secs. 19, 24, 25 and 30, Ts.30N, Rs.2&3E, is monumented by a limestone, 8x10x16 ins., firmly set, mkd. with 4 notches on the N. and 2 notches on the S., from which the original bearing trees

A pine, 36 ins. diam., bears N. 70½° E., 250 lks. dist., mkd. T30NR3E S 19 BT.

A pine, 40 ins. diam., bears S. 65° E., 183 lks. dist., mkd. T30NR3E S30 BT.

A pine, 36 ins. diam., bears S. 70° W., 132 lks. dist., mkd. T30NR2E S 25 BT.

A pine, 42 ins. diam., bears N. 19° W., 149 lks. dist., mkd. T30NR2E S 24 BT.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30N
R2E R3E
<u>S24</u> <u>S19</u>
<u>S25</u> <u>S30</u>
1964

Build a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle SE. slope with a draw 200 lks. E., draining N.

The ¼ sec. cor. of secs. 19 and 24, Ts.30N, Rs.2&3E, is monumented by a limestone, 8x12x16 ins., firmly set, mkd. ¼ on the W., from which the original bearing trees

CHAINS

A pine, 18 ins. diam., bears N. 50° E., 186 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears S. 15° W., 49 lks. dist., mkd. 1/4 S 24 BT.

At the cor. point

Set an iron post 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, with a mound of stones with 3 1/2 ft. base to the top, with brass cap mkd.

T30N
R2E R3E
1/4
S24 | S19
1964

from which

A pine, 8 ins. diam., bears N. 55° E., 87 lks. dist., mkd. 1/4 S 19 BT.

Bury the original corner stone alongside the iron post.

Cor. is in nearly level area with sage and moderate trees and with a track road 50 lks. S., bearing NE. and SW.

The cor. of secs. 13, 18, 19 and 24, Ts.30N, Rs.2&3E, is monumented by a limestone, 5x11x16 ins., firmly set, mkd. with 3 notches on the N. and S., from which the original bearing trees

A pine, 36 ins. diam., bears N. 55 1/2° E., 130 lks. dist., mkd. T30NR3E S 18 BT.

A pine, 45 ins. diam., bears S. 56° E., 126 lks. dist., mkd. T30NR3E S 19 BT.

A pine, 24 ins. diam., bears N. 59° W., 131 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears S. 65° W., 55 lks. dist., mkd. T30NR2E S 24 BT.

At the cor. point

Set an iron post 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with a mound of stones with 3 1/2 ft. base to the top, with brass cap mkd.

T30N
R2E R3E
S13 | S18
S24 | S19
1964

Bury the original corner stone alongside the iron post.

Cor. is on a N. slope among scattered pine trees, with a draw 150 lks. N. draining W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 24 and 25 is monumented by a limestone, 8x18x20 ins., firmly set, mkd. $\frac{1}{4}$ on the N., with a mound of stones to the N., from which the original bearing trees

A pine, 36 ins. diam., bears South, 58 lks. dist., mkd. $\frac{1}{4}$ S 25 BT.

A pine, 32 ins. diam., bears N. 54° W., 84 lks. dist., mkd. with faint scribe mks.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T30NR2E
 $\frac{1}{4}$ S 24
 S 25
 1964

from which

A pinon, 12 ins. diam., bears N. $66\frac{1}{2}^\circ$ E., 64 lks. dist., mkd. $\frac{1}{4}$ S 24 BT.

Build a mound of stones to the N. of the iron post.

Bury the original corner stone in the mound of stones N. of the iron post.

Cor. is in nearly level area with a draw about 3 chs. SW. which drains NW.

The $\frac{1}{4}$ sec. cor. of secs. 23 and 24 is monumented by a limestone, 4x16x24 ins., firmly set in a collar of stones, mkd. $\frac{1}{4}$ on the W., from which an original bearing tree

A pine 22 ins. diam., bears S. $84\frac{1}{2}^\circ$ E., 121 lks. dist., blaze partly grown over with parts of scribe mks. visible.

No evidence of the other original bearing tree.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., on solid rock, with a mound of stones with 5 ft. base to the top, with brass cap mkd.

T30NR2E
 $\frac{1}{4}$
 S23 | S24
 1964

from which

A pine, 6 ins. diam., bears N. $23\frac{1}{2}^\circ$ W., 47 lks. dist., mkd. $\frac{1}{4}$ S 23 BT.

Place the original corner stone in the mound of stones alongside the iron post.

Cor. is on a rocky S. slope with a power line 50 lks. W. which bears NW. and SE., and an unimproved road 75 lks. which bears NE. and SW.

BOOK 4737

Remonumentation, Township 30 North, Range 2 East, Arizona 4.

4

CHAINS

The cor. of secs. 13, 14, 23 and 24 is monumented by a limestone, 8x14x20 ins., firmly set, dimly mkd. with 3 notches on the S. and 1 notch on the E., from which the original bearing trees

A pine stump 18 ins. diam., bears N. 55° E., 116 lks. dist., no scribe mks. found.

A pine stump 40 ins. diam., bears S. 27° E., 232 lks. dist., no scribe mks. found.

A pine, 30 ins. diam., bears S. 72 $\frac{3}{4}$ ° W., 69 lks. dist., mkd. with an overgrown blaze.

A pine, 40 ins. diam., bears N. 17° W., 97 lks. dist., mkd. T30NR2E S 14 BT.

At the cor. point

Set an iron post 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30NR2E	
S14	S13
S23	S24
1964	

from which

A pine 6 ins. diam., bears N. 82° E., 121 lks. dist., mkd. T30NR2E S 13 BT.

A pine 14 ins. diam., bears S. 44° E., 130 lks. dist., mkd. T30NR2E S 24 BT.

Build a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle S. slope.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24 is monumented by a limestone, 8x15x20 ins., firmly set, mkd. $\frac{1}{4}$ on the N., from which the original bearing trees

A pinon stump 24 ins. diam., bears N. 62 $\frac{1}{2}$ ° E., 26 lks. dist., mkd. BT on the stump.

A pinon 16 ins. diam., bears S. 71 $\frac{1}{2}$ ° W., 83 lks. dist., mkd. $\frac{1}{4}$ S 24 BT.

At the cor. point

Set an iron post 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with a collar of stones to the top, with brass cap mkd.

T30NR2E	
$\frac{1}{4}$ S 13	
S 24	
1964	

Bury the original corner stone alongside the iron post.

CHAINS

Cor. is on a gentle S. slope in a burned area with a track road 50 lks. S. which bears E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 14 is monumented by a sandstone, 6x14x24 ins., firmly set, mkd. $\frac{1}{4}$ on the W., from which the original bearing trees

A pine 32 ins. diam. bears S. 42° E., 163 lks. dist., mkd. $\frac{1}{4}$ S 13 BT

A pine 36 ins. diam. bears N. 57° W., 78 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30NR2E
 $\frac{1}{4}$
 S14|S13
 1964

Bury the original corner stone alongside the iron post.

Cor. is on a gentle SE. slope with a track road 150 lks. E.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 15 is monumented by a limestone, 6x12x20 ins., firmly set, mkd. $\frac{1}{4}$ on the W., from which the original bearing trees

A pine 30 ins. diam. bears S. 38° E., 144 lks. dist., mkd. $\frac{1}{4}$ S 14 BT

A pine 24 ins. diam. bears N. 76° W., 141 lks. dist., mkd. $\frac{1}{4}$ S 15 BT

At the cor. point

Set an iron post 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T30NR2E
 $\frac{1}{4}$
 S15|S14
 1964

Build a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle S. slope with a track road 75 lks. S. and a draw 210 lks. S. which drains SW.

7

BOOK 4737
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 22 day of June, 19 64,
I have remonumented cadastral survey corners in Township 30 North,
Range 2 East

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 24, 1965
(Date)

Wallace R. Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in
Township 30 North, Range 2 East, of the Gila and Salt River Meridian,
in the State of Arizona,

executed by Wallace R. Ott, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JUL 2 1965
(Date)

E. L. Summerton
(Chief, Division of Engineering) *NE*

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~_____ is a true copy of the original field notes.~~

(Date)

(Chief, Division of Engineering)