

1A

BOOK 4742 INDEX DIAGRAM

Township 20 South, Range 28 East,

6	5	4	3	2	1
7	8	9	10	11	1 12
18	17	16	15	14	2 13
19	20	21	22	23	3 24
30	29	28	27	26	3 25
31	32	33	34	35	4 36

BOOK 4742

Township 20 South, Range 28 East
Gila and Salt River Meridian, Arizona

14

CHAINS

The south boundary was surveyed in 1883 by J. B. McLaughlin and partly resurveyed in 1905 by J. F. Hesse, and the resurvey completed in 1916 by S. E. Blout. The east boundary was surveyed in 1884 by W. B. Neil and partly resurveyed in 1916 by S. E. Blout. The west boundary was surveyed in 1885 by R. C. Powers and resurveyed in 1916 by S. E. Blout. The north boundary was surveyed in 1902 by F. B. Jacobs and resurveyed in 1916 by S. E. Blout. The subdivisional lines were partly surveyed in 1909 by J. B. Wright, and the rest of the subdivisional lines, including a resurvey between the sections of 25 and 36 were surveyed in 1916 by S. E. Blout.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 22, 1964, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open site compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, Township 20 South, Range 28 East, Arizona

The cor. of secs. 1, 2, 11 and 12, T. 20 S., R. 28 E., is monumented by a granite stone 5x5x10 ins., loosely set, mkd. with 1 notch on the E. and 5 notches on the S., with a mound of stones to the W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20S R28E	
S 2	S 1
S11	S12
1964	

Raise a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a NW. slope and one chain E. of a draw, 80 lks. wide, which drains SW., and 45 lks. W. of a N. and S. fence.

The ¼ sec. cor. of secs. 11 and 12 is monumented by a granite stone 6x8x14 ins., firmly set, mkd. ¼ on the W.

At the cor. point

BOOK 4742

2

Remonumentation, Township 20 South, Range 28 East, Arizona 2.

CHAINS

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20S R28E

¼

S11|S12

1964

Raise a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle N. slope and 3 chs. S. of a draw, 2 chs. wide, draining W., with a fence 32 lks. E., bearing N. and S.

The cor. of secs. 11, 12, 13 and 14 is monumented by a granite stone, firmly set, mkd. with 1 notch on the E. and 4 notches on the S., with a small mound of stones to the W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20S R28E

S11|S12

S14|S13

1964

from which

An oak 16 ins. diam. bears N. 70° E., 48 lks. dist., mkd. T20S R28E S12 BT

An oak 14 ins. diam. bears S. 21½° E., 15 lks. dist., mkd. T20S R28E S13 BT

Raise a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a N. slope and 50 lks. S. of a draw which is 50 lks. wide and drains W.

The ¼ sec. cor. of secs. 13 and 14 is monumented by a granite stone 6x16x18 ins., firmly set, mkd. ¼ S 14 on the W. and S 13 on the E., with a mound of stones to the W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20S R28E

¼

S14|S13

1964

Raise a mound of stones to the W. of the iron post.

BOOK 4742

Remonumentation, Township 20 South, Range 28 East, Arizona 3.

CHAINS

Bury the original corner stone alongside the iron post.

Cor. is on a NW. slope and 188 lks. W. of a N. and S. fence with a wash about 200 lks. N., draining SW.

The witness cor. of secs. 13, 14, 23 and 24 is monumented by a granite stone 10x14x18 ins., firmly set, mkd. with 3 notches on the S. and 1 notch on the E., with a mound of stones to the W., from which the remains of the original bearing tree

An oak 12 ins. diam. bears N. 85° W., 41 lks. dist., mkd. with an overgrown blaze.

At the witness cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20S	R28E
S14	S13
S23	S24
WC	
1964	

Raise a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is 40 lks. N. of a wash 15 lks. wide which drains irregularly W., and is 90 lks. W. of a N. and S. fence.

The cor. of secs. 23, 24, 25 and 26 is monumented by a granite stone 5x7x16 ins., firmly set, mkd. with 2 notches on the S. and 1 notch on the E., with a mound of stones to the W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.

T20S	R28E
S23	S24
S26	S25
1964	

Raise a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle N. slope with a ridge 150 lks. to the S. which bears NE. and W.

The ¼ sec. cor. of secs. 25 and 26 is monumented by a granite stone 8x12x12 ins., firmly set, mkd. ¼ on the W., with a mound of stones to the W.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

BOOK 4742

4

Remonumentation, Township 20 South, Range 28 East, Arizona 4.

CHAINS

T20S R28E

$\frac{1}{2}$
S26|S25
1964

Raise a mound of stones to the W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is at the head of a small rocky draw draining NW., and is 39 lks. W. of a N. and S. fence.

The point for the cor. of secs. 25, 26, 35 and 36 was reestablished by using record bearing and distance from the remains of the original bearing trees

An oak stump 14 ins. diam. bears N. 89° E., 72 lks. dist., mkd. with a dim blaze.

An oak 14 ins. diam. bears S. 31½° E., 92 lks. dist., mkd. with an overgrown blaze.

An oak 16 ins. diam. bears S. 52¾° W., 89 lks. dist., part of scribe mks. visible.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., 8 ins. in the ground, with a mound of stones with 4 ft. base to the top, with brass cap mkd.

T20S R28E

S26|S25
S35|S36
1964

Cor. is in what appears to be the remains of a mound of stones and is 75 lks. W. of a N. and S. fence, and 350 lks. E. of a bladed road which bears NW. and SE.

The standard ¼ sec. cor. on the S. bdy. of sec. 36 is monumented by a granite stone 8x10x16 ins., firmly set, mkd. ¼ S C on the N., with a mound of stones to the N., from which the remains of an original bearing tree

An oak 12 ins. diam. bears N. 14¾° W., 173 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam. 24 ins. in the ground, with brass cap mkd.

T20S R28E

SC
 $\frac{1}{4}$ S 36
1964

Raise a mound of stones to the N. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a steep S. slope of a spur sloping W., and is 100 lks. N. of a wash draining irregularly W.

6

BOOK 4742
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 22 day of June, 19 64,
I have remonumented cadastral survey corners in Township 20 South, Range
28 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

February 3, 1965
(Date)

Wallace R. Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumentation of cadastral survey corners
in Township 20 South, Range 28 East, of the Gila and Salt River Meridian
in the State of Arizona,

executed by Wallace R. Ott, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JUL 2 1965
(Date)

E. E. Pennington
(Chief, Division of Engineering) *NEB*

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Engineering)