

Form 4-679
(January 1963)

BOOK 4743
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Remonumented

Cadastral Survey Corners

Township 20 South, Range 30 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Cadastral Surveyor

Under special instructions dated June 22, 19 64, which provided for the surveys
included under Group Number 417, approved June 22, 1964,
and assignment instructions dated August 27, 19 64.

Survey commenced September 6, 19 64

Survey completed October 27, 19 64

BOOK 4743 INDEX DIAGRAM

Township 20 South, Range 30 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4743

Township 20 South, Range 30 East
Gila and Salt River Meridian, Arizona

1.6

CHAINS

The south boundary was surveyed in 1883 by J. B. McLaughlin. The west boundary was surveyed in 1883 by W. B. Neal. The north and west boundaries and subdivisional lines were surveyed in 1884 by W. B. Neil. The north boundary was partly resurveyed in 1915 by C. A. Long. The east and west boundaries and subdivisional lines were partly resurveyed in 1905 by J. P. Walker.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 22, 1964, gave authority to proceed with the remonumentation in accordance with the Director's order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open site Dietzgen compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Re monumentation, Township 20 South, Range 30 East, Arizona

The $\frac{1}{4}$ sec. cor. of secs. 12 and 13 is monumented by a granite stone 5x10x20 ins., firmly set, mkd. $\frac{1}{4}$ on the N., with a scattered mound of stones to the N.

At the cor. point

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T20S R30E

$\frac{1}{4}$ $\frac{S 12}{S 13}$

1964

Build a mound of stones to the N. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land, and in an E. and W. fence, with a bladed road 140 lks. W. bearing N. and S., and a track road 70 lks. N., bearing E. and W.

BOOK 4743
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 22 day of June, 19 64,
I have remonumented cadastral survey corners in Township 20 South, Range
30 East

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

January 19, 1965
(Date)

Wallace R. Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 25 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumentation of cadastral survey corners
in Township 20 South, Range 30 East, of the Gila and Salt River Meridian
in the State of Arizona,

executed by Wallace R. Ott, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

JUL 2 1965
(Date)

E. J. Lemington
(Chief, Division of Engineering) *MS*

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~
~~, is a true copy of the original field notes.~~

(Date)

(Chief, Division of Engineering)