

BOOK 4762
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

COMPLETION SURVEY

of the

Subdivisional Lines

of

Township 40 North, Range 11 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens, Cadastral Surveyor

Under special instructions dated April 14, 1964, which provided for the surveys
included under Group Number 411, approved April 14, 1964,
and assignment instructions dated May 27, 1965.

Survey commenced May 28, 1965

Survey completed July 6, 1965

1A

BOOK 4762 INDEX DIAGRAM

Township 40 North, Range 11 West,

39($\frac{1}{4}$)	39($\frac{1}{4}$)	28($\frac{1}{4}$)	21($\frac{1}{4}$)	21($\frac{1}{4}$)	9($\frac{1}{4}$)
6 38	5 27	4	3 20	2 9	1
38	37	26	20	19	8
7 36	8 26	9	10 18	11 7	12
36	35		18	17	7
18 34	17	16	15 16	14 6	13
34	33		16	15	5
19 32	20 25	21	22 14	23 5	24
32	31	24	13	13	4
30 30	29 23	28	27 12	26 3	25
29	29	23	11	10	2
31 28	32 22	33	34 10	35 1	36

CHAINS

The north boundary, the Tenth Standard Parallel North, and the south and east boundaries were surveyed in 1939 by Muscott, Warner and Motch. The west boundary and a portion of the subdivisional lines were surveyed in 1955 by P. K. Russell.

The following field notes are those of the completion survey of the subdivisional lines of Township 40 North, Range 11 West, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated April 14, 1964.

Only the true line bearings and horizontal distances are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 36°49'02.9" North and Longitude 112°25'06.8" West, as calculated from a tie to U. S. Coast and Geodetic Survey triangulation station RED BLUFF.

The mean magnetic declination was found to be 16° East.

Survey of the Subdivisional Lines
Township 40 North, Range 11 West

Beginning at the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

N. 0°01' W., bet. secs. 35 and 36.

Over rolling land, through scattered greasewood, yellow brush, Spanish bayonet and cactus.

.50	Small draw, drains N. 30° W.
4.40	Wash, 20 lks. wide, 6 ins. deep, drains N. 75° W.
12.30	Spur, slopes W.
18.00	Draw, 30 lks. wide, 6 ins. deep, drains N. 40° W.
37.40	Small draw, drains N. 20° W.
40.00	Point for the ¼ sec. cor. of secs. 35 and 36.

Set the iron post 22 ins. in the ground, cap mkd.

T40N R11W
¼
S35 | S36
1965

from which

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

2

2.

CHAINS		
	<p>A pond 4.00 chs. by 4.00 chs. bears S. 48°34' W., 32.60 chs. dist.</p> <p>Raise a mound of stones W. of the cor.</p>	
41.00	Enter wash area, drains N.	
47.90	Fence, bears S. 35° W. and N. 35° E. for 4.00 chs., thence bears N. 15° W.	
62.50	Same fence, bears S. 15° E. and N. 15° W.	
70.30	Small wash, drains S. 20° W.	
77.60	Fence, bears N. 20° E. and S. 20° W.	
80.00	Point for the cor. of secs. 25, 26, 35 and 36.	
	<p>Set the iron post 10 ins. in the ground, raise a mound of stones to top, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{S26}{S35} \frac{S25}{S36}$ 1965</p> <p>from which</p> <p style="text-align: center;">A fenced pond bears S. 15°36' W., 12.42 chs. dist.</p> <p>Land, south one-half mile rolling, north one-half mile nearly level. Soil, rocky. Timber, none. Undergrowth, yellow brush, greasewood, Spanish bayonet and cactus.</p>	
	<p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p> <p>S. 89°55' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land, through blackbrush, grass and cactus.</p>	
19.90	Small draw, drains S.	
21.70	Track road, bears SE. and NW.	
39.99	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.	
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4} \frac{S25}{S36}$ 1965</p> <p>Raise a mound of stones N. of the cor.</p>	
58.50	Rocky draw, drains S. 15° W. for 3.50 chs. to main wash draining W.	

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS		
68.30	Rocky point projects S.; desc. along steep and ledge W. slope.	
76.00	N. edge of curve in wash, drains SW. from SE.	
79.44	Fence, bears N. 15° E. and S. 15° W.	
79.98	The cor. of secs. 25, 26, 35 and 36.	
	Land, east one-half mile rolling, west one-half mile broken.	
	Soil, rocky.	
	Timber, none.	
	Undergrowth, yellow brush, Spanish bayonet and cactus.	
	N. 0°01' W., bet. secs. 25 and 26.	
	Over steep mountainous land.	
1.40	Low spur, slopes S. 70° W.	
4.00	Rocky draw, drains W. from NE.; asc. over broken SW. slope.	
23.00	SW. rim of mesa, bears S. 30° E. and N. 10° W.; thence over mesa top.	
34.20	NW. rim of same mesa, bears N. 50° E. and S. 50° W.; desc. NW. slope.	
40.00	Point for the ¼ sec. cor. of secs. 25 and 26.	
	Set the iron post 12 ins. in the ground, mound of stones to top, cap mkd.	
	T40N R11W ¼ S26 S25 1965	
48.70	Wash, 5.00 chs. wide, 2 ft. deep, drains E. Track road in bottom of wash.	
65.40	Small draw, drains NE.	
67.80	Small draw, drains E.; asc. over S. slope.	
72.50	Low spur, slopes N. 80° E.; desc. NE. slope.	
77.00	Rocky wash, 30 lks. wide, 1 ft. deep, drains N. 80° E.; asc. S. slope.	
80.00	Point for the cor. of secs. 23, 24, 25 and 26.	
	Set the iron post over an X chiseled on a limestone ledge, mound of stones to top, cap mkd.	
	T40N R11W S23 S24 S26 S25 1965	

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

4

4.

CHAINS	
	<p>from which</p> <p>A pond, 3.50 chs. diam., bears S. 41°13' E., 29.48 chs. dist.</p> <p>Land, steep and broken. Soil, shallow gravelly loam. Timber, none. Undergrowth, scattered yellow brush, greasewood and cactus.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p> <p>S. 89°54' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land.</p>
10.80	Small draw, drains SW.; thence curves to NW.
24.30	Track road, bears SE. and NW.
27.20	Small draw, drains NW.
36.60	Wash, 15 lks. wide, 1 ft. deep, drains N. 15° E. to a small stock pond.
40.00	Point for the ¼ sec. cor. of secs. 24 and 25.
	Set the iron post 24 ins. in the ground, cap mkd.
	<p>T40N R11W</p> <p>¼ $\frac{S24}{S25}$</p> <p>1965</p>
	<p>from which</p> <p>A small catch pond bears N. 37° E., 8.80 chs. dist.</p> <p>Build a mound of stones N. of the cor.</p>
40.50	Track road, bears NE. and SW.
60.20	W. rim of mesa, bears S. 20° E. and N. 20° W.; desc. over steep W. slope.
68.60	Track road, bears S. 20° E. and N. 20° W.; thence over rolling land.
68.90	Wash, 20 lks. wide, 1 ft. deep, drains N. 20° W.
80.00	The cor. of secs. 23, 24, 25 and 26.
	<p>Land, rolling and broken. Soil, shallow loam. Timber, none. Undergrowth, scattered blackbrush, grasses and cactus.</p> <hr/>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS	
	N. 0°01' W., bet. secs. 23 and 24.
	Over rolling and broken land, through scattered undergrowth.
1.40	Low spur, projects S. 70° E. for 2.00 chs.
5.70	Small draw, drains S. 60° E.
9.60	Spur, projects SE. for 4.00 chs.
18.80	Wash, 30 lks. wide, 1 ft. deep, drains N. 70° E.
38.30	Spur, slopes N. 40° E.; desc. NW. slope.
40.00	Point for the ¼ sec. cor. of secs. 23 and 24.
	Set the iron post 22 ins. in the ground, cap mkd.
	T40N R11W ½ S23 S24 1965
	Build a mound with stones W. of the cor.
44.80	Small spur, slopes N. 30° W.
56.50	Wash, 120 lks. wide, with 8-ft. banks, drains N. 75° W.
57.00	Track road, bears N. 75° W. and SE. curving to S.
62.40	Rim of mesa, bears SE. and W. for 8.00 chs., thence N.
73.30	Rocky draw, drains W. from SE.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W S14 S13 S23 S24 1965
	Land, steep and mountainous. Soil, shallow loam. Timber, none. Undergrowth, scattered blackbrush, buckbrush and cactus.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.
	S. 89°51' W., bet. secs. 13 and 24.
	Over gently rolling land, through scattered undergrowth.
25.80	Small draw, drains N., curving to NE.
40.00	Point for the ¼ sec. cor. of secs. 13 and 24.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

6

6.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4}$ $\frac{S13}{S24}$ 1965</p> <p>Build a mound with stones N. of the corner.</p>
40.40	Track road, bears SE. and NW.
80.00	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, gently rolling. Soil, shallow, gravelly loam. Timber, none. Undergrowth, moderate blackbrush, scattered yellow brush and cactus.</p> <hr/> <p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over rolling land, through scattered undergrowth.</p>
1.60	Head of small draw, drains W.
14.40	Bladed cow trail, bears E. and N. 80° W.
16.70	Small draw, drains N. 60° W.
30.40	Wash, 10 lks. wide, 1 ft. deep, drains irregularly W. from SE.
37.90	Bladed cow trail, bears E. and NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4}$ S14 S13 1965</p> <p>Build a mound with stones W. of the corner.</p>
56.00	Wash, 15 lks. wide, 1 ft. deep, drains N. 80° W.
67.50	Track road, bears E. and W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4}$ S11 S12 S14 S13 1965</p> <p>Build a mound of stones W. of the cor.</p> <p>Land, gently rolling. Soil, shallow, gravelly loam. Timber, none. Undergrowth, dense blackbrush, scattered grass and cactus.</p> <hr/>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

7.

CHAINS	
	<p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p> <p>S. 89°51' W., bet. secs. 12 and 13.</p> <p>Over broken land, through scattered undergrowth.</p> <p>Asc. over NE. slope.</p>
25.00	East rim of mesa, bears SE. and N. 20° W.; thence over nearly level mesa top.
35.30	West rim of same mesa, bears irregularly N. and S.; desc. steep and ledgy W. slope.
40.00	Point for the ¼ sec. cor. of secs. 12 and 13.
	<p>Set the iron post 20 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W ¼ $\frac{S12}{S13}$ 1965</p> <p>Build a mound of stones N. of the cor.</p>
40.50	Wash, 40 lks. wide, 3 ft. deep, drains N.; asc. over ledgy NE. slope.
60.00	East rim of mesa, bears SE. and NW.; thence over rolling mesa top.
61.70	Track road, bears NE. and SW.
70.20	Ledgy draw, drains N. for 6.00 chs., thence drains NE.
80.00	The cor. of secs. 11, 12, 13 and 14.
	<p>Land, rolling and broken. Soil, shallow loam. Timber, none. Undergrowth, blackbrush, grass Brigham tea and cactus.</p> <hr/> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Desc. gentle N. slope, through dense undergrowth.</p>
1.60	Small draw, drains N. 80° E. from SW.; asc. S. slope.
5.20	Small draw, drains SE. for 3.00 chs., thence drains N. 80° E.
40.00	Point for the ¼ sec. cor. of secs. 11 and 12.
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W ¼ S11 S12 1965</p> <p>Build a mound of stones W. of the cor.</p>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

8

8.

CHAINS	
44.50	Head of small draw, drains E., curving to NE.
80.00	Point for the cor. of secs. 1, 2, 11 and 12.
	Set the iron post 24 ins. in the ground, cap mkd.
	T40N R11W $\frac{S\ 2}{S11} \frac{S\ 1}{S12}$ 1965
	Build a mound with stones W. of the cor.
	Land, gently rolling. Soil, rocky clay loam. Timber, none. Undergrowth, dense blackbrush, scattered grass, Brigham tea and cactus.
	<hr/> From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.
	S. 89°49' W., bet. secs. 1 and 12.
	Over rolling land, through moderate undergrowth; asc. E. slope.
3.00	Crest of small ridge, bears N. and S.; desc. W. slope.
20.10	Sunshine Trail, a bladed road, bears N. and S.
24.09	Fence, bears N. 55° W. and S. 55° E. for 1.00 chain, thence bears S.
39.00	Wash, 15 lks. wide, 2 ft. deep, drains NW.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.
	Set the iron post 22 ins. in the ground, cap mkd.
	T40N R11W $\frac{1}{4} \frac{S\ 1}{S12}$ 1965
	Build a mound with stones N. of the corner.
44.50	Small draw, drains N. from SW.
51.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.
59.34	Fence, bears N. 70° E. and S. 70° W.; asc. over NE. slope.
69.70	Draw, drains NE.; asc. steep E. slope.
76.50	E. rim of West Mesa, bears SE. and N.
79.94	The cor. of secs. 1, 2, 11 and 12.
	Land, east one-half rolling, west one-half broken. Soil, rocky clay loam. Timber, none. Undergrowth, moderate blackbrush, scattered grass, Brigham tea and cactus.

CHAINS	
	<p>N. 0°01' W., bet. secs. 1 and 2.</p>
	<p>Over nearly level mesa top, through moderate undergrowth.</p>
3.00	<p>Mesa rim, bears NW. and E. 4.00 chs., thence S.; desc. over broken NE. slope.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2.</p>
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T40N R11W $\frac{1}{4}$ S 2 S 1 1965</p>
47.70	<p>Wash, 10 lks. wide, 1 ft. deep, drains E. for 3.50 chs., thence drains N.</p>
65.70	<p>Low spur, projects E. 6.00 chs.</p>
72.50	<p>Wash, 20 lks. wide, 1 ft. deep, drains irregularly E.; asc. over S. slope.</p>
75.95	<p>Intersect the S. bdy. of T. 41 N., R. 11 W., the Tenth Standard Parallel North.</p>
	<p>Point for the closing cor. of secs. 1 and 2.</p>
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T41N R11W S36 <u>S 2 S 1</u> T40N R11W C C 1965</p>
	<p>Build a mound of stones S. of the cor.</p>
	<p>From the closing cor. the standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 41 N., R. 11 W., bears East 13.09 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p>
	<p>Land, broken and rolling. Soil, shallow loam. Timber, none. Undergrowth, scattered blackbrush and cactus.</p>
	<hr/> <p>The point for the $\frac{1}{4}$ sec. cor. of sec. 1 is on the N. bdy. at mid-point bet. the closing corners.</p>
	<p>Set the iron post 22 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">$\frac{1}{4}$ S 1 T40N R11W 1965</p>
	<p>Build a mound of stones S. of the cor.</p>
	<p>From this cor. the Standard Township cor. of T. 41 N., Rs. 10 and 11 W., bears East 13.12 chs. dist., monumented by an iron post 3 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

10

10.

CHAINS	
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the township, monumented by an iron post 2 ins. diam. set, mkd. and witnessed as described in the official record of the 1939 survey.</p>
	<p>N. 0°01' W., bet. secs. 34 and 35.</p>
	<p>Over rolling land through moderate juniper trees.</p>
1.10	<p>Small draw, drains E.</p>
32.40	<p>Wash, 15 lks. wide, 1 ft. deep, drains E. for 3 chs., thence NE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 34 and 35.</p>
	<p>Set the iron post 24 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T40N R11W</p>
	<p style="text-align: center;">1/4 S34 S35</p>
	<p style="text-align: center;">1965</p>
	<p>Build a mound with stones W. of the corner.</p>
41.90	<p>Wash, 10 lks. wide, 1 ft. deep, drains E.</p>
55.90	<p>Road, bears NE. and SW.</p>
67.20	<p>Wash, 15 lks. wide, 1 ft. deep, drains E. for 5.00 chs., thence circles to NW.</p>
75.00	<p>Same wash, drains N. 20° W., curving E.; asc. SW. slope.</p>
80.00	<p>Point for the cor. of secs. 26, 27, 34 and 35.</p>
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T40N R11W</p>
	<p style="text-align: center;">S27 S26</p>
	<p style="text-align: center;">S34 S35</p>
	<p style="text-align: center;">1965</p>
	<p>Land, rolling and broken.</p>
	<p>Soil, shallow, gravelly loam.</p>
	<p>Timber, scattered juniper and pinon.</p>
	<p>Undergrowth, scattered grass.</p>
	<hr/>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p>
	<p>West, bet. secs. 26 and 35.</p>
	<p>Over rolling land; asc. SE. slope.</p>
1.70	<p>Spur, slopes W.; desc. W. slope.</p>
9.00	<p>East edge of wash area, drains N. 20° E. from S. 20° E.</p>
11.40	<p>Road, bears same as wash.</p>
14.20	<p>West edge of same wash area.</p>
23.40	<p>Spur, projects N. 80° E. for 3.50 chs.</p>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

11.

CHAINS	
39.60	Low ridge, bears S. 60° E. and N. 60° W.; desc. SW. slope.
40.01	Point for the ¼ sec. cor. of secs. 26 and 35. Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W $\frac{1}{4} \frac{S26}{S35}$ 1965
	Cor. falls on ledgy SW. slope.
46.70	Saddle of low ridge, bearing NE. and SW.; asc. E. slope.
65.40	Track road, bears S. and N. 20° W.
75.00	Spur, slopes N.; desc. W. slope.
80.02	The cor. of secs. 26, 27, 34 and 35.
	Land, steep and rolling. Soil, shallow and rocky. Timber, scattered juniper. Undergrowth, scattered blackbrush, Brigham tea, buckbrush and cactus.
	S. 89°56' W., bet. secs. 27 and 34.
	Over rolling land, through scattered juniper and pinon.
3.90	Wash, 30 lks. wide, 1 ft. deep, drains N. 20° W., circling to E.; asc. SE. slope.
28.60	Top of small limestone hill; desc. W. slope.
34.10	Track road, bears irregularly SW. and N.
37.50	Small draw, drains S. 20° E.
40.01	Point for the ¼ sec. cor. of secs. 27 and 34.
	Set the iron post 18 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W $\frac{1}{4} \frac{S27}{S34}$ 1965
43.90	Limestone ledge, bears N. 50° E. and S. 50° W.
67.20	A cave, 20 ft. by 35 ft., 8 ft. high, bears S., 40 lks. distant.
75.10	Track road, in bottom of wash, 20 lks. wide, 1 ft. deep, drains N. from SW.
80.02	The cor. of secs. 27, 28, 33 and 34, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

12

12.

CHAINS

Land, steep and rolling.
Soil, shallow loam.
Timber, scattered juniper and pinon.
Undergrowth, blackbrush, Brigham tea, buckbrush and cactus.

From the cor. of secs. 26, 27, 34 and 35.

N. 0°01' W., bet. secs. 26 and 27.

Over rolling and broken land.

- 1.10 Spur, projects NW. for 1 chain; desc. steep N. slope.
 - 4.40 Wash, 30 lks. wide, 1 ft. deep, drains E. for 4.00 chs., thence NE.
 - 12.60 Wash, 10 lks. wide, 1 ft. deep, drains SE. from W.
 - 21.60 Small draw, drains E.
 - 31.40 Bladed road, bears S. 20° E. and NW.
 - 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
- Set the iron post 16 ins. in the ground, mound with stones to top, cap mkd.

T40N R11W
 $\frac{1}{4}$
S27 | S26
1965

Cor. falls on S. slope.

- 41.20 Limestone outcrop, bears SE. and NW.
 - 54.60 Shallow wash, drains S. 75° E.; asc. S. slope.
 - 60.00 Ridge, bears NW. and E. for 4.00 chs., thence circling to N.
 - 65.80 Draw, drains E. for 4.00 chs., thence circles to N.; asc. S. slope.
 - 73.00 Top of asc.; desc. NE. slope.
 - 80.00 Point for the cor. of secs. 22, 23, 26 and 27.
- Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T40N R11W
S22 | S23
S27 | S26
1965

Land, rolling.
Soil, shallow, gravelly loam.
Timber, none.
Undergrowth, blackbrush, buckbrush and cactus.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

13.

CHAINS		
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>West, bet. secs. 23 and 26.</p> <p>Over rolling and broken land.</p>	
9.20	Wash, 10 lks. wide, 1 ft. deep, drains S. 50° E.; asc. E. slope.	
20.40	Limestone outcrop 20 ft. high, bears N. and S.; desc. W. slope.	
30.80	Small draw, drains N. 60° W.	
35.10	Small rock outcrop, projects N. for 40 lks.	
40.03	<p>Point for the ¼ sec. cor. of secs. 23 and 26.</p> <p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R11W ¼ $\frac{S23}{S26}$ 1965</p>	
56.00	Wash, ledgy and deep, with bottom 40 lks. wide, 2 ft. deep, drains N. for about 10.00 chs., thence drains NE.	
63.10	Ridge, bears S. and N. 20° W.	
68.20	Shallow wash, drains irregularly N.	
74.30	Spur, projects N. 35° E. for 10.00 chs.	
77.00	Head of small draw, drains N. 20° E.	
80.06	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, rolling and broken. Soil, gravelly clay loam. Timber, none. Undergrowth, blackbrush, Brigham tea and cactus.</p> <hr/> <p>S. 89°55' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through scattered undergrowth; asc. NE. slope.</p>	
2.00	Ridge, bears S. and NW.; desc. W. slope.	
19.90	Wash, 1.00 chain wide, 1 ft. deep, drains N. 15° E.	
20.30	Track road in same wash, bears irregularly N. and S.	
31.80	Low spur, slopes N. 75° E.	
40.02	<p>Point for the ¼ sec. cor. of secs. 22 and 27.</p> <p>Set the iron post 19 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W ¼ $\frac{S22}{S27}$ 1965</p>	

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

14

CHAINS	
	Build a mound of stones N. of the cor.
43.00	Track road, bears NE. and SW.; asc. NE. slope.
56.00	Rocky draw, drains NW.
67.90	Small draw, drains N. 20° E.
69.80	West rim of a low mesa, bears S. 30° W. and N.; desc. steep W. slope.
76.70	Small draw, drains N. 10° W.
80.04	The cor. of secs. 21, 22, 27 and 28, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.
	Land, rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, blackbrush, Brigham tea and cactus.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 0°01' W., bet. secs. 22 and 23.
	Over rolling land; desc. NE. slope.
6.20	Spur, slopes N. 70° E.
9.30	Small draw, drains N. 60° E.; asc. over SE. slope.
26.00	Low spur, slopes E.; desc. over NE. slope.
34.00	Shallow wash, drains N. 40° W.; asc. SW slope.
34.50	Fence, bears NW. and SE. for 1.50 chs.; thence bears S.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23 falls on a SW. slope at the base of a 10-ft. ledge.
	Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W ¼ S22 S23 1965
	from which
	A metal stock tank bears N. 68°40' W., 19.10 chs. distant.
40.10	Limestone ledge, bears S. 20° E. and N. 20° W.
42.50	Spur, slopes W.; desc. NW. slope.
53.20	Wash, 10 lks. wide, 1 ft. deep, drains N 30° E.
56.50	Track road, bears NE. and SW.
57.40	Wash, 40 lks. wide, 3 ft. deep, drains NE.

CHAINS	
62.70	Begin asc. over SE. slope.
68.00	Small draw, drains S. 30° E.
75.00	Limestone outcrop, bears E. and W.; desc. steep N. slope.
79.00	Wash, 20 lks. wide, 1 ft. deep, drains E.; asc. S. slope.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post over an X chiseled on a limestone outcrop, mound with stones to top, cap mkd.
	<p>T40N R11W $\frac{S15}{S22} \frac{S14}{S23}$ 1965</p>
	<p>Land, steep and broken. Soil, shallow clay loam. Timber, none. Undergrowth, blackbrush, greasewood and cactus.</p>
	From the cor. of secs. 13, 14, 23 and 24.
	N. 89°59' W., bet. secs. 14 and 23.
0.40	West rim of mesa, bears N. and S.; desc. steep W. slope.
14.00	Wash, 50 lks. wide, 5 ft. deep, drains N. 10° W.; asc. E. slope.
16.20	Track road, bears S. 10° E. and N. 10° W.
32.50	Ridge, bears NE. and SW.; desc. over broken W. slope.
38.40	Small spur, slopes SW.; desc. NW. slope.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.
	<p>T40N R11W $\frac{1}{4} \frac{S14}{S23}$ 1965</p>
53.00	Track road, bears NE. and SW.
57.30	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° E.
60.00	Wash, 40 lks. wide, 3 ft. deep, drains N. 35° E.; asc. E. slope.
64.00	Track road, bears N. and S.
71.40	Wash, 50 lks. wide, 1 ft. deep, drains N. 30° E.
80.02	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, steep and rolling. Soil, clay loam. Timber, none. Undergrowth, blackbrush, yellowbrush, greasewood and cactus.</p>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

16

16.

CHAINS	
	S. 89°56' W., bet. secs. 15 and 22. Over rolling land.
4.20	Wash, 30 lks. wide, 2 ft. deep, drains irregularly E. from N. 80° W.
18.00	Same wash, drains N. for 6 chs. thence drains irregularly East.
32.10	Small draw, drains S.
37.30	Fence, bears N. and S.
38.00	Underground water line, bears SE. and NW.
39.50	Wash, 50 lks. wide, 1 ft. deep, drains S. 50° E.
40.05	Point for the ¼ sec. cor. of secs. 15 and 22. Set the iron post 20 ins. in the ground, cap mkd. T40N R11W ¼ $\frac{S15}{S22}$ 1965 Build a mound of stones N. of the cor.
40.80	Water line, bears S. 15° E. and NW.; asc. E. slope.
50.70	Spur, projects NE. for 30 lks.
73.60	Spur, projects E. for 3 chs. from SW.
80.10	The cor. of secs. 15, 16, 21, and 22, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey. Land, rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, blackbrush, grass and cactus.
	From the cor. of secs. 14, 15, 22 and 23. N. 0°01' W., bet. secs. 14 and 15. Over rolling land; asc. S. slope.
5.70	Track road, bears S. 40° E. and N. 50° W.
16.00	S. rim of mesa, bears E. and irregularly W.
17.20	Fence, bears N. 30° E. and S. 30° W. to rim of mesa.
29.80	Shallow draw, drains E.
39.90	Cow trail, bears E. and W.
40.00	Point for the ¼ sec. cor. of secs. 14 and 15. Set the iron post 16 ins. in the ground, collar of stones to top, cap mkd.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS		
	<p style="text-align: center;">T40N R11W $\frac{1}{4}$ S15 S14 1965</p> <p>Build a mound of stones W. of the cor. Cor. falls on a steep N. slope.</p> <p>58.40 Top of low knoll.</p> <p>64.40 Wash, 30 lks. wide, 1 ft. deep, drains irregularly E.</p> <p>80.00 Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p>	
	<p style="text-align: center;">T40N R11W S10 S11 S15 S14 1965</p> <p>Build a mound of stones W. of the cor.</p> <p>Land, steep and rolling. Soil, shallow clay loam. Timber, none. Undergrowth, blackbrush, grass and cactus.</p>	
	<hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>West, bet. secs. 11 and 14.</p> <p>Over rolling and broken land.</p> <p>1.00 Small draw, drains NE.</p> <p>8.30 Track road, bears N. and S. for 4.00 chs. thence bears West.</p> <p>25.00 E. rim of mesa, bears N. and S.</p> <p>31.00 E. rim of canyon 50 ft. deep, bears N. and S.; desc. steep W. slope.</p> <p>32.80 Wash in canyon bottom, 50 lks. wide, 4 ft. deep, drains N.; asc. E. slope.</p> <p>36.00 W. rim of same canyon, bears N. and S.</p> <p>39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.</p>	
	<p style="text-align: center;">T40N R11W $\frac{1}{4}$ $\frac{S11}{S14}$ 1965</p> <p>45.80 Head of small draw, drains N., circling to NE.</p>	

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

18

18.

CHAINS

- 72.80 Small draw, drains N., circling to NE.
- 77.90 Small draw, drains NE.
- 79.98 The cor. of secs. 10, 11, 14 and 15.

Land, east half rolling and broken, west half gently rolling.
Soil, gravelly clay loam.
Timber, none.
Undergrowth, blackbrush, grass and cactus.

- S. 89°50' W., bet. secs. 10 and 15.

Over rolling and broken land.
- 9.60 E. rim of mesa, bears SE. and NE.; thence over mesa top.
- 20.10 Draw, drains NE.
- 38.30 NW. rim of mesa, bears NE. and SW.; desc. steep NW. slope.
- 40.07 Point for the ¼ sec. cor. of secs. 10 and 15.

Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.

T40N R11W
¼ $\frac{S10}{S15}$
1965
- 49.40 Spur from mesa, slopes irregularly N.
- 58.70 Track road, bears N. and S.
- 59.80 Fence, bears N. and S.
- 63.40 Wash, 15 lks. wide, 1 ft. deep, drains NE.
- 70.80 Low spur, slopes S.
- 76.80 Shallow draw, drains S. 30° E.
- 80.14 The cor. of secs. 9, 10, 15 and 16, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.

Land, rolling and broken.
Soil, shallow clay loam.
Timber, none.
Undergrowth, blackbrush and cactus.

- From the cor. of secs. 10, 11, 14 and 15.

N. 0°01' W., bet. secs. 10 and 11.

Over rolling land, with drainage to the E.
- 5.90 Wash, 10 lks. wide, 1 ft. deep, drains E.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS	
20.00	Spur, slopes E.
30.60	Small draw, drains N. 55° E.
36.60	Wash, 15 lks. wide, 1 ft. deep, drains N. 40° E.
40.00	Point for the ¼ sec. cor. of secs. 10 and 11.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W ¼ S10 S11 1965
44.30	Small draw, drains E.
52.50	Wash, 10 lks. wide, 1 ft. deep, drains E.
67.40	Wash, 15 lks. wide, 1 ft. deep, drains E.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W S 3 S 2 S10 S11 1965
	Land, rolling. Soil, shallow clay loam. Timber, none. Undergrowth, blackbrush, grass and cactus.
	<hr/> From the cor. of secs. 1, 2, 11 and 12.
	S. 89°56' W., bet. secs. 2 and 11.
	Over rolling land, on top of West Mesa.
30.00	W. rim of West Mesa, bears irregularly N. and S.; desc. steep SW. slope.
39.98	Point for the ¼ sec. cor. of secs. 2 and 11.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W ¼ $\frac{S 2}{S 11}$ 1965
	Thence by triangulation, topography estimated.
41.00	Deep draw, 40 lks. wide, drains N. 35° W.
55.00	Dutchman Draw, drains irregularly N.
63.00	Draw, drains N. into Dutchman Draw from SW.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

20

20.

CHAINS		
70.00	Cross N. slope of low hill.	
79.00	Wash, 30 lks. wide, 2 ft. deep, drains SE.	
79.96	The cor. of secs. 2, 3, 10 and 11; end of triangulation.	
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, blackbrush, yellow brush, buckbrush and cactus.	
	S. 89°55' W., bet. secs. 3 and 10.	
	Over rolling land.	
8.20	Wash, 60 lks. wide, 2 ft. deep, drains E. circling SE.	
36.70	Crest of narrow ridge, bears N. and S.; desc. W. slope.	
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.	
	Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.	
	T40N R11W $\frac{1}{4}$ $\frac{S\ 3}{S10}$ 1965	
40.70	Small draw, drains N. 20° W.	
48.80	Limestone outcrop, bears S. 15° E. and N. 15° W.	
62.50	Head of deep, narrow draw, drains N.	
78.80	Wash, 60 lks. wide, 2 ft. deep, drains W. for 10.00 chs., thence circles to N.	
80.12	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.	
	Land, rolling. Soil, shallow clay loam. Timber, none. Undergrowth, blackbrush, buckbrush and cactus.	
	From the cor. of secs. 2, 3, 10 and 11.	
	N. 0°01' W., bet. secs. 2 and 3.	
	Over rolling land.	
1.70	Wash, 40 lks. wide, 2 ft. deep, drains S. 60° E.	
16.50	Shallow wash, drains N. 60° E.	
19.80	Low spur, slopes NE.	
22.90	Shallow draw, drains NE.	
24.40	Shallow draw, drains E. for 2.00 chs., thence drains NE.	

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS	
38.90	Wash, 20 lks. wide, 1 ft. deep, drains irregularly SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T40N R11W $\frac{1}{4}$ S 3 S 2 1965</p>
44.00	Low spur, slopes E.
50.80	Wash, 10 lks. wide, 1 ft. deep, drains E.
71.50	Spur, slopes E.
76.04	Intersect the S. bdy. of T. 41 N., R. 11 W., the Tenth Standard Parallel North.
	Point for the closing cor. of secs. 2 and 3.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	<p style="text-align: center;">T41N R11W S35 <hr style="width: 50%; margin: 0 auto;"/> S 3 S 2 T40N R11W C C 1965</p>
	<p>From the closing corner the Standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 41 N., R. 11 W., bears East 12.99 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p>
	<p>Land, rolling. Soil, shallow clay loam. Timber, none. Undergrowth, blackbrush, grass and cactus.</p>
	<hr/> <p>The point for the $\frac{1}{4}$ sec. cor. of sec. 2 is on the N. bdy. at mid-point bet. the closing cors.</p>
	<p>Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">$\frac{1}{4}$ S 2 <hr style="width: 50%; margin: 0 auto;"/> T40N R11W 1965</p>
	<p>From this cor. the Standard cor. of secs. 35 and 36, T. 41 N., R. 11 W., bears East, 13.04 chs. dist., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.</p>
	<hr/> <p>The point for the $\frac{1}{4}$ sec. cor. of sec. 3 is on the N. bdy. at mid-point bet. the closing cors.</p>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

$\frac{1}{4}$ S 3
 T40N R11W
 1965

From this cor. the Standard cor. of secs. 34 and 35, T. 41 N., R. 11 W., bears East, 13.04 chs. dist., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

from which

Triangulation station RED BLUFF bears N. 0°25' E., 29.05 chs. dist.,

The S. end of a Fish and Game Department concrete water tank bears N. 57°26' W., 12.54 chs. dist.

N. 0°03' W., bet. secs. 32 and 33.

Over mountainous land; asc. over S. slope through a railed area.

0.80 Fence, bears NE. and SW.

5.40 Leave railed area; enter dense juniper and pinon trees.

6.20 Track road, bears NE. and SW.

29.10 ^{selected} Point/for the witness $\frac{1}{4}$ sec. cor. of secs. 32 and 33; falls on N. end of top of Seegmuller Mountain.

Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.

T40N R11W
 $\frac{1}{4}$
 S32 | S33
 W C
 1965

Desc. steep N. slope; thence by triangulation.

40.00 True point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33 falls in an insecure place on steep and ledgy N. slope, where the monument cannot be perpetuated.

46.00 Head of large draw, drains N. 20° E.; asc. over steep and broken SE. slope.

79.00 ^{selected} Point/for the witness cor. of secs. 28, 29, 32 and 33; end of triangulation.

Set the iron post 22 ins. in the ground, cap mkd.

T40N R11W
 $\frac{1}{4}$
 S29 | S28
 S32 | S33
 W C
 1965

CHAINS		
	Build a mound of stones W. of the cor.	
80.00	True point for the cor. of secs. 28, 29, 32 and 33 falls in an insecure place on the N. edge of a draw draining S. 80° E.	
	Land, mountainous. Soil, shallow clay loam. Timber, moderate juniper and pinon. Undergrowth, scattered grass and blackbrush.	
	From the cor. of secs. 27, 28, 33 and 34, previously described.	
	S. 89°55' W., bet. secs. 28 and 33.	
	Over mountainous land; asc. steep E. slope.	
37.00	Ridge, bears N. 30° E. and S. 30° W.; desc. over steep NW. slope.	
40.00	Point for the ¼ sec. cor. of secs. 28 and 33.	
	Set the iron post 15 ins. in the ground, mound with stones to top, cap mkd.	
	<p style="text-align: center;">T40N R11W ¼ $\frac{S28}{S33}$ 1965</p>	
	Desc. steep NW. slope; by triangulation, topography estimated.	
56.50	Wash, 50 lks. wide, 1 ft. deep, drains NE. from S.; asc. E. slope.	
72.00	Small spur, projects SE. for 1.00 chain; asc. SE. slope.	
80.00	True point for the cor. of secs. 28, 29, 32 and 33; end of triangulation.	
	Land, mountainous. Soil, shallow clay loam. Timber, moderate juniper and pinon. Undergrowth, buckbrush, yellow brush, blackbrush, Brigham tea and cactus.	
	N. 0°03' W., bet. secs. 28 and 29.	
	Over mountainous land; asc. steep NE. slope.	
0.50	Deep draw, drains S. 80° E.; asc. steep SE. slope.	
11.30	Ridge, bears N. 15° E. and S. 15° W.	
40.00	Point for the ¼ sec. cor. of secs. 28 and 29.	
	Set the iron post 20 ins. in the ground, cap mkd.	
	<p style="text-align: center;">T40N R11W ¼ $\frac{S29}{S28}$ 1965</p>	
	from which	

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

24

24.

CHAINS

Indian picture writing on large boulders bears
N. 9°50' W., 7.60 chs. dist.

Build a mound of stones W. of the cor.

45.80 Same ridge, bears S. 10° E. and N. 10° W.; asc. over SE.
slope.

80.00 Point for the cor. of secs. 20, 21, 28 and 29.

Set the iron post 20 ins. in the ground, collar of
stones to top, cap mkd.

T40N R11W
S20 | S21
S29 | S28
1965

from which

A juniper, 5 ins. diam., bears S. 37° W., 33 lks.
dist., mkd. T40N R11W S29 B T

A juniper, 8 ins. diam., bears N. 4°45' W.,
48 lks. dist., mkd. T40N R11W S20 B T

Build a mound of stones W. of the cor.

Land, mountainous.

Soil, gravelly clay loam.

Timber, moderate juniper and pinon.

Undergrowth, blackbrush, sagebrush, Brigham tea and
cactus.

From the cor. of secs. 21, 22, 27 and 28, previously
described.

S. 89°55' W., bet. secs. 21 and 28.

Over mountainous land; asc. E. slope.

0.30 Low spur, slopes N.; desc. W. slope.

5.00 Wash, 100 lks. wide, 2 ft. deep with ledgy bottom,
drains N. circling to NE.; asc. NE. slope.

18.90 Limestone spur, slopes SE.

27.60 Deep draw, drains S. 30° E.

36.90 Small draw, drains S. 60° E.

39.98 Point for the ¼ sec. cor. of secs. 21 and 28.

Set the iron post 6 ins. in the ground, mound with
stones to top, cap mkd.

T40N R11W
¼ S21
S28
1965

Asc. SE. slope.

CHAINS	
41.30	Head of rocky draw, drains S., circling to S. 70° E.
49.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 40° E.
79.96	The cor. of secs. 20, 21, 28 and 29.
	Land, mountainous. Soil, rocky clay loam. Timber, moderate to dense juniper and pinon. Undergrowth, sagebrush, blackbrush, buckbrush, Brigham tea and cactus.
	N. 0°04' W., bet. secs. 20 and 21.
	Over mountainous land; asc. SE. slope.
1.00	Top of Seegmuller Mountain, bears S. 20° W. and N. 20° W. Desc. NE. slope.
15.30	Begin steep descent over NE. slope.
39.97	Point for the ½ sec. cor. of secs. 20 and 21.
	Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W ½ S20 S21 1965
47.20	Rocky draw, drains E.
50.30	Rocky draw, drains E.; desc. SE. slope.
52.90	Spur, slopes E.; desc. NE. slope.
74.20	Draw, drains E. for 50 lks., thence drains N. 20° E.
79.94	The cor. of secs. 16, 17, 20 and 21, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.
	from which
	Seegmuller Spring bears N. 70°17' W., 17.32 chs. dist.
	Land, mountainous. Soil, shallow clay loam. Timber, moderate juniper and pinon. Undergrowth, sage, blackbrush, grass, Brigham tea and cactus.
	From the cor. of secs. 8, 9, 16 and 17, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.
	from which
	A metal water tank, 64 lks. diam., bears S. 38°05' E., 28.99 chs. dist.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

26

26.

CHAINS	
	N. 0°03' W., bet. secs. 8 and 9.
	Over rolling land.
1.50	Wash, 20 lks. wide, 2 ft. deep, drains NE.
24.70	Shallow draw, drains NW.
40.00	Point for the ¼ sec. cor. of secs. 8 and 9.
	Set the iron post 5 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W
	¼
	S 8 S 9
	1965
43.00	Limestone ledge, bears NE. and SW.
52.30	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.
74.20	Bladed road, bears N. 30° E. and S. 60° W.
77.65	Underground water line, bears N. 40° E. and S. 40° W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	Set the iron post over an X chiseled on solid rock, mound with stones to top, cap mkd.
	T40N R11W
	S 5 S 4
	S 8 S 9
	1965
	Cor. falls on a NW. slope.
	Land, rolling.
	Soil, gravelly clay loam.
	Timber, none.
	Undergrowth, blackbrush, yellow brush, grass and cactus.
	From the cor. of secs. 3, 4, 9 and 10, previously described.
	S. 89°58' W., bet. secs. 4 and 9.
	Over mountainous land.
3.60	Fence, bears S. and N. for 1 chain.
4.60	Head of small canyon, drains W.
7.60	Same canyon, drains N. from E.
20.00	Limestone outcrop, bears S. and NW.; desc. steep W. slope.
35.00	Wash, 20 lks. wide, 3 ft. deep, in bottom of canyon draining N. 20° W.
39.97	Point for the ¼ sec. cor. of secs. 4 and 9.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS	
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$ 1965</p>
67.80	Head of steep, rocky draw, drains NW.
77.70	Road, bears N. and SW.
79.94	The cor. of secs. 4, 5, 8 and 9.
	<p>Land, rolling. Soil, shallow clay loam. Timber, none. Undergrowth, blackbrush and cactus.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
14.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° E.
19.00	Spur, slopes NE.
23.60	Wash, 10 lks. wide, 1 ft. deep, drains irregularly E.
30.90	Wash, 15 lks. wide, 1 ft. deep, drains N. 15° E. circling to E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	<p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4}$ S 5 S 4 1965</p>
63.00	S. rim of mesa, bears N. 70° E. and S. 70° W.; desc. steep N. slope.
71.50	S. rim of canyon, 200 ft. deep, drains NE. from NW.
74.00	N. rim of same canyon.
76.33	Intersect the S. bdy. of T. 41 N., R. 11 W., the Tenth Standard Parallel North.
	<p>Point for the closing cor. of secs. 4 and 5.</p> <p>Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T41N R11W $\frac{1}{4}$ S 5 S 4 T40N R11W C C 1965</p>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

28

28.

CHAINS

From the closing cor. the Standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 41 N., R. 11 W., bears East, 12.91 chs. dist., monumented by an iron post 1 inch in diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

Land, rolling and broken.
Soil, gravelly clay loam.
Timber, none.
Undergrowth, blackbrush, grass and cactus.

The point for the $\frac{1}{4}$ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing cors.

Set the iron post 22 ins. in the ground, cap mkd.

 $\frac{1}{4}$ S 4
T40N R11W
1965

Build a mound of stones S. of the cor.

From this cor. the Standard cor. of secs. 33 and 34, T. 41 N., R. 11 W., bears East, 13.00 chs. dist., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the township, monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

N. 0°03' W., bet. secs. 31 and 32.

Over gently rolling land, through dense juniper and pinon.

25.00 Enter railed area, bears NE. and SW.

27.80 Track road, bears N. 70° E. and S. 70° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.

Set the iron post 24 ins. in the ground, cap mkd.

T40N R11W
 $\frac{1}{4}$
S31|S32
1965

Build a mound of stones W. of the cor.

54.50 Leave railed area, bears SE. and N. 65° W.; enter dense juniper and pinon.

57.00 Begin desc. over broken NE. slope.

80.00 Point for the cor. of secs. 29, 30, 31 and 32.

Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.

T40N R11W
S30|S29
S31|S32
1965

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS		
	<p>Land, gently rolling to broken. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, blackbrush, sagebrush, grass and cactus.</p> <hr/> <p>the true point for From/the cor. of secs. 28, 29, 32 and 33.</p> <p>N. 89°57' W., bet. secs. 29 and 32.</p> <p>Over mountainous land, through dense juniper and pinon. Asc. steep E. slope.</p>	
3.90	Ridge, bears S. 10° W. and N.; desc. broken W. slope.	
27.30	Bladed road, bears N. 30° E. and S. 30° W.	
39.97	Point for the ¼ sec. cor. of secs. 29 and 32. Set the iron post 22 ins. in the ground, cap mkd.	
	<p>T40N R11W ¼ $\frac{S29}{S32}$ 1965</p>	
	<p>Build a mound of stones N. of the cor. Thence by triangulation, topography estimated. Desc. over rolling land, N. drainage.</p>	
72.90	Bottom of a deep canyon, drains N.; asc. E. slope.	
79.94	The cor. of secs. 29, 30, 31 and 32; end of triangulation.	
	<p>Land, mountainous. Soil, rocky clay loam. Timber, moderate to dense juniper and pinon. Undergrowth, blackbrush, sagebrush, yellow brush, grass and cactus.</p> <hr/> <p>S. 89°51' W., bet. secs. 30 and 31.</p> <p>Over mountainous land, through dense juniper and pinon.</p>	
3.50	Spur, slopes N. 30° E.; desc. over NW. slope.	
6.80	E. rim of deep canyon, bears NE. and SW.	
18.80	Bottom of same deep canyon, drains irregularly N.; asc. steep E. slope.	
29.30	W. rim of same canyon, bears irregularly N. and S.; thence over rolling and broken land.	
36.80	Shallow draw, drains N. 35° W.	
40.00	Point for the ¼ sec. cor. of secs. 30 and 31. Set the iron post 20 ins. in the ground, cap mkd.	

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

30

30.

CHAINS		
	<p style="text-align: center;">T40N R11W $\frac{1}{4}$ $\frac{S30}{S31}$ 1965</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 35°30' W., 61 lks. dist., mkd. T40N R11W $\frac{1}{4}$ S31 B T</p> <p style="padding-left: 40px;">A juniper limb, 6 ins. diam., bears N. 48°30' W., 44 lks. dist., mkd. T40N R11W $\frac{1}{4}$ S30 B T</p> <p>Build a mound with stones N. of the iron post.</p>	
49.30	Bladed road, bears S. 20° E. and N.	
53.50	Leave timbered area; enter railed area.	
76.16	<p>The cor. of secs. 30 and 31 only, on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.</p> <p>Land, mountainous. Soil, rocky, clay loam. Timber, juniper and pinon. Undergrowth, blackbrush, sagebrush, grass and cactus.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over mountainous land, through moderate juniper and pinon; asc. steep SE. slope.</p>	
3.60	Spur, slopes N. 60° E.; desc. gentle N. slope.	
11.40	Desc. over steep N. slope.	
26.50	Wash, 250 lks. wide, 2 ft. deep, in bottom of a deep canyon, drains NW.; asc. SW. slope.	
28.00	Bulldozed road, bears SE. and NW.	
34.50	Draw, drains SW.	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4}$ $\frac{S30}{S29}$ 1965</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 79° E., 47 lks. dist., mkd. $\frac{1}{4}$ S29 B T</p> <p style="padding-left: 40px;">A juniper limb, 6 ins. diam., bears N. 15° W., 39 lks. dist., mkd. T40N R11W $\frac{1}{4}$ S30 B T</p> <p>Thence by triangulation, topography estimated.</p>	

CHAINS	
48.00	Spur, slopes W.
60.00	Draw, drains W.; asc. steep SW. slope.
76.50	SW. rim of mesa, bears S. 80° E. and N. 40° W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30, and end of triangulation.
	Set the iron post 20 ins. in the ground, cap mkd.
	T40N R11W S19 S20 S30 S29 1965
	from which
	A fenced stock pond, dry, bears S. 60°47' W., 35.48 chs. dist.
	Build a mound with stones W. of the corner.
	Land, mountainous. Soil, rocky clay loam. Timber, moderate to dense juniper and pinon. Undergrowth, blackbrush, sagebrush, yellow brush, grass and cactus.
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°59' W., bet. secs. 20 and 29.
	Over mountainous land, through moderate juniper and pinon.
1.40	Top of Seegmuller Mountain, bears irregularly N. and S.; desc. over W. slope.
20.30	Enter railed area, bears N. and S.
29.30	Bladed road, bears N. and S.
39.95	Point for the ¼ sec. cor. of secs. 20 and 29.
	Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W ¼ S20 S29 1965
	Set a 7-inch squared post, 6 ft. long, 24 ins. in the ground alongside the iron post as a guardstake.
53.60	Bulldozed road, bears N. 30° W. and S. 30° E. to a small stock pond 3.00 chs. dist.
56.90	Leave railed area, bears SE. and N.; enter moderate pinon and juniper.
76.20	Leave timbered area, bears irregularly N. and S.; enter railed area.
79.40	Leave railed area, bears N. and S.; enter moderate timber.

CHAINS	
79.90	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, strip of juniper and pinon bet. railed areas. Undergrowth, sagebrush, blackbrush, Brigham tea, grass and cactus.</p>
	<p>S. 89°52' W., bet. secs. 19 and 30.</p> <p>Over mountainous land, through moderate juniper and pinon.</p>
2.00	<p>W. rim of mesa, bears SE. and N.; desc. steep W. slope.</p>
34.10	<p>Wash, 20 lks. wide, 3 ft. deep, in bottom of a deep canyon, drains N. 15° E.; asc. steep E. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 30.</p> <p>Set the iron post 8 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p>T40N R11W ¼ $\frac{S19}{S30}$ 1965</p>
40.30	<p>Rocky draw, 20 lks. wide, 1 ft. deep, drains N. 65° E.</p>
57.90	<p>W. rim of canyon, bears NE. and S.</p>
67.70	<p>Enter railed area, bears N. and S.</p>
74.20	<p>Leave railed area, bears N. and S.; enter timbered area.</p>
76.02	<p>The cor. of secs. 19 and 30 only, on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, moderate juniper and pinon. Undergrowth, sagebrush, blackbrush, buckbrush, grass and cactus.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p>
	<p>N. 0°03' W., bet. secs. 19 and 20.</p>
	<p>Over rolling land, through moderate juniper and pinon.</p>
16.10	<p>E. rim of a deep canyon, bears N. 15° E. and S. 15° W.; desc. steep and rocky NW. slope.</p>
39.30	<p>Rocky draw, drains N. 50° W.; asc. broken NW. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 20.</p> <p>Set the iron post 6 ins. in the ground, mound with stones to top, cap mkd.</p>

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS	
	<p style="text-align: center;">T40N R11W $\frac{1}{4}$ S19 S20 1965</p>
77.30	<p>Wash, 30 lks. wide, 3 ft. deep, drains N. 30° E.; asc. SE. slope.</p>
80.00	<p>Point for the cor. of secs. 17, 18, 19 and 20. Set the iron post 20 ins. in the ground, cap mkd.</p>
	<p style="text-align: center;">T40N R11W S18 S17 S19 S20 1965</p>
	<p>Build a mound of stones W. of the cor. Land, mountainous. Soil, shallow clay loam with malpai boulders. Timber, juniper and pinon. Undergrowth, blackbrush, yellowbrush, buckbrush and cactus.</p>
	<p>From the cor. of secs. 16, 17, 20 and 21, previously described.</p>
	<p>N. 89°58' W., bet. secs. 17 and 20.</p>
	<p>Over mountainous land, through moderate juniper and pinon.</p>
	<p>Asc. NE. slope.</p>
8.50	<p>Spur, slopes NW.; desc. steep W. slope.</p>
16.20	<p>Wash, 50 lks. wide, 3 ft. deep, drains N.; asc. NE. slope.</p>
32.60	<p>Spur, slopes N.</p>
39.90	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd.</p>
	<p style="text-align: center;">T40N R11W $\frac{1}{4}$ $\frac{S17}{S20}$ 1965</p>
41.60	<p>Small draw, drains N. 40° E.; desc. steep W. slope.</p>
77.50	<p>Wash, 30 lks. wide, 3 ft. deep, drains N. from SW.</p>
79.80	<p>The cor. of secs. 17, 18, 19 and 20.</p>
	<p>Land, mountainous. Soil, rocky clay loam. Timber, juniper and pinon. Undergrowth, blackbrush, yellowbrush, grass and cactus.</p>

CHAINS	
	S. 89°49' W., bet. secs. 18 and 19.
	Over mountainous land, through scattered juniper and pinon.
11.00	Draw, drains S. 70° E.; asc. steep and broken E. slope.
39.40	E. rim of a mesa, bears N. 20° E. and S. 20° W.; asc. E. slope.
40.00	Point for the ¼ sec. cor. of secs. 18 and 19.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W
	¼ $\frac{S18}{S19}$
	1965
	Cor. falls on gentle E. slope.
52.40	Wash, 20 lks. wide, 1 ft. deep, drains N.
75.94	The cor. of secs. 18 and 19 only, on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.
	Land, mountainous.
	Soil, rocky clay loam.
	Timber, scattered juniper and pinon.
	Undergrowth, blackbrush, yellowbrush, sagebrush, grass and cactus.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°03' W., bet. secs. 17 and 18.
	Over rolling land.
20.90	Deep draw, drains E.
40.00	Point for the ¼ sec. cor. of secs. 17 and 18.
	Set the iron post 12 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W
	¼
	S18 S17
	1965
	from which
	Canyon Spring bears S. 71°04' E., 14.67 chs. dist.
49.30	Spur, slopes E.; desc. over steep, rolling land with a NE. drainage.
80.00	Point for the cor. of secs. 7, 8, 17 and 18.
	Set the iron post 24 ins. in the ground, cap mkd.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

CHAINS	
	<p style="text-align: center;">T40N R11W $\frac{S\ 7}{S18} \frac{S\ 8}{S17}$ 1965</p> <p>from which</p> <p>A pole corral, 2.00 chs. diam., bears S. 55°59' E., 13.05 chs. dist.</p> <p>A fence-enclosed water valve bears S. 44°33' E., 35.43 chs. dist.</p> <p>Two metal water troughs with running water bear N. 30°36' W., 28.13 chs. dist.</p> <p>Build a mound of stones W. of the cor.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered juniper and pinon. Undergrowth, blackbrush, yellowbrush, grass and cactus.</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17, previously described.</p> <p>N. 89°52' W., bet. secs. 8 and 17.</p> <p>Over rolling land.</p> <p>0.10 Wash, 10 lks. wide, 1 ft. deep, drains irregularly N. from SE.</p> <p>33.00 Wash, 30 lks. wide, 3 ft. deep, drains irregularly N.</p> <p>39.87 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p> <p>Set the iron post 24 ins. in the ground, cap mkd.</p> <p style="text-align: center;">T40N R11W $\frac{1}{4} \frac{S\ 8}{S17}$ 1965</p> <p>Build a mound with stones N. of the cor.</p> <p>52.40 Bladed road, bears SE. and NW.</p> <p>52.70 Underground water line, bears N. 20° E. and S. 20° W.</p> <p>64.20 Wash, 20 lks. wide, 3 ft. deep, drains NW.</p> <p>73.40 Road, bears S. 30° E. and N. 30° W.</p> <p>73.60 Underground water line, bears S. 25°16' E. and N. 25°16' W.</p> <p>79.74 The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, blackbrush, yellowbrush, and cactus.</p> <hr/>

CHAINS	
	S. 89°47' W., bet. secs. 7 and 18.
	Over rolling land; asc. steep E. slope.
12.00	Top of asc.; thence desc. along gentle N. slope.
28.40	Wash, 20 lks. wide, 2 ft. deep, drains irregularly N.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.
	Set the iron post 14 ins. in the ground, mound with stones to top, cap mkd.
	T40N R11W $\frac{1}{4}$ $\frac{S 7}{S 18}$ 1965
54.00	Limestone outcrop, bears SE. and NW.; desc. SW. slope.
60.00	Wash, 15 lks. wide, 1 ft. deep, drains N. 50° W.
75.84	The cor. of secs. 7 and 18 only, on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey.
	Land, rolling.
	Soil, gravelly clay loam.
	Timber, none.
	Undergrowth, blackbrush, yellowbrush, greasewood, grass and cactus.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over rolling land; desc. N. slope.
13.70	Underground water line, bears S. 30° E. and N. 70° W.
15.30	Track road, bears S. 30° E. and N. 70° W.
19.20	Wash, 20 lks. wide, 1 ft. deep, drains N. 80° W.
20.10	Wash, 30 lks. wide, 1 ft. deep, drains N. 80° W.
30.20	Wash, 10 lks. wide, 1 ft. deep, drains SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	Set the iron post 18 ins. in the ground, in a collar of stones to top, cap mkd.
	T40N R11W $\frac{1}{4}$ S 7 S 8 1965
	Build a mound of stones W. of the cor.
	Asc. S. slope.
60.30	Draw, drains N. 80° W.

CHAINS

- 64.70 Crest of limestone hill, bears E. and NW.
 - 73.70 Wash, 15 lks. wide, 1 ft. deep, drains N. 75° W.
 - 80.00 Point for the cor. of secs. 5, 6, 7 and 8.
- Set the iron post 4 ins. in the ground, mound with stones to top, cap mkd.

T40N R11W
 $\frac{S\ 6}{S\ 7} | \frac{S\ 5}{S\ 8}$
 1965

Land, rolling.
 Soil, rocky clay loam.
 Timber, none.
 Undergrowth, blackbrush, yellowbrush, buckbrush and cactus.

From the cor. of secs. 4, 5, 8 and 9.

N. 89°53' W., bet. secs. 5 and 8.

Over steep, rolling land; desc. NW. slope.

- 4.70 Draw, drains N. 30° E.
 - 11.30 Small spur, projects N. 30° E. for 3.00 chs.
 - 12.00 Wash, 20 lks. wide, 1 ft. deep, drains NE.
 - 18.30 Narrow limestone ridge, bears NE. and SW.
 - 20.40 Wash, 15 lks. wide, 2 ft. deep, drains NE.
 - 33.60 Small draw, drains NE.
 - 39.87 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
- Set the iron post 20 ins. in the ground, cap mkd.

T40N R11W
 $\frac{1}{4} \frac{S\ 5}{S\ 8}$
 1965

Build a mound of stones N. of the cor.

- 47.40 Limestone rim, facing W., bears S. 30° W. and N.; desc. steep W. slope.
 - 56.00 Wash, 20 lks. wide, 3 ft. deep, drains irregularly N.; asc. E. slope.
 - 79.74 The cor. of secs. 5, 6, 7 and 8.
- Land, rolling.
 Soil, rocky clay loam.
 Timber, none.
 Undergrowth, blackbrush, yellowbrush, Brigham tea, scattered grass and cactus.

BOOK 4762

Subdivision, T. 40 N., R. 11 W., Arizona

38

38.

CHAINS	
	S. 89°46' W., bet. secs. 6 and 7. Over rolling land; desc. W. slope.
10.90	Wash, 40 lks. wide, 2 ft. deep, drains N.; asc. E. slope.
35.00	Bulldozed road, bears S. and N. for 3.00 chs., thence bears W.
39.70	Wash, 30 lks. wide, 2 ft. deep, drains N. 20° E.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7. Set the iron post 20 ins. in the ground, cap mkd. T40N R11W S 6 ¼ — S 7 1965 Build a mound with stones N. of the cor.
43.10	Same bulldozed road, bears irregularly W. from NE.
45.10	Same road, bears irregularly E. and S. 80° W. about 15.00 chs. to end.
75.78	The cor. of secs. 6 and 7 only, on the W. bdy. of the township, monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1955 survey. Land, rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, blackbrush, yellowbrush, greasewood, Brigham tea, grass and cactus.
	From the cor. of secs. 5, 6, 7 and 8. N. 0°03' W., bet. secs. 5 and 6. Over rolling land; asc. SW. slope.
14.00	Spur, slopes W.; desc. NW. slope.
22.00	Rocky spur, slopes NW.
38.60	S. rim of Quail Draw, bears N. 70° E. and S. 30° W.; desc. steep NW. slope.
39.40	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.
40.00	True point for the ¼ sec. cor. of secs. 5 and 6 falls in an insecure place on face of a ledge where the monument cannot be perpetuated.
41.00	Point selected for the witness ¼ sec. cor. of secs. 5 and 6. Set the iron post 10 ins. in the ground, mound with stones to top, cap mkd. T40N R11W ¼ S 6 S 5 W C 1965

CHAINS

- 52.00 Rocky spur, slopes NE.
- 65.00 Wash, 20 lks. wide, 2 ft. deep, drains N. 60° E.
- 68.00 Draw, drains S. 75° E.
- 76.23 Intersect the S. bdy. of T. 41 N., R. 11 W.
Point for the closing cor. of secs. 5 and 6.
Set the iron post 19 ins. in the ground, collar of stones to top, cap mkd.

T41N R11W
S32

S 6 | S 5
T40N R11W
C C
1965

Build a mound of stones S. of the cor.

From this cor. the Standard $\frac{1}{4}$ sec. cor. of sec. 32, T41N, R11W, bears East, 12.69 chs. dist., monumented by an iron post 1 inch diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

Land, rolling and broken.
Soil, gravelly clay loam.
Timber, none.
Undergrowth, blackbrush, yellowbrush, grass and cactus.

The point for the $\frac{1}{4}$ sec. cor. of sec. 5 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 24 ins. in the ground, cap mkd.

$\frac{1}{4}$ S 5

T40N R11W
1965

Build a mound with stones S. of the iron post.

From this cor. the Standard Corner of secs. 32 and 33, T. 41 N., R. 11 W., bears East, 12.80 chs. dist., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record of the 1939 survey.

The point for the $\frac{1}{4}$ sec. cor. of sec. 6 is on the N. bdy. at 40.00 chs. in westing from the closing cor. of secs. 5 and 6.

Set the iron post 18 ins. in the ground, cap mkd.

$\frac{1}{4}$ S 6

T40N R11W
1965

Build a mound of stones S. of the cor.

CHAINS

From this cor. the Standard Corner of secs. 31 and 32, T. 41 N., R. 11 W., bears East, 12.69 chs. dist., monumented by an iron post 2 ins. diam., set, mkd. and witnessed as described in the official record.

General Description

Township 40 North, Range 11 West, of the Gila and Salt River Meridian is in rough mountainous country. Seegmuller Mountain is in the southwest portion of the township. The elevation ranges from about 5,300 feet in the southwest portion to about 4,100 feet in the northeast corner. The general drainage is to the northeast.

There is a heavy growth of juniper and pinon in the southwest portion, gradually thinning into sagebrush, blackbrush and grass upon reaching the northerly slopes. Considerable railing has been done in the southwest portion, and the railed areas have been seeded to grass.

An unimproved road known as Sunshine Trail traverses the northeast corner of the township. There are several other unimproved roads leading to water reservoirs throughout the township.

The land is used primarily for grazing.

A few old undeveloped gypsum mining claims were noticed in the northern portion of the township.

There are no dwellings in this township.

42

BOOK 4762
CERTIFICATE OF SURVEY

I, Boyd S. Owens, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 4th day of April, 19 64,
I have made a completion survey of the subdivisional lines of Township 40
North, Range 11 West,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

October 22, 1965
(Date)

Boyd S. Owens
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date DEC 20 1965

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the completion survey of the subdivisional lines of
Township 40 North, Range 11 West, of the Gila and Salt River Meridian
in the State of Arizona

executed by Boyd S. Owens, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

FEB 7 1966
(Date)

E. E. Lemington
(Chief, Division of Engineering) NES

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY~~ That the foregoing transcript of the field notes of the above-described surveys in
_____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)