

BOOK 4789

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

1

FIELD NOTES

of

REMONUMENTATION

in

Township 14 North, Range 11 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 25, 19 66, which provided for the surveys included under Group Number 445, approved March 25, 1966, and assignment instructions dated May 17, 19 66.

Survey commenced May 25, 19 66

Survey completed June 30, 19 66

412

INDEX DIAGRAM

Township 14 North, Range 11 East,
3 2 2 1 1

6	5	4	3	2	1
					4
7	8	9	10	11	4 12
					3
18	17	16	15	14	13
		5			
19	20	21	22	23	24
30	29	28	27	26	25
	5				
31	32	33	34	35	36

Township 14 North, Range 11 East
Gila and Salt River Meridian, Arizona

1.B

CHAINS

The north, east, west and part of the south boundaries and the subdivisional lines were surveyed in 1881 by T. F. White. The south boundary was resurveyed in 1893 by D. Drummond, and resurveyed again in 1900 by P. Contzen, and the $W\frac{1}{2}$ mile resurveyed again in 1934 by C. W. Devendorf and B. J. Mollette.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 25, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

 Remonumentation, T. 14 N., R. 11 E., Arizona

The cor. of secs. 1, 2, 35 and 36, Ts. 14 and 15 N., R. 11 E., is monumented by the remains of a rotted wooden stake in a mound of stone, from which the remains of the original bearing trees

A pine, 20 ins. diam., bears N. $48\frac{1}{2}^{\circ}$ E., 107 lks. dist., mkd. TXVNRXIEXXXVI

A pine, 20 ins. diam., bears N. 57° W., 20 lks. dist., part of scribe marks visible.

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15NR11E

S35	S36
S 2	S 1

 T14N
 1966

from which

A pine, 15 ins. diam., bears S. 64° E., 108 lks. dist., mkd. T14NR11ES1BT

An oak, 10 ins. diam., bears S. $60\frac{1}{2}^{\circ}$ W., 47 lks. dist., mkd. T14NR11ES2BT

Cor. is on a gentle E. slope in moderate timber, and about 8.00 chs. W. of a track road bearing N. and S.

The $\frac{1}{2}$ sec. cor. of secs. 2 and 35, Ts. 14 and 15 N., R. 11 E., is monumented by a squared wooden stake in a mound of stone, mkd. with faint scribe marks, from which the remains of the original bearing trees

A stump hole bears N. 64° E., 24 lks. dist.

A pine, 16 ins. diam., bears S. 16° W., 16 lks. dist., mkd. with an overgrown blaze. I remark this tree $\frac{1}{2}$ S2BT

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T15NR11E
 $\frac{1}{4} \frac{S35}{S 2}$
 T14N
 1966

from which

A pine, 32 ins. diam., bears N. 23¾° E., 62 lks. dist., mkd. T15NR11E½S35BT

Reset the wooden stake inverted and alongside the iron post.

Cor. is on a gentle NW. slope in moderate timber.

The cor. of secs. 2, 3, 34 and 35, Ts. 14 and 15 N., R. 11 E., is monumented with a rebar in a mound of stone, from which the original bearing trees

An oak, 17 ins. diam., bears N. 54° E., 63 lks. dist., mkd. with an overgrown blaze

A pine, 22 ins. diam., bears S. 64° E., 31 lks. dist., mkd. T14NR11ES2BT

A pine, 22 ins. diam., bears S. 59° W., 67 lks. dist., mkd. with an overgrown blaze

A pine, 24 ins. diam., bears N. 54° W., 64 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T15NR11E
 $\frac{S34}{S 3} \frac{S35}{S 2}$
 T14N
 1966

from which

A pine, 14 ins. diam., bears S. 56½° W., 71 lks. dist., mkd. T14NR11ES3BT

Cor. is on gently rolling land in thick timber.

The cor. of secs. 3, 4, 33 and 34, Ts. 14 and 15 N., R. 11 E., is monumented with the remains of a rotted wooden stake in a mound of stone, from which the remains of the original bearing trees

A fallen pine, 26 ins. diam., bears N. 55° E., 196 lks. dist., mkd. T15NR11ES34BT

A stump hole, bears S. 9½° E., 81 lks. dist.

A pine, 24 ins. diam., bears S. 43½° W., 166 lks. dist., mkd. with an overgrown blaze

A fallen pine, bears N. 58½° W., 89 lks. dist., no marks

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR11E

S33	S34
S 4	S 3

T14N
1966

from which

An oak, 16 ins. diam., bears S. 77° E., 50 lks. dist., mkd. T14NR11ES3BT

A pine, 18 ins. diam., bears S. 5° W., 72 lks. dist., mkd. T14NR11ES4BT

Raise a mound of stone W. of the iron post.

Cor. is on a NE. slope in thick timber.

The cor. of secs. 4, 5, 32 and 33, Ts. 14 and 15 N., R. 11 E., is monumented by a mound of stone, the center of which is accepted as the cor. point, from which the remains of the original bearing trees

A fallen pine, bears N. 37° E., 151 lks. dist., mkd. T15NR11ES33BT

A pine, 32 ins. diam., bears S. 38° E., 143 lks. dist., mkd. with an overgrown blaze

A pine, 20 ins. diam., bears S. 30½° W., 167 lks. dist., mkd. with an overgrown blaze

A pine stump, bears N. 24½° W., 70 lks. dist., no marks

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR11E

S32	S33
S 5	S 4

T14N
1966

from which

A pine, 5 ins. diam., bears N. 1° E., 24 lks. dist., mkd. S33BT

A pine, 9 ins. diam., bears N. 58° W., 83 lks. dist., mkd. T15NR11ES32BT

Raise a mound of stone W. of the iron post.

Cor. is on a NE. slope among moderate timber, and is 30 lks. E. of a track road, bearing N. and S.

The point for the cor. of secs. 11, 12, 13 and 14 is determined by using record bearing and distance from the original bearing trees

A pine, 22 ins. diam., bears N. 31° E., 124 lks. dist., mkd. with an overgrown blaze

CHAINS

A pine, 32 ins. diam., bears S. 52° E., 93 lks. dist., mkd. with an overgrown blaze

A pine, 34 ins. diam., bears S. 67° W., 132 lks. dist., mkd. with an overgrown blaze

A pine stump, bears N. 34° W., 69 lks. dist., no marks found

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T14NR11E
 S11 | S12
 S14 | S13
 1966

from which

A pine, 8 ins. diam., bears S. 72° W., 30 lks. dist., mkd. T14NR11ES14BT

A pine, 26 ins. diam., bears N. 49½° W., 97 lks. dist., mkd. T14NR11ES11BT

Raise a mound of stone W. of the iron post.

Cor. is 14 lks. E. of a fence bearing N. and S., on a grassy NE. slope in moderate timber.

The ¼ sec. cor. of secs. 11 and 12 is monumented by a sandstone, 6 x 10 x 28 ins. firmly set, mkd. ¼ on the W., from which the original bearing trees

A pine, 34 ins. diam., bears N. 35° E., 9 lks. dist., mkd. with a partly overgrown blaze

A pine, 18 ins. diam., bears S. 16° W., 63 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T14NR11E
 ¼
 S11 | S12
 1966

Raise a mound of stone W. of the cor. and deposit glass alongside the iron post.

Cor. is on a N. slope in moderate timber, with a track road 1.00 chs. S.; road bears NE. and SW.

The cor. of secs. 1, 2, 11 and 12 is monumented by a scattered mound of stone, the center of which is accepted as the cor. point, from which the remains of the original bearing trees

A pine, 22 ins. diam., bears N. 75° E., 92 lks. dist., mkd. with an overgrown blaze

A pine, 24 ins. diam., bears S. 45° E., 110 lks. dist., mkd. TXIVNRXIEX11BT

CHAINS

A pine stump bears S. 47° W., 171 lks. dist.,
mkd. with an overgrown blaze

A pine stump bears N. 85° W., 107 lks. dist.,
no marks

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins.
in the ground, mound of stone to top, brass cap mkd.

T14NR11E
S 2 | S 1
S11 | S12
1966

from which

A pine, 16 ins. diam., bears N. 20¾° W., 82 lks.
dist., mkd. T14NR11ES2BT

Cor. is on a S. slope among moderate timber, about
15.00 chs. S. of State Highway No. 65.

The point for the cor. of secs. 16, 17, 20 and 21 is
determined by using record bearing and distance from
the original bearing trees

A pine, 36 ins. diam., bears N. 78° E., 41 lks.
dist., mkd. with an overgrown blaze

A fallen pine bears S. 16° E., 118 lks. dist.,
no marks

A pine, 38 ins. diam., bears S. 27½° W., 17 lks.
dist., mkd. with an overgrown blaze

A pine, 40 ins. diam., bears N. 28° W., 40 lks.
dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.
in the ground, brass cap mkd.

T14NR11E
S17 | S16
S20 | S21
1966

Raise a small mound of stone W. of the iron post.

Cor. is on rolling land, about 100 lks. E. of a gravel
road bearing N. and S.

The cor. of secs. 29, 30, 31 and 32 is monumented by a
mound of stone, the center of which is accepted as the
cor. point, from which the remains of the original
bearing trees

A pine, 22 ins. diam., bears S. 29½° E., 14 lks.
dist., mkd. with an overgrown blaze

A pine, 28 ins. diam., bears S. 43° W., 47 lks.
dist., mkd. TXIVNRXIESXXXIBT

A pine, 24 ins. diam., bears N. 55° W., 65 lks.
dist., mkd. with an overgrown blaze

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR11E
S30 | S29
S31 | S32
 1966

from which

An oak, 6 ins. diam., bears N. 64½° E., 39 lks. dist., mkd. T14NR11ES29BT

A pine, 20 ins. diam., bears S. 72½° W., 60 lks. dist., mkd. T14NR11ES31BT

Cor. is on top of E. Clear Creek Canyon rim, in medium to thick timber and undergrowth.

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of March, 1966, I have remonumented cadastral survey corners in Township 14 North, Range 11 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 18, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 15 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 14 North, Range 11 East, Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician, having been critically examined and found correct, are hereby approved.

MAY 18 1967
(Date)

E. E. Livingston
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)