

12

INDEX DIAGRAM

Township 14 North, Range 12 East
4 3 3 2 1 1

6	8 5	4	3	2	1
	7	7			
7	8	9	10	11	12
			6		
18	17	16	5 15	14	13
			4 5		
19	20	21	22	23	24
30	29	28	27	26	25
		6			
31	32	33	34	35	36

Township 14 North, Range 12 East
Gila and Salt River Meridian, Arizona

1.B

CHAINS

The south and west boundaries were surveyed in 1881 by T. F. White. The east boundary was surveyed in 1883 by J. B. McLaughlin. The north boundary and subdivisional lines were surveyed and the south and east boundaries resurveyed in 1893 by D. Drummond.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 25, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, T. 14 N., R. 12 E., Arizona

The tp. cor. of Ts. 14 and 15 N., Rs. 12 and 13 E., monumented by a sandstone, 5 x 12 x 18 ins., lying loose upon the ground, mkd. with 6 notches on the N., E., S. and W. edges, from which the remains of the original bearing trees

A pine, 14 ins. diam., bears S. 41° W., 71 lks. dist., mkd. with an overgrown blaze

A juniper, 12 ins. diam., bears N. 1° W., 11 lks. dist., mkd. with partly overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, mound of stone to top, brass cap mkd.

T15N
R12E R13E
S36 | S31
S 1 | S 6
T14N
1966

from which

A pine, 12 ins. diam., bears N. 68½° W., 51 lks. dist., mkd. T15NR12ES36BT

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on a steep E. slope in thick timber and undergrowth.

The cor. of secs. 3, 4, 33 and 34, Ts. 14 and 15 N., R. 12 E., is monumented by a sandstone, 5 x 9 x 18 ins., firmly set, mkd. with 3 notches on the E. and W., from which the original bearing trees

A pine, 22 ins. diam., bears N. 27° E., 60 lks. dist., mkd. with an overgrown blaze

CHAINS

A pine, 22 ins. diam., bears S. 87° E., 63 lks. dist., mkd. with an overgrown blaze

A pine, 15 ins. diam., bears S. 73½° W., 82 lks. dist., mkd. with an overgrown blaze

A pine, 22 ins. diam., bears N. 21° W., 25 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR12E
 $\frac{S33}{S4} | \frac{S34}{S3}$
 T14N
 1966

from which

A pine, 30 ins. diam., bears N. 59¾° E., 117 lks. dist., mkd. T15NR12ES34BT

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a NE. slope in thick timber and undergrowth, about 8.00 chs. S. of canyon draining SE.

The ¼ sec. cor. of secs. 4 and 33, Ts. 14 and 15 N., R. 12 E., monumented by a sandstone, 10 x 11 x 20 ins., firmly set, mkd. ¼ on the N., from which the original bearing trees

An oak, 10 ins. diam., bears N. 50° E., 44 lks. dist., mkd. with an overgrown blaze

A fallen pine bears S. 56° W., 48 lks. dist., no marks found

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T15NR12E
 $\frac{1}{4} \frac{S33}{S4}$
 T14N
 1966

from which

A pine, 14 ins. diam., bears S. 63° E., 66 lks. dist., mkd. T14NR12ES4BT

Bury the original corner stone alongside the iron post.

Cor. is on a N. slope about 2.00 chs. S. of a wash draining E.

CHAINS

The cor. of secs. 4, 5, 32 and 33, Ts. 14 and 15 N., R. 12 E., monumented by a limestone, 8 x 20 x 28 ins., firmly set and in a mound of stone, mkd. with 4 notches on the E. and 2 notches on the W., from which the original bearing trees

A pine, 22 ins. diam., bears N. 85° E., 85 lks. dist., mkd. with an overgrown blaze

An oak, 9 ins. diam., bears S. 8½° E., 66 lks. dist., mkd. with an overgrown blaze

A pine, 30 ins. diam., bears S. 58½° W., 119 lks. dist., mkd. with an overgrown blaze

An oak, 13 ins. diam., bears N. 33° W., 30 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, brass cap mkd.

T15NR12E
 S32 | S33
 S 5 | S 4
 T14N
 1966

from which

A juniper, 4 ins. diam., bears S. 39½° E., 44 lks. dist., mkd. XBT

An oak, 5 ins. diam., bears N. 48½° W., 46 lks. dist., mkd. T15NR12ES32BT

Raise a mound of stone W. of the iron post.

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is on nearly level land, about 3.50 chs. W. of a dirt road bearing NE. and SW.

The ¼ sec. cor. of secs. 5 and 32, Ts. 14 and 15 N., R. 12 E., monumented by a sandstone, 5 x 10 x 18 ins., firmly set, mkd. with ¼ on the N., from which the original bearing trees

A pine, 26 ins. diam., bears N. 14° E., 45 lks. dist., mkd. with an overgrown blaze

An oak, 13 ins. diam., bears S. 60° W., 51 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR12E
 ¼ S32
 S 5
 T14N
 1966

from which

CHAINS

A pine, 14 ins. diam., bears N. $6\frac{3}{4}^{\circ}$ W., 57 lks. dist., mkd. T15NR12ES32BT

Raise a mound of stone N. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on a gentle N. slope in moderate timber.

The cor. of secs. 5, 6, 31 and 32, Ts. 14 and 15 N., R. 12 E., monumented by a sandstone, 6 x 12 x 18 ins., firmly set and in a mound of stone, mkd. with 5 notches on the E. and 1 notch on the W., from which the original bearing trees

An oak snag, 10 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ E., 120 lks. dist., mkd. with most of scribe marks visible

A pine, 22 ins. diam., bears S. 56° E., 85 lks. dist., mkd. T14NR12ES5BT

An oak, 12 ins. diam., bears S. 56° W., 41 lks. dist., mkd. with partly overgrown blaze

An oak, 18 ins. diam., bears N. 46° W., 53 lks. dist., mkd. with partly overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone to top, grass cap mkd.

T15NR12E	
S31	S32
S 6	S 5
T14N	
1966	

from which

An oak, 5 ins. diam., bears N. 54° E., 60 lks. dist., mkd. S32BT

A pine, 26 ins. diam., bears S. $20\frac{1}{2}^{\circ}$ W., 60 lks. dist., mkd. T14NR12ES6BT

Deposit the original corner stone in the mound of stone around the iron post.

Cor. is in a shallow draw draining N., and in moderate timber and undergrowth.

The cor. of secs. 15, 16, 21 and 22, monumented by a sandstone, 5 x 14 x 26 ins., lying loose upon the ground, mkd. with 3 notches on the E. and the S., from which the original bearing trees

A pine, 12 ins. diam., bears N. $10\frac{1}{4}^{\circ}$ E., 45 lks. dist., mkd. with an overgrown blaze

An oak, 10 ins. diam., bears S. 66° E., 37 lks. dist., mkd. with an overgrown blaze

A pine, 16 ins. diam., bears S. $31\frac{3}{4}^{\circ}$ W., 57 lks. dist., mkd. with an overgrown blaze

A pine, 16 ins. diam., bears N. 12° W., 47 lks. dist., mkd. with an overgrown blaze

At the cor. point

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR12E
 $\frac{S16}{S21} | \frac{S15}{S22}$
 1966

Bury the original corner stone alongside the iron post.

Cor. is on a W. slope, 1.00 ch. W. of a track road bearing N. and S.

The ¼ sec. cor. of secs. 15 and 22, monumented by a mound of stone, the center of which is accepted as the cor. point, from which the original bearing trees

A juniper, 12 ins. diam., bears S. 4½° W., 105 lks. dist., mkd. ¼SBT

An oak, 14 ins. diam., bears N. 69° W., 97 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR12E
 $\frac{1}{4} \frac{S15}{S22}$
 1966

from which

A pine, 7 ins. diam., bears S. 39° W., 6 lks. dist., mkd. T14NR12E ¼S22BT

Cor. is on an E. slope in thick timber, about 8.00 chs. W. of dirt road bearing N. and S.

The ¼ sec. cor. of secs. 15 and 16 is monumented by a small mound of stone, the center of which is accepted as the cor. point, from which the original bearing trees

A pine, 16 ins. diam., bears N. 28¾° E., 31 lks. dist., mkd. ¼SBT

A pine, 11 ins. diam., bears S. 71¾° W., 43 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T14NR12E
 $\frac{1}{4} \frac{S16}{S15}$
 1966

from which

A pine, 16 ins. diam., bears N. 73¾° W., 53 lks. dist., mkd. T14NR12E ¼S16BT

Raise a mound of stone W. of the iron post.

CHAINS

Cor. is on the W. slope of a ridge bearing N. and S., and in moderate timber.

The cor. of secs. 9, 10, 15 and 16, monumented by a limestone, 8 x 14 x 24 ins., firmly set and in a mound of stone, mkd. with 4 notches on the S. and 3 notches on the E., from which the remains of the original bearing trees

A pine, 22 ins. diam., bears N. 70° E., 29 lks. dist., mkd. with an overgrown blaze

An oak, 6 ins. diam., bears S. 44½° E., 51 lks. dist., mkd. with an overgrown blaze, tree is dead

A pine stump bears S. 68½° W., 35 lks. dist., no marks found

A pine, 28 ins. diam., bears N. 25½° W., 9 lks. dist., mkd. T14NR12ES9BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR12E	
S 9	S10
S16	S15
1966	

from which

A pine, 14 ins. diam., bears N. 82° E., 31 lks. dist., mkd. T14NR12E S10BT

A juniper, 6 ins. diam., bears S. 52° W., 57 lks. dist., mkd. S16BT

Bury the original corner stone alongside the iron post.

Cor. is on the W. slope of a ridge, about 5.00 chs. from the top; ridge bears N. and S.

The cor. of secs. 28, 29, 32 and 33, monumented by a sandstone, 8 x 10 x 18 ins., set 10 ins. in the ground, mkd. with 4 notches on the E. and 1 notch on the S., from which the remains of the original bearing trees

A stump hole bears N. 7° E., 29 lks. dist., (record)

A pine, 18 ins. diam., bears S. 53° E., 32 lks. dist., mkd. with an overgrown blaze

A stump hole bears S. 75° W., 62 lks. dist., (record)

A stump hole bears N. 17° W., 43 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

CHAINS

T14NR12E
S29 | S28
S32 | S33
 1966

from which

A pine, 22 ins. diam., bears N. 31° E., 56 lks. dist., mkd. T14NR12ES28BT

Raise a mound of stone W. of the iron post.

Bury the original corner stone alongside the iron post.

Cor. is on an E. slope in moderate to thick timber, 1.00 ch. E. of bladed road bearing N. and S.

The cor. of secs. 4, 5, 8 and 9, monumented by a sandstone, 8 x 16 x 20 ins., firmly set, mkd. with 5 notches on the S. and 4 notches on the E., from which the remains of the original bearing trees

A pine stump, 24 ins. diam., bears N. 61° E., 53 lks. dist., mkd. T14NR12ES4BT

A juniper, 48 ins. diam., bears S. 50° E., 43 lks. dist., mkd. T14NR12ES9BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T14NR12E
S5 | S4
S8 | S9
 1966

from which

An oak, 7 ins. diam., bears N. 34° E., 77 lks. dist., mkd. T14NR12ES4BT

A pine, 28 ins. diam., bears S. 70½° W., 114 lks. dist., mkd. T14NR12ES8BT

Raise a mound of stone W. of the iron post

Deposit the original corner stone in the mound of stone to the W. of the iron post.

Cor. is on an E. slope in moderate timber and undergrowth.

The point for the cor. of secs. 5, 6, 7 and 8 is determined by using record course and distance from the original bearing trees

A pine stump bears N. 15° E., 7 lks. dist., mkd. T14NR12ES5BT

A pine, 16 ins. diam., bears S. 75° E., 43 lks. dist., mkd. T14NR12ES8BT

A juniper, 14 ins. diam., bears S. 41° W., 22 lks. dist., mkd. with a partly overgrown blaze

A pine, 18 ins. diam., bears N. 89½° W., 45 lks. dist., mkd. with an overgrown blaze

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 36 ins. in the ground, brass cap mkd.

T14NR12E
 $\frac{S6}{S7} | \frac{S5}{S8}$
 1966

from which

A pine, 15 ins. diam., bears S. 61° E., 57 lks. dist., mkd. T14NR12ES8BT

A pine, 28 ins. diam., bears N. 23° W., 87 lks. dist., mkd. T14NR12ES6BT

Raise a mound of stone W. of the iron post.

Cor. is on the W. edge of a gravel road bearing N. and S.

The ¼ sec. cor. of secs. 5 and 6, monumented by a sandstone, 8 x 12 x 18 ins., firmly set, mkd. ¼ on the W., from which the original bearing trees

A pine, 18 ins. diam., bears N. 39° E., 23 lks. dist., mkd. with an overgrown blaze

A juniper stump, 16 ins. diam., bears S. 59° W., 18 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T14NR12E
 $\frac{1}{4}$
 $\frac{S6}{S5}$
 1966

from which

A juniper, 12 ins. diam., bears N. 55° W., 102 lks. dist., mkd. T14NR12E¼S6BT

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land in scattered to moderate timber.

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of March, 1966, I have remonumented cadastral survey corners in Township 14 North, Range 12 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 18, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 15 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 14 North, Range 12 East, of the Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician, having been critically examined and found correct, are hereby approved.

MAY 18 1967
(Date)

E. E. Remington
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)