

1

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 15 North, Range 13 East

Of the Gila & Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 25, 19 66, which provided for the surveys
included under Group Number 445, approved March 25, 1966,
and assignment instructions dated May 17, 19 66.

Survey commenced May 25, 19 66

Survey completed June 30, 19 66

(1A)

INDEX DIAGRAM

Township 15 North, Range 13 East,

6	5	4	3	2	1
7	8	9	10	11	12
13	14	15	16	17	18
19	20	21	22	23	24
25	26	27	28	29	30
31	32	33	34	35	36

Township 15 North, Range 13 East
Gila and Salt River Meridian, Arizona

1. B

CHAINS

The west boundary was surveyed in 1883 by J. B. McLaughlin and resurveyed in 1893 by D. Drummond. The east boundary was surveyed in 1893 by P. Contzen. The north and south boundaries and the subdivisional lines were surveyed in 1893 by D. Drummond.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 25, 1966, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to the corner accessories.

Remonumentation, T. 15 N., R. 13 E., Arizona

The cor. of secs. 5, 6, 31 and 32, Ts. 15 and 16 N., R. 13 E., is monumented by a malpais stone, 6 x 12 x 18 ins., firmly set, mkd. with 5 notches on the E. and 1 notch on the W., from which the remains of the original bearing trees

A fallen pinon, 12 ins. diam., bears S. 46° E., 137 lks. dist., mkd. T15NR13ES5BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

T16NR13E	
S31	S32
S 6	S 5
T15N	
1966	

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land in a railed area.

The cor. of secs. 8, 9, 16 and 17, is monumented by a limestone, 8 x 14 x 20 ins., set 12 ins. in the ground, and in a small mound of stone, mkd. with 4 notches on the E. and 4 dim notches on the S., from which the remains of the original bearing trees

A fallen pinon, 5 ins. diam., bears S. 77° E., 88 lks. dist., mkd. T15NR13ES16BT

A fallen pinon, 6 ins. diam., bears N. 33° W., 50 lks. dist., mkd. T15NR13ES8BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone to top, brass cap mkd.

2

2.

CHAINS

T15NR13E
S 8 | S 9
S17 | S16
 1966

Bury the original corner stone alongside the iron post.

Cor. is on a S. slope, 35 lks. N. of a track road bearing E. and W.

The cor. of secs. 4, 5, 8 and 9, is monumented by a malpais stone, 4 x 16 x 18 ins., set 8 ins. in the ground, and in a mound of stone, dimly mkd. with 4 notches on the E. and 5 notches on the S., from which the remains of the original bearing trees

A juniper, 6 ins. diam., bears N. 47° E., 12 lks. dist., mkd. with an open blaze

A fallen pinon, 8 ins. diam., bears S. 82½° E., 50 lks. dist., mkd. T15NR13ES9BT

A juniper, 9 ins. diam., bears S. 60° W., 28 lks. dist., mkd. T15NR13ES8BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T15NR13E
S 5 | S 4
S 8 | S 9
 1966

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land in a railed area.

The cor. of secs. 17, 18, 19 and 20, is monumented by a sandstone, 3 x 14 x 20 ins., firmly set, mkd. with 3 notches on the S. and 5 notches on the E., with a small mound of stone to the W., from which the original bearing trees

A dead pinon, 9 ins. diam., bears N. 55½° E., 72 lks. dist., mkd. T15NR13ES17BT

A fallen pinon, 14 ins. diam., bears S. 63° E., 25 lks. dist., mkd. T15NR13ES20BT

A dead pinon, 12 ins. diam., bears S. 78½° W., 53 lks. dist., mkd. T15NR13ES19BT

A dead pinon, 11 ins. diam., bears N. 11° W., 66 lks. dist., mkd. T15NR13ES18BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR13E
S18 | S17
S19 | S20
 1966

from which

CHAINS

A pinon, 14 ins. diam., bears S. $61\frac{1}{2}^{\circ}$ E., 161 lks. dist., mkd. T15NR13ES20BT

Raise a mound of stone W. of the iron post.

Bury the original corner stone and deposit glass alongside the iron post.

Cor. is at the SW. edge of a railed area on rolling land, and by an old fence cor., from which fences bear N. and W.

The point for the cor. of secs. 7, 8, 17 and 18, is determined by using record bearing and distance from the remains of the original bearing trees

A pinon, 18 ins. diam., bears S. 15° W., 44 lks. dist., mkd. T15NR13ES18BT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T15NR13E
 $\frac{S\ 7\ | S\ 8}{S\ 18\ | S\ 17}$
 1966

Raise a mound of stone W. of the iron post.

Cor. is on rolling land in a railed area.

The cor. of secs. 5, 6, 7 and 8, is monumented by a malpais stone, 5 x 10 x 20 ins., loosely set in a small mound of stone, mkd. with 5 notches on the S. and the E., from which the remains of the original bearing trees

A fallen pinon, 6 ins. diam., bears S. $38\frac{1}{2}^{\circ}$ W., 100 lks. dist., mkd. T15NR13ES7BT

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, collar of stone to top, brass cap mkd.

T15NR13E
 $\frac{S\ 6\ | S\ 5}{S\ 7\ | S\ 8}$
 1966

Bury the original corner stone alongside the iron post.

Cor. is on nearly level land in a railed area.

6

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day of March, 1966, I have remonumented cadastral survey corners in Township 15 North, Range 13 East,

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 18, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 15 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 15 North, Range 13 East, of the Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician, having been critically examined and found correct, are hereby approved.

MAY 18 1967
(Date)

E. L. Hemington
(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)