

1

BOOK 4802

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY

of the

EAST AND NORTH BOUNDARIES

and the

WEST HALF OF THE SUBDIVISIONAL LINES

of

TOWNSHIP 3 NORTH, RANGE 8 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Cadastral Surveyor

Gary T. Oviatt, Surveying Technician

Under special instructions dated September 10, 19 65, which provided for the surveys included under Group Number 434, approved September 13, 1965, and assignment instructions dated December 16, 19 65, and March 4, 1966.

Survey commenced January 25, 19 66

Survey completed March 28, 19 66

1A

BOOK 4802

INDEX DIAGRAM

Township 3 North, Range 8 East,

10	9	8	7	6	6
6	31 8	21 4	14 3	2	1 5
30	30	21			
7	29 8	20 9	13 10	11	12 4
28	28	19			
18	27 17	19 16	13 15	14	18 4
26	26	18			
19	25 20	17 21	12 22	23	24 3
25	24	17			
30	23 29	16 28	11 27	26	25 2
23	22	15			
31	22 32	14 33	10 34	35	36 1

CHAINS

The south boundary was surveyed concurrently under this same group and described in the field notes of the survey of the north boundary of Township 2 North, Range 8 East. The west boundary was surveyed concurrently under this same group and described in the field notes of the survey of the east boundary of Township 3 North, Range 7 East.

The following notes are those of the survey of the east and north boundaries and the west half of the subdivisional lines of Township 3 North, Range 8 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions, dated September 10, 1965.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographical position of the southeast corner of the township, as computed from triangulation station STEWART DAM is: Latitude, 33°33'11.9" North, and Longitude, 111°28'34.04" W.

The mean magnetic declination was found to be 14° East.

Survey of the East Boundary
Township 3 North, Range 8 East
Arizona

Beginning at the true point for the cor. of Ts. 2 and 3 N., Rs. 8 and 9 E.

North, bet. secs. 31 and 36.

Over broken mountainous land through moderate palo verde.

- 0.50 The witness Tp. cor. of Ts. 2 and 3 N., Rs. 8 and 9 E., an iron post 2½ ins. diam., described in the field notes of the concurrent survey of the E. bdy. of Tp. 2 N., R. 8 E.
 - 1.70 Rocky spur, slopes E.; desc. over N. slope.
 - 16.00 Begin triangulation, topography as estimated.
 - 20.00 Desc. over sheer wall, facing N.
 - 23.80 Center of the Salt River, course W.
 - 27.70 Right bank of the Salt River, bears E. and W. End of triangulation.
 - 31.20 Spur, slopes SE.
 - 40.00 Point for the ¼ sec. cor. of secs. 31 and 36.
- Set the iron post over an "X" chiseled in solid rock, mound with stone to top, brass cap mkd.

BOOK 4802

East Boundary, T. 3 N., R. 8 E., Arizona

CHAINS	
	<p style="text-align: center;">T3N R8E R9E $\frac{1}{4}$ S36 S31 1966</p> <p>The cor. is located in the bottom of a draw, draining SE.</p>
47.80	Spur, slopes W.
60.30	Low ridge, bears N. 80° E. and S. 80° W.
69.80	Large draw, drains W. about 9.00 chs. dist. to Saguaro Lake.
74.00	Rocky spur, slopes W.
80.00	Point for the cor. of secs. 25, 30, 31 and 36.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	<p style="text-align: center;">T3N R8E R9E <u>S25 S30</u> <u>S36 S31</u> 1966</p> <p>Land, broken and rolling. Soil, rocky. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw, brush and grass.</p>
	North, bet. secs. 25 and 30.
	Over rolling land, through moderate palo verde.
7.40	Wash, 10 lks. wide, 2 ft. deep, drains W.
14.60	Spur, slopes S. 70° W.
19.20	Draw, drains S. 30° W.
27.00	Ridge, bears E. and W.
36.20	Wash, 30 lks. wide, 1 ft. deep, drains W.
38.50	Spur, slopes W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
	<p style="text-align: center;">T3N R8E R9E $\frac{1}{4}$ S25 S30 1966</p>
40.80	Wash, 20 lks. wide, 1 ft. deep, drains SW.
79.50	Small spur, slopes SE.

CHAINS	
80.00	<p>Point for the cor. of secs. 19, 24, 25 and 30.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R8E R9E <u>S24</u> <u>S19</u> <u>S25</u> <u>S30</u> 1966</p> </div> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, cat claw and brush.</p>
	<hr/>
	<p>North, bet. secs. 19 and 24.</p>
	<p>Over rolling land, through moderate palo verde.</p>
17.60	<p>Wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.</p>
35.00	<p>Small wash, drains SW.</p>
40.00	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 19 and 24.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R8E R9E $\frac{1}{2}$ <u>S24</u> <u>S19</u> 1966</p> </div> <p>Raise a mound of stone W. of the cor.</p>
41.00	<p>Jeep road, bears N. 30° E. and S. 25° W.</p>
69.00	<p>Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.</p>
72.70	<p>Long spur, slopes SW.</p>
74.10	<p>Wash, 10 lks. wide, 1 ft. deep, drains SW.</p>
74.90	<p>Jeep road, bears N. 35° E. and SW.</p>
80.00	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T3N R8E R9E <u>S13</u> <u>S18</u> <u>S24</u> <u>S19</u> 1966</p> </div> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cat claw, cacti, brush and scattered creosote.</p>

BOOK 4802

East Boundary, T. 3 N., R. 8 E., Arizona

4

4.

CHAINS	
	North, bet. secs. 13 and 18.
	Over rolling land, through moderate palo verde.
12.70	Spur, slopes W.
38.40	Wash, 25 lks. wide, 1 ft. deep, drains S. 35° W.
40.00	Point for the ½ sec. cor. of secs. 13 and 18.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T3N R8E R9E ½ S13 S18 1966
50.40	Spur, slopes S. 10° W.
55.60	Wash, 30 lks. wide, 1 ft. deep, drains SW. for 2.00 chs., thence S.
67.20	Long spur, slopes S. 15° W.
80.00	Point for the cor. of secs. 7, 12, 13 and 18.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T3N R8E R9E S12 S 7 S13 S18 1966
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and brush.
	North, bet. secs. 7 and 12.
	Over rolling land, through moderate palo verde.
0.50	Draw, drains irregularly W.
5.20	Spur, slopes W.
13.30	Wash, 20 lks. wide, 1 ft. deep, drains S. 15° W.
40.00	Point for the ½ sec. cor. of secs. 7 and 12.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T3N R8E R9E ½ S12 S 7 1966
	Raise a mound of stone W. of the cor.
52.40	High spur, slopes E.

BOOK 4802

East Boundary, T. 3 N., R. 8 E., Arizona

5.

CHAINS

59.70 Jeep road, bears N. 40° E. and S. 40° W.
 80.00 Point for the cor. of secs. 1, 6, 7 and 12.
 Set the iron post 22 ins. in the ground, brass cap mkd.

T3N
 R8E R9E
S 1 | S 6
S12 | S 7
 1966

Raise a mound of stone W. of the cor.

Land, rolling.
 Soil, rocky and sandy.
 Timber, moderate palo verde.
 Undergrowth, moderate cacti, brush and grass.

North, bet. secs. 1 and 6.

Over rolling land, through moderate palo verde.

17.50 Bladed road, bears S. 25° E. and N. 25° W.
 25.20 Wash, drains SE.; road follows along the bottom of wash.
 40.00 Point for the 1/4 sec. cor. of secs. 1 and 6.
 Set the iron post 22 ins. in the ground, brass cap mkd.

T3N
 R8E R9E
 1/4
S 1 | S 6
 1966

Raise a mound of stone W. of the cor.

58.40 Spur, slopes S. 5° E.
 67.20 Spur, slopes E.
 80.00 Point for the Tp. cor. of Ts. 3 and 4 N., Rs. 8 and 9 E.
 Set the iron post 22 ins. in the ground, brass cap mkd.

T4N
 R8E R9E
S36 | S31
S 1 | S 6
 T3N
 1966

Raise a mound of stone S. of the cor.

Land, rolling.
 Soil, rocky and sandy.
 Timber, moderate palo verde.
 Undergrowth, moderate cacti, cat claw, brush and grass.

BOOK 4802

North Boundary, T. 3 N., R. 8 E., Arizona

6

6.

CHAINS

Survey of the North Boundary
Township 3 North, Range 8 East
Arizona

From the Tp. cor. of Ts. 3 and 4 North, Rs. 8 and 9 East.

West, bet. secs. 1 and 36.

Over rolling land, through moderate palo verde.

3.90 Low ridge, bears N. and S.

37.00 Small wash, drains S. 25° W.

40.00 Point for the ¼ sec. cor. of secs. 1 and 36.

Set the iron post 20 ins. in the ground, brass cap mkd.

T4N R8E
¼ $\frac{S36}{S 1}$
T3N
1966

Raise a mound of stone W. of the cor.

41.80 Bladed road, bears S. and N. 50 lks., curving to N. 30° E.

67.80 Wash, 10 lks. wide, 3 ft. deep, drains S.

73.20 Ridge, bears N. 30° E. and S.

80.00 Point for the cor. of secs. 1, 2, 35 and 36.

Set the iron post 22 ins. in the ground, brass cap mkd.

T4N R8E
 $\frac{S35}{S 2} | \frac{S36}{S 1}$
T3N
1966

Raise a mound of stone W. of the cor.

Land, rolling.

Soil, sandy.

Timber, moderate palo verde.

Undergrowth, moderate cacti, creosote, cat claw and grass.

West, bet. secs. 2 and 35.

Over rolling land, through moderate palo verde.

6.80 Bladed road, bears N. 20° E. and S. 20° W.

11.00 Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.

21.00 Low ridge, bears N. and S.

38.50 Wash, 20 lks. wide, 1 ft. deep, drains S. 20° W.

40.00 Point for the ¼ sec. cor. of secs. 2 and 35.

Set the iron post 20 ins. in the ground, brass cap mkd.

BOOK 4802

North Boundary, T. 3 N., R. 8 E., Arizona

7.

CHAINS	
	<p style="text-align: center;">T4N R8E $\frac{1}{4}$ $\frac{S35}{S 2}$ T3N 1966</p> <p>Raise a mound of stone W. of the cor.</p>
59.40	Wash, 30 lks. wide, 1 ft. deep, drains S. 30° W.
75.80	Low ridge, bears N. and S.
79.50	Small wash, drains irregularly S.
80.00	Point for the cor. of secs. 2, 3, 34 and 35.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R8E $\frac{S34}{S 3}$ $\frac{S35}{S 2}$ T3N 1966</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy. Timber, moderate palo verde. Undergrowth, moderate cat claw, cacti, creosote and grass.</p>
	<p>West, bet. secs. 3 and 34.</p> <p>Over rolling land, through moderate palo verde.</p>
1.40	Low rise, bears N. and S.
8.30	Diversion ditch, drains S. 20° E.
22.00	Bladed road, bears N. 15° E. and S. 15° W.
29.10	Bladed road, bears S. 75° E. and N. 75° W.
30.30	Jeep road, bears N. and S.
34.50	Spur, slopes NW.
36.50	Wash, 20 lks. wide, 1 ft. deep, drains S.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R8E $\frac{1}{4}$ $\frac{S34}{S 3}$ T3N 1966</p> <p>Raise a mound of stone W. of the cor.</p>
54.30	Bladed road, bears N. 30° E. and S. 30° W.
56.60	Wash, 30 lks. wide, 1 ft. deep, drains S.

CHAINS

- 57.90 Bladed road, bears S. 80° E. and N. 70° W.
- 62.40 Low ridge, bears N. and S.
- 68.80 NE. cor. of corral, bears N. 70° W. and S. 20° W.
- 70.90 W. side of corral, bears N. and S. for 50 lks. to fence bearing N. 85° W. and SE.
- 80.00 Point for the cor. of secs. 3, 4, 33 and 34.

Set the iron post 22 ins. in the ground, brass cap mkd.

T4N	R8E
<u>S33</u>	<u>S34</u>
S 4	S 3
T3N	
1966	

The cor. is set in a fence line, bearing S. 85° E. and N. 85° W.

Raise a mound of stone W. of the cor.

Land, rolling.

Soil, sandy.

Timber, moderate palo verde.

Undergrowth, moderate cacti, cat claw, brush and scattered creosote.

West, bet. secs. 4 and 33.

Over rolling land, through moderate palo verde.

- 1.25 Four strand barbed wire fence, bears S. 10° W. and N. 10° E. for 10 lks.; thence S. 85° E.
 - 7.00 Wash, 30 lks. wide, 2 ft. deep, drains SW.
 - 26.40 Bladed road, bears N. 48° E. and S. 35° W.
 - 40.00 Point for the 1/4 sec. cor. of secs. 4 and 33.
- Set the iron post 20 ins. in the ground, brass cap mkd.

T4N	R8E
<u>1/4 S33</u>	
S 4	
T3N	
1966	

Raise a mound of stone W. of the cor.

- 47.20 Bladed road, bears NE. and S. 25° W.
 - 55.40 Beeline Highway (Arizona State Hwy. 87), bears N. 48°10' E. and S. 48°10' W.
 - 62.70 Bladed road, bears N. 40° E. and S. 40° W.
 - 63.10 Low ridge, bears NE. and SW.
 - 80.00 Point for the cor. of secs. 4, 5, 32 and 33.
- Set the iron post 22 ins. in the ground, brass cap mkd.

BOOK 4802

North Boundary, T. 3 N., R. 8 E., Arizona

CHAINS

T4N R8E
S32 | S33
 S 5 | S 4
 T3N
 1966

Raise a mound of stone W. of the cor.

Land, rolling.
 Soil, rocky and sandy.
 Timber, moderate palo verde.
 Undergrowth, moderate cacti, cat claw, brush, and scattered creosote.

West, bet. secs. 5 and 32.

Over rolling land, through moderate palo verde.

21.00 Long spur, slopes NW.

29.60 Large draw, drains N. 50° W.

33.30 Jeep road, bears SE. and NW.

38.00 Spur, slopes N. 30° W.

39.60 Small draw, drains N. 10° W.

40.00 Point for the 1/4 sec. cor. of secs. 5 and 32.

Set the iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.

T4N R8E
 1/4 S32
 S 5
 T3N
 1966

55.00 Spur, slopes N. 30° W.

78.50 Draw, drains NW.

80.00 Point for the cor. of secs. 5, 6, 31 and 32.

Set the iron post 20 ins. in the ground, brass cap mkd.

T4N R8E
S31 | S32
 S 6 | S 5
 T3N
 1966

Raise a mound of stone W. of the cor.

Land, rolling.
 Soil, rocky and sandy.
 Timber, moderate palo verde.
 Undergrowth, moderate cacti, cat claw, brush and scattered creosote.

CHAINS

West, bet. secs. 6 and 31.

Over rolling land, through moderate palo verde.

0.90 Spur, slopes N.

3.30 Draw, drains N.

22.30 Jeep road, bears S. 60° E. and N. 60° W.

27.30 Draw, drains NW.

40.00 Point for the ¼ sec. cor. of secs. 6 and 31.

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T4N R8E
 ¼ S31
 S 6
 T3N
 1966

Raise a mound of stone W. of the cor.

59.80 Spur, slopes SW.

62.70 Wash, 20 lks. wide, 1 ft. deep, drains N. 50° W.

70.50 Wash, 60 lks. wide, 2 ft. deep, drains N.

72.40 Spur, slopes SE.

78.81 The Tp. cor. of Ts. 3 and 4 N., Rs. 7 and 8 E.

Land, rolling.
 Soil, rocky and sandy.
 Timber, moderate palo verde.
 Undergrowth, moderate cacti, cat claw, and scattered creosote.

Subdivision, T. 3 N., R. 8 E., Arizona

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., a 2½ in. iron post described in concurrent survey notes of the N. bdy., T. 2 N., R. 8 E.

N. 0°02' W., bet. secs. 33 and 34.

Over broken mountainous land, through scattered palo verde.

6.80 Large draw, drains SE.

10.24 Begin triangulation, topography as taken from U.S.G.S. topographic sheet STEWART MTN.

20.20 Ledgy point, projects E.; desc. over broken N. slope.

25.00 Leave mountainous land; enter gently rolling land.

29.00 Wash, drains N. 50° W.

40.00 Point for the ¼ sec. cor. of secs. 33 and 34.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T3N R8E $\frac{1}{2}$ S33 S34 1966</p> <p>from which</p> <p>STEWART DAM Triangulation Station bears N. 21°11' W., 27.73 chs. dist., monumented with a brass tablet 3 ins. in diam., set, mkd. and witnessed as described in the official record.</p> <p>The center of Stewart Mtn. Dam bears N. 43°26' W., 47.34 chs. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>End of triangulation.</p>	
64.50	Ridge, bears S. 83° E., and N. 83° W.	
70.70	<p>South bank of Saguaro Lake, bears S. 65° E. and N. 65° W.</p> <p>Point for the witness point bet. secs. 33 and 34.</p> <p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">W P T3N R8E S33 S34 1966</p>	
71.20	Water line of Saguaro Lake.	
80.00	<p>Point for the cor. of secs. 27, 28, 33 and 34, falls in Saguaro Lake, and was not monumented.</p> <p>Land, broken and rolling. Soil, rocky and sandy. Timber, moderate and scattered palo verde and mesquite. Undergrowth, dense cat claw and moderate cacti.</p> <hr/> <p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Across Saguaro Lake, by triangulation.</p>	
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 27 and 28, falls in Saguaro Lake and was not monumented.	
43.50	High water mark on N. bank of Saguaro Lake, bears S. 68° E. and N. 77°40' W.	
43.70	<p>Point for the witness point bet. secs. 27 and 28.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">W P T3N R8E S28 S27 1966</p> <p>Deposit glass in bottom of the hole.</p> <p>End of triangulation.</p>	
43.85	Paved access road, bears S. 78° E. and N. 78° W.	
45.90	Base of sheer ledge, about 200 ft. high, facing S.	

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

12

12.

CHAINS	
50.30	Top of rocky ridge, bears E. and W.
75.40	Wash, 50 lks. wide, 1 ft. deep, drains S. 50° E.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T3N R8E <u>S21 S22</u> <u>S28 S27</u> 1966 </div>
	Raise a mound of stone W. of the cor. Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde last half. Undergrowth, moderate cacti, cat claw and scattered creosote, last half.
	N. 0°02' W., bet. secs. 21 and 22. Over rolling land, through moderate palo verde.
10.60	Butcher Jones beach road, bears S. 58° E. and N. 66°15' W.
12.80	Four strand barbed wire fence, bears S. 85° E. and N. 85° W.
26.70	Spur, slopes SE.
40.00	Point for the ¼ sec. cor. of secs. 21 and 22. Set the iron post over an "X" chiseled in solid rock, mound with stone to top, brass cap mkd. <div style="text-align: center;"> T3N R8E ¼ <u>S21 S22</u> 1966 </div>
44.40	Draw, drains S. 15° E.
64.80	Spur, slopes S. 40° E.
76.90	Wash, 40 lks. wide, 1 ft. deep, drains S. 25° E.
79.30	Deep ravine, drains S. 50° E. for 100 lks., thence S. into main wash.
80.00	Point for the cor. of secs. 15, 16, 21 and 22. Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd. <div style="text-align: center;"> T3N R8E <u>S16 S15</u> <u>S21 S22</u> 1966 </div>
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush, scattered creosote and cat claw.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

CHAINS	
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land, through moderate palo verde.</p>
5.80	Ravine, drains SW.
28.20	Spur, slopes S. 35° E.
40.00	Point for the ¼ sec. cor. of secs. 15 and 16.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T3N R8E $\frac{1}{4}$ S16 S15 1966</p>
	Raise a mound of stone W. of the cor.
41.60	Small wash, drains S. 30° W.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T3N R8E <u>S 9 S10</u> S16 S15 1966</p>
	Raise a mound of stone W. of the cor.
	<p>Land, rolling.</p> <p>Soil, rocky and sandy.</p> <p>Timber, moderate palo verde.</p> <p>Undergrowth, moderate cacti, cat claw and scattered creosote.</p>
	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over rolling land, through moderate palo verde.</p>
1.40	Wash, 50 lks. wide, 1 ft. deep, drains S. 30° W.
29.60	Wash, 20 lks. wide, 1 ft deep, drains SW.
40.00	Point for the ¼ sec. cor. of secs. 9 and 10.
	<p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T3N R8E $\frac{1}{4}$ S 9 S10 1966</p>
64.10	Spur, slopes S. 50° W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.
	<p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T3N R8E <u>S 4 S 3</u> S 9 S10 1966</p>

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

14

14.

CHAINS

Land, rolling.
Soil, rocky and sandy.
Timber, moderate palo verde.
Undergrowth, moderate cacti, scattered creosote and cat
claw.

N. 0°08' W., bet. secs. 3 and 4.

Over rolling land, through moderate palo verde.

- 7.00 Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.
- 18.20 Spur, slopes S. 25° W.
- 40.00 Point for the ½ sec. cor. of secs. 3 and 4.

Set the iron post 14 ins. in the ground, mound with
stone to top, brass cap mkd.

T3N R8E
S 4 ½ S 3
1966

from which

A stock water tank bears N. 28°30' W., 16.62 chs.
dist.

A stock water tank bears N. 6°49' W., 24.80 chs.
dist.

- 46.15 Four strand barbed wire fence, bears S. 85° E. and
N. 85° W.
- 54.60 Four strand barbed wire fence, bears N. 38°18' E. and
S. 38°18' W.
- 62.80 Bladed road, bears N. 30° E. and SW.
- 66.80 Wash, 30 lks. wide, 2 ft. deep, drains S. 30° W.
- 79.98 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of
the Tp.

Land, rolling.
Soil, rocky and sandy.
Timber, moderate palo verde.
Undergrowth, moderate cacti, cat claw and brush.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy.
of the Tp., a 2½ in. iron post described in the con-
current survey notes of the N. bdy., T. 2 N., R. 8 E.

N. 0°02' W., bet. secs. 32 and 33.

Over rolling land, through moderate palo verde.

- 5.00 Old right bank of the Salt River, bears N. 70° E. and
S. 70° W.
 - 7.70 Power line, bears N. 58°55' E. and S. 58°55' W.
 - 8.00 Point for the witness point bet. secs. 32 and 33.
- Set the iron post 22 ins. in the ground, brass cap mkd.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

15.

CHAINS	
	<p style="text-align: center;">W P T3N R8E S32 S33 1966</p> <p>Raise a mound of stone W. of the iron post.</p>
8.60	Bush Highway (bladed road), bears N. 61°30' E. and S. 61°30' W.
8.70	Power line, bears N. 64°25' E. and S. 64°25' W.
26.80	Spur, slopes S. 60° E.
34.80	Draw, drains S. 35° E.
40.00	Point for the 1/4 sec. cor. of secs. 32 and 33.
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
	T3N R8E 1/4 S32 S33 1966
	Raise a mound of stone W. of the cor.
43.70	Spur, slopes E.
66.50	Wash, 30 lks. wide, 2 ft. deep, drains SE.
73.80	Spur, slopes W.
80.00	Point for the cor. of secs. 28, 29, 32 and 33.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T3N R8E S29 S28 S32 S33 1966
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw, brush and grass.
	Counting bearing and dist. from the true point for the cor. of secs. 27, 28, 33 and 34.
	S. 89°56' W., bet. secs. 28 and 33.
	Over Saguaro Lake.
7.60	Water line of Saguaro Lake, bears NW. and SE.
10.04	Point for the witness point bet. secs. 28 and 33.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	W P T3N R8E S28 S33 1966

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

16

16.

CHAINS	
	Thence, over rolling land.
16.30	Top of round knoll.
24.10	Water line of Saguaro Lake, bears N. and S.; thence over Saguaro Lake by triangulation.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33 falls in Saguaro Lake and was not monumented.
40.44	Water line on W. side of Saguaro Lake, bears N. and S.
40.94	Point for the witness point bet. secs. 28 and 33. Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd. W P T3N R8E <u>S28</u> S33
	End of triangulation; asc. over E. slope.
45.70	High spur, slopes SE.
48.00	Power line, bears S. 20° E. and N. 20° W.
48.10	Trail, parallels power line.
59.90	Ridge, bears N. and S.
67.70	Spur, slopes S.
72.40	Bush Highway, bears N. and S.
79.94	The cor. of secs. 28, 29, 32 and 33. Land, rolling, with Saguaro Lake entering into eastern portion. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti and brush.
	N. 0°02' W., bet. secs. 28 and 29.
	Over rolling land, through moderate palo verde.
2.40	Bladed road, bears irregularly E. and S. 50° W.
8.60	Top of knoll.
15.90	Wash, 15 lks. wide, 1 ft. deep, drains SE.
21.80	Spur, slopes SE.
30.30	Wash, 100 lks. wide, 1 ft. deep, drains SE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd. T3N R8E $\frac{1}{4}$ S29 S28 1966
	Raise a mound of stone W. of the cor.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

17.

CHAINS	
56.40	Spur, slopes N. 80° E.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T3N R8E <u>S20</u> <u>S21</u> <u>S29</u> <u>S28</u> 1966
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush, grass and scattered creosote.
	From the cor. of secs. 21, 22, 27 and 28.
	S. 89°59' W., bet. secs. 21 and 28.
	Over rolling land, through moderate palo verde.
3.10	Wash, 40 lks. wide, 1 ft. deep, drains S. 30° E.
26.40	Four strand barbed wire fence, bears S. 30° E. and N. 30° W.
39.50	Spur, slopes N.
39.94	Point for the ¼ sec. cor. of secs. 21 and 28.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T3N R8E ¼ <u>S21</u> <u>S28</u> 1966
	Raise a mound of stone N. of the cor.
51.30	Bush Highway (bladed road), bears N. and S. 15° W.
61.60	Large draw, drains irregularly SE.
79.88	The cor. of secs. 20, 21, 28 and 29.
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and scattered creosote.
	N. 0°02' W., bet. secs. 20 and 21.
	Over rolling E. slope, through moderate palo verde.
2.10	Spur, slopes E.
9.80	Spur, slopes S. 60° E.
28.70	Wash, drains E.
40.00	Point for the ¼ sec. cor. of secs. 20 and 21.

CHAINS	
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T3N R8E $\frac{1}{4}$ S20 S21 1966
	Raise a mound of stone W. of the cor.
63.20	Wash, 15 lks. wide, 2 ft. deep, drains E.
67.95	Four strand barbed wire fence, bears S. 50° E. and N. 50° W.
72.40	Bladed road, bears irregularly E. and N. 80° W.
79.00	Wash, 20 lks. wide, 1 ft. deep, drains E.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T3N R8E S17 S16 S20 S21 1966
	Raise a mound of stone W. of the cor.
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and scattered creosote.
	From the cor. of secs. 15, 16, 21 and 22.
	West, bet. secs. 16 and 21.
	Over rolling land, through moderate palo verde.
2.60	Wash, 25 lks. wide, 2 ft. deep, drains S. 30° E.
8.10	Ridge, bears S. 30° E. and N. 30° W.
33.50	Spur, slopes S. 10° W.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T3N R8E $\frac{1}{4}$ S16 S21 1966
	Raise a mound of stone N. of the cor.
41.10	Wash, 30 lks. wide, 1 ft. deep, drains S.
65.90	Old Bush Highway (bladed road), bears S. 10° E. and N. 10° W.
70.50	Wash, 20 lks. wide, 2 ft. deep, drains S. 10° E.
74.30	Bush Highway (paved), bears S. 14°45' E. and N. 14°45' W.
79.86	The cor. of secs. 16, 17, 20 and 21.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

CHAINS	
	<p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and scattered creosote.</p>
	<p>N. 0°02' W., bet. secs. 16 and 17.</p> <p>Over rolling land, through moderate palo verde.</p>
4.60	Spur, slopes S. 50° E.
21.16	Bush Highway, bears S. 14°45' E. and N. 14°45' W.
24.90	Wash, 20 lks. wide, 2 ft. deep, drains S. 15° E.
40.00	Point for the ¼ sec. cor. of secs. 16 and 17.
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T3N R8E ½ S17 S16 1966</p>
	<p>Raise a mound of stone W. of the cor.</p>
55.30	Wash, 10 lks. wide, 2 ft. deep, drains SW.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	<p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T3N R8E S 8 S 9 S17 S16 1966</p>
	<p>from which</p> <p style="padding-left: 40px;">Center of stock pond bears N. 30°13' E., 26.97 chs. dist.</p> <p style="padding-left: 40px;">Center of stock pond, bears N. 25°14' E., 31.84 chs. dist.</p>
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and creosote.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°59' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through moderate palo verde.</p>
1.00	Wash, 50 lks. wide, 1 ft. deep, drains S. 30° W.
3.90	Ridge, bears S. and N. 10° W.
10.50	Wash, 20 lks. wide, 1 ft. deep, drains S. 10° W.
24.10	Wash, 90 lks. wide, 1 ft. deep, drains S. 10° E.

CHAINS

37.00 Spur, slopes S. 15° E.

39.96 Point for the ¼ sec. cor. of secs. 9 and 16.
Set the iron post 22 ins. in the ground, brass cap mkd.

T3N R8E
¼ S 9
S16
1966

Raise a mound of stone N. of the cor.

45.10 Wash, 15 lks. wide, 1 ft. deep, drains S. 25° W.

63.40 Old Bush Highway (bladed road), bears N. 5° W. and S. 3° E.

69.50 Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.

79.92 The cor. of secs. 8, 9, 16 and 17.

Land, rolling.
Soil, rocky and sandy.
Timber, moderate palo verde.
Undergrowth, moderate cacti, cat claw and scattered creosote.

N. 0°02' W., bet. secs. 8 and 9.
Over rolling land, through moderate palo verde.

8.40 Wash, 20 lks. wide, 1 ft. deep, drains S. 65° W.

26.00 Ridge, bears N. 70° E. and S. 70° W.

40.00 Point for the ¼ sec. cor. of secs. 8 and 9.
Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T3N R8E
¼
S 8 | S 9
1966

Raise a mound of stone W. of the cor.

55.40 Ridge, bears N. 30° E. and S. 30° W.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.
Set the iron post 22 ins. in the ground, brass cap mkd.

T3N R8E
S 5 | S 4
S 8 | S 9
1966

Raise a mound of stone W. of the cor.

Land, rolling.
Soil, rocky and sandy.
Timber, moderate palo verde.
Undergrowth, moderate cacti, brush and scattered creosote and cat claw.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

21.

CHAINS	
	From the cor. of secs. 3, 4, 9 and 10.
	West, bet. secs. 4 and 9.
	Over rolling land, through moderate palo verde.
2.80	Wash, 10 lks. wide, 1 ft. deep, drains SW.
26.20	Wash, 60 lks. wide, 1 ft. deep, drains S.
36.70	Old Bush Highway, bears N. 9°45' E. and S. 9°45' W.
39.97	Point for the ¼ sec. cor. of secs. 4 and 9.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T3N R8E ¼ S 4 S 9 1966
	Raise a mound of stone N. of the cor.
44.50	Wash, 10 lks. wide, 1 ft. deep, drains S.
52.40	Ridge, bears N. and SE.
64.30	Wash, 10 lks. wide, 1 ft. deep, drains S.
67.70	Dirt road, bears N. and S.
72.80	Wash, 30 lks. wide, 1 ft. deep, drains S.
79.94	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush, scattered creosote and cat claw.
	N. 0°09' W., bet. secs. 4 and 5.
	Over rolling land, through moderate palo verde.
29.70	Ridge, bears NE. and SW.
40.00	Point for the ¼ sec. cor. of secs. 4 and 5.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T3N R8E ¼ S 5 S 4 1966
	Raise a mound of stone W. of the cor.
57.70	Beeline Highway (Arizona State Hwy. 87), bears N. 47°48' E. and S. 48°34' W.
63.50	Ridge, bears N. 30° E. and S. 30° W.
77.80	Dirt road, bears N. 55°35' E. and S. 55°35' W.
79.97	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.

CHAINS	
	<p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and scattered creosote.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., a 2½ in. iron post described in the concurrent survey notes of T. 2 N., R. 8 E.</p> <p>N. 0°03' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, through moderate palo verde.</p>
0.30	Power line, bears E. and W.
1.00	Telephone line, bears E. and W.
10.00	Asc. over heavy rolling S. slope.
40.00	Point for the ¼ sec. cor. of secs. 31 and 32.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p>T3N R8E ½ S31 S32 1966</p>
	Raise a mound of stone W. of the cor.
42.30	High ridge, bears E. and W.
54.50	Bottom of large draw, 8.00 chs. wide, drains W.
58.00	Wash, 30 lks. wide, 1 ft. deep, drains W.
71.60	Spur, slopes W.
80.00	Point for the cor. of secs. 29, 30, 31 and 32.
	Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
	<p>T3N R8E S30 S29 S31 S32 1966</p>
	<p>Land, heavy rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush, scattered cat claw and brigham tea.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°59' W., bet. secs. 29 and 32.</p> <p>Over rolling land, through moderate palo verde.</p>
17.40	Small draw, drains S. 60° E.
30.90	Spur, slopes S.
34.40	Wash, 20 lks. wide, 2 ft. deep, drains S. 30° E.
40.02	Point for the ¼ sec. cor. of secs. 29 and 32.

CHAINS		
	<p>Set the iron post over an "X" chiseled in solid rock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T3N R8E $\frac{1}{4}$ <u>S29</u> S32 1966</p>	
47.20	Rocky spur, slopes N.; continue along rolling N. slope.	
53.30	Spur, slopes N.	
79.00	Draw, drains N. 10° W.	
80.04	The cor. of secs. 29, 30, 31 and 32.	
	<p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered cat claw.</p>	
	<p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Over rolling land, through moderate palo verde.</p>	
9.00	Spur, slopes NW.	
16.00	Draw, drains S.	
24.00	Spur, slopes S.; desc. over steep SW. slope.	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.	
	<p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T3N R8E $\frac{1}{4}$ <u>S30</u> S31 1966</p>	
	Continue over gently rolling land.	
69.40	Wash, 10 lks. wide, 1 ft. deep, drains NW.	
79.28	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., a 2½ in. iron post described in the concurrent survey notes of T. 3 N., R. 7 E.	
	<p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw and scattered creosote.</p>	
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through moderate palo verde; desc. over N. slope.</p>	
11.00	Enter gently rolling land.	
34.00	Wash, 25 lks. wide, 1 ft. deep, drains W.	

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

24

24.

CHAINS	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30.
	Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.
	T3N R8E $\frac{1}{4}$ S30 S29 1966
	Asc. over rolling SW. slope of Stewart Mtn.
64.20	Spur, slopes SW.
74.70	Slope changes to rolling W.
78.00	Spur, slopes W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.
	T3N R8E S19 S20 S30 S29 1966
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered cat claw.
From the cor. of secs. 20, 21, 28 and 29.	
S. 89°59' W., bet. secs. 20 and 29.	
Over steep E. slope of Stewart Mtn., through moderate palo verde.	
By triangulation.	
27.50	Top of Stewart Mtn., bears N. and S.; end of triangulation. Desc. over W. slope.
39.98	Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.
	Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	T3N R8E $\frac{1}{4}$ S20 S29 1966
	from which
	STEWART MTN. Triangulation Station bears S. 86°12' W., 15.34 chs. dist., monumented by a brass cap, 3 ins. diam., set in cement.
42.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° E.; asc. over E. slope.
55.00	Top of Stewart Mtn., bears N. and S. 15° W.; by triangulation, desc. over steep broken W. slope.

CHAINS	
79.96	<p>The cor. of secs. 19, 20, 29 and 30. End of triangulation.</p> <p>Land, mountainous. Soil, rocky. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered cat claw.</p>
	<p>N. 89°58' W., bet. secs. 19 and 30.</p>
	<p>Desc. over rolling land, through moderate palo verde.</p>
36.30	<p>Wash, 10 lks. wide, 1 ft. deep, drains N. 50° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 30.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T3N R8E ¼ $\frac{S19}{S30}$ 1966</p>
	<p>Raise a mound of stone N. of the cor.</p>
61.80	<p>Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.</p>
76.90	<p>Wash, 25 lks. wide, 1 ft. deep, drains S. 10° E.</p>
79.31	<p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., a 2½ in. iron post described in the concurrent survey notes of T. 3 N., R. 7 E.</p>
	<p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered cat claw.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p>
	<p>N. 0°03' W., bet. secs. 19 and 20.</p>
	<p>Over steep W. slope of Stewart Mtn., through moderate palo verde.</p>
0.90	<p>Draw, drains W.</p>
18.90	<p>Saddle of ridge, bears N. 80° E. and W.; desc. over steep N. slope.</p>
33.60	<p>Wash, 10 lks. wide, 2 ft. deep, drains W.; asc. over steep S. slope.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 19 and 20.</p>
	<p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T3N R8E ¼ $\frac{S19}{S20}$ 1966</p>
44.50	<p>Spur, slopes SW.</p>

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

26

26.

CHAINS	
45.10	Spur, slopes W.; desc. over steep N. slope.
58.00	Enter gently rolling land.
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
	T3N R8E <u>S18</u> <u>S17</u> S19 S20 1966
	Land, mountainous to gently rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered cat claw.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°58' W., bet. secs. 17 and 20.
	Over rolling land, through moderate palo verde.
3.20	Wash, 20 lks. wide, 1 ft. deep, drains S. 50° E.
15.10	Four strand barbed wire fence, bears S. 50° E. and N. 50° W.
20.20	Wash, 15 lks. wide, 2 ft. deep, drains N. 65° E.
27.00	Spur, slopes SE.
40.00	Point for the ¼ sec. cor. of secs. 17 and 20.
	Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.
	T3N R8E ¼ <u>S17</u> S20 1966
43.10	Spur, slopes N.
73.30	Draw, drains NW.
78.50	Draw, drains N.
80.00	The cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, cat claw, brush and scattered creosote.
	N. 89°59' W., bet. secs. 18 and 19.
	Over rolling land, through moderate palo verde.
8.50	Draw, drains N. 40° W.
25.70	Wash, 30 lks. wide, 1 ft. deep, drains SW.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

27.

CHAINS

- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
Set the iron post 24 ins. in the ground, brass cap mkd.
- T3N R8E
 $\frac{1}{4}$ $\frac{S18}{S19}$
1966
- Raise a mound of stone N. of the cor.
- 50.80 Four strand barbed wire fence, bears N. 50° E. and S. 50° W.
- 62.90 Wash, 10 lks. wide, 2 ft. deep, drains S.
- 79.28 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., a 2 $\frac{1}{2}$ in. iron post described in the concurrent survey notes of T. 3 N., R. 7 E.
- Land, rolling.
Soil, rocky and sandy.
Timber, moderate palo verde.
Undergrowth, moderate cacti, cat claw and scattered creosote.
-
- From the cor. of secs. 17, 18, 19 and 20.
N. 0°03' W., bet. secs. 17 and 18.
Over rolling land, through moderate palo verde.
- 7.50 Wash, 10 lks. wide, 1 ft. deep, drains irregularly W.
- 12.60 Spur, slopes S. 70° W.
- 23.50 Wash, 20 lks. wide, 1 ft. deep, drains SW.; asc. over SE. slope.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.
Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.
- T3N R8E
 $\frac{1}{4}$
S18 | S17
1966
- 46.40 Four strand barbed wire fence, bears S. 65° E. and N. 50° W.
- 55.40 Ridge, bears NE. and W.
- 80.00 Point for the cor. of secs. 7, 8, 17 and 18.
Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.
- T3N R8E
S 7 | S 8
S18 | S17
1966

28

CHAINS

Land, rolling.
Soil, rocky and sandy.
Timber, moderate palo verde.
Undergrowth, moderate cacti, brush and scattered cat
claw.

From the cor. of secs. 8, 9, 16 and 17.

S. 89°59' W., bet. secs. 8 and 17.

Over rolling land, through moderate palo verde.

8.60 Spur, slopes S.

20.20 Dirt road, bears NE. and SW.

23.00 Wash, 25 lks. wide, 1 ft. deep, drains S. 50° W.

24.90 Bush Highway, bears S. 43° E. and N. 20° W.

27.20 Wash, 50 lks. wide, 1 ft. deep, drains S. 65° W.

40.00 Point for the ¼ sec. cor. of secs. 8 and 17.

Set the iron post over an "X" chiseled in solid rock,
mound with stone to top, brass cap mkd.

T3N R8E

¼ $\frac{S 8}{S17}$

1966

Asc. over steep E. slope.

47.60 Top of knoll; desc. over steep W. slope.

57.10 Wash, 20 lks. wide, 2 ft. deep, drains S., thence over
rolling land.

71.20 Low ridge, bears N. and S.

80.00 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.
Soil, rocky and sandy.
Timber, moderate palo verde.
Undergrowth, moderate cacti, brush and scattered cat
claw.

N. 89°58' W., bet. secs. 7 and 18.

Over rolling land, through moderate palo verde.

40.00 Point for the ¼ sec. cor. of secs. 7 and 18.

Set the iron post 24 ins. in the ground, brass cap mkd.

T3N R8E

¼ $\frac{S 7}{S18}$

1966

Deposit broken glass in bottom of hole.

The cor. is set in fence line bearing S. 67°45' E. and
N. 66°26' W.

BOOK 4802

Subdivision, T. 3 N., R. 8 E., Arizona

CHAINS	
41.60	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.
42.80	Four strand barbed wire fence, bears N. 36°45' E. and S. 37°20' W.
46.50	Beeline Highway (Arizona State Hwy. 87), bears N. 36° E. and S. 36° W.
50.10	Four strand barbed wire fence, bears N. 36° E. and S. 36° W.
73.30	Wash, 35 lks. wide, 2 ft. deep, drains S. 10° E.
79.18	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., a 2½ in. iron post described in the concurrent survey notes of T. 3 N., R. 7 E.
	<p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote, brush and scattered cat claw.</p>
	<p>From the cor. of secs. 7, 8, 17 and 18.</p>
	<p>N. 0°03' W., bet. secs. 7 and 8.</p>
	<p>Over rolling land, through moderate palo verde.</p>
27.70	Spur, slopes N. 80° W.
35.00	Wash, 5 lks. wide, 2 ft. deep, drains S. 80° W.
40.00	Point for the ¼ sec. cor. of secs. 7 and 8.
	<p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p>
	<p>T3N R8E ¼ S 7 S 8 1966</p>
51.10	Spur, slopes N. 60° W.
64.00	Wash, 10 lks. wide, 6 ins. deep, drains S. 70° W.
68.80	Beeline Highway (Arizona State Hwy. 87), bears NE. and SW.
80.00	Point for the cor. of secs. 5, 6, 7 and 8.
	<p>Set the iron post 18 ins. in the ground, brass cap mkd.</p>
	<p>T3N R8E S 6 S 5 S 7 S 8 1966</p>
	<p>Raise a mound of stone W. of the cor.</p>
	<p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush and scattered creosote and cat claw.</p>

CHAINS

From the cor. of secs. 4, 5, 8 and 9.

N. 89°59' W., bet. secs. 5 and 8.

Over rolling land, through moderate palo verde.

2.00 Small wash, drains S.

11.00 Spur, slopes S.

21.00 Wash, 15 lks. wide, 2 ft. deep, drains S.

33.80 Spur, slopes S.

40.00 Point for the ¼ sec. cor. of secs. 5 and 8.

Set the iron post 4 ins. in the ground, mound with stone to top, brass cap mkd.

T3N R8E

¼ $\frac{S\ 5}{S\ 8}$

1966

52.60 Bush Highway, bears S. 15° E. and N. 15° W.

55.30 Dirt road, bears N. and S.

68.40 Beeline Highway (Arizona State Hwy. 87), bears N. 45°20' E. and S. 45°20' W.

70.20 Dirt road, bears NE. and SW.

72.70 Ridge, bears N. 15° E. and S. 15° W.

80.00 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.

Soil, rocky and sandy.

Timber, moderate palo verde.

Undergrowth, moderate cacti, brush and scattered creosote and cat claw.

N. 89°57' W., bet. secs. 6 and 7.

Over rolling land, through moderate palo verde.

1.60 Wash, 10 lks. wide, 1 ft. deep, drains SW.

24.60 Wash, 30 lks. wide, 1 ft. deep, drains S. 10° W.

40.00 Point for the ¼ sec. cor. of secs. 6 and 7.

Set the iron post 24 ins. in the ground, brass cap mkd.

T3N R8E

¼ $\frac{S\ 6}{S\ 7}$

1966

Raise a mound of stone N. of the cor.

43.40 Wash, 10 lks. wide, 1 ft. deep, drains S.

60.20 Wash, 20 lks. wide, 1 ft. deep, drains S.

71.10 Wash, 5 lks. wide, 1 ft. deep, drains S. 10° E.

CHAINS		
79.07	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., a 2½ in. iron post described in the concurrent survey notes of T. 3 N., R. 7 E.</p> <p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, creosote and brush.</p>	
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°10' W., bet. secs. 5 and 6.</p> <p>Over rolling land, through moderate palo verde.</p>	
17.30	Dirt road, bears S. 40° W. and N. 35° E.	
28.30	Dirt road, bears S. 25° E. and N. 80° W.	
28.50	Spur, slopes N. 80° W.	
40.00	<p>Point for the ¼ sec. cor. of secs. 5 and 6.</p> <p>Set the iron post 12 ins. in the ground, mound with stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">T3N R8E ¼ S 6 S 5 1966</p>	
49.30	Wash, 10 lks. wide, 1 ft. deep, drains W.	
62.80	Dirt road, bears N. 80° E. and S. 70° W.	
79.99	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <p>Land, rolling. Soil, rocky and sandy. Timber, moderate palo verde. Undergrowth, moderate cacti, brush, scattered creosote and cat claw.</p>	
	<p>General Description</p>	
	<p>The land surveyed in T. 3 N., R. 8 E., located in the Tonto National Forest, varies in elevation from 1400 feet in section 31 to 2988 feet above sea level in sections 20 and 29 at the top of Stewart Mountain. The soil at the higher elevations is primarily rocky and exposed limestone, with sand and rock at the lower elevations.</p> <p>Palo verde and desert undergrowth, with some native grasses and brush, afford limited graze for livestock, which is one of the many uses in the township.</p> <p>Saguaro Lake, located in the southeast portion of the township extending westerly into sections 28 and 33, provides, in addition to power and water storage, excellent recreational activities.</p>	

BOOK 4802

Township 3 North, Range 8 East
Gila and Salt River Meridian, Arizona

32

32.

CHAINS

The Beeline Highway enters the township in section 18, cutting diagonally across the northwest corner. Bush Highway enters the township in section 32, following along the Salt River into section 33, extending northerly through the township, joining the Beeline Highway in section 5. Access roads leading to picnic and recreation areas in sections 27, 28 and 33, branch off from Bush Highway.

BOOK 4802

CERTIFICATE OF SURVEY

We, Wallace R. Ott, Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9 day of September, 1965, we have surveyed the east and north boundaries and the west half of the subdivisioal lines of Township 3 North, Range 8 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~me~~^{us} and under ~~my~~^{our} direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 18, 1966 (Date)

Wallace R. Ott (Cadastral Surveyor)

November 18, 1966 (Date)

Gary T. Oviatt (Survey Technician) Surveying

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date JUL 25 1967

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the survey of the east and north boundaries and the west half of the subdivisioal lines of Township 3 North, Range 8 East of the Gila and Salt River Meridian in the State of Arizona

executed by Wallace R. Ott, Cadastral Surveyor, and Gary T. Oviatt, Survey Technician, having been critically examined and found correct, are hereby approved.

DEC 21 1967 (Date)

R. E. Brown Acting (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)