

1A

BOOK 4804

INDEX DIAGRAM

Township 17 North, Range 9 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1

3
2
2
1

BOOK 4804

Township 17 North, Range 9 East
Gila and Salt River Meridian, Arizona

1.B

CHAINS

The boundaries and subdivisional lines were surveyed in 1879 by J. L. Harris. The north boundary was retraced in 1883 by O. D. Wheeler. The south boundary, the 4th Standard Parallel North, was retraced in 1883 by J. B. McLaughlin and the standard corner of secs. 33 and 34 was reestablished by Arizona Highway Department, Bureau of Public Roads, in 1936, a copy of the data on file at the Land Office, Phoenix, Arizona.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Remonumentation, T. 17 N., R. 9 E., Arizona

The cor. of secs. 19, 24, 25 and 30, T. 17 N., Rs. 9 and 10 E., monumented by an old mound of stone and verified by record course and distance from the original bearing trees

A pine, 30 ins. diam., bears N. $64\frac{1}{2}^{\circ}$ E., 48 lks. dist., mkd. with part of scribe mks. visible

A pine, 34 ins. diam., bears South, 66 lks. dist., mkd. with an overgrown blaze

A pine, 30 ins. diam., bears N. 53° W., 40 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone to top, brass cap mkd.

T17N
R9E R10E
S24 | S19
S25 | S30
1966

Cor. is on an E. slope in heavy timber and undergrowth, about 12.00 chs. N. of a track road bearing E. and W.

The SC of secs. 32 and 33, T. 17 N., R. 9 E., monumented by a rotted wooden post set in an old mound of stone, from which the original bearing trees

A pine stump, bears N. 62° E., 65 lks. dist.

A pine, 25 ins. diam., bears N. 61° W., 41 lks. dist., with parts of scribe mks. visible

At the cor. point

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone to top, brass cap mkd.

SC
T17N R9E
S32 | S33
S1
T16N
1966

from which

A pine, 14 ins. diam., bears N. 13° E., 28 lks. dist., mkd. SCT17NR9ES33 BT

Cor. is on a rocky E. slope about 4.00 chs. W. of a track road, bearing N. and S.

The cor. of secs. 25, 26, 35 and 36, monumented by an old wooden post firmly set in a mound of stone, plainly mkd. on 3 sides, from which the original bearing trees

A pine, 24 ins. diam., bears N. 31½° W., 20 lks. dist., mkd. with an overgrown blaze

A pine, 30 ins. diam., bears S. 0°30' W., 17 lks. dist., with parts of scribe mks. visible

A pine stump, bears S. 67½° E., 13 lks. dist., mkd. TXVIINRIXEXXXVI

A pine, 22 ins. diam., bears N. 72½° E., 49 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T17N R9E
S26 | S25
S35 | S36
1966

from which

A pine, 8 ins. diam., bears S. 81° W., 74 lks. dist., mkd. T17NR9ES35 BT

Raise a mound of stone W. of the iron post.

Bury the original corner post alongside the iron post.

Cor. is on a S. slope in heavy timber 1.20 chs. N. of a track road, bearing E. and W.

The ¼ sec. cor. of secs. 25 and 26, monumented by a mound of stone and verified by record course and dist. from the remains of the original bearing trees

A pine stump, bears S. 79° E., 1.04 chs. dist., mkd. ¼S on fallen tree

A pine stump hole, bears N. 86° W., 23 lks. dist., mkd. ¼S on fallen tree

At the cor. point

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T17N R9E

½
S26 | S25
1966

from which

A pine, 7 ins. diam., bears N. 51° E., 17 lks. dist., mkd. ½S25 BT

A pine, 10 ins. diam., bears N. 9½° W., 9 lks. dist., mkd. T17NR9E½S26 BT

Raise a mound of stone W. of the iron post.

Cor. is on an E. slope in heavy timber.

The cor. of secs. 23, 24, 25 and 26, monumented by an old mound of stone and verified by record course and dist. from the remains of the original bearing trees

A pine, 34 ins. diam., bears S. 59½° E., 36 lks. dist., mkd. with an overgrown blaze

A fallen pine, bears S. 88° W., 75 lks. dist.

A pine, 18 ins. diam., bears N. 17° W., 54 lks. dist., mkd. TXVIINR1XEXXIII

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone to top, brass cap mkd.

T17N R9E

S23 | S24
S26 | S25
1966

from which

An oak, 11 ins. diam., bears S. 22° W., 50 lks. dist., mkd. T17NR9ES26BT

Cor. is on a rocky W. slope in heavy timber.

The ¼ sec. cor. of secs. 33 and 34, monumented by an iron pipe, 1½ ins. diam., and a mound of stone, from which the original bearing trees

A pine, 30 ins. diam., bears East, 39 lks. dist., mkd. ½S

A pine stump, bears S. 87° W., 79 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, collar of stone to top, brass cap mkd.

T17N R9E

½
S33 | S34
1966

4

CHAINS

Cor. is on nearly level land, about 10.00 chs. W. of road from Flagstaff to Happy Jack.

The cor. of secs. 27, 28, 33 and 34, monumented by an old mound of stone and verified by record course and dist. from the original bearing trees

A pine, 26 ins. diam., bears N. 48° E., 64 lks. dist., mkd. with an overgrown blaze

A pine, 24 ins. diam., bears S. 32° E., 56 lks. dist., mkd. with an overgrown blaze

A pine stump, bears S. 38° W., 50 lks. dist., mkd. with XXXIII visible

A pine, 20 ins. diam., bears N. 15° W., 112 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T17N R9E	
S28	S27
S33	S34
1966	

Cor. is on a S. slope in moderate timber about 10.00 chs. W. of the road from Flagstaff to Happy Jack.

The cor. of secs. 28, 29, 32 and 33, monumented by a wooden post, 3 ft. long, 4 ins. square, firmly set in a mound of stone, plainly mkd. and notched, from which the remains of the original bearing trees

A pine stump, bears S. 49° E., 32 lks. dist., mkd. with an overgrown blaze

A pine stump, bears S. 51° W., 27 lks. dist.

A fallen pine, bears N. 19° W., 37 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone to top, brass cap mkd.

T17N R9E	
S29	S28
S32	S33
1966	

from which

A pine, 18 ins. diam., bears N. 68½° E., 46 lks. dist., mkd. T17NR9ES28 BT

A pine, 20 ins. diam., bears N. 51° W., 38 lks. dist., mkd. T17NR9ES29 BT

6

BOOK 4804

CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 28 day of March, 19 66, I have remonumented cadastral survey corners in Township 17 North, Range 9 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 18, 1966

(Date)

Wallace R. Ott

(Cadastral Surveyor)

(Supervisory Surveying Technician)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumented cadastral survey corners in Township 17 North, Range 9 East, Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician, having been critically examined and found correct, are hereby approved.

FEB 27 1968

(Date)

R. E. Brown

(Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)