

BOOK 4805

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

of

FORT APACHE INDIAN RESERVATION BOUNDARY

in

Township 11 North, Range 15 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Wallace R. Ott, Supervisory Surveying Technician

Under special instructions dated March 28, 19 66, which provided for the surveys included under Group Number 446, approved March 29, 1966, and assignment instructions dated June 28, 19 66.

Survey commenced July 6, 19 66

Survey completed October 25, 19 66

BOOK 4805 INDEX DIAGRAM

Township 11 North, Range 15 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
29 (119 1/2 M)	28	27	26	25	24
31 3 2 2 2 1 FORT APACHE INDIAN RES.	32 1	33 (AP931)	34	35	36

CHAINS

The Fort Apache Indian Reservation Boundary, through Township 11 North, Range 15 East, was surveyed in 1887 by Wallace, resurveyed in 1906 by J. B. Wright and partially resurveyed in 1937 by H. M. Muscott.

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on March 29, 1966 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Remonumentation, Fort Apache Indian Reservation
Boundary, T. 11 N., R. 15 E., Arizona


Angle point 931, monumented by a pine stump, partly rotted away, mkd. APNBWMIR 931 on SW. face and BMFR on NE. face, from which the original accessories

A mound of stone, 4 ft. base, bears S. 56° E.,
12 lks. dist.

A mound of stone, 4 ft. base, bears S. 72° W.,
48 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground (alongside original corner), mound of stone to top, brass cap mkd.



The angle point is on the point of a spur sloping sharply S.

The 119 mile cor., monumented by a sandstone in place, 15 x 20 x 40 ins. above ground, mkd. with an X and part of chisel mks. visible, from which the original bearing trees

A spruce, 22 ins. diam., bears N. 83½° E., 28 lks. dist., mkd. with an overgrown blaze, I remark 119MBT

A juniper, 28 ins. diam., bears S. 30° E., 22 lks. dist., mkd. NBWMIR 119M

A juniper, 28 ins. diam., bears S. 41¾° W., 35 lks. dist., mkd. NBWMIR 119M

A juniper, 30 ins. diam., bears N. 51° W., 39 lks. dist., mkd. NBWMIR 119M

Cor. is on a rocky SW. slope in moderate timber.

BOOK 4805

Remonumentation, Fort Apache Indian Reservation
Boundary, T. 11 N., R. 15 E., Arizona

2

2.

CHAINS

Angle point 932, monumented by a pine stump and verified by record course and distance from angle point 933.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground (alongside original corner), mound of stone to top, brass cap mkd.

T11N
R15E
S31
AP932
FAIR
1966

The angle point is on a S. slope in moderate timber, 1.50 chs. S. of a track road bearing E. and W. and 1.00 chs. N. of a fence bearing SE. and W.

Angle point 933, monumented by a sandstone, 6 x 15 x 30 ins., firmly set, mkd. with X on top, APNBWMIR 933 on S. face and BMFR on N. face, from which the remains of the original bearing trees

A fallen pine, bears N. 33° W., 65 lks. dist., mkd. AP933BT

A fallen pine, bears N. 10° W., 42 lks. dist., mkd. AP933 BT

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T11N
R15E
S31
AP933
FAIR
1966

Raise a mound of stone E. of cor.

Deposit the original corner stone in the mound E. of cor.

The angle point is in thick timber 40 lks. S. of a fence bearing E. and W.

Angle point 934, monumented by a cairn, 4 ft. high, 4 ft. diam., with a sandstone, 12 x 18 x 24 ins., firmly set on top of mound, mkd. APNBWMIR 934 on S. face and BMFR on N. face, from which an original bearing tree

A pine, 8 ins. diam., bears N. 38° W., 34 lks. dist., mkd. with overgrown blaze

from the cor.

A pine, 13 ins. diam., bears S. 8° E., 42 lks. dist., mkd. AP934FAIRBT

A pine, 18 ins. diam., bears N. 20° W., 42 lks. dist., mkd. AP934BT

BOOK 4805

Remonumentation, Fort Apache Indian Reservation
Boundary, T. 11 N., R. 15 E., Arizona

3.

CHAINS

The angle point is on a rocky W. slope in moderate timber.

The 119½ mile cor., monumented by a sandstone, 5 x 28 x 32 ins., (large mound of stone W.), mkd. WMIR119½M on NW. cor., from which the original bearing trees

A pine, 16 ins. diam., bears S. 64° E., 24 lks. dist., mkd. with an overgrown blaze

A pine, 22 ins. diam., bears S. 62½° W., 46 lks. dist., mkd. with an overgrown blaze

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, mound of stone to top, brass cap mkd.

T11N
R15E
S31

NW COR
119½M
FAIR
1966

from which

A pine, 12 ins. diam., bears N. 60° E., 46 lks. dist., mkd. NWCOR119½MBT

A pine, 14 ins. diam., bears N. 51½° W., 69 lks. dist., mkd. NWCOR119½MBT

Bury the original corner stone alongside the iron post.

Cor. is on E. rim of a canyon bearing N. and SE.

BOOK 4805
CERTIFICATE OF SURVEY

I, Wallace R. Ott, HEREBY CERTIFY upon honor that,
in pursuance of special instructions bearing date of the 28th day of March, 1966,
I have remonumented a portion of the cadastral survey corners of the
Fort Apache Indian Reservation Boundary in Township 11 North, Range 15 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by me and under my direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

November 18, 1966
(Date)

Wallace R. Ott
(Cadastral Surveyor)
Supervisory Surveying Technician

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAY 26 1967

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumentation of a portion of the cadastral
survey corners of the Fort Apache Reservation Boundary in T. 11 N., R. 15 E.,
of the Gila and Salt River Meridian, Arizona,

executed by Wallace R. Ott, Supervisory Surveying Technician,
having been critically examined and found correct, are hereby approved.

FEB 27 1968
(Date)

R.E. Brown
(Chief, Division of Engineering)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Engineering)~~