

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of

A Portion of the

SOUTH BOUNDARY

of

Township 1 North, Range 14 East

and a

DEPENDENT RESURVEY

of the

BOUNDARIES

and

SUBDIVISION

of Section 2

Township 1 South, Range 14 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Kenneth D. Herman, Cadastral Surveyor

Under special instructions dated May 2, 19 67, which provided for the surveys supplemental special instructions dated and approved November 30, 1967 included under Group Number 495, approved May 3, 1967, and assignment instructions dated May 4, 19 67.

Survey commenced May 15, 19 67

Survey completed December 26, 19 67

1A

BOOK 4822

INDEX DIAGRAM

Township 1 South, Range 14 East
2 3 4

6	5	4	3	16- 21 8 2 11- 15 6	5 1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4822

Township 1 North, Range 14 East
Gila and Salt River Meridian, Arizona

CHAINS

The south boundary of Township 1 North, Range 14 East (the Gila and Salt River Base Line) was surveyed in 1899, by A. T. Colton, and independently resurveyed in 1906, by P. Contzen, who also surveyed Township 1 South, Range 14 East, the same year. The Homestead in sec. 2, Township 1 South, Range 14 East, patented February 15, 1915, was surveyed in 1948, by a registered civil engineer, Arizona, and a plat of his survey is on file in the Gila County Courthouse, Globe, Arizona.

The following field notes are those of a dependent resurvey of the east half-mile of the south boundary of sec. 34, the south boundary of sec. 35, and the west half-mile of the south boundary of sec. 36, Township 1 North, Range 14 East; and the east, west, and south boundaries of sec. 2, Township 1 South, Range 14 East, designed to restore the corners according to the best available evidence, and survey of subdivisions in sec. 2, necessary to delineate the Federal land and establish Lots 10 and 11.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated May 2, 1967, and Supplemental Special Instructions dated November 30, 1967.

Only the true line bearings and distances for the surveyed lines are given herein. Testimony by local land owners was accepted, in addition to direct evidence, to verify the positions of local survey corners. Unless otherwise indicated, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, and with a brass cap riveted to the top.

The geographic position of the southeast corner of sec. 2, as scaled from U.S. Geological Quadrangle, Pinal Ranch, 7.5 minute series, is: Latitude, 33°32' North, and Longitude, 110°54'04" West.

The mean magnetic declination was found to be 12°45' East.

Dependent Resurvey of a Portion of the South Boundary
of Township 1 North, Range 14 East

Reestablishment of the Survey
Executed by P. Contzen in 1906

The standard ¼ sec. cor. of sec. 34, monumented by a granite stone, 14 x 10 x 6 ins., firmly set in a mound of stone, mkd. SC ¼ on the N. face.

At the corner point

Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.

S C
T1N R14 E
¼ S 34

1967

BOOK 4822

2.

Dep. Resurvey of Portion of S. Bdy., T. 1 N., R. 14 E., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 5 ins. diam., bears N. 0°15' W., 16½ lks. dist., mkd. SC ¼ S 34 BT.</p> <p>Corner is located 9 lks. N. of a fence bearing E. and W.</p> <p>Deposit the orig. cor. stone in the mound of stone.</p> <p>N. 89°58' E., along the S. bdy. of sec. 34.</p> <p>Descend E. slope, over rolling land that has been bladed for mineral exploration.</p>
1.20	Bladed mine road, bears irregularly N. and S.
5.20	Bladed mine road, bears N. 10° W. and S. 10° E.; asc. W. slope.
6.10	Entrance to mine tunnel, bears North, 20 lks. dist.
6.70	Power line, bears N. 45° E. and S. 45° W.
7.70	Power line, bears N. 45° E. and S. 45° W.
7.70	Bladed mine road, bears N. 10° W. and S. 10° E.
9.20	Bladed mine road, bears irregularly NE. and SW.
11.40	Top of hill, desc. E. slope.
11.80	Fence, bears N. 22° W. and S. 22° E. for 10 lks. to cor. of fences bearing N., S., E. and W.
13.30	Bladed mine road, bears N. 20° E. and S. 20° W.
13.70	Bladed mine road, bears irregularly N. and S.
16.08	The closing cor. of secs. 2 and 3, T. 1 S., R. 14 E., hereafter described.
17.20	Draw, drains N. for approx. 2 chs., thence SE.; leave mine area, asc. over NW. slope.
29.40	Spur, slopes S.
32.60	Power line, bears N. and S.
34.20	Bladed road, bears N. 5° W. and S. 5° E.; cattle guard, bears S. 5° E., 100 lks. dist.
34.50	Fence, bears N. 5° W. and S. 5° E.
35.50	Wash, 10 lks. wide, 1 ft. deep, drains S.; asc. W. slope.
39.97	<p>The standard cor. of secs. 34 and 35, monumented by a granite stone, 12 x 10 x 5 ins., firmly set in a mound of stone, mkd. SC on the N. face, with 2 notches on the E. edge, and 4 notches on the W. edge.</p> <p>At the corner point</p>

BOOK 4822

3.

Dep. Resurvey of Portion of S. Bdy., T. 1 N., R. 14 E., Arizona

CHAINS		
	<p>Set the iron post 8 ins. in the ground, to bedrock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">S C T1N R14E <u>S34 S 35</u></p> <p style="text-align: center;">1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 54° W., 46 lks. dist., mkd. BT.</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears N. 49° W., 35 lks. dist., mkd. T1N R14E S 34 BT.</p> <p>Corner is located 6 lks. N. of a fence, bearing E. and W.</p> <p>Deposit the orig. cor. stone in the mound of stone.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered mesquite, juniper and pine. Undergrowth, dense to moderate oak bush, cat claw and cacti.</p>	
	<p>East along the S. bdy. of sec. 35.</p> <p>Ascend W. slope, over mountainous land, through medium undergrowth.</p> <p>3.30 Telephone line, bears N. 45° E. and S. 45° W.</p> <p>4.70 Spur, slopes S.; desc.</p> <p>8.95 Cor. of fences, bearing irregularly S. and W.</p> <p>10.40 Wash, 10 lks. wide, 1 ft. deep, drains S.</p> <p>15.20 Spur, slopes S.; desc. E. slope.</p> <p>15.60 Cliff, 100 ft. high, edge bears NE. and SW.</p> <p>16.70 U.S. Highway No. 60 and 70, bears NE. and SW.</p> <p>17.50 Bloody Tanks Wash, 50 lks. wide, 15 ft. deep, drains NE.</p> <p>18.40 Old abandoned highway, bears NE. and SW.</p> <p>18.60 Base of cliff, 60 ft. high, edge bears NE. and SW.</p> <p>19.80 Asc. along a rocky N. slope.</p> <p>20.20 The W. end of a fence, bearing irregularly E.</p> <p>21.90 Slope changes to W.</p> <p>31.60 Spur, slopes N.; desc. along NE. slope.</p> <p>39.96 Point for the standard ¼ sec. cor. of sec. 35, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 12 ins. in the ground, to bedrock, mound with stone to top, brass cap mkd.</p>	

BOOK 4822

4.

Dep. Resurvey of a Portion of S. Bdy., T. 1 N., R. 14 E., Arizona

CHAINS		
	<p>S C T1N R14E <u>¼ S 35</u> 1967</p>	
	<p>from which</p> <p style="padding-left: 40px;">An oak, 4 ins. diam., bears N. 55¼° W., 19 lks. dist., mkd. SC ¼ S 35 BT.</p> <p>Corner falls in the remains of a fence, bearing irregularly E. and W.</p>	
44.60	Steep rocky draw, course N.; asc. along NW. slope.	
48.20	Spur, slopes steeply N.; desc. along NE. slope.	
53.20	Exposed granite draw, course N.; asc. along NW. slope.	
55.90	Spur, slopes steeply N.; desc. along NE. slope.	
55.98	The closing cor. of secs. 1 and 2, T. 1 S., R. 14 E., hereafter described.	
79.92	Point for the standard cor. of secs. 35 and 36, at proportionate dist.; unable to find any remaining evidence of the orig. cor.	
	<p>Set the iron post over an "X" chiseled in solid rock, mound with stone to top, brass cap mkd.</p>	
	<p>S C T1N R14E <u>S35 S 36</u> 1967</p>	
	<p>from which</p> <p style="padding-left: 40px;">A steel fence post, cemented in rock, bears S. 52° E., 28 lks. dist.</p> <p style="padding-left: 40px;">A steel fence post, cemented in rock, bears S. 37° W., 22 lks. dist.</p> <p>Corner falls on a large smooth rock slab, approximately 100 ft. long and 60 ft. wide, 17 lks. North of a fence bearing E. and W.</p> <p>Land, mountainous. Soil, rocky. Timber, widely scattered mesquite. Undergrowth, dense to moderate oak bush, cat claw and cacti.</p>	
	<p>East along the S. bdy. of sec. 36.</p> <p>Descend along a NE. slope, over mountainous land, through medium undergrowth.</p>	
.60	Asc. over NW. slope.	
3.90	Spur, slopes N.; desc. E. slope.	
14.60	Fence, bears N. and S. for 23 lks., to the corner of fences, bearing N., S., E. and W.	

BOOK 4822

5.

Dep. Resurvey, Boundaries, Sec. 2, T. 1 S., R. 14 E., Arizona

CHAINS	
20.70	Wash, 30 lks. wide, 15 ft. deep, drains N.
27.90	Fence, bears N. and S., for 23 lks. to the corner of fences, bearing N., E. and W.
31.50	Wash, 30 lks. wide, 20 ft. deep, drains N.; asc. W. slope.
35.80	Ravine, drains NW.
39.96	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented by a granite stone, 11 x 8 x 8 ins., firmly set in the ground, mkd. SC $\frac{1}{4}$ on the N. face, and with a mound of stone to the S.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S C T1N R14E <u>$\frac{1}{4}$ S 36</u> 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Corner falls on a W. slope, 97 lks. W. of a trail road on top of a spur, sloping N. 25° W., and 25 lks. N. of a fence, bearing E. and W.</p>
<p>Dependent Resurvey, Boundaries, Section 2 Township 1 South, Range 14 East</p>	
<p>Reestablishment of the Survey Executed in 1906 by P. Contzen</p> <hr/> <p>The cor. of secs. 1, 2, 11 and 12, monumented by a granite stone, 9 x 9 x 9 ins., firmly set, mkd. with 5 notches on the S. face and 1 notch on the E. face, and with a mound of stone W.</p> <p>At the corner point,</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1S R14E <u>S 2 S 1</u> <u>S11 S12</u> 1967</p> <p>Raise a mound of stone W. of the corner.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>N. 0°07' W., bet. secs. 1 and 2.</p> <p>Over mountainous land, through dense undergrowth; desc. over rocky NE. slope.</p>	
5.00	Rocky wash, drains NE.; asc. over SE. slope.
15.60	Low ridge, bears E. and W.
39.00	Top of ridge, bears E. and W.; desc. over N. slope.

BOOK 4822

6.

Dep. Resurvey, Boundaries, Sec. 2, T. 1 S., R. 14 E., Arizona

CHAINS		
39.80	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, to bedrock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E $\frac{1}{4}$ S 2 S 1 1967</p>	
49.15	<p>Mine shaft, bears West, 40 lks. dist.</p>	
72.20	<p>Rocky ravine, drains NW.</p>	
75.65	<p>The closing cor. of secs. 1 and 2, on the N. bdy. of the Tp., monumented by a rock in place, 20 x 18 x 5 ins., mkd. with an "X" on top, CC on S., 5 notches on the W. and 1 notch on the E.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1N R14E <u>S 35</u> S 2 S 1 C C T1S R14E 1967</p> <p>from which</p> <p style="padding-left: 40px;">The standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 1 N., R. 14 E., bears West, 16.02 chs. dist.</p> <p>Deposit the orig. cor. stone in the mound alongside the iron post.</p> <p>The cor. is located 5 lks. S. of a fence bearing E. and W.</p> <p>Land, mountainous. Soil, rocky. Timber, scattered mesquite. Undergrowth, moderate to dense oak, cat claw and cacti.</p>	
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°47' W., bet. secs. 2 and 11.</p> <p>Over mountainous land, through medium undergrowth; asc. over NE. slope.</p>	
10.00	<p>Ridge, bears N. and S.; desc. over W. slope through dense undergrowth.</p>	
23.20	<p>Wash, 20 lks. wide, 2 ft. deep, drains NW.</p>	
29.20	<p>Wash, 20 lks. wide, 3 ft. deep, drains N.</p>	
32.40	<p>Spur, slopes N.</p>	
35.10	<p>Wash, 10 lks. wide, 3 ft. deep, drains N.; asc. along N. slope.</p>	

BOOK 4822

7.

Dep. Resurvey, Boundaries, Sec. 2, T.1 S., R. 14 E., Arizona

CHAINS	
39.96	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented by a granite stone, 10 x 8 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on N. face, with a mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1S R14E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{2}{11}$ 1967</p> <p>Raise a mound of stone N. of the corner.</p> <p>Bury the orig. cor. stone alongside the iron post.</p>
1.10	<p>S. 89°53' W., beginning new measurement.</p>
1.10	<p>Ravine, drains NE.</p>
5.90	<p>Spur, slopes N.; continue over small rolling hills.</p>
18.45	<p>Top of small hill; desc. W. slope.</p>
20.07	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 2 and 11, at proportionate dist.</p> <p>Set the iron post 15 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E W $\frac{1}{16}$ $\frac{S}{S}$ $\frac{2}{11}$ 1967</p>
23.90	<p>Ravine, steep sloping sides, 10 lks. wide, drains N.; asc. E. slope.</p>
27.90	<p>Top of small hill; desc. NW. slope.</p>
33.00	<p>Ravine, steep rocky sides, 10 lks. wide, drains N.</p>
38.20	<p>Top of spur, slopes N. from 1 ch. S.; desc. W. slope.</p>
40.14	<p>The cor. of secs. 2, 3, 10 and 11, monumented by a granite stone, 18 x 8 x 4 ins., firmly set in a mound of stone, mkd. with 4 notches on the S. edge and 2 notches on the E. edge. A nail was cemented in the top of the stone.</p> <p>from which the original bearing trees</p> <p style="padding-left: 40px;">An oak, 7 ins. diam., with healed blaze, bears S. 61½° E., 84 lks. dist.</p> <p style="padding-left: 40px;">A dead oak, 7 ins. diam., with healed blaze, bears S. 69½° W., 236 lks. dist. (Record: S. 55° W., 237 lks. dist.)</p> <p>At the corner point,</p> <p>Set an iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E S 3 S 2 S10 S11 1967</p>

BOOK 4822

8.

Dep. Resurvey, Boundaries, Sec. 2, T.1 S., R. 14 E., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 8 ins. diam., bears N. 44-3/4° W., 163 lks. dist., mkd. S 3 BT.</p> <p>Deposit the orig. cor. stone in the mound of stone, alongside the iron post.</p> <p>Land, mountainous. Soil, rocky. Timber, widely scattered juniper and oak. Undergrowth, dense oak bush, cat claw, mesquite, manzanita, and mountain laurel.</p>
	<p>N. 0°37' E., bet. secs. 2 and 3.</p> <p>Ascend along brushy W. slope.</p>
1.70	Small spur, slopes NW.; desc. along E. slope.
16.60	Ravine, 10 lks. wide, drains N. 60° W.; asc. along W. slope.
19.98	Point for the S 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.
	<p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E S 1/16 S 3 S 2 1967</p>
21.20	Spur, slopes N. 60° W.; desc. N. slope.
29.965	The N-S 1/64 sec. cor. of secs. 2 and 3, determined longitudinally by proportionate measurement, and latitudinally by fence bearing E. and W., which was pointed out by property owners as the property bdy.
	<p>At the corner point</p> <p>Set an iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E N-S 1/64 S 3 S 2 1967</p>
35.70	Fence, bears W. and E., curving N.
37.60	Bladed road to Copper Springs Canyon, bears N. 60° E. and S. 60° W.; enter wash area.
39.935	Point for the 1/4 sec. cor. of secs. 2 and 3, at pro- portionate dist. This cor. was not monumented. There was no evidence of the orig. witness cor. or its accessories.
43.30	Power line, bears N 75° E. and S. 75° W.
43.40	Bloody Tanks Wash, 20 lks. wide, 3 ft. deep, drains N. 30° E.
43.50	Leave wash area; enter gently rolling land.

CHAINS	
44.92	<p>The S-S-N 1/256 sec. cor. of secs. 2 and 3, which is mkd. by a pipe, 16 ins. long, 1 in. diam., set 12 ins. in the ground. This cor. was pointed out by local property owners and identified as a corner of the homestead bdy. as established by the private surveyor.</p> <p>At the corner point</p> <p>Set an iron post 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R14E S-S-N 1/256 S 3 S 2 1967</p> <p>from which</p> <p style="padding-left: 40px;">A birch, 7 ins. diam., bears N. 27° E., 92 lks. dist., mkd. S S N 1/256 S 2 BT.</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N. 33-3/4° W., 193 lks. dist., mkd. S S N 1/256 S 3 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°42' W., beginning new measurement.</p>
.10.	Bladed road, bears N. 28° E. and S. 28° W..
2.60	Dim road, bears N. 54° E. and S. 54° W.
3.40	Telephone line, bears N. 54° E. and S. 54° W.
3.90	Fence, bears N. 54° E. and S. 54° W.
5.005	<p>Point for the S-N 1/64 sec. cor. of secs. 2 and 3, at proportionate dist.</p> <p>Set a "T" bar, 24 ins. long, 12 ins. in the ground, and in a collar of stone.</p> <p>from which</p> <p style="padding-left: 40px;">A spike in a telephone pole, bears S. 16-3/4° E., 113 lks. dist.</p> <p style="padding-left: 40px;">An oak, 2 ins. diam., bears S. 32-1/2° W., 13 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. 33-1/4° W., 136 lks. dist., mkd. S N 1/64 S 3 BT.</p> <p style="padding-left: 40px;">A birch, 6 ins. diam., bears S. 55-1/2° W., 182 lks. dist., mkd. S N 1/64 S 3 BT.</p> <p style="padding-left: 40px;">Mile marker 241 on the N. side of U.S. Highway 60 and 70, bears S. 77-3/4° W., 273 lks. dist.</p> <p>Corner falls on the fill for U. S. Highway 60 and 70.</p>
5.70	Center line of U. S. Highway 60 and 70, bears S. 54° W. and N. 57 1/2° E.
7.10	Entrance road to house, bears irregularly E. and W.
8.40	Bladed dirt road, bears N. 60° W. and S. 60° E., asc. SW. slope.
9.10	Entrance to tunnel, bears West, 70 lks. dist.

BOOK 4822

10.

Dep. Resurvey, Boundaries, Sec. 2, T.1 S., R. 14 E., Arizona

CHAINS	
9.10	Fence, bears S. 40° E. and N. 40° W. for 65 lks., thence N. 30° W.
12.00	Corrugated steel storage tank, 8 ft. diam., bears West, 110 lks. dist.
12.20	Mine road, bears irregularly S. 70° E. and N. 70° W.
15.015	Point for the N 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.
	Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.
	T1S R14E N 1/16 S 3 S 2 1967
16.80	Enter area that has been heavily bladed for mining exploration. There are numerous mine roads in this area.
27.00	S. end of mine road, bearing irregularly N.; follow generally along the E. edge of road.
30.92	The closing cor. of secs. 2 and 3, on the N. bdy. of the Tp., monumented by a granite stone, 9 x 9 x 4 ins., firmly set, mkd. CC on the S. face, with 4 notches on the W. face and 2 notches on the E. face, and with a nail cemented in the top.
	At the corner point,
	Set an iron post 16 ins. in the ground, mound with stone to top, brass cap mkd.
	T1N R14E S 34 <hr style="width: 50px; margin: 0 auto;"/> S 3 S 2 T1S R14E C C 1967
	from which
	A spike in the post at the W. end of a fence, bearing E., bears S. 56° E., 16 lks. dist.
	Deposit the orig. cor. stone in the mound of stone.
	The standard ¼ sec. cor. of sec. 34, T. 1 N., R. 14 E., bears S. 89°58' W., 16.08 chs. dist.
	The point for the ¼ sec. cor. of sec. 2 is at mid-point bet. the closing cor. and on the N. bdy. of the Township.
	At the corner point, Chisel an "X" at the true point, on a sheer rock cliff, 8 ft. high, on the NW. side of U.S. Highway 60 and 70.

BOOK 4822

11.

Subdivision of Section 2, T.1 S., R. 14 E., Arizona

CHAINS

from which

A birch, 10 ins. diam., bears S. 87° E., 153 lks. dist., mkd. $\frac{1}{4}$ S 2 BT.

The standard cor. of secs. 34 and 35, on the S. bdy., T. 1 N., R. 14 E., bears West, 16.05 chs. dist.

The point selected for the witness $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 2, bears East, 250 lks. dist.

Set the iron post 8 ins. in the ground and in a mound of stone to top, brass cap mkd.

$\xleftarrow{\quad W \quad}$
 $\frac{1}{4}$ S 2 C
 T1S R14E

1967

The point for the W 1/16 sec. cor. of sec. 2 is at mid-point between the closing cor. of secs. 2 and 3, and the $\frac{1}{4}$ sec. cor. of sec. 2 and on the N. bdy. of the Tp.

At the cor. point,

Set the iron post 14 ins. in the ground, mound with stone to top, brass cap mkd.

$\overline{W \ 1/16 \ S \ 2}$
 T1S R14E

1967

from which

A pine, 7 ins. diam., bears N. 56 $\frac{1}{2}$ ° E., 40 lks. dist., mkd. BT.

A pine, 10 ins. diam., bears S. 61° E., 41 lks. dist., mkd. W 1/16 S 2 BT.

The standard cor. of secs. 34 and 35, T. 1 N., R. 14 E., bears N. 89°58' E., 3.92 chs. dist.

Corner falls 7 $\frac{1}{2}$ lks. N. of a fence bearing E. and W.

Subdivision of Section 2, T. 1 S., R. 14 E.

From the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.

N. 0°05' W., on the N. and S. center line of sec. 2.

Descend brushy NW. slope.

2.40 Ravine, 10 lks. wide, drains NE.

8.90 Spur, slopes E.

12.40 Spring, bears East, 40 lks. dist.; spring has been developed and a water pipe, 2 ins. diam., runs down wash.

12.70 Spring, bears East, 75 lks. dist.; spring has been developed and water is piped into the same pipe as above.

BOOK 4822

12.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS		
13.30	Wash, 20 lks. wide, 5 ft. deep, drains N. 15° W.; asc. S. slope.	
20.01	Point for the C-S 1/16 sec. cor. of sec. 2. Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.	
	<p>T1S R14E</p> <p>C</p> <p>S $\frac{1}{16}$ </p> <p>S 2</p> <p>C</p> <p>1967</p>	
20.60	Spur, slopes SE.; desc. N. slope.	
26.00	Wash, 20 lks. wide, 5 ft. deep, drains NW.	
30.015	Point for the C-N-S 1/64 sec. cor. of sec. 2. This cor. was not monumented.	
30.10	Spur, slopes E.	
34.50	Spur, slopes W.	
37.30	Ravine, drains W.; asc. S. slope.	
40.02	Point for the C- $\frac{1}{4}$ sec. cor. of sec. 2. Set the iron post 18 ins. in the ground, and in a collar of stone to top, brass cap mkd.	
	<p>T1S R14E</p> <p>C $\frac{1}{4}$</p> <p>S 2</p> <p>1967</p>	
41.00	Spur, slopes W.; desc. N. slope.	
49.965	Point for the C-S-N 1/64 sec. cor. of sec. 2. This cor. was not monumented.	
50.80	Ravine, drains NW.; asc. S. slope.	
55.00	Spur, slopes W.; asc. along W. slope.	
59.91	Point for the C-N 1/16 sec. cor. of sec. 2. Set the iron post 6 ins. in the ground, mound with stone to top, brass cap mkd.	
	<p>T1S R14E</p> <p>C</p> <p>N $\frac{1}{16}$ </p> <p>S 2</p> <p>C</p> <p>1967</p>	
62.80	Desc. steep N. slope.	
71.90	Fence, bears W., and E. for 50 lks. to end of fence.	
73.70	Bloody Tanks Wash, 50 lks. wide, 12 ft. deep, drains NE.	

BOOK 4822

13.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
75.10	Center of U. S. Highway 60 and 70, bears NE. and SW.
75.60	Base of cliff, bears NE. and SW.
75.79	The true point for the $\frac{1}{2}$ sec. cor. of sec. 2 on the N. bdy. of the Tp.
<p>From the $\frac{1}{2}$ sec. cor. of secs. 1 and 2.</p> <p>N. $89^{\circ}57'$ W., on the E. and W. center line of sec. 2.</p> <p>Ascend rocky NE. slope.</p>	
6.60	Spur, slopes N.; desc. NW. slope.
13.50	Wash, 10 lks. wide, 2 ft. deep, drains N.
25.60	Ridge, bears N. and S.; desc. W. slope, through dense undergrowth.
39.95	The center $\frac{1}{2}$ sec. cor. of sec. 2.
49.40	Wash, 10 lks. wide, drains S. 75° W.
50.20	<p>The C-E-W $\frac{1}{64}$ sec. cor. of sec. 2, monumented with a pipe, 7 ft. long, $\frac{3}{4}$ ins. diam., and a steel bar, $\frac{1}{2}$ in. diam. alongside. Both set firmly in the ground. This cor. was pointed out by property owners as being a corner of the homestead as established by the private surveyor.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd.</p>
<p style="text-align: center;">T1S R14E S 2 C-E-W $\frac{1}{64}$ 1967</p> <hr style="width: 10%; margin: auto;"/>	
<p>S. $89^{\circ}43'$ W., beginning new measurement.</p>	
8.25	Fence, bears N. 44° E. and S. 44° W.; thence over cleared land.
9.805	Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 2. This cor. was not monumented.
11.60	Dirt road, bears irregularly N. from SE.
12.10	Fence, bears N. 41° W. and S. 41° E.
14.30	Wash, 20 lks. wide, 1 ft. deep, drains N. 75° W.
16.65	Fence, bears irregularly N. and S.
17.40	Wash, 20 lks. wide, 1 ft. deep, drains N. 75° W.
17.80	Dirt road, bears NW. and SE. for 1 ch. to junction of dirt roads bearing SE. and E.; asc. brushy E. slope.
19.61	Point for the C-W-W $\frac{1}{64}$ sec. cor. of sec. 2. This corner was not monumented.

BOOK 4822

14.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
20.40	Steel water tank, 8 ft. diam., 8 ft. high, bears South, 25 lks. dist.; a wood water tank, 8 ft. diam., 6 ft. high, is W. of steel tank; top of spur, slopes N., desc. W. slope.
24.40	Fence, bears N. 60° W. and S. 60° E.
24.515	Point for the C-W-W-W 1/256 sec. cor. of sec. 2. This cor. was not monumented.
27.20	Fence, bears N. 30° E. and S. 30° W.
27.50	Bladed road to Copper Springs Canyon, bears N. 30° E. and S. 30° W.
27.60	Enter wash area.
29.42	The point for the 1/4 sec. cor. of secs. 2 and 3.
	From the W 1/16 sec. cor. of secs. 2 and 11. N. 0°01' W., on the N. and S. center line of the SW 1/4 of sec. 2. Descend along a brushy W. slope.
11.50	Top of small knoll.
16.40	Ravine, 10 lks. wide, steep brushy banks, drains W.
20.00	Point for the SW 1/16 sec. cor. of sec. 2. Set the iron post 10 ins. in the ground, mound with stone to top, brass cap mkd. T1S R14E SW $\frac{1}{16}$ S 2 1967 Corner falls at the NW. edge of small rock outcrop on a NW. slope.
29.10	Wash, 10 lks. wide, 2 ft. deep, drains NW.
30.00	Point for the C-N-SW 1/64 sec. cor. of sec. 2. This point was not monumented.
37.80	Dirt road, bears NW. and SE.; thence across cleared land.
38.00	Fence, bears NW., and SE. for 40 lks., thence N. 44° E.
38.50	Wash, 20 lks. wide, 3 ft. deep, drains NW.
40.00	Point for the C-W 1/16 sec. cor. of sec. 2.
	From the C-S 1/16 sec. cor. of sec. 2. S. 89°47' W., on the E. and W. center line of the SW 1/4 of sec. 2.
.50	Spur, slopes S.; desc. brushy W. slope.
8.80	Wash, 20 lks. wide, 3 ft. deep, drains N.; asc. steep E. slope.

BOOK 4822

15.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS											
10.04	Point for the C-E-SW 1/64 sec. cor. of sec. 2. This point was not monumented.										
10.10	Pipeline from spring, old and broken, bears irregularly NW. and SE.										
13.10	Spur, slopes W.; desc. along top of spur.										
20.08	The SW 1/16 sec. cor. of sec. 2.										
25.60	Wash, 30 lks. wide, 3 ft. deep, drains W. for 50 lks., thence N., continue over rolling land.										
28.80	Ravine, 10 lks. wide, drains N.; asc. E. slope.										
38.80	Low ridge, bears N. and S.; desc. W. slope.										
39.93	The S. 1/16 sec. cor. of secs. 2 and 3.										
	<p>From the point for the C-E-SW 1/64 sec. cor. of sec. 2.</p> <p>N. 2°13' W., on the N. and S. center line of the NE ¼ SW ¼ of sec. 2.</p> <p>Descend along a steep, brushy E. slope.</p> <tr> <td data-bbox="256 1239 407 1274">5.10</td> <td data-bbox="407 1239 1341 1314">Wash, 20 lks. wide, 10 ft. deep, drains NW.; asc. SW. slope.</td> </tr> <tr> <td data-bbox="256 1341 407 1376">9.84</td> <td data-bbox="407 1341 1341 1534"> <p>The NE-SW 1/64 cor. of sec. 2, monumented with a squared cedar post, 30 ins. long, 4 ins. diam., mkd. with a 4 on each face and set loosely in a mound of stone, with a mound of stone to the W. This cor. was pointed out by interested property owners as being the SE. cor. of the homestead.</p> <p>At the corner point,</p> <p>Set the iron post on solid rock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E NE-SW <u>1</u> S 2 64</p> <p style="text-align: center;">1967</p> <p>Reset the wood post, inverted, alongside the iron post.</p> <p>Corner falls at the NW. base of a large boulder 10 ft. high.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°40' E., beginning new measurement.</p> <tr> <td data-bbox="256 2169 407 2204">.80</td> <td data-bbox="407 2169 1341 2204">Spur, slopes W.; desc. along NW. slope.</td> </tr> <tr> <td data-bbox="256 2231 407 2265">4.20</td> <td data-bbox="407 2231 1341 2265">Ravine, 10 lks. wide, steep brushy sides, drains NW.</td> </tr> <tr> <td data-bbox="256 2292 407 2327">10.205</td> <td data-bbox="407 2292 1341 2327">The C-E-W 1/64 sec. cor. of sec. 2.</td> </tr> </td></tr>	5.10	Wash, 20 lks. wide, 10 ft. deep, drains NW.; asc. SW. slope.	9.84	<p>The NE-SW 1/64 cor. of sec. 2, monumented with a squared cedar post, 30 ins. long, 4 ins. diam., mkd. with a 4 on each face and set loosely in a mound of stone, with a mound of stone to the W. This cor. was pointed out by interested property owners as being the SE. cor. of the homestead.</p> <p>At the corner point,</p> <p>Set the iron post on solid rock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E NE-SW <u>1</u> S 2 64</p> <p style="text-align: center;">1967</p> <p>Reset the wood post, inverted, alongside the iron post.</p> <p>Corner falls at the NW. base of a large boulder 10 ft. high.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°40' E., beginning new measurement.</p> <tr> <td data-bbox="256 2169 407 2204">.80</td> <td data-bbox="407 2169 1341 2204">Spur, slopes W.; desc. along NW. slope.</td> </tr> <tr> <td data-bbox="256 2231 407 2265">4.20</td> <td data-bbox="407 2231 1341 2265">Ravine, 10 lks. wide, steep brushy sides, drains NW.</td> </tr> <tr> <td data-bbox="256 2292 407 2327">10.205</td> <td data-bbox="407 2292 1341 2327">The C-E-W 1/64 sec. cor. of sec. 2.</td> </tr>	.80	Spur, slopes W.; desc. along NW. slope.	4.20	Ravine, 10 lks. wide, steep brushy sides, drains NW.	10.205	The C-E-W 1/64 sec. cor. of sec. 2.
5.10	Wash, 20 lks. wide, 10 ft. deep, drains NW.; asc. SW. slope.										
9.84	<p>The NE-SW 1/64 cor. of sec. 2, monumented with a squared cedar post, 30 ins. long, 4 ins. diam., mkd. with a 4 on each face and set loosely in a mound of stone, with a mound of stone to the W. This cor. was pointed out by interested property owners as being the SE. cor. of the homestead.</p> <p>At the corner point,</p> <p>Set the iron post on solid rock, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E NE-SW <u>1</u> S 2 64</p> <p style="text-align: center;">1967</p> <p>Reset the wood post, inverted, alongside the iron post.</p> <p>Corner falls at the NW. base of a large boulder 10 ft. high.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°40' E., beginning new measurement.</p> <tr> <td data-bbox="256 2169 407 2204">.80</td> <td data-bbox="407 2169 1341 2204">Spur, slopes W.; desc. along NW. slope.</td> </tr> <tr> <td data-bbox="256 2231 407 2265">4.20</td> <td data-bbox="407 2231 1341 2265">Ravine, 10 lks. wide, steep brushy sides, drains NW.</td> </tr> <tr> <td data-bbox="256 2292 407 2327">10.205</td> <td data-bbox="407 2292 1341 2327">The C-E-W 1/64 sec. cor. of sec. 2.</td> </tr>	.80	Spur, slopes W.; desc. along NW. slope.	4.20	Ravine, 10 lks. wide, steep brushy sides, drains NW.	10.205	The C-E-W 1/64 sec. cor. of sec. 2.				
.80	Spur, slopes W.; desc. along NW. slope.										
4.20	Ravine, 10 lks. wide, steep brushy sides, drains NW.										
10.205	The C-E-W 1/64 sec. cor. of sec. 2.										

| | From the point for the C-N-S 1/64 sec. cor. of sec. 2. S. 88°59' W., on the E. and W. center line of the NE ¼ of the SW ¼ of sec. 2. |

BOOK 4822

16.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
10.395	<p>Descend along the S. edge of spur sloping W. The NE-SW 1/64 sec. cor. of sec. 2.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 89°07' W., beginning new measurement.</p>
2.40	Ravine, drains NW.; asc. E. slope.
6.50	Low ridge, bears S. and NW.; desc. SW. slope.
9.675	The point for the C-N-SW 1/64 sec. cor. of sec. 2.
	<p>From the point for the C-W 1/16 sec. cor. of sec. 2. N. 0°04' E., on the N. and S. center line of the NW ¼ of sec. 2.</p> <p>Thence through a residential area.</p>
2.50	Fence, bears N. 70° W. and S. 70° E.
3.20	Dirt road, bears E. and W.
9.965	Point for the C-S-NW 1/64 sec. cor. of sec. 2. This corner was not monumented.
15.80	Ravine, drains NW.; across gently rolling land.
18.90	Fence, bears N. 60° E. and S. 60° W.
19.60	Bloody Tanks Wash, 20 lks. wide, drains N. 30° E.
19.93	Point for the NW 1/16 sec. cor. of sec. 2. Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T1S R14E NW $\frac{1}{16}$ S 2 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">A white oak, 10 ins. diam., bears N. 38½° E., 97 lks. dist., mkd. NW 1/16 S 2 BT.</p> <p style="padding-left: 40px;">A birch, 22 ins. diam., bears N. 77-3/4° W., 98 lks. dist., mkd. NW 1/16 S 2 BT.</p> <p>Raise a barrier of stone around corner as it falls in the W. edge of the wash.</p>
23.30	Center of U. S. Highway 60 and 70, bears N. 58° E. and S. 58° W.
23.70	Asc. over brushy S. slope.
27.20	Telephone line, bears N. 40° E. and S. 40° W.
35.80	Fence, bears E. and W.
35.84	The W 1/16 sec. cor. on the N. bdy. of sec. 2.

BOOK 4822

17.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
	From the C-N 1/16 sec. cor. of sec. 2. S. 89°58' W., on the E. and W. center line of the NW ¼ of sec. 2. Descend steep W. slope.
6.70	Ravine, 20 lks. wide, drains N.; asc. E. slope.
10.02	Point for the C-E-NW 1/64 sec. cor. of sec. 2. This point was not monumented.
10.40	Top of high spur, slopes N.; desc. W. slope.
17.10	Wash, 10 lks. wide, 1 ft. deep, drains N.
19.10	Fence, bears N. 10° E. and S. 10° W. for 50 lks.; thence SW.
19.30	Enter wash area.
20.04	The NW 1/16 sec. cor. of sec. 2.
24.10	Leave wash area; power line bears N. and S.
25.15	Center of U.S. Highway 60 and 70, bears N. 58° E. and S. 58° W.; telephone line bears NE. and SW.
26.27	Intersect an Arizona Highway Department brass tablet set in cement level with the ground mkd.
	FAY P & M 1965
27.90	Fence, bears N. 58° E. and S. 58° W.; asc. SW. slope; enter mine area.
29.92	Point for the C-W-NW 1/64 sec. cor. of sec. 2. This point was not monumented.
31.60	Mine road, bears N., and S. for 50 lks., thence W.
37.40	Excavation pit.
38.60	Mine road, bears N. 20° E., curving E., and S 20° W., curving W.
39.80	The N 1/16 sec. cor. of secs. 2 and 3.
	From the C-E-W 1/64 sec. cor. of sec. 2. N. 0°31' E., on the N. and S. center line of the SE¼NW¼ of sec. 2.
.10	Ravine, drains W.; asc. along W. slope.
3.00	Spur, slopes W.; desc. along W. slope.
6.40	Spring, drains W. underneath dirt road.
7.60	Spring, with pipe running westerly under road, bears East 80 lks. dist.
7.70	Dirt road, bears irregularly SW. Dead ends at this point.

BOOK 4822

18.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
9.59	<p>The SE-NW 1/64 sec. cor. of sec. 2, monumented with a pipe, 7 ft. long, 1 in. diam., and a steel rod, 24 ins. long, ½ in. diam., both set firmly in the ground. This cor. was pointed out by local property owners as being the NE. cor. of the homestead, as established by the private surveyor.</p> <p>At the corner point,</p> <p>Set the iron post 4 ins. in the ground, mound with stone to top, brass cap mkd.</p> <p style="text-align: center;">T1S R14E S 2 SE-NW 1/64 1967</p> <p>Reset the local cor. pipes alongside the iron post.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 0°52' E., beginning new measurement.</p>
.20	<p>Ravine, drains W.; asc. along E. slope.</p>
10.33	<p>The point for the C-E-NW 1/64 sec. cor. of sec. 2.</p>
10.185	<p>From the point for the C-S-N 1/64 sec. cor. of sec. 2. S. 87°56' W. on the E. and W. center line of the SE ¼ NW ¼ of sec. 2.</p> <p>The SE-NW 1/64 cor. of sec. 2.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 88°01' W., beginning new measurement.</p>
9.885	<p>The point for the C-S-NW 1/64 sec. cor. of sec. 2.</p>
3.40	<p>From the point for the C-W-W 1/64 sec. cor. of sec. 2. N. 2°00' W., on the N. and S. center line of the SW ¼ NW ¼ of sec. 2. Descend NE. slope.</p> <p>Fence, bears N. 56° E. and S. 56° W.; thence across level land, with houses, corrals, etc.</p>
4.885	<p>The C-S-SW-NW 1/256 sec. cor. of sec. 2, monumented with a pipe, 5 ft. above ground, 1 in. diam.; a pipe, 2 ins. above ground, 1 in. diam.; and a pipe, 5 ft. above ground, 3 ins. diam., which is also the cor. of fences bearing N., E. and S. 50° E., all cemented in the ground, side by side. This cor. was pointed out by local property owners as being a cor. of the homestead, as established by the local surveyor. This cor. also functions as Cor. 4, Lot 11.</p> <hr style="width: 10%; margin: 10px auto;"/>

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
	<p>N. 0°32' E., beginning new measurement.</p>
1.925	<p>Point for Cor. 1, Lot 11, and Cor. 4, Lot 10.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T1S R14E</p>
	<p style="text-align: center;">S 2</p>
	<p style="text-align: center;">Lot 10</p>
	<p style="text-align: center;">Cor 4</p>
	<p style="text-align: center;">Cor 1</p>
	<p style="text-align: center;">Lot 11</p>
	<p style="text-align: center;">1967</p>
4.885	<p>The SW-NW 1/64 sec. cor. of sec. 2, monumented with a</p>
	<p>pipe, 5 ft. above ground, 3 ins. diam., used as a</p>
	<p>post in fence bearing N. 70° W. and S. 70° E.,</p>
	<p>cemented into the ground, and painted silver. This</p>
	<p>cor. was pointed out by local property owners as being</p>
	<p>a corner of the homestead, as established by the</p>
	<p>private surveyor. This corner also functions as</p>
	<p>Cor. 1, Lot 10.</p>
	<p>At the corner point,</p>
	<p>Placed the brass cap from a standard iron post in the</p>
	<p>top of the pipe used as the local cor. and marked it.</p>
	<p style="text-align: center;">T1S R14E</p>
	<p style="text-align: center;">S 2</p>
	<p style="text-align: center;">Cor 1</p>
	<p style="text-align: center;">Lot 10</p>
	<p style="text-align: center;">1967</p>
	<p>from which</p>
	<p>A cottonwood, 7 ins. diam., bears N. 16½° E.,</p>
	<p>195 lks. dist., mkd. COR 1, LOT 10 BT.</p>
	<p>An elm, 17 ins. diam., bears N. 12¼° W.,</p>
	<p>141 lks. dist., mkd. COR 1, LOT 10 BT.</p>
	<p>N. 0°18' E., beginning new measurement.</p>
4.30	<p>Bloody Tanks Wash, 10 lks. wide, 1 ft. deep, drains NE.</p>
6.00	<p>Gravel road, bears N. 50° E. and S. 50° W.</p>
6.00	<p>Telephone line, bears N. 50° E. and S. 50° W.</p>
6.30	<p>Fence, bears N. 70° E. and S. 70° W.</p>
7.10	<p>U. S. Highway 60 and 70, bears N. 58° E. and S. 58° W.</p>
8.50	<p>Fence, bears N. 58° E. and S. 58° W.; asc. SE. slope.</p>
10.21	<p>The point for the C-W-NW 1/64 sec. cor. of sec. 2.</p>
	<p>From the point for the C-S-NW 1/64 sec. cor. of sec. 2.</p>
	<p>S. 88°33' W., on the E. and W. center line of the</p>
	<p>SW ¼ NW ¼ of sec. 2.</p>
.90	<p>Small pond, 1½ ch. diam.</p>

BOOK 4822

20.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
3.00	Fence, bears N. 40° W. and S. 40° E.
3.70	Road, bears N. 40° W. and S. 40° E.
4.00	Fence, bears N. 40° W. and S. 40° E.
9.20	Wash, 20 lks. wide, 3 ft. deep, drains N.
9.93	The SW-NW 1/64 sec. cor., identical with Cor. 1, Lot 10.
—————	
	N. 88°52' W., beginning new measurement.
2.10	Dirt road, bears N. 20° E. and S. 20° W.
3.635	Point for Cor. 2, Lot 10, sec. 2.
	Set the iron post 18 ins. in the ground, and in a collar of stone to top, brass cap mkd.
	<p>T1S R14E S 2</p> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin: 5px;"> <p>Cor 2 Lot 10</p> </div> <p>1967</p>
	from which
	<p>A willow tree, 10 ins. diam., bears N. 37½° W., 26 lks. dist., mkd. COR 2, LOT 10 BT.</p>
4.845	Point for the C-W-SW-NW 1/256 sec. cor. of sec. 2. This cor. was not monumented.
5.80	Bloody Tanks Wash, 30 lks. wide, 1 ft. deep, drains N. 30° E.
7.30	Dirt road, bears N. 30° E. and S. 30° W.
8.10	Telephone line, bears N. 54° E. and S. 54° W.
9.40	Fence, bears N. 54° E. and S. 54° W.
9.69	The SN 1/64 sec. cor. of secs. 2 and 3.
From the point for the C-W-W-W 1/256 sec. cor. of sec. 2.	
	N. 0°24' W., on the N. and S. center line of the SW ¼ SW ¼ NW ¼ of sec. 2.
	Descend N. slope.
.20	Fence, bears E. and W.
1.20	Fence, bears N. 70° E. and S. 70° W.; cross nearly level land.
1.40	SE. cor. of a barn, bears West, 27 lks. dist.
2.90	Dirt road to Copper Springs Canyon, bears N. 20° E. and S. 20° W.
4.945	Point for the SW-SW-NW 1/256 sec. cor. of sec. 2. This cor. was not monumented.

BOOK 4822

21.

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS	
6.80	Power line, bears N. 53° W. and S. 53° E.; enter wash area.
9.89	Point for the C-W-SW-NW 1/256 sec. cor. of sec. 2.
From the C-S-SW-NW 1/256 sec. cor., identical with Cor. 4, Lot 11.	
N. 89°38' W., on the E. and W. center line of the SW¼ SW¼ NW ¼ of sec. 2.	
.98	Cor. of fences, bearing N. 30° E. and N. 60° W., bears North 1 lk.
3.20	Dirt road, bears N. 30° W. and S. 30° E.
3.585	Point for Cor. 3, Lot 11, sec. 2.
Set the iron post 24 ins. in the ground, brass cap mkd.	
<p>T1S R14E S 2 Lot 11 Cor 3</p>	
1967	
from which	
A spike in a power pole, bears N. 20½° E., 65 lks. dist.	
A power pole, bears N. 18½° W., 87 lks. dist.	
3.70	Power line, bears N. 28°30' E. and S. 28°30' W.
3.80	Dirt road to Copper Springs Canyon, bears N. 20° E. and S. 20° W.
4.78	Point for the SW-SW-NW 1/256 sec. cor. of sec. 2.
7.80	Power line, bears N. 53°30' E. and S. 53°30' W.
9.30	Bloody Tanks Wash, 30 lks. wide, 5 ft. deep, drains N. 20° E.
9.60	The S-S-N 1/256 sec. cor. of secs. 2 and 3.
From Cor. 3, Lot 11, sec. 2.	
N. 0°13' W., along the W. bdy. of Lots 10 and 11.	
1.00	Dirt road to Copper Springs Canyon, bears N. 20° E. and S. 20° W.
1.94	Point for the cor. of Cor. 2, Lot 11, and Cor. 3, Lot 10.
Set the iron post 18 ins. in the ground, in a collar of stone to top, brass cap mkd.	

Subdivision of Section 2, T. 1 S., R. 14 E., Arizona

CHAINS		T1S R14E S 2 Lot 10 Cor 3 Cor 2 Lot 11 1967	
	4.93		from which A cottonwood, 18 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W. 92 lks. dist., mkd. COR 2 LOT 11 BT. A cottonwood, 12 ins. diam., bears N. $47\frac{1}{4}^{\circ}$ W., 74 lks. dist., mkd. LOT 10 COR 3 BT. Cor 2 of Lot 10, sec. 2.
	2.60		From the cor. of Cor. 4, Lot 10, and Cor. 1, Lot 11, sec. 2. N. $89^{\circ}19'$ W., bet. Lots 10 and 11. Power line, bears N. $26^{\circ}30'$ E. and S. $26^{\circ}30'$ W.
	2.80		Fence, bears N. 16° E. and S. 16° W.
	3.25		Dirt road to Copper Springs Canyon, bears N. 20° E. and S. 20° W.
	3.60		Cor. 3, Lot 10, and Cor. 2, Lot 11, sec. 2.
General Description			
The land in sec. 2, Township 1 South, Range 14 East, varies from high, steep mountains in the west and south halves of the section to nearly level land in the south half of the northwest quarter and gently rolling in the north half of the northwest quarter. The entire section is covered with dense to moderate undergrowth of oak bush, manzanita and mountain laurel. The soil is sandy along the Bloody Tanks Wash but is generally rocky in the remainder of the section. There are four springs within the section, each having been developed, and the water piped to the homes within the area. There are several homes on the homestead, and one on each of Lots 10 and 11. The area north of U. S. Highway 60 and 70 has been bladed for mineral exploration and some ore has been taken out.			

BOOK 4822

CERTIFICATE OF SURVEY

I, Kenneth D. Herman, HEREBY CERTIFY upon honor that,
 in pursuance of special instructions bearing date of the 2d day of May, 19 67,
 and supplemental special instructions bearing date of the 30th day of November, 1967,
 I have made a dependent resurvey of a portion of the south boundary of
 Township 1 North, Range 14 East, and a dependent resurvey of the boundaries
 and subdivision of Section 2, Township 1 South, Range 14 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by me and under my direction;
 and that said survey has been made in strict conformity with said special instructions, the Manual
 of Instructions for the Survey of the Public Lands of the United States, and in specific manner
 described in the foregoing field notes.

January 3, 1968
 (Date)

Kenneth D. Herman
 (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date JAN 3 1968

BUREAU OF LAND MANAGEMENT,
 Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary
 of Township 1 North, Range 14 East, and a dependent resurvey of the boundaries
 and subdivision of Section 2, Township 1 South, Range 14 East, of the Gila
 and Salt River Meridian, Arizona,

executed by Kenneth D. Herman

having been critically examined and found correct, are hereby approved.

APR 2 1968
 (Date)

R. E. Brown
 (Chief, Division of Engineering)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)