

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

of

FORT APACHE INDIAN RESERVATION BOUNDARY

in

TOWNSHIP 9 NORTH, RANGE 24 EAST

TOWNSHIP 8 NORTH, RANGE 24 EAST

TOWNSHIP 8 NORTH, RANGE 23 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Howard H. Thomas, Cadastral Surveyor

Under special instructions dated June 17, 19 68, which provided for the surveys included under Group Number 501, approved June 17, 1968, and assignment instructions dated June 26, 19 68.

Survey commenced July 1, 19 68

Survey completed September 12, 19 68

BOOK 4858
INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1A

BOOK 4858
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 9 N. R. 24 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25 (AP211)
31	32	33 (39M)	34	35 (AP215)	36 (35M)

FAIR

NOTE

ONLY THE BEGINNING
AND ENDING CORNERS
REMONUMENTED IN EACH
SECTION ARE
DIAGRAMMED.

SEE PAGE INDEX FOR
COMPLETE LIST OF
CORNERS REMONUMENTED
IN EACH TOWNSHIP.

Tp. 8 N. R. 24 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

FORT APACHE INDIAN RESERVATION

Tp. 8 N. R. 23 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

FORT APACHE INDIAN RESERVATION

PAGE INDEX TO CORNER MONUMENTS

TOWNSHIP 9 NORTH, RANGE 24 EAST, G&SR M.

<u>Corner</u>		<u>Page</u>
Mile Corner	35 (AP211)---	1
Angle Point	213 -----	2
" "	214 -----	2
Mile Corner	35½ -----	3
Angle Point	215 -----	3
Mile Corner	39 -----	4

TOWNSHIP 8 NORTH, RANGE 24 EAST, G&SR M.

<u>Corner</u>		<u>Page</u>	<u>Corner</u>		<u>Page</u>
Angle Point	218 -----	5	Angle Point	237 -----	11
" "	219 -----	5	Mile Corner	39½ -----	11
" "	220 -----	5	Angle Point	239 -----	12
Mile Corner	36½ -----	6	" "	241 -----	12
Angle Point	221 -----	6	Mile Corner	40½ -----	12
" "	222 -----	7	" "	41 -----	13
Mile Corner	37 (AP223)---	7	Angle Point	247 -----	13
Angle Point	224 -----	8	Mile Corner	41½ -----	14
" "	226 -----	8	Angle Point	250 -----	14
Mile Corner	37½ (AP227)---	8	" "	251 -----	14
Angle Point	228 -----	9	Mile Corner	42 (AP253)---	15
Mile Corner	38 -----	9	" "	42½ (AP257)---	15
Angle Point	229 -----	10	Angle Point	258 -----	16
Mile Corner	38½ (AP230)---	10			

TOWNSHIP 8 NORTH, RANGE 23 EAST, G&SR M.

<u>Corner</u>		<u>Page</u>
Mile Corner	45 -----	17
" "	45½ (AP278)---	17
" "	46 (AP282)---	18
Angle Point	283 -----	19
" "	286 -----	19
Mile Corner	47 (AP287)---	19
" "	47½ (AP290)---	20
Angle Point	292 -----	20
Mile Corner	48 -----	21
Angle Point	293 -----	21
" "	294 -----	22
" "	295 -----	22
" "	298 -----	22
Mile Corner	49 (AP299)---	22

BOOK 4858

Township 9 North, Range 24 East
 Township 8 North, Range 24 East
 Township 8 North, Range 23 East
 Gila and Salt River Meridian, Arizona

1C

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on June 17, 1968 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Township 9 North, Range 24 East, G&SR M., Arizona

The Fort Apache Indian Reservation Boundary was resurveyed in 1906 by J. B. Wright and retraced in 1915 by S. E. Blout.

Remonumentation, T. 9 N., R. 24 E., G&SR M., Arizona

The 35 mile cor. and angle point 211, monumented by a malpais stone, 24 x 18 x 6 ins., set 12 ins. in the ground, mkd. NBWMIR 35M on S. face, from which the remains of the orig. bearing trees

A pine stump, 24 ins. diam., bears N. 2½° E., 25 lks. dist., mkd. with faint scribe marks.


A pine stump, 12 ins. diam., bears N. 85° E., 89 lks. dist., no mks.

A pine, 18 ins. diam., bears S. 53½° E., 62 lks. dist., mkd. NBWMIR 35M B.

A pine snag, 24 ins. diam., bears S. 77¾° W., 13 lks. dist., mkd. NBWMIR 35M BT.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 9 ins. diam., bears N. 24° E., 21 lks. dist., mkd. 35M BT.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 9 N., R. 24 E.

CHAINS

Bury the orig. cor. stone alongside the iron post.

Cor. is 35 lks. S. of a fence bearing E. and W.

Angle point 213, monumented by a dead pine stump, with a log, 18 ins. diam., alongside, stump mkd. WMIR 213 on S. face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 17 ins. diam., bears N. 75° E., 55 lks. dist., mkd. AP213 BT.

A pine, 15 ins. diam., bears N. 77° W., 36 lks. dist., mkd. AP213 BT.

Raise a mound of stone N. of the iron post.


Deposit the orig. cor. stump alongside the iron post.

Angle point is 80 lks. N. of a fence, bearing irregularly E. and W.

Angle point 214, monumented by a dead pine stump, with a log, 24 ins. diam., alongside, stump mkd. BMFR on N. face and APNBWMIR 214 on S. face.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 85° E., 36 lks. dist., mkd. AP214 FAIR BT.

A pine, 10 ins. diam., bears S. 21° W., 22 lks. dist., mkd. AP214 FAIR BT.

Deposit orig. cor. stump alongside the iron post.

Angle point is on a fence, bearing irregularly NE. and SW.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 9 N., R. 24 E.

CHAINS

The 35½ mile cor., monumented by a malpais stone, 24 x 18 x 8 ins., set 10 ins. in the ground, in a mound of stone, mkd. BMFR on NW. face and 35½M NBWMIR on E. face, from which the remains of the orig. bearing trees

A pine stump, 20 ins. diam., bears East, 23 lks. dist., no mks.


A pine, 30 ins. diam., bears S. 20° W., 42 lks. dist., mkd. NBWMIR 35½M BT.

A pine, 21 ins. diam., bears S. 73¾° W., 33 lks. dist., mkd. with an overgrown blaze.
(Note: record dist. 83 lks.).

A pine, 23 ins. diam., bears N. 29° W., 18 lks. dist., mkd. NBWMIR 35½M BT.

At the cor. point

Set the iron post, 6 ins. in the ground to bedrock, mound of stone to top, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 2° E., 73½ lks. dist., mkd. 35½M FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 9 lks. E. of a fence, bearing irregularly NE. and SW.

Angle point 215, monumented by a dead pine snag, 24 ins. diam., mkd. BMFR on NE. face and NBWMIR 215 on S. face, from which the remains of the orig. bearing accessories


A mound of stone, bears S. 21½° W., 33 lks. dist., no mks.

A dead pine stump, 12 ins. diam., bears S. 59° W., 40 lks. dist., mkd. with an overgrown blaze.

A pine, 20 ins. diam., bears S. 82° W., 38 lks. dist., mkd. with blaze, partly overgrown, and scribe marks BT.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 32° E., 34 lks. dist., mkd. AP215 FAIR BT.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 9 N., R. 24 E.

CHAINS

Deposit the orig. cor. snag alongside the iron post.

Angle point is 15 lks. E. of fence bearing irregularly NE. and SW.

The 39 mile cor., monumented by a malpais stone, 12 x 10 x 8 ins., lying loose on ground, mkd. NBWMIR 39M on one side, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 20 ins. diam., bears S. 76° E., 28 lks. dist., mkd. NBWMIR 39M BT. (Note: record bearing S. 65° E.).

A pine stump, with a fallen tree, 30 ins. diam., alongside, bears S. 55° E., 26 lks. dist., tree mkd. NBWMIR 39M BT. (Note: record bearing S. 40° W.).

A stump hole bears S. 3° W., 12 lks. dist.

A stump hole, with a dead and fallen pine tree, 20 ins. diam., alongside, bears N. 71° W., 9 lks. dist., scribe mks. burned out on tree.

At the cor. point

Set the iron post, 18 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R24E
S33
39M
FAIR
1968

from which

A pine, 8 ins. diam., bears S. 81° E., 41 lks. dist., mkd. 39M FAIR BT.

A pine, 8 ins. diam., bears N. 47° W., 46 lks. dist., mkd. 39M BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 8 lks. E. of a fence, bearing irregularly NE. and SW.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Township 8 North, Range 24 East, G&SR M., Arizona

The Fort Apache Indian Reservation Boundary was resurveyed in 1906 by J. B. Wright and a portion was retraced in 1915 by S. E. Blout.

Remonumentation, T. 8 N., R. 24 E., G&SR M., Arizona

Angle point 218, monumented by a pine stump, 24 ins. diam., mkd. APNBWMIR 218 on S. face and BMFR on N. face, from which new accessories

A pine, 12 ins. diam., bears S. 54° W., 19 lks. dist., mkd. AP218 FAIR BT.

An iron post, set 26 ins. in the ground, for a reference monument, bears S. 70° E., 25.8 lks. dist., with brass cap mkd. T8N R24E AP218 RM 17 FT FAIR 1968 and an arrow pointing to the true cor.

Angle point is 12 lks. S. of a fence, bearing E. and W.

Angle point 219, monumented by a dead pine stump, 10 ins. diam., no mks., verified by record course and dist. from the remains of the orig. bearing accessories

A stone monument, bears S. 77° E., 44 lks. dist.

A pine tree, 17 ins. diam., bears N. 76° W., 52 lks. dist., mkd. BT.

A stump hole, bears N. 37½° W., 56 lks. dist.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 12 ins. diam., bears S. 57° E., 16 lks. dist., mkd. AP219 FAIR BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is 20 lks. S. of fence, bearing irregularly E. and W.

Angle point 220, monumented by a dead pine stump, 24 ins. diam., mkd. BMFR on N. face, no mks. on S. face.

At the cor. point


Set the iron post, 25 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

T8N R24E

S1



AP220

FAIR

1968

from which

A pine, 12 ins. diam., bears S. 45° E., 70 lks. dist., mkd. AP220 FAIR BT.

A pine, 10 ins. diam., bears N. 16° W., 33 lks. dist., mkd. AP220 BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is on a fence, bearing irregularly SE. and W.

The 36½ mile cor., monumented by a malpais stone, 16 x 9 x 6 ins., lying loose on ground, mkd. NBWMIR 36½ on one face and BMF on the other face, verified by record course and dist. from the orig. bearing trees

A pine, 30 ins. diam., bears South, 57 lks. dist., mkd. with an overgrown blaze.

A pine, 30 ins. diam., bears S. 70° W., 13 lks. dist., mkd. NBWMIR 36½M.

A pine stump, 24 ins. diam., bears S. 83½° W., 23 lks. dist., mkd. NBWMIR 36½M BT.

A pine stump, 30 ins. diam., bears N. 51½° W., 44 lks. dist., mkd. NBWMIR 36½M.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T8N R24E

S1



36½M

FAIR

1968

No new bearing trees available.

Bury the orig. cor. stone alongside the iron post.

Cor. is 8 lks. N. of a fence, bearing E. and W.

Angle point 221, monumented by a dead pine stump, 24 ins. diam., mkd. NBWMIR on S. face and R on N. face, from which new accessories

An iron post, set 26 ins. in the ground, for a reference monument, bears S. 41° W., 19.7 lks. dist., with brass cap mkd. T8N R24E AP221 RM 13 FT FAIR 1968 and an arrow pointing to the true cor.

A pine, 12 ins. diam., bears N. 7° W., 50 lks. dist., mkd. AP221 BT.

Angle point is on a fence, bearing E. and W.


Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Angle point 222, monumented by a dead pine stump, 18 ins. diam., mkd. BMFR on N. face and APNBWMIR 222 on S. face.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 8 ins. diam., bears North, 19 lks. dist., mkd. AP222 BT.

A pine, 4 ins. diam., bears S. 59° E., 39 lks. dist., mkd. X BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is 15 lks. S. of a fence, bearing E. and W.

The 37 mile cor. and angle point 223, monumented by a malpais stone, 20 x 12 x 12 ins., set 2 ins. in the ground, mkd. with faint scribe marks, verified by record course and dist. from the orig. bearing trees

A pine stump, with a dead and fallen tree, 24 ins. diam., alongside, bears N. 19½° E., 40 lks. dist., tree mkd. NBWMIR 37M BT.


A pine, 20 ins. diam., bears S. 5° E., 40 lks. dist., mkd. NBWMIR 37M BT.

A pine, 12 ins. diam., bears S. 13½° W., 37 lks. dist., mkd. NBWMIR 37M BT.

A pine, 21 ins. diam., bears S. 64½° W., 40 lks. dist., mkd. NBWMIR 37M BT.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 12 ins. diam., bears N. 9° W., 52 lks. dist., mkd. 37M BT.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 10 lks. N. of a fence, bearing irregularly E. and W.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Angle point 224, monumented by a dead pine stump, 30 ins. diam., mkd. BMFR on N. face, with a piece of stump lying on ground, alongside, mkd. 224, from which new accessories

A pine, 13 ins. diam., bears N. 30° E., 44 lks. dist., mkd. AP224 BT.


An iron post, set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 64° W., 28.8 lks. dist., with brass cap mkd. T8N R24E AP224 RM 19 FT S2 1968 and an arrow pointing to the true cor.

Angle point is 5 lks. N. of a fence, bearing irregularly E. and SW.

Angle point 226, monumented by a dead pine stump, with a cut log, 15 ins. diam., alongside, log mkd. AP NBWMIR 226 on S. face, no mks. on N. face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 8 ins. diam., bears S. 36° E., 38 lks. dist., mkd. AP226 FAIR BT.

A pine, 8 ins. diam., bears S. 20° W., 28 lks. dist., mkd. AP226 FAIR BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is 25 lks. S. of a fence bearing irregularly E. and NW.

The 37½ mile cor. and angle point 227, monumented by a malpais stone, 21 x 12 x 9 ins., set 16 ins. in the ground, mkd. with faint scribe marks, from which the remains of the orig. bearing trees

A pine stump, 24 ins. diam., bears North, 45 lks. dist., mkd. 37½M BT.

A pine stump, 21 ins. diam., bears S. 87° E., 68 lks. dist., mkd. NBWMIR 37½M BT.

A pine stump, 18 ins. diam., bears S. 28° E., 66 lks. dist., no mks.


A pine stump, with a dead and fallen tree, 18 ins. diam., alongside, bears S. 82½° W., 65 lks. dist., tree mkd. NBWMIR 37½M BT. (Note: record dist. 43 lks.).

At the cor. point

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 9 ins. diam., bears N. 68° E., 19 lks. dist., mkd. 37½M BT.

A pine, 9 ins. diam., bears N. 7° W., 14 lks. dist., mkd. 37½M BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 10 lks. S. of a fence, bearing irregularly SE. and NW.

Angle point 228, monumented by a pine tree, 18 ins. diam., mkd. 228 on S. face and BMFR on N. face, from which new accessories

A pine, 12 ins. diam., bears S. 19° E., 47 lks. dist., mkd. AP228 FAIR BT.

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears S. 80° W., 25.8 lks. dist., with brass cap mkd. T8N R24E AP228 RM 17 FT FAIR 1968 and an arrow pointing to the true cor.

Angle point is on a fence, bearing irregularly SE. and NW.

The 38 mile cor., monumented by a malpais stone, 16 x 9 x 7 ins., set 10 ins. in the ground, mkd. NBWMIR 38M on S. face, from which the remains of the orig. bearing trees

A pine stump, 20 ins. diam., bears N. 54½° E., 5 lks. dist., mkd. NBWMIR 38M BT.


A pine, 24 ins. diam., bears S. 9° W., 16 lks. dist., mkd. NBWMIR 38M BT.

A pine, 30 ins. diam., bears N. 88° W., 33 lks. dist., mkd. NBWMIR 38M BT.

A pine, 20 ins. diam., bears N. 40° W., 18 lks. dist., mkd. NBWMIR 38M BT.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS	
	<p>from which</p> <p>A pine, 8 ins. diam., bears S. 43° W., 91 lks. dist., mkd. 38M FAIR BT.</p> <p>Raise a mound of stone N. of the iron post.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. is 5 lks. S. of a fence, bearing irregularly SE. and NW.</p> <hr/> <p>Angle point 229, monumented by a pine tree, 30 ins. diam., mkd. AP NBWMIR 229 on S. face and BMFR on N. face, from which new bearing trees</p> <p>A pine, 15 ins. diam., bears S. 24° W., 60 lks. dist., mkd. AP229 FAIR BT.</p> <p>A pine, 16 ins. diam., bears N. 46° E., 58 lks. dist., mkd. AP229 BT.</p> <p>Angle point is on a fence bearing irregularly SE. and W.</p> <hr/> <p>The 38½ mile cor. and angle point 230, monumented by a malpais stone, 15 x 10 x 9 ins., set 10 ins. in the ground, in a scattered mound of stone, mkd. NBWMIR 38½M on S. face and BMFR on N. face, from which the remains of the orig. bearing trees</p> <p>A pine, 15 ins. diam., bears S. 80° E., 54 lks. dist., mkd. with an overgrown blaze.</p> <p>A stump hole, with a dead and fallen pine tree, 26 ins. diam., alongside, bears S. 39° W., 18 lks. dist., mkd. NBWMIR 38½M BT.</p> <p>A pine stump, 21 ins. diam., bears S. 68° W., 38 lks. dist., mkd. with faint scribe marks.</p> <p>A partial pine stump, bears N. 63° W., 78 lks. dist., no mks.</p> <p>At the cor. point</p> <p>Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R24E S3 AP230 38½M FAIR 1968</p> </div> <p>from which</p> <p>A pine, 10 ins. diam., bears S. 49° W., 34 lks. dist., mkd. 38½M FAIR BT.</p> <p>A pine, 12 ins. diam., bears N. 15° W., 107 lks. dist., mkd. 38½M BT.</p> <p>Raise a mound of stone N. of the iron post.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Cor. is 20 lks. S. of a fence, bearing irregularly E. and NW.</p>


Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Angle point 237, monumented by a stump hole, with a dead and fallen pine snag, 24 ins. diam., alongside, mkd. APN on S. face and BMFR on N. face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 49° W., 71 lks. dist., mkd. AP237 BT.

Deposit the orig. cor. snag alongside the iron post.

Angle point is on top of Brushy Mt. on the S. edge, 12 lks. W. of a fence, bearing irregularly NE. and SW.

The 39½ mile cor., monumented by a malpais stone, 18 x 12 x 8 ins., set 8 ins. in the ground, in a mound of stone, mkd. 39½M on NE. face, NBWMIR on SE. face and BMFR on NW. face, from which the remains of the orig. bearing trees

A stump hole, bears N. 9½° E., 88 lks. dist.


A pine stump, 30 ins. diam., bears N. 65° E., 84 lks. dist., mkd. with faint scribe marks.

A pine stump, 24 ins. diam., bears S. 15° W., 27 lks. dist., mkd. with faint scribe marks.

A stump hole, bears N. 47° W., 83 lks. dist.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 25° E., 85 lks. dist., mkd. 39½M FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is on steep SE. slope of Brushy Mt., 81 lks. W. of a fence bearing irregularly NE. and W.


Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Angle point 239, monumented by a dead pine stump, 36 ins. diam., mkd. APNBW on S. face and B on N. face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 6 ins. diam., bears N. 17° E., 28 lks. dist., mkd. AP239 BT.

A pine, 7 ins. diam., bears S. 15° E., 67 lks. dist., mkd. AP239 FAIR BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is on a fence, bearing irregularly E. and SW.

Angle point 241, monumented by a dead pine stump, 24 ins. diam., mkd. 41 on S. face, from which new accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears N. 84° E., 21.2 lks. dist., with brass cap mkd. T8N R24E AP241 RM 14 FT FAIR 1968 and an arrow pointing to the true cor.

A pine, 8 ins. diam., bears S. 13° E., 27 lks. dist., mkd. AP241 FAIR BT.

Angle point is 25 lks. E. of a fence, bearing irregularly NE. and SW.

The 40½ mile cor., monumented by a malpais stone, 24 x 12 x 8 ins., set 18 ins. in the ground, mkd. NBWMIR on S. face and 40½ on SE. face, from which the remains of the orig. bearing trees

A stump hole, bears S. 44° E., 56 lks. dist.


A pine stump, 36 ins. diam., bears South, 29 lks. dist., no mks.

A pine, 20 ins. diam., bears N. 86° W., 44 lks. dist., mkd. NBWMIR 40½

A stump hole, bears N. 71½° W., 38 lks. dist.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

from which

A pine, 8 ins. diam., bears S. 84° E., 66 lks.
dist., mkd. 40¹/₂M FAIR BT.

A pine, 10 ins. diam., bears N. 54° W., 52¹/₂ lks.
dist., mkd. 40¹/₂M BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 25 lks. W. of a fence, bearing irregularly NE.
and SW.

The 41 mile cor., monumented by a malpais stone, 18 x
14 x 10 ins., set 10 ins. in the ground, in a scattered
mound of stone, mkd. NBW on top and 41M on SE. face,
from which the remains of the orig. bearing trees

A stump hole, bears S. 47° W., 26 lks. dist.


An oak stump, 18 ins. diam., bears S. 85° W.,
8 lks. dist., no mks.

A pine stump, 40 ins. diam., bears N. 48° W.,
47 lks. dist., no mks.

A stump hole, bears N. 32° W., 51 lks. dist.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of
stone, brass cap mkd.



from which

A pine, 13 ins. diam., bears N. 68° E., 73¹/₂ lks.
dist., mkd. 41M BT.

A pine, 10 ins. diam., bears N. 3° W., 157 lks.
dist., mkd. 41M BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is on a fence, bearing irregularly E. and W.

Angle point 247, monumented by a dead pine stump, 20
ins. diam., 5 ft. high, mkd. AP NBWMIR 247 on S. face,
from which new accessories

An iron post, set 18 ins. in the ground, mound of
stone to top, for a reference monument, bears
N. 6° E., 43.9 lks. dist., with brass cap mkd.
T8N R24E AP247 RM 29 FT S8 1968 and an arrow
pointing to the true cor.

A pine, 12 ins. diam., bears S. 53¹/₂° W., 138 lks.
dist., mkd. AP247 FAIR BT.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Angle point is on a fence, bearing irregularly E. and W.

The $4\frac{1}{2}$ mile cor., monumented by a malpais stone, 16 x 12 x 8 ins., set 6 ins. in the ground, mkd. with faint scribe marks, with mound of stone to the E. From the cor., the remains of the orig. bearing trees

A pine stump, 18 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ E., 14 lks. dist., mkd. with faint scribe marks.

A stump hole, bears S. 60° E., 25 lks. dist.

A stump hole, bears N. 86° W., 49 lks. dist.

A portion of a pine stump, bears N. $57\frac{1}{2}^{\circ}$ W., 27 lks. dist., mkd. with faint scribe marks.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T8N R24E
S8
←→
4 $\frac{1}{2}$ M
FAIR
1968

from which

A pine, 14 ins. diam., bears S. 43° E., 48 lks. dist., mkd. 4 $\frac{1}{2}$ M FAIR BT.

A pine, 8 ins. diam., bears N. 65° W., 63 lks. dist., mkd. 4 $\frac{1}{2}$ M BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 20 lks. S. of a fence, bearing irregularly E. and W.

Angle point 250, monumented by a pine tree, 20 ins. diam., mkd. NBWMIR 250 on S. face and with an overgrown blaze on N. face, from which new bearing trees

A pine, 12 ins. diam., bears N. 40° E., 23 lks. dist., mkd. AP250 BT.

A pine, 8 ins. diam., bears S. 46° W., 44 lks. dist., mkd. AP250 FAIR BT.

Angle point is 20 lks. S. of a fence, bearing irregularly E. and NW.

Angle point 251, monumented by a pine tree, 24 ins. diam., mkd. APNBWMIR 251 on S. face and with an overgrown blaze on the N. face, from which new bearing trees

A pine, 17 ins. diam., bears S. 5° W., 104 lks. dist., mkd. AP251 FAIR BT.

A pine, 10 ins. diam., bears N. 60° W., 65 lks. dist., mkd. AP251 BT.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS

Angle point is 55 lks. N. of a fence, bearing irregularly SE. and W.

The 42 mile cor. and angle point 253, monumented by a malpais stone, 20 x 14 x 8 ins., set 8 ins. in the ground, mkd. NBWMIR 42M on S. face and BMFR on N. face, with mound of stone to the NE. From the cor., the remains of the orig. bearing trees

A pine stump, 30 ins. diam., bears N. $72\frac{1}{2}^{\circ}$ E., 100 lks. dist., mkd. with faint scribe marks.


A pine stump, 24 ins. diam., bears S. $5\frac{3}{4}^{\circ}$ W., 63 lks. dist., mkd. with faint scribe marks.

A stump hole, bears S. 16° W., 70 lks. dist.

A pine stump, 24 ins. diam., bears S. 79° W., 27 lks. dist., mkd. with faint scribe marks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



No new bearing trees available.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 50 lks. N. of a fence, bearing irregularly E. and W.

The $42\frac{1}{2}$ mile cor. and angle point 257, monumented by a malpais stone, 16 x 12 x 12 ins., set 6 ins. in the ground, mkd. with faint scribe marks, with mound of stone to the NE. From the cor., the remains of the orig. bearing trees

A pine, 24 ins. diam., bears N. $17\frac{1}{2}^{\circ}$ E., 22 lks. dist., mkd. NBWM.

A burned stump, 24 ins. diam., bears S. $68\frac{1}{4}^{\circ}$ E., 27 lks. dist., no mks.

A pine, 30 ins. diam., bears S. 32° E., 31 lks. dist., mkd. NBWMIR 42 $\frac{1}{2}$ M BT.


An oak, 10 ins. diam., bears S. 16° W., 39 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 24 E.

CHAINS



from which

A pine, 8 ins. diam., bears N. 88° E., 44 lks. dist., mkd. 42 1/2 M FAIR BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 15 lks. S. of a fence bearing irregularly E. and W.

Angle point 258, monumented by a pine tree, 24 ins. diam. mkd. BMFR on N. face and PNBWMIR 258 on S. face, from which the remains of the orig. bearing trees

A pine, 25 ins. diam., bears S. 24 1/2° W., 40 lks. dist., mkd. with an overgrown blaze.

A dead oak stump, 8 ins. diam., bears S. 56 1/2° W., 22 lks. dist., no mks.

from which a new bearing tree

A pine, 14 ins. diam., bears S. 76° E., 80 lks. dist., mkd. AP258 FAIR BT.

From this cor., the closing corner of secs. 7 and 12, T. 8 N., Rs. 23 and 24 E., at its intersection with the Fort Apache Indian Reservation Boundary, which is an iron post, 2 ins. diam., projecting 18 ins. above ground, in a collar of stone, with brass cap mkd. and witnessed as described in the official record of the 1929 completion survey of the E. bdy. of T. 8 N., R. 23 E., bears S. 62° W., 14 lks. dist.

Angle point is 5 lks. S. of a fence, bearing irregularly E. and SW.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 23 E.

CHAINS

Township 8 North, Range 23 East, G&SR M., Arizona

The Fort Apache Indian Reservation Boundary was resurveyed in 1906 by J. B. Wright. The subdivisional lines were surveyed in 1908 by S. E. Blout.

Remonumentation, T. 8 N., R. 23 E., G&SR M., Arizona

The 45 mile cor., monumented by a malpais stone, 18 x 14 x 10 ins., set 4 ins. in the ground in a scattered mound of stone, mkd. NBWMIR on S. face and with faint scribe marks on N. face, from which the remains of the orig. bearing trees

A stump hole, bears N. 77° W., 51 lks. dist.


A burned oak stump, 10 ins. diam., bears N. 72° W., 52 lks. dist., no mks.

A stump hole, bears N. 69½° W., 56 lks. dist.

A stump hole, bears N. 49½° W., 58 lks. dist.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 12 ins. diam., bears S. 84° E., 15 lks. dist., mkd. 45M BT.

A pine, 12 ins. diam., bears S. 14° W., 38 lks. dist., mkd. 45M FAIR BT.

A pine, 12 ins. diam., bears N. 9° W., 29 lks. dist., mkd. 45M BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 1 ch. S. of a fence, bearing irregularly E. and W.

The 45½ mile cor. and angle point 278, monumented by a malpais stone, 16 x 14 x 10 ins., set 8 ins. in the ground, mkd. BMFR on N. face and NBWMIR 45½M on S. face, with mound of stone to the N. From the cor., the remains of the orig. bearing trees

A burned out stump hole, bears N. 41½° E., 86 lks. dist.

A burned out stump hole, bears S. 7° W., 76 lks. dist.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 23 E.


CHAINS

A stump hole, bears S. $14\frac{1}{2}^{\circ}$ W., 83 lks. dist.

A rotted burned pine stump, 6 ins. diam., bears West, 32 lks. dist., no mks.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



No new bearing trees available.

Rebuild the orig. mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 70 lks. S. of a fence, bearing irregularly SE. and W.

The 46 mile cor. and angle point 282, monumented by a galv. pipe, $\frac{1}{2}$ in. diam., 18 ins. long, with 10 in. spike under pipe, verified by record course and dist. from the remains of the orig. bearing trees

A pine, 32 ins. diam., bears N. 30° E., 21 lks. dist., mkd. 46.


A stump hole bears S. 68° E., 33 lks. dist.

A pine stump, 20 ins. diam., with nail in top, bears S. 18° E., 21 lks. dist., mkd. with faint scribe marks.

A pine stump, 20 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ W., 52 lks. dist., mkd. with faint scribe marks.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 47° E., 38 lks. dist., mkd. 46M FAIR BT.

A pine, 10 ins. diam., bears S. 22° W., 61 lks. dist., mkd. 46M FAIR BT.

Deposit galv. pipe in hole with iron post.

Cor. is 40 lks. S. of rim road.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 23 E.

CHAINS

Angle point 283, monumented by a 12 in. rebar, falls on N. edge of rim road, verified by record course and dist. from the orig. bearing trees

A pine, 27 ins. diam., bears N. $46\frac{1}{2}^{\circ}$ E., 37 lks. dist., mkd. AP283.

A pine, 25 ins. diam., bears N. 64° E., 43 lks. dist., mkd. AP283.

from which new accessories

A pine, 14 ins. diam., bears S. 41° E., 70 lks. dist., mkd. AP283 FAIR BT.

An iron post, set 26 ins. in the ground, for a reference monument, bears S. 19° W., 75.8 lks. dist., mkd. T8N R23E AP283 RM 50 FT FAIR 1968 and an arrow pointing to the true cor. Raise a mound of stone to the SE.

Angle point 286, monumented by a pine tree, 24 ins. diam., mkd. MIR on S. face and with an overgrown blaze on N. face, from which new bearing trees

A pine, 20 ins. diam., bears S. 8° W., 71 lks. dist., mkd. AP286 FAIR BT.

A pine, 15 ins. diam., bears S. 64° W., 43 lks. dist., mkd. AP286 FAIR BT.

Angle point is about 160 lks. S. of rim road and 40 lks. S. of a fence, bearing irregularly E. and NW.

The 47 mile cor. and angle point 287, monumented by a malpais stone, 24 x 12 x 8 ins., set 12 ins. in the ground, mkd. NBWMIR on S. face, from which the remains of the remaining orig. bearing trees


An oak stump, 6 ins. diam., bears N. 69° E., 27 lks. dist., mkd. with faint scribe marks.

A pine, 18 ins. diam., bears S. 25° W., 102 lks. dist., scribe marks burned out.

A stump hole, bears S. $40\frac{1}{2}^{\circ}$ W., 82 lks. dist.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 20° E., 26 lks. dist., mkd. 47M FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 105 lks. S. of rim road and 35 lks. N. of a fence, bearing irregularly SE. and NW.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 23 E.

CHAINS

The $47\frac{1}{2}$ mile cor. and angle point 290, monumented by a malpais stone, 12 x 12 x 6 ins., set 8 ins. in the ground, mkd. NBWMIR $47\frac{1}{2}$ on S. face, with mound of stone to the N. From the cor., the remains of the orig. bearing trees

A pine, 24 ins. diam., bears N. $6\frac{3}{4}^{\circ}$ E., 44 lks. dist., mkd. NBWMIR $47\frac{1}{2}$ M BT.


A pine stump, 18 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ E., 34 lks. dist., mkd. NBWMIR $47\frac{1}{2}$ M BT.

A stump hole, with roots in ground, bears S. 32° W., 22 lks. dist.

An oak, 15 ins. diam., bears N. $70\frac{3}{4}^{\circ}$ W., 94 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 29° W., 46 lks. dist., mkd. $47\frac{1}{2}$ M FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 250 lks. S. of rim road and 5 lks. S. of a fence, bearing irregularly SE. and NW.


Angle point 292, monumented by a malpais stone, 12 x 9 x 6 ins., broken at the ground, set in a mound of stone, mkd. BMFR on N. face and AP292 on S. face, verified by record course and dist. from the orig. bearing trees

A dead oak, 9 ins. diam., bears S. 4° E., 22 lks. dist., mkd. AP292 BT.

An oak, 12 ins. diam., bears S. 31° W., 25 lks. dist., mkd. AP292 BT.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.



from which

The 48 mile cor., bears N. $53^{\circ}37'$ W., 170 lks. dist.

Bury the orig. cor. stone alongside the iron post.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 23 E.

CHAINS

Cor. is 65 lks. S. of rim road and 20 lks. S. of a fence, bearing irregularly SE. and NW.

The 48 mile cor., monumented by a malpais stone, 20 x 14 x 6 ins., set 12 ins. in the ground, mkd. BMFR on N. face and NBWMIR 48M on S. face, with mound of stone to the N. From the cor., the remains of the remaining orig. bearing trees


An oak stump, 14 ins. diam., bears North, 64 lks. dist., no mks.

An alligator juniper stump, 20 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ E., 32 lks. dist., mkd. NBWMIR 48M BT.

A stump hole, bears S. 52° W., 41 lks. dist.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 9 ins. diam., bears S. 36° E., 30 lks. dist., mkd. 48M FAIR BT.

A pine, 8 ins. diam., bears S. 70° W., 15 lks. dist., mkd. 48M FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 70 lks. S. of rim road and 25 lks. S. of a fence, bearing irregularly SE. and NW.

Angle point 293, monumented by a dead pine stump, 26 ins. diam., mkd. APNBWMIR on S. face and BMFR on N. face, from which new accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears S. 7° E., 60.6 lks. dist., mkd. T8N R23E AP293 RM 40 FT FAIR 1968 and an arrow pointing to the true cor.

A pine, 10 ins. diam., bears S. 55° W., 83 lks. dist., mkd. AP293 FAIR BT.

Angle point is 30 lks. N. of rim road and 95 lks. N. of a fence, bearing irregularly SE. and W.

Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 23 E.

CHAINS

Angle point 294, monumented by a dead oak tree, 15 ins. diam., mkd. APNBWMIR 294 on S. face and with an overgrown blaze on N. face. I cut open blaze and find scribe marks BMFR. From the cor., a new accessory

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. $53\frac{1}{2}^{\circ}$ W., 15.2 lks. dist., mkd. T8N R23E AP295 RM 10 FT FAIR 1968 and an arrow pointing to the true cor. Raise a mound of stone to the S.

From this cor., the closing cor. of secs. 5 and 6, T. 8 N., R. 23 E., at its intersection with the Fort Apache Indian Reservation Boundary, which is a malpais stone, 12 x 12 x 10 ins. above ground, firmly set, mkd. CC on N. face, and witnessed as described in the official record of the 1908 survey of the subdivisional lines of T. 8 N., R. 23 E., bears N. $67^{\circ}15'$ E., 32 lks. dist.

Angle point is about 185 lks. S. of rim road and 120 lks. S. of a fence, bearing irregularly E. and W.

Angle point 295, monumented by a pine tree, 20 ins. diam., mkd. with burned scribe marks APNBWMIR 295 on S. face and with an overgrown blaze on N. face, from which new accessories

A pine, 10 ins. diam., bears S. 60° E., 66 lks. dist., mkd. AP295 FAIR BT.

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 34° W., 18.2 lks. dist., mkd. T8N R23E AP295 RM 12 FT FAIR 1968 and an arrow pointing to the true cor.

Angle point is 30 lks. S. of rim road and 50 lks. N. of a fence, bearing irregularly SE. and W.

Angle point 298, monumented by a pine tree, 24 ins. diam., mkd. FR on N. face and APNBWMIR on S. face, from which new bearing trees

A pine, 5 ins. diam., bears S. 32° E., 90 lks. dist., mkd. AP298 FAIR BT.

A pine, 8 ins. diam., bears S. 50° W., 103 lks. dist., mkd. AP298 FAIR BT.

Angle point is 20 lks. N. of rim road and 85 lks. N. of a fence, bearing irregularly E. and SW.

The 49 mile cor. and angle point 299, monumented by a malpais stone, 15 x 12 x 12 ins., set 6 ins. in the ground, mkd. 49M on NE. face, from which the remains of the orig. bearing trees

An alligator juniper, 20 ins. diam., bears N. 57° E., 51 lks. dist., mkd. with faint scribe marks. (Note: record dist. 48 lks.).

A stump hole, bears S. $8\frac{1}{2}^{\circ}$ E., 43 lks. dist.

A stump hole, bears N. $44\frac{3}{4}^{\circ}$ W., 29 lks. dist.


Remonumentation, Fort Apache Indian Reservation Bdy.
T. 8 N., R. 23 E.

CHAINS

A stump hole, bears N. $34\frac{1}{2}^{\circ}$ W., 31 lks. dist.,
with pieces of stump still in hole.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar
of stone, brass cap mkd.

T8N R23E
S6
AP299

49M
FAIR
1968

from which

A pine, 8 ins. diam., bears N. 88° E., 42 lks.
dist., mkd. 49M FAIR BT.

A pine, 8 ins. diam., bears S. 23° W., 38 lks.
dist., mkd. 49M FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 100 lks. S. of rim road and 40 lks. S. of a
fence, bearing irregularly NE. and W.

General Statement

The official record was found to be in error for some
of the bearings and distances given for the bearing
trees. A few of the trees were misnamed as to specie.
A ring growth count was made on several trees which
proved they were marked at the time of the original
survey.

Where the original corner monument appeared to be
undisturbed, it was accepted as the true point for the
corner.

25

BOOK 4858

CERTIFICATE OF SURVEY

(I) (~~Was~~), Howard H. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 17th day of June, 19 68, (I) (~~Was~~) have remonumented a portion of the cadastral survey corners of the Fort Apache Indian Reservation Boundary in Township 9 North, Range 24 East, and Township 8 North, Ranges 23 and 24 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 14, 1969 (Date) Howard H. Thomas (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date JUL 3 0 1969

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners of the Fort Apache Indian Reservation Boundary in Township 9 North, Range 24 East, and Township 8 North, Ranges 23 and 24 East, all of the Gila and Salt River Meridian, Arizona, executed by Howard H. Thomas, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 3 1970 (Date) Clark F. Sumner (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

~~(Date) (Chief, Division of Cadastral Survey) GPO 849-626~~