

Form 9180-6
(April 1965)
(formerly 4-679)

BOOK 4861
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

SURVEY

of

PARTIAL SUBDIVISION OF SECTION 22

and

SURVEY OF TRACT 37

TOWNSHIP 1 NORTH, RANGE 14 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Louis D. Gilbert

Supervisory Cadastral Surveyor

Under special instructions dated April 9, 1969, which provided for the surveys
included under Group Number 506, approved April 10, 1969,
and assignment instructions dated April 29, 1969.

Survey commenced May 7, 1969


Survey completed May 9, 1969

11A

BOOK 4861
INDEX DIAGRAM

Township 1 North, Range 14 East,

| | | | | | |
|----|----|----|----|----|----|
| 6 | 5 | 4 | 3 | 2 | 1 |
| 7 | 8 | 9 | 10 | 11 | 12 |
| 18 | 17 | 16 | 15 | 14 | 13 |
| 19 | 20 | 21 | 22 | 23 | 24 |
| 30 | 29 | 28 | 27 | 26 | 25 |
| 31 | 32 | 33 | 34 | 35 | 36 |



Line 1-2, Tract 37 Page 4
Line 2-3, Tract 37 Page 4
Line 3-4, Tract 37 Page 5
Line 4-1, Tract 37 Page 6

Township 1 North, Range 14 East
Gila and Salt River Meridian, Arizona

CHAINS

The west boundary and the west half mile of the north and south boundaries of Section 22 were surveyed by W. B. Kimmel in 1923.

The following field notes are those of a survey of the north and south centerline of Section 22, and a survey of Tract 37 in the SW $\frac{1}{4}$ SE $\frac{1}{4}$ of the unsurveyed portion of Section 22, Township 1 North, Range 14 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated April 9, 1969.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2 $\frac{1}{2}$ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, as scaled from USGS quadrangle "Inspiration Arizona", edition of 1947, scale 1:24000 is Latitude: 33°24'28" N., Longitude: 110°55'08" W.

The magnetic declination was found to be 14° East.

Partial Subdivision of Section 22

From the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented by an iron post, 1 in. diam., set 10 ins. above ground, brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$
1923

from which an original bearing tree:

An oak, 10 in. diam., bears N. 68°36' W., 100 lks. dist., blaze overgrown. (Record, N. 59°45' W., 100 lks. dist.) No evidence of the other orig. bearing tree.

The original iron post being badly eroded, I replace it with an iron post, set 24 ins. in the ground, brass cap mkd.

T1N R14E
 $\frac{1}{4}$ $\frac{S\ 22}{S\ 27}$
1969

from which

U.S.L.M. No. 2652, bears S. 66°42' E., 8.39 chs. dist. monumented by a wooden post, 6 ins. square, 5 ft. above ground, set in mound of stone, marked U.S.L.M. No. 2652 on E. side. (Record, S. 66°46' E., 8.39 chs. dist.)

BOOK 4861

Partial Subdivision of Section 22, T. 1 N., R. 14 E.

| CHAINS | |
|--------|--|
| 4.677 | <p>An iron pipe, 3 in. diam., set in concrete with 16 ins. above ground, bears S. 14°03' W., 1.73 chs. dist., mkd. S.E. JRM. (Record S. 13°35' W., 1.71 chs. dist.)</p> <p>Bury the original iron post alongside the corner. Raise a mound of stone W. of the cor. N. 0°07' E., on the N. and S. centerline of sec. 22. Over mountainous terrain through dense oak brush and manzanita interspersed with juniper timber.</p> <p>Intersect line 1-2 of Buckeye No. 3 lode, M.S. No. 3965. Point for Cor. No. 1, Tract 37. Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T1N R14E S 22 TR 37 COR 1 1969</p> <p>from which</p> <p>Cor. No. 1, Buckeye No. 3 lode, M.S. 3965, identical with Cor. No. 2, Buckeye No. 2 lode, M.S. 3965, bears N. 78°43' E., 0.157 chs. dist., monumented by an iron pipe, 2 in. diam., set in cement 2½ ft. above ground and in a mound of stone, cap mkd. U.S.M.S. No. 3965 1-Bky. 3, 2-Bky. 2.</p> <p>Cor. No. 2, Buckeye No. 3 lode, M.S. 3965, identical with Cor. No. 1, Buckeye No. 4 lode, M.S. 3965, bears S. 78°43' W., 8.934 chs. dist., monumented by an iron pipe, 2 in. diam., set in cement 2½ ft. above ground and in a mound of stone, cap mkd. U.S.M.S. No. 3965 2-Bky. 3, 1-Bky. 4.</p> <p>A bolt, ½ in. diam., set 3 ins. above ground, bears S. 78°43' W., 0.438 chs. dist.</p> |
| 8.10 | Graveled road, bears N. 50° E. and S. 50° W. |
| 9.80 | Telephone line, bears S. 82° E. and N. 82° W. |
| 10.25 | Webster Gulch, 60 lks. wide, 1½ ft. deep, drains irregularly E. |
| 10.75 | Fence, bears S. 80° E. and N. 80° W. |
| 11.20 | Enter fenced corral, bears E. and W., and SE. cor. of corral bears East, 25 lks. dist. |
| 11.70 | Leave fenced corral, bears E. and W., and NE. cor. of corral bears East 25 lks. dist. |
| 11.847 | <p>Point for Cor. No. 2, Tract 37. Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R14E S 22 COR 2 TR 37 1969</p> <p>Raise a mound of stone W. of the iron post.</p> |
| 13.395 | Intersect line 3-4 of unsurveyed Chief No. 5 lode, amended. |

Partial Subdivision of Sec. 22, T. 1 N., R. 14 E.

CHAINS

from which

The South End Center cor. of Chief No. 5 lode, amended, bears N. 74°06' E., 1.094 chs. dist., monumented by a wooden post, 6 ins. square, 5 ft. above ground set in a mound of stone, with brass plate, 3 ins. by 1 in. tacked to top of post, mkd. AMENDED S.E.C. CHIEF No. 5.

Cor. No. 4, Chief, No. 5 lode, Amended, bears S. 74°06' W., 4.103 chs. dist., monumented by a wooden post, 6 ins. square, 5 ft. above ground, set in a mound of stone, with brass plate tacked to top of post, mkd. AMENDED COR. No. 4, CHIEF No. 5.

Cor. No. 3, Chief No. 5 lode, Amended, bears N. 74°06' E., 5.808 chs. dist., monumented by a wooden post, 6 ins. square, 5 ft. above ground, set in a mound of stone, with brass plate tacked to top of post, mkd. AMENDED COR. No. 3 CHIEF No. 5.

An iron pipe 1 in. in diam., set flush with ground, bears S. 74°06' W., 0.464 chs. dist.

An iron pipe, 1 in. in diam., set flush with ground, bears N. 74°06' E., 5.344 chs. dist.

- 13.60 Telephone line bears E. and W.
 18.90 Center of stock pond, 60 lks. in diam.
 25.80 Wash, 10 lks. wide, 1½ ft. deep, drains irregularly SE.
 51.214 Intersect line 2-3 of Copper No. 11 lode, M.S. 3924.

from which

Cor. No. 2, Copper No. 11 lode, M.S. 3924, identical with Cor. No. 2, Copper No. 5 lode, M.S. 3924, bears S. 26°35' E., 0.339 chs. dist., monumented by an iron pipe, ¾ ins. in diam., set 26 ins. above ground and in a mound of stone, with 2 in. brass cap mkd. U.S. MINERAL SURVEY No. 3924-2-CNo. 5, 2-CNo. 11.

Cor. No. 3, Copper No. 11 lode, M.S. 3924, bears N. 26°35' W., 10.479 chs. dist., monumented by an iron pipe, ¾ ins. in diam., set 28 ins. above ground and in a mound of stone with 2 in. brass cap mkd. U.S. MINERAL SURVEY No. 3924-3-CNo. 11.

- 56.60 Fence, bears SE. and NW.
 60.079 Intersect line 3-4 of Copper No. 11 lode, M.S. 3924.

from which

Cor. No. 3, Copper No. 11 lode, M.S. 3924, bears N. 83°34' W., 4.621 chs. dist., hereinbefore described.

Cor. No. 1, Copper No. 9 lode, M.S. 3924, bears S. 83°34' E., 2.546 chs. dist., monumented by an iron pipe, ¾ ins. in diam., set 27 ins. above ground and in a mound of stone, with 2 in. brass cap mkd. U.S. MINERAL SURVEY NO. 3924-1-CNo. 9.

Partial Subdivision of Section 22, T. 1 N., R. 14 E.

CHAINS

79.87

The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented by an iron post, 1 in. in diam., set 6 ins. above ground, brass cap mkd.

$\frac{1}{4}$ S 15
S 22
1923

from which

An oak, 18 ins. in diam., bears N. 6° E., 79 lks. dist., mkd. with an overgrown blaze.

An oak stump, 12 ins. in diam., bears S. 73° W., 117 lks. dist.

Land, heavy rolling to mountainous.
Soil, rocky loam.
Timber, scattered juniper.
Undergrowth, oak brush and manzanita.

Survey of Tract 37

Beginning at Cor. No. 1, Tract 37, hereinbefore described.

N. 0°07' E., along the W. bdy. of Tract 37, and on the N. and S. centerline of sec. 22.

7.17

Cor. No. 2, Tract 37, hereinbefore described.

Thence, N. 73°28' E., along the N. bdy. of Tract 37.

3.30

Wash, 20 lks. wide, 1 ft. deep, drains S. 10° E.

5.796

Intersect line 1-4 of Huntessville lode, M.S. No. 2652.

Point for Cor. No. 3, Tract 37

Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.

T1N R14E
S 22

COR 3
TR 37
1969

from which

Cor. No. 1, Huntessville lode, M.S. No. 2652, bears S. 17°00' E., 5.401 chs. dist., monumented by an iron post, 4 ins. diam., set in cement, cap mkd. HUNTESVILLE-1-2652.

Note: record was 4 in. square wooden post witnessed 51 ft. east.

Survey of Tract 37, T. 1 N., R. 14 E.

| CHAINS | |
|--------|--|
| | <p>Cor. No. 4, Huntessville lode, M.S. No. 2652, identical with cor. No. 1, Ellen lode, M.S. No. 3924, bears N. 17°00' W., 2.889 chs. dist., monumented by an iron post, 3 ins. diam., set in cement, cap mkd. HUNTESVILLE-4-2652; ELLEN-1-3924.</p> <p>A 1/2 in. iron pipe, bears N. 17°00' W., 1.431 chs. dist.</p> <p>Telephone line, bears N. 17° W., 5 lks. dist.; line bears E. and W.</p> <p>Raise a mound of stone N. of the cor.</p> <p>Thence, S. 17°00' E., along the E. bdy. of Tract 37.</p> |
| .50 | Fence, bears S. 80° E. and N. 80° W. |
| 1.60 | Webster Gulch, 40 lks. wide, 1 ft. deep, drains irregularly E. |
| 3.30 | Graveled road, bears irregularly E. and W. |
| 3.80 | Television Cable, bears N. 55° E. and S. 55° W. |
| 5.401 | Cor. No. 1, Huntessville lode, M.S. No. 2652, hereinbefore described. |
| 6.40 | SE. cor. of shed on line. |
| 7.60 | Intersect line 1-2, Buckeye No. 2 lode, M.S. No. 3965. |
| | <p>Point for Cor. No. 4, Tract 37.</p> <p>Cement a brass tablet, with a 3 in. stem, in solid rock, cap mkd.</p> <p style="text-align: center;">T1N R14E S 22</p> <div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 10px auto;"> <p style="margin: 0;">TR 37 COR 4</p> </div> <p style="text-align: center;">1969</p> <p>from which</p> <p>Cor. No. 1, Buckeye No. 2 lode, M.S. No. 3965, identical with Cor. No. 1, Buckeye No. 1 lode, M.S. No. 3965, bears N. 78°43' E., 1.256 chs. dist., monumented by an iron pipe, 2 ins. diam., set in cement and in a mound of stone, cap mkd. USMS No. 3965 1 BKY 1; 1 BKY 2.</p> <p>Cor. No. 2, Buckeye No. 2 lode, M.S. No. 3965, identical with Cor. No. 1, Buckeye No. 3 lode, M.S. No. 3965, bears S. 78°43' W., 7.789 chs. dist., hereinbefore described.</p> <p>SW. cor. of shed measuring 13 ft. by 23 ft., bears N. 10°05' W., 4.97 chs. dist., with the long side of the shed bearing N. 85° E.</p> <p>SE. cor. of shed measuring 9 ft. by 16 ft., bears N. 13°15' W., 4.59 chs. dist., with the long side of the shed bearing West.</p> |

Survey of Tract 37, T. 1 N., R. 14 E.

| CHAINS | |
|--------|--|
| | SE. cor. of shed measuring 8 ft. by 10 ft., bears N. 17°00' W., 1.20 chs. dist., with the long side of the shed bearing N. 57° W. |
| | NE. cor. of shed measuring 8 ft. by 11 ft., bears N. 26°11' W., 3.37 chs. dist., with the long side of the shed bearing S. 43° W. |
| | NE. cor. of shed measuring 9 ft. by 11 ft., bears N. 29°24' W., 3.14 chs. dist., with the long side of the shed bearing S. 40° W. |
| | NE. cor. of shed measuring 12 ft. by 15 ft., bears N. 30°18' W., 1.48 chs. dist., with the long side of the shed bearing S. 47° E. |
| | SE. cor. of house measuring 16 ft. by 37 ft., bears N. 34°33' W., 3.69 chs. dist., with the long side of the house bearing N. 55° E. |
| | NE. cor. of toilet measuring 4 ft. by 4 ft., bears N. 35°02' W., 2.38 chs. dist., a side bears S. 45° E. |
| | SE. cor. of shed measuring 10 ft. by 11 ft., bears N. 35°58' W., 3.63 chs. dist., with the long side of the shed bearing N. 45° E. |
| | SE. Cor. of shed measuring 8 ft. by 10 ft., bears N. 36°34' W., 4.04 chs. dist., with the long side of the shed bearing N. 30° W. |
| | NE. cor. of shed measuring 15 ft. by 20 ft., bears N. 37°07' W., 4.24 chs. dist., with the long side of the shed bearing N. 28° W. |
| | SE. cor. of shed measuring 10 ft. by 12 ft., bears N. 39°05' W., 3.84 chs. dist., with the long side of the shed bearing N. 55° E. |
| | SE. cor. of old house measuring 12 ft. by 15 ft., bears N. 40°28' W., 4.15 chs. dist., with the long side of the old house bearing N. 35° W. |
| | SE. cor. of chicken pen measuring 9 ft. by 10 ft., bears N. 40°48' W., 2.92 chs. dist., with the long side of the chicken pen bearing N. 40° W. |
| | NE. cor. of chicken house measuring 4 ft. by 7 ft., bears N. 40°57' W., 3.40 chs. dist., with the long side of the chicken house bearing N. 40° W. |
| | NE. cor. of shed measuring 10 ft. by 24 ft., bears N. 45°12' W., 3.04 chs. dist., with the long side of the shed bearing S. 45° E. |
| | Center of metal water tank, 14 ft. in diam., bears N. 45°13' W., 1.38 chs. dist. |
| | SE. cor. of shed measuring 10 ft. by 13 ft., bears N. 47°06' W., 3.25 chs. dist., with the long side of the shed bearing N. 45° W. |
| | Thence S. 78°43' W., along the S. bdy. of Tract 37. |
| 1.50 | Wash, 10 lks. wide, 1 ft. deep, drains N. |

Survey of Tract 37, T. 1 N., R. 14 E.

| CHAINS | |
|--|--|
| 3.20 | Top of spur, slopes N. |
| 5.90 | Wash, 10 lks. wide, 1 ft. deep, drains N. |
| 7.789 | Cor. No. 2, Buckeye No. 2 lode, M.S. No. 3965 identical with Cor. No. 1, Buckeye No. 3 lode, hereinbefore described. |
| 7.946 | Cor. No. 1, Tract 37, point of beginning. |
| GENERAL DESCRIPTION | |
| <p>The land in Section 22, Township 1 North, Range 14 East, varies from heavy rolling to mountainous, with Webster Gulch cutting through the southern portion of the section. A portion of Camelback Mountain lies in the northern portion of the section.</p> <p>Scattered junipers, together with dense oak brush and manzanita covers a large portion of the section. There has been considerable mineral activity in the past.</p> <p>There are several improvements which lie in Tract 37, all of which ties were given in these field notes.</p> | |

9

CERTIFICATE OF SURVEY

(I) (~~We~~), Louis D. Gilbert, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 9th day of April, 1969, (I) (~~We~~) have made a survey of partial subdivision of Section 22 and a survey of Tract 37, Township 1 North, Range 14 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 4, 1969
(Date)

Louis D. Gilbert
~~LOUIS D. GILBERT~~
Supervisory Cadastral Surveyor

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date OCT 8 1969

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the survey of partial subdivision of Section 22 and the survey of Tract 37, Township 1 North, Range 14 East, Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert

having been critically examined and found correct, are hereby approved.

JUN 16 1970
(Date)

Clark I. Linn
(Chief, Division of Cadastral Survey)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Cadastral Survey) GPO 849-1086~~