

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of a

Portion of the

SUBDIVISIONAL LINES

SURVEY

of

Portions of the

SUBDIVISION and MEANDERS

and

ESTABLISHMENT OF THE MEDIAL LINE OF THE GILA RIVER

in SECTION 9

TOWNSHIP 7 SOUTH, RANGE 26 EAST

Of the Gila & Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Paul G. Bauer, Cadastral Surveyor

Robert F. Johnson, Surveying Technician

Under special instructions dated November 22, 19 65, which provided for the surveys
included under Group Number 439, approved November 29, 1965,
and assignment instructions dated November 29, 19 65.

Survey commenced February 7, 19 66

Survey completed March 11, 19 66

1A

BOOK 4865

INDEX DIAGRAM

Township 7 South, Range 26 E

6	5	4 6	3	2	1
7	8 4	9	2 10	11	12
18	17	3 16	1 15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Sec..9 -----	Pg. 7
NE $\frac{1}{4}$ -----	" 8-9
NW $\frac{1}{4}$ -----	" 10
Medial Line - SE $\frac{1}{4}$ NE $\frac{1}{4}$ -----	" 11
Meanders - NW $\frac{1}{4}$ NW $\frac{1}{4}$ -----	" 11

Township 7 South, Range 26 East
Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>Township 7 South, Range 26 East, and the meanders of the right bank of the Gila River were originally surveyed in 1875 by T. F. White.</p> <p>The following field notes are those of a dependent resurvey of a portion of the subdivisional lines, designed to restore the corners according to the best available evidence, a survey of the subdivision and a portion of the meanders in sec. 9, and survey of the medial line of the Gila River in the SE$\frac{1}{4}$ NE$\frac{1}{4}$ of sec. 9, as the river was returned by the original survey.</p> <p>Between the time of the official survey in 1875 and the present survey, the Gila River has shifted its course to some extent by normal erosion. The major changes have been made by large floods and by diversion dams and dykes.</p> <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated November 22, 1965.</p> <p>Only the true line bearings and horizontal distances are given in these notes. Unless described, all corner monuments used in this survey were standard iron posts 30 inches long, 2$\frac{1}{2}$ inches diameter, flanged at the base, and with brass caps riveted to the top.</p> <p>The geographic position of the southeast corner of sec. 9 as scaled from U.S.G.S. Quadrangle "Safford, Arizona, 1960, is: Latitude 32°49'50.3" North, and Longitude 109°42'53.8" West.</p> <p>The mean magnetic declination was found to be 13° East.</p>				
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, Tp. 7 S., R. 26 E.</p>				
	<p>Reestablishment of a Portion of the Survey Executed by T. F. White in 1875</p>				
	<p>Beginning at the cor. of secs. 15, 16, 21 and 22, monumented by a brass tablet, 1$\frac{1}{2}$ ins. diam., set flush with the surface of an intersection of surfaced roads bearing N., S., E. and W., by G. P. Smith, local surveyor. This point is used by adjacent land owners and the city of Safford, Arizona; it is accepted as the best available evidence of the original position of the cor., brass tablet mkd.</p>				
	<table border="0"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S16</td> <td style="padding-left: 5px;">S15</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S21</td> <td style="padding-left: 5px;">S22</td> </tr> </table>	S16	S15	S21	S22
S16	S15				
S21	S22				
	<p>N. 0°01' E., bet. secs. 15 and 16.</p> <p>Along center of surfaced road, bears N. and S.</p>				
5.40	<p>Southern Pacific Railroad (branch line), bears S. 68°30' E. and N. 68°30' W., curving to the NW.</p>				
7.10	<p>U. S. Highway No. 70, bears S. 68°30' E., curving to the E. and N. 68°30' W., curving to the NW.</p>				
	<p>Thence, along center of a bladed road, bears N.</p>				
39.45	<p>Union Canal, 30 lks. wide, 6 ft. deep, flows W.</p>				

Dependent Resurvey, Subdivision, T. 7 S., R. 26 E., Arizona

CHAINS		
39.77	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16 at proportionate dist.; there is no remaining evidence of the orig. cor. and the cor. point is not monumented.	
40.70	Intersection of bladed roads bearing N., E. and S.; continue along center of bladed road bearing N.	
74.10	Curve in bladed road, bears S. and NW.; thence over cultivated land.	
79.54	Point for the cor. of secs. 9, 10, 15 and 16 at proportionate dist.; there is no remaining evidence of the orig. cor. and the cor. is not monumented.	
	<p>from which</p> <p>The true point for the cor. of secs. 7, 12, 13 and 18, T. 7 S., Rs. 26 and 27 E., bears S. $89^{\circ}58'$ E., 238.70 chs. dist. From this true point, the witness cor., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record of the 1957 resurvey, bears N. $0^{\circ}05'$ E., 9.00 chs. dist. This control line was fully retraced, and careful search was made for evidence of intervening corners, none of which was recovered.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, none; undergrowth, none.</p>	
	N. $0^{\circ}04'$ W., bet. secs. 9 and 10.	
	Over nearly level land.	
0.23	Fence, bears E. and W.	
0.40	Bladed road, bears E. and W.	
3.00	Fence, bears E. and W., thence over cultivated lands covered with silt and debris from a recent flood.	
26.42	Point for the 1875 meander cor. on the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; this point is not monumented.	
27.98	Point for the 1875 meander cor. on the right bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; this point is not monumented.	
30.84	Left bank of an abandoned channel of the Gila River, 3 ft. high, bears N. 80° E. and S. 80° W., thence over sandy and gravelly river bottom land.	
39.77	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p>T7S R26E</p> <p>$\frac{1}{4}$</p> <p>S 9 S10</p> <p>1966</p>	

Dependent Resurvey, Subdivision, T. 7 S., R. 26 E., Arizona

CHAINS					
	<p>from which</p> <p>A diversion dam, blocking off the above-mentioned channel of the Gila River, bears S. 66° E., 19.50 chs. dist.</p> <p>Set a cottonwood post, 5 ft. long, 5 ins. diam., 18 ins. in the ground, alongside the iron post.</p>				
44.00	Present left bank of the Gila River, a low gravel bar, bears S. 60° E. and N. 60° W.				
46.45	Present right bank of the Gila River, bears S. 52° E. and N. 52° W., asc. steep and broken SW. slope.				
50.00	Top of ascent, bears SE. and NW., thence over rolling land and through moderate creosote bush and cacti.				
59.66	Point for the N. 1/16 sec. cor. of secs. 9 and 10, at proportionate dist.; this cor. point was not monumented.				
59.75	Wash, 9 lks. wide, 1 ft. deep, drains SW. from NW.				
62.60	Track road, bears S. 60° E. and NW.				
74.20	Water pipeline, underground, bears S. 78° E. and N. 78° W.				
79.54	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a granite stone, 16 x 10 x 8 ins., firmly set and mkd. with 3 notches on the E. face and 5 notches on the S. face, as described in the official record of the 1875 survey.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R26E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> </table> <p>1966</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Build a mound with stones W. of the iron post.</p> <p>Land, nearly level to rolling. Soil, sandy loam in S. ½ and shallow, gravelly loam in the N ½. Timber, none. Undergrowth, moderate creosote bush in the area north of the river.</p>	S 4	S 3	S 9	S 10
S 4	S 3				
S 9	S 10				
	<p>From the proportionate point for the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°30' W., bet. secs. 9 and 16.</p> <p>Over nearly level land, along the N. edge of a cultivated field.</p>				
6.01	Fence, bears S. 35° E. and N. 35° W., for 31 lks. to a cor. of fences bearing E. and S. 35° E.				
6.82	Intersection of bladed roads bearing E. and S. 35° E., and a surfaced road bearing W.				

Dependent Resurvey, Subdivision, T. 7 S., R. 26 E., Arizona


CHAINS	
	Thence along the S. side of a surfaced road and through the village of Hollywood, Arizona.
10.12	Side street, bears S.
16.02	Side street, bears S.
19.72	Side street, bears S.; leave village.
35.52	Farm road, bears S.
39.69	Point for the $\frac{1}{2}$ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor. and the cor. is not monumented.
50.17	Stockton Wash, a drainage ditch, 30 lks. wide, and 6 ft. deep, drains N. $1^{\circ}48'$ E.
76.44	U. S. Highway No. 70, 4 lanes wide, bears S. 50° E. and N. 50° W.
79.19	Graveyard Wash, a rock-lined drainage ditch, 80 lks. wide and 8 ft. deep, drains N.
79.38	<p>The cor. of secs. 8, 9, 16 and 17, monumented by an iron post, 2 ins. diam., with an illegible marking on a $2\frac{1}{2}$ in. brass cap, set flush with the bottom of the drainage ditch.</p> <p>This cor. was set by a local surveyor; is used by the city of Safford, Arizona; and is accepted as the best remaining evidence of the orig. cor.</p> <p>Land, nearly level. Soil, gravelly loam. Timber, none. Undergrowth, none.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. $0^{\circ}05'$ W., bet. secs. 8 and 9.</p> <p>Along the W. slope of Graveyard Wash.</p>
2.73	U. S. Highway No. 70, 4 lanes wide, bears S. 50° E. and N. 50° W.
34.80	Small wooden bridge, crosses Graveyard Wash from E. to W.
39.78	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, collar of stones to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R26E $\frac{1}{2}$ S 8 S 9 1966</p>
56.80	Point for the 1875 meander cor. on the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; this point was not monumented.

Dependent Resurvey, Subdivision, T.7S.,R.26 E.,Arizona

CHAINS

- 58.65 Point for the 1875 record meander cor. on the right bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; this point is not monumented.
- 59.67 Point for the N 1/16 sec. cor. of secs. 8 and 9 at proportionate dist.; this point was not monumented.
- 66.80 The present left bank of the Gila River, 5 ft. high, bears E. and W., and end of graveyard wash.
- 68.50 Main channel of Gila River, 3.40 chs. wide, 4 ft. deep, flows N. 88° W.; thence over low gravel bar.
- 74.00 The present right bank of the Gila River, bears S. 75°54' E. and N. 75°54' W., and point for the meander cor. of secs. 8 and 9.


Set the iron post 18 ins. in the ground, collar of stones to top, brass cap mkd.



Leave low gravel bar; enter moderate salt cedar.

- 79.56 Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 22 ins. in the ground, collar of stones to top, brass cap mkd.



from which


The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record of the 1960 resurvey, bears N. 0°06' E., 79.68 chs. dist.

The cor. of secs. 5, 6, 7 and 8, monumented by an iron rod, ½ in. diam., set by a local surveyor, Robert Feather, bears S. 89°54' W., 79.73 chs. dist. This cor. point is accepted and is being used by the city of Safford, Arizona, and other interested land owners. It is the best remaining evidence of the orig. cor.

These control lines were fully retraced, and careful search was made for evidence of intervening cors., none of which was recovered.

At the cor. point,

Set the iron post 22 ins. in the ground, collar of stones to top, brass cap mkd.



Dependent Resurvey, Subdivision, T.7 S., R.26 E., Arizona

CHAINS	
	<p>Bury the iron rod alongside the iron post. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, moderate salt cedar in the extreme N. portion.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10. N. 89°29' W., bet. secs. 4 and 9. Over gently rolling land, through moderate creosote bush and scattered cacti.</p>
19.86	Point for the E 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.; this point is not monumented.
23.80	Fence, bears S. 78° E. and N. 78° W.
24.30	Water pipeline, underground, bears same as fence.
37.55	Telephone line, bears E. and N. 80° W.
39.72	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor. and the cor. was not monumented.
43.70	Bladed road, bears S. 80° E. and N. 80° W.; enter brushy bottom land.
53.75	Track road, bears S. 40° E. and N. 40° W.
57.50	Track road, bears N. and S. 20° E.
59.58	Point for the W 1/16 sec. cor. of secs. 4 and 9, at proportionate dist. Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T7S R26E $\frac{W\ 1}{16} \quad \frac{S\ 4}{9}$ 1966</p>
60.80	Build a mound with stones N. of the iron post. Power line, bears S. 55° E. and N. 55° W.
61.00	Lone Star Wash, 65 lks. wide, 2 ft. deep, drains S. 25° E.
66.70	Graham Canal, 30 lks. wide, 4 ft. deep, flows N. 55° W.; thence over river bottom land subject to flooding.
79.44	The cor. of secs. 4, 5, 8 and 9. Land, gently rolling E. ½ mile; nearly level W. ½ mile. Soil, gravelly loam E. ½ mile; sandy loam in W. ½ mile. Timber, none. Undergrowth, creosote bush, scrub mesquite and cacti.

Subdivision of Section 9, T. 7 S., R. 26 E., Arizona


CHAINS	Subdivision of Sec. 9, T7S, R26E
	<p>From the point for the 1/4 sec. cor. of secs. 9 and 16. N. 0°04'30" W., on the N. and S. center line of sec. 9. Over nearly level cultivated land.</p>
0.18	Surfaced road, bears E. and W.
0.50	Cor. of fences bearing N., E. and W.
0.56	Irrigation ditch, 5 lks. wide, 2 ft. deep, flows W.
27.80	Irrigation ditch, 5 lks. wide, 2 ft. deep, flows W.
39.78	Point for the center 1/4 sec. cor. of sec. 9 at the intersection with the E. and W. center line of sec. 9. This cor. point was not monumented.
54.87	Fence, bears E. and W. 44 lks. to a cor. of fences bearing N., S. and E.
55.80	Leave cultivated land, bears SE. and N. 80° W.; enter dense salt cedar undergrowth.
59.67	Point for the CN 1/16 sec. cor. of sec. 9; this cor. point was not monumented. From this point, the S. end of a diversion dam, bearing North across the Gila River, and belonging to Graham Canal Co., bears N. 36°45' E., 6.30 chs. dist.
63.80	The present left bank of the Gila River, a cut bank, 2 ft. high, bears N. 80° E. and S. 80° W.
67.45	The present right bank of the Gila River, a low gravel bar, bears N. 80° E. and S. 80° W.
76.80	Leave lowlands, bears S. 70° E. and N. 70° W.; asc. S. slope.
79.55	<p>The point for the 1/4 sec. cor. of secs. 4 and 9.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, dense salt cedar adjacent to the Gila River.</p>
	<p>From the 1/4 sec. cor. of secs. 9 and 10. N. 89°29'30" W., on the E. and W. center line of sec. 9. Over sand-drifted flood land.</p>
12.30	The left bank of an abandoned channel of the Gila River, a cut bank, 5 ft. high, bears N. 10° E. and S. 10° W.; enter cultivated land.
14.01	Intersect the adjusted 1875 record meander line on the right bank of the Gila River, as originally surveyed, and point for the special meander cor. of sec. 9; this point was not monumented.
14.84	Point for the auxiliary meander cor. on the medial line of the abandoned channel of the Gila River, bears N. 18°20' W.

Subdivision of Section 9, T. 7 S., R. 26 E., Arizona

CHAINS

Set the iron post 22 ins. in the ground, brass cap mkd.

T7S R26E



Set a steel fence post, 5 ft. long, 18 ins. in the ground, alongside the iron post.


15.70 Irrigation ditch, 5 lks. wide, 2 ft. deep, flows N.

19.85 Point for the CE 1/16 sec. cor. of sec. 9.

Set the iron post 24 ins. in the ground, brass cap mkd.

T7S R26E

E $\frac{1}{16}$



Set a steel fence post 5 ft. long, 18 ins. in the ground, alongside the iron post.

30.00 Irrigation ditch, 6 lks. wide, 2 ft. deep, flows NW.

39.70 The point for the center $\frac{1}{2}$ sec. cor. of sec. 9.

40.15 Fence, bears N. and S.

48.18 Roadway on right bank of Stockton Wash.

48.65 Stockton Wash, 75 lks. wide, 7 ft. deep, drains N. $1^{\circ}48'$ E.

49.12 Roadway on left bank of Stockton Wash.

49.30 Fence, bears N. and S.

59.55 Point for the CW 1/16 sec. cor. of sec. 9; this cor. point was not monumented.

60.05 Irrigation ditch, 9 lks. wide, 3 ft. deep, flows N.

78.63 Roadway on right bank of Graveyard Wash.

79.05 Graveyard Wash, 65 lks. wide, 6 ft. deep, drains N.

79.40 The $\frac{1}{2}$ sec. cor. of secs. 8 and 9.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, none.


Subdivision of the NE $\frac{1}{4}$ of Sec. 9, T7S, R26E

From the CE 1/16 sec. cor. of sec. 9.


N. $0^{\circ}04'15''$ W., along the N. and S. centerline of the NE $\frac{1}{4}$ of sec. 9.

Over nearly level cultivated land.

Subdivision of Section 9, T. 7 S., R. 26 E., Arizona

CHAINS	
7.38	<p>Point for the auxiliary meander cor. on the medial line of the abandoned channel of the Gila River, bears S. 50° 38' E.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p>T7S R26E</p>  <p>1966</p>
	<p>Set a steel fence post, 5 ft. long, 18 ins. in the ground, alongside the iron post.</p>
8.21	<p>Intersect the adjusted record meander line on the right bank of the Gila River as originally surveyed; point for the special meander cor. of sec. 9; this point is not monumented.</p>
14.16	<p>The present left bank of the Gila River, a cut bank, 4 ft. high, bears SE. and NW.</p>
19.89	<p>Point for the NE 1/16 sec. cor. of sec. 9 at the intersection with the E. and W. center line of the NE 1/4 of sec. 9 falls in the Gila River, not monumented.</p>
20.78	<p>The present right bank of the Gila River, a low gravel bar, bears SE. and NW.; thence through scattered salt cedar.</p>
24.80	<p>A cut bank, 4 ft. high, bears S. 80° E. and N. 80° W.; ascend S. slope.</p>
30.60	<p>S. rim of a mesa, bears E. and NW.; thence over gently rolling land.</p>
38.70	<p>Water pipeline, underground, bears S. 78° E. and N. 78° W.</p>
39.77	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p>
	<p>From the point for the N 1/16 sec. cor. of secs. 9 and 10.</p>
	<p>N. 89°29'15" W., along the E. and W. centerline of the NE 1/4 of sec. 9.</p>
	<p>Over gently rolling land, through moderate creosote bush.</p>
0.15	<p>Wash, 15 lks. wide, 1 ft. deep, drains SW.</p>
2.70	<p>Wash, 10 lks. wide, 2 ft. deep, drains S.</p>
7.25	<p>Wash, 15 lks. wide, 2 ft. deep, drains SE.</p>
8.80	<p>S. rim of a mesa, bears SE. and NW.; descend broken SW. slope.</p>
11.60	<p>Bottom of descent, thence over sand-drifted flood land.</p>
19.40	<p>The present right bank of the Gila River, a low gravel bar bears SE. and NW.</p>
19.85	<p>The point for the NE 1/16 sec. cor. of sec. 9.</p>
23.18	<p>The present left bank of the Gila River, a cut bank, 4 ft. high, bears SE. and NW.; thence through scattered salt cedar.</p>
39.71	<p>The point for the CN 1/16 sec. cor. of sec. 9.</p>

Subdivision of Section 9, T. 7 S., R. 26 E., Arizona

CHAINS	Subdivision of the NW $\frac{1}{4}$ of Sec. 9, T. 7 S., R. 26 E.
	<p>From the point for the CW 1/16 sec. cor. of sec. 9.</p> <p>N. 0°04'45" W., along the N. and S. centerline of the NW$\frac{1}{4}$ of sec. 9.</p> <p>Over nearly level cultivated land.</p>
0.50	Irrigation ditch, 6 lks. wide, 2 ft. deep, flows W.
23.50	Leave cultivated land, bears E. and W.
23.70	Farm road, bears E. and W.
23.85	Dyke, 6 ft. high, 10 ft. wide, bears N. 85° E. and S. 85° W.
23.95	Fence, parallels dyke; enter moderate salt cedar.
27.45	The present left bank of the Gila River, a low gravel bar, bears S. 62° E. and N. 62° W.
32.98	<p>The present right bank of the Gila River, a cut bank, 6 ft. high, bears N. 73°35' E. and S. 73°35' W., and point for the special meander cor. of sec. 9, at the intersection of the adjusted record meander line of the right bank of the Gila River, as originally surveyed.</p> <p>Set a plastic post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., flanged at the base, and with a brass cap fastened to the top, 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R26E</p> <p>W</p> <p>S 9</p>  <p>W</p> <p>SMC</p> </div> <p>Set a cottonwood post, 4 ins. diam., 5 ft. long, 24 ins. in the ground, alongside the plastic post.</p>
36.80	Graham Canal, 30 lks. wide, 4 ft. deep, flows N. 67° W.
39.78	The W 1/16 sec. cor. of secs. 4 and 9.
	<p>Traverse of the adjusted record meander line on the right bank of the Gila River as originally surveyed in the SE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 9, for informational purposes only.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the special meander cor. on the E. and W. center line of sec. 9.</p> <p>N. 18°01' W., 5.21 chs. Angle Point No. 4; this point is not monumented.</p> <p>N. 52°06' W., 5.37 chs. Intersect the point for the special meander cor. on the N. and S. centerline of the NE$\frac{1}{4}$ of sec. 9.</p>

Subdivision and Meanders in Section 9, T.7S., R.26E., Arizona

CHAINS	
	<p>Subdivision of the Abandoned Bed of the Gila River, as originally surveyed.</p> <hr/> <p>Lot 10, sec. 9, as originally surveyed, was bounded on its northeast side by the left bank of the Gila River, a non-navigable stream. The river has subsequently abandoned this channel because of a diversion dam in sec. 10. The following survey is that of the division of that part of the abandoned channel inuring to former Lot 10.</p> <hr/> <p>From the auxiliary meander corner on the E. and W. center line of sec. 9.</p> <p>N. 18°20' W., along the medial line of the Gila River.</p> <p>4.77 Angle point No. 4.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R26E AP 4 S 9 1966</p> </div> <p>Set a steel fence post, 5 ft. long, 18 ins. in the ground, alongside the iron post.</p> <p>Thence</p> <p>N. 50°38' W.; continue along medial line.</p> <p>4.55 The auxiliary meander cor. on the N-S centerline of the NE¼ of sec. 9.</p> <p>Land, nearly level cultivated bottom land of Gila Valley. Soil, sandy loam. Timber, scattered cottonwood. Undergrowth, none.</p>
	<p>Traverse of the adjusted record meander line on the right bank of the Gila River as originally surveyed in the NW¼NW¼ of sec. 9, for informational purposes only.</p>
	<p>From the proportionate point for the special meander cor. on the N and S center line of the NW¼ of sec. 9, identical with the present right bank of the Gila River, downstream.</p> <p>S. 73°35' W., 1.80 chs. This course is identical with the present right bank meanders.</p> <p>S. 21°27' W., 3.76 chs.</p> <p>S. 69°48' W., 5.82 chs.</p> <p>S. 36°22' W., 5.14 chs.</p> <p>S. 58°54' W., 3.65 chs.</p> <p>S. 69°47' W., 5.43 chs. At end of this course, intersect the proportionate point for the meander cor. of secs. 8 and 9.</p>
	<p>Meanders of the present right bank of the Gila River in the NW¼NW¼ of sec. 9, downstream.</p> <hr/>

Meanders in Section 9, T. 7S, R. 26 E. Arizona

<p>CHAINS</p>	<p>From the special meander cor. on the N. and S. center line of the NW$\frac{1}{4}$ of sec. 9; along a well-defined bank, 6 ft. high, through moderate salt cedar.</p> <p>S. 73°35' W., 1.80 chs.</p> <p>S. 81°36' W., 6.66 chs. At end of this course, leave high bank; thence over gravel bar along the S. edge of moderate salt cedar growth.</p> <p>N. 75°54' W., 11.90 chs. Intersect the meander cor. of secs. 8 and 9.</p>
<p>General Description</p>	
<p>Section 9, Township 7 South, Range 26 East, is located northeast of the city limits of Safford, Arizona. The elevation ranges from about 2,900 ft. above sea level in the bottom lands to about 3,015 ft. on the rolling range land in the NE$\frac{1}{4}$ of the section. Most of the land within the section is under cultivation. The Gila River flows northwesterly through the east one-half of the section and flows westerly through the west one-half of the section. Timber consists of scattered mesquite and cottonwood along the Gila River. The undergrowth consists of moderate salt cedar and scattered willow adjacent to the river. There is moderate creosote bush and scattered cacti in the higher elevations. No mining activity was noted in this area.</p>	

14

BOOK 4865

CERTIFICATE OF SURVEY

We
 I, Paul G. Bauer and Robert F. Johnson, HEREBY CERTIFY upon honor that,
 in pursuance of special instructions bearing date of the 22d day of November, 19 65,
 we
 I have made a dependent resurvey of a portion of the subdivisional lines,
 and survey of portions of the subdivision and meanders in Section 9, and
 established the medial line of the abandoned bed of the Gila River in the
 SE $\frac{1}{4}$ NE $\frac{1}{4}$ of Section 9, Township 7 South, Range 26 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
 us our
 are represented in the foregoing field notes as having been executed by me and under my direction;
 and that said survey has been made in strict conformity with said special instructions, the Manual
 of Instructions for the Survey of the Public Lands of the United States, and in specific manner
 described in the foregoing field notes.

November 15, 1966

 (Date)

Paul G. Bauer

 (Cadastral Surveyor)

November 15, 1966

 (Date)

Robert F. Johnson

 (Cadastral Surveyor)
 Surveying Technician

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT,
 Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the subdivisional
 lines and survey of portions of the subdivision and meanders in Section 9,
 and establishment of the medial line of the abandoned bed of the Gila River
 in the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of Section 9, Township 7 South, Range 26 East, Gila and Salt
 River Meridian, Arizona,

executed by Paul G. Bauer and Robert F. Johnson,
 having been critically examined and found correct, are hereby approved.

AUG 4 1970

 (Date)

Clark F. Lumm

 (Chief, Division of Engineering)
 Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

 (Date)

 (Chief, Division of Engineering)
 Cadastral Survey