

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

OF THE

SOUTH BOUNDARY (THE SECOND STANDARD PARALLEL NORTH), THE

EAST AND WEST BOUNDARIES

AND THE

RETRACEMENT OF A PORTION OF THE NORTH BOUNDARY

AND THE

SURVEY OF SUBDIVISIONS OF CERTAIN SECTIONS

TOWNSHIP 9 NORTH, RANGE 23 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer, Cadastral Surveyor

Kenneth D. Herman, Cadastral Surveyor

Gary T. Oviatt, Cadastral Surveyor

Jerrold E. Knight, Cadastral Surveyor

Under special instructions dated August 23, 1967, which provided for the surveys included under Group Number 458, approved August 23, 1967, and assignment instructions dated August 23, 1967.

Survey commenced September 1, 1967

Survey completed December 13, 1967

1A

BOOK 4867

INDEX DIAGRAM

Township 9 North, Range 23 East

		28	28	27			
26	6 95 94	5 77 93	4 63 76	3 51 62	2 39 50	1 38	16
24	7 91 90	8 74 89	9 61 72	10 49 60	11 38 48	12 37	15
23	18 87 87	17 71 86	16 59 70	15 47 58	14 36 46	13 35	14
21	19 85 84	20 69 84	21 57 68	22 44 55	23 34 44	24 32	13
19	30 83 81	29 67 81	28 55 67	27 42 53	26 31 42	25 30	11
17	31 79	32 64	33 52	34 40	35 29	36	10
	8	7	5	4	3	1	

SUBDIVISIONS:

<u>SEC.</u>	<u>PAGE</u>
1	105
2	114
3	141
4	153
5	174
8	168
9	150
10	137
16	149
17	165

<u>SEC.</u>	<u>PAGE</u>
18	187
22	123
23	106
25	97
27	122
30	186
31	179
32	162
33	148
34	120

Township 9 North, Range 23 East
Gila and Salt River Meridian, Arizona

CHAINS

The south boundary (the Second Standard Parallel North), was surveyed in 1883 by O. D. Wheeler, and was dependent-ly resurveyed in 1908 by Jesse B. Wright. The east half of the south boundary of section 32 was retraced in 1914 by C. A. Long. The east boundary was surveyed in 1882 by A. P. Johnson. The west and north boundaries and subdivisional lines were surveyed in 1883 by O. D. Wheeler and the north boundary was resurveyed by Theodore Vander Meer in 1935. The line between sections 32 and 33 was resurveyed and Homestead Entry Survey No. 209 in section 32 was surveyed in 1914 by C. A. Long. Certain corners along the south boundary were remonumented in 1966, under the U. S. Forest Service Remonumentation Program.

The following notes are those of a dependent resurvey of the south, east and west boundaries and the subdivisional lines designed to restore the corners in their true original locations according to the best available evidence; a retracement of portion of the north boundary and the survey of subdivisions of sections 1, 2, 3, 4, 5, 8, 9, 10, 16, 17, 18, 22, 23, 25, 27, 30, 32, 33 and 34 of Township 9 North, Range 23 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the Specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 23, 1967.

Only the true line bearings and horizontal distances are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 ins. long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 34°07'33" North, and Longitude, 109°50'55" West, as determined from a direct tie to USGS Triangulation Station SPRINGER MOUNTAIN, located in section 30.

The mean magnetic declination was found to be 14° East.

Dependent Resurvey of the South Boundary
T. 9 N., R. 23 E., G&SR M., Arizona

Reestablishment of the Survey Executed
by Jesse B. Wright in 1908

The standard cor. of Ts. 9 N., Rs. 23 and 24 E., monumented by a basalt stone, 20 x 12 x 10 ins., firmly set in a mound of stone, mkd. T8NR24E SC on S. face, T9NR23E and 6 notches on NW. face and R24E SC with 6 notches on NE. face, from which the orig. bearing trees:

A pine, 20 ins. diam., bears N. 51° E., 33 lks. dist., mkd. with a healed blaze. (Record: N. 46° E., 38 lks. dist.)

Dep. Resurvey, S. Bdy., T. 9 N., R. 23 E.

CHAINS	
	<p>A pine, 38 ins. diam., bears N. $26\frac{1}{2}^{\circ}$ W., 70 lks. dist., mkd. T9NR23 E S36 BT. (Record bearing N. 30° W.)</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground to bed rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S C T9N R23E R24E <u>S36 S31</u> 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 21 lks. west of a fence bearing N. and S.</p> <p>S. $89^{\circ}52'$ W., along the S. bdy. of sec. 36.</p> <p>Over gently rolling land, through dense timber.</p>
2.50	Track road, bears N. 15° E. and S. 15° W.
12.70	Wet Weather Creek, drains NW. (Locally named)
14.50	Old logging road, bears NE. and SW.
40.34	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented by a malpais stone, 14 x 10 x 6 ins., loosely set, no legible mks., mound of stone N. This is accepted as best remaining evidence of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S C T9N R23E <u>$\frac{1}{4}$ S36</u> 1967</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ}56'$ W., beginning new measurement.</p> <p>Over gently rolling land, through dense timber.</p>
5.22	<p>The closing Tp. cor. of Ts. 8 N., Rs. 23 and 24 E., monumented by a malpais stone, 30 x 15 x 6 ins., firmly set in a mound of stone, mkd. 6 notches on S., E., and W. faces and CC on S. face, mound of stone S., from which the orig. bearing trees:</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. $77\frac{1}{2}^{\circ}$ E., 21 lks. dist., dimly mkd. (Record bearing S. $73\frac{1}{4}^{\circ}$ E.)</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 6° W., 74 lks. dist., dimly mkd.</p>
40.30	<p>The standard cor. of secs. 35 and 36, monumented by a malpais stone, 16 x 10 x 6 ins., firmly set in a mound of stone, no legible mks., mound of stone N., from which the orig. bearing trees:</p>

Dep. Resurvey, S. Bdy., T. 9 N., R. 23 E.

CHAINS

A pine, 18 ins. diam., bears N. 47° E., 40 lks. dist., mkd. T9NR23E S36 BT. (Record N. 32° E., 34 lks. dist.)

A pine, 20 ins. diam., bears N. 22½° W., 103 lks. dist., mkd. T9NR23E S35 BT. (Record N. 68° W., 59 lks. dist.)

At the corner point

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.

S C
T9N R23E
S35|S36
1967

Deposit the orig. cor. stone alongside the iron post.

Raise a mound of stone N. of the cor.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine and juniper.
Undergrowth, bunch grass.

S.89°53' W., along the S. bdy. of sec. 35.

Over gently rolling land, through moderate timber.

5.17 The ¼ sec. cor. of sec. 1, T. 8 N., R. 23 E., bears South, 2.6 lks. dist., monumented by a malpais stone, 14 x 10 x 10 ins., firmly set, mkd. ¼ on N. face and an "X" on top, mound of stone N.

18.90 Rocky knoll, bears South, 150 lks. dist.

40.39 The standard ¼ sec. cor. of sec. 35, monumented by a malpais stone, 20 x 14 x 5 ins., firmly set in a mound of stone, mkd. ¼ SC on N. face, from which the remains of an orig. bearing tree:

A stump 5 ft. high, bears N. 41¼° E., 45 lks. dist., no legible markings.

At the corner point

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

S C
T9N R23E
¼ S 35
1967

from which

A pine, 6 ins. diam., bears N. 79° E., 17 lks. dist., mkd. ¼ S35 BT.

A pine, 5 ins. diam., bears N. 8° W., 72 lks. dist., mkd. ¼ S35 BT.

Deposit the orig. cor. stone alongside the iron post.

Raise a mound of stone N. of the cor.

Dep. Resurvey, S. Bdy., R. 9 N., R. 23 E.

CHAINS		
	S. 89°58' W., beginning new measurement.	
	Over gently rolling land, through moderate timber.	
4.66	The cor. of secs. 1 and 2, T. 8 N., R. 23 E., bears South, 5.7 lks. dist., monumented by a lava stone, 12 x 12 x 4 ins., firmly set in a mound of stone, mkd. 5 notches on W. and 1 notch on E. faces, from which an orig. bearing tree: A pine, 14 ins. diam., bears S. 58° E., 25 lks. dist., mkd. T8NR23E S 1 BT.	
13.80	Old logging road, bears NE. and SW.	
33.10	Old railroad bed, bears S. 75° E. and N. 75° W.	
40.29	The standard cor. of secs. 34 and 35, monumented by a lava stone, 18 x 14 x 10 ins., loosely set in a mound of stone, mkd. 4 notches on W. and 2 notches on E. faces. At the corner point Set the iron post 20 ins. in the ground, brass cap mkd. S C T9N R23E <u>S34 S35</u> 1967	
	from which A pine, 8 ins. diam., bears N. 50° E., 11 lks. dist., mkd. T9NR23E S35 BT. A pine, 7 ins. diam., bears N. 13° W., 47 lks. dist., mkd. T9NR23E S34 BT.	
	Bury the orig. cor. stone alongside the iron post.	
	Raise a mound of stone N. of the cor.	
	Land, gently rolling.	
	Soil, clay loam.	
	Timber, pine, juniper and oak.	
	Undergrowth, bunch grass.	
	S. 89°48' W., along the S. bdy. of sec. 34.	
	Over gently rolling land, through dense timber.	
4.38	The ¼ sec. cor. of sec. 2, T. 8 N., R. 23 E., bears North, 2 lks. dist., monumented by a lava stone, 14 x 14 x 5 ins., firmly set, mkd. ¼ on S. face, mound of stone S., from which the orig. bearing tree: A pine, 24 ins. diam., bears S. 50°W., 24 lks. dist., mkd. ¼ BT.	
40.02	Fence, bears SE and NW.	

Dep. Resurvey, S. Bdy., T. 9 N., R. 23 E.

CHAINS	
40.28	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 34, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set mkd. and witnessed as described in the official record. This cor. was set in 1966, under the US Forest Service Remonumentation Program.</p> <hr/> <p>S. $89^{\circ}53'$ W., beginning new measurement.</p> <p>Over gently rolling land, through dense timber.</p>
4.28	<p>The cor. of secs. 2 and 3, T. 8 N., R. 23 E., bears North, 9 lks. dist., monumented by a mound of stone, from which an orig. bearing tree :</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears S. 62° E., 95 lks. dist., mkd. T8NR23E S2 BT.</p>
5.30	<p>Apache Railroad, on a curve, bears N. $12^{\circ}30'$ W. and SE.</p>
6.50	<p>Track road, on a curve, bears SE. and N. $12^{\circ}30'$ W.</p>
6.70	<p>Telephone line, bears SE. and N. $12^{\circ}30'$ W.</p>
22.50	<p>Graded road, bears N. and S.</p>
24.50	<p>Bladed road, bears NE. and W.</p>
26.80	<p>Bladed road, bears E. and NW.</p>
38.00	<p>Power line, bears NE. and W.; leave timber, enter open Utility Right-of-Way.</p>
40.35	<p>The standard cor. of secs. 33 and 34, monumented by an iron post $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. This cor. was set in 1966, under the US Forest Service Remonumentation Program.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p> <hr/> <p>S. $89^{\circ}51'$ W., along the S. bdy. of sec. 33.</p> <p>Over gently rolling land, along a Utility Right-of-Way.</p>
4.09	<p>The $\frac{1}{4}$ sec. cor. of sec. 3, T. 8 N., R. 23 E., bears North 2 lks. dist., monumented by a malpais stone, 24 x 12 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on S. face.</p>
40.23	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented by an iron post, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the official record. This cor. was set in 1966, under the US Forest Service Remonumentation Program.</p> <hr/> <p>S. $89^{\circ}56'$ W., beginning new measurement.</p> <p>Over gently rolling land, continue along cleared area.</p>

Dep. Resurvey, S. Bdy., T. 9 N., R. 23 E.

CHAINS	
3.80	<p>The cor. of secs. 3 and 4, T. 8 N., R. 23 E., determined from the remains of an orig. bearing tree:</p> <p style="padding-left: 40px;">A pine stump, 27 ins. diam., bears S. 10° E., 40 lks. dist., mkd. T8NR23E S3 BT (Record)</p> <p>At the corner point</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N <u>S33</u> S4 S3 T8N R23E 1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 60° W., 68 lks. dist., mkd. T8N R23E S4 BT.</p> <p>Cor. is located under a power line bearing E. and W.</p> <p>Raise a mound of stone S. of cor.</p>
19.10	Power line, bears S. 47°45' E. and N. 47°45' W.
20.00	Power line, bears S. 47°45'E. and N. 47°45' W.
20.10	Point for the standard W. 1/16 sec. cor. of sec. 33, at proportionate dist., not monumented.
30.15	<p>Point for the standard W-W 1/64 sec. cor. of sec. 33, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>S C T9N R23E <u>W-W 1/64 S33</u> 1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 56° E., 52 lks. dist., mkd. W-W 1/64 S33 BT.</p> <p style="padding-left: 40px;">A nail in a power pole, bears S. 84½°E., 108 lks. dist.</p> <p style="padding-left: 40px;">A developed spring, bears NE., 89 lks. dist., capped with a cement lid, 3 x 3 ft.</p>
30.20	Fence, bears N. and S.
33.82	<p>Point for the W-E 1/64 sec. cor. of sec. 4, T. 8 N., R. 23 E., at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>

Dep. Resurvey, S. Bdy., T. 9 N., R. 23 E.

CHAINS	
40.20	<p style="text-align: center;"> <u>W E</u> 1/64. S4 T8N R23E 1967 </p> <p>Raise a mound of stone S. of cor.</p> <p>The standard cor. of secs. 32 and 33, monumented by a malpais stone, 30 x 15 x 15 ins., firmly set, mkd. 2 notches on the W. and SC on the S. faces. A malpais stone, 24 x 14 x 14 ins., mkd. HES 209, is set alongside the standard cor.</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 46° E., 110 lks. dist., no legible markings. (Record dist. 100 lks.)</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 33° W., 89 lks. dist., mkd. T9NR23E S32.</p> <p style="padding-left: 40px;">A fence cor. bears South, 28 lks. dist., fences bear N., E. and W.</p> <p style="padding-left: 40px;">A power line, bears South, 14 lks. dist., power line bears E. and W.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak.. Undergrowth, bunch grass.</p>
	<p>S. 89°59' W., along the S. bdy. of sec. 32.</p>
	<p>Over gently rolling land, along Utility Right-of-Way.</p>
3.62	<p>The ¼ sec. cor. of sec. 4, T. 8 N., R. 23 E., monumented by an iron pipe, 2 ins. diam., set firmly in the ground. This point is accepted locally and is accepted as the best evidence of the orig. cor. position.</p>
6.00	<p>Bladed road, bears N. and S. 85° W.; leave cleared area, enter moderate timber.</p>
9.00	<p>Fence, bears N. and S.</p>
14.40	<p>Power line, bears N. 75° E. and S. 75° W.</p>
19.50	<p>Track road, bears N. 25° E. and S.</p>
19.73	<p>Cor. No. 2 of HES 209, monumented by a malpais stone, 10 x 8 ins., projecting 8 ins. above the ground, set under a fence, bearing N. and S., mkd. HES 209 on N. face and an "X" on top.</p>
20.19	<p>Point for the standard E 1/16 sec. cor. of sec. 32, at proportionate dist., not monumented.</p>
	<p>Leave timber; thence along a gravel road bearing W. and SE.</p>
23.20	<p>Leave gravel road; enter black top road bearing W.</p>

Dep. Resurvey, S. Bdy., T. 9 N., R. 23 E.

CHAINS		
40.38	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented by a water pipe $\frac{1}{2}$ in. diam., firmly set 3 ins. below the surface of the black top, in the center of the road. This has been accepted by interested property owners and is accepted as the best available evidence of the orig. cor. position.</p>	
	<p style="text-align: center;">—————</p> <p>N. $89^{\circ}45'$ W., beginning new measurement.</p> <p>Continue along the blacktop road.</p>	
3.38	<p>The cor. of secs. 4 and 5, T. 8 N., R. 23 E., monumented by a water pipe $\frac{1}{2}$ in. diam., set under the surface of a paved road. This point is accepted by local residents and is the best evidence of the orig. cor. position.</p>	
12.10	<p>Intersection of McCoy Ave. and Arizona Highway No. 173.</p>	
12.30	<p>Enter Arizona Highway No. 173, bears S. 60° E. and W.</p>	
40.20	<p>The standard cor. of secs. 31 and 32, monumented by an Arizona Highway Elevation Marker, set 6 ins. below the surface, under a steel plate in the center of Arizona Highway No. 173.</p> <p>The cor. is located at the intersection of Clare Ave. and Highway No. 173.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine. Undergrowth, bunch grass.</p>	
	<p>S. $89^{\circ}59'$ W., along the S. bdy. of sec. 31.</p> <p>Continue along Highway No. 173.</p>	
2.77	<p>Arizona Highway Elevation Marker, set 6 ins. below the surface, under a steel plate in the center of Arizona Highway No. 173.</p>	
3.21	<p>The $\frac{1}{4}$ sec. cor. of sec. 5, T. 8 N., R. 23 E., monumented by a nail driven in the paved road. This point was identified by officials of the Arizona Highway Department and is accepted by the local residents and is the best evidence of the orig. cor. position.</p>	
15.60	<p>Leave Arizona Highway No. 173, on a curve bearing E. and NW.</p>	
20.085	<p>Point for the standard $\frac{1}{16}$ sec. cor. of sec. 31, at proportionate dist., not monumented.</p>	
27.60	<p>Draw, flowing stream, course S. 5° W.</p>	
28.10	<p>Fence cor., fences, bear E., S. and W.</p>	
30.00	<p>Fence cor., fences, bear E., S. and W.</p>	
40.17	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 31, as determined from an orig. bearing tree:</p>	

Dep. Resurvey, S. Bdy., T. 9 N. , R. 23 E.

CHAINS

A pine, 26 ins. diam., bears N. 60° E., 107 lks. dist., illegibly mkd.

The orig. cor. stone, a malpais, 20 x 15 x 10 ins., mkd. SC 1/4 was found NW., 5 lks. dist., lying loose on the ground. It had been moved. There were 3 spikes set as local cors., near the cor. position.

The cor. point is located under a fence bearing E. and W. Reset the orig. cor. stone 10 ins. in the ground at the true cor. point.

N. 89°58' W., beginning new measurement.

Over gently rolling land, through moderate timber.

3.00 Cor. of fences, bearing E., S. and W.

3.04 The cor. of secs. 5 and 6, T. 8 N., R. 23 E., monumented by an iron pipe 2 1/2 ins. diam., firmly set in a mound of stone, cap mkd.

LACY C GREER ENG CO
T9N R23E
S31
S6|S5
T8N R23E
C C
1964

from which an orig. bearing tree

A pine, 24 ins. diam., bears S. 70° W., 112 lks. dist., mkd. T8N R23E S 6 BT (Record)

The original cor. stone properly marked was set alongside the iron pipe.

9.89 Point for the standard E-W 1/64 sec. cor. of sec. 31, monumented by a local cor., a pipe 3/4 in. diam., firmly set, mkd. LS 4651. This cor. is accepted by local land owners and was set by local surveyors.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

S C
T9N R23E
E-W 1/64 S31
1967

from which

An angle pole for a power line bearing N. and E., bears North, 20 lks. dist.

Bury the local cor. alongside the iron post.

10.50 Woodland Reservoir road, bears N. and S. 15° W.

17.60 Leave timber, enter Woodland Reservoir area.

19.95 Point for the standard W 1/16 sec. cor. of sec. 31, at proportionate dist., not monumented.

Dep. Resurvey, S. Bdy., T. 9 N., R. 23 E.

CHAINS	
21.10	Edge of Woodland Reservoir, bears irregularly N. and W.
32.50	East edge of a finger of Woodland Reservoir, bears N. and S.
35.80	West edge of Woodland Reservoir, bears N. and S.
38.10	Top of dyke of Woodland Reservoir, bears N. and S.; enter moderate timber.
39.50	Track road, bears N. and S.
40.06	The standard cor. of Ts. 9N., Rs. 22 and 23 E., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the official record. This cor. was set in 1966, under the US Forest Service Remonumentation Program.
	Land, gently rolling. Soil, rocky, clay loam. Timber, Pine, juniper and oak. Undergrowth, bunch grass.
<p>Dependent Resurvey of the East Boundary T. 9 N., R. 23 E., G&SR M., Arizona</p>	
<p>Reestablishment of the Survey Executed by A. P. Johnson in 1882</p>	
	<p>From the standard cor. of Ts. 9 N., Rs. 23 and 24 E. N. 0°19' W., bet. secs. 31 and 36.</p>
	Over nearly level land, through dense timber.
4.80	Logging road, bears E. and W.
6.50	Fence cor., fences bear N. 0°10' W., S. 2° E. and E.
12.50	Track road, bears N. 15° E. and S. 15° W.
40.36	The ¼ sec. cor. of secs. 31 and 36, monumented by a mound of stone, from which the remains of an orig. bearing tree:
	<p>A stump hole, with old fallen tree alongside, bears S. 31° W., 27 lks. dist.</p>
	At the corner point
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	<p>T9N R23E R24E ¼ S36 S31 1967</p>

CHAINS

Raise a mound of stone W. of the cor.

The cor. is located 11 lks. East of a fence bearing N. and S.

N. 0°11' W., beginning new measurement.

Along a fence bearing irregularly N. and S.

30.00 Bladed road, bears E. and W.

40.26 The cor. of secs. 25, 30, 31 and 36, monumented by a basalt stone, 10 x 6 x 4 ins., firmly set in a mound of stone, mkd. 5 notches on N. face, from which the orig. bearing trees:

A pine, 26 ins. diam., bears S. 64½° E., 37 lks. dist. mkd. with a healed blaze, (Record: S. 52° E., 46 lks. dist.)

A pine, 22 ins. diam., bears S. 62¾° W., 47 lks. dist., mkd. T9NR23E S36 BT. (Record: S. 49° W., 50 lks. dist.)

A pine, 24 ins. diam., bears N. 60° W., 68 lks. dist., mkd. with a healed blaze. (Record: N. 68° W., 59 lks. dist.)

At the corner point

Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R23E R24E
S25 | S30
S36 | S31
1967

Bury the orig. cor. stone alongside the iron post.

The cor. is located 1 lk. East of a fence bearing N. and S.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine and juniper.
Undergrowth, bunch grass.

N. 0°21'W., bet. secs. 25 and 30.

Over gently rolling land, through dense timber.

Along a fence bearing irregularly N. and S.

40.40 Fence, bears W. and E., 17 lks. dist., thence irregularly S.

40.49 The ¼ sec. cor. of secs. 25 and 30, determined from the orig. bearing trees:

A pine, 16 ins. diam., bears S. 40° E., 20 lks. dist., mkd. with a healed blaze.

CHAINS

A pine, 20 ins. diam., bears S. 82° W., 53 lks. dist., mkd. ½ S BT.

At the corner point

Set the iron post, 15 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R23E R24E
½
S25|S30
1967

from which

A fence cor., bears S. 40° E., 20 lks. dist., fences bear irregularly S. and W.

N. 0°23' W., beginning new measurement.

Over gently rolling land, through dense timber.

7.20 Draw, 20 lks. wide, drains W.

18.50 Dim logging road, bears NE. and SW.

40.42 The cor. of secs. 19, 24, 25 and 30 monumented by a basalt stone, 16 x 8 x 6 ins., firmly set, mkd. 2 notches on S. face, mound of stone W., from which the remains of the orig. bearing trees:

A pine, 20 ins. diam., bears N. 47½° E., 50 lks. dist., mkd. with a healed blaze. (Record bearing N. 50° E.)

A pine, 20 ins. diam., bears S. 42¾° E., 22 lks. dist., mkd. with a healed blaze. (Record bearing S. 33° E.)

A pine, 18 ins. diam., bears S. 67° W., 34 lks. dist., mkd. with a healed blaze. (Record bearing S. 70° W.)

A pine, 18 ins. diam., bears N. 54¾° W., 51 lks. dist., mkd. with a healed blaze. (Record bearing N. 59° W.)

At the corner point

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R23E R24E
S24|S19
S25|S30
1967

Deposit the orig. cor. stone alongside the iron post.

Dep. Resurvey, E. Bdy., T. 9 N., R. 23 E.

CHAINS

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

N. 0°12' W., bet. secs. 19 and 24.

Over gently rolling land, through dense timber.

9.40 Draw, 16 lks. wide, drains NW.

40.25 The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, monumented by a basalt stone, 18 x 13 x 9 ins., firmly set, dimly mkd. $\frac{1}{4}$ on W. face, mound of stone W., from which the orig. bearing trees:

A pine, 21 ins. diam., bears N. 53° E., 67 lks. dist., mkd. with a healed blaze.

A pine, 27 ins. diam., bears N. 67° W., 71 lks. dist., mkd. with a healed blaze.

At the corner point

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

T9N
R23E R24E
 $\frac{1}{4}$
S24|S19
1967

from which

A pine, 5 ins. diam., bears S. 14° E., 14 lks. dist., mkd. T9NR24E S19 BT.

An oak, 5 ins. diam., bears S. 25 $\frac{1}{4}$ ° W., 30 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

N. 0°14' W., beginning new measurement.

Over gently rolling land, through dense timber.

23.30 Elk Springs Draw, 30 lks. wide, drains SW.

40.22 The cor. of secs. 13, 18, 19 and 24, monumented by a basalt stone, 24 x 16 x 10 ins., firmly set, mkd. 3 notches on N. face, mound of stone W., from which the orig. bearing trees:

A pine, 12 ins. diam., bears S. 57° E., 22 lks. dist., mkd. with a healed blaze.

A pine, 18 ins. diam., bears S. 61° W., 51 lks. dist., mkd. with a healed blaze.

Dep. Resurvey, E. Bdy., T. 9 N., R. 23 E.

CHAINS

Remains of a stump, 18 ins. diam., bears N. 29° W., 70 lks. dist., mkd. T9NR23E S13 BT.

At the corner point

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R23E R24E
S13|S18
S24|S19
1967

from which

A fence cor., bears N. 66½° E., 19 lks. dist., fences bear E., W. and N. 25° W.

Deposit the orig. cor. stone alongside the iron post.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

N. 0°14' W., bet. secs. 13 and 18.

Over gently rolling land, through dense timber.

.05 Fence, bears E. and W.

.56 Fence, bears S. 25° E. and N. 25° W.

22.00 Old railroad bed, bears E. and W.

22.40 Small stream, 30 lks. wide, 8 ins. deep, course W.

40.28 The ¼ sec. cor. of secs. 13 and 18, monumented by a basalt stone, 20 x 9 x 7 ins., firmly set in a mound of stone, no legible mks., from which the remains of an orig. bearing tree:

A stump hole, bears N. 37° W., 33 lks. dist., with a fallen pine mkd. ¼ S. alongside. (Record)

At the corner point

Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R23E R24E
¼
S13|S18
1967

from which

A pine, 10 ins. diam., bears S. 63° E., 27 lks. dist., mkd. ¼ S18 BT.

A pine, 4 ins. diam., bears S. 53¾° W., 11 lks. dist., mkd. ¼ S13 BT.

Deposit the orig. cor. stone alongside the iron post.

CHAINS	
	N. 0°06' W., beginning new measurement.
.90	Small stream, 20 lks. wide, 1 ft. deep, course W.
18.60	Spur, slopes W., from Turkey Mountain.
40.36	The cor. of secs. 7, 12, 13 and 18, monumented by a basalt stone, 22 x 20 x 7 ins. firmly set, mkd. 4 notches on S. and 2 notches on N. faces, mound of stone W., from which the remains of an orig. bearing tree: An oak stump, bears N. 71° W., 58 lks. dist., mkd. T9NR23E. At the corner point Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd. <div style="text-align: center;"> T9N R23E R24E <u>S12 S7</u> S13 S18 1967 </div> from which A pine, 5 ins. diam., bears N. 46° E., 15 lks. dist., mkd. T9NR24E S7 BT. A pine, 5 ins. diam., bears N. 61½° W., 41 lks. dist., mkd. T9N R23E S12 BT. Deposit the orig. cor. stone alongside the iron post. Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.
2.30	N . 0°38' E., bet. secs. 7 and 12. Over gently rolling land, through dense timber. Spur, slopes SW.
20.60	Fence, bears E. and W., 120 lks. dist., thence irregularly N. and S.
24.00	Draw, 20 lks. wide, 8 ins. deep, drains NW.
40.39	The ¼ sec. cor. secs. 7 and 12, monumented by a basalt stone, 16 x 10 x 5 ins. firmly set, mkd. ¼ on W. face, mound of stone alongside. At the corner point Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd. <div style="text-align: center;"> T9N R23E R24E ¼ <u>S12 S7</u> 1967 </div> from which

Dep. Resurvey, E. Bdy., T. 9 N., R. 23 E.

CHAINS		
	<p>A pine, 10 ins. diam., bears S. 23° E., 31 lks. dist., mkd ¼ S7 BT.</p> <p>A pine, 10 ins. diam., bears S. 69° W., 53 lks. dist., mkd. ¼ S12 BT.</p> <p>A fence cor. bears N. 83° W., 28 lks. dist; fences, bear N., S. and W.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 46' E., beginning new measurement.</p> <p>Along E. side of a fence bearing N. and S.</p>	
20.30	Turkey Mountain Fire Road, bears E. and W.	
40.40	<p>The cor. of secs. 1, 6, 7 and 12, monumented by a basalt stone, 24 x 12 x 7 ins., firmly set, mkd. 5 notches on S. and 1 notch on N. faces, from which an orig. bearing tree:</p> <p style="padding-left: 40px;">A pine, 27 ins. diam., bears N. 34° W., 70 lks. dist., mkd. with a healed blaze.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T9N R23E R24E S1 S6 S12 S7 1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 88½° E., 28 lks. dist., mkd. T9NR24E S7 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 11 lks. East of a fence bearing N. and S.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
17.80	<p>N. 0°51' E., bet. secs. 1 and 6.</p> <p>Over gently rolling land, through dense timber.</p> <p>Wash, 40 lks. wide, 1 ft. deep drains NW.</p>	
20.80	Spur, slopes W.	
40.37	<p>The ¼ sec. cor. of secs. 1 and 6, monumented by a basalt stone, 17 x 16 x 3 ins., firmly set, mkd. ¼ on W. face, mound of stone to W.</p> <p>At the corner point</p>	

Dep. Resurvey, E. Bdy., T. 9N., R. 23 E.

CHAINS

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R23E R24E
 $\frac{1}{4}$
S1|S6
1967

from which

A pine, 7 ins. diam., bears N. 32° E., 63 lks. dist., mkd. $\frac{1}{4}$ S. 6 BT.

A pine, 5 ins. diam., bears N. 41 $\frac{1}{2}$ ° W., 39 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Deposit the orig. cor. stone alongside the iron post.

The cor. is located 174 lks. East of fence bearing N. and S.

N. 1°02' E., beginning new measurement.

41.68

The cor. of Ts. 9 and 10 N., Rs. 23 and 24 E., monumented by an iron post, 3 ins. diam., firmly set in a mound of stone, brass cap mkd.

T10N
R23E R24E
S36|S31
S1|S6
T9N
1935

from which

A fence cor., bears N. 42° W., 28 lks. dist.; fences bear S. and W.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

Dependent Resurvey of the West Boundary
T. 9 N., R. 23 E., G&SR M., Arizona

Reestablishment of the Survey Executed
by O. D. Wheeler in 1883

From the standard cor. of Ts. 9 N., Rs. 22 and 23 E.

N. 0°05' W., bet. secs. 31 and 36.

Over gently rolling land, through dense timber.

5.70

Bladed road, bears irregularly E. and W.

11.50

Walnut Creek, 30 lks. wide, 2 ft. deep, course N. 85° W.

20.135

Point for the S 1/16 sec. cor. of secs. 31 and 36, at proportionate dist., not monumented.

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS		
40.27	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented by a wood stake, mkd. $\frac{1}{4}$ cor. 172 - 54, set in a mound of stone. This position was verified from the orig. bearing trees:</p> <p>A pine, 25 ins. diam., bears S. 13° E., 34 lks. dist., with partially overgrown blaze and dim scribe mks. (Record bearing S. 17° E.)</p> <p>A pine, 19 ins. diam., bears S. $25\frac{1}{2}^{\circ}$ W., 31 lks., dist., mkd. $\frac{1}{4}$ S BT. (Record bearing S. 23° W.)</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R22E R23E $\frac{1}{4}$ S36 S31 1967</p> <p>from which</p> <p>A pine, 8 ins. diam., bears S. 88° E., 40 lks. dist., mkd. T9N R23 E S31 $\frac{1}{4}$ BT.</p> <p>A pine, 12 ins. diam., bears N. 58° W., 50 lks. dist., mkd. $\frac{1}{4}$ S36 BT.</p> <p>A power line cor. pole, bears N. 48° E., 22 lks. dist., power line bears E. and N. $0^{\circ}45'$ W.</p> <p>The orig. cor. monument, a basalt stone, 24 x 12 x 7 ins. lying loose on the ground, mkd. $\frac{1}{4}$, was found 5 lks. NW. and was deposited alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. $0^{\circ}13'$ W., beginning new measurement.</p> <p>Along Utility Right-of Way.</p>	
3.00	Turkey Track Drive, bears E.	
4.20	NW. cor. of a house, 21 x 29 ft., bears East, 36 lks. dist.	
17.20	Power line, bears S. $0^{\circ}45'$ E. and N. $0^{\circ}45'$ W.	
20.00	Pinecrest Road, bears E. and a track road curves irregularly N.	
20.10	Power line bears E. and W. for 25 lks., thence N. $0^{\circ}45'$ W. and S. $0^{\circ}45'$ E.	
20.15	Point for the N $\frac{1}{16}$ sec. cor. of secs. 31 and 36, at proportionate dist., not monumented. Point is located at E. side of fence cor. Fences bear N. and E.	

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS

40.30

The cor. of secs. 25, 30, 31 and 36, monumented by an iron pipe, 1 in. diam., firmly set, cap mkd. 25, 30, 31 and 26 (sic). This cor. was shown to me by interested property owners, who have been in the vicinity for many years and is accepted as best available evidence of the orig. cor. position, from which the remains of the orig. bearing trees:

A pine, 30 ins. diam., bears S. 78° E., 61 lks. dist., mkd. 23 E.S in a partially overgrown blaze. (Record dist. 43 lks.)

A pine stump, 27 ins. diam., bears S. 15½° W., 36 lks. dist., mkd. T9NR22E S36. (Record, S. 13° W., 35 lks.)

A pine, 30 ins. diam., bears N. 56° W., 18 lks. dist. Tree has been blazed high and low as is commonly found on this line. Blaze has been chopped into and no marks are visible.

At the corner point

Set the iron post 28 ins. in the ground, brass cap mkd.

T9N	
R22E R23E	
<u>S25</u>	<u>S30</u>
S36	S31
1967	

from which

A pine, 13 ins. diam., bears S. 38½° W., 126 lks. dist., mkd. S 36 BT.

A pine, 8 ins. diam., bears S. 64° W., 86 lks. dist., mkd. T9NR22E S36 BT.

A spike in a utility pole, bears S. 84½° W., 38 lks. dist.

Bury the local iron pipe alongside the iron post.

The cor. is located alongside a fence cor. Fences bear N., S. and W.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

N. 1°13' W., bet. secs. 25 and 30.

Over gently rolling land, through dense timber.

4.90

Fence cor., fences bear S. and NW.

6.20

Arizona Highway No. 173, bears SE. and NW.

7.40

Power line, bears SE. and NW.

7.70

Fence cor., fences bear N., SE. and NW.

20.20

Fence cor., fences bear N., S., E. and W.; desc. N. slope into Billy Creek.

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS	
23.20	Billy Creek, 30 lks. wide, 2 ft. deep, course N. 50° W.; asc. over SW. slope.
24.60	Top of ascent, thence over gently rolling land.
40.27	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by a water pipe, 1 in. diam., projecting 6 ins. above the ground, in a collar of stone. This position is harmoniously related to existing orig. cors. and has been recognized as the cor. by residents of the area, and is accepted as best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R22E R23E $\frac{1}{4}$ S25 S30 1967</p> <p>from which</p> <p>A pine, 10 ins. diam., bears North, 24 lks. dist., mkd. T9NR23E $\frac{1}{4}$ S30 BT.</p> <p>A pine, 9 ins. diam., bears N. 25° E., 43 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p>N. end of fence, bears N. 83°55' W., 17 lks. dist., fence bears very irregularly S.</p> <p>Fence cor., bears N. 31°23' W., 13 lks. dist., fences bear N. and W.</p> <p>Bury the water pipe alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 1°11' W., beginning new measurement.</p>
17.80	Gravel road, bears irregularly E. and W.
20.285	<p>Point for the N 1/16 sec. cor. of secs. 25 and 30, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R22E R23E N 1/16 S25 S30 1967</p> <p>from which</p> <p>A pine, 7 ins. diam., bears N. 38° E., 56 lks. dist., mkd. N 1/16 S30 BT.</p> <p>A juniper, 9 ins. diam., bears West, 23 lks. dist., mkd. N 1/16 S25 BT.</p> <p>Raise a mound of stone W. of the cor.</p>

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS

39.30 Track road, bears irregularly SE. and NW.

40.57 The cor. of secs. 19, 24, 25 and 30, monumented by a basalt stone, 12 x 10 x 4 ins., loosely set in a mound of stone, mkd. 4 notches on one edge and 2 notches on one edge, from which the remains of the orig. bearing trees:

A juniper, 43 ins. diam., bears S. 66½° E., 54 lks. dist., mkd. T9NR23E S30. (Record bearing S. 59° E.)

A pine stump, 24 ins. diam., bears S. 51° W., 81 lks. dist., mkd. BT.

At the corner point

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R22E R23E
S24 | S19
S25 | S30
1967

from which

A pine, 15 ins. diam., bears N. 54½° E., 61 lks. dist., mkd. T9NR23E S19 BT.

A pine, 8 ins. diam., bears S. 42 3/4° E., 23 lks. dist., mkd. T9NR23E S30 BT.

A pine, 5 ins. diam., bears S. 64½° W., 19 lks. dist., mkd. X BT.

A pine, 8 ins. diam., bears N. 33° W., 80 lks. dist., mkd. T9NR22E S24 BT.

Deposit the orig. cor. stone alongside the iron post.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

N. 1°03' W., bet. secs. 19 and 24.

Over gently rolling land, through dense timber.

5.70 Power line, bears S. 47°45' E. and N. 47°45' W.

6.40 Power line, bears S. 47°45' E. and N. 47°45' W.

21.90 Track road, bears irregularly E. and W.

28.00 Wash, 20 lks. wide, 1 ft. deep, drains NW.

40.26 The ¼ sec. cor. of secs. 19 and 24, monumented by a lava stone, 15 x 14 x 6 ins., firmly set, mkd. ¼ on W. face, mound of stone NW., from which the orig. bearing trees:

A pine, 33 ins. diam., bears S. 53½° E. 27 lks. dist., mkd. ¼ S. (Record: 40 ins. diam., S. 40° E.)

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS

A juniper, 35 ins. diam., bears S. $53\frac{3}{4}^{\circ}$ W., 50 lks. dist., mkd. $\frac{1}{4}$ S. (Record bearing S. 63° W.)

At the corner point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R22E R23E
 $\frac{1}{4}$
S24|S19
1967

from which

A pine, 9 ins. diam., bears N. $52\frac{1}{4}^{\circ}$ E., 110 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

A pine, 9 ins. diam., bears N. $24\frac{1}{4}^{\circ}$ W., 65 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

Deposit the orig. cor. stone alongside the iron post.

N. $0^{\circ}12'$ W., beginning new measurement.

22.00 Desc. N. slope.

26.30 Confluence of two creeks, 150 lks. wide, course W., asc. S. slope.

33.50 Top of ascent, desc. over gentle N. slope.

40.19 The cor. of secs. 13, 18, 19 and 24, monumented by a lava stone, 10 x 10 x 8 ins., firmly set, mkd. 3 notches on N. and 3 notches on S. faces, mound of stone W., from which the orig. bearing trees:

A pine, 22 ins. diam., bears N. 61° E., 94 lks. dist., mkd. T9NR23E S1 in partially overgrown blaze.

A pine, 18 ins. diam., bears S. 41° E., 47 lks. dist., mkd. T9NR23E in partially overgrown blaze.

A pine, 18 ins. diam., bears S. 55° W., 45 lks. dist., mkd. NR23E S24 in partially overgrown blaze.

A pine, 16 ins. diam., bears N. 27° W., 17 lks. dist., mkd. E8 in partially overgrown blaze.

At the corner point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T9N
R22E R23E
S13|S18
S24|S19
1967

from which

A pine, 15 ins. diam., bears N. 69° E., 97 lks. dist., mkd. T9NR23E S18 BT.

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS	<p>A fence cor., bears N. 27° W., 17 lks. dist., fences bear N. and W.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>N. 0°04' E., bet. secs. 13 and 18.</p> <p>Over gently rolling land, through dense timber.</p>
10.30	<p>Wash, 10 lks. wide, 18 ins. deep, drains W.</p>
40.40	<p>Wash, 15 lks. wide, 1 ft. deep, drains S. 50° W.</p>
40.42	<p>The ¼ sec. cor. of secs. 13 and 18, monumented by a basalt stone, 16 x 14 x 8 ins., set under a fence bearing irregularly N. and S., mkd. ¼ on top, mound of stone, from which an orig. bearing tree:</p>
	<p>A pine, 32 ins. diam., bears S. 45½° W., 61 lks. dist., mkd. ¼ S. (Record: S. 54° W., 56 lks. dist.)</p>
	<p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T9N R22E R23E ¼ S13 S18 1967</p>
	<p>from which</p>
	<p>A pine, 23 ins. diam., bears N. 70¼° E., 189 lks. dist., mkd. ¼ S18 BT.</p>
	<p>A pine, 15 ins. diam., bears S. 82¾ E., 93 lks. dist., mkd. ¼ S18 BT.</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°02' E., beginning new measurement.</p>
	<p>Begin asc. S. slope, along W. side of fence bearing irregularly N. and S.</p>
16.30	<p>Top of ascent, desc. N. slope.</p>
18.50	<p>Fence, bears W. and E., 253 lks., thence E., S. and W.</p>
20.16	<p>Point for the N 1/16 sec. cor. of secs. 13 and 18, at proportionate dist.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">T9N R22E R23E N 1/16 S13 S18 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 57° E., 108 lks. dist., mkd. N 1/16 S18 BT.</p> <p>40.30 Porter Creek, 50 lks. wide, 2 ft. deep, course S. 80° W.</p> <p>40.32 The cor. of secs. 7, 12, 13 and 18, determined from an orig. bearing tree:</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 63° W., 186 lks. dist., mkd. 9NR22E S13 B in a partially overgrown blaze.</p> <p>The cor. falls in a creek, impractical to monument.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
<p>1.00</p> <p>4.40</p> <p>4.70</p> <p>5.30</p> <p>5.40</p> <p>16.90</p>	<p>N. 0°01' W., bet. secs. 7 and 12.</p> <p>Over gently rolling land, through dense timber.</p> <p>Begin to asc. S. slope.</p> <p>Point selected for the witness cor. of secs. 7, 12, 13 and 18.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">W C T9N R22E R23E S12 S7 S13 S18 1967</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 17¼° E., 54 lks. dist., mkd. WC T9NR23E S7 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 57¼° E., 17 lks. dist., mkd. WC T9NR23E S18 BT.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Irrigation ditch, course S. 71° W.</p> <p>Fence, bears N. 72° E. and S. 72° W.</p> <p>Gravel road, bears N. 72° E and S. 72° W.</p> <p>Power line, bears S. 66¾° W. and N. 66¾° E.</p> <p>Top of ascent; thence over gently rolling land.</p>

CHAINS		
19.89	<p>Point for the S 1/16 sec. cor. of secs. 7 and 12, at proportionate dist.</p>	
	<p>Set the iron post 18 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T9N R22E R23E S 1/16 S12 S7 1967</p>	
	<p>Set a wooden post, 4 ins. diam., 4 ft. long, alongside the iron post.</p>	
20.60	<p>Fence, bears E. and W.</p>	
39.78	<p>The 1/4 sec. cor. of secs. 7 and 12, monumented by a basalt stone, 16 x 12 x 12 ins., firmly set, no legible mks., mound of stone W., from which an orig. bearing tree:</p>	
	<p style="padding-left: 40px;">A white oak, 16 ins. diam., bears N. 77° W., 51 lks. dist., mkd. with a healed blaze. (Record bearing N. 35° W.)</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T9N R22E R23E 1/4 S12 S7 1967</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A pine, 25 ins. diam., bears N. 82 1/4° E., 188 lks. dist., mkd. 1/4 S 7 BT.</p>	
	<p style="padding-left: 40px;">A pine, 25 ins. diam., bears S. 18 1/2° W., 54 lks. dist., mkd. 1/4 S12 BT.</p>	
	<p>Deposit the orig. cor. stone alongside the iron post.</p>	
	<p>Raise a mound of stone W. of the cor.</p>	
	<p style="text-align: center;">_____</p> <p>N. 0°15' W., beginning new measurement.</p>	
40.34	<p>The cor. of secs. 1, 6, 7 and 12, monumented by a basalt stone, 14 x 12 x 8 ins., firmly set, mkd. 5 notches on S. face, mound of stone W., from which the remains of the orig. bearing trees:</p>	
	<p style="padding-left: 40px;">A pine, 22 ins. diam., bears S. 40 1/2° E., 134 lks. dist., mkd. T9NR23E S7 BT. (Record: S. 39° E., 137 lks. dist.)</p>	
	<p style="padding-left: 40px;">A white oak stump, 16 ins. diam., bears N. 89° W., 26 lks. dist., mkd. T9NR23E S1.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>	

Dep. Resurvey, W. Bdy., T. 9 N., R. 23 E.

CHAINS

T9N
R22E R23E
S1 | S6
S12 | S7
1967

from which

A pine, 15 ins. diam., bears N. $86\frac{1}{4}^{\circ}$ E., 53 lks. dist., mkd. T9NR23E S6 BT.

A pine, 8 ins. diam., bears S. $40\frac{1}{2}^{\circ}$ E., 44 lks. dist., mkd. T9NR23E S7 BT.

A pine, 5 ins. diam., bears S. $51\frac{1}{4}^{\circ}$ W., 47 lks. dist., mkd. T9NR22E S12 BT.

A pine, 8 ins. diam., bears N. $21\frac{3}{4}^{\circ}$ W., 59 lks. dist., mkd. T9NR22E S1 BT.

Deposit the orig. cor. stone alongside the iron post.

Land, gently rolling.
Soil, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

N. $0^{\circ}12'$ E., bet. secs. 1 and 6.

Over nearly level land, through dense timber.

15.00 Track road, bears NE. and SW.

30.50 Track road, bears E. and W.

40.52 The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented by a basalt stone, 24 x 16 x 6 ins., firmly set in the ground, mkd. $\frac{1}{4}$ on top, from which the orig. bearing trees:

A white oak, 15 ins. diam., bears S. $35\frac{1}{2}^{\circ}$ E., 56 lks. dist., mkd. $\frac{1}{4}$ S. (Record bearing S. 39° E.)

A yellow pine, 27 ins. diam., bears S. 63° W., 40 lks. dist., mkd. with a healed blaze.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T9N
R22E R23E
 $\frac{1}{4}$
S1 | S6
1967

from which

A pine, 7 ins. diam., bears N. $53\frac{1}{4}^{\circ}$ E., 31 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

A juniper, 8 ins. diam., bears S. 78° W., 56 lks. dist., mkd. $\frac{1}{4}$ S 1 BT.

Raise a mound of stone W. of the cor., and deposit the orig. cor. stone in the mound.

Dep. Resurvey, W. Bdy., T. 9N., R. 23 E.

CHAINS													
	<p>N. 0°04' E., beginning new measurement.</p>												
40.70	<p>The cor. of Ts. 9 and 10 N., Rs. 22 and 23 E., monumented by an iron post, 3 ins. diam., firmly set in a mound of stone, brass cap mkd.</p>												
	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2" style="text-align: center;">T10N</td></tr> <tr><td colspan="2" style="text-align: center;">R22E R23E</td></tr> <tr><td style="text-align: center;">S36</td><td style="text-align: center;">S31</td></tr> <tr><td style="text-align: center;">S1</td><td style="text-align: center;">S6</td></tr> <tr><td colspan="2" style="text-align: center;">T9N</td></tr> <tr><td colspan="2" style="text-align: center;">1935</td></tr> </table>	T10N		R22E R23E		S36	S31	S1	S6	T9N		1935	
T10N													
R22E R23E													
S36	S31												
S1	S6												
T9N													
1935													
	<p>Land, nearly level. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>												
	<p style="text-align: center;">Retracement of Portions of the North Boundary T. 9 N., R. 23 E., G&SR M., Arizona</p>												
	<p style="text-align: center;">Retracement of the Survey Executed by Theodore Vander Meer in 1935</p>												
	<p>Portions of the north boundary were retraced to establish corner points for control of subdivisions of sections 2, 3 and 4.</p>												
	<p>The ¼ sec. cor. of sec. 2, only, on the N. bdy. of the Tp., monumented by an iron post 1 in diam., projecting 10 ins. above the ground, properly mkd., and witnessed as described in the official record of the 1935 resurvey.</p>												
	<p>S. 89°40' W., along the N. bdy. of sec. 2.</p>												
	<p>Over gently rolling land, through scattered timber.</p>												
7.80	<p>Apache Railroad, bears N. 2° E. and S. 2° W.</p>												
10.115	<p>Point for the E-W 1/64 sec. cor. of sec 2, only, at proportionate dist., not monumented.</p>												
20.23	<p>Point for the W 1/16 sec. cor. of sec. 2, only, at proportionate dist., not monumented.</p>												
30.345	<p>Point for the W-W 1/64 sec. cor. of sec. 2, only, at proportionate dist., not monumented.</p>												
33.50	<p>Wash, 50 lks. wide, 1 ft. deep, drains NW.</p>												
38.38	<p>The cor. of secs. 34 and 35, T. 10 N., R. 23 E., monumented by an iron post 2 ins. diam., projecting 10 ins. above the ground, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p>												
40.46	<p>The cor. of secs. 2 and 3, only, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p>												
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine and juniper Undergrowth, bunch grass.</p>												

Retracement, N. Bdy., T. 9 N., R. 23 E.

CHAINS	
<p>20.25</p> <p>37.88</p> <p>40.50</p>	<p>S. 89°48' W., along the N. bdy. of sec. 3.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the E 1/16 sec. cor. of sec. 3, only, at proportionate dist., not monumented.</p> <p>The 1/4 sec. cor. of sec. 34, T. 10 N., R. 23 E., monumented by an iron post 1 in. diam., firmly set in a mound of stone, properly mkd. and witnessed as described in the 1935 resurvey.</p> <p>The 1/4 sec. cor. of sec. 3, only, monumented by an iron post 1 in. diam., firmly set in a mound of stone, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine and juniper. Undergrowth, bunch grass.</p>
<p>20.27</p> <p>36.88</p> <p>40.54</p>	<p>The cor. of secs. 3 and 4 only, on the N. bdy. of the Tp., monumented by a basalt stone, 12 x 10 x 6 ins., firmly set in a mound of stone, mkd. 3 notches on E. and 3 notches on W. faces, from which the remains of an orig. bearing tree:</p> <p style="padding-left: 40px;">A dead pine, 19 ins. diam., bears S. 55 1/4° W., 192 lks. dist., mkd. T9NR23E S 4BT. (Record bearing S. 59° W.)</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T10N R23E</p> <p style="margin-left: 40px;">S33</p> <hr style="width: 50%; margin: 0 auto;"/> <p style="margin-left: 40px;">S4 S3</p> <p>T9N R23E</p> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 59° E., 22 lks. dist., mkd. T9NR23E S3 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 81 1/4° W., 36 lks. dist., mkd. T9NR23E S4 BT.</p> <p>S. 89°40' W., along the N. bdy. of sec. 4.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the E 1/16 sec. cor. of sec. 4, only, at proportionate dist., not monumented.</p> <p>The 1/4 sec. cor. of sec. 33, T. 10 N., R. 23 E., monumented by an iron post, 1 in. diam., projecting 4 ins. above the ground, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p> <p>The 1/4 sec. cor. of sec. 4 only, monumented by an iron post 1 ins. diam., projecting 12 ins. above the ground in a mound of stone, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p>

Retracement, N. Bdy., T. 9 N., R. 23 E.

CHAINS	
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine and juniper. Undergrowth, bunch grass.</p>
	<p>Dependent Resurvey of the Subdivisional Lines T. 9 N., R. 23 E., G&SR M., Arizona</p>
	<p>Reestablishment of the Surveys Executed by O. D. Wheeler in 1883 and C. A. Long in 1914</p>
	<p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p>
	<p>N. 1°14' E., bet. secs. 35 and 36.</p>
	<p>Over gently rolling land, through dense timber.</p>
7.00	Dim logging road, bears E. and W.
8.90	Old railroad bed, bears E. and W.
40.56	<p>The $\frac{1}{4}$ sec. cor. of secs. 35 and 36, monumented by a basalt stone, 20 x 16 x 8 ins., firmly set, no legible mks., mound of stone alongside, from which an orig. bearing tree:</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears S. 35° W., 43 lks. dist., mkd. with a healed blaze. (Record; S. 76° W., 46 lks. dist.).</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E $\frac{1}{4}$ S35 S36 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears S. 57½° E., 33 lks. dist., mkd. $\frac{1}{4}$ S36 BT.</p> <p>Raise a mound of stone W. of the cor. and deposit the orig. cor. stone in the mound.</p>
	<p>N. 0°34' W., beginning new measurement.</p>
11.10	Wash, 40 lks. wide, 10 ins. deep, drains NW.
12.70	Bladed road, bears SE. and NW.
17.30	Logging road, bears NE. and SW.
40.34	<p>The cor. of secs. 25, 26, 35 and 36, monumented by a basalt stone, 20 x 17 x 9 ins., firmly set in a mound of stone, mkd. 1 notch on S. and 1 notch on E. faces, from which the remains of the orig. bearing trees:</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

A pine, 15 ins. diam., bears N. 23° E.,
80 lks. dist., mkd. 3E.

A pine, 15 ins. diam., bears S. 37° E.,
110 lks. dist., mkd. S36.

A pine stump, bears S. 60° W., 77 lks.
dist., mkd. T9NR 35.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T9N R23E
S26 | S25
S35 | S36
1967

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

39.93

From the cor. of secs. 25, 30, 31 and 36, on the E.
bdy. of the Tp.

N. 88°38' W., bet. secs. 25 and 36.

Over gently rolling land, through dense timber.

The ¼ sec. cor. of secs. 25 and 36, monumented by a
basalt stone, 14 x 10 x 6 ins., firmly set, mkd. ¼ on
N. face, mound of stone N.

At the corner point

Set the iron post 18 ins. in the ground, in a collar
of stone, brass cap mkd.

T9N R23E
¼ S25
S36
1967

from which

A pine, 8 ins. diam., bears S. 40° E.,
25 lks. dist., mkd. ¼ S36 BT.

A pine, 4 ins. diam., bears N. 40° W.,
36 lks. dist., mkd. ¼ S25 BT.

Deposit the orig. cor. stone alongside the iron post.

39.89

S. 88°48' W., beginning new measurement.

The cor. of secs. 25, 26, 35 and 36.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

CHAINS	
	N. 1°03' W., bet. secs. 25 and 26.
	Over gently rolling land, through dense timber.
40.37	The ¼ sec. cor. of secs. 25 and 26, monumented by a lava stone, 20 x 12 x 6 ins., firmly set, no legible mks., from which an orig. bearing tree:
	<p style="padding-left: 40px;">A pine, 30 ins. diam., bears N. 20° E., 70 lks. dist., mkd. with an old blaze.</p>
	At the corner point
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T9N R23E ¼ S26 S25 1967</p>
	from which
	<p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 50° E., 22 lks. dist., mkd. ¼ S25 BT.</p>
	<p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 45° W., 36 lks. dist., mkd. ¼ S26 BT.</p>
	<p style="padding-left: 40px;">A fence cor., bears S. 80° W., 6 lks. dist., fences bear N. and S. 60° W.</p>
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.

	N. 1°21' W., beginning new measurement.
3.80	Top of spur, slopes SW.
10.107	Point for the S-N 1/64 sec. cor. of secs. 25 and 26, at proportionate dist., not monumented.
14.40	Fence, bears E. and W., 6 lks. dist.; thence N., E. and S.
19.20	Old railroad bed, bears E. and W.
19.80	Wash, 40 lks. wide, 1 ft. deep, drains NW.
20.215	Point for the N 1/16 sec. cor. of secs. 25 and 26, at proportionate dist., not monumented.
22.50	Wash, 40 lks. wide, 1 ft. deep, drains SW.
30.322	Point for the N-N 1/64 sec. cor. of secs. 25 and 26, at proportionate dist., not monumented.
32.20	Track road, bears SE. and NW.
40.43	The cor. of secs. 23, 24, 25 and 26, monumented by a lava stone, 14 x 12 x 9 ins., firmly set, mkd. 2 notches on S face, mound of stone W., from which the orig. bearing trees:

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

A pine, 35 ins. diam., bears N. 20° E.,
66 lks. dist., mkd. with a blaze.
(Record; 53 lks. dist.).

A pine, 37 ins. diam., bears S. 50° E.,
63 lks. dist., mkd. with an old blaze.

At the corner point

Set the iron post 16 ins. in the ground, mound of stone
to top, brass cap mkd.

T9N R23E	
S23	S24
S26	S25
1967	

from which

A pine, 6 ins. diam., bears S. 30½° E.,
20 lks. dist., mkd. T9NR23E S25 BT.

A pine, 4 ins. diam., bears S. 83½° W.,
19 lks. dist., mkd. T9NR23E S26 BT.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone, W. of the cor.

Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

From the cor. of secs. 19, 24, 25 and 30, on the E. bdy.
of the Tp.

N. 89°19' W., bet. secs. 24 and 25.

Over gently rolling land, through dense timber.

31.80 Draw, drains S.

40.47 The ¼ sec. cor. of secs. 24 and 25, monumented by a
basalt stone, 18 x 9 x 9 ins., (record calls for a wooden
post), firmly set 6 ins. below the surface alongside
the remains of an old fence cor., mkd. ¼ on N. face,
mound of stone N. This is accepted as best available
evidence of the orig. cor. position, from which an old
bearing tree:

A pine, 27 ins. diam., bears N. 10° E.,
101 lks. dist., mkd. ¼ S. (Record: a white
oak, 14 ins. diam., bears N. 30° E., 28 lks.
dist.). There are no white oaks in this immedi-
ate area.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

CHAINS	
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ $\frac{S24}{S25}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 60° W., 4 lks. dist., mkd. $\frac{1}{4}$ S25 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <p style="text-align: center;">—————</p> <p>S. 89°15' W., beginning new measurement.</p>
4.95	Fence, bears S. and N., 13 lks. dist., to cor. of fences bearing E., S. and W.
5.067	Point for the E-E-W 1/256 sec. cor. of secs. 24 and 25, at proportionate dist.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p>S24 E-E-W 1/256 S25 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 44° E., 18 lks. dist., fences bear E., S. and W.</p> <p>Raise a mound of stone N. of the cor.</p>
10.135	Point for the E-W 1/64 sec. cor. of secs. 24 and 25, at proportionate dist., not monumented.
	The cor. point is located 4 lks. South of a fence bearing N. 79° E. and S. 79° W.
11.70	Fence, bears N. 79° E. and S. 79° W.
15.202	Point for the W-E-W 1/256 sec. cor. of secs. 24 and 25, at proportionate dist.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p>S24 W-E-W 1/256 S25 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 77° E., 34 lks. dist., fences bear N. 79° E. and S.</p> <p>Raise a mound of stone N. of the cor.</p>
20.27	Point for the W 1/16 sec. cor. of secs. 24 and 25, at proportionate dist., not monumented.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
25.337	Point for the E-W-W 1/256 sec. cor. of secs. 24 and 25, at proportionate dist., not monumented.
30.405	Point for the W-W 1/64 sec. cor. of secs. 24 and 25, at proportionate dist., not monumented.
32.90	Old railroad bed, bears N. and S.
33.00	Wash, 30 lks. wide, 3 ft. deep, drains S. 25° W.
40.54	The cor. of secs. 23, 24, 25 and 26.
<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
<p>N. 1°16' W., bet. secs. 23 and 24.</p>	
<p>Over gently rolling land, through dense timber.</p>	
34.00	Track road, bears NE. and SW.
39.15	<p>The ¼ sec. cor. of secs. 23 and 24, monumented by a basalt stone, 14 x 9 x 5 ins., loosely set, mkd. ¼ on one face, mound of stone W., from which an orig. bearing tree:</p>
<p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 81° W., 44 lks. dist., mkd. ¼.</p>	
<p>At the corner point</p>	
<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>	
<p style="text-align: center;">T9N R23E ¼ S23 S24 1967</p>	
<p>from which</p>	
<p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 80° E., 86 lks. dist., mkd. T9NR23E S24 BT.</p>	
<p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. 10° W., 35 lks. dist., mkd. ¼ S23 BT.</p>	
<p>Bury the orig. cor. stone alongside the iron post.</p>	
<p>Raise a mound of stone W. of the cor.</p>	
<p style="text-align: center;">—————</p>	
<p>N. 0°21' E., beginning new measurement.</p>	
13.30	Begin desc. N. slope into Elk Springs Draw.
14.10	Old railroad bed, bears E. and W.; enter Elk Springs Draw, bears SE. and NW.
14.50	Wash in bottom of Elk Springs Draw, 80 lks. wide, 1 ft. deep, drains NW.; asc. S. slope.
20.14	Point for the N 1/16 sec. cor. of secs. 23 and 24, at proportionate dist., not monumented.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS									
21.00	Leave Elk Springs Draw, bears SE. and NW.								
33.00	Desc. gentle N. slope.								
40.28	<p>The cor. of secs. 13, 14, 23 and 24, monumented by a basalt stone, 18 x 14 x 10 ins., firmly set, no legible markings, from which the orig. bearing trees:</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 28° E., 27 lks. dist., mkd. N.</p> <p style="padding-left: 40px;">A pine, 21 ins. diam., bears S. 39° W., 13 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 42° W., 31 lks. dist., mkd. 9NR23E S14 BT.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="0"> <tr><td colspan="2">T9N R23E</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S14</td><td style="padding-left: 5px;">S13</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S23</td><td style="padding-left: 5px;">S24</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raised a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	T9N R23E		S14	S13	S23	S24	1967	
T9N R23E									
S14	S13								
S23	S24								
1967									
41.17	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 88°28' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land, through dense timber.</p> <p>The ¼ sec. cor. of secs. 13 and 24, monumented by a basalt stone, 16 x 7 x 7 ins., firmly set in a mound of stone, mkd. ¼ on N. face, from which the orig. bearing trees:</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears S. 33° E., 33 lks. dist., mkd. ¼.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 43° W., 34 lks. dist., mkd. with a healed blaze.</p> <p>At the corner point</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="0"> <tr><td colspan="2">T9N R23E</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">¼</td><td style="padding-left: 5px;">S13</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding-left: 5px;">S24</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div>	T9N R23E		¼	S13		S24	1967	
T9N R23E									
¼	S13								
	S24								
1967									

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
40.23	<p>from which</p> <p>A fence cor. bears S. 33° E., 33 lks. dist.; fences bear S. 5° W. and N. 85° E.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr/> <p>S. 89°55' W., beginning new measurement.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
40.10	<p>N. 0°26' E., bet. secs. 13 and 14.</p> <p>Over gently rolling land, through dense timber.</p> <p>The ¼ sec. cor. of secs. 13 and 14, monumented by a broken basalt stone, 10 x 10 x 6 ins., firmly set, mkd. ¼ on W. face, from which the remains of the orig. bearing trees:</p> <p>A pine, 24 ins. diam., bears S. 83½° E., 42 lks. dist., mkd. ¼. (Record, S. 78° E.).</p> <p>A pine stump, 20 ins. diam., bears S. 80¼° W., 78 lks. dist., mkd. BT. (record, S. 87° W., 61 lks. dist.).</p> <p>At the corner point.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E ¼ S14 S13 1967</p>
40.24	<p>from which</p> <p>A pine, 8 ins. diam., bears N. 37 3/4° E., 46 lks. dist., mkd. ¼ S13 BT.</p> <p>A pine, 8 ins. diam., bears N. 60° W., 11 lks. dist., mkd. ¼ S14 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>N. 0°16' E., beginning new measurement.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented by a basalt stone, 20 x 14 x 10 ins., firmly set in a mound of stone, no legible markings, from which the remains of the orig. bearing trees:</p>

CHAINS

A pine stump, 24 ins. diam., bears N. 26° E., 155 lks. dist., mkd. with a healed blaze.

A pine stump, 28 ins. diam., bears S. 63° W., 64 lks. dist., mkd. with a blaze.

At the corner point

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
S11 | S12
S14 | S13
 1967

from which

A pine, 10 ins. diam., bears S. 66½° E., 49 lks. dist., mkd. T9NR23E S13 BT.

A pine, 10 ins. diam., bears S. 31½° W., 38 lks. dist., mkd. S14 BT.

A pine, 8 ins. diam., bears N. 47° W., 66 lks. dist., mkd. S11 BT.

Deposit the orig. cor. stone alongside the iron post.

Land, gently rolling.
 Soil, rocky, clay loam.
 Timber, pine, juniper and oak.
 Undergrowth, bunch grass.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.

S. 88°54' W., bet. secs. 12 and 13.

Over gently rolling land, through dense timber.

3.50 Fence, bears N. 5° E. and S. 5° W.

40.40 The ¼ sec. cor. of secs. 12 and 13, monumented by a basalt stone, 12 x 8 x 5 ins., firmly set, mkd. ¼ on N. face, mound of stone N.

At the corner point

Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
¼ S12
S13
 1967

from which

A pine, 7 ins. diam., bears N. 18 3/4° E., 13 lks. dist., mkd. ¼ S12 BT.

A pine, 10 ins. diam., bears S. 45 3/4° E., 14 lks. dist., mkd. ¼ S13 BT.

Deposit the orig. cor. stone alongside the iron post.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
<p>9.80</p> <p>40.27</p>	<p>S. 88°59' W., beginning new measurement.</p> <p>Track road, bears S. 7° E. and N. 2° W.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
<p>9.70</p> <p>38.90</p> <p>40.70</p>	<p>N. 1°43' E., bet. secs. 11 and 12.</p> <p>Over gently rolling land, through dense timber.</p> <p>Bladed road, bears N. 40° E. and S. 40° W.</p> <p>Track road, bears NE. and irregularly W.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by a basalt stone, 16 x 12 x 8 ins., firmly set, dimly mkd., mound of stone W., from which an old bearing tree:</p> <p style="padding-left: 40px;">A pine, 27 ins. diam., bears N. 45° E., 95 lks. dist., mkd. $\frac{1}{4}$ S. (Record, 35 lks. dist.).</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E</p> <p>$\frac{1}{4}$</p> <p>S11 S12</p> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 72° W., 5 lks. dist., mkd. $\frac{1}{4}$ S11 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p>
<p>28.30</p> <p>41.04</p>	<p>N. 3°04' E., beginning new measurement.</p> <p>Track road, bears S. 80° E. and N. 80°W.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented by an iron post, 2$\frac{1}{2}$ ins. diam., firmly set in a mound of stone, properly mkd. and witnessed as described in the 1966 remonumentation field notes.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>S. 87°39' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through dense timber.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
.11	Fence, bears N. and S.
37.92	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented by a basalt stone, 19 x 13 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on N. face, mound of stone N., from which the orig. bearing trees:</p> <p>A pine, 21 ins. diam., bears S. 12° W., 57 lks. dist., mkd. with a healed blaze. (Record, 70 lks. dist.).</p> <p>A pine, 30 ins. diam., bears N. 18° W., 70 lks. dist., mkd. with a healed blaze. (Record, 37 lks. dist.).</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E $\frac{1}{4}$ $\frac{S 1}{S12}$ 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 88°40' W., beginning new measurement.</p>
10.00	Wash, 30 lks. wide, 1 ft. deep, drains N.
11.00	Bladed road, bears NE. and irregularly S.
40.33	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>N. 3°35' E., bet. secs. 1 and 2.</p> <p>Over gently rolling land, through dense timber.</p>
5.50	Leave dense timber, enter moderate timber, bears E. and W.
13.00	Leave moderate timber, enter dense timber, bears E. and W.
40.37	<p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented by a basalt stone, 19 x 7 x 5 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, mound of stone W., from which the remains of the orig. bearing trees:</p> <p>A dead pine, 27 ins. diam., bears N. 82° E., 122 lks. dist., mkd. BT. (No record of this tree)</p> <p>A pine, 34 ins. diam., bears N. 29° W., 140 lks. dist., mkd. $\frac{1}{4}$ B.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS		
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ S 2 S 1 1967</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 10%; margin: 10px auto;"/> <p>N. 5°26' W., beginning new measurement.</p> <p>21.00 Leave timber, enter meadow, bears E. and W.</p> <p>21.18 Point for the N 1/16 sec. cor. of secs. 1 and 2, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E N1/16 S 2 S 1 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>21.50 Fence, cor., fences bear E., W. and N. 5°W.</p> <p>36.40 Power line, bears N. 75° E. and S. 75° W.</p> <p>42.26 The cor. of secs. 1 and 2, only, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., projecting 10 ins. above the ground, properly mkd. and witnessed as described in the official record of the 1935 resurvey, the cor. is set alongside a cor. of fences bearing E. and S. 5° E.</p> <p>from which</p> <p style="padding-left: 40px;">The cor. of secs. 35 and 36, T. 10 N., R. 23 E., bears N. 89° 47' E., 106 lks. dist., monumented by an iron post 2 ins. diam., firmly set, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
	<p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.</p> <p>N. 2°28' E., bet. secs. 34 and 35.</p> <p>Over gently rolling land, through dense timber.</p> <p>25.30 Old railroad bed, bears NE. and SW.</p> <p>40.85 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented by a basalt stone, 15 x 11 x 9 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face.</p> <p>At the corner point</p> <p>Set the iron post 15 ins. in the ground, in a collar of stone, brass cap mkd.</p>	

CHAINS

T9N R23E

$\frac{1}{2}$
S34|S35
1967

from which

A pine, 6 ins. diam., bears N. 68° E., 12 lks.
dist., mkd. $\frac{1}{2}$ S35 BT.

A pine, 6 ins. diam., bears N. 65° W., 2 lks.
dist., mkd. $\frac{1}{2}$ S34 BT.

Deposit the orig. cor. stone alongside the iron post.

N. 0°03' W., beginning new measurement.

20.075 Point for the N 1/16 sec. cor. of secs. 34 and 35, at proportionate dist.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E

N1/16
S34|S35
1967

from which

A pine, 4 ins. diam., bears S. 47° E., 10 lks.
dist., mkd. N1/16 S35 BT.

A pine, 4 ins. diam., bears N. 68° W., 19 lks.
dist., mkd. N1/16 S34 BT.

23.50 Old logging road, bears NE. and SW.

33.10 Wash, 20 lks. wide, 1 ft. deep, drains NW.

33.60 Old railroad bed, bears SE. and NW., 20 lks., thence N.

40.15 The cor. of secs. 26, 27, 34 and 35, monumented by an old mound of stone, from which the orig. bearing trees:

A pine, 22 ins. diam., bears N. 70° E., 53 lks.
dist., mkd. with an old blaze. (Record, N. 64° E.).

A pine, 25 ins. diam., bears S. 32° E., 65 lks.
dist., mkd. with an old blaze. (Record, 93 lks. dist.).

A pine, 26 ins. diam., bears N. 45° W., 98 lks.
dist., mkd. with an old blaze. (Record dist. 100 lks.).

At the corner point

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E

S27|S26
S34|S35
1967

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°38' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through dense timber.</p>
27.20	<p>Wash, 25 lks. wide, 2 ft. deep, drains NW.</p>
28.80	<p>Bladed road, bears SE. and NW.</p>
39.44	<p>The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented by a basalt stone, 17 x 10 x 8 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face, from which the orig. bearing trees:</p>
	<p>A pine, 20 ins. diam., bears N. 2°E., 70 lks. dist., mkd. BT.</p>
	<p>A pine, 22 ins. diam., bears S. 25° W., 40 lks. dist., mkd. with a healed blaze.</p>
	<p>At the corner point</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ S26 S35 1967</p>
	<p>from which</p>
	<p>A pine, 4 ins. diam., bears S. 35° W., 11 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p>
	<p>Chipmunk Spring, bears N. 73°50' E., 13.60 chs. dist., a taped water pipe, $1\frac{1}{2}$ ins. diam.; drains into a cement tank, 12 x 4 x 1 ft.; producing 1 pint per minute.</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Raise a mound of stone N. of the cor.</p>
	<p style="text-align: center;">—————</p> <p>S. 89°38' W., beginning new measurement.</p>
17.90	<p>Dim logging road, bears E. and NW.</p>
39.88	<p>The cor. of secs. 26, 27, 34 and 35.</p>
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>N. 1°10' W., bet. secs. 26 and 27.</p>

CHAINS	
2.00	Over gently rolling land, through dense timber.
35.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 75° W.
39.90	Bladed road, bears NE. and SW.
40.23	Fence, bears E. and W.
	The 1/4 sec. cor. of secs. 26 and 27, monumented by basalt stone, 19 x 12 x 9 ins., firmly set in a mound of stone, dimly mkd., from which an old bearing tree: A pine, 27 ins. diam., bears SW., 45 lks. dist., mkd. 1/4 S. (No record of this tree)
	At the corner point
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ S27 S26 1967</p>
	from which
	A pine, 6 ins. diam., bears N. 40° E., 26 lks. dist., mkd. T9NR23E S26 BT.
	Deposit the orig. cor. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> N. 3°13' W., beginning new measurement.
4.00	Track road, bears NE. and SW.
13.80	Track road, bears NE. and SW.; asc. S. slope of Pat Mullen Mountain.
34.40	Top of Pat Mullen Mountain, bears NE. and SW.; desc. N. slope of mountain.
39.82	The cor. of secs. 22, 23, 26 and 27, monumented by a basalt stone, 20 x 14 x 6 ins., with a local cor., a 1 in. water pipe, set alongside, no legible mks., from which an orig. bearing tree: An oak, 20 ins. diam., bears N. 30° E., 24 lks. dist., mkd. 23. (Record dist. 29 lks.).
	At the corner point
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T9N R23E S22 S23 S27 S26 1967</p>
	from which
	A pine, 8 ins. diam., bears N. 70° E., 43 lks. dist., mkd. T9NR23E S23 BT.
	Deposit the orig. cor. stone and local pipe alongside the iron post.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p>
	<p>S. 89°42' W., bet. secs. 23 and 26.</p>
3.00	Track road, bears S. 40° E. and N. 40° W.
40.35	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented by an old mound of stone, also verified by using record bearing of orig. bearing trees:</p> <p style="padding-left: 40px;">A pine, 27 ins. diam., bears N. 10° E., 40 lks. dist., mkd. with a healed over blaze. (Record N. 10° E., 49 lks. dist.).</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. 30° E., 59 lks. dist., mkd. $\frac{1}{4}$ S. (Record, S. 30° E., 98 lks. dist.).</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T9N R23E</p> <p>$\frac{1}{4}$ <u>S23</u></p> <p>S26</p> <p>1967</p> </div> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°08' W., beginning new measurement.</p>
9.30	Wash, 30 lks. wide, 1 ft. deep, drains NW.
11.70	Asc. NE. slope of Pat Mullen Mountain.
26.20	Fence, bears N. 35° E. and S. 35° W.
26.40	Enter S. end of cinder pit, bears E. and W.
30.00	Leave cinder pit, continue ascent.
30.60	Fence, bears S. 25° E. and N. 25° W.
35.90	Spur, slopes N.; desc. NW. slope of Pat Mullen Mountain.
40.30	The cor. of secs. 22, 23, 26 and 27.
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>N. 0°28' W., bet. secs. 22 and 23.</p> <p>Over rolling land, through dense timber.</p>
10.00	Point for the S-S $\frac{1}{64}$ sec. cor. of secs. 22 and 23, at proportionate dist., not monumented.
10.30	Bladed road, at the base of Pat Mullen Mountain, bears N. 70° E. and S. 70° W.; thence over gently rolling land.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
11.80	Bladed road, bears NE and SW.
14.70	Wash, 50 lks. wide, 1 ft. deep, drains NW.
15.00	Point for the N-S-S 1/256 sec. cor. of secs. 22 and 23, at proportionate dist., not monumented.
20.00	Point for the S 1/16 sec. cor. of secs. 22 and 23, at proportionate dist., not monumented.
20.30	A developed spring, bears West, 50 lks. dist. This spring is enclosed in a cement box.
30.00	Point for the N-S 1/64 sec. cor. of secs. 22 and 23, at proportionate dist., not monumented.
40.00	The 1/4 sec. cor. of secs. 22 and 23, monumented by a basalt stone, 17 x 10 x 8 ins., firmly set, dimly mkd. A local cor., a water pipe, 1 in. diam., set alongside, with cap mkd. SE CO 4128 22.23, from which an orig. bearing tree: An oak, 12 ins. diam., bears S. 36° E., 45 lks. dist., mkd. T. At the corner point Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd. T9N R23E 1/4 S22 S23 1967 from which A pine, 5 ins. diam., bears N. 50° E., 16 lks. dist., mkd. T9NR23E S23 BT. A pine, 7 ins. diam., bears S. 77 1/2° W., 22 lks. dist., mkd. T9NR23E S22 BT. Deposit the orig. cor. stone and bury the local pipe, inverted, alongside the iron post. Raise a mound of stone W. of the cor. _____
2.40	Track road, bears NE. and SW.
10.125	Point for the S-N 1/64 sec. cor. of secs. 22 and 23, at proportionate dist., not monumented.
15.10	Power line, bears E. and W.
20.25	Point for the N 1/16 sec. cor. of secs. 22 and 23, at proportionate dist., not monumented.
40.50	The cor. of secs. 14, 15, 22 and 23, monumented by a local survey cor., a water pipe, 1 in. diam., set firmly in a mound of stone, cap mkd. SE CO 4128, with secs. 14, 15, 22 and 23 in their appropriate quadrants, from which the orig. bearing trees:

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>A pine, 22 ins. diam., bears N. 60° E., 56 lks. dist., mkd. S B.</p> <p>A pine, 34 ins. diam., bears S. 70° E., 89 lks. dist., mkd. T9NR.</p> <p>A pine, 16 ins. diam., bears S. 26° W., 79 lks. dist., mkd. T9NR23E. (Record, 100 lks. dist.).</p> <p>A pine, 18 ins. diam., bears N. 38° W., 92 lks. dist., mkd. B. (Record, 97 lks. dist.).</p> <p>At the corner point</p> <p>Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E <u>S15</u> <u>S14</u> S22 S23 1967</p> <p>Deposit the local pipe, inverted, alongside the iron post.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°46' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through dense timber.</p>
20.07	Point for the E 1/16 sec. cor. of secs. 14 and 23, at proportionate dist., not monumented.
30.10	Point for the W-E 1/64 sec. cor. of secs. 14 and 23, at proportionate dist., not monumented.
39.50	Track road, bears N. 50° E. and S. 50° W.
40.13	The 1/4 sec. cor. of secs. 14 and 23, monumented by an iron post, 2 1/2 ins. diam., set, mkd. and witnessed as described in the 1966 remonumentation field notes.
	<hr style="width: 20%; margin: 0 auto;"/>
	N. 89°49' W., beginning new measurement.
5.02	Point for the E-E-W 1/256 sec. cor. of secs. 14 and 23, at proportionate dist., not monumented.
6.50	Track road, bears N. and SE.
10.04	Point for the E-W 1/64 sec. cor. of secs. 14 and 23, at proportionate dist., not monumented.
15.06	Point for the W-E-W 1/256 sec. cor. of secs. 14 and 23, at proportionate dist., not monumented.
18.90	Enter Elk Springs Draw, bears SE. and NW.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
20.08	Point for the W 1/16 sec. cor. of secs. 14 and 23, at proportionate dist., not monumented.
22.70	Creek in Elk Springs Draw, course NW.
24.00	Leave Elk Springs Draw, bears SE. and N. 60° W.
24.30	Bladed road, bears N. 30° E. and S. 50° W.
27.80	Track road, on a curve, bears irregularly E. and N. 30° W.
40.17	The cor. of secs. 14, 15, 22 and 23. Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.
	N. 0°11' E., bet. secs. 14 and 15.
	Over gently rolling land, through dense timber.
6.90	Track road, bears E. and W.
7.40	Old railroad bed, bears S. 80° E. and N. 80° W.
10.90	Elk Springs Draw, drains NW.
40.27	The 1/4 sec. cor. of secs. 14, and 15, monumented by a basalt stone, 15 x 12 x 7 ins., firmly set, dimly mkd. 1/4 on W. face, mound of stone W., from which the remains of the orig. bearing trees: A dead oak, 6 ins. diam., bears S. 79° E., 62 lks. dist., mkd. 1/4 S BT. (Record dist. 68 lks.). A pine stump, 24 ins. diam., bears N. 28° W., 40 lks. dist., mkd. 1/4.
	At the corner point
	Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.
	T9N R23E 1/4 S15 S14 1967
	From which
	A pine, 8 ins. diam., bears N. 47° E., 9 lks. dist., mkd. 1/4 S14 BT.
	Deposit the orig. cor. stone alongside the iron post.

	N. 2°35' E., beginning new measurement.
14.30	Old railroad bed, bears N. 85° E. and S. 85° W.
14.70	Small draw, drains SW.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS						
40.98	<p>The cor. of secs. 10, 11, 14 and 15, monumented by a basalt stone, 12 x 10 x 7 ins., firmly set, no legible mks., mound of stone W., from which the orig. bearing trees:</p> <p>A dead oak, 14 ins. diam., bears N. 55° E., 9 lks. dist., mkd. with a healed blaze.</p> <p>An oak, 14 ins. diam., bears S. 43° E. 15 lks. dist., mkd. with a healed blaze.</p> <p>A pine, 30 ins. diam., bears S. 50° W., 58 lks. dist., mkd. with a healed blaze. (Record, 41 lks. dist.).</p> <p>A pine, 36 ins. diam., bears N. 45° W., 25 lks. dist., mkd. with a healed blaze.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E</p> <table border="1" style="margin: auto;"> <tr> <td>S10</td> <td>S11</td> </tr> <tr> <td>S15</td> <td>S14</td> </tr> </table> <p>1967</p> </div> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	S10	S11	S15	S14	
S10	S11					
S15	S14					
<p>9.20</p> <p>24.70</p> <p>24.90</p> <p>40.19</p>	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°32' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through dense timber.</p> <p>Graded road, bears N. 40° E. and S. 40° W.</p> <p>Old railroad bed, bears N. 75° E. and S. 75° W.</p> <p>Track road, bears N. 75° E. and S. 75° W.</p> <p>The ¼ sec. cor. of secs. 11 and 14, as determined from the orig. bearing trees:</p> <p>A pine, 36 ins. diam., bears N. 6° E., 108 lks. dist., mkd. ¼ S BT.</p> <p>A pine, 26 ins. diam., bears S. 39° W., 19 lks. dist., mkd. ¼ S.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>					

CHAINS	
	<p>T9N R23E $\frac{1}{4}$ $\frac{S11}{S14}$ 1967</p> <hr/> <p>N. 88°53' W., beginning new measurement.</p>
38.73	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
1.10	<p>N. 1°21' E., bet. secs. 10 and 11.</p> <p>Over gently rolling land, through dense timber.</p> <p>Draw, drains W.</p>
40.86	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented by a basalt stone, 14 x 12 x 6 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, mound of stone alongside, from which the remains of an orig. tree:</p> <p style="padding-left: 40px;">A stump hole, bears S. 75° W., 47 lks. dist., a fallen pine, 25 ins. diam., alongside, mkd. $\frac{1}{4}$. (Record, S. 67° W.).</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p>T9N R23E $\frac{1}{4}$ $\frac{S10}{S11}$ 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears N. 87° E., 12 lks. dist., mkd. $\frac{1}{4}$ S11 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 50° W., 35 lks. dist., mkd. $\frac{1}{4}$ S10 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
	<hr/> <p>N. 1°05' E., beginning new measurement.</p>
12.90	Dim track road, bears S. 60° E. and N. 60° W.
18.80	Dim track road, bears SE. and NW.
28.60	Track road, bears SE. and NW.
35.30	Track road, bears N. 40° E. and S. 40° W.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS							
41.00	<p>The cor. of secs. 2, 3, 10 and 11, monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the 1966 remonumentation field notes.</p> <p>from which</p> <p style="padding-left: 40px;">Fence cor., bears North, 1 lk. dist., fences bear N., E. and W.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>						
39.92	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°23' W., bet. secs. 2 and 11.</p> <p>Over gently rolling land, through dense timber.</p> <p>The ¼ sec. cor. of secs. 2 and 11, as determined from the orig. bearing tree:</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 3° E., 89 lks. dist., mkd. ¼ S.</p> <p>At the corner point</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T9N R23E</p> <table style="margin: auto;"> <tr> <td style="padding-right: 5px;">¼</td> <td style="border-top: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">S 2</td> </tr> <tr> <td></td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S11</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1967</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears S. 48° E., 77 lks. dist., mkd. ¼ S11 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°53' W., beginning new measurement.</p>	¼	S 2		S11		1967
¼	S 2						
	S11						
	1967						
4.30	Dim track road, bears S. 20° E. and N. 20° W.						
8.10	Track road, bears SE. and NW.						
12.40	Track road, bears N. 25° E. and S. 25° W.						
20.20	Dim track road, bears N. and S.						
20.31	<p>Point for the W 1/16 sec. cor. of secs. 2 and 11, at proportionate dist.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T9N R23E</p> <table style="margin: auto;"> <tr> <td style="padding-right: 5px;">W 1</td> <td style="border-top: 1px solid black; border-bottom: 1px solid black; padding: 0 5px;">S 2</td> </tr> <tr> <td style="padding-right: 5px;">16</td> <td style="border-bottom: 1px solid black; padding: 0 5px;">S11</td> </tr> <tr> <td></td> <td style="padding: 0 5px;">1967</td> </tr> </table> </div> <p>from which</p>	W 1	S 2	16	S11		1967
W 1	S 2						
16	S11						
	1967						

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>A fence cor., bears N. 7° E., 76 lks. dist., fences bear N. and S. 42° W.</p> <p>Set a wooden post 3½ ft. long, 3 ins. diam., alongside the iron post.</p>
20.90	Fence cor., bears N. 42° E. and W., thence along E. and W. fence.
40.62	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>N. 1°24' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land, along a fence bearing N. 1°24' W. across open meadow.</p>
10.025	Point for the S-S 1/64 sec. cor. of secs. 2 and 3, at proportionate dist., not monumented.
12.30	Remains of an old fence line, projects W.
20.05	Point for the S 1/16 sec. cor. of secs. 2 and 3, at proportionate dist., not monumented.
25.00	Fence, bears S. 1°24' E. and N. 10°17' E., to cattle guard on the Apache Railroad.
27.30	Apache Railroad, bears N. 10°17' E. and S. 10°17' W.
31.90	Fence, bears S. 10°17' W. and N. 1°24' W.; enter dense timber, bears N. and SW.
40.10	Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E 1/4 S 3 S 2 1967</p> <p>The cor. is located 2 lks. East of a fence bearing S. 1°24' E. and N. 1°24' W.</p>
50.125	Point for the S-N 1/64 sec. cor. of secs. 2 and 3, at proportionate dist., not monumented.
50.15	Fence, bears E. and W.
53.50	Graded road, bears N. 80° E. and S. 80° W.
53.90	Power line, bears N. 80° E. and S. 80° W.
59.50	S. rim of a draw, bears NE. and SW.; desc. N. slope, end of N. and S. fence line.
60.15	Point for the N 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.

CHAINS	
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E N1/16 S 3 S 2 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located in the bottom of a deep draw, draining NE.; asc. S. slope.</p>
62.40	N. rim of draw, bears NE. and SW.; continue over gently rolling land.
70.175	Point for the N-N 1/64 sec. cor. of secs. 2 and 3, at proportionate dist., not monumented.
80.71	<p>The cor. of secs. 2 and 3, only, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the standard cor. of secs. 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 1°24' E., bet. secs. 33 and 34.</p> <p>Over gently rolling land, through dense timber.</p>
1.50	Track road, bears E. and W.
23.20	S. edge of a draw, bears SE. and NW.
24.90	Thompson Creek, 4 lks. wide, 1 ft. deep, course NW.
25.50	N. edge of draw, bears SE. and NW.
40.65	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E 1/4 S33 S34 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears S. 76° E., 24 lks. dist., mkd. 1/4 S34 BT.</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. 30° W., 28 lks. dist., mkd. 1/4 S33 BT.</p>
51.40	Wash, 20 lks. wide, 1 ft. deep, drains SW.
76.50	Bladed road, bears NE. and SW.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS											
81.30	<p>The cor. of secs. 27, 28, 33 and 34, monumented by an old mound of stone, from which the orig. bearing trees:</p> <p style="padding-left: 40px;">A pine, 20 ins. diam., bears S. 56° E., 85 lks. dist., mkd. 23 (Record dist. 35 lks.)</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 53° W., 59 lks. dist., mkd. T9NR23E S28 BT.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T9N</td><td>R23E</td></tr> <tr><td>S28</td><td>S27</td></tr> <tr><td>S33</td><td>S34</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears N. 28° E., 38 lks. dist., mkd. T9NR23E S27 BT.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	T9N	R23E	S28	S27	S33	S34	1967			
T9N	R23E										
S28	S27										
S33	S34										
1967											
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°53' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through dense timber.</p>										
4.40	<p>Fence cor., bears South, 13 lks. dist., fences bear N. and W.</p>										
5.022	<p>Point for the E-E-E 1/256 sec. cor. of secs. 27 and 34, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T9N</td><td>R23E</td></tr> <tr><td colspan="2">S27</td></tr> <tr><td colspan="2">E-E-E 1/256</td></tr> <tr><td colspan="2">S34</td></tr> <tr><td colspan="2">1967</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">Fence cor., bears S. 17° W., 12 lks. dist., fences bear S., E., and S. 89° W.</p> <p>Enter open meadow, edge bears S. and W.</p>	T9N	R23E	S27		E-E-E 1/256		S34		1967	
T9N	R23E										
S27											
E-E-E 1/256											
S34											
1967											
10.00	<p>Wash, 20 lks. wide, 2 ft. deep, drains SW.</p>										
15.10	<p>Fence cor. bears South, 25 lks. dist., fences bear N. and N. 89° E.</p>										
15.40	<p>Bladed road, bears SE. and NW.</p>										

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
20.09	Point for the E 1/16 sec. cor. of secs. 27 and 34, at proportionate dist., not monumented.
28.60	Bladed road, bears N. and S.
29.60	Enter dense timber, edge bears N. and S.
30.30	Fence, bears N. and S.
33.00	Madison Meadows Road, bears S. 20° E. and N. 20° W.
35.157	Point for the W-W-E 1/256 sec. cor. of secs. 27 and 34, at proportionate dist.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T9N R23E S27 W-W-E 1/256 S34 1967
40.18	The 1/4 sec. cor. of secs. 27 and 34, monumented by a weathered wooden post, 3 ft. long, 3 ins. diam., squared on one side, set in an old mound of stone.
	At the corner point
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T9N R23E S27 $\frac{1}{4}$ S34 1967
	from which
	A pine, 6 ins. diam., bears S. 35° W., 6 lks. dist., mkd. 1/4 S34 BT.
	A pine, 6 ins. diam., bears N. 40° W., 7 lks. dist., mkd. 1/4 S27 BT.
	Deposit the wooden post alongside the iron post.
	<hr style="width: 20%; margin: 0 auto;"/> S. 89°59' W., beginning new measurement.
12.00	Track road, bears N. and S.
13.30	Fence, bears N. and S.
15.00	Apache Railroad, bears N. 27° E. and S. 27° W.
15.30	Power line, parallels railroad.
15.60	Bladed road, bears N. 35° E. and S. 35° W.
36.40	Track road, bears SE. and NW.
40.17	The cor. of secs. 27, 28, 33 and 34.
	Land, gently rolling.
	Soil, rocky clay loam.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

Timber, pine, juniper and oak.
Undergrowth, bunch grass.

40.05

N. 2°30' W., bet. secs. 27 and 28.
Over gently rolling land, through dense timber.
Point for the ¼ sec. cor. of secs. 27 and 28 at proportionate dist.
Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
¼
S28 | S27
1967

from which

A pine, 8 ins. diam., bears N. 45° E., 28 lks. dist., mkd. ¼ S27 BT.

A pine, 6 ins. diam., bears N. 80° W., 39 lks. dist., mkd. ¼ S28 BT.

78.10

Draw, drains E.

80.11

The cor. of secs. 21, 22, 27 and 28, monumented by a basalt stone, 18 x 9 x 8 ins., firmly set in a mound of stone, no legible mks., from which an orig. bearing tree:

A dead pine, 27 ins. diam., bears S. 42° W., 30 lks. dist., mkd. T9NR23E S28 BT. (No record of this tree.)

At the corner point

Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
S21 | S22
S28 | S27
1967

from which

A pine, 7 ins. diam., bears S. 88¼° E., 9 lks. dist., mkd. T9NR23E S27 BT.

A pine, 4 ins. diam., bears S. 81 3/4° W., 8 lks. dist., mkd. T9NR23E S28 BT.

Deposit the orig. cor. stone alongside the iron post.

Land, rolling.
Soil, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

From the cor. of secs. 22, 23, 26 and 27.

N. 89°54' W., bet. secs. 22 and 27.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS							
	Over rolling land, through dense timber.						
	Desc. NW. slope of Pat Mullen Mountain.						
10.102	Point for the E-E 1/64 sec. cor. of secs. 22 and 27, at proportionate dist., not monumented.						
20.205	Point for the E 1/16 sec. cor. of secs. 22 and 27, at proportionate dist., not monumented.						
21.90	Bladed road, bears N. 40° E. and S. 40° W.; base of Pat Mullen Mountain; thence over gently rolling land.						
25.00	Fence, bears N. 30° E. and S. 30° W.						
28.20	Apache Railroad, on a curve, bears NE. and SW.						
28.90	Power line, bears N. 15° E. and S. 15° W.						
30.307	Point for the W-E 1/64 sec. cor. of secs. 22 and 27, at proportionate dist., not monumented.						
37.40	Fence, bears S. 2° E. and N. 2° W. This fence was built by the Forest Service.						
40.41	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; unable to find any remaining evidence of the orig. cor.						
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.						
	<p>T9N R23E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">1/4</td> <td style="text-align: center;">S22</td> </tr> <tr> <td style="border-top: 1px solid black; text-align: center;">1/4</td> <td style="text-align: center;">S27</td> </tr> <tr> <td></td> <td style="text-align: center;">1967</td> </tr> </table>	1/4	S22	1/4	S27		1967
1/4	S22						
1/4	S27						
	1967						
	from which						
	A pine, 10 ins. diam., bears S. 67° W., 11 lks. dist., mkd. 1/4 S27 BT.						
	A pine, 8 ins. diam., bears N. 25° W., 7 lks. dist., mkd. 1/4 S22 BT.						
	A local survey cor. bears S. 88°07' E., 299.6 lks. dist., monumented by a pipe, 2 ins. diam., brass cap mkd. T9NR23E 22/27 SECO 4128. The plat of the Sky-Hi-Retreat, which is recorded in volume 5 of Plats, Page 47, Records of Navajo County, Arizona, indicates a rock and bearing tree were found at this point. (Record: a post 3 ft. long, 3 ins. diam., with mkd. stone 12 ins. in the ground, pits E. and W. and mound of earth around post.) No evidence of a mkd. rock, a post or a bearing tree was found near the local cor.						
73.30	Wash, 20 lks. wide, 2 ft. deep, drains N.						
80.82	The cor. of secs. 21, 22, 27 and 28.						
	Land, rolling.						
	Soil, rocky, clay loam.						
	Timber, pine, juniper and oak.						
	Undergrowth, bunch grass and scrub oak.						

CHAINS

N. 0°06' W., bet. secs. 21 and 22.
 Over rolling land, through dense timber.

4.40 Desc. over N. slope.

16.60 Draw, drains E., asc. S. slope.

34.50 Top of hill; desc. N. slope.

40.23 The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented by a lava stone, 15 x 10 x 8 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, mound of stone W., from which an orig. bearing tree:
 An oak, 10 ins. diam., bears S. 87° E., 77 lks. dist., mkd $\frac{1}{4}$ S.
 At the corner point
 Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
 T9N R23E
 $\frac{1}{4}$
 S21 | S22
 1967
 from which
 A pine, 5 ins. diam., bears S. 72° W., 31 lks. dist., mkd. T9NR23E $\frac{1}{4}$ S21 BT.
 Deposit the orig. cor. stone alongside the iron post.

 N. 0°30' W., beginning new measurement.

34.30 Fence, bears E. and W.

37.40 Fence, bears N. 40° E. and S. 40° W.; enter open field.

41.94 The cor. of secs. 15, 16, 21 and 22, monumented by a lava stone, 18 x 13 x 9 ins., firmly set in a mound of stone, no legible mks. I accepted this as the best remaining evidence of the orig. cor.
 At the corner point
 Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
 T9N R23E
 S16 | S15
 S21 | S22
 1967
 from which
 A pine, 8 ins. diam., bears N. 60° E., 20 lks. dist., mkd. T9NR23E S15 BT.
 Deposit the orig. cor. stone alongside the iron post.
 The cor. is located on the N. edge of the open field.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23. N. 89°57' W., bet. secs. 15 and 22. Over gently rolling land, through dense timber.</p>
20.18	Point for the E 1/16 sec. cor. of secs. 15 and 22, at proportionate dist., not monumented. A local cor. bears West, 2 lks. dist.
29.00	Old logging road, bears N. and SE.
31.50	Apache Railroad, bears N. and S.
34.00	Fence bears S. 10° E. and N. 10° W.
34.70	Wash, 45 lks. wide, 1 ft. deep, drains NW.
40.36	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented by a basalt stone, 16 x 12 x 7 ins., firmly set, mkd. 1/4 on N. face, mound of stone alongside.</p> <p>At the corner point</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E 1/4 S15 S22 1967</p> <p>from which</p> <p>A USC&GS bench mark, bears S. 84°05' E., 7.24 chs. dist., monumented by a brass tablet, 3 ins. diam., cemented to a boulder, mkd. H46 1934.</p> <p>A fence cor. bears North, 167 lks. dist., fences bear E., S. and W.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87°34' W., beginning new measurement.</p>
.01	Fence, bears N. and S.
34.50	Fence, bears N. and S.
36.80	Enter open field, edge bears N., and S.
37.20	Fence, bears N. 40° E. and S. 40° W.
40.52	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, gently rolling. Soil, rocky, clay loam.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
	<p>N. 0°07' E., bet. secs. 15 and 16. Over gently rolling land, through dense timber.</p>
1.05	Fence, bears E. and W.
3.60	Fence, bears E. and W.
25.30	Morgan Wash, 30 lks. wide, 2 ft. deep, drains N. 35° W.
38.54	Fence, bears W. and E. for 27 lks. to cor. of fences bearing S. 35° E., N. 25° W. and West.
38.64	<p>The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, as determined from the remains of an orig. bearing tree:</p> <p style="padding-left: 40px;">A pine stump, bears N. 10° W., 102 lks. dist., mkd. $\frac{1}{4}$ S BT.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E</p> <p>$\frac{1}{4}$</p> <p>S16 S15</p> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 39$\frac{1}{2}$° W., 39 lks. dist., mkd. $\frac{1}{4}$ S16 BT.</p> <p style="padding-left: 40px;">A fence cor. post, 10 ins. diam., bears S. 70$\frac{1}{4}$° E., 27 lks. dist., mkd. $\frac{1}{4}$ S15 B0.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°15' W., beginning new measurement.</p>
.60	Fence, bears S. 25° E. and N. 25° W.
6.60	Same fence, bears N. 25° E. and S. 25° W.
40.33	<p>The cor. of secs. 9, 10, 15 and 16, monumented by a rebar $\frac{1}{4}$ in. diam., firmly set in an old mound of stone, from which the remains of the orig. bearing trees:</p> <p style="padding-left: 40px;">A pine stump, bears S. 60° E., 159 lks. dist. (Record, S. 63° E., 151 lks. dist.).</p> <p style="padding-left: 40px;">A stump hole, bears S. 38° W., 69 lks. dist. (Record, S. 34° W.).</p> <p style="padding-left: 40px;">A pine stump, bears N. 42° W., 77 lks. dist. (Record, N. 44° W.).</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	<p style="text-align: center;">T9N R23E <u>S 9 S10</u> <u>S16 S15</u> 1967</p> <p>from which</p> <p>A pine, 8 ins. diam., bears N. 66° E., 104 lks. dist., mkd. T9NR23E S10 BT.</p> <p>A pine, 7 ins. diam., bears S. 45° E., 54 lks. dist., mkd. T9NR23E S15 BT.</p> <p>Set a wooden post, 4 ft. long, 4 ins. diam., and reset the rebar alongside the iron post.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°41' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land, through dense timber.</p> <p>35.20 Drainage ditch, 50 lks. wide, 4 ft. deep, drains N. 20° W.</p> <p>36.40 Old logging road, bears SE. and NW.</p> <p>40.17 The 1/4 sec. cor. of secs. 10 and 15, monumented by an old mound of stone, from which an orig. bearing tree:</p> <p style="padding-left: 40px;">A dead pine, 25 ins. diam., bears N. 10° E., 105 lks. dist., mkd. BT.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>	
	<p style="text-align: center;">T9N R23E <u>1/4 S10</u> S15 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 38° E., 11 lks. dist., mkd. 1/4 S10 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°10' W., beginning new measurement.</p> <p>9.70 Apache Railroad, bears S. 10° E. and N. 10° W.</p> <p>10.50 Track road, bears S. 10° E. and N. 10° W.</p> <p>10.675 Point for the E-W 1/64 sec. cor. of secs. 10 and 15, at proportionate dist., not monumented.</p> <p>21.35 Point for the W 1/16 sec. cor. of secs. 10 and 15, at proportionate dist., not monumented.</p>	

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
41.40	Fence, bears N. and S.
42.70	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
10.10	<p>N. 0°23' E., bet. secs. 9 and 10.</p> <p>Over gently rolling land, through moderate timber.</p> <p>Point for the S-S 1/64 sec. cor. of secs. 9 and 10, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E S-S 1/64 S 9 S10 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 31° E., 130 lks. dist., mkd. SS 1/64 S10 BT.</p> <p style="padding-left: 40px;">Fence cor., bears S. 46° E., 106 lks. dist., fences bear E. and S.</p> <p>Raise a mound of stone W. of the cor.</p>
20.20	Point for the S 1/16 sec. cor. of secs. 9 and 10, at proportionate dist., not monumented.
24.40	Track road, bears N. 60° E. and S. 60° W.
36.00	Enter open meadow, edge bears irregularly NW. and SE.
40.40	<p>The 1/4 sec. cor. of secs. 9 and 10, marked by a local cor., a water pipe, 1 in. diam., firmly set alongside a cor. of fences bearing N. and W. This is accepted as best available evidence of the orig. cor. position.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°48' E., beginning new measurement.</p> <p>Along a fence bearing N.</p>
10.00	A fence cor. bears West 14 lks. dist., fences bear S. and W.
20.17	Point for the N 1/16 sec. cor. of secs. 9 and 10, at proportionate dist, not monumented.
29.80	Fence cor., fences bear N. and W.
40.34	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a basalt stone, 16 x 9 x 5 ins., loosely set alongside a fence cor., fences bear S. and E., mkd. 5 notches on S. and 3 notches on E. faces. A local cor., a water pipe, 1 in. diam., is set alongside the orig. cor.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS							
	<p>Land, nearly level. Soil, rocky, clay loam. Timber, pine and juniper in S $\frac{1}{2}$. Undergrowth, bunch grass.</p>						
	<p>From the cor. of secs. 2, 3, 10 and 11. S. 88°57' W., bet. secs. 3 and 10. Over nearly level land, through dense timber, along the S. side of a fence bearing E. and W.</p>						
6.20	Fence cor., fences bear NE. and E.						
6.90	Apache Railroad, on a curve, bears N. 10° E. and SW.						
7.70	Fence cor., fences bear NE. and W.						
10.485	<p>Point for the E-E 1/64 sec. cor. of secs. 3 and 10, at proportionate dist. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <table> <tr> <td></td> <td>T9N R23E</td> </tr> <tr> <td>E-E $\frac{1}{64}$</td> <td>$\frac{S 3}{S10}$</td> </tr> <tr> <td></td> <td>1967</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 23 ins. diam., bears South, 23 lks. dist., mkd. T9NR23E EE 1/64 S10 BT.</p> <p style="padding-left: 40px;">NE. cor. of a corral at Sponseller Siding, bears S. 16° 40' W., 6.88 chs. dist.</p> <p>The cor. is located alongside a fence cor. of fences bearing N., E. and W.</p>		T9N R23E	E-E $\frac{1}{64}$	$\frac{S 3}{S10}$		1967
	T9N R23E						
E-E $\frac{1}{64}$	$\frac{S 3}{S10}$						
	1967						
12.50	Fence cor., fences bear E., S. and W.						
12.80	Fence cor., fences bear N. and E.						
17.00	Top of ridge, bears E. and W.						
20.97	Point for the E 1/16 sec. cor. of secs. 3 and 10, at proportionate dist., not monumented.						
29.60	Graded road, bears SE. and NW.						
32.70	Track road, bears N. 15° E. and S. 15° W.						
35.40	Draw, drains N. 10° E.						
39.70	Drainage ditch, 5 lks. wide, 1 ft. deep, drains SE.						
41.94	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate dist.; unable to find any remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>						

CHAINS

T9N R23E
 $\frac{1}{4}$ $\frac{S}{S10}$ $\frac{3}{1967}$

from which

A pine, 5 ins. diam., bears N. 25° E., 30 lks.
 dist., mkd. $\frac{1}{4}$ S3 BT.

A pine, 10 ins. diam., bears S. 61 $\frac{1}{4}$ ° W., 17 lks.
 dist., mkd. $\frac{1}{4}$ S10 BT.

46.60 Track road, bears S. 30° E. and N. 30° W.

52.425 Point for the E-W 1/64 sec. cor. of secs. 3 and 10, at proportionate dist.

Set the iron post 18 ins. in the ground, brass cap mkd.

T9N R23E
 E-W $\frac{1}{64}$ $\frac{S}{S10}$ $\frac{3}{1967}$

from which

A fence cor., bears S. 30 3/4° W., 151 lks.
 dist., fences bear S. and W.

Raise a mound of stone N. of the cor.

56.70 Leave dense timber; enter widely scattered timber.

62.91 Point for the W 1/16 sec. cor. of secs. 3 and 10, at proportionate dist.

Set the iron post 18 ins. in the ground, brass cap mkd.

T9N R23E
 W $\frac{1}{16}$ $\frac{S}{S10}$ $\frac{3}{1967}$

Raise a mound of stone N. of the cor.

63.27 Fence, bears N. and S.

83.88 The cor. of secs. 3, 4, 9 and 10.

Land, gently rolling.
 Soil, rocky, clay loam.
 Timber, pine, juniper and oak.
 Undergrowth, bunch grass.

N. 0°39' E., bet. secs. 3 and 4.

Over nearly level land.

9.30 Diversion ditch, 10 lks. wide, 1 ft. deep, drains NW.

17.90 Track road, bears S. 70° E. and N. 70° W.

19.40 Power line, bears E. and W.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS		
20.405	Point for the S 1/16 sec. cor. of secs. 3 and 4, at proportionate dist., not monumented.	
20.50	Fence, bears E. and W.; enter open field, bears E. and W.	
30.607	Point for the N-S 1/64 sec. cor. of secs. 3 and 4, at proportionate dist., not monumented.	
40.81	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E 1/4 S 4 S 3 1967</p> <p>Set a wooden post, 4 ft. long, 4 ins. diam., alongside the iron post.</p>	
44.80	Enter dense timber, edge bears SE. and NW., begin asc. S. slope.	
48.90	Fence, bears SE. and NW.	
49.50	Bladed road, bears SE. and NW.	
51.012	<p>Point for the S-N 1/64 sec. cor. of secs. 3 and 4, at proportionate dist.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E S-N 1/64 S 4 S 3 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 21° E., 10 lks. dist., mkd. SN 1/64 S3 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 29 1/4° W., 42 lks. dist., mkd. X BT.</p>	
61.215	Point for the N 1/16 sec. cor. of secs. 3 and 4, at proportionate dist., not monumented.	
81.91	<p>The cor. of secs. 3 and 4, only, on the N. bdy. of the Tp.</p> <p>Land, nearly level to rolling. Soil, rocky, clay loam. Timber, pine and juniper in N. 1/2. Undergrowth, bunch grass.</p>	
<p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0°43' E., bet. secs. 32 and 33.</p> <p>Over gently rolling land, through dense timber, along the E. side of a fence bearing N. and S.</p>		

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

- 10.177 The S-S 1/64 sec. cor. of secs. 32 and 33, identical to Cor. No. 4 of HES 209, monumented by a basalt rock in place, 24 x 18 x 8 ins. above the ground, mkd. with an X on top and HES 209 on S. face.

Cor. is located 2 lks. East of a fence bearing N. and S.

N. 0°55' E., beginning new measurement.
- 1.20 Fence bears irregularly NE. and SW.
- 8.20 Power line, bears S. 47°45' E. and N. 47°45' W.
- 9.00 Power line, bears S. 47°45' E. and N. 47°45' W.
- 10.177 The S 1/16 sec. cor. of secs. 32 and 33, monumented by a 3/4 ins. steel bar, firmly set in an old mound of stone, from which the local bearing trees:

A pine, 12 ins. diam., bears S. 14° E., 20 lks. dist., mkd. with visible scribes in a partially healed blaze.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T9N R23E
S1/16
S32|S33
1967

from which

A pine, 10 ins. diam., bears N. 9½° E., 117 lks. dist., mkd. S 1/16 S33 BT.

A pine, 8 ins. diam., bears N. 34½° W., 62 lks. dist., mkd. S 1/16 S32 BT.

Bury the steel bar alongside the iron post.

Raise a mound of stone W. of the cor.

N. 0°33' E., beginning new measurement.
- 9.30 Begin desc. into Thompson Creek, bears E. and W.
- 12.00 Thompson Creek, course W.; asc. S. slope.
- 16.70 Top of ascent, continue over rolling land.
- 20.30 The ¼ sec. cor. of secs. 32 and 33, monumented by a basalt stone, 24 x 20 x 20 ins., firmly set mkd. ¼ on W. face, mound of stone E., from which the orig. bearing trees:

A pine, 25 ins. diam., bears N. 19½° E., 51 lks. dist., mkd. ¼ S. (Record bearing N. 15°28' E.)

A pine, 25 ins. diam., bears S. 74° E., 49 lks. dist., mkd. ¼ S. (Record bearing S. 67°47' E.)

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>At the corner point</p>
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T9N R23E</p>
	<p style="text-align: center;"> $\frac{1}{4}$</p>
	<p style="text-align: center;">S32 S33</p>
	<p style="text-align: center;">1967</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 82° W., 19 lks. dist., mkd. $\frac{1}{4}$ S32 BT.</p>
	<p>Deposit the orig. cor. stone along side the iron post.</p>
	<p style="text-align: center;">—————</p>
	<p>N. 0°43' E., beginning new measurement.</p>
16.30	<p>Bladed road, bears E. and W.</p>
40.63	<p>The cor. of secs. 28, 29, 32 and 33, monumented by a basalt stone, 17 x 16 x 10 ins., firmly set in a mound of stone, mkd. 1 notch on S. and 4 notches on E. faces, from which the remains of the orig. bearing trees:</p>
	<p style="padding-left: 40px;">A dead oak, 10 ins. diam., bears N. 31 3/4° E., 29 lks. dist., mkd. with a rotted blaze. (Record: N. 28° E., 31 lks. dist.)</p>
	<p style="padding-left: 40px;">An oak stump, bears S. 34 1/2° E., 35 lks. dist., mkd. with an old blaze. (Record: S. 28° E., 33 lks. dist.)</p>
	<p style="padding-left: 40px;">An oak, 12 ins. diam., bears S. 41 1/2° W., 35 lks. dist., mkd. with a healed blaze. (Record: S. 49° W., 33 lks. dist.)</p>
	<p style="padding-left: 40px;">A juniper, 45 ins. diam., bears N. 60 1/4° W., 23 lks. dist., mkd. T9NR23E S29 BT. (Record: N. 54° W., 56 lks. dist.)</p>
	<p>At the corner point</p>
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T9N R23E</p>
	<p style="text-align: center;">S29 S28</p>
	<p style="text-align: center;">S32 S33</p>
	<p style="text-align: center;">1967</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 42 1/2° E., 110 lks. dist., mkd. T9NR23E S28 BT.</p>
	<p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 67° E., 77 lks. dist., mkd. T9NR23E S33 BT.</p>
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 80 1/2° W., 25 lks. dist., mkd. T9NR23E S32 BT.</p>
	<p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 66 3/4° W., 46 lks. dist., mkd. T9NR23E S29 BT.</p>
	<p>Deposit the orig. cor. stone alongside the iron post.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
40.72	<p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34. S. 89°50' W., bet. secs. 28 and 33. Over gently rolling land, through moderate timber.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented by a basalt stone, 15 x 10 x 4 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face.</p> <p>At the corner point Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E $\frac{1}{4}$ $\frac{S28}{S33}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 32° E., 30 lks. dist., mkd. $\frac{1}{4}$ S33 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 60° W., 12 lks. dist., mkd. $\frac{1}{4}$ S28 BT.</p> <p>Bury the orig. cor. stone alongside the iron post. Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°58' W., beginning new measurement.</p>
9.30	Rocky wash, 25 lks. wide, 1 ft. deep, drains S.
40.68	<p>The cor. of secs. 28, 29, 32 and 33.</p> <p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
40.06	<p>N. 1°30' W., bet. secs. 28 and 29. Over rolling land, through dense timber. Asc. S. slope.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E $\frac{1}{4}$ S29 S28 1967</p>

Dep, Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS										
	<p>from which</p> <p>A pine, 20 ins. diam., bears N. 85½° E., 81 lks. dist., mkd. ¼ S28 BT.</p> <p>A pine, 23 ins. diam., bears N. 81 3/4° W., 26 lks. dist., mkd. ¼ S29 BT.</p>									
58.40	Slope changes to W.									
71.20	Slope changes to NE.									
80.12	<p>The cor. of secs. 20, 21, 28 and 29, monumented by a basalt stone, 15 x 8 x 6 ins., firmly set, mkd. 2 notches on S. and 4 notches on E. face, from which the remains of the orig. bearing trees:</p> <p>A dead pine, 20 ins. diam., bears S. 60° E., 68 lks. dist., mkd. T9NR23E S28 BT.</p> <p>A dead pine, 30 ins. diam., bears S. 49° W., 9 lks. dist., mkd. T9N R23E S29 BT.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2" style="text-align: center;">T9N R23E</td> </tr> <tr> <td style="text-align: center;">S20</td> <td style="text-align: center;">S21</td> </tr> <tr> <td style="text-align: center;">S29</td> <td style="text-align: center;">S28</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table> <p>from which</p> <p>A pine, 10 ins. diam., bears N. 44½° E., 50 lks. dist., mkd. T9NR23E S21 BT.</p> <p>A pine, 12 ins. diam., bears S. 32½° E., 74 lks. dist., mkd. T9NR23E S28 BT.</p> <p>A pine, 12 ins. diam., bears S. 4½° W., 53 lks. dist., mkd. T9NR23E S29 BT.</p> <p>A pine, 14 ins. diam., bears N. 9° W., 29 lks. dist., mkd. T9NR23E S20 BT.</p> <p>A concrete wild life reservoir, bears S. 8° W., 13.10 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	T9N R23E		S20	S21	S29	S28	1967		
T9N R23E										
S20	S21									
S29	S28									
1967										
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°58' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through dense timber.</p> <p>Asc. E. slope.</p>									

CHAINS

40.10

The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented by a basalt stone, 8 x 8 x 8 ins., firmly set, mkd. $\frac{1}{4}$ on top, mound of stone W., from which the orig. bearing trees:

An oak, 9 ins. diam., bears S. 27° W., 68 lks. dist., mkd. with a healed blaze. (Record bearing S. 22° W.)

An oak, 8 ins. diam., bears N. 20° W., 34 lks. dist., mkd. with a healed blaze. (Record bearing N. 22° W.)

At the corner point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
 $\frac{1}{4}$ $\frac{S21}{S28}$
1967

from which

A pine, 27 ins. diam., bears N. 65° W., 48 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

A pine, 8 ins. diam., bears S. 1° E., 59 lks. dist., mkd. $\frac{1}{4}$ S28 BT.

U.S.G.S. triangulation station, "Blue Ridge" bears S. 75°11' W., 17.15 chs. dist., monumented by a standard bronze tablet, set in cement in a rock, mkd. Elev. Bench Mk.

Deposit the orig. cor. stone alongside the iron post.

S. 89°51' W., beginning new measurement.

14.70

Top of ascent on N. slope of Blue Ridge Mountain; desc. NW. slope.

27.30

Small ravine, drains N.; asc. NE. slope.

39.94

The cor. of secs. 20, 21, 28 and 29.

Land, rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

40.19

N. 0°33' W., bet. secs. 20 and 21.

Over rolling land, through dense timber.

Desc. N. slope.

Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

T9N R23E
 $\frac{1}{4}$
 S20|S21
 1967

from which

A pine, 10 ins. diam., bears S. $55\frac{1}{4}^\circ$ E., 34 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

A pine, 7 ins. diam., bears N. 88° W., 61 lks. dist., mkd. $\frac{1}{4}$ S20 BT.

80.38

The cor. of secs. 16, 17, 20 and 21, monumented by a basalt stone, 17 x 10 x 8 ins., firmly set in a mound of stone, mkd. 3 notches on S. and 4 notches on E. faces, from which the orig. bearing trees:

A pine, 20 ins. diam., bears N. 20° E., 90 lks. dist., illegible mks. (Record dist. 50 lks.)

A dead pine, 22 ins. diam., bears S. 70° W., 37 lks. dist., mkd. 20. (Record bearing S. 78° W.)

A pine, 28 ins. diam., bears N. 76° W., 115 lks. dist., mkd. 17. (Record bearing N. 71° W.)

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T9N R23E
S17|S16
 S20|S21
 1967

from which

A pine, 9 ins. diam., bears N. 64° E., 73 lks. dist., mkd. T9NR23E S16 BT.

A pine, 13 ins. diam., bears S. 40° E., 49 lks. dist., mkd. T9NR23E S21 BT.

A pine, 6 ins. diam., bears S. 32° W., 24 lks. dist., mkd. T9NR23E S20 BT.

A pine, 9 ins. diam., bears N. 48° W., 13 lks. dist., mkd. T9NR23E S17 BT.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

Land, rolling.
 Soil, rocky, clay loam.
 Timber, pine, juniper and oak.
 Undergrowth, bunch grass.

From the cor. of secs. 15, 16, 21 and 22.

S. $87^\circ 28'$ W., bet. secs. 16 and 21.

Over gently rolling land, through scattered timber.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
29.70	Fences bear N. 84° E. and S. 84° W.
32.40	Fence, bears N. and S.
40.11	<p>The ¼ sec. cor. of secs. 16 and 21, monumented by a basalt stone, 15 x 12 x 6 ins., firmly set in a mound of stone, no legible mks., from which the orig. bearing tree:</p> <p style="padding-left: 40px;">A pine, 27 ins. diam., bears S. 40° E., 78 lks. dist., mkd. with a healed blaze. This blaze was opened to reveal mks. BT.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E</p> <p>¼ $\frac{S16}{S21}$</p> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 7° E., 29 lks. dist., mkd. ¼ S21 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 44° W., 57 lks. dist., mkd. ¼ S16 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°39' W., beginning new measurement.</p> <p>Asc. NE. slope.</p>
38.60	Spur, slopes N.; desc. NW. slope.
40.29	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
40.13	<p>N. 0°24' W., bet. secs. 16 and 17.</p> <p>Over gently rolling NW. slope, through dense timber.</p> <p>The ¼ sec. cor. of secs. 16 and 17, monumented by a basalt stone, 12 x 10 x 4 ins., loosely set, mkd. ¼ on top.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E</p> <p>¼ $\frac{S17}{S16}$</p> <p>1967</p> </div>

CHAINS						
	<p>from which</p> <p>A pine, 10 ins. diam., bears N. 69° E., 32 lks. dist., mkd. $\frac{1}{4}$ S16 BT.</p> <p>A pine, 12 ins. diam., bears N. 55° W., 21 lks. dist., mkd. $\frac{1}{4}$ S17 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr/> <p>N. 0°32' W., beginning new measurement.</p>					
20.10	Point for the N 1/16 sec. cor. of secs. 16 and 17, at proportionate dist., not monumented.					
29.00	Bottom of ravine, drains W.; asc. S. slope.					
38.20	Top of ascent, continue over gently rolling land.					
40.20	<p>The cor. of secs. 8, 9, 16 and 17, monumented by a basalt stone, 18 x 10 x 10 ins., firmly set, mkd. 4 notches on S. and 4 notches on E. faces, mound of stone W., from which the remains of the orig. bearing trees:</p> <p>A pine stump, bears N. 73° E., 84 lks. dist., no legible mks.</p> <p>A pine, 40 ins. diam., bears S. 20$\frac{1}{4}$° W., 122 lks. dist., illegible mks. (Record: S. 29° W., 120 lks.)</p> <p>A pine stump, bears N. 15° W., 32 lks. dist., no legible mks.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E</p> <table border="1" style="margin: auto;"> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td>S17</td> <td>S16</td> </tr> </table> <p>1967</p> </div> <p>from which</p> <p>A pine, 6 ins. diam., bears S. 65° E., 29 lks. dist., mkd. T9NR23E S16 BT.</p> <p>A pine, 6 ins. diam., bears S. 13$\frac{1}{4}$° W., 22 lks. dist., mkd. T9NR23E S17 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>The cor. is located under a fence bearing E. and W.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	S 8	S 9	S17	S16	
S 8	S 9					
S17	S16					
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°33' W., bet. secs. 9 and 16.</p>					

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	Over gently rolling land, through dense timber.
18.50	Morgan Wash, 150 lks. wide, 5 ft. deep, drains N. 30° W.
20.28	Point for the E 1/16 sec. cor. of secs. 9 and 16, at proportionate dist.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T9N R23E E $\frac{1}{16}$ S $\frac{9}{16}$ S16 1967</p>
	from which
	A pine, 18 ins. diam., bears S. 30° W., 96 lks. dist., mkd. E 1/16 S16 BT.
	Fence cor. bears S. 78° W., 71 lks. dist., fences bear S. and W.
40.56	The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented by a basalt stone, 12 x 8 x 4 ins., firmly set, mkd. $\frac{1}{4}$ on N. face, from which the remains of an orig. bearing tree:
	A pine stump, bears N. 51° W., 50 lks. dist., no legible mks.
	At the corner point
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ S $\frac{9}{16}$ S16 1967</p>
	from which
	A pine, 9 ins. diam., bears S. 60° W., 70 lks. dist., mkd. $\frac{1}{4}$ S16 BT.
	Deposit the orig. cor. stone alongside the iron post.
	The cor. is located alongside a fence cor. of fences bearing N., E. and S. 30° W.
	<hr style="width: 20%; margin: auto;"/> S. 89°31' W., beginning new measurement.
1.50	Morgan Wash, 30 lks. wide, 3 ft. deep, drains SW.
14.90	Fence, bears N. and S.
25.30	Morgan Wash, 100 lks. wide, 3 ft. deep, drains N. 70° W.
28.40	Fence cor., bears South, 30 lks. dist., fences bear S. 70° E. and N. 88° W.
40.29	The cor. of secs. 8, 9, 16 and 17.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>N. 0°43' W., bet. secs. 8 and 9. Over gently rolling land, through dense timber.</p>
6.80	S. edge of Morgan Wash, bears S. 70° E. and N. 70° W.
7.80	Morgan Wash, 430 lks. wide, 20 ft. deep, drains N. 70° W.
11.10	N. edge of Morgan Wash, bears S. 70° E. and N. 70° W.
16.00	Track road, bears E. and W.
20.24	Point for the S 1/16 sec. cor. of secs. 8 and 9, at proportionate dist., not monumented.
22.90	Fence cor., bears East, 42 lks. dist., fences bear N. and E.; enter open field.
24.10	Track road, bears E. and W.
40.48	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented by a basalt stone, 20 x 12 x 6 ins., loosely set, mkd. 1/4 on top, a local cor., a water pipe, 1 in. diam., projecting 2 ins. above the ground is set alongside, from which the remains of the orig. bearing trees:</p> <p style="padding-left: 40px;">A stump hole, bears S. 23° E., 118 lks. dist.</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears N. 75° W., 95 lks. dist., mkd. 1/4 S.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T9N R23E 1/4 S 8 S 9 1967</p> <p>Bury the orig. cor. stone and local cor. pipe alongside the iron post.</p> <p>The cor. is located 12 lks. East of a fence bearing N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°11' W., beginning new measurement.</p>
20.38	<p>Point for the N 1/16 sec. cor. of secs. 8 and 9, at proportionate dist.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E N1/16 S 8 S 9 1967</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

from which

A pine, 7 ins. diam., bears N. 65° W., 135 lks. dist., mkd. N 1/16 S8 BT.

A fence, cor., bears N. 18°35' W., 217 lks. dist., fences bear N., E. and W.

22.40 Fence, bears E. and W.

25.30 Power line, bears S. 75° E. and N. 75° W.

30.57 The N-N 1/64 sec. cor. of secs. 8 and 9, at proportionate dist., monumented by a local cor., a water pipe, 3/4 in. diam., set in a mound of stone.

At the corner point

Set the iron post over an X chiseled in solid rock, mound of stone to top, brass cap mkd.

T9N R23E
N-N 1/64
S 8 | S 9
1967

Deposit the local cor. inside the iron post.

37.60 Bladed road, bears E.

37.90 Wood rail fence, bears E. and W.

40.76 The cor. of secs. 4, 5, 8 and 9, monumented by an iron pipe, 1 1/2 in. diam., firmly set in a collar of stone, verified from the remains of the orig. bearing tree:

A stump hole, bears N. 82° W., 137 lks. dist., found a large spike in the center of the hole. (Record bearing N. 92° W.) A fallen pine, alongside the stump hole, is mkd. with illegible scribe mks. in an open blaze.

At the corner point

Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
S 5 | S 4
S 8 | S 9
1967

from which

A pine, 7 ins. diam., bears N. 20° E., 16 lks. dist., mkd. T9NR23E S4 BT.

A pine, 10 ins. diam., bears S. 65° W., 20 lks. dist., mkd. T9NR23E S8 BT.

A pine, 10 ins. diam., bears N. 45° W., 30 lks. dist., mkd. T9NR23E S5 BT.

Deposit the iron pipe alongside the iron post.

Raise a mound of stone W. of the cor.

BOOK 4867

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS		
	<p>Cor. is located 3 lks. E. of a fence cor., fences bear N., S. and E.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grasss and scrub oak.</p>	
10.37	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°54' W., bet. secs. 4 and 9.</p> <p>Over nearly level land, through widely scattered timber.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 4 and 9, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T9N R23E} \\ \text{E-E } \frac{1}{64} \frac{\text{S } 4}{\text{S } 9} \\ \text{1067} \end{array}$ <p>Raise a mound of stone N. of the cor.</p>	
20.74	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9, at proportionate dist., not monumented.</p>	
31.11	<p>Point for the W-E 1/64 sec. cor. of secs. 4 and 9, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T9N R23E} \\ \text{W-E } \frac{1}{64} \frac{\text{S } 4}{\text{S } 9} \\ \text{1967} \end{array}$ <p>from which</p> <p>A fence cor., bears West, 30 lks. dist., fences bear N. 20° E. and W.</p> <p>Raise a mound of stone N. of the cor.</p>	
31.41	<p>Fence cor., fences bear W. and N. 20° E.</p>	
41.48	<p>The 1/4 sec. cor. of secs. 4 and 9, monumented by a water pipe, 1 in. diam., projecting 4 ins. above the ground, alongside a fence cor. of fences bearing E. and S. This was accepted as the best available evidence of the cor. position.</p>	
	<p>S. 89°56' W., beginning new measurement.</p> <p>Enter dense timber.</p>	
3.60	<p>Park Drive, a graded road, bears N. and S.</p>	
3.75	<p>Water line, bears N., S. and W.</p>	
4.90	<p>Power line, bears N. 60° E. and S. 60° W.</p>	

Dep. Resurvey, Subdivision T. 9 N., R. 23 E.

CHAINS	
10.20	Water line, bears E., S. and W.
16.40	Water line, bears N., E. and S.
17.40	Deer Run Road, a graded road, bears N. and S.
20.75	Point for the W 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T9N R23E W $\frac{1}{16}$ S $\frac{4}{9}$ 1 6 S 9 1967</p>
	from which
	<p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 57° W., 30 lks. dist., mkd. W 1/16 S4 BT.</p>
34.40	Track road, bears S. 30° E. and N. 30° W.
41.50	The cor. of secs. 4, 5, 8 and 9.
	<p>Land, nearly level. Soil, rocky, clay loam. Timber, pine and juniper. Undergrowth, bunch grass and scrub oak.</p>
	N. 0°05' W., bet. secs. 4 and 5.
	Over gently rolling land, through dense timber; along E. side of fence bearing irregularly N.
9.80	Enter open field, edge bears E. and W.
9.985	Point for the S-S 1/64 sec. cor. of secs. 4 and 5, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T9N R23E S-S 1/64 S 5 S 4 1967</p>
	from which
	<p style="padding-left: 40px;">A juniper, 7 ins. diam., bears S. 14° E., 22 lks. dist., mkd. SS 1/64 S4 BT.</p>
	<p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 73° W., 32 lks. dist., mkd. SS 1/64 S5 BT.</p>
	Raise a mound of stone W. of cor.
13.47	The NE. cor. of a frame cabin, 22 x 16 ft., bears West, 23 lks. dist.
14.01	The SW. cor. of a frame building, 44 x 32 ft., bears East, 65 lks. dist.
14.44	The SE. cor. of a frame building, 20 x 40 ft., bears West, 35 lks. dist.

Dep, Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
14.89	The S. side of a frame building, 16 x 32 ft., 8 lks. E. of SW. cor.
15.19	The N. side of same building, 8 lks. E. of the NW. cor.
17.37	The S. side of a frame building, 32 x 16 ft., 13 lks. W. of the SE. cor.
17.61	The N. side of same building, 13 lks. E. of the NE. cor.
18.72	The NW. cor. of a frame building, 32 x 16 ft., bears West, 10 lks. dist.
19.97	Point for the S 1/16 sec. cor. of secs. 4 and 5, at proportionate dist., not monumented.
19.99	The NE. cor. of a frame building, 32 x 17 ft., bears West, 12 lks. dist.
24.10	Fence cor., bears West, 74 lks. dist., fences bear E. and S.; enter timber; asc. S. slope.
24.90	Track road, bears E. and SW.
24.963	Point for the S-N-S 1/256 sec. cor. of secs. 4 and 5, at proportionate dist.
	Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.
	<p>T9N R23E S-N-S 1/256 S 5 S 4 1967</p>
	from which
	A pine, 22 ins. diam., bears N. 80° E., 161 lks. dist., mkd. S-N-S 1/256 S4 BT.
	A pine, 8 ins. diam., bears S. 86° W., 43 lks. dist., mkd. S-N-S 1/256 S5 BT.
	A USC&GS Bench Mark, bears S. 77° 51' W., 9.96 chs. dist., monumented by a brass tablet, 3 ins. diam., set in a concrete block, mkd. N141 1935.
	Set a wooden post 6 ft. long, 4 ins. diam., alongside the iron post.
29.60	Gravelled road, bears S. 70° E. and N. 70° W.
39.94	The 1/4 sec. cor. of secs. 4 and 5, monumented by a sandstone, 18 x 10 x 8 ins., firmly set in a mound of stone, mkd. 1/4 on W. face, from which old bearing trees:
	A dead oak, 9 ins. diam., bears S. 79° E., 11 lks. dist., mkd. with a healed blaze. (No record)
	A juniper, 35 ins. diam., bears N. 65 1/2° W., 10 lks. dist., mkd. 1/4. (No record)
	At the corner point
	Set the iron post 20 ins. in the ground, brass cap mkd.

BOOK 4867

79

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ S 5 S 4 1967</p> <p>from which</p> <p>A pine, 18 ins. diam., bears S. $63\frac{1}{4}^{\circ}$ E., 72 lks. dist., mkd. $\frac{1}{4}$ S4 BT.</p> <p>A pine, 12 ins. diam., bears S. $11\frac{1}{2}^{\circ}$ W., 51 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p> <p>Raise a mound of stone W. of the cor. and deposit the orig. cor. stone in the mound.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. $4^{\circ}04'$ E., beginning new measurement.</p> <p>.40 Spur, slopes W.; desc. NW. slope.</p> <p>6.10 Ravine, drains W.; asc. SW. slope.</p> <p>16.80 Spur, slopes W.; desc. NW. slope.</p> <p>33.30 Ravine, drains W.; asc. SW. slope.</p> <p>41.73 The cor. of secs. 4 and 5, only, on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., firmly set in a mound of stone, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p> <p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
	<p>From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp.</p> <p>N. $1^{\circ}00'$ E., bet. secs. 31 and 32.</p> <p>Over gently rolling land, along Stephans Ave. in Pine Top, Arizona.</p> <p>20.19 Point for the S $1/16$ sec. cor. of secs. 31 and 32 at proportionate dist., monumented by a water pipe, $3/4$ in. diam., set flush with the road surface.</p> <p>Set a standard iron post, $2\frac{1}{2}$ ins. diam., cut to 18 ins. long, 20 ins. in the ground to bed rock, brass cap mkd.</p> <p style="text-align: center;">T9N R23E S1/16 S31 S32 1967</p> <p>from which</p> <p>A pine, 7 ins. diam., bears N. 72° E., 73 lks. dist., mkd. S $1/16$ S32 BT.</p> <p>A pine, 10 ins. diam., bears N. 70° W., 72 lks. dist., mkd. S $1/16$ S31 BT.</p> <p>Bury the local cor. pipe alongside the iron post.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS														
20.20	N. end of Stephans Ave., track road bears irregularly NW.; enter dense timber.													
27.40	Begin descent over N. slope.													
35.00	Bladed road, bears irregularly NE. and SW.													
35.90	Billy Creek, 40 lks. wide, 1 ft. deep, course NW.; asc. S. slope.													
40.38	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented by a rock in place, 4 x 2 x 2 ft. above the ground, mkd. $\frac{1}{4}$ on W. face and an X on the top, from which the remains of the orig. bearing trees:</p> <p style="padding-left: 40px;">A pine, stump, 32 ins. diam., bears N. $79\frac{3}{4}^{\circ}$ E., 22 lks. dist., no legible mks. (Record bearing N. 73° E.)</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. $72\frac{1}{4}^{\circ}$ W., 62 lks. dist., mkd. with a cut open blaze. (Record bearing N. 68° W.)</p> <p style="padding-left: 40px;">A pine 8 ins. diam., bears S. 26° E., 41 lks. dist., mkd. $\frac{1}{4}$ S32 BT. (This tree was recently mkd.)</p>													
	<hr style="width: 20%; margin: 0 auto;"/> <p>N. $0^{\circ}17'$ W., beginning new measurement.</p>													
5.10	Top of ascent, continue over gently rolling W. slope.													
40.42	<p>The cor. of secs. 29, 30, 31 and 32, monumented by a basalt stone, 15 x 9 x 5 ins., firmly set in a mound of stone, mkd. 5 notches on the E. face, from which the remains of an orig. bearing tree:</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., bears S. 42° W., 77 lks. dist., mkd. BT. (Record, 88 lks. dist.)</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">T9N</td> <td style="padding: 0 5px;">R23E</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S30</td> <td style="padding: 0 5px;">S29</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S31</td> <td style="padding: 0 5px;">S32</td> <td></td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1967</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 46° E., 36 lks. dist., mkd. T9NR23E S29 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 53° E., 47 lks. dist., mkd. T9NR23E S32 BT.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 11° W., 53 lks. dist., mkd. T9N R23E S31 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 14° W., 47 lks. dist., mkd. T9NR23E S30 BT.</p>	T9N	R23E		S30	S29		S31	S32		1967			
T9N	R23E													
S30	S29													
S31	S32													
1967														
	Deposit the orig. cor. stone alongside the iron post.													
	Land, gently rolling.													

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p>Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
31.70	<p>From the cor. of secs. 28, 29, 32 and 33. S. 89°46' W., bet. secs. 29 and 32. Over gently rolling land, through dense timber.</p>
	<p>Draw, 20 lks. wide, 1 ft. deep, drains SW.</p>
40.55	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented by a juniper tree, 50 ins. diam., mkd. $\frac{1}{4}$ S. on N. face, from which an orig. bearing tree:</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 28° W., 19 lks. dist., mkd. with a healed blaze.</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears S. 79° E., 51 lks. dist., mkd. $\frac{1}{4}$ S32 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 12° E., 7 lks. dist., mkd. $\frac{1}{4}$ S29 BT.</p>
25.20	<p>S. 89°52' W., beginning new measurement. Bladed road, bears N. and S.</p>
27.20	<p>Power line, bears S. 47°45' E. and N. 47°45' W.</p>
28.20	<p>Power line, bears S. 47°45' E. and N. 47°45' W.</p>
40.49	<p>The cor. of secs. 29, 30, 31 and 32. Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
25.60	<p>S. 89°50' W., bet. secs. 30 and 31. Over gently rolling land, through dense timber. Small draw, drains SW.</p>
40.56	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31, monumented by a basalt stone, 16 x 10 x 7 ins., firmly set, no legible mks., mound of stone NE., from which the orig. bearing trees:</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears N. 20° E., 24 lks. dist., illegible mks.</p> <p style="padding-left: 40px;">An oak, 14 ins. diam., bears S. 2$\frac{3}{4}$° W., 93 lks. dist., mkd. with a healed blaze. (Record bearing S. 6° E.)</p> <p>At the corner point</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E $\frac{1}{4}$ $\frac{S30}{S31}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. $56\frac{1}{2}^\circ$ E., 89 lks. dist., mkd. $\frac{1}{4}$ S30 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. $80\frac{1}{4}^\circ$ W., 45 lks. dist., mkd. $\frac{1}{4}$ S31 BT.</p> <p>Raise a mound of stone N. of the cor. and deposit the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. $89^\circ 50'$ W., beginning new measurement.</p>	
7.80	Desc. W. slope..	
19.87	<p>Point for the W 1/16 sec. cor. of secs. 30 and 31, at proportionate dist.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E W $\frac{1}{16}$ $\frac{S30}{S31}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 71° E., 50 lks. dist., mkd. W 1/16 S30 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 34° E., 20 lks. dist., mkd. W 1/16 S31 BT.</p> <p>The cor. is located under a fence bearing N. and S.</p> <p>Raise a mound of stone W. of cor.</p>	
26.20	Billy Creek, 100 lks. wide, 2 ft. deep, course NW.	
33.10	Fence, bears N. $34^\circ 08'$ W. and S. $34^\circ 08'$ E.	
33.30	Power line, bears N. $34^\circ 08'$ W. and S. $34^\circ 08'$ E.	
35.40	Arizona Highway No. 173, bears S. $34^\circ 08'$ E. and N. $34^\circ 08'$ W.	
40.30	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
	From the cor. of secs. 29, 30, 31 and 32.	

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

N. 0°39' W., bet. secs. 29 and 30.

Asc. gentle S. slope, through dense timber.

10.40 Power line, bears S. 47°45' E. and N. 47°45' W.

11.50 Power line, bears S. 47°45' E. and N. 47°45' W.

14.00 Track road, bears irregularly NE. and S. 75°W.

24.90 Bladed road, bears irregularly SE. and NW.

37.70 Track road, bears irregularly E. and W.

40.40 Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate dist.; unable to find any remaining evidence of the orig. cor.

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
 $\frac{1}{4}$
S30|S29
1967

from which

A pine, 12 ins. diam., bears S. 45 $\frac{1}{2}$ ° E., 52 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

A pine, 10 ins. diam., bears N. 44 $\frac{3}{4}$ ° W., 32 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

54.90 Slope changes to W.

75.70 Wash, 30 lks. wide, 3 ft. deep, drains S. 60° W.

80.80 The cor. of secs. 19, 20, 29 and 30, monumented by a basalt stone, 12 x 10 x 8 ins., firmly set, mkd. 2 notches on S. and 5 notches on E. faces, mound of stone W., from which the remains of the orig. bearing trees:

A dead oak, 10 ins. diam., bears S. 48 $\frac{1}{4}$ ° E., 63 lks. dist., mkd. T. 9NR23E S29 BT. (Record: S. 54° E., 66 lks)

An oak, 15 ins. diam., bears N. 73° W., 31 lks. dist., illegible mks.

At the corner point

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T9N R23E
S19|S20
S30|S29
1967

from which

A pine, 8 ins. diam., bears N. 22° E., 17 lks. dist., mkd. T9NR23E S20 BT.

A pine, 8 ins. diam., bears S. 33 $\frac{1}{4}$ ° E., 29 lks. dist., mkd. T9NR23E S29 BT.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS		
	<p>A pine, 6 ins. diam., bears S. 66° W., 73 lks. dist., mkd. T9NR23E S30 BT.</p> <p>A pine, 11 ins. diam., bears N. 49° W., 41 lks. dist., mkd. T9NR23E S19 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
1.70	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 88°58' W., bet. secs. 20 and 29.</p> <p>Asc. NE. slope, through dense timber.</p> <p>Spur slopes N.; desc. W. slope.</p>	
39.92	<p>The ¼ sec. cor. of secs. 20 and 29, monumented by a basalt stone, 14 x 12 x 6 ins., firmly set, mkd. ¼ on N. face, mound of stone N., from which the remains of the orig. bearing trees:</p> <p>A pine stump, bears N. 72° E., 53 lks. dist., no legible mks. (Record, N. 79° E., 55 lks. dist.)</p> <p>An oak, 10 ins. diam., bears S. 27° E., 40 lks. dist., mkd. with a healed blaze. (Record bearing S. 35° E.)</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E</p> <p>¼ $\frac{S20}{S29}$</p> <p>1967</p> </div> <p>from which</p> <p>A pine, 7 ins. diam., bears N. 75° E., 44 lks. dist., mkd. ¼ S29 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°37' W., beginning new measurement.</p>	
39.94	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
	<p>S. 89°56' W., bet. secs. 19 and 30.</p>	

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	Over rolling land, through dense timber.
34.90	Wash, 15 lks. wide, 2 ft. deep, drains N. 65° W.
40.18	The ¼ sec. cor. of secs. 19 and 30, monumented by a basalt stone, 16 x 10 x 6 ins. firmly set in a mound of stone, mkd. ¼ on N. face, from which the remains of the original bearing trees:
	A juniper, 15 ins. diam., bears S. 79° W., 52 lks. dist., mkd. with a healed blaze.
	A pine stump, 22 ins. diam., bears N. 66° W., 48 lks. dist., illegible mks.
	At the corner point
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ <u>S19</u> S30 1967</p>
	from which
	A pine, 10 ins. diam., bears S. 45° E., 42 lks. dist., mkd. ¼ S30 BT.
	A pine, 10 ins. diam., bears N. 58° W., 40 lks. dist., mkd. ¼ S19 BT.
	Deposit the orig. cor. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> S. 89°48' W., beginning new measurement.
34.60	Power line, bears S. 47°45' E., and N. 47°45' W.
35.50	Power line, bears S. 47°45' E. and N. 47°45' W.
41.47	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.
	Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.
	From the cor. of secs. 19, 20, 29 and 30.
	N. 2°35' W., bet. secs. 19 and 20.
	Over rolling land, through dense timber.
10.00	Wash, 15 lks. wide, 1 ft. deep, drains W.
39.82	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ S19 S20 1967</p> <p>from which</p> <p>A pine, 20 ins. diam., bears N. 89° E., 64 lks. dist., mkd. $\frac{1}{4}$ S20 BT.</p> <p>A pine, 11 ins. diam., bears S. 41$\frac{1}{2}$° W., 38 lks. dist., mkd. $\frac{1}{4}$ S19 BT.</p> <p>72.00 Wash, 30 lks. wide, 2 ft. deep, drains W.</p> <p>79.64 The cor. of secs. 17, 18, 19 and 20, monumented by a mound of stone, with a squared wooden post 4 x 4 ins., 4 ft. long, lying alongside. (Record: a lava stone 4 x 4 x 4 ins. with a mound of stone alongside.) There are no marks on the post or any of the stones. The mound and post appear to be old and undisturbed and are accepted as the best available evidence of the orig. cor. position.</p> <p>from which the orig. bearing trees</p> <p>A juniper, 27 ins. diam., bears N. 64° E., 28 lks. dist., mkd. with a healed blaze. (Record, N. 55° W., 21 lks. dist.)</p> <p>A juniper, 20 ins. diam., bears S. 7° W., 121 lks. dist., mkd. T9NR23E S19. (Record, S. 12° W., 15 lks. dist.)</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E S18 S17 S19 S20 1967</p> <p>from which</p> <p>A pine, 6 ins. diam., bears S. 41° E., 52 lks. dist., mkd. T9NR23E S20 BT.</p> <p>A pine, 6 ins. diam., bears N. 70° W., 59 lks. dist., mkd. T9NR23E S18 BT.</p> <p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
40.16	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°43' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land, through dense timber.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented by a basalt stone, 16 x 14 x 9 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face, from which the remains of the orig. bearing trees:</p>

Dep. Resurvey, Subdivision T. 9 N., R. 23 E.

CHAINS	
	<p>A pine, 19 ins. diam., bears S. 51° E., 98 lks. dist., dim mks. in a partially healed blaze. (Record S. 55° E., 91 lks. dist.)</p> <p>A pine, 27 ins. diam., bears N. 74° W., 112 lks. dist., dim mks. in a partially healed blaze (Record: N. 66° W., 120 lks. dist.)</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E $\frac{1}{4}$ <u>S17</u> S20 1967</p> <p>from which</p> <p>A forked juniper, 6 ins. diam., bears N. 35° E., 51 lks. dist., mkd. $\frac{1}{4}$ S17 Bt.</p> <p>A pine, 8 ins. diam., bears S. 33° E., 16 lks. dist., mkd. $\frac{1}{4}$ S20 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89°44' W., beginning new measurement.</p>
42.35	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
5.90	<p>S. 89°33' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land, through dense timber.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W.</p>
40.25	<p>The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented by a white oak, 12 ins. diam., mkd. with a healed blaze on the N. face, from which the orig. bearing tree:</p> <p style="padding-left: 40px;">A dead white oak, 6 ins. diam., bears S. 5° W., 19 lks. dist., mkd. $\frac{1}{4}$ SBT. (Record bearing 5.19° W.)</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A juniper 6 ins. diam., bears N. 10° E., 23 lks. dist., mkd. $\frac{1}{4}$ S18 BT.</p> <p style="padding-left: 40px;">A juniper 8 ins. diam., bears S. 66° W., 61 lks. dist., mkd. $\frac{1}{4}$ S19 BT.</p> <p style="text-align: center;">_____</p>
30.00	<p>N. 88°36' W., beginning new measurement.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains NW.</p>
38.60	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.</p> <p>Land, rolling Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°08' E., bet. secs. 17 and 18.</p> <p>Over gently rolling land, through dense timber.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS 40.23	<p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented by a lava stone, 18 x 14 x 12 ins., firmly set, mkd. $\frac{1}{4}$ on W. face, mound of stone E., from which the remains of the orig. bearing trees:</p> <p style="padding-left: 40px;">A stump hole with a blazed pine lying alongside, bears N. 55° E., 50 lks. dist. (Record: N. 50° E., 44 lks. dist.)</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., bears N. 75° W., 50 lks. dist., mkd. with a healed blaze.</p> <p>At the corner point Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E $\frac{1}{4}$ S18 S17 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 85° E., 39 lks. dist., mkd. $\frac{1}{4}$ S17 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 60° W., 92 lks. dist., mkd. $\frac{1}{4}$ S18 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' W., beginning new measurement.</p> <p>.20 Fence, bears SW. and NE., 45 lks. dist., thence N. 6° W.</p> <p>3.90 Fence, bears S. 6° E. and N. 6° W.</p> <p>20.185 Point for the N 1/16 sec. cor. of secs. 17 and 18, at proportionate dist.</p> <p>Set the iron post 4 ins. in the ground, over an X mkd. on bed rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E N1/16 S18 S17 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 26$\frac{1}{2}$° E., 24 lks. dist., mkd. N 1/16 S17 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 62$\frac{1}{2}$° W., 64 lks. dist., mkd. N 1/16 S18 BT.</p> <p>20.70 Fence, bears E. and W.</p> <p>25.70 Jeep road, bears irregularly SE. and W.</p> <p>26.10 Morgan Wash, 100 lks. wide, 5 ft. deep, drains N. 60° W.</p> <p>40.37 The cor. of secs. 7, 8, 17 and 18, monumented by a lava stone, 20 x 12 x 10 ins., firmly set, mkd. 5 notches on E. and 2 notches on S. faces, mound of stone W., from which the orig. bearing trees:</p> <p style="padding-left: 40px;">A pine, 26 ins. diam., bears N. 81° E., 126 lks. dist., mkd. with a healed blaze. (Record: N. 72° E. 124 lks. dist.)</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 22$\frac{1}{2}$° W., 38 lks. dist., mkd. with a healed blaze. (Record: S. 14° W. 28 lks. dist.)</p> <p>At the corner point Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>
-----------------	---

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">T9N R23E $\frac{S\ 7}{S18} \frac{S\ 8}{S17}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 66° E., 19 lks. dist., mkd. T9NR23E S17 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 63° W., 40 lks. dist., mkd. T9NR23E S7 BT.</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17. S. 89°56' W., bet secs. 8 and 17. Over gently rolling land, through moderate timber. Along a fence bearing E. and W.</p>
1.70	Top of ridge, bears N. and S.; desc. over W. slope.
19.90	Fence cor., bears North, 40 lks. dist., fences bear E., S. and NW.
20.495	Point for the E 1/16 sec. cor. of secs. 8 and 17, at proportionate dist.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T9N R23E E $\frac{1}{16}$ $\frac{S\ 8}{S17}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 26° E., 111 lks. dist., mkd. E 1/16 S17 BT.</p> <p>The cor. is located on the S. edge of a jeep road, bearing N. 75° W. and N. 75° E. for 50 lks. to end.</p>
28.10	Jeep road bears N. 15° W. and S. 15° E.
37.60	Morgan Wash, 200 lks. wide, 12 ft. deep, drains S. 20° W.
40.50	Ravine, 80 lks. wide, 8 ft. deep drains S. 10° W., into Morgan Wash.
40.99	Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T9N R23E $\frac{1}{4} \frac{S\ 8}{S17}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 47° W., 20 lks. dist., mkd. 1/4 S8 BT.</p> <p>Cor. is located on the NW. edge and near bottom of ravine.</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS		
43.90	Fence, bears NE. and SW.	
46.113	Point for the E-E-W 1/256 sec. cor. of secs. 8 and 17, at proportionate dist.	
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.	
	$\begin{array}{r} \text{T9N R23E} \\ \text{E-E-W } \frac{1}{256} \frac{\text{S } 8}{\text{S17}} \\ 1967 \end{array}$	
	from which	
	A pine, 6 ins. diam., bears N. 51° E., 16 lks. dist., mkd. EEW 1/256 S8 BT.	
	A pine, 8 ins. diam., bears S. 59½° W., 34 lks. dist., mkd. EEW 1/256 S17 BT.	
61.485	Point for the W 1/16 sec. cor. of secs. 8 and 17, at proportionate dist., not monumented.	
81.98	The cor. of secs. 7, 8, 17 and 18.	
	Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.	
20.145	S. 89°44' W., bet secs. 7 and 18.	
	Over gently rolling land, through dense timber.	
	Point for the E 1/16 sec. cor. of secs. 7 and 18, at proportionate dist.	
	Set the iron post 20 ins. in the ground, brass cap mkd.	
	$\begin{array}{r} \text{T9N R23E} \\ \text{E } \frac{1}{16} \frac{\text{S } 7}{\text{S18}} \\ 1967 \end{array}$	
	from which	
	A pine, 15 ins. diam., bears N. 46° E., 24 lks. dist., mkd. E 1/16 S 7 BT.	
	A pine, 6 ins. diam., bears S. 19° E., 10 lks. dist., mkd. E 1/16 S18 BT.	
	Raise a mound of stone N. of the cor.	
25.00	Track road, bears NE. and SW.	
35.50	Bladed road, bears S. 75° E. and N. 75° W.	
40.29	The ¼ sec. cor. of secs. 7 and 18, as determined from the orig. bearing tree:	
	A dead pine, 20 ins. diam., bears N. 13° E., 78 lks. dist., mkd. ¼ S. (Record)	

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

A lava stone, 8 x 5 x 4 ins., mkd. $\frac{1}{4}$, was found N. 30° E., 15 lks. dist., from the true point. This stone was lying loose on the ground with fresh pine needles beneath it. This point was not accepted.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T9N R23E
 $\frac{1}{4}$ $\frac{S 7}{S18}$
1967

from which

A pine, 10 ins. diam., bears N. 25° E., 41 lks. dist., mkd. T9NR23E $\frac{1}{4}$ S7 BT.

A pine, 8 ins. diam., bears N. 24° W., 51 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

Bury the mkd. stone alongside the iron post.

Raise a mound of stone N. of cor.

Cor. is located 90 lks. South of a jeep road bearing N. 75° W. and S. 75° E.

N. 88°34' W., beginning new measurement.

- 2.70 Fence, bears irregularly SE. and NW.
 - 15.30 Morgan Wash, drains N. 65° W.
 - 18.51 Point for the W 1/16 sec. cor. of secs. 7 and 18, at proportionate dist., not monumented.
 - 24.40 Irrigation ditch, 3 lks. wide, 1 ft. deep, drains NW.
 - 26.00 Enter wash area.
 - 26.70 Porter Creek, 5 lks. wide, 1 ft. deep, course irregularly W. from SE.
 - 37.00 Confluence of Morgan Wash and Porter Creek.
 - 38.54 The true point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
- Land, gently rolling.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass.

From the cor. of secs. 7, 8, 17 and 18.

N. 0°22' E., bet. secs. 7 and 8.

Over rolling land, through dense timber.

- 9.50 Jeep road, bears S. 60° E. and N. 60° W.

BOOK 4867

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
17.70	Wash, 10 lks. wide, 2 ft. deep, drains SW.
24.20	Gravel road, bears NE. and SW.
31.60	Jeep road, bears S. 60° E. and N. 60° W., curving N.
35.30	Wash, 5 lks. wide, 2 ft. deep, drains S. 20° E.; asc. SW. slope.
40.37	The 1/4 sec. cor. of secs. 7 and 8, monumented by a basalt stone, 16 x 9 x 9 ins., loosely set, mkd. 1/4 on W. face, from which the remains of the orig. bearing trees:
	A rotted pine, bears S. 71° E., 57 lks. dist., no legible mks.
	A pine, 18 ins. diam., bears N. 38° W., 51 lks. dist., visible scribes in a partially overgrown blaze. (Record: N. 31° W., 57 lks. dist.)
	At the corner point
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p>T9N R23E</p> <p>1/4</p> <p>S 7 S 8</p> <p>1967</p>
	from which
	A juniper, 9 ins. diam., bears S. 25° E., 34 lks. dist., mkd. 1/4 S8 BT.
	A pine, 10 ins. diam., bears S. 49° W., 73 lks. dist., mkd. 1/4 S7 BT.
	A USC&GS bench mark, bears S. 6°36' W., 18.78 chs. dist., monumented by a brass tablet, 3 ins. diam., set in a cement block, 8 x 8 x 6 ins., mkd. M141 1935.
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	<hr style="width: 20%; margin: auto;"/> <p>N. 0°11' W., beginning new measurement.</p>
	Continue ascent.
8.50	Ridge, bears E. and W.; desc. N. slope.
10.70	Power line, bears N. 60°28' E. and S. 60° 28' W.
15.60	Draw, drains S. 30° W.; asc. S. slope.
20.095	Point for the N 1/16 sec. cor. of secs. 7 and 8, at proportionate dist., not monumented.
23.60	Track road, bears NE. and SW.
28.90	Track road, bears S. 60° E. and N. 60° W.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS									
38.50	Hill,; desc. N. slope.								
40.19	<p>The cor. of secs. 5, 6, 7 and 8, monumented by a sandstone, 16 x 8 x 8 ins., firmly set in a mound of stone, mkd. 5 notches on E. and 5 notches on S. faces, from which the remains of the orig. bearing trees:</p> <p>A stump hole, bears N. 24½° E., 130 lks. dist., with an oak lying alongside mkd. T9NR23E S5 BT. (Record bearing N. 32° E.)</p> <p>An oak snag, 20 ins. diam., bears S. 39½° W., 14 lks. dist., mkd. T9NR23E S7 BT. (Record bearing S. 30° W.)</p> <p>An oak stump, bears N. 39½° W., 71 lks. dist., mkd. T9NR23E S. (Record bearing N. 36° W.)</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T9N</td> <td>R23E</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td colspan="2">1967</td> </tr> </table> </div> <p>from which</p> <p>A pine, 6 ins. diam., bears N. 52° E., 18 lks. dist., mkd. T9NR23E S5 BT.</p> <p>A pine, 8 ins. diam., bears S. 34° E., 17 lks. dist., mkd. T9NR23E S8 BT.</p> <p>A pine, 7 ins. diam., bears S. 62° W., 34 lks. dist., mkd. T9NR23E S7 BT.</p> <p>A pine, 6 ins. diam., bears N. 37½° W., 20 lks. dist., mkd. T9NR23E S6 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>	T9N	R23E	S 6	S 5	S 7	S 8	1967	
T9N	R23E								
S 6	S 5								
S 7	S 8								
1967									
20.125	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°25' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land, through dense timber.</p>								
30.187	<p>Point for the E 1/16 sec. cor. of secs. 5 and 8, at proportionate dist., not monumented.</p> <p>Point for the W-E 1/64 sec. cor. of secs. 5 and 8, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>								

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS	
	T9N R23E W-E $\frac{1}{64}$ $\frac{S}{S}$ $\frac{5}{8}$ 1967
	from which A pine, 28 ins. diam., bears S. 41° E., 8 lks. dist., mkd. WE 1/64 S8 BT. Raise a mound of stone N. of the cor.
30.70	Fence, bears N. and S., enter open field.
32.00	Power line, bears S. 10° E. and N. 10° W.
40.25	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; unable to find any remaining evidence of the orig. cor. This cor. was not monumented.
45.281	Point for the E-E-W 1/256 sec. cor. of secs. 5 and 8, at proportionate dist. Set the iron post 22 ins. in the ground, brass cap mkd.
	T9N R23E E-E-W $\frac{1}{256}$ $\frac{S}{S}$ $\frac{5}{8}$ 1967
	from which A pine, 15 ins. diam., bears S. 78° W., 104 lks. dist., mkd. EEW 1/256 S8 BT. A pine, 6 ins. diam., bears N. 49° W., 130 lks. dist., mkd. EEW 1/256 S5 BT. Set a wooden post, 4 ins. diam., 6 ft. long, alongside iron post.
45.50	Fence, bears N. and S.; enter dense timber.
50.312	Point for the E-W 1/64 sec. cor. of secs. 5 and 8, at proportionate dist., not monumented.
50.50	Track road, bears N. 15° E. and S. 15° W.
56.70	Track road, bears N. and S.
60.375	Point for the W 1/16 sec. cor. of secs. 5 and 8, at proportionate dist., not monumented.
76.40	Power line, bears S. 5° E. and N. 5° W.
76.90	Gravel road, bears S. 5° E. and N. 5° W.
80.50	The cor. of secs. 5, 6, 7 and 8. Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.
	N. 89°45' W., bet. secs. 6 and 7. Over gently rolling land, through dense timber.

CHAINS	
19.10	Track road, bears N. 60° E. and W.
22.00	Leave track road, bears irregularly S. 60° W. and E.
38.62	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$ 1967</p>
	from which
	<p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 45° E., 45 lks. dist., mkd. ½ S7 BT.</p>
	<p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 1° W., 46 lks. dist., mkd. ½ S6 BT.</p>
62.00	Same track road, bears irregularly S. 60° E. and N. 60° W.
79.14	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
	From the cor. of secs. 5, 6, 7 and 8.
	N. 1°49' E., bet. secs. 5 and 6.
	Over rolling land, through dense timber.
	Desc. N. slope.
2.10	Bottom of desc., asc. SE. slope.
3.60	Track road, bears NE. and SW.
13.70	Power line, bears S. 34°43' E. and N. 34°43' W.
20.55	Point for the S 1/16 sec. cor. of secs. 5 and 6, at proportionate dist., not monumented.
28.80	Bladed road bears SW. and E. for 1 ch. thence N. and S.
29.00	Fence, bears E. and W.; enter a cinder pit.
33.90	Center of a cinder pit.
41.10	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate dist.; unable to find any remaining evidence of the orig. cor.
	Set the iron post 26 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T9N R23E $\frac{1}{4}$ S 6 S 5 1967</p>

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

from which

A pine, 9 ins. diam., bears N. 37° E., 57 lks. dist., mkd. ¼ S5 BT.

USC&GS Triangulation Intersection Station, show Low TV Assoc., Tower, on top of Porter Mountain, bears S. 87°07' W. 24.05 chs.

Set a wooden post 5 ft. long. 4 ins. diam., alongside the iron post.

Desc. NE. slope.

65.80 Track road, bears N. 20° E. and S. 20° W.

80.70 Track road, bears E. and W.

81.98 The cor. of secs. 5 and 6, only, on the N. bdy. of the Tp., identical with cor. No. 1, H.E.S. 453, monumented by a lava stone, 18 x 12 x 8 ins., firmly set, mkd. 5 notches on E. and 1 notch on W. faces and an X on top, from which the remains of the orig. bearing trees:

A pine, 15 ins. diam., bears N. 13½° E., 48 lks. dist., mkd. with a healed blaze.

An oak, 12 ins. diam., bears N. 30° E., 57 lks. dist., mkd. with a healed blaze.

A pine, 18 ins. diam., bears S. 17½° E. 106 lks. dist., mkd. 23E S5.

A stump hole, with a fallen pine alongside, 15 ins. diam., mkd. HES 453 X BT, bears S. 55½° E., 99 lks. dist.

A pine, 28 ins. diam., bears S. 20° W., 212 lks. dist., mkd. with a healed blaze.

A pine, 10 ins. diam., bears S. 43° W., 56 lks. dist., mkd. T9NR23E S6 X BT.

A pine, 17 ins. diam., bears N. 3° W., 107 lks. dist., mkd. with a healed blaze.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T10N R23E	
HES 453	S31
Cor 1	
S 6	S 5
T9N	R23E
1967	

At a point 1½ lks. W. of the iron post is an oak post, 8 ins. square by 18 ins. above the ground, mkd. 1 HES 453 on NW. face. This post was inverted and reset as above.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone S. of the cor.

Dep. Resurvey, Subdivision, T. 9 N., R. 23 E.

CHAINS

Land, rolling to mountainous.
Soil, rocky, clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunch grass, scrub oak and manzanita.

Survey, Partial Subdivision of Certain
Sections T. 9N., R. 23 E.

Subdivision, Sec. 25

From the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.
N. $0^{\circ}44'$ W., on the N. and S. center line of sec. 25.
Over gently rolling land, through dense timber.

- 9.50 Old railroad bed, bears SE. and NW.
- 39.55 Point for the $C\frac{1}{4}$ sec. cor. of sec. 25, at the intersection with the E. and W. center line of sec. 25.

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

T9N R23E
C $\frac{1}{4}$ +S25
1967
- 39.64 Fence, bears E. and W.
- 49.78 Point for the C-S-N $\frac{1}{64}$ sec. cor. of sec. 25, not monumented.
- 59.50 Track road, bears E. and W.
- 60.01 Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 25.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

C
N1/16 | S25
C
1967
- from which

A fence cor., bears N. $4^{\circ}35'$ E., $47\frac{1}{2}$ lks. dist., fences bear N., S. 65° E. and W.

A metal water tank, 8 ft. diam., bears S. $59\frac{1}{2}^{\circ}$ E., 167 lks. dist.
- 60.70 Wash, 30 lks. wide, 1 ft. deep, drs. NW.
- 65.60 Wash, 40 lks. wide, 2 ft. deep, drains W.
- 69.10 Old railroad bed, bears NE. and SW.
- 70.00 Wash, 50 lks. wide, 1 ft. deep, drains SW.

Survey, Partial Subdivision, Sec. 25, T. 9N., R. 23 E.

CHAINS	
70.24	<p>Point for the C-N-N 1/64 sec. cor. of sec. 25.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N-N1/64 S25</p> <p>C</p> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 10° E., 23 lks. dist., fences bear S. and W.</p>
80.47	<p>The ¼ sec. cor. of secs. 24 and 25.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
13.10	<p>From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.</p> <p>S. 89°59' W., on the E. and W. center line of sec. 25.</p> <p>Over gently rolling land, through dense timber.</p>
19.10	<p>Old railroad bed, bears N. 70° E. and S. 85° W.</p>
40.18	<p>Fence, bears N. 70° E. and S. 85° W.</p>
50.21	<p>The C¼ sec. cor. of sec. 25.</p>
60.24	<p>Point for the C-E-W 1/64 sec. cor. of sec. 25, not monumented.</p>
61.50	<p>Point for the C-W 1/16 sec. cor. of sec. 25, not monumented.</p>
62.00	<p>Old railroad bed bears NW. and SE.</p>
70.27	<p>Wash, 40 lks. wide, 1 ft. deep, drains NW.</p>
80.30	<p>Point for the C-W-W 1/64 sec. cor. of sec. 25, not monumented.</p>
80.30	<p>The ¼ sec. cor. of secs. 25 and 26.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p style="text-align: center;">Subdivision, NW¼ Sec. 25</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the C-W 1/16 sec. cor. of sec. 25.</p> <p>N. 1°02' W., on the N. and S. center line of the NW¼ sec. 25.</p> <p>Over gently rolling land, through dense timber.</p>

Survey, Partial Subdivision, Sec. 25, T. 9N., R. 23 E.

CHAINS	
.50	Fence, bears irregularly E. and W.
10.17	Point for the C-S-NW 1/64 sec. cor. of sec. 25, not monumented.
15.70	Fence, bears irregularly E. and W.
19.80	Wash, 80 lks. wide, 1 ft. deep, drains NW.
20.34	Point for the NW 1/16 sec. cor. of sec. 25, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ sec. 25, not monumented.
25.425	Point for the C-S-N-NW 1/256 sec. cor. of sec. 25, not monumented.
29.90	Track road, bears SE. and NW.
30.51	Point for the C-N-NW 1/64 sec. cor. of sec. 25, not monumented.
35.595	Point for the C-N-N-NW 1/256 sec. cor. of sec. 25, not monumented.
35.70	Fence, bears irregularly E. and W.
40.68	The point for the W 1/16 sec. cor. of secs. 24 and 25.
	From the C-N 1/16 sec. cor. of sec. 25.
	S. 89°37'30" W., on the E. and W. center line of the NW $\frac{1}{4}$ sec. 25.
	Over gently rolling land, through dense timber.
4.50	Track road, bears NW. and SE.
9.95	Fence, bears N. and S.
10.085	Point for the C-E-NW 1/64 sec. cor. of sec. 25.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">S25 C-E-NW $\frac{1}{64}$ 1967</p>
	from which
	A fence cor., bears N. 20° E., 45 lks. dist., fences bear E. and S.
	SW. cor. of a fallen cabin, bears N. 20° E., 45 lks. dist.
	Leave dense timber; enter scattered timber.
19.80	Wash, 120 lks. wide, 3 ft. deep, drains SW.
20.17	The point for the NW 1/16 sec. cor. of sec. 25.
21.90	Same wash, 30 lks. wide, 4 ft. deep, drains irregularly N.

Survey, Partial Subdivision, Sec. 25, T. 9N., R. 23 E.

CHAINS	
25.21	Point for the C-E-W-NW 1/256 sec. cor. of sec. 25, not monumented.
30.00	Fence, bears irregularly N. and S.
30.25	Point for the C-W-NW 1/64 sec. cor. of sec. 25, not monumented.
33.50	Same wash, 80 lks. wide, 2 ft. deep, drains S. 60°W.
40.33	The point for the N 1/16 sec. cor. of secs. 25 and 26.
	From the point for the C-E-W 1/64 sec. cor. of sec. 25.
	N. 0°54' W., on the N. and S. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.
	Over rolling land, through dense timber.
.60	Fence, bears irregularly E. and W.
10.184	Point for the SE-NW 1/64 sec. cor. of sec. 25 at the intersection with the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25, not monumented.
15.292	Point for the C-N-SE-NW 1/256 sec. cor. of sec. 25.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">S25 C-N-SE-NW $\frac{1}{256}$ 1967</p>
	from which
	A fence cor., bears N. 10° W., 55 lks. dist., fences bear N. and W.
20.40	The C-E-NW 1/64 sec. cor. of sec. 25.
	From the point for the C-S-N 1/64 sec. cor. of sec. 25.
	S. 89°49' W., on the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.
	Over rolling land, through dense timber.
10.055	The point for the SE-NW 1/64 sec. cor. of sec. 25.
20.11	The point for the C-S-NW 1/64 sec. cor. of sec. 25.
	From the point for the C-W-W 1/64 sec. cor. of sec. 25.
	N. 1°10' W., on the N. and S. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.
	Over gently rolling land, through moderate timber.
1.10	Fence, bears irregularly E. and W.

Survey, Partial Subdivision, Sec. 25, T. 9 N., R. 23 E.

CHAINS

- 10.140 Point for the SW-NW 1/64 sec. cor. of sec. 25, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25, not monumented.
- 15.21 Point for the C-N-SW-NW 1/256 sec. cor. of sec. 25.
Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

S25
C-N-SW-NW
 $\frac{1}{256}$
1967

from which

A fence cor., bears N. 25^o E., 49 lks. dist., fences bear N., E. and W.
- 15.40 Wash, 20 lks. wide, 1 ft. deep, drains NW.
- 15.70 Fence, bears irregularly E. and W.
- 20.28 The point for the C-W-NW 1/64 sec. cor. of sec. 25.

From the point for the C-S-NW 1/64 sec. cor. of sec. 25.
S. 89°49' W., on the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.

Over rolling land, through moderate timber.

- 7.50 Wash, 40 lks. wide, 1 ft. deep, drains NW.
- 10.055 The point for the SW-NW 1/64 sec. cor. of sec. 25.
- 20.11 The point for the S-N 1/64 sec. cor. of secs. 25 and 26.

From the C-E-NW 1/64 sec. cor. of sec. 25.

N. 0°52' W., on the N. and S. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.

Over nearly level land, through open meadow.

- 6.40 Track road, bears SE. and NW.
- 8.60 Wash, 40 lks. wide, 2 ft. deep, drains SW.
- 10.197 Point for the NE-NW 1/64 sec. cor. of sec. 25, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25, not monumented.
- 15.294 Point for the C-N-NE-NW 1/256 sec. cor. of sec. 25, not monumented.
- 20.39 The point for the E-W 1/64 sec. cor. of secs. 24 and 25.

From the C-N-N 1/64 sec. cor. of sec. 25.

S. 89°25'30" W., on the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.

Survey, Partial Subdivision, Sec. 25, T. 9 N., R. 23 E.

CHAINS	
<p>5.052</p>	<p>Over gently rolling land, through moderate timber.</p> <p>Point for the C-E-NE-NW 1/256 sec. cor. of sec. 25.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S25 C-E-NE-NW <u>1</u> 256 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 22° E., 29 lks. dist., fences bear N. and E.</p> <p>Leave timber, enter open meadow, bears N. and S.</p> <p>8.30 Wash, 180 lks. wide, 4 ft. deep, drains SW.</p> <p>10.104 The point for the NE-NW 1/64 sec. cor. of sec. 25.</p> <p>15.156 Point for the C-W-NE-NW 1/256 sec. cor. of sec. 25, not monumented.</p> <p>20.208 The point for the C-N-NW 1/64 sec. cor. of sec. 25.</p>
<p>5.092</p>	<p>From the point for the C-W-NE-NW 1/256 sec. cor. of sec. 25.</p> <p>N. 0°56'30" W., on the N. and S. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 25.</p> <p>Over nearly level land, across an open meadow.</p> <p>Point for the NW-NE-NW 1/256 sec. cor. of sec. 25, at the intersection with the E. and W. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 25.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S25 NW-NE-NW <u>1</u> 256 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 60° E., 23 lks. dist., fences bear N. and W.</p> <p>10.184 The W-E-W 1/256 sec. cor. of secs. 24 and 25.</p>
<p>5.062</p>	<p>From the point for the C-N-NE-NW 1/256 sec. cor. of sec. 25.</p> <p>S. 89°21'15" W., on the E. and W. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 25.</p> <p>Over nearly level land, over an open meadow.</p> <p>The NW-NE-NW 1/256 sec. cor. of sec. 25.</p>

Resurvey, Partial Subdivision, Sec. 25, T. 9 N., R. 23 E.

CHAINS	
10.124	The point for the C-N-N-NW 1/256 sec. cor. of sec. 25.
	From the point for the C-W-NW 1/64 sec. cor. of sec. 25.
	N. 1°11' W., on the N. and S. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.
	Over nearly level land, through moderate timber.
1.50	Wash, 80 lks. wide, 2 ft. deep, drains W.
5.072	Point for the C-S-NW-NW 1/256 sec. cor. of sec. 25.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	S25
	C-S-NW-NW
	$\frac{1}{256}$
	1967
8.40	Track road, bears E. and W.
10.144	Point for the NW-NW 1/64 sec. cor. of sec. 25, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25, not monumented.
15.21	Point for the C-N-NW-NW 1/256 sec. cor. of sec. 25, not monumented.
20.277	The point for the W-W 1/64 sec. cor. of secs. 24 and 25.
	From the point for the C-N-NW 1/64 sec. cor. of sec. 25.
	S. 89°27'45" W., on the E. and W. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 25.
	Over gently rolling land, through moderate timber.
.70	Track road, bears SE. and NW.
4.70	Fence, bears irregularly N. and S.
5.056	Point for the C-E-NW-NW 1/256 sec. cor. of sec. 25, not monumented.
6.10	Track road, bears N. 40° E. and S. 40° W.
10.112	The point for the NW-NW 1/64 sec. cor. of sec. 25.
14.00	Wash, 50 lks. wide, 2 ft. deep, drains S. 20° W.
18.00	Track road, bears NW. and SE.
20.22	The point for the N-N 1/64 sec. cor. of secs. 25 and 26.
	From the point for the C-E-W-NW 1/256 sec. cor. of sec. 25.

Survey, Partial Subdivision, Sec. 25, T. 9N., R. 23 E.

CHAINS	
	<p>N. 1°04' W., on the N. and S. center line of the SE$\frac{1}{4}$NW$\frac{1}{4}$ NW$\frac{1}{4}$ sec. 25.</p>
	<p>Over nearly level land, across an open meadow.</p>
1.30	<p>Wash, 110 lks. wide, 3 ft. deep, drains W.</p>
5.076	<p>Point for the SE-NW-NW 1/256 sec. cor. of sec. 25, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$ NW$\frac{1}{4}$NW$\frac{1}{4}$ sec. 25.</p>
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">S25 SE-NW-NW</p>
	<p style="text-align: center;"><u>1</u></p>
	<p style="text-align: center;">256</p>
	<p style="text-align: center;">1967</p>
	<p>from which</p>
	<p style="text-align: center;">A fence cor., bears N. 47° E., 38 lks. dist., fences bear N., S. and W.</p>
5.40	<p>Old fence line, bears irregularly E. and W.</p>
10.152	<p>The point for the C-E-NW-NW 1/256 sec. cor. of sec. 25.</p>
	<p>From the point for the C-S-N-NW 1/256 sec. cor. of sec. 25.</p>
	<p>S. 89°32' W., on the E. and W. center line of the SE$\frac{1}{4}$ NW$\frac{1}{4}$NW$\frac{1}{4}$ sec. 25.</p>
	<p>Over nearly level land, across an open meadow.</p>
4.30	<p>Fence, bears irregularly N. and S.</p>
5.048	<p>The SE-NW-NW 1/256 sec. cor. of sec. 25.</p>
9.70	<p>Fence, bears irregularly N. and S.</p>
10.10	<p>The C-S-NW-NW 1/256 sec. cor. of sec. 25.</p>
	<p>From the point for the C-E-NW-NW 1/256 sec. cor. of sec. 25.</p>
	<p>N. 1°07'30" W., on the N. and S. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$NW$\frac{1}{4}$ sec. 25.</p>
	<p>Over gently rolling land, through moderate timber.</p>
.80	<p>Track road, bears NE. and SW.</p>
5.075	<p>Point for the NE-NW-NW 1/256 sec. cor. of sec. 25, at the intersection with the E. and W. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$NW$\frac{1}{4}$ sec. 25.</p>
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Survey, Partial Subdivision, Sec. 25, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">S25 NE-NW-NW <u>1</u> 256 1967</p> <p>from which</p> <p style="text-align: center;">A fence cor., bears N. 78° E., 53 lks. dist., fences bear E. and S.</p> <p>10.15 The point for the E-W-W 1/256 sec. cor. of secs. 24 and 25.</p>
	<p>From the point for the C-N-N-NW 1/256 sec. cor. of sec. 25.</p> <p>S. 89°22'15" W., on the E. and W. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$NW$\frac{1}{4}$, sec. 25.</p> <p>4.70 Fence, bears irregularly N. and S.</p> <p>5.07 The NE-NW-NW 1/256 sec. cor. of sec. 25.</p> <p>10.13 The point for the C-N-NW-NW 1/256 sec. cor. of sec. 25.</p>
	<p style="text-align: center;">Subdivision, Sec. 1</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 1 and 12.</p> <p>N. 0°55' W., on the N. and S. center line of sec. 1.</p> <p>Over gently rolling land, through dense timber.</p> <p>14.50 Gravel road, bears N. 15° E. and SW.</p> <p>29.80 Track road, bears E. and W.</p> <p>41.53 Point for the C$\frac{1}{4}$ sec. cor. of sec. 1, at the intersection with the E. and W. center line of sec. 1.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E C $\frac{1}{4}$ + S1 1967</p> <p>Raise a mound of stone W. of the cor.</p>
	<p>62.52 Point for the C-N 1/16 sec. cor. of sec. 1, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S1 C 1967</p> <p>from which</p> <p style="text-align: center;">A fence cor., bears S. 30° E., 75 lks. dist., fences bear N. and W.</p>

Survey, Partial Subdivision, Sec. 1, T. 9 N., R. 23 E.

CHAINS	
64.00	Wash, 20 lks. wide 1 ft. deep, drains N. 10° W.
83.46	<p>The ¼ sec. cor. of sec. 1, only, on the N. bdy. of the Tp., monumented by an iron post, 1 in. diam., projecting 10 ins. above the ground, properly mkd. and witnessed as described in the official record of the 1935 resurvey.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the ¼ sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.</p>
	<p>S. 89°31' W., on the E. and W. center line of sec. 1.</p>
	<p>Over gently rolling land, through dense timber.</p>
1.74	<p>S. edge of a gate, on a fence bearing N. and S.</p>
26.00	<p>Draw, drains NW.</p>
34.90	<p>Gravel road, bears N. 15° E. and S. 15° W.</p>
39.15	<p>The C¼ sec. cor. of sec. 1.</p>
45.60	<p>Track road, bears S. 20° E. and N. 20° W.</p>
61.60	<p>Draw, drains NW.</p>
76.30	<p>The ¼ sec. cor. of secs. 1 and 2.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass scrub oak.</p>
Subdivision, Sec. 23	
	<p>From the ¼ sec. cor. of secs. 23 and 26.</p>
	<p>N. 0°20' W., on the N. and S. center line of sec. 23.</p>
	<p>Over gently rolling land, through dense timber.</p>
25.90	<p>Track road, bears S. 56° E. and N. 56° W.</p>
39.41	<p>Point for the C¼ sec. cor. of sec. 23, at the intersection with the E. and W. center line of sec. 23.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p>C ¼ + S23 1967</p>
	<p>from which</p>
	<p>A pine, 6 ins. diam., bears S. 74° W., 15 lks. dist., mkd. C¼ S23 BT.</p>
49.50	<p>Point for the C-S-N 1/64 sec. cor. of sec. 23, not monumented.</p>

Survey, Partial Subdivision, Sec. 23, T. 9 N., R. 23 E.

CHAINS	
54.55	Point for the C-N-S-N 1/256 sec. cor. of sec. 23, not monumented.
55.10	Old fence line, bears E. and W.
56.20	Enter open meadow, edge bears E. and W.
59.60	Point for the C-N 1/16 sec. cor. of sec. 23 not monumented.
64.645	Point for the C-S-N-N 1/256 sec. cor. of sec. 23.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	S23 C-S-N-N $\frac{1}{256}$ 1967
	Set a wooden post, 4 ft. long, 4 ins. diam., alongside the iron post.
69.60	Elk Springs Draw, 30 lks. wide, 2 ft. deep, drains NW.
69.69	Point for the C-N-N 1/64 sec. cor. of sec. 23.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	S23 C-N-N $\frac{1}{64}$ 1967
70.50	Old fence line, bears SE. and NW.
71.10	Enter timber, edge bears E. and W.
74.74	Point for the C- N-N-N 1/256 sec. cor. of sec. 23, not monumented.
77.50	Track road, bears SW. and NE.
79.79	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.
	From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.
	West, on the E. and W. center line of sec. 23.
	Over gently rolling land, through dense timber.
19.84	Point for the C-E 1/16 sec. cor. of sec. 23, not monumented.
29.76	Point for the C-W-E 1/64 sec. cor. of sec. 23, not monumented.
39.68	The $C\frac{1}{4}$ sec. cor. of sec. 23.
49.763	Point for the C-E-W 1/64 sec. cor. of sec. 23, not monumented.

Survey, Partial Subdivision, Sec. 23, T. 9 N., R. 23 E.

CHAINS	
58.70	Track road, bears SE. and NW.
59.846	Point for the C-W 1/16 sec. cor. of sec. 23, not monumented.
63.90	Gravel road, bears N. 17°E. and S. 17° W.
80.01	The 1/4 sec. cor. of secs. 22 and 23.
	Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.
	Subdivision, NE 1/4 Sec. 23
	From the point for the C-E 1/16 sec. cor. of sec. 23. North, on the N. and S. center line of the NE 1/4 sec. 23.
	Over gently rolling land, through dense timber.
10.075	Point for the C-S-NE 1/64 sec. cor. of sec. 23, not monumented.
20.15	Point for the NE 1/16 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the NE 1/4 sec. 25, not monumented.
20.20	Elk Springs Draw, 80 lks. wide, 2 ft. deep, drains N. 80° W.
30.23	Point for the C-N-NE 1/64 sec. cor. of sec. 23, not monumented.
40.31	The point for the E 1/16 sec. cor. of secs. 14 and 23.
	From the point for the N 1/16 sec. cor. of secs. 23 and 24.
	N. 89°52' W., on the E. and W. center line of the NE 1/4 sec. 23.
	Over gently rolling land, through dense timber.
19.90	Elk Springs Draw, 80 lks. wide, 2 ft. deep, drains westerly.
19.954	The point for the NE 1/16 sec. cor. of sec. 23.
29.93	Point for the C-W-NE 1/64 sec. cor. of sec. 23, not monumented.
34.80	Old fence line, bears N. and S.; enter meadow.
34.92	Point for the C-W-W-NE 1/256 sec. cor. of sec. 23, not monumented.
39.91	The point for the C-N 1/16 sec. cor. of sec. 23.

Survey, Partial Subdivision, Sec. 23, T. 9 N., R. 23 E.

CHAINS	
<p>10.085</p> <p>15.125</p> <p>20.165</p>	<p>From the point for the C-W-E 1/64 sec. cor. of sec. 23. N. 0°11' W., on the N. and S. center line of the SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>Point for the SW-NE 1/64 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23, not monumented.</p> <p>Point for the C-N-SW-NE 1/256 sec. cor. of sec. 23, not monumented.</p> <p>The point for the C-W-NE 1/64 sec. cor. of sec. 23.</p>
<p>9.95</p> <p>14.925</p> <p>19.90</p>	<p>From the point for the C-S-NE 1/64 sec. cor. of sec. 23. N. 89°56' W., on the E. and W. center line, of the SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>The point for the SW-NE 1/64 sec. cor. of sec. 23.</p> <p>Point for the C-W-SW-NE 1/256 sec. cor. of sec. 23, not monumented.</p> <p>The point for the C-S-N 1/64 sec. cor. of sec. 23.</p>
<p>3.50</p> <p>5.05</p> <p>10.10</p>	<p>From the point for the C-W-SW-NE 1/256 sec. cor. of sec. 23.</p> <p>N. 0°15' W., on the N. and S. center line of the NW$\frac{1}{4}$SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>Enter open meadow, edge bears NW. and SE.</p> <p>Point for the NW-SW-NE 1/256 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the NW$\frac{1}{4}$SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S23 NW-SW-NE <u>1</u> 256 1967</p> <p>Set a wooden post, 3 ins. square, 3$\frac{1}{2}$ ft. long, alongside the iron post.</p> <p>The point for the C-W-W-NE 1/256 sec. cor. of sec. 23.</p>
<p>4.00</p> <p>4.98</p> <p>6.00</p> <p>9.96</p>	<p>From the point for the C-N-SW-NE 1/256 sec. cor. of sec. 23.</p> <p>N. 89°54'30" W., on the E. and W. center line of the NW$\frac{1}{4}$SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>Enter open meadow, edge bears N. and S.</p> <p>The NW-SW-NE 1/256 sec. cor. of sec. 23.</p> <p>Enter moderate timber, edge bears NW. and SE.</p> <p>The point for the C-N-S-N 1/256 sec. cor. of sec. 23.</p>
	<p>From the point for the C-W-NE 1/64 sec. cor. of sec. 23.</p>

Survey, Partial Subdivision, Sec. 23 T. 9 N., R. 23 E.

CHAINS	
	<p>N. 0°10' W., on the N. and S. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>.70 Elk Springs Draw, 50 lks. wide, 2 ft. deep, drains N. 60° W.</p> <p>5.046 Point for the C-S-NW-NE 1/256 sec. cor. of sec. 23, not monumented.</p> <p>10.092 Point for the NW-NE 1/64 sec. cor. of sec. 23 at the intersection with the E. and W. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23, not monumented.</p> <p>20.188 The point for the W-E 1/64 sec. cor. of secs. 14 and 23.</p>
	<p>From the point for the C-N-NE 1/64 sec. cor. of sec. 23.</p> <p>N. 89°49' W., on the E. and W. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through dense timber.</p> <p>10.01 The point for the NW-NE 1/64 sec. cor. of sec. 23.</p> <p>15.02 Point for the C-W-NW-NW 1/256 sec. cor. of sec. 23, not monumented.</p> <p>18.00 Enter open meadow, edge bears NW. and SE.</p> <p>20.03 The C-N-N 1/64 sec. cor. of sec. 23.</p>
	<p>From the point for the C-W-W-NE 1/256 sec. cor. of sec. 23.</p> <p>N. 0°14' W., on the N. and S. center line of the SW$\frac{1}{4}$NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, across open meadow.</p> <p>4.80 Elk Springs Draw, 40 lks. wide, 1 ft. deep, drains N. 30° W.</p> <p>5.05 Point for the SW-NW-NE 1/256 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S23 SW-NW-NE 1 256 1967</p> <p>Set a wooden post, 4 ins. square, 3 ft. long, alongside the iron post.</p> <p>6.40 Old fence line, bears S. 60° E. and N. 60° W.; enter moderate timber.</p> <p>10.10 The point for the C-W-NW-NE 1/256 sec. cor. of sec. 23.</p>
	<p>From the point for the C-S-NW-NE 1/256 sec. cor. of sec. 23.</p> <p>N. 89°47' W., on the E. and W. center line of the SW$\frac{1}{4}$NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>4.99 The SW-NW-NE 1/256 sec. cor. of sec. 23.</p> <p>5.30 Elk Springs Draw, 40 lks. wide, 1 ft. deep, drains N. 30° W.</p>

Survey, Partial Subdivision, Sec. 23, T. 9 N., R. 23 E.

CHAINS	
9.98	The C-S-N-N 1/256 sec. cor. of sec. 23.
Subdivision, NW $\frac{1}{4}$ Sec. 23	

From the point for the C-W 1/16 sec. cor. of sec. 23. N. 0°14' W., on the N. and S. center line of the NW $\frac{1}{4}$ sec. 23.	
Over gently rolling land, through dense timber.	
.90	Track road, bears SE. and NW.
7.10	Track road, bears W. and E., 34 lks.; thence NE.
10.11	Point for the C-S-NW 1/64 sec. cor. of sec. 23, not monumented.
15.60	Power line, bears E. and W.
20.22	Point for the NW 1/16 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ sec. 23, not monumented.
30.33	Point for the C-N-NW 1/64 sec. cor. of sec. 23, not monumented.
34.30	S. rim of Elk Springs Draw, bears E. and N. 60° W.; desc. N. slope.
35.385	Point for the C-N-N-NW 1/256 sec. cor. of sec. 23, not monumented.
38.60	Wash in bottom of Elk Springs Draw, 30 lks. wide, 2 ft. deep, drains N. 70° W.; asc. S. slope.
40.44	The point for the W 1/16 sec. cor. of secs. 14 and 23.
From the point for the C-N 1/16 sec. cor. of sec. 23.	
N. 89°55' W., on the E. and W. center line of the NW $\frac{1}{4}$ sec. 23.	
Over gently rolling land, through open meadow.	
4.90	Fence, bears N. 75° E. and S. 75° W.; enter dense timber, edge bears SE. and NW.
7.90	Fence, bears S. 5° E. and N. 5° W.
10.07	Point for the C-E-NW 1/64 sec. cor. of sec. 23, not monumented.
20.14	The point for the NW 1/16 sec. cor. of sec. 23.
27.10	Gravel road, bears S. 18° E. and N. 18° W.
40.25	The point for the N 1/16 sec. cor. of secs. 22 and 23.
From the point for the C-E-W 1/64 sec. cor. of sec. 23.	
N. 0°17'30" W., on the N. and S. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 23.	
Over gently rolling land, through moderate timber.	
10.11	Point for the SE-NW 1/64 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 23 not monumented.
14.60	Track road, bears N. 80° E. and S. 80° W.
15.165	Point for the C-N-SE-NW 1/256 sec. cor. of sec. 23.
Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.	

Survey, Partial Subdivision, Sec. 23, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">S23 C-N-SE-NW <u>1</u> 256 1967</p> <p>15.60 Fence cor., fences bear N. 1° E. and E.</p> <p>15.90 Power line, bears E. and W.</p> <p>18.80 Fence cor., bears East, 17 lks. dist., fences bear E. and S. 1° W.</p> <p>20.22 The point for the C-E-NW 1/64 sec. cor. of sec. 23.</p>
	<p>From the point for the C-S-N 1/64 sec. cor. of sec. 23. N. 89°57'30" W., on the E. and W., center line of the SE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 23.</p> <p>Over nearly level land, through moderate timber.</p> <p>10.083 The point for the SE-NW 1/64 sec. cor. of sec. 23.</p> <p>16.40 Track road, bears SW. and NE.</p> <p>20.166 The point for the C-S-NW 1/64 sec. cor. of sec. 23.</p>
	<p>From the point for the C-E-NW 1/64 sec. cor. of sec. 23. N. 0°16'30" W., on the N. and S. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>10.10 Point for the NE-NW 1/64 sec. cor. of sec. 23, at the intersection with the E. and W. center line at the NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 23.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S23 NE-NW <u>1</u> 6 4 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 34° E., 36 lks. dist., fences bear irregularly S. and W.</p> <p>10.90 Enter open meadow, edge bears E. and NW.</p> <p>12.80 Elk Springs Draw, 40 lks. wide, 2 ft. deep, drains W.</p> <p>15.154 Point for the C-N-NE-NW 1/256 sec. cor. of sec. 23, not monumented.</p> <p>15.80 Old fence line, bears E. and W.; enter moderate timber.</p> <p>20.208 The point for the E-W 1/64 sec. cor. of secs. 14 and 23.</p>
	<p>From the C-N-N 1/64 sec. cor. of sec. 23. N. 89°53' W., on the E. and W. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, across open meadow.</p> <p>.40 Elk Springs Draw, 30 lks. wide, 2 ft. deep, drains N. 80° W.</p> <p>5.031 Point for the C-E-NE-NW 1/256 sec. cor. of sec. 23.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>

Survey, Partial Subdivision, Sec. 23, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">S23 C-E-NE-NW $\frac{1}{256}$ 1967</p> <p>Set a wooden post 3 ins. square, 4 ft. long, alongside the iron post.</p> <p>8.60 Enter moderate timber, edge bears NW. and SE.</p> <p>10.063 The NE-NW 1/64 sec. cor. of sec. 23.</p> <p>15.096 Point for the C-W-NE-NW 1/256 sec. cor. of sec. 23.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S23 C-W-NE-NW $\frac{1}{256}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 55½° E., 20 lks. dist.; fences bear N. and E.</p> <p>20.13 The point for the C-N-NW 1/64 sec. cor. of sec. 23.</p>
	<p>From the C-E-NE-NW 1/256 sec. cor. of sec. 23.</p> <p>N. 0°15'30" W., on the N. and S. center line of the NE¼NE¼NW¼ sec. 23.</p> <p>Over gently rolling land, through an open meadow.</p> <p>1.20 Elk Springs Draw, 30 lks. wide, 2 ft. deep, drains N. 80° W.</p> <p>3.30 Enter moderate timber, edge bears NW. and SE.</p> <p>5.05 Point for the NE-NE-NW 1/256 sec. cor. of sec. 23, at the intersection with the E. and W. center line at the NE¼NE¼ sec. 23.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S23 NE-NE-NW $\frac{1}{256}$ 1967</p> <p>5.20 Old fence line, bears SE. and W.</p> <p>7.60 Track road, bears NW. and SE.</p> <p>10.10 The point for the E-E-W 1/256 sec. cor. of secs. 14 and 23.</p>
	<p>From the point for the C-N-N-N 1/256 sec. cor. of sec. 23.</p> <p>N. 89°53' W., on the E. and W. center line of the NE¼NE¼NW¼ sec. 23.</p> <p>Over nearly level land, through moderate timber.</p> <p>4.80 Old fence line, bears NW. and SE.</p> <p>5.03 The NE-NE-NW 1/256 sec. cor. of sec. 23.</p> <p>9.00 Enter open meadow, edge bears NW. and SE.</p> <p>10.06 The point for the C-N-NE-NW 1/256 sec. cor. of sec. 23.</p>
	<p>From the C-W-NE-NW 1/256 sec. cor. of sec. 23.</p>

Survey, Partial Subdivision, Sec. 23, T. 9 N., R. 23 E.

<p>CHAINS</p> <p>2.20</p> <p>2.80</p> <p>5.057</p> <p>5.60</p> <p>7.30</p> <p>10.114</p>	<p>N. 0°13' W., on the N. and S. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, through moderate timber.</p> <p>S. rim of Elk Springs Draw, bears E. and W.</p> <p>Enter open meadow, edge bears NW. and SE.</p> <p>Point for the NW-NE-NW 1/256 sec. cor. of sec. 23, at the intersection with the E. and W. center line of NW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 23.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S23 NW-NE-NW $\frac{1}{256}$ 1967</p> <p>Wash in bottom of Elk Springs draw, 30 lks. wide, 2 ft. deep, drains N. 80° W.</p> <p>Enter moderate timber, edge bears NW. and SE.</p> <p>The point for the W-E-W 1/256 sec. cor. of sec. 14 and 23.</p>
<p>2.50</p> <p>5.03</p> <p>8.00</p> <p>10.064</p>	<p>From the point for the C-N-NE-NW 1/256 sec. cor. of sec. 23.</p> <p>N. 89°51' W., on the E. and W. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 23.</p> <p>Over gently rolling land, across open meadow.</p> <p>Wash, in bottom of Elk Springs Draw, 30 lks. wide, 2 ft. deep, drains N. 80° W.</p> <p>The NW-NE-NW 1/256 sec. cor. of sec. 23.</p> <p>Enter moderate timber, edge bears NW. and SE.</p> <p>The point for the C-N-N-NW 1/256 sec. cor. of sec. 23.</p>
<p>Subdivision, Sec. 2</p>	
<p>40.40</p> <p>50.663</p> <p>60.00</p> <p>60.90</p> <p>60.926</p>	<p>From the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.</p> <p>N. 1°33' W., on the N. and S. center line of sec. 2.</p> <p>Point for the C$\frac{1}{4}$ sec. cor. of sec. 2, at the intersection with the E. and W. center line of sec. 2.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9N R23E C$\frac{1}{4}$ + S 2 1967</p> <p>Point for the C-S-N 1/64 sec. cor. of sec. 2 at proportionate dist., not monumented.</p> <p>Enter open meadow, edge bears E. and W.</p> <p>Fence, bears E. and W.</p> <p>Point for the C-N 1/16 sec. cor. of sec. 2 at proportionate dist., not monumented.</p>

Survey, Partial Subdivision, Sec. 2, T. 9 N., R. 23 E.

CHAINS	
63.10	Power line, bears N. 70° E. and S. 70° W.
63.90	Gravel road, bears N. 70° E. and S. 70° W.
68.50	Enter timber, edge bears E. and W.
71.19	Point for the C-N-N 1/64 sec. cor. of sec. 2 at proportionate dist., not monumented.
81.66	The ¼ sec. cor. of sec. 2 only, on the N. bdy. of the Tp.
	Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.
	From the ¼ sec. cor. of secs. 1 and 2.
	N. 89°18' W., on the E. and W. center line of sec. 2.
	Over gently rolling land, through dense timber.
43.50	The C¼ sec. cor. of sec. 2.
53.625	Point for the C-E-W 1/64 sec. cor. of sec. 2, not monumented.
62.90	Fence, bears N. and S.
63.750	Point for the C-W 1/16 sec. cor. of sec. 2, not monumented.
63.80	Enter open meadow, edge bears N. and S.
78.80	Enter scattered timber, edge bears N. and S.
81.30	Apache Railroad, bears N. 8° E. and S. 8° W.
82.70	Old fence line, bears irregularly N. and S.
84.00	The ¼ sec. cor. of secs. 2 and 3.
	Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.
	<u>Subdivision, NW¼ Sec. 2</u>
	From the point for the C-W 1/16 sec. cor. of sec. 2.
	N. 1°31' W., on the N. and S. center line of the NW¼ sec. 2.
	Over gently rolling land, along the E. edge of a meadow.
10.143	Point for the C-S-NW 1/64 sec. cor. of sec. 2.
	Set the iron post 20 ins. in the ground, brass cap mkd.

Partial Subdivision, Sec. 2, T. 9N., R. 23 E.

CHAINS	Survey,
	<p style="text-align: center;">S 2 C-S-NW $\frac{1}{64}$ 1967</p> <p>from which</p> <p style="text-align: center;">A fence cor., bears N. 80° E., 115 lks. dist., fences bear E. and S.</p> <p>Raise a mound of stone W. of the cor.</p>
16.00	Gravel road, bears N. 70° E. and S. 80° W.
16.90	Power line, bears S. 87° E. and N. 87° W.
17.30	Apache Railroad, bears N. 60° E. and S. 60° W.
20.286	Point for the NW 1/16 sec. cor. of sec. 2, at the intersection with the E. and W. center line of the NW 1/4 sec. 2, not monumented.
30.44	Point for the C-N-NW 1/64 sec. cor. of sec. 2, at proportionate dist., not monumented.
31.40	Fence, bears W. and E., 140 lks., thence E., W. and N. 30° W.
33.90	Fence, bears S. 30° E. and N. 30° W.
38.30	Dike at N. end of stock pond, bears N. 70° E. and S. 70° W.
40.95	The point for the W 1/16 sec. cor. of sec. 2 only, on the bdy. of the Tp.
	<p>From the point for the C-N 1/16 sec. cor. of sec. 2.</p> <p>West, on the E. and W. center line of the NW 1/4 sec. 2.</p> <p>Over gently rolling land, through open meadow, along the N. side of a fence.</p>
3.90	Fence cor. fences bear N., E. and S.
6.80	Power line, bears N. 70° E. and S. 70° W.
7.50	Gravel road, bears N. 70° E. and S. 70° W.
10.115	Point for the C-E-NW 1/64 sec. cor. of sec. 2, not monumented.
15.50	Apache Railroad, on a curve, bears NE. and SW.
20.23	The point for the NW 1/16 sec. cor. of sec. 2.
23.30	Track road, bears N. and S.
29.30	Enter moderate timber, bears N. and S.
30.355	Point for the C-W-NW 1/64 sec. cor. of sec. 2.
	Set the iron post 22 ins. in the ground, brass cap mkd.

Survey, Partial Subdivision, Sec. 2, T. 9 N., R. 23 E.

CHAINS	
40.48	<p style="text-align: center;">S 2 C-W-NW $\frac{1}{64}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears North, 50 lks. dist., fences bear N. and W.</p> <p>Raise a mound of stone N. of the cor.</p> <p>The N 1/16 sec. cor. of secs. 2 and 3.</p>
10.20	<p>From the point for the C-E-W 1/64 sec. cor. of sec. 2.</p> <p>N. 1°32' W., on the N. and S. center line of the SE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 2.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the SE-NW 1/64 sec. cor. of sec. 2, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 2, not monumented.</p>
11.00	<p>Fence, bears E. and W.; enter meadow.</p>
19.30	<p>Power line, bears N. 70° E. and S. 70° W.</p>
19.60	<p>Gravel road, bears N. 70° and S. 70° W.</p>
20.404	<p>The point for the C-E-NW 1/64 sec. cor. of sec. 2.</p>
5.06	<p>From the point for the C-S-N 1/64 sec. cor. of sec. 2.</p> <p>N. 89°40' W., on the E. and W. center line of the SE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 2.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the C-E-SE-NW 1/256 sec. cor. of sec. 2.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S 2 C-E-SE-NW $\frac{1}{256}$ 1967</p> <p>Raise a mound of stone N. of the cor.</p> <p>The cor. is located 92 lks. S. of a fence bearing E. and W.</p>

Survey, Partial Subdivision, Sec. 2, T. 9 N., R. 23 E.

CHAINS	
10.12	The point for the SE-NW 1/64 sec. cor. of sec. 2
19.10	Fence, bears S. and N. for 40 lks.. thence S. and E.; enter meadow.
20.24	The C-S-NW 1/64 sec. cor. of sec. 2.
<hr/>	
From the point for the C-E-NW 1/64 sec. cor. of sec. 2.	
N. 1°31' W., on the N. and S. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 2.	
Over gently rolling land, through an open meadow.	
9.60	Apache Railroad, on a curve, bears NE. and SW.
10.21	Point for the NE-NW 1/64 sec. cor. of sec. 2, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 2, not monumented.
10.90	Fence, bears E. and W.
20.70	The point for the E-W 1/64 sec. cor. of sec. 2, on the N. bdy. of the Tp.
<hr/>	
From the point for the C-N-N 1/64 sec. cor. of sec. 2.	
S. 89°41' W., on the E-W center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 2.	
Over gently rolling land, through moderate timber.	
.60	Leave timber, enter open meadow, edge bears N. and S.
3.40	Track road, bears N. and S.
3.55	Fence, bears N. and S.
5.052	Point for the C-E-NE-NW 1/256 sec. cor. of sec. 2.
Set the iron post 20 ins. in the ground, brass cap mkd.	
<p>S 2 C-E-NE-NW <u>1</u> 256 1967</p>	
from which	
<p>A fence cor., bears N. 70° E., 151 lks. dist., fences bear S. and W.</p>	

Survey, Partial Subdivision, Sec. 2, T. 9 N., R 23 E.

CHAINS	
	Raise a mound of stone N. of the cor.
8.80	Apache Railroad, on a curve, bears N. and SW.
10.105	The point for the NE-NW 1/64 sec. cor. of sec. 2.
20.22	The point for the C-N-NW 1/64 sec. cor. of sec. 2.
	From the C-W-NW 1/64 sec. cor. of sec. 2.
	N. 1°28' W., on the N. and S. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 2.
	Over gently rolling land, across an open meadow.
.50	Fence cor., fences bear N. and W.
10.08	Point for the NW-NW 1/64 sec. cor. of sec. 2, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 2.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	S 2
	NW-NW
	$\frac{1}{64}$
	1967
	Raise a mound of stone W. of the cor.
11.40	Enter moderate timber, edge bears E. and W.
20.585	The point for the W-W 1/64 sec. cor. of sec. 2, on the N. bdy. of the Tp.
	From the point for the C-N-NW 1/64 sec. cor. of sec. 2.
	S. 89°38' W., on the E. and W. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 2.
	Over gently rolling land, across an open meadow.
1.00	Track road, bears N. and S.
9.55	Fence, bears N. and S.
10.12	The NW-NW 1/64 sec. cor. of sec. 2.
10.20	Enter moderate timber, edge bears N. and S.
12.70	Wash, 30 lks. wide, 2 ft. deep, drains N. 30° E.
20.25	Point for the N-N 1/64 sec. cor. of secs. 2 and 3.

Survey, Partial Subdivision, Sec. 34, T. 9 N., R. 23 E.

CHAINS	Subdivision, Sec. 34.
	<p>From the standard $\frac{1}{4}$ sec. cor. of sec. 34, on the S.bdy. of the Tp.</p>
	<p>N. $1^{\circ}16'$ E., on the N. and S. center line of sec. 34.</p>
	<p>Over gently rolling land, through dense timber.</p>
.30	<p>Fence, bears SE. and NW.</p>
5.80	<p>Old railroad bed, bears NE. and SW.</p>
40.77	<p>Point for the $C\frac{1}{4}$ sec. cor. of sec. 34, at the intersection with the E. and W. center line of sec. 34, falls in the center of a pine tree, 7 ins. diam., on which I scribe $C\frac{1}{4}$ S 34 on the W. face.</p>
40.87	<p>Point selected for the witness cor. for the $C\frac{1}{4}$ sec. cor. of sec. 34.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E C $\frac{1}{4}$ + S34 W C 1967</p> </div>
43.10	<p>Track road, bears N. 40° E. and S. 40° W.</p>
60.99	<p>Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 34.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R23E C N $\frac{1}{16}$ S34 C 1967</p> </div>
	<p>from which</p>
	<p>A pine, 4 ins. diam., bears S. 52° E., 10 lks. dist., mkd. CN $\frac{1}{16}$ S34 BT.</p>
64.50	<p>Wash, 30 lks. wide, 2 ft. deep, drains W.</p>
65.00	<p>Power line, bears E. and W. for 50 lks., thence NW.</p>
81.21	<p>The $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p>
	<p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p> <p>S. $89^{\circ}43'$ W., on the E. and W. center line of sec. 34.</p> <p>Over gently rolling land, through dense timber.</p>

Survey, Partial Subdivision, Sec. 34. T. 9 N., R. 23 E.

CHAINS	
20.535	Point for the C-E 1/16 sec. cor. of sec. 34, not monumented.
41.07	The C $\frac{1}{4}$ sec. cor. of sec. 34.
42.30	Dim track road, bears N. 10° E. and S. 10° W.
54.60	Fence, bears N. 12°30' W. and S. 12°30' E.
56.30	Apache Railroad, bears N. 12°30' W. and S. 12°30' E.
57.00	Gravel road, bears N. 12°30' W. and S. 12°30' E.
57.30	Power line, bears N. 12°30' W. and S. 12°30' E.
81.32	The $\frac{1}{4}$ sec. cor. of secs. 33 and 34.
	Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.
	Subdivision, NE $\frac{1}{4}$ Sec. 34.
	From the point for the C-E 1/16 sec. cor. of sec. 34. N. 0°36'30" E., on the N. and S. center line of the NE $\frac{1}{4}$ sec. 34.
	Over gently rolling land, through dense timber.
20.135	Point for the NE 1/16 sec. cor. of sec. 34, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ sec. 34, not monumented.
23.70	Fence, bears E. and W.; enter an open meadow.
24.20	Bladed road, bears E. and W.
24.30	Power line, bears E. and W.
31.50	Wash, 30 lks. wide, 6 ins. deep, drains S. 70° W.
40.28	The point for the E 1/16 sec. cor. of secs. 27 and 34.
	From the N 1/16 sec. cor. of secs. 34 and 35.
	S. 89°56' W., on the E. and W. center line of the NE $\frac{1}{4}$ sec. 34.
	Over gently rolling land, through dense timber.
5.08	Point for the C-E-E-NE 1/256 sec. cor. of sec. 34.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	S34 C-E-E-NE 1 256 1967

Survey, Partial Subdivision, Sec. 34, T. 9 N., R. 23 E.

CHAINS		
	<p>from which</p> <p>A local cor., a re-bar $\frac{1}{2}$ in. diam., bears N. $89^{\circ}19'$ E., 33.6 lks. dist.</p>	
20.32	The point for the NE $\frac{1}{16}$ sec. cor. of sec. 34.	
28.00	Track road, bears N. and S.	
35.55	<p>Point for the C-W-W-NE $\frac{1}{256}$ sec. cor. of sec. 34.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S34 C-W-W-NE $\frac{1}{256}$ 1967</p>	
	<p>from which</p> <p>A local cor., a re-bar, $\frac{1}{2}$ in. diam., bears S. $49^{\circ}49'$ E., 71.5 lks. dist.</p>	
40.63	The C-N $\frac{1}{16}$ sec. cor. of sec. 34.	
	<p>Subdivision, SE$\frac{1}{4}$ Sec. 27</p> <hr/> <p>The subdivision in the SE$\frac{1}{4}$ sec. 27 was surveyed on courses and distances calculated to delineate the SW$\frac{1}{4}$SE$\frac{1}{4}$SE$\frac{1}{4}$SE$\frac{1}{4}$, S$\frac{1}{2}$SW$\frac{1}{4}$SE$\frac{1}{4}$SE$\frac{1}{4}$, S$\frac{1}{2}$SE$\frac{1}{4}$SW$\frac{1}{4}$SE$\frac{1}{4}$ and SE$\frac{1}{4}$SW$\frac{1}{4}$SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 27.</p> <p>From the E-E-E $\frac{1}{256}$ sec. cor. of secs. 27 and 34.</p> <p>N. $1^{\circ}19'$ W., on a calculated course and distance.</p> <p>Over gently rolling land, through dense timber.</p>	
2.00	Wash, 30 lks. wide, 2 ft. deep, drains SW.	
5.025	<p>Point for the SE-SE-SE $\frac{1}{256}$ sec. cor. of sec. 27.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S27 SE-SE-SE $\frac{1}{256}$ 1967</p>	
	<p>from which</p> <p>A local cor., a re-bar, $\frac{1}{2}$ in. diam., bears S. $4^{\circ}46'$ E., 13 lks. dist.</p>	
30.218	<p>N. $89^{\circ}54'$ W., on a calculated course and distance.</p> <p>Point for the SW-SW-SE $\frac{1}{256}$ sec. cor. of sec. 27.</p>	

Survey, Partial Subdivision, Sec. 27, T. 9 N., R. 23 E.

CHAINS	
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S27 SW-SW-SE <u>1</u> 256 1967</p> <p>from which</p> <p style="text-align: center;">A local cor., a re-bar, ½ in. diam., bears S. 1°27' W., 67 lks. dist.</p> <p>The cor. is located alongside a pine stump, 16 ins. diam.</p>
<p>3.30</p> <p>5.015</p>	<p>S. 2°14' E., on a calculated course and distance.</p> <p>Madison Meadows road, bears SE. and NW.</p> <p>The W-W-E 1/256 sec. cor. of secs. 27 and 34.</p>
	<p>Subdivision, Sec. 22</p>
<p>10.035</p> <p>20.07</p> <p>25.088</p> <p>30.105</p> <p>30.70</p> <p>40.14</p>	<p>From the ¼ sec. cor. of secs. 22 and 27.</p> <p>N. 0°15' W., on the N. and S. center line of sec. 22.</p> <p>Over nearly level land, through dense timber.</p> <p>Point for the C-S-S 1/64 sec. cor. of sec. 22, not monumented.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 22, not monumented.</p> <p>Point for the C-S-N-S 1/256 sec. cor. of sec. 22, not monumented.</p> <p>Point for the C-N-S 1/64 sec. cor. of sec. 22, not monumented.</p> <p>Track road, bears irregularly SE. and NW.</p> <p>Point for the C¼ sec. cor. of sec. 22, at the intersection with the E. and W. center line of sec. 22.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">C ¼+ S22 1967</p> <p>from which</p> <p style="text-align: center;">A local cor., bears N. 89°23' E., 149 lks. dist., monumented by a water pipe firmly set with a cap, 2 ins. diam., mkd. T9NR23E CEN 22 4128.</p>

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS		
	<p>Raise a mound of stone W. of cor.</p>	
45.19	<p>Point for the C-S-S-N 1/256 sec. cor. of sec. 22.</p>	
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">S22 C-S-S-N $\frac{1}{256}$ 1967</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A local cor., bears S. 87°01' E., 130 lks. dist., monumented by a water pipe, 3/4 in. diam., projecting 2 ins. above the ground.</p>	
	<p style="padding-left: 40px;">An old fence cor., bears S. 39° E., 22 lks. dist., fences bear N. and S. 32° E.</p>	
47.30	<p>Drainage ditch, 30 lks. wide, 4 ft. deep, drains NW.</p>	
50.24	<p>Point for the C-S-N 1/64 sec. cor. of sec. 22, not monumented.</p>	
60.25	<p>Fence, bears E. and W.</p>	
60.34	<p>Point for the C-N 1/16 sec. cor. of sec. 22.</p>	
	<p>Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.</p>	
	<p style="text-align: center;">C N $\frac{1}{16}$ S22 C 1967</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A local cor., bears S. 82°34' E., 73 lks. dist., monumented by a water pipe, 3/4 in. diam., set alongside a fence cor., fences bear E., S. 2° E., W. and N. 2° W.</p>	
	<p>Raise a mound of stone W. of the cor.</p>	
69.00	<p>Wash, 30 lks. wide, 2 ft. deep, drains N. 25° E.</p>	
80.54	<p>The 1/4 sec. cor. of secs. 15 and 22.</p>	
	<p>Land, nearly level. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
	<p>From the 1/4 sec. cor. of secs. 22 and 23.</p>	
	<p>N. 89°46' W., on the E. and W. center line of sec. 22.</p>	
	<p>Over gently rolling land, through dense timber.</p>	
10.07	<p>Point for the C-E-E 1/64 sec. cor. of sec. 22.</p>	

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS

Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.

S22
C-E-E
 $\frac{1}{64}$
1967

from which

A local cor., bears S. 78° 30' E., 42 lks. dist., monumented by a water pipe, 3/4 in. diam., projecting 2 ins. above the ground.

Raise a mound of stone S. of the cor.

15.105 Point for the C-W-E-E 1/256 sec. cor. of sec. 22.

Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.

S22
C-W-E-E
 $\frac{1}{256}$
1967

from which

A local cor., bears S. 82°35' E., 60 lks. dist., monumented by a water pipe, 3/4 in. diam., projecting 2 ins. above the ground.

17.00 Power line, bears N. and S.

17.20 Gravel road, bears N. and S.

17.30 Enter open meadow, edge bears N. and S.

20.14 Point for the C-E 1/16 sec. cor. of sec. 22, not monumented.

27.30 Track road, bears N. and S.

28.40 Apache Railroad, bears S. 5° E. and N. 5° W.

29.00 Drainage ditch, 20 lks. wide, 2 ft. deep, drains N.

29.10 Power line, bears N. and S.

30.21 Point for the C-W-E 1/64 sec. cor. of sec. 22, not monumented.

31.70 Bladed road, bears N. and S.

35.245 Point for the C-W-W-E 1/256 sec. cor. of sec. 22, not monumented.

36.40 Enter dense timber, edge bears N. and S.

37.40 Fence, bears SE. and NW.

38.80 New fence, bears S. 2°30' E. and N. 2°30' W.

40.28 The C $\frac{1}{4}$ sec. cor. of sec. 22.

49.90 Track road, bears irregularly SE. and NW.

survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
80.60	<p>The $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass and scrub oak.</p>
<p>Subdivision, SE$\frac{1}{4}$ Sec. 22</p> <hr/>	
	<p>From the point for the E $\frac{1}{16}$ sec. cor. of secs. 22 and 27.</p>
	<p>N. $0^{\circ}21'$ W., on the N. and S. center line of the SE$\frac{1}{4}$ sec. 22.</p>
	<p>Over gently rolling land, through dense timber.</p>
2.00	<p>Graded road, bears NE. and SW.; enter moderate timber.</p>
10.02	<p>Point for the C-S-SE $\frac{1}{64}$ sec. cor. of sec. 22, not monumented.</p>
12.70	<p>Comanche Drive, a graded road, bears E. and W.; enter open meadow.</p>
13.00	<p>Power line, bears E. and W.</p>
18.10	<p>Street, bears E. and W.</p>
20.04	<p>Point for the SE $\frac{1}{16}$ sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$ sec. 22.</p>
20.50	<p>Drainage ditch, 25 lks. wide, 3 ft. deep, drains N. 55° W.</p>
22.70	<p>Aztec Circle, a graded street, bears E. and W.</p>
25.05	<p>Point for the C-S-N-SE $\frac{1}{256}$ sec. cor. of sec. 22, not monumented.</p>
27.70	<p>Street, bears E. and W.</p>
30.06	<p>Point for the C-N-SE $\frac{1}{64}$ sec. cor. of sec. 22, not monumented.</p>
32.70	<p>Street, bears E. and W.</p>
33.20	<p>South end of pond, 4 chs. long and 4 chs. wide.</p>
38.80	<p>Street, bears E. and W.</p>
40.08	<p>Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 22.</p>
<p>From the point for the S $\frac{1}{16}$ sec. cor. of secs. 22 and 23.</p>	
	<p>N. $89^{\circ}54'$ W., on the E. and W. center line of the SE$\frac{1}{4}$ sec. 22.</p>
	<p>Over gently rolling land, through dense timber.</p>
5.04	<p>Point for the C-E-E-SE $\frac{1}{256}$ sec. cor. of sec. 22, not monumented.</p>

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
10.08	Point for the C-E-SE 1/64 sec. cor. of sec. 22, not monumented.
11.30	Enter open meadow, edge bears NW. and SE.
13.50	Aztec Circle, bears N. and S.
15.12	Point for the C-W-E-SE 1/256 sec. cor. of sec. 22, not monumented.
18.20	Drainage ditch, 20 lks. wide, 2 ft. deep, drains N. 55° W.
18.40	Power line, bears N. and S.
18.90	Comanche Drive, bears N. and S.
20.16	The point for the SE 1/16 sec. cor. of sec. 22.
24.90	Street, bears N. and S.; enter timber.
25.20	<p>Point for the C-E-W-SE 1/256 sec. cor. of sec. 22.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S22 C-E-W-SE $\frac{1}{256}$ 1967</p>
27.00	Apache Railroad, bears S. 5° E. and N. 5° W.
27.50	Track road, bears S. 5° E. and N. 5° W.
27.70	Power line, bears S. 5° E. and N. 5° W.
30.24	<p>Point for the C-W-SE 1/64 sec. cor. of sec. 22.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S22 C-W-SE $\frac{1}{64}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A local cor., bears S. 85°40' E., 169 lks. dist., monumented by a water pipe, 1 in. diam.</p>
35.28	Point for the C-W-W-SE 1/256 sec. cor. of sec. 22, not monumented.
40.32	The point for the C-S 1/16 sec. cor. of sec. 22.
	<p>From the point for the E-E 1/64 sec. cor. of secs. 22 and 27.</p> <p>N. 0°24' W., on the N. and S. center line of the SE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over rolling land, through dense timber.</p>

Survey, Partial Subdivision, Sec. 22, T. 9, N., R. 23 E.

CHAINS	
8.20	Gravel road, bears N. 80° E. and S. 80° W.
10.03	Point for the SE-SE 1/64 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 22, not monumented.
10.05	Intersect the E. portions of the S. side of a cabin, in the SKY-HI RETREAT Subdivision.
12.10	Street, bears E. and W.; enter open meadow.
12.40	Power line, bears E. and W.
15.04	Point for the C-N-SE-SE 1/256 sec. cor. of sec. 22. Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">S22 C-N-SE-SE $\frac{1}{256}$ 1967</p>
	from which
	<p style="text-align: center;">A local cor., bears S. 73°46' E., 63 lks. dist., monumented by a water pipe, 1 in. diam.</p>
	Set a wooden post 3 ft. long, 3 ins. diam., alongside the iron post.
16.00	Wash, 25 lks. wide, 3 ft. deep, drains N. 55° W.
16.50	Enter dense timber, edge bears E. and W.
20.05	The point for the C-E-SE 1/64 sec. cor. of sec. 22.
	From the point for the S-S 1/64 sec. cor. of secs. 22 and 23.
	N. 89°59' W., on the E. and W. center line of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 22.
	Over gently rolling land, through dense timber.
1.40	Graded road, bears N. 80° E. and S. 80° W.
2.80	Graded road, bears N. 55° E. and S. 55° W., 50 lks., to intersection.
5.05	Point for the C-E-SE-SE 1/256 sec. cor. of sec. 22. Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">S22 C-E-SE-SE $\frac{1}{256}$ 1967</p>
	from which
	<p style="text-align: center;">A pine, 6 ins. diam., bears S. 29$\frac{1}{2}$° E., 24 lks. dist., mkd. C E SE SE 1/256 S22 BT.</p>

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
	<p>A local cor., bears S. 56°10' E., 38 lks. dist., monumented by a water pipe 1 in. diam.</p> <p>7.80 Intersect the S. portion of the E. side of a building (Office), in the SKY-HI-RETREAT, a private subdivision.</p> <p>9.00 Entrance road to SKY-HI-RETREAT, bears N. and S.</p> <p>10.10 The point for the SE-SE 1/64 sec. cor. of sec. 22.</p> <p>20.19 The point for the C-S-SE 1/64 sec. cor. of sec. 22.</p>
	<p>From the C-E-SE-SE 1/256 sec. cor. of sec. 22.</p> <p>N.0°25' W., on the N. and S. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p> <p>2.80 Old fence line, bears E. and W.</p> <p>4.50 Wash, 30 lks. wide, 2 ft. deep, drains W.</p> <p>5.00 Point for the NE-SE-SE 1/256 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S22 NE-SE-SE <u>1</u> 256 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 44 3/4° E., 19 lks. dist., mkd. NE SE SE 1/256 S22 BT.</p> <p>10.00 The point for the C-E-E-SE 1/256 sec. cor. of sec. 22.</p>
	<p>From the point for the N-S-S 1/256 sec. cor. of secs. 22 and 23.</p> <p>West, on the E. and W. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over nearly level land.</p> <p>5.04 The NE-SE-SE 1/256 sec. cor. of sec. 22.</p> <p>7.20 Wash, 25 lks. wide, 3 ft. deep, drains N. 80° W.</p> <p>10.08 The C-N-SE-SE 1/256 sec. cor. of sec. 22.</p>
	<p>From the point for the C-E-SE 1/64 sec. cor. of sec. 22.</p> <p>N. 0°25' W., on the N. and S. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p> <p>5.01 Point for the C-S-NE-SE 1/256 sec. cor. of sec. 22.</p>

Survey, Partial Subdivision, Sec. 22 T. 9 N., R. 23 E.

CHAINS		
10.02	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S22 C-S-NE-SE $\frac{1}{256}$ 1967</p> <p>Raise a mound of stone W. of the cor.</p> <p>Point for the NE-SE 1/64 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22, not monumented.</p>	
20.04	<p>The C-E-E 1/64 sec. cor. of sec. 22.</p> <hr/> <p>From the point for the N-S 1/64 sec. cor. of secs. 22 and 23.</p> <p>N. 89°49' W., on the E. and W. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p> <p>10.07 The point for the NE-SE 1/64 sec. cor. of sec. 22.</p> <p>15.105 Point for the C-W-NE-SE 1/256 sec. cor. of sec. 22, not monumented.</p> <p>17.40 Power line, bears N. and S.; enter meadow.</p> <p>17.70 Comanche Drive, bears N. and S.</p> <p>20.14 The point for the C-N-SE 1/64 sec. cor. of sec. 22.</p>	
10.02	<p>From the point for the C-W-E-SE 1/256 sec. cor. of sec. 22.</p> <p>N. 0°25' W., on the N. and S. center line of the SW$\frac{1}{4}$NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through an open meadow.</p> <p>1.90 Power line, bears E. and W.</p> <p>2.20 Aztec Circle, bears E. and W.; enter moderate timber.</p> <p>5.01 Point for the SW-NE-SE 1/256 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S22 SW-NE-SE $\frac{1}{256}$ 1967</p> <p>Set a wooden post, 5 ft. long, 4 ins. diam., alongside the iron post.</p> <p>The point for the C-W-NE-SE 1/256 sec. cor. of sec. 22.</p>	

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
<p>4.60</p> <p>5.04</p> <p>7.80</p> <p>8.20</p> <p>10.08</p>	<p>From the C-S-NE-SE 1/256 sec. cor. of sec. 22.</p> <p>N. 89°52' W., on the E. and W. center line of the SW$\frac{1}{4}$ NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p> <p>Enter open meadow, edge bears N. and S.</p> <p>The SW-NE-SE 1/256 sec. cor. of sec. 22.</p> <p>Power line, bears N. and S.</p> <p>Comanche Drive, bears N. and S.</p> <p>The point for the C-S-N-SE 1/256 sec. cor. of sec. 22.</p>
<p>10.03</p> <p>20.06</p>	<p>From the point for the W-E 1/64 sec. cor. of secs. 22 and 27.</p> <p>N. 0°18'30"., on the N. and S. center line of the SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the SW-SE 1/64 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22, not monumented.</p> <p>The C-W-SE 1/64 sec. cor. of sec. 22.</p>
<p>5.045</p> <p>6.20</p> <p>6.80</p> <p>6.90</p> <p>10.09</p> <p>20.18</p>	<p>From the point for the C-S-SE 1/64 sec. cor. of sec. 22.</p> <p>N. 89°53'30" W., on the E. and W. center line of the SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the C-E-SW-SE 1/256 sec. cor. of sec. 22.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S22 C-E-SW-SE <u>1</u> 256 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 61° W., 25 lks. dist., mkd. C E SW SE 1/256 S22 BT.</p> <p>Apache Railroad, bears S. 5° E. and N. 5°W.</p> <p>Track road, bears S. 5° E. and N. 5° W.</p> <p>Power line, bears S. 5° E. and N. 5° W.</p> <p>The point for the SW-SE 1/64 sec. cor. of sec. 22.</p> <p>The point for the C-S-S 1/64 sec. cor. of sec. 22.</p>

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
	From the C-W-SE 1/64 sec. cor. of sec. 22.
	N. 0°19' W., on the N. and S. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 22.
	Over gently rolling land, through dense timber.
3.10	Track road, bears S. 30° E. and N. 30° W.
5.01	Point for the C-S-NW-SE 1/256 sec. cor. of sec. 22.
	Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
	S22
	C-S-NW-SE
	<u>1</u>
	256
	1967
	Raise a mound of stone W. of the cor.
5.20	Enter open meadow, edge bears SE. and NW.
7.50	Street, bears E. and W.
10.02	Point for the NW-SE 1/64 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 22, not monumented.
20.05	The point for the C-W-E 1/64 sec. cor. of sec. 22.
	From the point for the C-N-SE 1/64 sec. cor. of sec. 22.
	N. 89°47' W., on the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 22.
	Over nearly level land, through an open meadow.
6.40	Street, bears N. and S.
7.50	Apache Railroad, bears S. 5° E. and N. 5° W.
8.20	Drainage ditch, 40 lks. wide, 3 ft. deep, drains N.
8.50	Power line, bears S. 5° E. and N. 5° W.
10.08	The point for the NW-SE 1/64 sec. cor. of sec. 22.
11.20	Street, bears N. and S.
14.50	Enter dense timber, edge bears N. and S.
15.12	Point for the C-W-NW-SE 1/256 sec. cor. of sec. 22, not monumented.
19.56	Track road, bears irreg. SE. and NW.
20.16	The point for the C-N-S 1/64 sec. cor. of sec. 22.
	From the point for the C-W-W-SE 1/256 sec. cor. of sec. 22.
	N. 0°17'30" W., on the N. and S. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 22.
	Over nearly level land, through dense timber.
5.01	Point for the SW-NW-SE 1/256 sec. cor. of sec. 22, at the

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
	<p>intersection with the E. and W. center line of the SW$\frac{1}{4}$NW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S22 SW-NW-SE $\frac{1}{256}$ S22 BT. 1967</p> <p>from which</p> <p style="text-align: center;">A pine, 8 ins. diam., bears S. 65$\frac{1}{2}$° W., 22 lks. dist., mkd. SW-NW-SE 1/256 S22 BT.</p>
7.10	Track road, bears E. and W.
10.02	The point for the C-W-NW-SE 1/256 sec. cor. of sec. 22.
	<p>From the C-S-NW-SE 1/256 sec. cor. of sec. 22.</p> <p>N. 89°48'30" W., on the E. and W. center line of the SW$\frac{1}{4}$NW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 22.</p> <p>Over nearly level land, through dense timber.</p>
1.50	Track road, bears NW. and SE.
5.045	The SW-NW-SE 1/256 sec. cor. of sec. 22.
10.09	The point for the C-S-N-S 1/256 sec. cor. of sec. 22.
	<p>Subdivision, NE$\frac{1}{4}$ Sec. 22</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the C-E 1/16 sec. cor. of sec. 22.</p> <p>N. 0°10' W., on the N. and S. center line of the NE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through an open meadow.</p>
2.60	Apache Lane, bears E. and W.
7.50	Bonanza Road, bears E. and W.
7.80	Power line, bears E. and W.
9.00	Enter dense timber, edge bears E. and W.
10.00	Power line, bears E. and W.
10.11	Point for the C-S-NE 1/64 sec. cor. of sec. 22.
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S22 C-S-NE $\frac{1}{64}$ S22 BT. 1967</p> <p>from which</p>

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
	<p>A local cor., bears S. 82° E., 57 lks. dist., monumented by a water pipe 1 in. diam.</p>
15.165	<p>Point for the C-N-S-NE 1/256 sec. cor. of sec. 22.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">S22 C-N-S-NE <u>1</u> 256 1967</p>
	<p>from which</p> <p>A local cor., bears S. 79°44' E., 46½ lks. dist., monumented by a water pipe 1 in. diam.</p>
20.22	<p>Point for the NE 1/16 sec. cor. of sec. 22, at the inter- section with the E. and W. center line of the NE¼ sec. 22, not monumented.</p>
40.44	<p>The point for the E 1/16 sec. cor. of secs. 15 and 22.</p>
	<p>From the point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>N. 89°52' W., on the E. and W. center line of the NE¼ sec. 22.</p>
	<p>Over gently rolling land, through dense timber.</p>
10.07	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 22, not monumented.</p>
20.14	<p>The point for the NE 1/16 sec. cor. of sec. 22.</p>
29.60	<p>Track road, bears N. and S.</p>
29.80	<p>Apache Railroad, bears S. 5° E. and N. 5° W.</p>
30.10	<p>Track road, bears S. 5° E. and N. 5° W.</p>
30.22	<p>Point for the C-W-NE 1/64 sec. cor. of sec. 22.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">S22 C-W-NE <u>1</u> 64 1967</p>
	<p>from which</p> <p>A local cor., bears S. 81°42' E., 56 lks. dist., monumented by a water pipe, 1 in. diam.</p>
30.60	<p>Intersect pole at N. end of power line bearing S.</p>
31.60	<p>Fence bears N. and S.</p>
40.30	<p>The C-N 1/16 sec. cor. of sec. 22.</p>

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
.50	<p>From the C-E-E 1/64 sec. cor. of sec. 22.</p> <p>N. 0°08' W., on the N. and S. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p> <p>Track road, bears E. and W.</p>
10.115	<p>Point for the SE-NE 1/64 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ sec. 22.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S22 SE-NE $\frac{1}{64}$ 1967</p> <p>from which</p> <p style="padding-left: 40px;">A local cor., bears S. 73°42' E., 31 lks. dist., monumented by a water pipe, 1 in. diam.</p>
14.70	<p>Power line, bears S. 60° W. and N. 60° E. for 50 lks., thence E.</p>
20.23	<p>The point for the C-E-NE 1/64 sec. cor. of sec. 22.</p>
10.07	<p>From the point for the S-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>N. 89°49' W., on the E. and W. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ sec. 22.</p> <p>Over gently rolling land, through dense timber.</p>
15.30	<p>The SE-NE 1/64 sec. cor. of sec. 22.</p>
19.10	<p>The NE. cor. of a house, bears South, 29 lks. dist.</p>
19.10	<p>Power line, bears N. 60° E. and S. 60° W. for 20 lks., thence W.</p>
20.14	<p>The C-S-NE 1/64 sec. cor. of sec. 22.</p>
4.50	<p>From the point for the C-W-E 1/64 sec. cor. of sec. 22.</p> <p>N. 0°12' W., on the N. and S. center line of the SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 22.</p> <p>Over nearly level land, through an open meadow.</p>
5.05	<p>Drainage ditch, 30 lks. wide, 3 ft. deep, drains N. 85° W.</p>
5.05	<p>Point for the C-S-SW-NE 1/256 sec. cor. of sec. 22, not monumented.</p>

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
10.10	Point for the SW-NE 1/64 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 22, not monumented.
11.60	Track road, curving N. and W.
15.15.	Point for the C-N-SW-NE 1/256 sec. cor. of sec. 22. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	S22 C-N-SW-NE <u>1</u> 256 1967
	from which A local cor., bears N. 21°19' W., 9 lks. dist., monumented by a water pipe, 1 in. diam.
20.20	The C-W-NE 1/64 sec. cor. of sec. 22.
	From the C-S-NE 1/64 sec. cor. of sec. 22.
	N. 89°49' W., on the E. and W. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 22.
	Over gently rolling land, through dense timber.
2.10	Street, bears N. and S.
2.40	Power line, bears N. and S.
9.00	Apache Railroad, bears S. 5° E. and N. 5° W.; enter an open meadow.
10.07	The point for the SW-NE 1/64 sec. cor. of sec. 22.
11.60	Street, bears N. and S; enter moderate timber.
14.50	Power line, bears N. and S.
15.11	Point for the C-W-SW-NE 1/256 sec. cor. of sec. 22, not monumented.
16.80	Street, bears N. and S.
20.15	The point for the C-S-N 1/64 sec. cor. of sec. 22.
	From the point for the C-W-W-E 1/256 sec. cor. of sec. 22.
	N. 0°10'30" W., on the N. and S. center line of the SW $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 22.
	Over level land, through open meadow.
4.00	Drainage ditch, 30 lks. wide, 3 ft. deep, drains W.; enter moderate timber.
5.05	Point for the SW-SW-NE 1/256 sec. cor. of sec. at the intersection with the E. and W. center line of the SW $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 22.

Survey, Partial Subdivision, Sec. 22, T. 9 N., R. 23 E.

CHAINS	
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S22 SW-SW-NE $\frac{1}{256}$ 1967</p> <p>from which</p> <p style="text-align: center;">A local cor., bears S. 87°48' E., 114 lks. dist., monumented by a water pipe, 1 in. diam.</p> <p>7.20 Power line, bears E. and W.</p> <p>7.50 Street, bears E. and W.</p> <p>10.10 The point for the C-W-SW-NE 1/256 sec. cor. of sec. 22.</p>
	<p>From the point for the C-S-SW-NE 1/256 sec. cor. of sec. 22.</p> <p>N. 89°47' W., on the E. and W., center line of the SW$\frac{1}{4}$SW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 22.</p> <p>Over nearly level land, through an open meadow.</p> <p>1.60 Street, bears, N. and S.; enter moderate timber.</p> <p>5.035 The SW-SW-NE 1/64 sec. cor. of sec. 22.</p> <p>8.10 Drainage ditch, 30 lks. wide, 3 ft. deep, drains NW.</p> <p>10.07 The C-S-S-N 1/256 sec. cor. of sec. 22.</p>
	<p style="text-align: center;">Subdivision, Sec. 10</p> <hr style="width: 20%; margin: auto;"/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>N.0°02' E., on the N. and S. center line of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p> <p>5.60 Ditch, 30 lks. wide, 2 ft. deep, drains NW.</p> <p>10.055 Point for the C-S-S 1/64 sec. cor. of sec. 10, not monumented.</p> <p>14.40 Wash, 20 lks. wide, 1 ft. deep, drains irregularly W.</p> <p>20.11 Point for the C-S 1/16 sec. cor. of sec. 10, not monumented.</p> <p>40.22 Point for the C$\frac{1}{4}$ sec. cor. of sec. 10, at the intersection with the E. and W. center line of sec. 10.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9N R23E C$\frac{1}{4}$ +S10 1967</p> <p>Raise a mound of stone W. of the cor.</p>

Survey, Partial Subdivision, Sec. 10, T. 9 N., R. 23 E.

CHAINS	
40.70	Apache Railroad, bears N. 46°25' E. and S. 46°25' W.
41.70	Track road, bears N. 46°25' E. and S. 46°25' W.
49.30	Fence, bears S. 80° E. and N. 80° W.
54.90	Track road, bears SE. and N. 15° W.
60.565	Point for the C-N 1/16 sec. cor. of sec. 10, not monumented.
64.50	Wash, 20 lks. wide, 1 ft. deep, drains N. 10° E.
80.91	The 1/4 sec. cor. of secs. 3 and 10.
	Land, gently rolling. Soil, rocky, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.
	From the 1/4 sec. cor. of secs. 10 and 11.
	S. 89°27' W., on the E. and W. center line of sec. 10.
	Over gently rolling land, through moderate timber.
41.16	The C 1/4 sec. cor. of sec. 10.
41.63	Apache Railroad, bears N. 46°25' E. and S. 46°25' W.
42.60	Track road, bears N. 46°25' E. and S. 46°25' W.
45.40	Fence, bears irregularly N. and S.
46.468	Point for the C-E-E-W 1/256 sec. cor. of sec. 10.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	S10 C-E-E-W $\frac{1}{256}$ 1967
49.20	Wash, 20 lks. wide, 2 ft. deep, drains N.
51.775	Point for the C-E-W 1/64 sec. cor. of sec. 10.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	S10 C-E-W $\frac{1}{64}$ 1967
	from which
	A pine 8 ins. diam., bears S. 35°E., 19 lks. dist., med. C E W 1/64 S10 BT.
	Raise a mound of stone N. of the cor.
58.30	Track road, bears SE. and NW.; leave dense timber, enter widely scattered timber.

Survey, Partial Subdivision, Sec. 10, T. 9 N., R. 23 E.

CHAINS	
62.39	Point for the C-W 1/16 sec. cor. of sec. 10, not monumented.
63.20	Track road, bears N. and S.
83.62	The 1/4 sec. cor. of secs. 9 and 10.
	Land, gently rolling. Soil, rocky, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.
	Subdivision, SW 1/4 Sec. 10
	From the point for the W 1/16 sec. cor. of secs. 10 and 15.
	N. 0°13' E., on the N. and S. center line of the SW 1/4 sec. 10.
	Over gently rolling land, through dense timber.
9.60	Fence, bears E. and W.
10.075	Point for the C-S-SW 1/64 sec. cor. of sec. 10, not monumented.
20.15	Point for the SW 1/16 sec. cor. of sec. 10, at the intersection with the E. and W. center line of the SW 1/4 sec. 10, not monumented.
30.50	Enter open field, edge bears E. and W.
40.28	The point for the C-W 1/16 sec. cor. of sec. 10.
	From the point for the C-S 1/16 sec. cor. of sec. 10.
	S. 89°21' W., on the E. and W. center line of the SW 1/4 sec. 10.
	Over gently rolling land, through dense timber.
4.00	Wash, 20 lks. wide and 1 ft. deep, drains N.
9.50	Apache Railroad, bears N. 12°17' E. and S. 12°17' W.
10.30	Track road, bears N. 12°17' E. and S. 12°17' W.
10.65	Point for the C-E-SW 1/64 sec. cor. of sec. 10, not monumented.
11.10	Fence, bears irregularly N. and S.
19.80	Enter scattered timber.
21.30	Point for the SW 1/16 sec. cor. of sec. 10.
25.20	Enter open field, edge bears N. and S.
32.10	Enter dense timber, edge bears SE. and NW.
42.59	Point for the S 1/16 sec. cor. of secs. 9 and 10.
	From the Point for the E-W 1/64 sec. cor. of secs. 10 and 15.

Survey, Partial Subdivision, Sec. 10, T. 9 N., R. 23 E.

CHAINS	
	N. 0°07'30" E., on the N. and S. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 10. Power gently rolling land, through dense timber.
1.00	Track road, bears N. 12° W. and S. 12° E.
5.50	Apache, Railroad, bears N. 12° W. and S. 12° E.
10.06	Point for the SE-SW 1/64 sec. cor. of sec. 10, at the intersection with the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 10. Set the iron post 20 ins. in the ground, brass cap mkd. S10 SE SW $\frac{1}{64}$ 1967.
	Raise a mound of stone W. of cor.
14.20	Apache Railroad, bears N. 12° E. and S. 12° W.
18.60	Track road, bears N. 12° E. and S. 12° W.
20.12	The point for the C-E-SW 1/64 sec. cor. of sec. 10.
	From the point for the C-S-S 1/64 sec. cor. of sec. 10. S. 89°15'30" W., on the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 10. Over nearly level land, through dense timber.
4.00	Man made ditch, 30 lks. wide, 2 ft. deep, drains N. 20° W.
10.657	The SE-SW 1/64 sec. cor. of sec. 10.
11.13	Apache Railroad, bears N. 12° E. and S. 12° W.
11.70	Track Road, curves SE. and NW.
12.30	Fence, bears irregularly N. 20°E. and S. 20° W.
21.313	The point for the C-S-SW 1/64 sec. cor. of sec. 10.
	Subdivision, NW $\frac{1}{4}$ Sec. 10 <hr/>
	From the point for the C-W 1/16 sec. cor. of sec. 10. N. 0°25' E., on the N. and S. center line of the NW $\frac{1}{4}$ sec. 10. Over nearly level land, across on open meadow.
1.70	Track road, bears N. 5° E. and S. 5° W.
10.10	Dim track road, bears N. 85° E. and S. 85° W.

Survey, Partial Subdivision, Sec. 10, T. 9 N., R. 23 E.

CHAINS	
20.24	Point for the NW 1/16 sec. cor. of sec. 10, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ sec. 10.
39.60	Fence, bears E. and W.
40.52	The W 1/16 sec. cor. of secs. 3 and 10.
	From the point for the C-N 1/16 sec. cor. of sec. 10.
	S. 89°09' W., on the E. and W. center line of the NW $\frac{1}{4}$ sec. 10.
.70	Wash, 20 lks. wide, 1 ft. deep, drains N. 10° E.
1.40	Track road, bears N. 10° E., SW. and S. 15° E.
5.275	Point for the C-E-E-NW 1/256 sec. cor. of sec. 10.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">S10 C-E-E-NW $\frac{1}{256}$ 1967</p>
	Cor. is located 70 cks. N. of a fence bearing E. and W.
10.55	Point for the C-E-NW 1/64 sec. cor. of sec. 10.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">S10 C-E-NW $\frac{1}{64}$ 1967</p>
	from which
	A fence cor., bears S. 25° W., 85 lks. dist., fences, bear N. and E.
10.80	Fence, bears N. and E.; enter open meadow.
21.10	The point for the NW 1/16 sec. cor. of sec. 10.
42.20	The point for the N 1/16 sec. cor. of secs. 9 and 10.
	Subdivision Sec. 3
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	N.0°26' W., on the N. and S. center line of sec. 3.
	Over nearly level land, through dense timber.
9.70	Bladed road, on curve, bears NW. and E.
9.96	Fence cor., fences bear N. and E.

Survey, Partial Subdivision, Sec. 3, T. 9 N., R. 23 E.

CHAINS	
10.10	<p>Point for the C-S-S 1/64 sec. cor. of sec. 3.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S3 C S S $\frac{1}{64}$ 1967</p> <p>from which</p> <p>A local cor., a water pipe, 1 in. in diam., bears S. 5°28' W., 11.5 lks. dist.</p> <p>A bench mark, monumented by a 3 in. brass tablet, set in a concrete block, 9x9x6" above the grd. mkd. D141 1935, brs. N 18°14' W., 4.95 chs. dist.</p> <p>Cor. is located 1 lk. East of a fence bearing N. and S. and 40 lks. East of a bladed road curving SE. and NW.</p> <p>Raise a mound of stone W. of cor.</p>
18.50	<p>Fence cor., fences bear N., S. and W., continue along fence.</p>
20.20	<p>Point for the C-S 1/16 sec. cor. of sec. 3, not monumented.</p>
33.90	<p>Power line, bears N. 65° E. and S. 65° W.</p>
40.05	<p>Fence cor., fences bear S. and N. 65° E.</p>
40.40	<p>Point for the C$\frac{1}{4}$ sec. cor. of sec. 3, at the intersection with the E. and W. center line of sec. 3. Cor. falls in the south edge of graded road.</p> <p>Set the iron post 3 ins. below the surface, brass cap mkd.</p> <p style="text-align: center;">T9NR23E C$\frac{1}{4}$ + S3 1967</p> <p>from which</p> <p>A pine 6 ins. diam., bears S. 29° W., 26 lks. dist., mkd. C$\frac{1}{4}$ S3 BT.</p> <p>A spike in a fence cor. post, bears S. 2°W., 35 lks. dist.</p> <p>A spike in a post at the W. end of a gate, bears S. 85 3/4° E., 80 lks. dist.</p>
40.50	<p>Graded road, bears N. 70° E. and S. 70° W.</p>
50.52	<p>Point for the C-S-N 1/64 sec. cor. of sec. 3, at proportionate dist.</p> <p>Set the iron post over an X chiseled on solid rock, mound at stone to top, brass cap mkd.</p> <p style="text-align: center;">S3 C-S-N $\frac{1}{64}$ 1967</p>

Survey, Partial Subdivision, Sec. 3, T. 9 N., R. 23 E.

CHAINS	
	<p>from which</p> <p>A rebar, $\frac{1}{2}$ in. diam., bears S. $4^{\circ}36'$ W., 31 lks. dist.</p>
55.80	Track road, bears SE. and NW.
60.64	Point for the C-N $1/16$ sec. cor. of sec., at proportionate dist., not monumented.
78.40	Track road, bears SE. and NW.
81.27	<p>The $\frac{1}{4}$ sec. cor. of sec. 3 only, on the N. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.</p> <p>S. $89^{\circ}28'$ W., on the E. and W. center line of sec. 3.</p> <p>Over nearly level land, through dense timber.</p>
.02	Fence, bears N. $1^{\circ}24'$ W. and S. $1^{\circ}24'$ E.
10.312	<p>Point for the C-E-E $1/64$ sec. cor. of sec. 3.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S3 C-E-E <u>1</u> 6 4 1967</p> <p>Raise a mound of stone N. of the cor.</p>
14.70	Wash, 20 lks. wide, 1 ft. deep drains NE.
20.625	Point for the C-E $1/16$ sec. cor. of sec. 3, not monumented.
36.70	Fence, bears N. 70° E. and S. 70° W.
36.80	Power line, bears NE. and SW.
41.25	The $C\frac{1}{2}$ sec. cor. of sec. 3.
41.50	Graded road, bears N. 70° E. and S. 70° W.
54.70	Same graded road, bears SE. and NW.
61.855	Point for the C-W $1/16$ sec. cor. of sec. 3, not monumented.
72.157	<p>Point for the C-W-W $1/64$ sec. cor. of sec. 3.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S3 C-W-W <u>1</u> 6 4 1967</p>

Survey, Partial Subdivision, Sec. 3, T. 9 N., R. 23 E.

<p>CHAINS</p> <p>77.20</p> <p>82.46</p>	<p>Raise a mound of stone N. of cor.</p> <p>Fence, bears S. 20° E., and N. 20° W; enter open field.</p> <p>The ¼ sec. cor. of secs. 2 and 3.</p> <p>Land, gently rolling. Soil, rocky, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>
	<p>Subdivision, SE¼ Sec. 3</p> <hr/>
<p>4.20</p> <p>9.60</p> <p>9.70</p> <p>9.90</p> <p>10.07</p> <p>12.30</p> <p>16.80</p> <p>20.14</p> <p>24.90</p> <p>40.28</p>	<p>From the point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°53' W., on the N. and S. center line of the SE¼ sec. 3.</p> <p>Over gently rolling land, through moderate timber, asc. over S. slope.</p> <p>Top of hill, desc. N. slope.</p> <p>Track road, bears E. and W. at base of hill.</p> <p>Fence, bears E. and W.</p> <p>Fence, bears E. and W.</p> <p>Point for the C-S-SE 1/64 sec. cor. of sec. 3, not monumented.</p> <p>Enter open field, edge bears E. and W.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains NE.</p> <p>Point for the SE 1/16 sec. cor. of sec. 3, at the intersection with the E. and W. centerline of the SE¼ sec. 3, not monumented.</p> <p>Enter dense timber, edge bears NE. and SW.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 3.</p>
<p>1.50</p> <p>9.00</p> <p>10.392</p> <p>16.40</p> <p>20.784</p> <p>22.70</p> <p>39.40</p> <p>41.58</p>	<p>From the point for the S 1/16 sec. cor. of secs. 2 and 3.</p> <p>S. 89°13' W., on the E. and W. centerline of the SE¼ sec. 3.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Apache Railroad, bears N. 10°17' E. and S. 10°17' W.</p> <p>Enter an open field, edge bears N. and S.</p> <p>Point for the C-E-SE 1/64 sec. cor. of sec. 3, not monumented.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains N. 20° E.</p> <p>The point for the SE 1/16 sec. cor. of sec. 3.</p> <p>Enter dense timber, edge bears NE. and SW.</p> <p>Fence, bears N. and S.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 3.</p>

Survey, Partial Subdivision, Sec. 3, T. 9 N., R. 23 E.

CHAINS	
	<p>From the E-E 1/64 sec. cor. of secs. 3 and 10.</p> <p>N. 1°08'30" W., on the N. and S. center line of the SE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 3.</p> <p>Over gently rolling land, along a fence of the W. edge of an open field.</p> <p>9.98 Fence cor.; fences bear S. and W.</p> <p>10.048 Point for the SE-SE 1/64 sec. cor. of sec. 3, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 3.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 3 SE-SE $\frac{1}{64}$ 1967</p> <p>Raise a mound of stone W. of cor.</p> <p>20.09 The point for the C-E-SE 1/64 sec. cor. of sec. 3.</p>
	<p>From the point for the S-S 1/64 sec. cor. of secs. 2 and 3.</p> <p>S. 89°10'30" W., on the E. and W. center line of the SE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 3.</p> <p>Over level land, through open field.</p> <p>3.60 Apache Railroad, bears N. 10°17' E. and S. 10°17' W.</p> <p>10.437 The SE-SE 1/64 sec. cor. of sec. 3.</p> <p>15.83 Intersect the E. side of a log cabin, 10 x 20 ft.</p> <p>20.87 The point for the C-S-SE 1/64 sec. cor. of sec. 3.</p>
	<p style="text-align: center;">Subdivision, NE$\frac{1}{4}$ Sec. 3.</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the C-E 1/16 sec. cor. of sec. 3.</p> <p>N. 0°52' W., on the N. and S. center line of the NE$\frac{1}{4}$ sec. 3.</p> <p>Over gently rolling land, through moderate timber.</p> <p>7.80 Fence, bears N. 70° E. and S. 70° W.</p> <p>7.90 Power line, bears N. 70° E. and S. 70° W.</p> <p>8.20 Graded road, bears N. 70° E. and S. 70° W.</p> <p>8.80 Track road, bears N. 10° E. and S. 10° W.</p> <p>10.065 Point for the C-S-NE 1/64 sec. cor. of sec. 3, not monumented.</p> <p>15.70 Track road, bears SE. and NW.</p>

BOOK 4867

Survey, Partial Subdivision, Sec. 3, T. 9 N., R. 23 E.

CHAINS	
20.13	Point for the NE 1/16 sec. cor. of sec. 3, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ sec. 3, not monumented.
40.73	The point for the E 1/16 sec. cor. of sec. 3 only, on the N. bdy. of the Tp.
From the N 1/16 sec. cor. of secs. 2 and 3.	
S. 89°45' W., on the E. and W. center line of the NE $\frac{1}{4}$ sec. 3.	
Through wash area.	
2.40	Leave wash, bank 20 ft. high, bears N. 60° E. and S. 60° W.; thence over gently rolling, through moderate timber.
10.215	Point for the C-E-NE 1/64 sec. cor. of sec. 3, not monumented.
20.43	The point for the NE 1/16 sec. cor. of sec. 3.
28.40	Track road, bears NW. and S. 70° E.
40.87	The point for the CN 1/16 sec. cor. of sec. 3.
From the C-E-E 1/64 sec. cor. of sec. 3.	
N. 1°11'30" W., on the N. and S. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ sec. 3.	
Over gently rolling land, through moderate timber.	
1.40	Wash, 20 lks. wide, 1 ft. deep, drains N. 60° E.
10.045	Point for the SE-NE 1/64 sec. cor. of sec. 3 at the intersection with the E. and W. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 3.
Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.	
<p style="text-align: center;">S 3 SE-NE $\frac{1}{64}$ 1967</p>	
from which	
A water pipe 1 in. diam., bears North, 5.6 lks. dist.	
Raise a mound of stone W. of cor.	
10.10	Fence, bears E. and W.
11.90	Power line, bears N. 70° E. and S. 70° W.
12.10	Graded road, bears N. 80° E. and S. 80° W.
20.09	The point for the C-E-NE 1/64 sec. cor. of sec. 3.
From the point for the S-N 1/64 sec. cor. of secs. 2 and 3.	

Survey, Partial Subdivision, Sec. 3, T. 9 N., R. 23 E.

CHAINS	
	S. 89°34' W., on the E. and W. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ sec. 3.
	Over nearly level land, through moderate timber, along the S. side of a fence.
3.20	Wash, 20 lks. wide, 1 ft. deep, drains N.
10.265	The SE-NE 1/64 sec. cor. of sec. 3.
14.20	Fence, bears S. 70° W. and N. 70° E. for 10 lks., thence E.
14.80	Power line, bears N. 70° E. and S. 70° W.
15.50	Graded road bears N. 70° E. and S. 70° W.
19.70	Track road, bears irregularly N. 10° E. and S. 10° W.
20.53	The point for the C-S-NE 1/64 sec. cor. of sec. 3.
Subdivision, SW $\frac{1}{4}$ Sec. 3 <hr/> From the W 1/16 sec. cor. of secs. 3 and 10. N. 0°08'30" E., on the N. and S. center line of the SW $\frac{1}{4}$ sec. 3. Over nearly level land, through scattered timber. 19.70 Fence, bears E. and W. 30 lks. dist., thence E., S. and W. 20.27 Point for the SW 1/16 sec. cor. of sec. 3, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$ sec. 3. Set the iron post 20 ins. in the ground, brass cap mkd. SW 1/16 + S3 1967 from which A fence cor., bears S. 30° W., 63 lks. dist., fences bear E., S. and W. Raise a mound of stone W. of cor. 24.20 Power line, bears N. 65° E. and S. 65° W. 24.60 Track road, bears N. 65° E. and S. 65° W. 26.00 Leave scattered timber, enter dense timber. 40.58 The point for the C-W 1/16 sec. cor. of sec. 3.	
5.00	From the point for the C-S 1/16 sec. cor. of sec. 3. S. 89°12' W., on the E. and W. center line of the SW $\frac{1}{4}$ sec. 3. Over level land, through dense timber. Graded road, bears S. 30° E. and N. 30° W.

Survey, Partial Subdivision, Sec. 3, T. 9 N., R. 23 E.

CHAINS	
12.40	Leave dense timber, enter scattered timber, bears N. and S.
20.79	The SW 1/16 sec. cor. of sec. 3.
20.80	Leave timber, enter open field, bears N. and S.
29.40	Power line, bears N. 65° E. and S. 65° W. for 115 lks., thence W.
31.19	<p>Point for the C-W-SW 1/64 sec. cor. of sec. 3.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 3 C-W-SW 1 6 4 1967</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 15° W., 24 lks. dist., fences bears N., E. and W.</p> <p>Raise a mound of stone N. of cor.</p>
31.30	Fence, bears N. and S.
41.59	The point for the S 1/16 sec. cor. of secs. 3 and 4.
Survey, Partial Subdivision, Sec. 33, T.9N., R.23 E.	
Subdivision, SW $\frac{1}{4}$ Sec. 33	
<p>From the standard W-W 1/64 sec. cor. of sec. 33, on the S. bdy. of the Tp.</p>	
<p>N. 0°42' E., on the N. and S. center line of the SW$\frac{1}{4}$SW$\frac{1}{4}$ sec. 33.</p>	
<p>Over gently rolling land, through scattered timber, along a fence bearing irregularly N. and S. at the E. edge of a pasture.</p>	
1.50	Stream, 10 lks. wide, water 6 ins. deep, course W.
9.00	Fence cor., fences bear E. and irregularly N. and S.
9.20	Power line, bears N. 47°45' W. and S. 47°45' E.
10.00	Power line, bears N. 47°45' W., and S. 47°45' E.
13.80	A small spring, bears West, 30 lks. dist., water course NW. and seeps into ground.
15.00	A small spring, bears East, 140 lks. dist., water course W. and seeps into ground.
20.21	<p>The C-W-SW 1/64 sec. cor. of sec. 33, monumented by an iron pin, firmly set with 6 ins. showing above the grd. This point was set by a local surveyor, and is accepted by local land owners.</p> <p>At the cor. point</p>

Survey, Partial Subdivision, Sec. 33, T. 9 N., R. 23 E.

CHAINS	
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C-W-SW $\frac{1}{64}$ S33 1967</p> <p>from which</p> <p>A pine, 21 ins. diam., bears N. 32° E., 31 lks. dist., mkd. C W SW 1/64 S33 BT.</p> <p>A pine, 7 ins. diam., bears S. 49° E., 65 lks. dist., mkd. C W SW 1/64 S33 BT.</p> <p>A small spring, bears S. 47° E., 570 lks. dist., water course NW. and seeps into ground.</p> <p>A fence cor. bears N. 83° E., 25 lks. dist., fences bear W. and S.</p> <p>Bury the iron pin alongside the iron post.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine and oak. Undergrowth, grass.</p>
<p>7.40</p> <p>10.01</p>	<p>N. 89°11' W., on the W. portion of the E. and W. center line of the SW$\frac{1}{4}$ sec. 33.</p> <p>Along the S. side of a fence at the N. edge of a pasture.</p> <p>Fence, bears S. and N. for 6 lks. thence E.; enter moderate timber.</p> <p>The S 1/16 sec. cor. of secs. 32 and 33.</p>
<p>40.14</p>	<p>Survey, Partial Subdivision, Sec. 16, T. 9 N., R. 23 E.</p> <p style="text-align: center;">Subdivision, Sec. 16</p> <hr style="width: 20%; margin: auto;"/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 16 and 21.</p> <p>N. 0°25' W., on the N. and S. center line of sec. 16.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the C$\frac{1}{4}$ sec. cor. of sec. 16, at the intersection with the E. and W. center line of sec. 16.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9NR23E C$\frac{1}{4}$ S16 1967</p> <p>from which</p> <p>A pine, 8 ins. diam., bears S. 14° E., 77 lks.</p>

Survey, Partial Subdivision, Sec. 16, T. 9 N., R. 23 E.

CHAINS	
80.43	<p>dist., mkd. C$\frac{1}{4}$ S16 BT.</p> <p>A pine, 6 ins. diam., bears N. 83° W. 51 lks. dist., mkd. X BT.</p> <p>A stock pond, bears S. 9$\frac{1}{2}$° W., 23.40 chs. dist.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>
4.50 5.20	<p>From the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.</p> <p>S. 89°38' W., on the E. and W. center line of sec. 16.</p> <p>Over gently rolling land, through dense timber, along N. side of a fence bearing E. and W.</p> <p>Morgan Wash, 15 lks. wide, 1 ft. deep, drains irreg. N.</p> <p>Old railroad bed, bears N. 40° E. and S. 40° W.</p>
20.22	<p>Point for the CE 1/16 sec. cor. of sec. 16.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9NR23E C E <u>1</u> S16 1 6 1967</p>
20.32	<p>from which</p> <p>An oak, 10 ins. diam., bears North, 7 lks. dist., mkd. CE 1/16 S16 BT.</p> <p>A pine, 6 ins. diam., bears S. 27° E., 17 lks. dist., mkd. X BT.</p>
	<p>Fence cor., bears S. 7°25' W., 74 lks. dist., fences bear N. and E.</p>
	<p>Set a wooden post 4 x 4 ins. squared, 6 ft. long, alongside the iron post.</p>
20.32	<p>Fence, bears N. and S.</p>
40.44	<p>The C$\frac{1}{4}$ sec. cor. of sec. 16.</p>
80.65	<p>The $\frac{1}{4}$ sec. cor. of sec. 16 and 17.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>
<p>Survey, Partial Subdivision, Sec. 9, T. 9 N., R. 23 E.</p>	
<p>Subdivision, Sec. 9</p>	
<p>From the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p>	

Survey, Partial Subdivision, Sec. 9, T. 9 N., R. 23 E.

CHAINS	
	N. 0°07' W., on the N. and S. center line of sec. 9.
	Over rolling land, through scattered timber, along a fence bearing irregularly N.
3.25	Morgan wash, 20 lks. wide, 2 ft. deep, drains S. 30° W.
14.80	Track road, bears E. and W.
19.70	Fence, bears W. and E. for 22 lks. to cor. of fences bearing E., W. and S.
20.215	Point for the C-S 1/16 sec. cor. of sec. 9, not monumented.
40.43	Point for the C $\frac{1}{2}$ sec. cor. of sec. 9, at the intersection with the E. and W. center line of sec. 9, not monumented.
60.70	Point for the C-N 1/16 sec. cor. of sec. 9.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	C-N 1/16
	S 9
	1967
	from which
	A pine, 11 ins. diam., bears N. 41° W., 100 lks. dist., mkd. C N 1/16 S9 BT.
70.835	Point for the C-N-N 1/64 sec. cor. of sec. 9, monumented by an iron pipe 1 $\frac{1}{2}$ ins. diam.
	Set the iron post 16 ins. in the ground, collar of stone to top, brass cap mkd.
	C-N-N 1/64
	S 9
	1967
	from which
	A pine, 7 ins. diam., bears S. 61 $\frac{1}{2}$ ° W., 42 lks. dist., mkd. CNN 1/64 S 9 BT.
	Bury the local cor. alongside the iron post.
	The cor. is located alongside a fence cor., fences bear N. and W.
80.97	The $\frac{1}{2}$ sec. cor. of secs. 4 and 9.
	Land, gently rolling.
	Soil, clay loam.
	Timber, pine and juniper.
	Undergrowth, bunch grass.
	From the $\frac{1}{2}$ sec. cor. of secs. 9 and 10.
	S. 89°34' W. on the E. and W. center line of sec. 9.
	Over nearly level land, through scattered timber, along the S. side of a fence.
20.00	Fence, bears S. and N. for 20 lks. to fence cor., fences bear E. and S.

Survey, Partial Subdivision, Sec. 9, T. 9 N., R. 23 E.

CHAINS	
20.45	<p>Point for the C-E 1/16 sec. cor. of sec. 9.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-E 1/16 S 9 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 82° W., 17 lks. dist., mkd. C E 1/16 S 9 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N. 68° E., 50 lks. dist., fences bear E. and S.</p>
35.79	<p>Point for the C-W-W-E 1/256 sec. cor. of sec. 9.</p> <p>Set the iron post 18 ins. in the ground, collar of stone, brass cap mkd.</p> <p style="text-align: center;">C-W-W-E <u>1</u> 256 S9 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 4° E., 78 lks. dist., mkd. C W W E 1/256 S9 BT.</p>
40.90	<p>The point for the C$\frac{1}{4}$ sec. cor. of sec. 9.</p>
61.60	<p>Fence, bears N. and S.</p>
79.20	<p>Track road, bears N. and S.</p>
81.63	<p>The $\frac{1}{4}$ sec. cor. of secs. 8 and 9.</p> <p>Land, nearly level. Soil, clay loam. Timber, pine and juniper. Undergrowth, bunch grass.</p>
<p>Subdivision, SE$\frac{1}{4}$ S 9</p> <hr style="width: 20%; margin: auto;"/>	
4.90	<p>From the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 0°08' E., on the N. and S. center line of the SE$\frac{1}{4}$ sec. 9.</p> <p>Over gently rolling land, through scattered timber.</p>
10.90	<p>Morgan wash, 30 lks. wide, 3 ft. deep, drains N. 80° W.</p>
19.93	<p>Track road, bears E. and W.</p>
19.93	<p>Fence, bears, E. and W.</p>
20.21	<p>Point for the SE 1/16 sec. cor. of sec. 9, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$ sec. 9.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>

Survey, Partial Subdivision, Sec. 9, T. 9 N., R. 23 E.

CHAINS	
40.43	<p style="text-align: center;">SE 1/16 S 9 1967</p> <p>from which</p> <p>A pine, 6 ins. diam., bears N. 36° W., 17 lks. dist., mkd. SE 1/16 S9 BT.</p> <p>A fence cor., bears S. 41° E., 37 lks. dist., fences, bear N. and W.</p> <p>Cor. is located at the base and on the S. side of a pine 8 ins. diam.</p> <p>The C-E 1/16 sec. cor. of sec. 9.</p>
1.50 20.13 20.37 35.65 40.74	<p>From the point for the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>S. 89°32' W., on the E. and W. center line of the SE 1/4 sec. 9.</p> <p>Over gently rolling land, through moderate timber.</p> <p>Track road, bears N. and S.</p> <p>Fence, bears N. and S.</p> <p>The SE 1/16 sec. cor. of sec. 9.</p> <p>Point for the C-W-W-SE 1/256 sec. cor. of sec. 9.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">C-W-W-SE 1/256 S 9 1967</p> <p>from which</p> <p>A pine, 8 ins. diam., bears N. 27° E. 95 lks. dist., mkd. C W W SE 1/256 S9 BT.</p> <p>The point for the C-S 1/16 sec. cor. of sec. 9.</p>
	<p style="text-align: center;">Survey, Partial Subdivision, Sec. 4, T. 9 N., R. 23 E.</p>
2.70 10.12 17.00	<p style="text-align: center;">Subdivision, Sec. 4</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 1°21' E., on the N. and S. center line of sec. 4.</p> <p>Over nearly level land, through dense timber.</p> <p>Power line, bears N. 60° E. and S. 60° W.</p> <p>Point for the C-S-S 1/64 sec. cor. of sec. 4, not monumented.</p> <p>Deer Run Road, gravelled, bears E. and W.; begin asc. gentle S. slope.</p>

BOOK 4867

Survey, Partial Subdivision, Sec. 4, T. 9 N., R. 23 E.

CHAINS	
17.30	Power line, bears E. and W.
20.24	Point for the C-S 1/16 sec. cor. of sec. 4, positioned latitudinally at a fence bearing S. 89°39' W. and N. 89° 39' E. This fence is accepted as the property line by local land owners. The cor. point is not monumented.
30.32	Point for the C-N-S 1/64 sec. cor. of sec. 4, not monumented.
31.60	Fence, bears N. 70° E. and S. 70° W.
32.60	Gravelled road, bears N. 70° E. and S. 70° W.; begin asc. S. slope.
40.40	Point for the C $\frac{1}{4}$ sec. cor. of sec. 4, at the intersection with the E. and W. center line of sec. 4.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	C $\frac{1}{4}$ S4 1967
	from which
	A juniper, 7 ins. diam., bears N. 47° E., 32 lks. dist., mkd. C $\frac{1}{4}$ S4 BT.
	A pine, 6 ins. diam., bears N. 64° W., 50 lks. dist., mkd. X BT.
56.50	Ridge, bears NE. and SW., desc. steep NW. slope.
61.00	Point for the C-N 1/16 sec. cor. of sec. 4, at proportionate dist., not monumented.
75.40	Track road, bears irregularly E. and W.; bottom of desc., continue over rolling land.
81.81	The $\frac{1}{4}$ sec. cor. of sec. 4, only, on the N. bdy. of the Tp.
	Land, nearly level to mountainous. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. S. 89°18' W., on the E. and W. center line of sec. 4. Over nearly level open field.
10.257	Point for the C-E-E- 1/64 sec. cor. of sec. 4.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	C-E-E 1/64 S 4 1967
	from which
	A fence cor., bears N. 18 $\frac{1}{2}$ ° W., 113 lks. dist., fences bear N. and W.

Survey, Partial Subdivision, Sec. 4, T. 9 N., R. 23 E.

CHAINS	
	Set a wooden post, 5 ins. diam., 5 ft. long, alongside the iron post.
	Asc. over gentle SE. slope.
15.10	Fence, bears N. and S.
20.515	Point for the C-E 1/16 sec. cor. of sec. 4.
	Set the iron post 22 ins. in the ground; brass cap mkd.
	C-E 1/16 S 4 1967
	Set a wooden post 4 ins. diam., 6 ft. long, alongside the iron post.
21.20	Fence, bears N. and S., enter dense timber.
23.50	Gravelled road, bears N. 30° E. and S. 30° W.
30.772	Point for the C-W-E 1/64 sec. cor. of sec. 4, not monumented.
38.90	Track road, bears N. 20° E. and S. 20° W.
41.03	The C $\frac{1}{4}$ sec. cor. of sec. 4.
49.20	Spur, slopes S.; desc. gentle SW. slope.
59.40	Track road, bears N. and S.
60.40	Ravine, drains southerly, asc. SE. slope.
62.285	Point for the C-W 1/16 sec. cor. of sec. 4, not monumented.
75.80	Spur, slopes W. from NE.; desc. W. slope.
83.54	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Land, rolling. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.
	Subdivision, SE $\frac{1}{4}$ S 4
	From the point for the E 1/16 sec. cor. of secs. 4 and 9.
	N. 1°00' E., on the N. and S. center line of the SE $\frac{1}{4}$ sec. 4.
	Over nearly level land, through dense timber.
9.60	Fence, bears E. and W.
10.16	Point for the C-S-SE 1/64 sec. cor. of sec. 4.
	Set the iron post 20 ins. in the ground.

Survey, Partial Subdivision Sec. 4, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">C-S-SE 1/64 S4 1967</p>
	<p>from which</p>
	<p>A pine, 6 ins. diam., bears S. 78½° E., 40 lks. dist., mkd. X BT.</p>
	<p>A pine, 10 ins. diam., bears S. 36° W., 40 lks. dist., mkd. C S SE 1/64 S 4 BT.</p>
	<p>Cor. is located 4 lks. West of a fence bearing N. and S.</p>
10.605	<p>A re-bar, ½ in. diam., bears West 15 lks. dist., with a lathe alongside mkd. 1/64th cor.</p>
14.40	<p>Power line, bears N. 55° E. and S. 55° W.</p>
20.32	<p>Point for the SE 1/16 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the SE¼ sec. 4, not monumented.</p>
30.46	<p>Point for the C-N-SE 1/64 sec. cor. of sec. 4.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">C-N-SE 1/64 S 4 1967</p>
	<p>from which</p>
	<p>A pine, 8 ins. diam., bears S. 56° E., 76 lks. dist., mkd. C N SE 1/64 BT.</p>
	<p>A fence cor., bears N. 33° W., 92 lks. dist., fences bear N., S. and E.</p>
31.20	<p>Fence, bears E. and W.; enter open field.</p>
35.20	<p>Track road, bears E. and W.</p>
35.53	<p>Point for the C-N-N-SE 1/256 sec. cor. of sec. 4.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">C-N-N-SE 1/256 S 4 1967</p>
	<p>Set a wooden post 5 ins. diam., 4 ft. long, alongside the iron post.</p>
	<p>Cor. is located 63 lks. East of a fence bearing N. and S.</p>
40.60	<p>The C-E 1/16 sec. cor. of sec. 4.</p>
	<p>From the point for the S 1/16 sec. cor. of secs. 3 and 4.</p>
	<p>S. 89°39' W., on the E. and W. center line of the SE¼ sec. 4.</p>
	<p>Over a nearly level open field, along a fence bearing irregularly E. and W.</p>

Survey, Partial Subdivision Sec. 4, T. 9 N., R. 23 E.

CHAINS	
10.32	Point for the C-E-SE 1/64 sec. cor. of sec. 4, not monumented.
10.45	Fence, bears N. and S. for 30 lks. to cor. of fences bearing N. and E.
10.90	Track road, bears N. and SW.; enter dense timber.
20.64	The point for the SE 1/16 sec. cor. of sec. 4.
20.80	Fence, bears irregularly N. and S.
21.50	Enter clearing, edge bears N. and S.
25.50	Deer Run Road, bears N. and S.
25.90	Power line, bears N. and S.
30.96	Point for the C-W-SE 1/64 sec. cor. of sec. 4, not monumented.
34.00	Enter moderate timber, edge bears N. and S.
36.12	Point for the C-W-W-SE 1/256 sec. cor. of sec. 4, monumented by a re-bar.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">C-W-W-SE 1/256 S 4 1967</p>
	from which
	<p style="text-align: center;">A pine, 7 ins. diam., bears N. 10° W., 29 lks. dist., mkd. C W W SE 1/256 S4 BT.</p>
	Reset the re-bar alongside the iron post.
36.14	Fence cor., fences bear S. 89°39' W. and S.
41.12	The point for the C-S 1/16 sec. cor. of sec. 4.
	<p>From the point for the C-E-SE 1/64 sec. cor. of sec. 4. N. 0°49' E., on the N. and S. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 4.</p>
3.60	Over nearly level open field. Fence, bears E. and W.
10.18	Point for the NE-SE 1/64 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 4.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">NE-SE 1/64 S 4 1967</p>
	Set a post, 5 ins. diam., 5 ft. long, alongside the iron post.
20.36	The C-E-E 1/64 sec. cor. of sec. 4.
	From the point for the N-S 1/64 sec. cor. of secs. 3 and 4.

Survey, Partial Subdivision Sec. 4, T. 9 N., R. 23 E.

CHAINS	
	<p>S. 89°30' W., on the E. and W. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$ sec. 4.</p> <p>Over nearly level open field.</p>
10.29	The NE-SE 1/64 sec. cor. of sec. 4.
14.00	Track road, bears N. 20°W. and S. 20° E.
14.50	Enter timber, edge bears N. and S.
20.59	The C-N-SE 1/64 sec. cor. of sec. 4.
	<p>From the W-E 1/64 sec. cor. of secs. 4 and 9.</p>
	<p>N. 1°11' E., on the N. and S. center line of the SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 4.</p>
	<p>Over nearly level land entering scattered timber.</p>
8.40	Power line, bears N. 60° E. and S. 60° W.
9.78	Fence, bears E. and W.
10.14	<p>Point for the SW-SE 1/64 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 4.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">SW-SE 1/64 S 4 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 5$\frac{1}{2}$° W., 46 lks. dist. fences bear S. and E.</p> <p>Raise a mound of stone W. of cor.</p>
16.60	Deer Run Road, bears E. and W.
16.90	Power line, bears E. and W.
18.20	Enter clearing, edge bears E. and W.
20.28	The point for the C-W-SE 1/64 sec. cor. of sec. 4.
	<p>From the C-S-SE 1/64 sec. cor. of sec. 4.</p>
	<p>S. 89°46' W., on the E. and W. center line of the SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 4.</p>
	<p>Over nearly level land, through dense timber.</p>
8.60	Power line, bears N. 60° E. and S. 60° W.
10.34	The SW-SE 1/64 sec. cor. of sec. 4.
16.50	Elk Drive, graded, bears N. and S.

Survey, Partial Subdivision Sec. 4, T. 9 N., R. 23 E.

CHAINS	
16.80	Power line, bears N. and S.
20.68	The point for the C-S-S- 1/64 sec. cor. of sec. 4.
	From the point for the C-W-SE 1/64 sec. cor. of sec. 4.
	N. 1°08' E., on the N. and S. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 4.
	Asc. a gentle S. slope, through a clearing.
2.60	Graded road, bears E. and W.
4.00	Enter timber, edge bears E. and W.
10.13	Point for the NW-SE 1/64 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 4.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">NW-SE 1/64 S 4 1967</p>
	from which
	<p style="text-align: center;">A juniper, 6 ins. diam., bears N. 79° W., 13 lks. dist., mkd. NW SE 1/64 S4 BT.</p>
11.20	Bladed road, bears E. and W.
15.19	Point for the C-N-NW-SE 1/256 sec. cor. of sec. 4, falls in a gravelled road.
	Set a standard iron post, 2 $\frac{1}{2}$ ins. diam., cut to 12 ins. long, set 20 ins. in the ground to bedrock, brass cap mkd.
	<p style="text-align: center;">C-N-NW-SE <u>1</u> 256 S 4 1967</p>
	from which
	<p style="text-align: center;">A pine, 6 ins. diam., bears N. 29$\frac{1}{2}$° E., 58 lks. dist., mkd. C N NW SE 1/256 S4 BT.</p>
	<p style="text-align: center;">A pine, 7 ins. diam., bears S. 39° W., 67 lks. dist., mkd. C N NW SE 1/256 S4 BT.</p>
15.20	Gravelled road, bears N. 70° E. and S. 70° W.
20.25	The point for the C-W-E 1/64 sec. cor. of sec. 4.
	From the C-N-SE 1/64 sec. cor. of sec. 4.
	S. 89°30' W., on the E. and W. center line of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 4.
	Over gently rolling land, through dense timber.
4.50	Deer Run Road, bears N. and S.

Survey, Partial Subdivision Sec. 4, T. 9 N., R. 23 E.

CHAINS	
10.285	The NW-SE 1/64 sec. cor. of sec. 4.
15.427	Point for the C-W-NW-SE 1/256 sec. cor. of sec. 4.
	Set the iron post, 22 ins. in the ground, brass cap mkd.
	C-W-NW-SE 1/256 S 4 1967
	from which
	A juniper, 6 ins. diam., bears S. 43° W., 44 lks. dist., mkd. C W NW SE 1/256 S4 BT.
20.57	The point for the C-N-S 1/64 sec. cor. of sec. 4.
	Subdivision, NE¼ Sec. 4
	From the C-E 1/16 sec. cor. of sec. 4.
	N. 1°00' E., on the N. and S. center line of the NE¼ sec. 4.
	Asc. gentle S. slope, through open field.
1.80	Fence, bears E. and W.
3.30	Gravelled road, bears NE. and SW.; enter timber.
10.25	Point for the C-S-SE 1/64 sec. cor. of sec. 4, not monumented.
15.30	Track road, bears SE. and NW.
20.50	Point for the NW 1/16 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the NE¼ sec. 4, not monumented.
25.50	Spur, slopes E., desc. N. slope.
35.10	Track road, bears N. 60° E. and West.
36.70	Bottom of desc.; thence over gently rolling land.
41.26	The point for the E 1/16 sec. cor. of sec. 4, only, on the N. bdy. of the Tp.
	From the point for the N 1/16 sec. cor. of secs. 3 and 4.
	S. 89°31' W., on the E. and W. center line of the NE¼ sec. 4.
	Over gently rolling land, through dense timber.
10.195	Point for the C-E-NE 1/64 sec. cor. of sec. 4, not monumented.
10.20	Track road, bears N. and S.
20.39	The point for the NE 1/16 sec. cor. of sec. 4.
23.20	Track road, bears NE. and SW.
40.78	The point for the C-N 1/16 sec. cor. of sec. 4.

Survey, Partial Subdivision Sec. 4, T 9 N., R. 23 E.

CHAINS	
<p>10.23</p>	<p>From the C-E-E 1/64 sec. cor. of sec. 4. N. 0°49' E., on the N. and S. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ sec. 4. Over nearly level open field.</p> <p>Point for the SE-NE 1/64 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ sec. 4. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SE-NE 1/64 S 4 1967</p> <p>from which A juniper, 8 ins. diam., bears N. 41° W., 54 lks. dist., mkd. SE NE 1/64 S4 BT. Set a wooden post, 5 ins. diam., 5 ft. long, alongside the iron post.</p>
<p>11.23</p> <p>11.50</p> <p>11.70</p> <p>20.46</p>	<p>Fence, bears E. and W.</p> <p>Gravelled road, bears E. and W.</p> <p>Enter dense timber, edge bears E. and W.</p> <p>The point for the C-E-NE 1/64 sec. cor. of sec. 4.</p>
<p>2.80</p> <p>3.90</p> <p>10.23</p> <p>10.60</p> <p>14.00</p> <p>20.46</p>	<p>From the S-N 1/64 sec. cor. of secs. 3 and 4. S. 89°24' W., on the E. and W. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ sec. 4. Over gently rolling land, through dense timber.</p> <p>Gravelled road, bears SE. and N. 70° W.</p> <p>Fence, bears N. 70° W. and S. 70° E.; enter nearly level open field.</p> <p>The SE-NE 1/64 sec. cor. of sec. 4.</p> <p>Fence, bears N. and S.; enter dense timber; asc. gentle SE. slope.</p> <p>Gravelled road, bears SW. and NE.</p> <p>The point for the C-S-NE 1/64 sec. cor. of sec. 4.</p>
<p>Subdivision, SW$\frac{1}{4}$ Sec. 4</p>	
<p>10.06</p> <p>19.90</p> <p>20.12</p>	<p>From the W 1/16 sec. cor. of secs. 4 and 9. N. 0°40' E., on the N. and S. center line of the SW$\frac{1}{4}$ sec. 4. Over nearly level land, through dense timber.</p> <p>Point for the C-S-SW 1/64 sec. cor. of sec. 4. Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-S-SW 1/64 S 4 1967</p> <p>Fence, bears E. and W.</p> <p>The SW 1/16 sec. cor. of sec. 4, monumented by a local cor., a water pipe, 1 in. diam., set in a mound of stone. This point is used and accepted by local landowners.</p>

Survey, Partial Subdivision Sec. 4, T. 9 N., R. 23 E.

CHAINS	
	<p>At the cor. point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SW $\frac{1}{16}$ S 4 1967</p> <p>Raise a mound of stone W. of the cor. and bury the water pipe inside the iron post.</p>
25.13	<p>Point for the C-S-N-SW $\frac{1}{256}$ sec. cor. of sec. 4.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-S-N-SW $\frac{1}{256}$ S 4 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 45° E., 63 lks. dist., mkd. C S N SW $\frac{1}{256}$ S4 BT.</p>
28.90	<p>Gravelled road, bears N. 80° E. and S. 80° W.; begin asc. gentle SE. slope.</p>
40.16	<p>The point for the C-W $\frac{1}{16}$ sec. cor. of sec. 4.</p>
	<p>From the point for the C-S $\frac{1}{16}$ sec. cor. of sec. 4.</p> <p>S. 89°39' W., on the E. and W. center line of the SW $\frac{1}{4}$ sec. 4.</p> <p>Along a fence line, over nearly level land, moderate timber.</p> <p>3.95 Fence cor., fences bear South and N. 89°39' E.</p> <p>10.80 Graded road, bears N. and S.</p> <p>21.01 The SW $\frac{1}{16}$ sec. cor. of sec. 4.</p> <p style="text-align: center;">_____</p> <p>S. 89°30' W., beginning new measurement.</p> <p>1.55 Fence, bears N. and S.; enter open field.</p> <p>21.00 The point for the S $\frac{1}{16}$ sec. cor. of secs. 4 and 5.</p>
	<p style="text-align: center;">Subdivision, Sec. 32</p>
20.31	<p>From the standard $\frac{1}{4}$ sec. cor. of sec. 32, on the S. bdy. of the Tp.</p> <p>N. 0°34' E., on the N. and S. center line of sec. 32.</p> <p>Through a private residential area.</p> <p>Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 32.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>

Survey, Partial Subdivision Sec. 32, T. 9 N., R. 23 E.

CHAINS

$$\begin{array}{c} \text{C} \\ \text{S } \frac{1}{16} \text{ S32} \\ \text{C} \\ 1967 \end{array}$$

from which

A pine, 11 ins. diam., bears N. $15\frac{1}{2}^{\circ}$ E., 31 lks. dist., mkd. C S $\frac{1}{16}$ S32 BT.

A pine, 9 ins. diam., bears N. 58° W., 18 lks. dist., mkd X BT.

A fence cor., bears S. $20^{\circ}50'$ W., 56 lks. dist., fences bear W. and S.

Thence over gently rolling land, through moderate timber.

- 30.10 Desc. N. slope into Billy Creek.
- 32.10 Billy Creek, 75 lks. wide, course N. 65° W.; asc. S. slope; enter dense timber.
- 40.62 Point for the $\frac{1}{4}$ sec. cor. of sec. 32, at the intersection with the E. and W. center line of sec. 32.
- Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
- $$\begin{array}{c} \frac{1}{4} \text{ S32} \\ 1967 \end{array}$$
- from which
- A pine, 6 ins. diam., bears N. $41\frac{1}{4}^{\circ}$ E., 48 lks. dist., mkd. $\frac{1}{4}$ S32 BT.
- A pine, 7 ins. diam., bears S. $16\frac{3}{4}^{\circ}$ W., 28 lks. dist., mkd. $\frac{1}{4}$ S32 BT.
- 46.70 Wash, 15 lks. wide, 1 ft. deep, drains SW.
- 48.90 Bladed road, bears N. 60° E. and S. 60° W.
- 54.30 Power line, bears S. $47^{\circ}45'$ E. and N. $47^{\circ}45'$ W.
- 55.50 Power line, bears S. $47^{\circ}45'$ E. and N. $47^{\circ}45'$ W.
- 59.50 Bladed road, bears S. 60° E. and N. 60° W.
- 68.20 Wash, 15 lks. wide, 1 ft. deep, drains SW.
- 81.12 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32.

Land, gently rolling.
Soil, clay loam.
Timber, pine, oak and juniper.
Undergrowth, bunch grass.

From the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

S $89^{\circ}57'$ W., on the E. and W. center line of sec. 32.

Over gently rolling land, through dense timber.

Survey, Subdivision Sec. 32, T. 9 N., R. 23 E.

<p>CHAINS</p> <p>20.22</p> <p>23.90</p> <p>25.10</p> <p>40.44</p> <p>61.20</p> <p>80.33</p>	<p>Point for the C-E 1/16 sec. cor. of sec. 32, not monumented.</p> <p>Power line, bears S. 47°45' E. and N. 47°45' W.</p> <p>Power line, bears S. 47°45' E. and N. 47°45' W.</p> <p>The C$\frac{1}{4}$ sec. cor. of sec. 32.</p> <p>Bladed road, bears N. 75° E. and S. 75° W.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>
	<p>Subdivision, SE$\frac{1}{4}$ Sec. 32</p> <hr/> <p>From the point for the standard E 1/16 sec. cor. of sec. 32 on the S. bdy. of the Tp.</p> <p>N. 0°39' E., on the N. and S. center line of the SE$\frac{1}{4}$ sec. 32.</p> <p>Over level land, through private residential area.</p>
<p>4.60</p> <p>7.10</p> <p>10.16</p> <p>10.84</p> <p>11.70</p> <p>13.00</p> <p>13.90</p> <p>16.60</p> <p>19.40</p> <p>20.32</p>	<p>Fence, bears E. and W.</p> <p>Billy Creek, 10 lks. wide, 1 ft. deep, course NE.</p> <p>Point for the C-S-SE 1/64 sec. cor. of sec. 32, not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">Cor. 3, H.E.S. No. 209, bears N. 89°56' E., 23 lks. dist., monumented by a basalt stone, 15x12x8 ins. above ground, mkd. HES on SE. face and X on top, firmly set at a fence cor., fences bear S. and E.</p> <p>South side of small temporary storage shed at a point 5 lks. W. of the SE. cor.</p> <p>Enter Billy Creek, 30 lks. wide, 1 ft. deep, course N.; through dense undergrowth.</p> <p>Fence, bears irregularly E. and W.</p> <p>Leave Billy Creek, course N. 20° E.; enter dense timber.</p> <p>Billy Creek, 120 lks. wide, 3 ft. deep, course NW.</p> <p>Fence, bears very irregularly SE. and NW.</p> <p>Point for the SE 1/16 sec. cor. of sec. 32, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$ sec. 32.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>

Survey, Subdivision Sec. 32, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">SE $\frac{1}{16}$ S32 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 53$\frac{1}{2}$° E., 65 lks. dist., mkd. SE 1/16 S32 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 15° E., 10 lks. dist., mkd. SE 1/16 S32 BT.</p>
25.50	Top of ascent; desc. into Thompson Creek
27.60	Thompson Creek, 100 lks. wide, 5 ft. deep, course N. 60° W.; asc. S. slope.
36.50	Power line, bears S. 47°45' E. and N. 47°45' W.
37.70	Power line, bears S. 47°45' E. and N. 47°45' W.
40.62	The point for the C-E 1/16 sec. cor. of sec. 32.
	<p>From the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>S. 89°53' W., on the E. and W. center line of the SE$\frac{1}{4}$ sec. 32.</p> <p>Over gently rolling land, through moderate timber.</p>
1.50	Power line, bears S. 47°45' E. and N. 47°45' W.
2.70	Power line, bears S. 47°45' E. and N. 47°45' W.
16.00	Low rim, bears N. and S.; desc. W. slope.
20.25	The SE 1/16 sec. cor. of sec. 32.
20.50	Fence, bears very irregularly SE. and NW.
23.00	Billy Creek, 100 lks. wide, 3 ft. deep, course NW.
23.50	Same fence, bears very irregularly N. 60° E. and S. 60° W.
40.43	The point for the C-S 1/16 sec. cor. of sec. 32.
	<p>Lines 2-3 and 3-4 of H.E.S. No. 209 in the SE$\frac{1}{4}$ sec. 32, were retraced to obtain a closure within limits. Line 2-3 is N. 0°39' W., 10.16 chs. dist. Line 3-4 is N. 89°56' E., 19.99 chs.</p>
	Subdivision, Sec. 17
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.</p> <p>N. 0°58' W., on the N. and S. center line of sec. 17.</p> <p>Desc. gentle N. slope, through dense timber.</p>
40.17	<p>Point for the C$\frac{1}{4}$ sec. cor. of sec. 17, at the intersection with the E. and W. center line of sec. 17.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>

Survey, Subdivision Sec. 17, T. 9 N., R. 23 E.

CHAINS		
	<p style="text-align: center;">C$\frac{1}{4}$ S17 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears N. 34° E. 50 lks. dist., mkd. C$\frac{1}{4}$ S17 BT.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 63$\frac{1}{2}$° W., 33 lks. dist., mkd. C$\frac{1}{4}$ S17 BT.</p> <p>Raise a mound of stone W. of the cor.</p>	
51.40	Jeep road, bears E. and W.	
55.40	Wash, 20 lks. wide, 2 ft. deep, drains W.	
60.315	Point for the C-N 1/16 sec. cor. of sec. 17.	
	Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.	
	$\begin{array}{c} \text{C} \\ \text{N } \frac{1}{16} \text{ S17} \\ \text{16} \\ \text{C} \\ \text{1967} \end{array}$	
	<p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 59° E., 35 lks. dist., mkd. C N 1/16 S17 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 89°W., 50 lks. dist., mkd. X BT.</p> <p>Raise a mound of stone W. of cor.</p>	
61.10	Fence, bears E. and W.	
74.00	Morgan Wash, at confluence with ravine, drains SW.; continue in ravine.	
80.46	The $\frac{1}{4}$ sec. cor. of secs. 8 and 17.	
	<p>Land, gently rolling. Soil, clay loam, rocky. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.</p> <p>S. 89°50' W., on the E. and W. center line of sec. 17.</p> <p>Over gently rolling land, through dense timber.</p>	
20.335	Point for the C-E 1/16 sec. cor. of sec. 17, not monumented.	
40.67	The C $\frac{1}{4}$ sec. cor. of sec. 17.	
61.46	Point for the C-W 1/16 sec. cor. of sec. 17, not monumented.	
82.25	The $\frac{1}{4}$ sec. cor. of secs. 17 and 18.	

Survey, Subdivision Sec. 17, T. 9 N., R. 23 E.

CHAINS

Land, gently rolling.
Soil, clay loam, rocky.
Timber, pine, oak and juniper.
Undergrowth, bunch grass.

Subdivision NE $\frac{1}{4}$ Sec. 17

From the point for the C-E 1/16 sec. cor. of sec. 17.
N. 0°44' W., on the N. and S. center line of the NE $\frac{1}{4}$ sec. 17.

Over gently rolling land, through dense timber.

15.50 Jeep road, bears E. and W.

19.62 Fence, bears E. and W.

20.12 Point for the NE 1/16 sec. cor. of sec. 17, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ sec. 17.

Set the iron post 20 ins. in the ground, brass cap mkd.

NE $\frac{1}{16}$
S17
1967

from which

A pine, 13 ins. diam., bears S. 80 $\frac{3}{4}$ ° E.,
20 lks. dist., mkd. T9NR23E NE 1/16 S17 BT.

A pine, 10 ins. diam., bears S. 55 $\frac{1}{4}$ ° W., 23
lks. dist., mkd. NE 1/16 S17 BT.

Raise a mound of stone W. of cor.

40.24 The E 1/16 sec. cor. of secs. 8 and 17.

From the point for the N 1/16 sec. cor. of secs. 16 and 17.

S. 89°52'30" W., on the E. and W. center line of the NE $\frac{1}{4}$ sec. 17.

Over gently rolling land, through dense timber.

19.68 Fence, bears N. and S.

20.43 The NE 1/16 sec. cor. of sec. 17.

28.60 Fence, bears irregularly N. 86° W. and S. 86° E.

40.84 The C-N 1/16 sec. cor. of sec. 17.

Subdivision, NW $\frac{1}{4}$ Sec. 17

From the C-W 1/16 sec. cor. of sec. 17.

N. 0°34' W., on the N. and S. center line of the NW $\frac{1}{4}$ sec. 17.

Over gentle N. slope, through moderate timber.

Survey, Subdivision Sec. 17, T. 9 N., R. 23 E.

CHAINS	
17.60	Jeep road, bears S. 70° E. and N. 70° W.
20.16	Point for the NW 1/16 sec. cor. of sec. 17, at the intersection with the E. and W. center line of the NW 1/4 sec. 17, not monumented.
20.60	Fence, bears irregularly E. and W.
21.50	Morgan Wash, 15 lks. wide, 3 ft. deep, drains N. 80° W.; asc. S. slope.
40.32	The point for the W 1/16 sec. cor. of secs. 8 and 17.
5.16	<p>From the C-N 1/16 sec. cor. of sec. 17.</p> <p>S. 89°53' W., on the E. and W. center line of the NW 1/4 sec. 17.</p> <p>Over gently rolling land, through moderate timber.</p> <p>Point for the C-E-E-NW 1/256 sec. cor. of sec. 17.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C-E-E-NW 1 256 S17 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears S. 71° E., 103 lks. dist., mkd. C E E NW 1/256 S17 BT.</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. 69 1/2° W., 89 lks. dist., mkd. X BT.</p> <p>The cor. is located near top of NE. rim of ravine.</p>
7.00	Bottom of ravine, drains NW.
20.645	The point for the NW. 1/16 sec. cor. of sec. 17.
24.00	Jeep road, bears S. 70° E. and N. 70° W.
41.29	The N 1/16 sec. cor. of sec. 17 and 18.
Subdivision, Sec. 8	
3.10	<p>From the 1/4 sec. cor. of secs. 8 and 17.</p> <p>N. 0°26' W., on the N. and S. center line of sec. 8.</p> <p>Asc. over gently rolling land, through dense timber.</p> <p>Fence, bears NE. and SW.</p>
5.054	<p>Point for the C-S-S-S 1/256 sec. cor. of sec. 8.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">C-S-S-S 1 256 S8 1967</p>

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
	<p>from which</p> <p>A pine, 6 ins. diam., bears S. 75° W., 29 lks. dist., mkd. C S S S 1/256 S8 BT.</p>
11.00	Jeep road, bears N. 60° E. and S. 60° W.
20.215	Point for the C-S 1/16 sec. cor. of sec. 8, not monumented.
40.43	<p>Point for the C$\frac{1}{4}$ sec. cor. of sec. 8, at the intersection with the E. and W. center line of sec. 8.</p> <p>Set the iron post 20 ins. in the ground; brass cap mkd.</p> <p style="text-align: center;">T9N R23E C$\frac{1}{4}$ S8 1967</p>
	<p>from which</p> <p>A pine, 6 ins. diam., bears N. 71° E., 37 lks. dist., mkd. C$\frac{1}{4}$ S8 BT.</p> <p>Raise a mound of stone W. of cor.</p>
60.66	Point for the C-N 1/16 sec. cor. of sec. 8, not monumented.
70.775	Point for the C-N-N 1/64 sec. cor. of sec. 8, not monumented.
73.60	Power line, bears N. 65° E. and S. 65° W.
75.50	Fence, bears E. and W.
75.832	Point for the C-N-N-N 1/256 sec. cor. of sec. 8, not monumented.
76.40	Enter open field, edge bears E. and W.
80.89	<p>The point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.</p> <p>S. 89°51'30" W., on the E. and W. center line of sec. 8.</p> <p>Over gently rolling land, through dense timber.</p>
.12	Fence, bears N. and S.
20.39	<p>Point for the C-E 1/16 sec. cor. of sec. 8.</p> <p>Set the iron post 20 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C-E $\frac{1}{16}$ S8 1967</p>

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
	<p>from which</p> <p>A pine, 8 ins. diam., bears N. 34° E., 20 lks. dist., mkd. C E 1/16 S8 BT.</p> <p>An iron pipe, 1½ ins. diam., bears S. 61°40' W., 25 lks. dist., with a Forest Service Boundary Sign alongside.</p> <p>Raise a mound of stone W. of cor.</p>
21.00	A fence cor., bears North, 2 lks. dist., fences bear S. and E.
40.78	The C¼ sec. cor. of sec. 8.
60.99	Point for the C-W 1/16 sec. cor. of sec. 8, not monumented.
62.80	Gravelled road, bears N. and S.
81.20	The ½ sec. cor. of secs. 7 and 8.
	<p>Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>
<p>Subdivision, SE¼ Sec. 8</p> <hr style="width: 20%; margin: auto;"/>	
	<p>From the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>N. 0°35' W., on the N. and S. center line of the SE¼ sec. 8.</p> <p>Over rolling land, through moderate timber, asc. S. slope.</p>
.70	Fence, bears NW. and SE.
5.056	Point for the C-S-S-SE 1/256 sec. cor. of sec. 8.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>C-S-S-SE $\frac{1}{256}$</p> <p>S8</p> <p>1967</p>
	<p>from which</p> <p>A pine, 7 ins. diam., bears N. 80° W., 28 lks. dist., mkd. C S S SE 1/256 S8 BT.</p>
10.30	Top of small knoll, desc. N. slope.
15.20	Base of knoll, thence over gently rolling land.
17.20	Morgan Wash, 50 lks. wide, 3 ft. deep, drains SW.
20.225	Point for the SE 1/16 sec. cor. of sec. 8, at the intersection with the E. and W. center line of the SE¼ sec. 8, not monumented.
22.70	Jeep road, bears E. and W.

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
28.60	Jeep road, bears E. and W.
40.45	The C-E 1/16 sec. cor. of sec. 8.
	From the point for the S 1/16 sec. cor. of secs. 8 and 9.
	S. 89°54' W., on the E. and W. center line of the SE $\frac{1}{4}$ sec. 8.
	Over gently rolling land, through moderate timber.
7.00	Jeep road, bears S. 60° E. and N. 60° W.
20.485	The point for the SE 1/16 sec. cor. of sec. 8.
20.70	Fence, bears N. and S.
30.10	Jeep road, bears N. 70° E. and S. 70° W.
40.93	The point for the C-S 1/16 sec. cor. of sec. 8.
	Subdivision, NE $\frac{1}{4}$ Sec. 8
	From the C-E 1/16 sec. cor. of sec. 8.
	N. 0°48' W., on the N. and S. center line of the NE $\frac{1}{4}$ sec. 8.
	Over gently rolling land, through moderate timber.
.02	Fence, bears E. and W.
20.31	Point for the NE 1/16 sec. cor. of sec. 8, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ sec. 8, not monumented.
30.20	Power line, bears S. 75° E. and N. 75° W.
30.47	Point for the C-N-NE 1/64 sec. cor. of sec. 8, not monumented.
40.63	The point for the E 1/16 sec. cor. of secs. 5 and 8.
	From the N 1/16 sec. cor. of secs. 8 and 9.
	S. 89°40' W., on the E. and W. center line of the NE $\frac{1}{4}$ sec. 8.
	Over gently rolling land, through open field.
.73	Fence, bears N. and S.; enter moderate timber.
20.26	The point for the NE 1/16 sec. cor. of sec. 8.
30.39	Point for the C-W-NE 1/64 sec. cor. of sec. 8, not monumented.
40.52	The point for the C-N 1/16 sec. cor. of sec. 8.
	From the point for the C-W-NE 1/64 sec. cor. of sec. 8.

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
	<p>N. 0°36' W., on the N. and S. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 8.</p>
	<p>Over gently rolling land, through moderate timber.</p>
10.13	<p>Point for the NW-NE 1/64 sec. cor. of sec. 8, at the intersection with the E. and W. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 8, not monumented.</p>
12.40	<p>Power line, bears S. 75° E. and S. 75° W.</p>
13.50	<p>Power line, bears S. 10° E. and N. 10° W.</p>
15.205	<p>Point for the C-N-NW-NE 1/256 sec. cor. of sec. 8.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">C-N-NW-NE $\frac{1}{256}$ S8 1967</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 35° E., 25 lks. dist., mkd. C-N NW-NE 1/256 S8 BT.</p>
20.28	<p>The W-E 1/64 sec. cor. of secs. 5 and 8.</p>
	<p>From the point for the C-N-NE 1/64 sec. cor. of sec. 8.</p>
	<p>S. 89°31' W., on the E. and W. center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$ sec. 8.</p>
	<p>Over gently rolling land, through moderate timber.</p>
.06	<p>Power line, bears S. 75° E. and N. 75° W.</p>
10.09	<p>The point for the NW-NE 1/64 sec. cor. of sec. 8.</p>
20.19	<p>The point for the C-N-N 1/64 sec. cor. of sec. 8.</p>
	<p style="text-align: center;">Subdivision NW$\frac{1}{4}$ Sec. 8</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the C-W 1/16 sec. cor. of sec. 8.</p>
	<p>N. 0°16' W., on the N. and S. center line of the NW$\frac{1}{4}$ sec. 8.</p>
	<p>Over gently rolling land, through dense timber.</p>
20.17	<p>Point for the NW 1/16 sec. cor. of sec. 8, at the intersection with the E. and W. center line of the NW$\frac{1}{4}$ sec. 8.</p>
21.90	<p>Power line, bears N. 60° E. and S. 60° W.</p>
30.255	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 8, not monumented.</p>
40.34	<p>The point for the W 1/16 sec. cor. of secs. 5 and 8.</p>

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
<p>10.09</p> <p>16.90</p> <p>20.18</p> <p>23.10</p> <p>24.60</p> <p>25.20</p> <p>40.34</p>	<p>From the point for the C-N 1/16 sec. cor. of sec. 8.</p> <p>S. 89°38' W., on the E. and W. center line of the NW$\frac{1}{4}$ sec. 8.</p> <p>Over gently rolling land, through dense timber.</p> <p>Point for the C-E-NW 1/64 sec. cor. of sec. 8, not monumented.</p> <p>Track road, bears irregularly N. 20° E. and S. 20° W.</p> <p>The point for the NW 1/16 sec. cor. of sec. 8.</p> <p>Power line, bears N. 60° E. and S. 60° W.</p> <p>Power line, bears S. 20° E. and N. 20° W.</p> <p>Gravelled road, bears S. 20° E. and N. 20° W.</p> <p>The point for the N 1/16 sec. cor. of secs. 7 and 8.</p>
<p>7.10</p> <p>10.11</p> <p>15.16</p> <p>20.21</p>	<p>From the point for the C-E-NW 1/64 sec. cor. of sec. 8.</p> <p>N. 0°21' W., on the N. and S. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 8.</p> <p>Over gently rolling land, through dense timber.</p> <p>Power line, bears N. 60° E. and S. 60° W.</p> <p>Point for the NE-NW 1/64 sec. cor. of sec. 8, at the intersection with the E. and W. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 8, not monumented.</p> <p>Point for the C-N-NE-NW 1/256 sec. cor. of sec. 8, not monumented.</p> <p>The point for the E-W 1/64 sec. cor. of secs. 5 and 8.</p>
<p>4.90</p> <p>5.037</p> <p>10.075</p> <p>15.50</p> <p>20.15</p>	<p>From the point for the C-N-N 1/64 sec. cor. of sec. 8.</p> <p>S. 89°33' W., on the E. and W. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 8.</p> <p>Over gently rolling land, through dense timber.</p> <p>Power line, bears N. 60° E. and S. 60° W.</p> <p>Point for the C-E-NE-NW 1/256 sec. cor. of sec. 8, not monumented.</p> <p>The point for the NE-NW 1/64 sec. cor. of sec. 8.</p> <p>Track road, bears N. and S.</p> <p>The point for the C-N-NW 1/64 sec. cor. of sec. 8.</p>
	<p>From the point for the C-E-NE-NW 1/256 sec. cor. of sec. 8.</p> <p>N. 0°25' W., on the N. and S. center line of the NE$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ sec. 8.</p>

BOOK 4867

174

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
	Over nearly level land, through dense timber.
5.00	Fence, bears E. and W., enter open field.
5.05	Point for the NE-NE-NW 1/256 sec. cor. of sec. 8, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 8.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	NE-NE-NW $\frac{1}{256}$
	S8
	1967
	from which
	A pine, 12 ins. diam., bears S. 36° E., 31 lks. dist., mkd. NE NE NW 1/256 S8 BT.
	A pine, 6 ins. diam., bears S. 27° W., 24 lks. dist., mkd. X BT.
	A fence cor., bears S. 81° W., 20 lks. dist., fences bear N. and E.
	Set a wooden post, 4 ins. diam., 7 ft. long, alongside the iron post.
10.11	The E-E-W 1/256 sec. cor. of secs. 5 and 8.
	From the point for the C-N-N-N 1/256 sec. cor. of sec. 8.
	S. 89°30' W., on the E. and W. center line of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$ sec. 8.
	Over a nearly level open field.
5.04	The NE-NE-NW 1/256 sec. cor. of sec. 8.
5.25	Fence, bears N. and S.; enter moderate timber.
10.07	The point for the C-N-NE-NW 1/256 sec. cor. of sec. 8.
	Subdivision, Sec. 5
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.
	N. 2°00' E., on the N. and S. center line of sec. 5.
	Over nearly level open field.
10.123	Point for the C-S-S 1/64 sec. cor. of sec. 5, not monumented.
14.40	Fence, bears E. and W.; enter dense timber.
14.90	Track road, bears E. and W.
15.184	Point for the C-N-S-S 1/256 sec. cor. of sec. 5, not monumented.
20.20	Bladed road, bears S. 30° E. and N. 30° W.

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
20.245	Point for the C-S 1/16 sec. cor. of sec. 5, not monumented.
23.30	Gravelled road, bears N. 70° E. and S. 70° W.
40.49	Point for the C $\frac{1}{4}$ sec. cor. of sec. 5, at the intersection with the E. and W. center line of sec. 5.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T9N R23E
	C $\frac{1}{4}$
	S5
	1967
	from which
	A pine, 6 ins. diam., bears N. 52 $\frac{3}{4}$ ° E., 42 lks. dist., mkd. X BT.
	A pine, 25 ins. diam., bears S. 87° W., 67 lks. dist., mkd. C $\frac{1}{4}$ S5 BT.
80.70	Track road, bears irregularly NE. and SW.
81.90	The $\frac{1}{4}$ sec. cor. of sec. 5, only, on the N. bdy. of the Tp., monumented by an iron post 1 in. diam., set, mkd. and witnessed as described in the official records of the 1935 resurvey.
	Land, gently rolling.
	Soil, clay loam.
	Timber, pine, juniper and oak.
	Undergrowth, grass.
	From the $\frac{1}{4}$ sec. cor. of sec. 4 and 5.
	N. 89°47' W., on the E. and W. center line of sec. 5.
	Over gently rolling land, through dense timber, desc. W. slope.
16.80	Track road, bears irregularly N. 30° E. and S. 30° W.; bottom of desc.; thence over gently rolling land.
19.375	Point for the C-E 1/16 sec. cor. of sec. 5, not monumented.
21.60	Track road, bears irregularly SE. and NW.
38.75	The C $\frac{1}{4}$ sec. cor. of sec. 5.
54.10	Track road, bears N. and S.; asc. E. slope.
58.93	Point for the C-W 1/16 sec. cor. of sec. 5, not monumented.
79.11	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	Land, gently rolling.
	Soil, clay loam.
	Timber, pine, oak and juniper.
	Undergrowth, bunch grass and scrub oak.

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
	<p>Subdivision, SE$\frac{1}{4}$ Sec. 5</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>N. 0°55' E., on the N. and S. center line of the SE$\frac{1}{4}$ sec. 5.</p> <p>Over gently rolling land, through dense timber.</p>
10.055	Point for the C-S-SE 1/64 sec. cor. of sec. 5, not monumented.
20.11	Point for the SE 1/16 sec. cor. of sec. 5, at the intersection with the E. and W. center line of the SE $\frac{1}{4}$ sec. 5, not monumented.
23.80	Track road, bears S. 80° E. and N. 80° W.
30.50	Gravelled road, bears N. 70° E. and S. 70° W.
38.20	Track road, bears irregularly SE. and NW.
40.22	The point for the C-E 1/16 sec. cor. of sec. 5.
	<p>From the point for the S 1/16 sec. cor. of secs. 4 and 5.</p> <p>S. 89°46' W., on the E. and W. center line of the SE$\frac{1}{4}$ sec. 5.</p> <p>Over nearly level open field.</p>
.12	The east side of a frame building.
.60	The west side of same building.
.65	Fence, bears N. and S.; enter moderate timber.
4.40	Track road, bears S. 50° E. and N. 50° W.
19.77	The point for the SE 1/16 sec. cor. of sec. 5.
29.645	Point for the C-W-SE 1/64 sec. cor. of sec. 5, not monumented.
39.50	Bladed road, bears S. 30° E. and N. 30° W.
39.52	The point for the C-S 1/16 sec. cor. of sec. 5.
	<p>From the W-E 1/64 sec. cor. of secs. 5 and 8.</p> <p>N. 1°28' E., on the N. and S. center line of the SW$\frac{1}{4}$SE$\frac{1}{4}$ sec. 5.</p> <p>Over gently rolling land, through dense timber.</p>
10.09	Point for the SW-SE 1/64 sec. cor. of sec. 5, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 5, not monumented.
15.135	Point for the C-N-SW-SE 1/256 sec. cor. of sec. 5.
	Set the iron post 20 ins. in the ground, brass cap mkd.

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">C-N-SW-SE $\frac{1}{256}$ S5 1967</p> <p>from which</p> <p>A pine, 13 ins. diam., bears N. 21° E., 22 lks. dist., mkd. C N SW SE 1/256 S5 BT.</p> <p>A pine, 10 ins. diam., bears S. 50° E., 28 lks. dist., mkd. C N SW SE 1/256 S5 BT.</p> <p>Raise a mound of stone W. of cor.</p>
20.18	The point for the C-W-SE 1/64 sec. cor. of sec. 5.
	<p>From the point for the C-S-SE 1/64 sec. cor. of sec. 5.</p> <p>S 89°37' W., on the E. and W. center line of the SW$\frac{1}{4}$ SE$\frac{1}{4}$ sec. 5.</p> <p>Desc. W. slope, through dense timber.</p>
9.97	The point for the SW-SE 1/64 sec. cor. of sec. 5.
10.60	Fence, bears N. and S.; enter nearly level open field.
13.00	Power line, bears S. 10° E. and N. 10° W.
19.94	The point for the C-S-S 1/64 sec. cor. of sec. 5.
	<p style="text-align: center;">Subdivision, SW$\frac{1}{4}$ Sec. 5</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>N. 1°54' E., on the N. and S. center line of the SW$\frac{1}{4}$ sec. 5.</p> <p>Over gently rolling land, through dense timber.</p>
.50	Track road, bears irregularly W. and N. 60° E.
10.20	Point for the C-S-SW 1/64 sec. cor. of sec. 5, not monumented.
15.80	Gravelled road, bears N. 70° E. and S. 70° W.
20.40	Point for the SW 1/16 sec. cor. of sec. 5, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$ of sec. 5, not monumented.
40.79	The point for the C-W 1/16 sec. cor. of sec. 5.
	<p>From the point for the C-S 1/16 sec. cor. of sec. 5.</p> <p>S. 89°50' W., on the E. and W. center line of the SW$\frac{1}{4}$ sec. 5.</p> <p>Over nearly level land, through moderate timber.</p>
5.038	Point for the C-E-E-SW 1/256 sec. cor. of sec. 5, not monumented.

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
8.00	Gravelled road, bears N. 70° E. and S. 70° W.
10.075	Point for the C-E-SW 1/64 sec. cor. of sec. 5, not monumented.
11.40	Track road, bears S. 20° E. and N. 20° W.
17.00	Track road, bears N. and S.
20.15	The point for the SW 1/16 sec. cor. of sec. 5.
39.80	Bladed road, bears N. and S.
40.28	The point for the S 1/16 sec. cor. of secs. 5 and 6.
	<p>From the point for the E-W 1/64 sec. cor. of secs. 5 and 8.</p> <p>N. 1°56' E., on the N. and S. center line of the SE$\frac{1}{4}$SW$\frac{1}{4}$ sec. 5.</p> <p>Over gently rolling land, through dense timber.</p>
.50	Track road, bears N. 15° E. and S. 15° W.
10.165	Point for the SE-SW 1/64 sec. cor. of sec. 5, at the intersection with the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 5, not monumented.
15.245	Point for the C-N-SE-SW 1/256 sec. cor. of sec. 5, not monumented.
19.50	Gravelled road, bears N. 70° E. and S. 70° W.
20.325	The point for the C-E-SW 1/64 sec. cor. of sec. 5.
	<p>From the point for the C-S-S 1/64 sec. cor. of sec. 5.</p> <p>S. 89°37' W., on the E. and W. center line of the SE$\frac{1}{4}$SW$\frac{1}{4}$ sec. 5.</p> <p>Over nearly level open field.</p>
5.035	Point for the C-E-SE-SW 1/256 sec. cor. of sec. 5, not monumented.
5.80	Fence, bears N. and S., enter dense timber.
8.00	Track road, bears N. and S.
10.07	The point for the SE-SW 1/64 sec. cor. of sec. 5.
20.14	The point for the C-S-SW 1/64 sec. cor. of sec. 5.
	<p>From the point for the C-E-SE-SW 1/256 sec. cor. of sec. 5.</p> <p>N. 1°56' E., on the N. and S. center line of the NE$\frac{1}{4}$SE$\frac{1}{4}$SW$\frac{1}{4}$ sec. 5.</p> <p>Over nearly level open field.</p>
4.30	Fence, bears E. and W.; leave field.

Survey, Subdivision Sec. 8, T. 9 N., R. 23 E.

CHAINS	
4.70	Track road, bears E. and W.; enter dense timber.
5.07	Point for the NE-SE-SW 1/256 sec. cor. of sec. 5, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 5.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	NE-SE-SW $\frac{1}{256}$ S5 1967
	from which
	A pine, 6 ins. diam., bears N. 21° W., 17 lks. dist., mkd. NE SE SW 1/256 S5 BT.
10.14	The point for the C-E-E-SW 1/256 sec. cor. of sec. 5.
	From the point for the C-N-S-S 1/256 sec. cor. of sec. 5 S. 89°42' W., on the E. and W. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ SW $\frac{1}{4}$ sec. 5.
	Over nearly level land, through dense timber.
5.04	The NE-SE-SW 1/256 sec. cor. of sec. 5.
10.07	The point for the C-N-SE-SW 1/256 sec. cor. of sec. 5.
	Subdivision, Sec. 31
	From the point for the standard $\frac{1}{4}$ sec. cor. of sec. 31, on the S. bdy. of the Tp.
	N. 0°16' E., on the N. and S. center line of sec. 31.
	Through a private residential area in Pine Top, Arizona.
3.00	Woodland Lake Road, gravelled, bears E. and W.
10.50	West Way, bladed dirt, bears N. 30° W. and S. 30° E.
18.80	Arizona Highway No. 173, paved, bears N. 30° W. and S. 30° E.
20.04	Point for the C-S 1/16 sec. cor. of sec. 31, not monumented.
27.00	Pineview Drive, gravelled, bears N. 61° E. and S. 61° W.
36.10	Evergreen Drive, paved, bears S. 28° E. and N. 28° W.
40.08	The C $\frac{1}{4}$ sec. cor. of sec. 31, monumented by a re-bar, $\frac{1}{2}$ in. diam., firmly set in a collar of stone. This point is used and accepted by local land owners.
	Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.

Survey, Subdivision Sec. 31, T. 9 N., R. 23 E.

CHAINS		
	<p style="text-align: center;">C$\frac{1}{4}$ S31 1967</p> <p>from which</p> <p>A pine, 10 ins. diam., bears N. 17° E. 76 lks. dist., mkd. C$\frac{1}{4}$ S31 BT.</p> <p>A pine, 22 ins. diam., bears N. 63° E. 113 lks. dist., mkd. C$\frac{1}{4}$ S31 Bt.</p> <p>A cor. pole of power line, bears S. 60° E., 22 lks. dist., power line bears N. and E.</p> <p>Reset the re-bar alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°42' W., beginning new measurement.</p> <p>Along utility right-of-way.</p>	
10.90	Track road, bears SE. and NW.	
17.90	N. end of utility right-of-way; enter moderate timber.	
18.50	Track road, bears NE. and SW.	
20.19	<p>The C-N 1/16 sec. cor. of sec. 31, monumented by a water pipe, $\frac{1}{2}$ in. diam., firmly set, mkd. LS 1651. This point is used and accepted by local land owners.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>C N $\frac{1}{16}$ S31 1 6 C 1967</p> </div> <p>from which</p> <p>A pine, 9 ins. diam., bears N. 14° E., 22 lks. dist., mkd. CN 1/16 S31 BT.</p> <p>A pine, 10 ins. diam., bears N. 57° W., 38 lks. dist., mkd. C-N 1/16 S31 BT.</p> <p>Reset the water pipe alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°32' E., beginning new measurement.</p>	
5.00	Billy Creek, 200 lks. wide, course S. 60° W.	
20.44	<p>The $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 31 and 32.</p> <p>S. 89°23' W., on the E. and W. center line of sec. 31.</p> <p>Over gently rolling land, through dense timber.</p>	

Survey, Subdivision Sec. 31, T. 9 N., R. 23 E.

CHAINS	
7.70	Billy Creek, 30 lks. wide, 3 ft. deep, course NW.
20.46	Point for the C-E 1/16 sec. cor. of sec. 31, not monumented.
25.00	Bladed road, bears S. 60° E. and N. 60° W.
30.69	The C-W-E 1/64 sec. cor. of sec. 31, monumented by a water pipe, ½ in. diam., firmly set. This point is used and accepted by local land owners.
	Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.
	$\begin{array}{c} \text{W-E } \frac{1}{64} \\ \text{C } \frac{\quad}{\text{S31}} \text{ C} \\ 1967 \end{array}$
	from which
	A pine, 10 ins. diam., bears N. 45° E., 15 lks. dist., mkd. C W E 1/64 S31 Bt.
	A pine, 9 ins. diam., bears S. 38° E., 28 lks. dist., mkd. C W E 1/64 S31 BT.
	A spike in cor. pole of a power line, bears S. 53° W., 13 lks. dist. power line bears S. and W.
	Reset the water pipe alongside the iron post.
	<hr style="width: 20%; margin: auto;"/>
	N. 89°55' W., beginning new measurement.
	Along utility right-of-way.
2.50	Bladed road, bears N. and S.
9.80	Power line, bears N. and S.
10.01	The C¼ sec. cor. of sec. 31.
	<hr style="width: 20%; margin: auto;"/>
	N. 89°32' W., beginning new measurement.
	Through private residential area.
2.20	Evergreen Drive, bears S. 30° E. and N. 30° W.
6.90	East Way, bears S. 30° E. and N. 30° W.
11.80	Arizona Highway No. 173, bears S. 30° E. and N. 30° W.
17.20	Juniper Road, bears N. and S.
20.14	The C-W 1/16 sec. cor. of sec. 31, monumented by a water pipe, ½ in. diam., firmly set. This point is used and accepted by local landowners.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	$\begin{array}{c} \text{W } \frac{1}{16} \\ \text{C } \frac{\quad}{\text{S31}} \text{ C} \\ 1967 \end{array}$

Survey, Subdivision Sec. 31, T. 9 N., R. 23 E.

CHAINS		
20.12	<p>from which</p> <p>A pine, 12 ins. diam., bears S. 47° W., 46 lks. dist., mkd. C-W 1/16 S31 BT.</p> <p>A nail in power pole, bears S. 4° E., 6 lks. dist.; power line bears N., S. and W.</p> <p>Reset the water pipe alongside the iron post.</p> <hr/> <p>N. 89°53' W., beginning new measurement.</p> <p>Along a utility right-of-way at the N. edge of timber and the S. edge of residential area.</p> <p>The C$\frac{1}{4}$ sec. cor. of secs. 31 and 36 on the W. bdy. of the Tp.</p> <p>Land, gently rolling to nearly level. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, grass.</p>	
	<p style="text-align: center;">Subdivision, SE$\frac{1}{4}$ Sec. 31</p> <hr/> <p>From the point for the standard E 1/16 sec. cor. of sec. 31, on the S. bdy. of the Tp.</p> <p>North, on the N. and S. center line of the SE$\frac{1}{4}$ sec. 31.</p> <p>Through private residential area.</p> <p>.20 Drainage ditch, 10 lks. wide, 1 ft. deep, drains W.</p> <p>1.20 Arizona Highway No. 173, on a curve, bears E. and NW.</p> <p>2.20 Thence along a utility right-of-way bearing N.</p> <p>17.00 Malapai Road, graded, bears E. and W.</p> <p>17.40 Fence cor., fences bear N. and W.</p> <p>20.02 A cor. pole of a power line, bears West 3 lks. dist., power line bears W. and S.</p> <p>20.07 The SE 1/16 sec. cor. of sec. 31, monumented by a water pipe, $\frac{3}{4}$ in. diam., mkd. LS 1651, and cemented firmly alongside a fence cor. Fences bear S. and E. and W.</p> <hr/> <p>N. 0°56' E., beginning new measurement.</p> <p>Enter dense timber, edge bears E. and W.</p> <p>17.30 Bladed road, bears S. 60° E. and N. 60° W.</p> <p>20.105 The point for the C-E 1/16 sec. cor. of sec. 31.</p>	
	<p>From the S 1/16 sec. cor. of secs. 31 and 32.</p> <p>S. 89°34' W., on the E. and W. center line of the SE$\frac{1}{4}$ sec. 31.</p>	

Survey, Subdivision Sec. 31, T. 9 N., R. 23 E.

CHAINS	
	Over nearly level land.
.75	The remains of a burned out cabin; thence along a fence between the forest to the N. and a residential area to the S.
20.44	The SE 1/16 sec. cor. of sec. 31. <hr/>
	S. 89°50' W., beginning new measurement.
10.00	The C-W-SE 1/64 sec. cor. of sec. 31, monumented by a water pipe, $\frac{3}{4}$ in. diam., firmly set, mkd. LS 1651. At the corner point Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd. CW-SE $\frac{1}{64}$ S31 1967 from which A cor. pole of a power line bears South 3 lks. dist., power line bears N., E. and W. Reset the water pipe alongside the iron post . <hr/>
	S. 89°57' W., beginning new measurement. Through private residential area.
3.00	Evergreen Drive, bears N. and S.
6.00	East Way, bears S. 30° E. and N. 30° W.
10.00	The point for the C-S 1/16 sec. cor. of sec. 31.
	<hr/> Subdivision, SW $\frac{1}{4}$ Sec. 31 <hr/>
	From the point for the standard W 1/16 sec. cor. of sec. 31 or the S. bdy. of the Tp. N. 0°03' W., on the N. and S. center line of the SW $\frac{1}{4}$ sec. 31. Over Woodland Reservoir.
7.00	N. edge of Woodland Reservoir, bears E. and W.; thence over gently rolling land, through dense timber.
10.80	Track road, bears E. and W.
20.05	Point for the SW 1/16 sec. cor. of sec. 31, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$ sec. 31. Set the iron post 22 ins. in the ground, brass cap mkd.

Survey, Subdivision Sec. 31, T. 9 N., R. 23 E.

CHAINS	
	<p style="text-align: center;">SW $\frac{1}{16}$ S31 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. $53\frac{1}{2}^\circ$ W., 26 lks. dist., mkd. SW $\frac{1}{16}$ S31 BT.</p> <p style="padding-left: 40px;">A cor. pole of a power line, bears S. 45° E., 3 lks. dist., power line bears N. and E.</p> <p>Thence along utility right-of-way.</p>
23.00	Oak Road, paved, bears E. A track road bears SW.
40.25	The C-W $\frac{1}{16}$ sec. cor. of sec. 31.
	<p>From the point for the C-S $\frac{1}{16}$ sec. cor. of sec. 31.</p> <p>S. $89^\circ 52'$ W., on the E. and W. center line of the SW $\frac{1}{4}$ sec. 31.</p> <p>Over nearly level land, through private residential area.</p>
.70	Arizona Highway No. 173, bears S. 30° E. and N. 30° W.
5.50	West Way, bears S. 30° E. and N. 30° W.
6.90	Forest Drive, bears N. and S.
10.03	The C-E-SW $\frac{1}{64}$ sec. cor. of sec. 31, monumented by a water pipe, $\frac{3}{4}$ in. diam., firmly set.
	<p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C-E-SW $\frac{1}{64}$ S31 1967</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 28° W., 90 lks. dist., mkd. C E SW $\frac{1}{64}$ S31 BT.</p> <p style="padding-left: 40px;">A cor. pole of a power line, bears N. 66° E., 2 lks. dist., power line bears S. and W.</p> <p>Reset the water pipe alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $89^\circ 44'$ W., beginning new measurement.</p> <p>Along a utility right-of-way, bet. a residential area to the N. and a forest to the S.</p>
10.01	The SW $\frac{1}{16}$ sec. cor. of sec. 31.
10.20	Enter dense timber.
11.00	Track road, bears irregularly N. and S.

Survey, Subdivision Sec. 31, T. 9 N., R. 23 E.

CHAINS	
30.12	The point for the S 1/16 sec. cor. of secs. 31 and 36 on the W. bdy. of the Tp.
Subdivision, NW $\frac{1}{4}$ Sec. 31	
From the C-W 1/16 sec. cor. of sec. 31.	
N. 0°26'30" E., on the N. and S. center line of the NW $\frac{1}{4}$ sec. 31.	
Through a private residential area, along a utility right-of-way.	
3.10	Turkey Track Road, bears E. and W.
6.60	West Way, bears S. 30° E. and N. 30° W.
15.60	Arizona Highway No. 173, bears, S. 30° E. and N. 30° W.
16.80	Billy Creek Road, bladed, bears E. and W.
20.29	The NW 1/16 sec. cor. of sec. 31, monumented by a cedar post, 10 ins. diam., firmly set with 8 ft. above ground. This point is used and accepted by local landowners.
At the corner point	
Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.	
NW $\frac{1}{16}$ S31 1 6 1967	
from which	
A pine, 8 ins. diam., bears N. 44° E., 52 lks. dist., mkd. NW 1/16 S31 BT.	
Reset the cedar post alongside the iron post.	
N. 0°03' E., beginning new measurement.	
6.50	S. edge of Billy Creek, leave residential area and enter forest.
8.50	Billy Creek, 100 lks. wide, drains NW.; asc. along a SW slope.
20.12	The W 1/16 sec. cor. of secs. 30 and 31.
From the C-N 1/16 sec. cor. of sec. 31.	
N. 89°15'30" W., on the E. and W. center line of the NW $\frac{1}{4}$ sec. 31.	
Over gently rolling land, through dense timber.	
5.00	High left bank of Billy Creek, bears W. and NE.; thence along S. edge of Billy Creek.
14.00	High left bank of Billy Creek, bears NW. and E.; enter residential area.

Survey, Subdivision Sec. 31, T. 9 N., R. 23 E.

CHAINS	
19.71	The NW 1/16 sec. cor. of sec. 31.
	<hr/> S. 89°42' W., beginning new measurement.
2.70	Arizona Highway No. 173, bears S. 30° E. and N. 30° W.
3.80	Thence along a utility right-of-way.
10.90	Thence along a fence on the N. side of Pinecrest Road.
20.35	The point for the N 1/16 sec. cor. of secs. 31 and 36 on the W. bdy. of the Tp.
	<hr/> Subdivision, Sec. 30
	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0°22'30" W., on the N. and S. center line of sec. 30.
	Over gently rolling land, through dense timber.
38.20	Spur, slopes E.; desc. N. slope.
39.10	Bladed dirt road, bears E. and W.
40.32	Point for the C1/2 sec. cor. of sec. 30, at the intersection with the E. and W. center line of sec. 30.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">C1/2 S30 1967</p>
	from which
	<p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 40° E., 21 lks. dist., mkd. C1/2 S30 BT.</p>
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 57° W., 30 lks. dist., mkd. C1/2 S30 BT.</p>
	Raise a mound of stone W. of cor.
47.70	Bladed road, bears S. 75° E. and N. 75° W.
47.80	Power line, bears S. 47°45' E. and N. 47°45' W.
48.70	Power line, bears S. 47°45' E. and N. 47°45' W.
80.84	The 1/4 sec. cor. of secs. 19 and 30.
	Land, gently rolling.
	Soil, clay loam.
	Timber, pine, oak and juniper.
	Undergrowth, scrub oak and bunch grass.
	<hr/> From the 1/4 sec. cor. of secs. 29 and 30.
	S. 89°43'30" W., on the E. and W. center line of sec. 30.
	Over gently rolling land, through dense timber.

Survey, Subdivision Sec. 30, T. 9 N., R. 23 E.

CHAINS

- 5.10 Track road, bears irregularly S. 70° E. and N. 70° W.
- 10.00 Same road, bears N. and S.
- 31.30 Power line, bears S. 47°45' E. and N. 47°45' W.
- 32.30 Power line, bears S. 47°45' E. and N. 47°45' W.
- 33.20 Bladed road, bears SE. and NW.; asc. NE. slope.
- 40.39 The $C\frac{1}{4}$ sec. cor. of sec. 30.
- 51.00 Top of ascent on N. slope of Springer Mountain; desc. NW. slope.
- 60.52 Point for the C-W 1/16 sec. cor. of sec. 30, at proportionate dist.

Set the iron post 20 ins. in the ground, brass cap mkd.

T9N R23E
W $\frac{1}{16}$
C ————— C
S30
1967

from which

A pine, 9 ins. diam., bears N. 26½° E.,
34 lks. dist., mkd. C W 1/16 S30 BT.

A pine, 9 ins. diam., bears S. 30½° E.,
30 lks. dist., mkd. X BT.

USGS Triangulation Station Springer Mountain,
bears S. 82°53'30" E. 7.69 chs. dist., monumented
by a standard brass tablet, mkd. U. S. Geological
Survey Bench Mark. The Station is under the
Springer Mountain Lookout Tower.

Raise a mound of stone N. of cor.

- 81.29 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30 on the W. bdy. of the Tp.

Land, rolling.
Soil, clay loam.
Timber, pine, juniper and oak.
Undergrowth, scrub oak and bunch grass.

Subdivision, Sec. 18

- 40.96 From the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
- North, on the N. and S. center line of sec. 18.
- Over gently rolling land, through dense timber.
- Point for the $C\frac{1}{4}$ sec. cor. of sec. 18, at the intersection with the E. and W. center line of sec. 18.
- Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

$C\frac{1}{4}$ S18
1967

Survey, Subdivision Sec. 18, T. 9 N., R. 23 E.

CHAINS		
	<p>from which</p> <p>A pine, 6 ins. diam., bears S. $21\frac{1}{2}^\circ$ W., 22 lks. dist., mkd. $C\frac{1}{4}$ S18 BT.</p> <p>A pine, 8 ins. diam., bears N. 19° W., 21 lks. dist., mkd. $C\frac{1}{4}$ S18 BT.</p>	
59.10	Fence, bears E. and W.	
60.83	<p>Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 18.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ N \frac{1}{16} \quad \quad S 18 \\ C \\ 1967 \end{array}$ </div> <p>Raise a mound of stone W. of cor.</p>	
63.20	S. edge of Evan's Pond, bears E. and W.	
66.00	N. edge of Evan's Pond, bears E. and W.	
71.70	Bladed road, bears N. 60° E. and S. 60° W.	
77.90	Morgan Wash, 150 lks. wide, 20 ft. deep, drains W.	
80.70	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 18.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, oak and juniper. Undergrowth, bunch grass.</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.</p> <p>N. $89^\circ 23'$ W., on the E. and W. center line of sec. 18.</p> <p>Over gently rolling land, through dense timber.</p>	
.30	Fence, bears N. 55° E. and S. 55° W.	
20.185	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 18, not monumented.	
38.70	Fence, bears N. and S.	
40.37	The $C\frac{1}{4}$ sec. cor. of sec. 18.	
78.91	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 18 on the W. bdy. of the Tp.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine, juniper and oak. Undergrowth, bunch grass.</p>	
	<p>Subdivision, NE$\frac{1}{4}$ Sec. 18</p> <hr/> <p>From the point for the C-E $\frac{1}{16}$ sec. cor. of sec. 18.</p>	

Survey, Subdivision Sec. 18, T. 9 N., R. 23 E.

CHAINS	
	N. 0°06' W., on the N. and S. center line of the NE $\frac{1}{4}$ sec. 18.
	Over gently rolling land, through dense timber.
12.00	Creek, 5 lks. wide, water 1 ft. deep, course W. from Porter Spring which is approximately N. 60° E., 11 chs. dist.
12.60	Track road, bears E. and W.
20.03	Point for the NE 1/16 sec. cor. of sec. 18, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ sec. 18.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">NE $\frac{1}{16}$ S18 1967</p>
	from which
	<p style="text-align: center;">A pine, 8 ins. diam., bears N. 22° E., 38 lks. dist., mkd. NE 1/16 S18 BT.</p>
	Raise a mound of stone W. of cor.
30.50	Fence, bears irregularly E. and W.
34.30	S. edge of stock pond, bears E. and W.
36.40	N. edge of stock pond, bears E. and W.
37.90	Jeep road, bears E. and W.
40.06	The E 1/16 sec. cor. of secs. 7 and 18.
	From the N 1/16 sec. cor. of secs. 17 and 18.
	N. 89°50'30" W., on the E. and W. center line of the NE $\frac{1}{4}$ sec. 18.
	Over gently rolling land, through dense timber.
1.30	Fence, bears S. 25° E. and N. 25° W.
20.16	The NE 1/16 sec. cor. of sec. 18.
30.60	Track road, bears S. 15° E. and N. 15° W.
32.90	The E. bank of Evan's Pond, bears S. and NW.
34.00	The W. bank of Evan's Pond, bears SE. and NW.
40.33	The C-N 1/16 sec. cor. of sec. 18.

CHAINS

General Description

Township 9 North, Range 23 East is located at the southern part of Navajo County and within the Sitgreaves National Forest. It is approximately 6 miles south of Show Low. The resort community of Pine Top is partially located in secs. 31 and 32.

The land is gently rolling with the elevation ranging from 6800 feet to 7600 feet above sea level. The general drainage is from East to West with Morgan Wash in the northern portion and Thompson Creek and Billy Creek in the southern portion. The clay loam soil is covered with a moderate to dense growth of pine, juniper and oak. Grass provides some grazing for cattle.

Arizona Highway No. 173, a paved two lane road, enters the township in sec. 30 and exits in sec. 32. The Apache Railroad enters in sec. 34 and exits in sec. 2. Other areas of the township are accessible by gravelled or track roads. Most of the private land within the area is provided with electricity and water and summer cabins are being built.

The mountains are of volcanic origin and cinders for roads are taken from Porter Mountain, in sec. 6, Springer Mountain, in sec. 30 and Pat Mullen Mountain, in sec. 26.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John H. Witmer	Surveying Technician
Howard H. Thomas	Surveying Technician
Ira M. Thiessen	Surveying Aid
Ray E. Thiessen	Surveying Aid
Ronald G. Williams	Surveying Aid
Martin W. Fuller	Surveying Aid
Arvel R. Jones	Surveying Aid
David G. Jaramillo	Surveying Aid
George P. Oviatt	Surveying Aid
Jerrel R. Jones	Surveying Aid
Craig L. Merrill	Surveying Aid
James H. Jolley	Surveying Aid

192

BOOK 4867

CERTIFICATE OF SURVEY

We, Paul G. Bauer, Kenneth D. Herman,
XX Gary T. Oviatt and Jerrold E. Knight , HEREBY CERTIFY upon honor that,

in pursuance of special instructions bearing date of the 23rd day of August , 1967 ,
We
XX have dependently resurveyed the South Boundary (the Second Standard
Parallel North), the East and West Boundaries and Subdivisional Lines,
Retraced a Portion of the North Boundary and Surveyed Subdivisions of
Certain Sections of Township 9 North, Range 23 East,

of the Gila and Salt River Meridian, in the State of Arizona , which
are represented in the foregoing field notes as having been executed by ^{US} ~~me~~ and under ^{our} ~~my~~ direction;
and that said survey has been made in strict conformity with said special instructions, the Manual
of Instructions for the Survey of the Public Lands of the United States, and in specific manner
described in the foregoing field notes.

March 28, 1968
(Date)
March 28, 1968
(Date)
March 28, 1968
(Date)
March 28, 1968
(Date)

Paul G. Bauer
(Cadastral Surveyor)
Kenneth D. Herman
(Cadastral Surveyor)
Gary T. Oviatt
(Cadastral Surveyor)
Jerrold E. Knight
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date OCT 28 1969

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of the South Boundary (the
Second Standard Parallel North), the East and West Boundaries, the Sub-
divisional Lines, the Retracement of the North Boundary and the Survey of
Subdivisions of Certain Sections of Township 9 North, Range 23 East,
Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer, Kenneth D. Herman, Gary T. Oviatt and Jerrold E.
Knight,
having been critically examined and found correct, are hereby approved.

JUN 29 1970
(Date)

Clark F. Lamm
(Chief, Division of ~~Engineering~~
Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Engineering)~~