

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

OF

A PORTION OF THE THIRD STANDARD PARALLEL NORTH

TOWNSHIP 13 NORTH, RANGES 1½ AND 2 EAST

DEPENDENT RESURVEY

OF

A PORTION OF THE SUBDIVISIONAL LINES

AND

SURVEY

OF

SUBDIVISION OF SECTIONS 8 AND 15

TOWNSHIP 12 NORTH, RANGE 2 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Louis D. Gilbert Cadastral Surveyor

Under special instructions dated May 19, 19 67, which provided for the surveys
included under Group Number 454, approved May 19, 1967,
and assignment instructions dated May 19, 19 67.

Survey commenced June 13, 19 67

Survey completed July 6, 19 67

1A

BOOK 4871

INDEX DIAGRAM

Township 12 North, Range 2 East
5 4 3 2 1

	(28)	(24)	(19)	(14)	(10)
6	27 5	23 4	19 3	14 2	9 1
7	26	22	18	13	9
	25 8	21 9	17 10	13 11	8 12
18	24	20	17	12	7
	17	16	16 15	11 14	7 13
19	20	21	15	10	6
			22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Sec. 8 - - - - Page 28
Subdivision of Sec.15 - - - - Page 33

Township 12 North, Range 2 East
Gila and Salt River Meridian, Arizona

CHAINS

The south boundary was surveyed in 1873 by C. B. Foster and resurveyed in 1918 by H. L. Baldwin; the east three miles was resurveyed in 1952 by C. E. Bilbray. The east boundary was surveyed in 1873 by C. B. Foster and resurveyed in 1934 by T. Vander Meer and B. G. Mollette. The north boundary, the Third Standard Parallel North, was surveyed in 1873 by C. B. Foster; the north boundary of Section 4 was retraced in 1910 by J. F. Hesse; a portion of the north boundary was resurveyed in 1917 by G. F. Rigby; the west four miles was resurveyed in 1923 by B. J. Kinsey and Ty White; the east two miles was resurveyed in 1928 by L. R. Hanson. The west boundary was surveyed by J. F. Hesse in 1910; a portion of the west boundary was resurveyed by H. L. Baldwin in 1918. The east half of the township was subdivided by C. B. Foster in 1873; a portion of the NW quarter of the township was subdivided by J. F. Hesse in 1910; the remainder of the township was subdivided by H. L. Baldwin in 1918.

The following field notes are those of a dependent resurvey of a portion of the north boundary, the Third Standard Parallel North, through Township 13 North, Ranges 1½ and 2 East, and a portion of the subdivisional lines of Township 12 North, Range 2 East, designed to restore the corners in their true original location according to the best available evidence, and the survey of subdivisions of sections 8 and 15, Township 12 North, Range 2 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions 1947, and the Special Instructions dated May 19, 1967.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the SE. corner of Section 13, as scaled from USGS & USC&GS quadrangle Mayer, Arizona, dated 1947, Scale 1:62500 is: Latitude 34°24'50" N., and Longitude 112°05'36" W.

The magnetic declination was found to be 15° E.

Dependent Resurvey
of a
Portion of the Third Stan. Par. N., T. 13 N., R. 2 E.

Reestablishment of the Resurvey executed by
L. R. Hanson in 1928

From the Stan. cor. of secs. 35 and 36, T. 13 N., R. 2 E., an iron post, 3 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1928.

N. 89°08' W., along the S. bdy. of sec. 35, T. 13 N., R. 2 E.

Over rolling land.

Dependent Resurvey
of a
Portion of the Third Stan. Par. N., T. 13 N., R. 2 E.

CHAINS	
1.30	Top of ridge and track road, bears N. and S.
4.04	The closing cor. of Tp. 12 N., Rs. 2 and 3 E., monumented by an iron post, 3 ins. in diam., set mkd. and witnessed as described in the official record of the dependent resurvey of the E. bdy., T. 12 N., R. 2E., in 1934.
10.40	Wash, 10 lks. wide, 3 ft. deep, drains S.
26.90	Top of ridge, bears N. and S. 15° E.
36.60	Top of ridge, bears NE. and SW.
41.20	The Stan. $\frac{1}{4}$ sec. cor. of sec. 35, T. 13 N., R. 2 E., an iron post, 1 in. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1928.
	—————
	S. 89°40' W., beginning new measurement.
	Over rolling land.
0.30	Wash, 10 lks. wide, 3 ft. deep, drains S. 40° W.
9.60	Top of spur, slopes SW.
22.10	Wash, 30 lks. wide, 5 ft. deep, drains SE.
40.31	The Stan. cor. of secs. 34 and 35, T. 13 N., R. 2 E., an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1928.
	Land, rolling. Soil, snady loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.
	—————
	S. 89°43' W., along the S. bdy. of sec. 34, T. 13 N., R. 2 E.
	Over rolling land.
4.20	Wash, 15 lks. wide, 4 ft. deep, drains SE.
11.50	Track road, bears S. 10° E. and N. 10° W.
25.70	Wash, 5 lks. wide, 1 ft. deep, drains S. 25° W.
31.20	Top of spur, slopes S.
40.44	The Stan. $\frac{1}{4}$ sec. cor. of sec. 34, T. 13 N., R. 2 E., an iron post, 1 in. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1928.
	—————
	N. 87°24' W., beginning new measurement.
	Over rolling land.
5.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 75° W.
8.60	Wash, 30 lks. wide, 1 ft. deep, drains southerly.

Dependent Resurvey
of a
Portion of the Third Stan. Par. N., T. 13 N., R. 2 E.

CHAINS	
11.00	Top of ridge, bears N. and S.
19.00	Top of spur, slopes S.
24.50	Wash, 5 lks. wide, 1 ft. deep, drains S.
27.80	Track road, bears N. and S.
36.80	Top of spur, slopes S.
39.94	<p>The Stan. cor. of secs. 33 and 34, T. 13 N., R. 2 E., an iron post 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1928.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.</p>
<p>Reestablishment of the Resurvey executed by B. J. Kinsey in 1923</p> <hr/>	
<p>N. 89°46' W., along the S. bdy. of sec. 33, T. 13 N., R. 2 E.</p>	
<p>Over rolling land.</p>	
12.20	Yarber Wash, .40 lks. wide, 3 ft. deep, drains S, 35° E.
15.00	Top of spur, slopes NE.
18.30	Track road, bears N. 80° E. and S. 80° W.
21.00	Track road, bears SE. and S. 80° W.
41.11	<p>Point for the Stan. ¼ sec. cor. of sec. 33, at proportionate dist., there is no remaining evidence of the orig. cor. (originally set as the Stan. ¼ sec. of sec. 34.)</p>
<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
<p>S C T13N R2E <u>¼ S 33</u> 1967</p>	
45.00	Top of ridge, bears SE. and NW.
58.10	<p>Fence, barbed wire, bears S. 10° E. and N. 10° W., and cor. of fences, bears N. 10° W., 58 lks. dist.; fences bear S. 10° E., W. and N. 10° W.</p>
70.30	Wash, 10 lks. wide, 2 ft. deep, drains S. 10° W.
76.90	<p>Fence, barbed wire, bears N. and S., and cor. of fences bears North, 14 lks. dist., fences bear N., E. and S., and cor. of fences bears North, Approx. 1.30 chs. dist., fences bear S. and S. 80° W.</p>
80.60	Track road, bears N. 80° E. and S. 80° W.
82.15	Fence, barbed wire, bears N., E. and W.

Dependent Resurvey
of a
Portion of the Third Stan. Par. N., T. 13 N., R. 2 E.

CHAINS	
82.22	<p>The Stan. cor. of secs. 32 and 33, T. 13 N., R. 2 E., an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1923. Cor. is in fence line extending E. and W.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.</p>
	<p>N. 89°40' W., along the S. bdy. of sec. 32, T. 13 N., R. 2 E.</p> <p>Over rolling land, along fence line.</p>
6.60	Wash, 5 lks. wide, 2 ft. deep, drains S. 10° E.
24.60	Wash, 10 lks. wide, 1 ft. deep, drains S.
37.90	Wash, 20 lks. wide, 4 ft. deep, drains S.
41.00	Wash, 5 lks. wide, 2 ft. deep, drains S.
41.15	<p>The Stan. $\frac{1}{4}$ sec. cor. of sec. 32, T. 13 N., R. 2 E., an iron post, 1 in. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1923. In cor. of fences extending E. and S. 83° 49' W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 83°48' W., beginning new measurement.</p> <p>Over rolling land, along fence line.</p>
8.70	Wash, 10 lks. wide, 5 ft. deep, drains S.
12.70	Brushy Wash, 30 lks. wide, 4 ft. deep, drains S.
39.03	<p>The Stan. cor. of secs. 31 and 32, T. 13 N., R. 2 E., an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1923.</p> <p>from which</p> <p style="padding-left: 40px;">Cor. of fences bears North 1.5 lks. dist.; fences bear N. and N. 83°49' E.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.</p>
	<p>S. 83°48' W., along the S. bdy. of sec. 31, T. 13 N., R. 2 E.</p>
6.20	Track road, bears N. and S. 10° E.
6.90	Top of spur, slopes S. 10° E.
10.81	Angle point, a lava stone, 8x6x4 ins., above ground, mkd. AP on N. face, with mound of stone N.

Dependent Resurvey
of a
Portion of the Third Stan. Par. N. T. 13 N., R. 2 E.

CHAINS	
	N. 89°59' W., continuing measurement. Over rolling land, through scattered timber.
11.21	The closing cor. of secs. 4 and 5, T. 12 N., R. 2 E., hereinafter described.
14.30	Wash, 5 lks. wide, 2 ft. deep, drains S. 10° W.
24.70	Track road, bears N. and S. 15° E.
28.60	Wash, 5 lks. wide, 1 ft. deep, drains S.
39.90	Wash, 5 lks. wide, 2 ft. deep, drains SW.
40.12	The Stan. $\frac{1}{4}$ sec. cor. of sec. 31, T. 13 N., R. 2 E., an iron post, 1 in. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1923.
	—————
	N. 89°59' W., beginning new measurement.
10.62	Angle Point, an iron post, 1 in. in diam., mkd. AP, projecting 12 ins. above ground. West, continuing measurement.
22.10	Rattlesnake Canyon, drains S.
34.50	Wash, 20 lks. wide, 1 ft. deep, drains SE.
40.13	The Stan. cor. of Tp. 13 N., Rs. 1 $\frac{1}{2}$ and 2 E., an iron post, 3 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1923. Land, rolling. Soil, rocky sandy loam. Timber, scattered cedar. Undergrowth, bunch grass, sagebrush, cat claw and cacti.
Dependent Resurvey of a Portion of the Third Stan. Par. N., T. 13 N., R. 1 $\frac{1}{2}$ E.	
Reestablishment of the Resurvey Executed by B. J. Kinsey in 1923	
	—————
	WEST, along the S. bdy. of sec. 36, T. 13 N., R. 1 $\frac{1}{2}$ E. Over rolling land, through scattered cedar timber.
10.64	The closing cor. of secs. 5 and 6, T. 12 N., R. 2 E., hereinafter described.
10.72	Angle Point, a lava stone, 15x12x12 ins., above ground, mkd. AP on W. face, in a mound of stone. Land, rolling. Soil, rocky, sandy loam. Timber, scattered cedar. Undergrowth, bunch grass, sagebrush, cat claw and cacti.
Dependent Resurvey of a Portion of the Subdivisional Lines, T. 12 N., R. 2 E.	
Reestablishment of the Surveys Executed by C. B. Foster in 1873 and J. F. Hesse in 1910	

BOOK 4871

6.

Dependent Resurvey

of a

Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS					
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1934. Cor. is in fence line extending E. and W.</p> <p>N. 89°41' W., bet. secs. 13 and 24.</p> <p>Over rolling land, along fence line.</p>				
15.70	Top of low ridge, bears N. and S.				
27.70	Top of low ridge, bears NE. and SW.				
32.90	Wash, 15 lks. wide, 4 ft. deep, drains S. 55° W.				
36.00	Top of spur, slopes S.				
39.40	Wash, 15 lks. wide, 3 ft. deep, drains S.				
41.03	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R2E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td>$\frac{1}{4}$</td> <td><u>S 13</u></td> </tr> <tr> <td></td> <td>S 24</td> </tr> </table> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence line, bears North, 15 lks. dist., fence bears E. and W.</p> <p>Set a wooden post, 3 ins. in diam., 4 ft. long, alongside the cor.</p>	$\frac{1}{4}$	<u>S 13</u>		S 24
$\frac{1}{4}$	<u>S 13</u>				
	S 24				
44.90	Top of low ridge, bears N. and S.				
59.40	Wash, 50 lks. wide, 1 ft. deep, drains S.				
62.70	Top of spur, slopes S.				
65.60	Wash, 10 lks. wide, 3 ft. deep, drains S. 45° E.				
72.20	Top of low ridge, bears N. and S., and track road, bears N. 15° E. and S., curving SW.				
82.06	<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R2E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td><u>S 14</u></td> <td><u>S 13</u></td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> </table> <p>1967</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence line, bears North, 34 lks. dist.; fence bears E. and W.</p> <p style="padding-left: 40px;">The cor. of secs. 1, 2, 35 and 36, Tps. 11 and 12</p>	<u>S 14</u>	<u>S 13</u>	S 23	S 24
<u>S 14</u>	<u>S 13</u>				
S 23	S 24				

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	<p>N., R. 2 E., bears S. 0°25' E., 242.11 chs. dist., an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1952.</p> <p>This control line was fully retraced, and careful search made for evidence of intervening corners, none of which was recovered.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, mesquite, cat claw and cacti.</p>
	<p>N. 0°32' E., bet. secs. 13 and 14.</p> <p>Over rolling land.</p>
0.34	Fence, barbed wire, bears E. and W.
17.50	Wash, 20 lks. wide, 2 ft. deep, drains SW.
27.30	Wash, 10 lks. wide, 2 ft. deep, drains S. 70° W.
34.50	Wash, 10 lks. wide, 3 ft. deep, drains S. 65° W.
40.35	Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R2E S 14 S 13 1967</p>
	<p>Deposit glass in hole alongside the iron post.</p>
45.70	Wash, 15 lks. wide, 2 ft. deep, drains S. 50° W.
80.70	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 18 ins. in the ground, rock collar to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E S 11 S 12 S 14 S 13 1967</p>
	<p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy., an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1934.</p> <p>N. 89°40' W., bet. secs. 12 and 13.</p> <p>Over rolling land.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
21.00	Wash, 20 lks. wide, 2 ft. deep, drains S.
27.70	Top of spur, slopes S.
41.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 12 and 13, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
T12N R2E $\frac{1}{4}$ S 12 S 13 1967	
49.60	Wash, 30 lks. wide, 2 ft. deep, drains S.
56.70	Top of spur, slopes S.
72.80	Wash, 15 lks. wide, 2 ft. deep, drains S.
77.30	Track road, bears N. and S.
82.44	The cor. of secs. 11, 12, 13 and 14. Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.
N. 0°35' E., bet. secs. 11 and 12.	
Over rolling land.	
0.40	Wash, 5 lks. wide, 2 ft. deep, drains S. 20° W.
11.50	Track road, bears N. 75° E. and S. 75° W.
20.60	Wash, 5 lks. wide, 4 ft. deep, drains W.
33.80	Wash, 5 lks. wide, 5 ft. deep, drains S. 80° W.
38.30	Top of spur, slopes W.
40.35	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.
T12N R2E $\frac{1}{4}$ S 11 S 12 1967	
41.40	Wash, 10 lks. wide, 3 ft. deep, drains W.
46.30	Track road, bears N. 85° E. and S. 85° W.
68.20	Track road, bears irregularly E. and W.
71.80	Fence, barbed wire, bears E. and W.
78.50	Track road, bears S. 5° E. and N. 20° W.

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
80.70	<p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E S 2 S 1 S 11 S 12 1967</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy., an iron post, 2 ins. in diam., set mkd. and witnessed as described in the official record of the dependent resurvey in 1934.</p> <p>N. 89°39' W., bet. secs. 1 and 12.</p> <p>Over rolling land.</p>
19.60	Top or ridge and track road, bears S. 25° E. and N. 25° W.
31.40	Top of spur, slopes S. 25° W.
39.20	Wash, 10 lks. wide, 2 ft. deep, drains S. 25° W.
41.36	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ S 1 S 12 1967</p>
50.90	Wash, 20 lks. wide, 2 ft. deep, drains S.
61.20	Cor. of fences, bears South, 1.52 chs. dist.; fences bear S. 80° E., S. 25° E. and S. 80° W.
76.10	Wash, 10 lks. wide, 2 ft. deep, drains S.
82.72	<p>The cor. of sec. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.</p>
	<p>N. 3°20' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p>
1.90	Wash, 5 lks. wide, 2 ft. deep, drains S. 65° E.
39.92	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 1 and 2.

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	<p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ W C S 2↑S 1 1967</p>
40.42	<p>True point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner. This point falls in wash, 10 lks. wide, 2 ft. deep draining S. 30° E.; impractical to monument.</p>
80.40	<p>Wash, 15 lks. 4 ft. deep, drains SE.</p>
80.84	<p>Intersect the Third Standard Parallel North.</p> <p>Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T13N R2E <u>S 34</u> S 2 S 1 C C T12N R2E 1967</p> <p>from which</p> <p style="text-align: center;">The Stan. cor. of secs. 34 and 35, T. 13 N., R. 2 E., bears N. 89°43' E., 3.71 chs. dist.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush and cacti.</p>
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 1, is at midpoint and on the N. bdy. of the Tp.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T13N R2E <u>$\frac{1}{4}$ S 1</u> T12N R2E 1967</p> <p>from which</p> <p style="text-align: center;">The Stan. $\frac{1}{4}$ sec. cor. of sec. 35, T. 13 N., R. 2 E., bears N. 89°40' E., 3.43 chs. dist.</p>
2.30	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°18' W., bet. secs. 14 and 23.</p> <p>Over rolling land, along fence line.</p> <p>Power line, bears S. 70°28' E. and N. 70°28' W.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
9.20	Top of spur, slopes N.
25.40	Fence, barbed wire, bears E. and W.
39.30	Wash, 20 lks. wide, 1 ft. deep, drains SW.
40.88	Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. <div style="text-align: center;"> T12N R2E $\frac{1}{4}$ $\frac{S\ 14}{S\ 23}$ 1967 </div> from which <div style="text-align: center;"> A fence line, bears South, 6 lks. dist.; fence bears E. and W. Set an iron fence post alongside the cor. </div>
48.05	Windmill, bears South, 1.38 chs. dist.
52.50	Yarber Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.
58.10	Top of ridge, bears N. and S.
61.90	Wash, 20 lks. wide, 3 ft. deep, drains S.
81.76	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. <div style="text-align: center;"> T12N R2E $\frac{S\ 15}{S\ 22} \mid \frac{S\ 14}{S\ 23}$ 1967 </div> from which <div style="text-align: center;"> A fence, bears South, 58 lks. dist.; fence bears E. and W. The cor. of secs. 2, 3, 34 and 35, Tps. 11 and 12 N., R. 2 E., bears S. 0°01' W., 242.71 chs. dist., an iron post, 2 ins. in diam., set, mkd. and witnessed as described in the official record of the dependent resurvey in 1952. This control line was fully retraced, and careful search was made for evidence of intervening corners, none of which was recovered. Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, mesquite, cat claw and cacti. </div> <hr/> <div style="text-align: center;"> N. 0°03' E., bet. secs. 14 and 15. Over rolling land. </div>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
24.70	Top of spur, slopes E.
27.50	Power line, bears S. 70°28' E. and N. 70°28' W.
32.70	Top of spur, slopes E.
40.45	Point for the ½ sec. cor. of secs. 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. T12N R2E ½ S 15 S 14 1967
63.60	Wash, 10 lks. wide, 4 ft. deep, drains W.
68.70	Top of spur, slopes W.
80.90	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 24 ins. in the ground, brass cap mkd. T12N R2E S 10 S 11 S 15 S 14 1967 Raise a mound of stone W. of the cor. Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, cat claw, mesquite and cacti.
	From the cor. of secs. 11, 12, 13 and 14. N. 89°09' W., bet. secs. 11 and 14. Over rolling land.
1.00	Wash, 10 lks. wide, 2 ft. deep, drains S.
13.40	Wash, 10 lks. wide, 2 ft. deep, drains S. 10° W.
41.22	Point for the ½ sec. cor. of secs. 11 and 14, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground, brass cap mkd. T12N R2E ½ S 11 S 14 1967 Raise a mound of stone N. of the cor. Set a wooden post, 3 ins. in diam., 4 ft. long, alongside the cor.

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
42.00	Yarber Wash, 30 lks. wide, 2 ft. deep, drains SE.
82.44	The cor. of secs. 10, 11, 14 and 15. Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, cat claw, sagebrush and cacti.
	N. 0°25' E., bet. secs. 10 and 11. Over rolling land.
.20	Track road, bears NE. and SW.
11.20	Wash, 20 lks. wide, 2 ft. deep, drains S. 20° E.
40.45	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T12N R2E $\frac{1}{4}$ S 10 S 11 1967 </div>
	Set a wooden post, 3 ins. in diam., 3 ft. long, alongside the cor.
70.60	Fence, barbed wire, bears E. and W.
80.90	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. <div style="text-align: center;"> T12N R2E S 3 S 2 S 10 S 11 1967 </div>
	Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, cat claw and cacti.
	From the cor. of secs. 1, 2, 11 and 12. N. 89°02' W., bet. secs. 2 and 11. Over rolling land.
2.50	Top of ridge and track road, bears S. 20° E. and N. 20° W.
35.70	Yarber Wash, 30 lks. wide, 2 ft. deep, drains SE.
41.36	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate distance; there is no remaining evidence of the original corner. Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
82.72	<p style="text-align: center;">T12N R2E $\frac{1}{4}$ $\frac{S\ 2}{S\ 11}$ 1967</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, cat claw and cacti.</p>
1.40	<p>N. 5°10' E., bet. secs. 2 and 3.</p> <p>Over rolling land.</p> <p>Top of spur, slopes E.</p>
9.60	<p>Top of spur, slopes.E.</p>
40.67	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ S 3 S 2 1967</p> <p>Draw, drains E.</p>
76.90	<p>Yarber Wash, 30 lks. wide, 2 ft. deep, drains S. 85° E.</p>
81.33	<p>Intersect the Third Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T13N R2E $\frac{S\ 33}{S\ 3 S\ 2}$ C C T12N R2E 1967</p> <p>from which</p> <p style="text-align: center;">The Stan. cor. of secs. 33 and 34, T. 13 N., R. 2E., bears S. 89°46' E., 3.40 chs. dist.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, sagebrush, cat claw and cacti.</p>
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 2, is at midpoint and on the N. bdy. of the Tp.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	<p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T13N R2E <u>¼ S 2</u> T12N R2E 1967</p> <p>from which</p> <p style="text-align: center;">The Stan. ¼ sec. cor. of sec. 34, T. 13 N., R. 2 E., bears S. 87°24' E., 3.29 chs. dist.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°31' W., bet. secs. 15 and 22.</p> <p>Over rolling land, along fence line.</p>
1.84	Fence, barbed wire, bears N. and S., and cor. of fences bears South, 48 lks. dist.; fences bear N. and E.
19.80	Wash, 15 lks. wide, 6 ft. deep, drains S.
27.10	Brushy Wash, 60 lks. wide, 3 ft. deep, drains S.
40.98	Point for the ¼ sec. cor. of secs. 15 and 22 at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R2E <u>¼ S 15</u> S 22 1967</p> <p>from which</p> <p style="text-align: center;">A fence, bears West, 1.28 chs. dist.; fence bears N. and S.</p> <p>Raise a mound of stone N. of the cor.</p>
42.24	Fence, barbed wire, bears N. and S. curving SW.
55.90	Bladed road, bears S. 20° E. and N. 20° W.
79.00	Fence, barbed wire, bears N. 80° E. and S. 80° W.
81.00	Wash, 30 lks. wide, 3 ft. deep, drains S.
81.96	<p>The cor. of secs. 15, 16, 21 and 22, monumented by a granite stone, 18x12x12 ins., mkd. 2E and 3 notches on E. and 12N and 3 notches on S. faces, firmly set, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R2E <u>S 16 S 15</u> <u>S 21 S 22</u> 1967</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	<p>Bury the original corner stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, mesquite, cat claw and cacti.</p>
	<p>NORTH, bet. secs. 15 and 16.</p> <p>Over rolling land.</p>
29.10	Wash, 20 lks. wide, 4 ft. deep, drains S. 20° E.
37.30	Top of spur, slopes SW.
39.73	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate distance; there is no remaining evidence of the original corner. Corner falls in cor. of fences bearing N. and W.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ S 16 S 15 1967</p> <p>Thence along fence line.</p>
52.80	Bladed road, bears W. and E., curving S. 80° E.
56.80	Power line, bears S. 70°28' E. and N. 70°28' W.
59.60	<p>Point for the N. 1/16 sec. cor. of secs. 15 and 16, at midpoint. Corner falls in fence bearing N. and S.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T12N R2E N 1/16 S 16 S 15 1967</p> <p>Raise a mound of stone W. of the cor.</p>
64.10	Wash, 10 lks. wide, 9 ft. deep, drains NE.
66.40	Wash, 20 lks. wide, 3 ft. deep, drains E.
79.46	<p>The cor. of secs. 9, 10, 15 and 16, monumented by a granite stone, 20x14x7 ins., plainly mkd. 3 notches on E. and 4 notches on S. faces, firmly set in cor. of fences bearing E., S. and W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E S 9 S 10 S 16 S 15 1967</p> <p>Bury the original corner stone alongside the iron post.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, mesquite, cat claw and cacti.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 88°33' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p> <p>0.20 Track road, bears NE. and SW.</p> <p>6.14 Fence, barbed wire, bears N. and S., and cor. of fences bears South, approx. 3.80 chs. dist.; fences bear N., S. and W.</p> <p>10.30 Top of ridge, bears N. and S.</p> <p>25.10 Brushy Wash, 2.30 chs. wide, 2 ft. deep, drains S.</p> <p>37.70 Wash, 20 lks. wide, 6 ft. deep, drains SE.</p> <p>41.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ S 10 S 15 1967</p> <p>45.80 Top of ridge, bears SE. and NW.</p> <p>54.80 Wash, 5 lks. wide, 4 ft. deep, drains S. 20° E.</p> <p>78.70 Fence, barbed wire, bears E. and W.</p> <p>82.04 The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, mesquite, cat claw and cacti.</p>
40.35	<p>N. 0°05' E., bet. secs. 9 and 10.</p> <p>Over rolling land.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ S 9 S 10 1967</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS									
65.40	Wash, 10 lks. wide, 3 ft. deep, drains S. 5° E.								
68.80	Saddle in ridge, bears E. and W.								
71.90	Draw, drains NE.								
77.80	Wash, 5 lks. wide, 2 ft. deep, drains E.								
80.70	The cor. of secs. 3, 4, 9 and 10, monumented by a granite stone, 20x10x8 ins., mkd. 3 notches on E. and 5 notches on S. faces, firmly set, with mound of stone W.								
	At the corner point								
	Set the iron post 22 ins. in the ground, brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T12N R2E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 4</td> <td style="padding: 0 5px;">S 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 9</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table>	T12N R2E		S 4	S 3	S 9	S 10	1967	
T12N R2E									
S 4	S 3								
S 9	S 10								
1967									
	Bury the original corner stone alongside the iron post.								
	Raise a mound of stone W. of the cor.								
	Land, rolling.								
	Soil, sandy loam.								
	Timber, none.								
	Undergrowth, bunch grass, mesquite cat claw and cacti.								
	From the cor. of secs. 2, 3, 10 and 11.								
	S. 88°24' W., bet. secs. 3 and 10.								
	Over rolling land.								
9.40	Wash, 10 lks. wide, 2 ft. deep, drains S.								
12.10	Fence, bears N. and S.								
19.70	Top of spur, slopes S.								
41.24	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner.								
	Set the iron post 22 ins. in the ground, brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T12N R2E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼ S 3</td> <td style="padding: 0 5px;">S 10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1967</td> </tr> </table>	T12N R2E		¼ S 3	S 10	1967			
T12N R2E									
¼ S 3	S 10								
1967									
	Raise a mound of stone N. of the cor.								
44.20	Brushy Wash, 30 lks. wide, 3 ft. deep, drains S.								
69.00	Wash, 5 lks. wide, 2 ft. deep, drains SE.								
82.48	The cor. of secs. 3, 4, 9 and 10.								
	Land, rolling.								
	Soil, sandy loam.								
	Timber, none.								
	Undergrowth, bunch grass, mesquite, cat claw and cacti.								

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	N. 5°29' E., bet. secs. 3 and 4.
	Over rolling land.
1.50	Top of spur, slopes E.
9.60	Top of spur, slopes E.
13.30	Wash, 5 lks. wide, 2 ft. deep, drains E.
18.90	Top of spur, slopes SE.
28.40	Wash, 20 lks. wide, 2 ft. deep, drains E.
42.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T12N R2E $\frac{1}{4}$ S 4 S 3 1967
	from which
	A windmill, bears N. 1°54' E., 25.14 chs. dist.
	Tri-metals Mine shaft (abandoned), bears N. 38°50' E., 32.49 chs. dist.
50.10	Top of ridge, bears E. and W.
57.30	Brushy Wash, 30 lks. wide, 2 ft. deep, drains E.
65.70	Track road, bears irregularly E. and W.
84.06	Intersect the Third Standard Parallel North.
	Point for the closing cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
	Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.
	T13N R2E <u>S 32</u> S 4 S 3 C C T12N R2E 1967
	from which
	The Stan. cor. of secs. 32 and 33, T. 13 N., R. 2 E., bears S. 89°40' E., 2.98 chs. dist.
	Land, rolling.
	Soil, sandy loam.
	Timber, none.
	Undergrowth, bunch grass, mesquite, cat claw and cacti.
	Point for the $\frac{1}{4}$ sec. cor. of sec. 3, is at midpoint and on the N. bdy. of the Tp.

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	<p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T13N R2E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">$\frac{1}{4}$ S 3 T12N R2E 1967</p> <p>from which</p> <p style="text-align: center;">The Stan. $\frac{1}{4}$ sec. cor. of sec. 33, T. 13 N., R. 2 E., bears S. 89°46' E., 3.19 chs. dist.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°45' W., bet. secs. 9 and 16.</p> <p>Over rolling land, along fence line.</p>
12.20	Wash, 25 lks. wide, 2 ft. deep, drains S. 50° E.
40.18	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented by a granite stone, 17 x 12 x 6 ins., mkd. $\frac{1}{4}$ on N. face, firmly set.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ S 9 S 16 1967</p> <p>from which</p> <p style="text-align: center;">A fence, bears North, 16 lks. dist.; fence bears E. and W.</p> <p>Bury the original corner stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°47' W., beginning new measurement.</p> <p>Over rolling land, along fence line.</p>
14.30	Top of spur, slopes S. 30° E.
19.90	Power line, bears S. 70°28' E. and N. 70°28' W.
26.10	Draw, drains S. 5° E.
31.80	Top of spur, slopes S. 10° E.
39.91	<p>The cor. of secs. 8, 9, 16 and 17, monumented by a granite stone, 36x12x12 ins., mkd. 3 notches on the E. and S. faces, no other mks. legible, firmly set in cor. of fences bearing N., E. and S.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	T12N R2E S 8 S 9 S 17 S 16 1967
	<p>Bury the original corner stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, mesquite, cat claw and cacti.</p>
	<p>N. 0°02' W., bet. secs. 8 and 9.</p> <p>Over rolling land, along fence line.</p>
6.50	Power line, bears S. 70°28' E. and N. 70°28' W.
19.80	Fence, barbed wire, bears E. and W., and cor. of fences bear East, 4 lks. dist.; fences bear S. and W.
19.96	<p>Point for the S. 1/16 sec. cor. of secs. 8 and 9, at midpoint.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	T12N R2E S 1/16 S 8 S 9 1967
39.92	<p>The ¼ sec. cor. of secs. 8 and 9, monumented by a granite stone, 26 x14x14 ins., mkd. ¼ on W. face, firmly set, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	T12N R2E ¼ S 8 S 9 1967
	<p>Bury the original corner stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over rolling land.</p>
20.07	<p>Point for the N. 1/16 sec. cor. of secs. 8 and 9, at midpoint.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	T12N R2E N 1/16 S 8 S 9 1967

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS		
23.20	Track road, bears N. 5° E. and S. 5° W.	
28.40	Track road, bears S. 5° E. and N. 5° W.	
33.60	Track road, bears N. and S. 5° W., thence down same.	
36.00	Track road, bears S. and N. 10° W., leaving same.	
40.14	The cor. of secs. 4, 5, 8 and 9, monumented by a granite stone, 16x10x10 ins., mkd. 4 notches on E. and 5 notches on S. faces, firmly set.	
	At the corner point	
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.	
	$\begin{array}{r} T12N R2E \\ \hline S 5 S 4 \\ S 8 S 9 \\ \hline 1967 \end{array}$	
	Bury the original corner stone alongside the iron post.	
	Land, rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, bunch grass, cat claw and cacti.	
	From the cor. of secs. 3, 4, 9 and 10.	
	S. 89°40' W., bet. secs. 4 and 9.	
	Over rolling land.	
9.60	Top of ridge, bears N. and S.	
19.60	Wash, 20 lks. wide, 4 ft. deep, drains S.	
34.50	Top of spur, slopes S.	
40.03	The ¼ sec. cor. of secs. 4 and 9, monumented by a granite stone, 24x12x6 ins., mkd. ¼ on N. face, firmly set in a mound of stone.	
	At the corner point	
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.	
	$\begin{array}{r} T12N R2E \\ \hline \frac{1}{4} S 4 \\ S 9 \\ \hline 1967 \end{array}$	
	Bury the original corner stone alongside the iron post.	
	S. 89°46' W., beginning new measurement.	
	Over rolling land.	
6.80	Wash, 5 lks. wide, 2 ft. deep, drains S.	
13.40	Top of spur, slopes S.	
20.50	Wash, 5 lks. wide, 4 ft. deep, drain S.	

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
40.10	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, widely scattered cedar. Undergrowth, bunch grass, cat claw and cacti.</p>
	<p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over rolling land.</p>
9.90	<p>Track road, bears N. 30° E. and S. 30° W.</p>
16.60	<p>Draw, drains W.</p>
31.90	<p>Track road, bears S. 10° E. and N. 10° E.</p>
40.03	<p>The ¼ sec. cor. of secs. 4 and 5, monumented by a granite stone, 20x12x10 ins., mkd. ¼ on W. face, firmly set, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E ¼ S 5 S 4 1967</p>
	<p>Bury the original corner stone alongside the iron post.</p>
	<p>N. 0°01' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
3.20	<p>Track road, bears S. 10° E. and NW.</p>
18.60	<p>Top of ridge, bears SE. and NW.</p>
38.85	<p>Intersect the Third Standard Parallel North.</p> <p>The closing cor. of secs. 4 and 5, monumented by a granite stone, 12x10x8 ins., mkd. 4 notches on E., 2 notches on W. and CC on S. faces, firmly set, with a mound of stone S.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T13N R2E S 31 S 5 S 4 C C T12N R2E 1967</p>
	<p>from which</p> <p>An Angle Point, T. 13 N., R. 2 E., bears S. 89°59' E., 40 lks. dist.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
	<p>Bury the original corner stone alongside the iron post.</p> <p>Land, rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, bunch grass, cat claw and cacti.</p>
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 4, is at midpoint and on the N. bdy. of the Tp.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T13N R2E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">$\frac{1}{4}$ S 4 T12N R2E 1967</p> <p>from which</p> <p style="text-align: center;">The Stan. $\frac{1}{4}$ sec. cor. of sec. 32, T. 13 N., R. 2 E., bears N. $83^{\circ}48'$ E., 5.92 chs. dist.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. $89^{\circ}52'$ W., bet. secs. 8 and 17.</p> <p>Over rolling land.</p>
1.90	Old fence, bears N. and S., enter open field, bears S. 10° E. and N. 10° W.
8.20	Leave field, bears N. and S., and left bank of Agua Fria River, 5 ft. high, bears N. and S.
11.40	Center of Agua Fria River, 10 lks. wide, running water 6 ins. deep, course S.
12.07	Intersect the calculated position of line 2-3 M.S. 2310 Tommy Tot lode, at a point from which the calculated position of cor. No. 3 bears N. 4° E., 5.08 chs. dist. (Cor. Nos. 2, 3 and 4 were searched for but not found; however, Cor. No. 1 was recovered).
12.60	Right bank of Agua Fria River, 20 ft. high, bears N. and S.
20.10	Track road, bears N. and S.
20.30	Fence, barbed wire, bears N. and S., and cor. of fences bear South, 20 lks. dist.; fences bears N. and W.
21.05	Intersect the calculated position of line 4-1 M.S. 2310 Tommy Tot lode, at a point from which Cor. No. 1 bears S. 4° W., 19.27 chs. dist.; monumented by an axle, 1 in. diam., projecting 6 ins. above ground, in a mound of stone, one of which conformed to record size, but no visible markings.
39.85	<p>The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented by a lava stone, 18x6x6 ins., mkd. $\frac{1}{4}$ on N. face, firmly set, with mound of stone N. Cor. falls on top of high spur, sloping SE.</p> <p>At the corner point</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T12N R2E

$\frac{1}{4}$ $\frac{S 8}{S 17}$

1967

from which

U.S.M.M. No. 1, bears S. 41°53' E., 14.31 chs. dist., monumented by volcanic boulder, 6 ft. square by 4 ft. thick, mkd. USMM No. 1 AFMD, with mound of stone.N.

A fence bears south, 25 lks. dist.; fence bears E. and W.

Bury the original corner stone alongside the iron post.

N. 89°49' W., beginning new measurement.

Over rolling land.

12.70 Draw, drains S.

19.99 Point for the W. 1/16 sec. cor. of secs. 8 and 17, at midpoint.

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T12N R2E

W 1/16 $\frac{S 8}{S 17}$

1967

from which

A fence bears north, 10 lks. dist.; fence bears irregularly E. and W.

25.80 Cor. of fences bears irregular N. 40° E., E. and W. and intersect line 2-3 M.S. 4601 Lone Star lode, at a point from which cor. No. 2 bears N. 24°26' E., 64 lks. dist., monumented by an iron pipe, $\frac{1}{2}$ in. diam., projecting 12 ins. above ground fitted with a 3 in. floor flange with copper plate bolted thereon, mkd. L S 2 4601. Cor. is in a mound of stone.

39.98 The cor. of secs. 7, 8, 17 and 18, monumented by a granite stone, 26x10x8 ins., mkd. 5 notches on E. and 4 notches on S. faces, firmly set, in fence line bearing E. and W.

At the corner point

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T12N R2E

$\frac{S 7}{S 18}$ | $\frac{S 8}{S 17}$

1967

Bury the original corner stone alongside the iron post.

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E

CHAINS	
	<p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered pine and cedar. Undergrowth, bunch grass, cat claw and cacti.</p>
	<p>North, bet, secs. 7 and 8. Over rolling land, through scattered timber.</p>
3.47	<p>Intersect line 1-2 M.S. 4601 Missing Link lode, at a point from which Cor. No. 1 identical with Cor. No. 1 M.S. 4601 Stonewall lode, bears N. 78°32' W., 1.49 chs. dist., monumented by an iron pipe, ½ in. diam., projecting 12 ins. above ground, fitted with a 3 in. floor flange with copper plate bolted thereon, mkd. L S 2 4601. Cor. is in a mound of stone.</p>
9.50	<p>Top of spur, slopes W.</p>
17.00	<p>Power line, bears N. 80° E. and S. 80° W.</p>
17.20	<p>Bladed road, bears E. and S. 80° W.</p>
19.96	<p>Point for the S. 1/16 sec. cor. of secs. 7 and 8, at midpoint. This point is not monumented.</p>
21.10	<p>Draw, drains N. 45° E.</p>
26.80	<p>Top of spur, slopes E.</p>
34.40	<p>Power line, bears S. 70°28' E. and N. 70°28' W.</p>
39.92	<p>The ¼ sec. cor. of secs. 7 and 8, as determined from the original bearing trees:</p> <p style="padding-left: 40px;">A pine, 16 ins. in diam., bears N. 88½° E., 127 lks. dist., mkd. ¼ S8 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. in diam., bears N. 75½° W., 109 lks. dist., having overgrown blaze.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R2E</p> <p>¼</p> <p>S 7 S 8</p> <p>1967</p> <hr style="width: 20%; margin: auto;"/> </div> <p>N. 0°07' E., beginning new measurement.</p> <p>Over rolling land, through scattered timber.</p>
12.00	<p>Fence, barbed wire, bears S. 70° E. and N. 70° W.</p>
15.40	<p>Wash, 50 lks. wide, 1 ft. deep, drains E.</p>
18.60	<p>Track road, bears SE. and NW.</p>
19.60	<p>Right bank of Agua Fria River, bears S. 10° E. and N. 10° W.</p>
20.04	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 8, at midpoint. This corner is not monumented.</p>
26.25	<p>Center of Agua Fria River (dry), drains S. 10° E.</p>
32.90	<p>Left bank of Agua Fria River, bears S. 10° E. and N. 75° W.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
40.08	<p>The cor. of secs. 5, 6, 7 and 8, monumented by a lava stone, 20x10x8 ins., mkd. 5 notches on E. and S. faces, firmly set, with mound of stone W.</p> <p>At the corner point Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E <u>S 6 S 5</u> <u>S 7 S 8</u> 1967</p> <p>Bury the original corner stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered pine and cedar. Undergrowth, bunch grass, cat claw and cacti.</p>
1.00	<p>From the cor. of secs. 4, 5, 8 and 9. N. 89°57' W., bet. secs. 5 and 8. Over rolling land. Track road, bears N. and S. 10° E.</p>
6.20	<p>Top of ridge, bears N. and S.</p>
30.90	<p>Rattle Snake Canyon, 80 lks. wide, 6 ft. deep, drains S.</p>
38.50	<p>Track road, bears SE. and N. 80° W.</p>
39.69	<p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented by a quartz stone, 12x8x4 ins., mkd. $\frac{1}{4}$ on N. face, firmly set, with mound of stone N.</p> <p>At the corner point Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T12N R2E $\frac{1}{4}$ <u>S 5</u> <u>S 8</u> 1967</p> <p>Bury the original corner stone alongside the iron post.</p> <p style="text-align: center;">—————</p> <p>N. 89°58' W., beginning new measurement. Over rolling land.</p>
8.60	<p>Wash, 10 lks. wide, 3 ft. deep, drains S.</p>
20.05	<p>Point for the W. 1/16 sec. cor. of secs. 5 and 8, at midpoint. This corner is not monumented.</p>
24.60	<p>Bear Track Canyon, 20 lks. wide, 2 ft. deep, drains S. 10° E.</p>
27.60	<p>Track road, bears S. 5° E. and N. 5° W.</p>
40.10	<p>The cor. of secs. 5, 6, 7 and 8. Land, rolling. Soil, rocky, sandy loam. Timber, scattered cedar. Undergrowth, bunch grass, cat claw and cacti.</p>
	<p>North, bet. secs. 5 and 6. Over rolling land, through scattered timber.</p>

Dependent Resurvey
of a
Portion of the Subdivisional Lines, T. 12 N., R. 2 E.

CHAINS	
31.50	Track road, bears SE. and NW.
31.80	Top of spur, slopes SE.
35.20	Bear Track Canyon, 20 lks. wide, 2 ft. deep, drains S. 80° E.
40.02	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented by a lava stone, 24x12x6 ins., mkd. $\frac{1}{4}$ on W. face, firmly set in a mound of stone. At the corner point Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd. <div style="text-align: center;"> T12N R2E $\frac{1}{4}$ S 6 S 5 1967 </div> Bury the original corner stone alongside the iron post. N. 0°03' E., beginning new measurement. Over rolling land, through scattered timber.
38.82	Intersect the Third Standard Parallel North. The closing cor. of secs. 5 and 6, monumented by a lava stone, 18x8x6 ins., mkd. 5 notches on E., 1 notch on N. and CC on S. faces, firmly set, with mound of stone S. At the corner point Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd. <div style="text-align: center;"> T13N R1$\frac{1}{2}$E S 36 <hr style="width: 50%; margin: 0 auto;"/> S 6 S 5 C C T12N R2E 1967 </div> from which An angle point, T. 13 N., R. 1 $\frac{1}{2}$ E., bears west, 8 lks. dist. Bury the original corner stone alongside the iron post. Land, rolling. Soil, rocky, sandy loam. Timber, scattered pine and cedar. Undergrowth, bunch grass, cat claw and cacti. <hr/> Point for the $\frac{1}{4}$ sec. cor. of sec. 5, is at midpoint and on the N. bdy. of the Tp. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T13N R2E $\frac{1}{4}$ S 5 T12N R2E 1967 </div> from which An angle point, T. 13 N., R. 2E., bears east, 31 lks. dist. <hr/> Subdivision of Section 8, T. 12 N., R. 2 E. <hr/> From the $\frac{1}{4}$ sec. cor. of secs. 8 and 17. N. 0°09' E., on the N. and S. center line of sec. 8.

Subdivision of Section 8, T. 12 N., R. 2 E.

CHAINS	
	Over rolling land.
1.00	Top of ridge, bears SE. and NW., thence descend NE. slope.
19.98	Point for the C-S 1/16 sec. cor. of sec. 8. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. <div style="text-align: center;"> T12N R2E C S 1/16 S 8 C 1967 </div>
20.30	Power line, bears S. 70°28' E. and N. 70°28' W.
30.90	Wash, 15 lks. wide, 5 ft. deep, drains SE.
31.80	Power line, bears E. and W.
33.10	Fence, barbed wire, bears SE. and NW.
33.70	Track road, bears E. and NW.
36.90	Fence, barbed wire, bears SE. and NW.
39.96	Point for the center 1/4 section corner of section 8, at the intersection with the E. and W. centerline of Section 8 falls in a cultivated field; impractical to monument.
41.26	Point selected for the witness center 1/4 sec. cor. of sec. 8. Set the iron post 24 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T12N R2E W C C 1/4 S 8 1967 </div>
	from which <div style="margin-left: 40px;"> A water pump, bears N. 70° E., 2.90 chs. dist. NW. cor. of house, bears S. 1°52' E., 6.52 chs. dist. NW. cor. of house, bears S. 6°22' E., 9.08 chs. dist. NE. cor. of barn, bears S. 58°22'30" W., 6.39 chs. dist. </div>
	Cor. is under fence line bearing N. 50° E. and S. 50° W.
41.31	Water pipeline, 6 ins. in diam., bears N. 50° E. and S. 50° W.
41.65	Power line and fence line, bears N. 50° E. and S. 50° W.
45.75	Fence, barbed wire, bears E. and W.
46.50	Right bank of Agua Fria River, 20 ft. high, bears SE. and N. 70° W.

Subdivision of Section 8, T. 12 N., R. 2 E.

CHAINS	
47.60	Center of Agua Fria River (dry), 2.20 chs. wide, 2 ft. deep, drains SE. from N. 70° W.
48.40	Track road, bears SE. and N. 70° W.
48.70	Left bank of Agua Fria River, 20 ft. high, bears SE. and N. 70° W.
60.01	Point for the C-N 1/16 sec. cor. of sec. 8. Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd. T12N R2E C N 1 S 8 1 6 C 1967
61.20	Spur, slopes SW.
80.06	The ¼ sec. cor. of secs. 5 and 8. Land, rolling to level farm land. Soil, sandy loam. Timber, scattered cedar and cottonwood. Undergrowth, bunch grass, cat claw and cacti.
	From the ¼ sec. cor. of secs. 8 and 9. N. 89°53' W., on the E. and W. center line of sec. 8. Over rolling land.
15.30	Draw, drains S. 80° W.
24.30	Left Bank of Agua Fria River, 20 ft. high, bears N. and S.
26.20	Center of Agua Fria River (dry), drains S.
28.10	Right Bank of Agua Fria River, 50 ft. high, bears N. and S.
28.60	Fence, barbed wire, bears SE. and NW.; enter level farm land.
33.40	Fence, barbed wire, bears N. 80° E. and S. 80° W.
34.90	Fence, barbed wire, bears S. 20° E. and N. 20° W.
39.76	The true point for the Center ¼ sec. cor. of sec. 8.
41.74	Fence, barbed wire, bears NE. and NW. and power line bears N. 50° E. and S. 50° W.
42.33	Fence, barbed wire, bears NE. and SW.
44.57	Fence, barbed wire, bears S. 20° E. and N. 20° W.
45.20	Center of E. edge of pond, approx. 3.00 chs. square, bears N. 20° W. and S. 20° E.
48.20	W. edge of same pond.
51.90	Track road, bears SE. and SW.
52.40	Track road, bears N. and S.
52.70	Fence, barbed wire, bears N. 50° E. and S. 50° W.

Subdivision of Section 8, T. 12 N., R. 2 E.

CHAINS					
53.40	Fence, barbed wire, bears S. 35° E. and N. 35° W.				
59.79	Point for the C-W 1/16 sec. cor. of sec. 8. This corner is not monumented.				
64.90	Draw, drains N.				
73.10	Top of spur, slopes N.				
78.10	Top of spur, slopes NE.				
79.82	<p>The ¼ sec. cor. of secs. 7 and 8.</p> <p>Land, rolling to level farm land. Soil, sandy loam. Timber, widely scattered cottonwood, pine and cedar. Undergrowth, bunch grass, mesquite, cat claw and cacti.</p>				
Subdivision SW¼ of Section 8					
From the W 1/16 sec. cor. of secs. 8 and 17.					
N. 0°02' E., on the N. and S. center line of the SW¼ of sec. 8.					
Over rolling land.					
19.97	<p>Point for the SW 1/16 section corner of section 8, at the intersection with the E. and W. centerline of the SW¼ of section 8.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T12N R2E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">SW</td> <td style="text-align: center; padding: 0 5px;">1 — 16</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> </tr> </table> <p>1967</p> </div>	SW	1 — 16	S	8
SW	1 — 16	S	8		
23.00	Bladed road, bears N. 85° E. and S. 85° W.				
26.80	Intersection of power lines, bears East, 65 lks. dist.; power lines bears N. 70° E., S. 70°28' E., S. 70° W. and N. 70°28' W.				
34.40	Draw, drains NE.				
39.94	The point for the C-W 1/16 sec. cor. of sec. 8.				
From the C-S 1/16 sec. cor. of sec. 8.					
N. 89°51' W., on the E. and W. center line of the SW¼ of sec. 8.					
Over rolling land.					
19.99	The SW 1/16 sec. cor. of sec. 8.				
25.60	Bladed road, bears NE. and SW.				
30.00	Draw, drains NE.				
33.90	Power line, bears N. 50° E. and S. 50° W.				
39.96	The point for the S 1/16 sec. cor. of secs. 7 and 8.				

Subdivision of Section 8, T. 12 N., R. 2 E.

CHAINS	Subdivision NW $\frac{1}{4}$ of Section 8
	<p>From the point for the C-W 1/16 sec. cor. of sec. 8. N. 0°09' E., on the N. and S. center line of the NW$\frac{1}{4}$ of sec. 8. Over rolling land.</p>
1.93	Fence, barbed wire, bears E. and W.
5.70	Right bank of Agua Fria River, 15 ft. high, bears E. and W.
6.15	Center of Agua Fria River (dry), drains E.
6.60	Left bank of Agua Fria River, 15 ft. high, bears E. and W.
6.80	Track road, bears E. and W.
13.00	Track road, bears N. 10° W. and S. 10° E., for approx. 20 lks., thence S. 40° E.
20.07	<p>Point for the NW 1/16 sec. cor. of sec. 8, at the intersection with the E. and W. centerline of the NW$\frac{1}{4}$ of section 8.</p> <p>Set the iron post 21 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T12N R2E \\ NW \frac{1}{16} \quad \quad S 8 \\ 1967 \end{array}$ </div> <p>Set a wooden post, 3 ins. diam., 3 ft. long, alongside the cor.</p>
26.70	Bear Track Canyon, 40 lks. wide, 5 ft. deep, drains S. 15° E.
40.11	The W 1/16 sec. cor. of secs. 5 and 8.
	<p>From the C-N 1/16 sec. cor. of sec. 8. N. 89°51' W., on the E. and W. center line of the NW$\frac{1}{4}$ of sec. 8. Over rolling land.</p>
5.00	Wash, 15 lks. wide, 5 ft. deep, drains S.
12.50	Top of spur, slopes S.
19.00	Bear Track Canyon, 1.20 chs. wide, 3 ft. deep, drains S.
20.05	The NW 1/16 sec. cor. of sec. 8.
22.80	Track road, bears N. and S.
32.60	Wash, 5 lks. wide, 5 ft. deep, drains S.
38.00	Left bank of Agua Fria River, 5 ft. high, bears S. 20° E. and N. 20° W.
39.10	Center of Agua Fria River (dry), 30 lks. wide, 2 ft. deep, drains S. 20° E.
40.09	The point for the N 1/16 sec. cor. of secs. 7 and 8.

Subdivision of Section 15, T. 12 N., R. 2 E.

CHAINS

Subdivision of Section 15, T. 12 N., R. 2 E.

From the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.

North on the N. and S. center line of sec. 15.

Over gently rolling land, along fence line to the W.

5.40 Wash, 10 lks. wide, 2 ft. deep, drains E.

8.80 Top of spur, slopes E.

17.40 Wash, 10 lks. wide, 2 ft. deep, drains E.

20.04 Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 15.

Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.

$$\begin{array}{c} \text{T12N R2E} \\ \text{C} \\ \text{S } \frac{1}{16} \text{ | S 15} \\ \text{C} \\ 1967 \end{array}$$

from which

A fence line, bears West, 1.07 chs. dist.; fence bears N. and S.

20.60 Top of spur, slopes E.

25.50 Wash, 10 lks. wide, 3 ft. deep, drains E.

40.08 Point for the center $\frac{1}{4}$ section corner of section 15, at the intersection with the E. and W. centerline of section 15.

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd..

$$\begin{array}{c} \text{T12N R2E} \\ \text{C } \frac{1}{2} + \text{S15} \\ 1967 \end{array}$$

40.60 Wash, 5 lks. wide, 3 ft. deep, drains E.

42.70 Power line, bears S. $70^{\circ}28'$ E. and N. $70^{\circ}28'$ W.

47.40 Wash, 10 lks. wide, 2 ft. deep, drains SE.

56.00 Wash, 20 lks. wide, 1 ft. deep, drains SE.

60.13 Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 15.

Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.

$$\begin{array}{c} \text{T12N R2E} \\ \text{C} \\ \text{N } \frac{1}{16} \text{ | S 15} \\ \text{C} \\ 1967 \end{array}$$

Subdivision of Section 15, T. 12 N., R. 2 E.

CHAINS	
	<p>from which</p>
	<p>A fence line, bears West, 74 lks. dist.; fence bears N. and S.</p>
77.86	<p>Fence, barbed wire, bears E. and W., and cor. of fences bear West, approx. 50 lks. dist.; fences bears E., S. and W.</p>
80.18	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, cat claw and cacti.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p>
	<p>S. 89°03' W., on the E. and W. center line of sec. 15.</p>
	<p>Over rolling land.</p>
3.90	<p>Fence, barbed wire, bears N. and S.</p>
4.20	<p>Top of spur, slopes S. 20° W.</p>
26.90	<p>Brushy Wash, 70 lks. wide, 2 ft. deep, drains S. 20° W.</p>
30.70	<p>Wash, 30 lks. wide, 1 ft. deep, drains S.</p>
34.10	<p>Power line, bears S. 70°28' E. and N. 70°28' W.</p>
34.80	<p>Wash, 30 lks. wide, 2 ft. deep, drains SE.</p>
41.09	<p>The C. $\frac{1}{4}$ sec. cor. of sec. 15.</p>
42.01	<p>Fence, barbed wire, bears N. and S.</p>
47.10	<p>Top of spur, slopes SE.</p>
57.90	<p>Bladed road, bears S. 20° E. and N. 20° W.</p>
82.15	<p>The $\frac{1}{4}$ sec. cor. of secs. 15 and 16.</p>
	<p>Land, gently rolling to rolling. Soil, sandy loam. Timber, none. Undergrowth, bunch grass, mesquite, cat claw and cacti.</p>
	<p style="text-align: center;">General Description</p>
	<p>The area embraced by this survey varies from rolling to heavy rolling terrain. Elevations range from 3850 feet in the southeastern portion to 4500 feet above sea level in the western portion of the surveyed area. The soil is primarily sandy loam which supports a moderate growth of bunch grass, mesquite, cat claw and cacti. Scattered pine and cedar timbers cover the most western portion of the surveyed area, with scattered cottonwood timber along the river bottom land.</p> <p>Drainage in the township is in a southerly direction draining into Agua Fria River which traverses in an easterly to southerly direction in the western part of the Tp.</p>

Subdivision of Section 15, T. 12 N., R. 2 E.

CHAINS

The only inhabitants in the surveyed area are situated in the central portion of section 8. Some of the land in section 8 is under cultivation.

There is no mineral activity at the present time, but the abandoned Tri-Metals Mine Shaft located in section 3, together with open pits reveal mineral activity in the past.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Louis D. Gilbert, _____, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day
 of May _____, 1967, (I) ~~(We)~~ have dependently resurveyed a portion of
 the Third Standard Parallel North, through Township 13 North, Ranges 1½
 and 2 East, dependently resurveyed a portion of the subdivisional lines
 and surveyed the subdivision of Sections 8 and 15, Township 12 North,
 Range 2 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

August 22, 1969 _____
 (Date) (Cadastral Surveyor)

 (Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date JAN 16 1970

BUREAU OF LAND MANAGEMENT
 Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the Third Standard
 Parallel North, through Township 13 North, Ranges 1½ and 2 East, the dependent
 resurvey of a portion of the subdivisional lines, and the survey of the sub-
 division in Sections 8 and 15, Township 12 North, Range 2 East, Gila and Salt
 River Meridian, Arizona,

executed by Louis D. Gilbert,

having been critically examined and found correct, are hereby approved.

OCT 23 1970 _____
 (Date) (Chief, Division of Cadastral Survey)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____ is a true copy of the original field notes.

 (Date) (Chief, Division of Cadastral Survey) GEO 473-626