

BOOK 4891

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

of the

NORTH BOUNDARY OF THE FORT APACHE INDIAN RESERVATION

TOWNSHIP 9 NORTH, RANGE 25 EAST

TOWNSHIP 9 NORTH, RANGE 24 EAST

TOWNSHIP 8 NORTH, RANGE 24 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

John H. Witmer, Cadastral Surveyor

Under special instructions dated July 1, 1969, which provided for the surveys included under Group Number 514, approved July 2, 1969, and assignment instructions dated July 2, 1969.

Survey commenced July 8, 1969

Survey completed September 11, 1969

BOOK 4891

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1A

PAGE INDEX TO CORNER MONUMENTS

TOWNSHIP 9 NORTH, RANGE 25 EAST, G&SR M.

<u>Corner</u>	<u>Page</u>
Mile Corner 26½ -----	1
" " 27 -----	2
Angle Point 152 -----	3
" " 153 -----	3
" " 155 -----	3
" " 158 -----	4
Mile Corner 28½ (AP160)---	4
Angle Point 161 -----	5
" " 163 -----	5
" " 164 -----	5
Mile Corner 29½ (AP171)---	6
Angle Point 172 -----	6
" " 173 -----	7
Mile Corner 30 -----	7
Angle Point 174 -----	8
" " 175 -----	8
" " 176 -----	8
" " 177 -----	8
Mile Corner 30½ -----	9
Angle Point 178 -----	9
" " 179 -----	10
" " 180 -----	10
" " 181 -----	10
" " 186 -----	10
" " 187 -----	11
" " 188 -----	11
" " 189 -----	11
" " 190 -----	11
" " 194 -----	12
" " 195 -----	12
" " 196 -----	12
" " 197 -----	12
" " 202 -----	13
" " 203 -----	13
" " 208 -----	13

TOWNSHIP 9 NORTH, RANGE 24 EAST, G&SR M.

<u>Corner</u>	<u>Page</u>
Angle Point 212 -----	14
" " 232 -----	14
" " 233 -----	14

TOWNSHIP 8 NORTH, RANGE 24 EAST, G&SR M.

<u>Corner</u>	<u>Page</u>
Angle Point 217 -----	15
Mile Corner 36 -----	15

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION
CORNER MONUMENTS

Tp. 9 N. R. 25 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
AP208 30	29	28	27	26	25
31	FORT APACHE INDIAN RESERVATION			35	36 26 1/2 M

NOTE

ONLY THE BEGINNING AND
ENDING CORNERS
REMONUMENTED IN EACH
TOWNSHIP ARE DIAGRAMMED.

SEE PAGE INDEX FOR
COMPLETE LIST OF CORNERS
REMONUMENTED IN EACH
TOWNSHIP.

Tp. 9 N. R. 24 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	AP233 33 AP232	34	35	36 AP212

FAIR

Tp. 8 N. R. 24 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	FORT APACHE INDIAN		15	14	13
19	20	21	22 RESERVATION	23	24
30	29	28 UNSURVEYED	26	25	25
31	32	33	34	35	36

36 M
AP217

Township 9 North, Range 25 East
 Township 9 North, Range 24 East
 Township 8 North, Range 24 East
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 2, 1969 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The magnetic declination used was 14° East.

Township 9 North, Range 25 East, G&SR M., Arizona

The north boundary of the Fort Apache Indian Reservation was surveyed in 1882 by A. P. Johnson, resurveyed in 1906 by J. B. Wright and retraced in 1915 by S. E. Blout.

Re monumentation, N. Bdy., Fort Apache Indian Reservation, T. 9 N., R. 25 E., Arizona

The 26½ mile cor., monumented by a malpais stone, 20 x 12 x 6 ins., set in the ground, mkd. NBWMIR on NW. face and B on E. face, with mound of stone to the SW., from which the remains of the orig. bearing trees

A pine, 18 ins. diam., bears N. 63° E., 44 lks. dist., mkd. NBWMIR 26½M BT.


A sawed-off pine stump, 15 ins. diam., bears S. 82° 20' E., 51 lks. dist., mkd. R 26½M BT.

A stump, with a rotted yellow pine tree lying alongside, tree mkd. NBWMIR 26½M BT.

A stump hole, with an uprooted yellow pine tree, 21 ins. diam., alongside, bears N. 43° W., 90 lks. dist., mkd. NBWMIR 26½M BT.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.



from which

A yellow pine, 7 ins. diam., bears S. 43° E., 32 lks. dist., mkd. 26½M BT.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

A yellow pine, 10 ins. diam., bears S. 88° W.,
26½ lks. dist., mkd. 26½M FAIR BT.

A yellow pine, 8 ins. diam., bears N. 26° W.,
19 lks. dist., mkd. 26½M FAIR BT.

Rebuild the mound of stone SW. of the iron post.

Bury orig. cor. stone alongside the iron post.

Cor. is 18 lks. E. of a fence bearing N. 40° E., and
S. 40° W.

The 27 mile cor., monumented by a malpais stone, 18 x 16
x 12 ins., firmly set 8 ins. in the ground, mkd. BMFR on
N. face and NBWMIR 27M on S. face, with mound of stone
to the E., from which the remains of the orig. bearing
trees

An aspen stump, with a rotted log, 12 ins. diam.,
alongside, bears S. 59½° E., 105 lks. dist., log
mkd. with faint scribe mks. on bark.

An aspen stump, with a log, 16 ins. diam., along-
side, bears S. 32½° E., 81 lks. dist., stump mkd.
WMIR 27M.

No evidence found of an aspen, 14 ins. diam.,
bearing S. 11½° W., 98 lks. dist., as called for
in record.

A pine snag, 26 ins. diam., 20 ft. high, bears
N. 12° W., 32 lks. dist., mkd. NBWMIR 27M BT.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of
stone, brass cap mkd.

T9N R25E
27M | S35
FAIR |
1969

from which

A Douglas fir, 5 ins. diam., bears N. 66° E.,
19 lks. dist., mkd. 27M BT.

A yellow pine, 8 ins. diam., bears S. 27° E.,
78 lks. dist., mkd. 27M BT.

A yellow pine, 11 ins. diam., bears S. 12° W.,
42 lks. dist., mkd. 27M FAIR BT.

A Douglas fir, 5 ins. diam., bears N. 22° W.,
62 lks. dist., mkd. 27M FAIR BT.

Rebuild the mound of stone E. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 69 lks. E. of a fence bearing N. and S.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle point 152, monumented by a pine tree, 21 ins. diam., mkd. APNBWMIR 152 on SW. face and BMFR on N. face, from which new accessories

An iron post, set 22 ins. in the ground, for a reference monument, bears N. 2° W., 10.7 lks. dist., brass cap mkd. T9N R25E AP152 RM 7 FT S35 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing N. 84° E., and S. 84° W.


A yellow pine, 12 ins. diam., bears S. 77° E., 49 lks. dist., mkd. AP152 BT.

Angle point is S. 53° W., 17 lks. dist. from a fence cor., from which fences bear S. 28° E., and S. 84° W.

Angle point 153, monumented by a stump hole, with an uprooted pine snag, 18 ins. diam., alongside, mkd. BMFR on one face and APNB on opposite face.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A Douglas fir, 7 ins. diam., bears N. 13½° E., 60 lks. dist., mkd. AP153 BT.

A yellow pine, 9 ins. diam., bears N. 81° E., 66½ lks. dist., mkd. AP153 BT.

Angle point is 4 lks. N. of a fence bearing East and N. 55° W.

Angle point 155, monumented by a pine tree, 28 ins. diam., mkd. APNBWMIR 155 on N. face and faint scribe mks. with R 155 visible on S. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. 2° E., 22.8 lks. dist., brass cap mkd. T9N R25E AP155 RM 15 FT S26 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing S. 18° E., and N. 18° W.

A yellow pine, 10 ins. diam., bears S. 40° E., 71 lks. dist., mkd. AP155 BT.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle point 158, monumented by a pine tree, 18 ins. diam., mkd. with overgrown blazes on N. and S. faces; I cut into blaze on S. face and find scribe mks. MIR 158; from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. 23° E., 15.1 lks. dist., brass cap mkd. T9N R25E AP158 RM 10 FT S26 1969 and an arrow pointing to the true cor. Reference monument is 1 lk. S. of a fence bearing S. 70° E., and N. 70° W.

A yellow pine, 10 ins. diam., bears S. 54° E., 43 lks. dist., mkd. AP148 FAIR BT.

The 28½ mile cor. and angle point 160, monumented by a malpais stone, 16 x 14 x 12 ins., loosely set in the ground, mkd. NBWMIR 28½M on SW. face, with mound of stone alongside, from which the remains of the orig. bearing trees

A pine, 14 ins. diam., bears S. 5° W., 20 lks. dist., mkd. NBWMIR.


A dead stump, 24 ins. diam., bears S. 40° W., 31 lks. dist., no mks.

A dead stump, 12 ins. diam., 3 ft. high, bears N. 61° W., 37 lks. dist., mkd. NBWMIR 28½M BT.

No evidence found of a tree, bearing N. 83° W., 112 lks. dist., as called for in record.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 7 ins. diam., bears S. 88° E., 34 lks. dist., mkd. 28½M AP160 BT.

A spruce, 6 ins. diam., bears S. 86° W., 55 lks. dist., mkd. 28½M FAIR BT.

A pine, 7 ins. diam., bears N. 11° W., 61 lks. dist., mkd. 28½M BT.

Bury orig. cor. stone alongside the iron post.

Cor. is 2 lks. S. of a fence, bearing S. 60° E., and N. 60° W.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS


Angle point 161, monumented by a decayed pine stump, 24 ins. diam., mkd. WM 6 on pieces broken off and lying alongside the stump, from which old bearing trees (not recorded in official record)

A pine, 25 ins. diam., bears N. 11° E., 34½ lks. dist., mkd. with an overgrown blaze. I cut into blaze and find scribe mk. T.

A pine, 35 ins. diam., bears N. 22° W., 39 lks. dist., mkd. AP161 BT.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 12 ins. diam., bears S. 88½° E., 75 lks. dist., mkd. AP161 FAIR BT.

Angle point is 7 lks. W. of a fence bearing N. 46° E., and S. 46° W.

Angle point 163, monumented by a pine, 30 ins. diam., mkd. APNBWMIR 163 on S. face and with an overgrown blaze on N. face, from which new accessories

An iron post, set 24 ins. in the ground, for a reference monument, bears West 22.7 lks. dist., brass cap mkd. T9N R25E S27 RM 15 FT AP163 1969 and an arrow pointing to the true cor.

A yellow pine, 10 ins. diam., bears S. 41° W., 28 lks. dist., mkd. AP163 BT.

Angle point is 49 lks. E. of a fence bearing N. 27° E., and S. 27° W.

Angle point 164, monumented by a pine, 19 ins. diam., mkd. APNBWMIR 164 on E. face and with an overgrown blaze on NW. face, from which new accessories

An iron post, set 20 ins. in the ground, for a reference monument, bears N. 77° E., 18.2 lks. dist., brass cap mkd. T9N R25E AP164 RM 12 FT S27 FAIR 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing N. and S.

A yellow pine, 8 ins. diam., bears S. 46° E., 48 lks. dist., mkd. AP164 FAIR BT.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

The 29½ mile cor. and angle point 171, monumented by a malpais stone, 24 x 14 x 8 ins., lying loose on top of ground, no mks., verified by record course from the remains of the orig. bearing trees

A pine, 12 ins. diam., bears East, 54 lks. dist., mkd. NBWMIR 29½M BT.

A stump hole, bears S. 64° E., 88 lks. dist.


A yellow pine, 23 ins. diam., bears S. 29° E., 100 lks. dist., mkd. NBWM.

A stump hole, with a decayed tree alongside, bears S. 47° E., 44 lks. dist.

(Note: record dist. 40 lks.).

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A white pine, 10 ins. diam., bears N. 13° E., 73 lks. dist., mkd. 29½M AP171 BT.

A yellow pine, 12 ins. diam., bears N. 37° W., 67 lks. dist., mkd. 29½M AP171 BT.

Raise a mound of stone NW. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 20 lks. S. of a fence bearing N. 80° E., and S. 80° W.

Angle point 172, monumented by a pine, 15 ins. diam., mkd. APNBWMIR 172 on S. face, and with an overgrown blaze on N. face, from which new accessories

An iron post, set 16 ins. in the ground, mound of stone to top, for a reference monument, bears S. 14° E., 15.1 lks. dist., brass cap mkd. T9N R25E S34 AP172 RM 10 FT FAIR 1969 and an arrow pointing to the true cor.

A Douglas fir, 6 ins. diam., bears S. 79° E., 41 lks. dist., mkd. AP172 FAIR BT.

Angle point is 71 lks. W. of a fence bearing N. 40° E., and S. 40° W.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle Point 173, monumented by a white pine tree, 20 ins. diam., mkd. BMFR on NW. face, NBWM 73 on N. face and with an overgrown blaze on SE. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. $82\frac{1}{2}^{\circ}$ W., 15.1 lks. dist., brass cap mkd. T9N R25E S34 RM 10 FT AP173 1969 and an arrow pointing to the true cor.

A Douglas fir, 6 ins. diam., bears S. 8° W., 43 lks. dist., mkd. AP173 FAIR BT.

Angle point is 95 lks. E. of a fence bearing N. 25° E., and S. 25° W.

The 30 mile cor., monumented by a malpais stone, 3 x 2 x 1 ft., mkd. BM on W. face and with faint scribe mks. on SE. face, with mound of stone to the W., from which the remains of the orig. bearing trees

A pine, 20 ins. diam., bears S. 80° E., 17 lks. dist., mkd. NBWMIR 30M BT.

A dead pine, 18 ins. diam., bears S. 55° E., 40 lks. dist., mkd. NBWMIR 30M BT.

No evidence found of a pine, 6 ins. diam., bearing S. 5° W., 30 lks. dist., as called for in record.

A cut-off pine stump, 8 ins. high, 30 ins. diam., bears S. 25° W., 45 lks. dist., no mks.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T9N R25E
S34 / 30M
FAIR
1969

from which

A pine, 5 ins. diam., bears S. 21° E., $35\frac{1}{2}$ lks. dist., mkd. X BT.

A pine, 7 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ W., 24 lks. dist., mkd. 30M BT.

A Douglas fir, 7 ins. diam., bears N. $14\frac{1}{2}^{\circ}$ W., 16 lks. dist., mkd. 30M BT.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 19 lks. W. of a fence bearing N. 40° E., and S. 40° W.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle point 174, monumented by a white pine, 34 ins. diam., mkd. NBWMIR 174 on E. face and with an overgrown blaze on W. face, from which new accessories

An iron post, set 20 ins. in the ground, for a reference monument, bears N. 19° W., 15.1 lks. dist., brass cap mkd. T9N R25E AP174 RM 10 FT S34 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing S. 80° E., and N. 80° W.

A white pine, 6 ins. diam., bears S. 63° E., 35 lks. dist., mkd. AP174 FAIR BT.

Angle point 175, monumented by a yellow pine tree, 24 ins. diam., mkd. BMFR on N. face and with an overgrown blaze on S. face; I cut into blaze on S. face and find scribe mk. 5; from which new accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears S. 13° E., 15.1 lks. dist., brass cap mkd. T9N R25E AP 175 RM 10 FT S34 FAIR 1969 and an arrow pointing to the true cor.

A yellow pine, 11 ins. diam., bears S. 56° W., 27 lks. dist., mkd. AP175 FAIR BT.

Angle point is under a fence bearing S. 74° W., and S. 86° E.

Angle point 176, monumented by a yellow pine tree, 19 ins. diam., mkd. APNBWMIR 176 on SE. face and with a blaze, partially overgrown, and scribe mks. BM on N. face, from which new accessories

An iron post, set 22 ins. in the ground, for a reference monument, bears N. 71° W., 15.1 lks. dist., brass cap mkd. T9N R25E S33 RM 10 FT AP176 1969 and an arrow pointing to the true cor.

A yellow pine, 9 ins. diam., bears S. 48° W., 45 lks. dist., mkd. AP176 BT.

Angle point is N. 55° W., 53 lks. dist., from a fence cor., from which fences bear N. 72° E., and North and South.

Angle point 177, monumented by a stump hole, with an up-rooted decayed pine tree, 26 ins. diam., alongside, mkd. 177.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A yellow pine, 7 ins. diam., bears N. 60° E., 22 lks. dist., mkd. AP177 FAIR BT.

A yellow pine, 10 ins. diam., bears N. 43° W., 22 lks. dist., mkd. AP177 BT.

Angle point is 62 lks. E. of a fence bearing N. 20° E., and SW.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

The 30½ mile cor., monumented by a malpais stone, 24 x 18 x 8 ins., firmly set in the ground, in a collar of stone, mkd. NBWMIR on SE. face, with mound of stone to the NE., from which the remains of the orig. bearing trees

A rotted pine stump, bears S. 73½° E., 45 lks. dist., no mks.


A pine, 18 ins. diam., bears S. 15½° W., 20 lks. dist., mkd. NBWMIR 30½M BT.

A pine, 12 ins. diam., bears S. 26½° W., 7 lks. dist., mkd. NBWMIR 30½M BT.

A pine, 30 ins. diam., bears S. 63° W., 29 lks. dist., mkd. NBWMIR M BT.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T9N R25E
S33

30½M
FAIR
1969

from which

A white pine, 9 ins. diam., bears N. 41° E., 32 lks. dist., mkd. 30½M BT.

Rebuild the mound of stone NE. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 15 lks. N. of a fence bearing N. 80° E., and S. 80° W.

Angle point 178, monumented by a dead yellow pine, 20 ins. diam., mkd. WMIR 178 on S. face and BMFR on N. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 29° W., 15.1 lks. dist., brass cap mkd. T9N R25E S33 RM 10 FT AP178 FAIR 1969 and an arrow pointing to the true cor.

A Douglas fir, 8 ins. diam., bears N. 73° W., 44 lks. dist., mkd. AP178 FAIR BT.

Angle point is under a fence bearing N. 80° E., and N. 35° W.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle point 179, monumented by a yellow pine tree, 21 ins. diam., mkd. APNBWMIR 179 on S. face and with an overgrown blaze on N. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 21° W., 15.1 lks. dist., brass cap mkd. T9N R25E AP179 RM 10 FT S33 FAIR 1969 and an arrow pointing to the true cor.

A yellow pine, 12 ins. diam., bears S. 74° E., 73 lks. dist., mkd. AP179 BT.

Cor. is 56 lks. N. of a fence bearing S. 60° E., and N. 60° W.

Angle point 180, monumented by a yellow pine tree, 21 ins. diam., mkd. WMIR 180 on E. face and with overgrown blazes on N. and S. faces, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. 3° E., 37.8 lks. dist., brass cap mkd. T9N R25E AP180 RM 25 FT S33 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing S. 60° E., and N. 60° W.

A Douglas fir, 6 ins. diam., bears West, 37 lks. dist., mkd. AP180 FAIR BT.

Angle point 181, monumented by a yellow pine tree, 20 ins. diam., mkd. with overgrown blazes; I cut into blaze and find scribe mks. IR 181, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 32° W., 22.7 lks. dist., brass cap mkd. T9N R25E AP181 RM 15 FT FAIR 1969 and an arrow pointing to the true cor.

A yellow pine, 8 ins. diam., bears S. 71° E., 50 lks. dist., mkd. AP181 BT.

Angle point is 124 lks. N. of a fence bearing irregularly S. 38° E., and N. 38° W.

Angle point 186, monumented by a yellow pine tree, 20 ins. diam., mkd. APNBWMIR 186 on SW. face, and BMFR on E. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 71½° W., 15.1 lks. dist., brass cap mkd. T9N R25E S28 RM 10 FT AP186 FAIR 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing S. 18° E., and N. 18° W.

A Douglas fir, 9 ins. diam., bears N. 74½° W., 31 lks. dist., mkd. AP186 FAIR BT.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle point 187, monumented by a yellow pine tree, 18 ins. diam., mkd. APNBWMIR 187 on SW. face and with an overgrown blaze on N. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 26° W., 15.1 lks. dist., brass cap mkd. T9N R25E S28 AP187 RM 10 FT FAIR 1969 and an arrow pointing to the true cor.

A Douglas fir, 6 ins. diam., bears N. 83½° E., 36½ lks. dist., mkd. AP187 BT.

Angle point 188, monumented by a yellow pine tree, 24 ins. diam., mkd. APNBWMIR 188 on S. face and BMFR on N. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 13° W., 18.2 lks. dist., brass cap mkd. T9N R25E AP188 RM 12 FT S28 FAIR 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing E. and W.

A spruce, 6 ins. diam., bears N. 33½° W., 33 lks. dist., mkd. AP188 BT.

Angle point 189, monumented by a yellow pine tree, 27 ins. diam., mkd. APNBWMIR 189 on S. face and BMFR on NE. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 28° W., 15.1 lks. dist., brass cap mkd. T9N R25E AP189 RM 10 FT S28 FAIR 1969 and an arrow pointing to the true cor.

A Douglas fir, 6 ins. diam., bears N. 31° W., 41 lks. dist., mkd. AP189 BT.

Angle point is 75 lks. North of a fence bearing N. 80° E. and S. 80° W.

Angle point 190, monumented by a yellow pine, 32 ins. diam., mkd. BMFR on N. face and with an overgrown blaze on S. face; I cut into blaze on S. face and find scribe mks. 190; from which new accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears N. 28° W., 48.4 lks. dist., brass cap mkd. T9N R25E AP190 RM 32 FT S29 1969 and an arrow pointing to the true cor. Reference monument is under a fence bearing N. 68° E., and S. 68° W.

A yellow pine, 8 ins. diam., bears N. 69° W., 38 lks. dist., mkd. AP190 BT.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle point 194, monumented by a yellow pine tree, 40 ins. diam., mkd. APNBWMIR 194 on S. face and with an overgrown blaze on N. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 80° E., 22.7 lks. dist., brass cap mkd. T9N R25E S32 RM 15 FT AP194 FAIR 1969 and an arrow pointing to the true cor.

A white pine, 8 ins. diam., bears S. 4° E., 47 lks. dist., mkd. AP194 FAIR BT.

Angle point is under a fence bearing N. 55° E., and S. 55° W.

Angle point 195, monumented by a yellow pine tree, 34 ins. diam., mkd. with overgrown blazes on N. and S. faces; I cut into blaze on S. face and find scribe mks. NBWMIR 195; from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 25° E., 22.7 lks. dist., brass cap mkd. T9N R25E AP195 RM 15 FT S32 FAIR 1969 and an arrow pointing to the true cor.

A yellow pine, 11 ins. diam., bears S. 77° W., 27 lks. dist., mkd. AP195 FAIR BT.

Angle point is 88 lks. S. of a fence bearing E. and W.

Angle point 196, monumented by a yellow pine tree, 30 ins. diam., mkd. with overgrown blazes on N. and S. faces; I cut into blaze on S. face and find scribe mks. R 196; from which new accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears N. 24° E., 15.1 lks. dist., brass cap mkd. T9N R25E AP196 RM 10 FT S32 1969 and an arrow pointing to the true cor.

A white pine, 8 ins. diam., bears N. 70° W., 41 lks. dist., mkd. AP196 BT.

Angle point 197, monumented by a yellow pine tree, 20 ins. diam., mkd. APNBWMIR 197 on S. face and with an overgrown blaze on N. face, from which new accessories

An iron post, set 24 ins. in the ground, in a collar of stone, for a reference monument, bears N. 4° E., 15.1 lks. dist., brass cap mkd. T9N R25E AP197 RM 10 FT S32 1969 and an arrow pointing to the true cor.

A yellow pine, 10 ins. diam., bears N. 44° W., 42 lks. dist., mkd. AP197 BT.

Angle point is 75 lks. S. of a fence bearing N. 84° E., and N. 76° W.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 25 E.

CHAINS

Angle point 202, monumented by a yellow pine tree, 22 ins. diam., mkd. with overgrown blazes on N. and S. faces; I cut into blaze on S. face and find scribe mks. 202; from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. 20° E., 18.2 lks. dist., brass cap mkd. T9N R25E AP202 RM 12 FT S31 1969 and an arrow pointing to the true cor.

A yellow pine, 6 ins. diam., bears S. 36° E., 43 lks. dist., mkd. AP202 FAIR BT.

Angle point is 97 lks. S. of a fence bearing S. 51° E., and N. 51° W.

Angle point 203, monumented by a yellow pine tree, 19 ins. diam., mkd. BMFR on SE. face and with an overgrown blaze on NW. face; I cut into blaze on NW. face and find scribe mks. R 203; from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears S. 27° W., 22.7 lks. dist., brass cap mkd. T9N R25E AP203 RM 15 FT S31 FAIR 1969 and an arrow pointing to the true cor. Reference monument is 3 lks. N. of a fence bearing S. 55° E., and West.

A white pine, 6 ins. diam., bears N. 78° E., 63 lks. dist., mkd. AP203 BT.

Angle point 208, monumented by a yellow pine tree, 24 ins. diam., mkd. APNBWMIR 208 on SE. face and with an overgrown blaze on NW. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. 81° W., 22.7 lks. dist., brass cap mkd. T9N R25E S31 RM 15 FT AP208 1969 and an arrow pointing to the true cor.

A yellow pine, 6 ins. diam., bears S. 21° W., 48 lks. dist., mkd. AP208 FAIR BT.

Angle point is 71 lks. E. of a fence bearing N. 25° E., and S. 25° W.

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 9 N., R. 24 E.

<p>CHAINS</p>	<p style="text-align: center;">Township 9 North, Range 24 East, G&SR M., Arizona</p> <p>The north boundary of the Fort Apache Indian Reservation was resurveyed in 1906 by J. B. Wright and retraced in 1915 by S. E. Blout.</p>
	<p style="text-align: center;">Remonumentation, N. Bdy., Fort Apache Indian Reservation, T. 9 N., R. 24 E., Arizona</p> <hr/> <p>Angle point 212, monumented by a yellow pine tree, 22 ins. diam., mkd. APN WMIR 212 on S. face and MF on N. face, from which new accessories</p> <p style="padding-left: 40px;">An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. 10° W., 22.7 lks. dist., brass cap mkd. T9N R24E AP212 RM 15 FT S36 1969 and an arrow pointing to the true cor.</p> <p style="padding-left: 40px;">A yellow pine, 6 ins. diam., bears S. 48° W., 60 lks. dist., mkd. AP212 FAIR BT.</p> <p>Angle point is 54 lks. S. of a fence bearing S. 80° E., and N. 80° W.</p>
	<p>Angle point 232, monumented by a yellow pine tree, 28 ins. diam., mkd. with a burned blaze and scribe mks. APNBW 232 on SW. face and BMF on NE. face, from which new accessories</p> <p style="padding-left: 40px;">An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears North, 15.1 lks. dist., brass cap mkd. T9N R24E AP232 RM 10 FT S33 1969 and an arrow pointing to the true cor.</p> <p style="padding-left: 40px;">A yellow pine, 12 ins. diam., bears S. 30° W., 110 lks. dist., mkd. AP232 FAIR BT.</p> <p>Angle point is on a steep E. Slope, under a fence bearing S. 52° E., and S. 65° W.</p>
	<p>Angle point 233, monumented by a yellow pine, 28 ins. diam., mkd. BMFR on N. face and with an overgrown blaze on S. face; I cut into blaze on S. face and find scribe mks. 233, from which new accessories</p> <p style="padding-left: 40px;">An iron post, set 20 ins. in the ground, for a reference monument, bears N. 24° W., 15.1 lks. dist., brass cap mkd. T9N R24E AP233 RM 10 FT S33 1969 and an arrow pointing to the true cor.</p> <p style="padding-left: 40px;">A yellow pine, 15 ins. diam., bears S. 34° E., 170 lks. dist., mkd. AP233 FAIR BT.</p> <p>Angle point is on E. edge of an open area, under a fence bearing N. 70° E., and SW.</p>

Remonumentation, N. Bdy., Fort Apache Indian Reservation
T. 8 N., R. 24 E.

CHAINS

Township 8 North, Range 24 East, G&SR M., Arizona

The north boundary of the Fort Apache Indian Reservation was resurveyed in 1906 by J. B. Wright and a portion was retraced in 1915 by S. E. Blout.

Remonumentation, N. Bdy., Fort Apache Indian
Reservation, T. 8 N., R. 24 E., Arizona

Angle point 217, monumented by a yellow pine tree, 19 ins. diam., mkd. MIR 217 on S. face and BMFR on E. face, from which new accessories

An iron post, set 20 ins. in the ground, in a collar of stone, for a reference monument, bears N. 49° W., 15.1 lks. dist., brass cap mkd. T8N R24E RM 10 FT AP217 1969, and an arrow pointing to the true cor.

A yellow pine, 6 ins. diam., bears S. 12° E., 25 lks. dist., mkd. AP217 FAIR BT.

Angle point is under a fence bearing NE. and SW.

The 36 mile cor., monumented by a malpais stone in place, 24 x 18 x 6 ins. above ground, mkd. BMFR on N. face and NBWMIR on SE. face, with mound of stone to the S., from which the remains of the orig. bearing trees

A pine, 25 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ E., 12 lks. dist., mkd. NBWMIR 36M BT.


A stump hole, with a decayed log alongside, bears S. $21^{\circ}45'$ E., 33 lks. dist., no mks.

A rotted stump bears West, 60 lks. dist., no mks.

A pine, 22 ins. diam., bears N. $75\frac{1}{2}^{\circ}$ W., 58 lks. dist., mkd. with a blaze, partially overgrown, and faint scribe mks.

At the cor. point

Drilled a hole in orig. cor. stone, and set a brass tablet, 3 ins. in diam., $2\frac{1}{2}$ in. stem, in concrete, flush with the top, tablet mkd.



from which

A yellow pine, 6 ins. diam., bears S. $36\frac{1}{2}^{\circ}$ E., $45\frac{1}{2}$ lks. dist., mkd. 36M FAIR BT.

A yellow pine, 12 ins. diam., bears S. 65° W., 88 lks. dist., mkd. 36M BT.

Rebuild the mound of stone S. of the iron post.

Cor. is 4 lks. W. of a fence bearing North and S. 30° W.

17

CERTIFICATE OF SURVEY

(I) ~~(We)~~, John H. Witmer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of July, 1969, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners of the North Boundary of the Fort Apache Indian Reservation in Township 9 North, Ranges 25 and 24 East, and Township 8 North, Range 24 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(us)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 1, 1969
(Date)

John H. Witmer
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date FEB 18 1970

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners of the North Boundary of the Fort Apache Indian Reservation in Township 9 North, Ranges 25 and 24 East, and Township 8 North, Range 24 East, all of the Gila and Salt River Meridian, Arizona, executed by John H. Witmer, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 2 1971
(Date)

Clark I. Sumner
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey)