

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 8 NORTH, RANGE 23 EAST

TOWNSHIP 9 NORTH, RANGE 14 EAST

TOWNSHIP 10 NORTH, RANGE 22 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

John H. Witmer, Cadastral Surveyor

Under special instructions dated July 1, 19 69, which provided for the surveys
included under Group Number 514, approved July 2, 1969,
and assignment instructions dated July 2, 19 69.

Survey commenced July 8, 19 69

Survey completed September 11, 19 69

BOOK 4896

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

BOOK 4896
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 8 N. R. 23 E. Mer. G&SR

6	5	4	3	● 3 2	● 2 1	● 2
7	8	9	10	11	12	● 1
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Tp. 9 N. R. 14 E. Mer. G&SR

6	5	● 6 4	3	2	1	
7	8	● 5 9	10	11	12	
18	17	16	15	14	13	
19	20	21	● 4 22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Tp. 10 N. R. 22 E. Mer. G&SR

6	5	4	3	2	1	● 8
7	8	9	10	11	12	
18	17	16	15	14	13	
			● 12	● 12	● 10	● 11
19	20	21	22	23	24	
● 14	● 14			● 10	● 10	
● 8	● 13	28	27	● 9	26	25
	● 13		● 11			
31	32	33	34	35	36	

Township 8 North, Range 23 East
 Township 9 North, Range 14 East
 Township 10 North, Range 22 East
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 2, 1969 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The magnetic declination used was 14° East.

Township 8 North, Range 23 East, G&SRM., Arizona

The east boundary and subdivisional lines were surveyed in 1908 by J. B. Wright.

Re monumentation, T. 8 N., R. 23 E., Arizona

The cor. of secs. 1, 6, 7 and 12, T. 8 N., Rs. 23 and 24 E., monumented by a malpais stone, 14 x 12 x 8 ins., firmly set 8 ins. in the ground, mkd. with 5 notches on the S. face and 1 notch on the N. face, with a local survey cor., a pipe, 1½ in. diam., set alongside, and with a mound of stone to the E., from which the remains of the orig. bearing trees

A cut-off pine stump, with a cut log, 18 ins. diam., alongside, bears S. 20° E., 28 lks. dist., log mkd. T8N R23E S7 BT.
 (Note: record course and dist. S. 2° E., 24 lks., and record shows range scribed as R24E).

A cut-off stump, with a rotted cut log, 24 ins. diam., alongside, bears S. 30° W., 6 lks. dist., log mkd. T8N R24E S12 BT.
 (Note: record dist. 23 lks., and record shows range scribed as R23E).

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T8N
 R23E R24E
 S 1 | S 6
 S12 | S 7
 1969

from which

Remonumentation, T. 8 N., R. 23 E., Arizona

CHAINS

A yellow pine, 6 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 28 lks. dist., mkd. T8N R24E S6 BT.

A yellow pine, 12 ins. diam., bears S. 46° E., 23 lks. dist., mkd. T8N R24E S7 BT.

Bury the orig. cor. stone and the local cor. pipe alongside the iron post.

Cor. is under a fence bearing N. and S.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, T. 8 N., Rs. 23 and 24 E., monumented by a local survey corner, a pipe, 1 in. diam., firmly set in the ground, with mound of stone to the N., verified by record dist. from the remains of the orig. bearing trees

A yellow pine, 22 ins. diam., bears N. 70° E., 82 lks. dist., mkd. with an overgrown blaze.
(Note: record bearing N. 63° E.).

A stump hole, bears S. 65° W., 9 lks. dist.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T8N
R23E R24E
 $\frac{1}{4}$
S1 | S6
1969

from which

A yellow pine, 7 ins. diam., bears N. 19° W., 86 lks. dist., mkd. T8N R23E $\frac{1}{4}$ S1 BT.

The orig. cor. stone; a granite stone, 24 x 13 x 8 ins., mkd. $\frac{1}{4}$ on one face, had been disturbed by fence construction and was found lying loose on top of the ground.

Bury the orig. cor. stone and local cor. pipe alongside the iron post.

Cor. is at a fence cor., from which fences bear S. and W.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented by a malpais stone, 24 x 12 x 10 ins., lying loose on the ground, with mound of stone to the W., verified by record course and dist. from the remains of the orig. bearing trees

A cut-off pine stump, 24 ins. diam., bears N. 47° E., 99 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A dead pine, 26 ins. diam., bears S. 50° W., 101 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

Remonumentation, T. 8 N., R. 23 E., Arizona

CHAINS

T8N R23E

 $\frac{1}{4}$
 S2|S1
 1969

from which

A pine, 7 ins. diam., bears N. 44° E., 39 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

A pine, 11 ins. diam., bears N. 77° W., 82 lks. dist., mkd. T8N R23E $\frac{1}{4}$ S2 BT.

A local survey cor., a pipe, 1½ ins. diam., firmly set under a fence bearing E. and W., bears South, 2 lks. dist.

Bury orig. cor. stone alongside iron post.

Cor. is 2 lks. N. of a fence bearing E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented by a malpais stone, 18 x 16 x 12 ins., loosely set in the ground, in a collar of stone, mkd. $\frac{1}{4}$ on W. face, with a local survey corner, a pipe, 1½ ins. diam., firmly set in ground, alongside, from which the remains of the orig. bearing trees

A rotted cut-off pine stump, 15 ins. diam., bears N. 44° E., 40 lks. dist., no mks.

A yellow pine, 20 ins. diam., bears S. 80° W., 67 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

At the cor. point

Set the iron post, 14 ins. in the ground to bed rock, mound of stone to top, brass cap mkd.

T8N R23E

 $\frac{1}{4}$
 S3|S2
 1969

from which

A yellow pine, 7 ins. diam., bears N. 75° E., 87 lks. dist., mkd. $\frac{1}{4}$ S2 BT.

Bury orig. cor. stone and local cor. pipe alongside the iron post.

Remonumentation, T. 9 N., R. 14 E., Arizona

CHAINS

Township 9 North, Range 14 East, G&SR M., Arizona

The north boundary and subdivisional lines were surveyed in 1907 by E. C. Dietrich, and the north boundary was resurveyed in 1938 by C. F. Warner.

Remonumentation, T. 9 N., R. 14 E., Arizona

The cor. of secs. 3, 4, 33 and 34, Tps. 9 and 10 N., R. 14 E., monumented by a granite stone in place, 10 x 6 x 6 ft. above ground, no mks., from which the remains of the orig. bearing trees

A sycamore, 14 ins. diam., bears N. 25° E., 146 lks. dist., mkd. with a rotted out blaze.

A juniper, 34 ins. diam., bears S. 60° E., 76 lks. dist., mkd. T9N R14E S3 BT.

A dead pine, 24 ins. diam., bears S. 30° W., 54 lks. dist., mkd. T9N R14E S4 BT.

No evidence found of a sycamore, 10 ins. diam., bearing N. 69° W., 127 lks. dist., as called for in record.

At the cor. point

Drilled a hole in the orig. cor. stone and set a brass tablet, 3 ins. in diam., 2½ in. stem, in concrete, flush with the top, tablet mkd.

T10N R14E
S33|S34
 S 4|S 3
 T9N
 1969

from which

A yellow pine, 15 ins. diam., bears N. 56° E., 80 lks. dist., mkd. T10N R14E S34 BT.

Cor. is on a steep W. slope, about 1 ch. E. of Cherry Creek.

The ¼ sec. cor. of secs. 21 and 22, monumented by a sandstone, 15 x 12 x 5 ins., set 6 ins. in the ground, mkd. ¼ on W. face, from which the remains of the orig. bearing trees

A stump hole, with a dead uprooted oak tree, 15 ins. diam., alongside, bears N. 39° E., 35 lks. dist., mkd. ¼ S22 BT.

No evidence found of an oak tree, bearing S. 36¼° W., 108 lks. dist., as called for in record.

At the cor. point

Set the iron post, 12 ins. in the ground to bed rock, mound of stone to top, brass cap mkd.

Remonumentation, T. 9 N., R. 14 E., Arizona

CHAINS

T9N R14E
 $\frac{1}{4}$
 S21|S22
 1969

from which

A juniper, 4 ins. diam., bears S. 10° E., 6 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

A pinon, 4 ins. diam., bears N. 6° W., 40 lks. dist., mkd. X BT.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is on a steep E. slope.

The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented by a sandstone, 18 x 6 x 6 ins., set 10 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, from which the remains of the orig. bearing trees

A juniper, 42 ins. diam., bears S. 17 $\frac{1}{2}$ ° E., 78 lks. dist., mkd. $\frac{1}{4}$ S21 BT.

A dead oak, 20 ins. diam., bears N. 49 $\frac{1}{2}$ ° W., 61 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 16 ins. in the ground, in a collar of stone, brass cap mkd.

T9N R14E
 $\frac{1}{4}$ $\frac{S16}{S21}$
 1969

from which

A juniper, 9 ins. diam., bears N. 83 $\frac{1}{2}$ ° W., 96 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

Cor. is in scattered oak and juniper on a NW. slope.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented by a sandstone, 16 x 8 x 6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone to the W.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T9N R14E
 $\frac{1}{4}$
 S8|S9
 1969

No bearing trees available.

Rebuild mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 9 N., R. 14 E., Arizona

CHAINS

Cor. is in widely scattered juniper on an E. slope, about 10 chs. W. of the main dirt road to Young, Arizona.

The cor. of secs. 4, 5, 8 and 9, monumented by a sandstone, 18 x 10 x 8 ins., firmly set 8 ins. in the ground, mkd. with 5 notches on S. face and 4 notches on E. face, with mound of stone to the W., from which the remains of the orig. bearing trees

An oak, 14 ins. diam., bears N. 29° E., 92 lks. dist., mkd. with an overgrown blaze.

An oak, 14 ins. diam., bears S. 60½° E., 67½ lks. dist., mkd. with an overgrown blaze.

A rotted oak stump, bears S. 23° W., 75 lks. dist., no mks.

A juniper, 28 ins. diam., bears N. 45¼° W., 85 lks. dist., mkd. with a rotted out blaze

The following BT, not called for in record, was also found, with mks. appearing to have been scribed with a pocket knife

A juniper, 27 ins. diam., bears S. 22° W., 109 lks. dist., mkd. T9N R14E S8 BT.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T9N R14E
 S5|S4
 S8|S9
 1969

No suitable new bearing trees available. They are all old Oak trees in bad condition.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 120 lks. E. of a fence bearing N. and S.

The witness ¼ sec. cor. of secs. 4 and 5, monumented by a granite stone, 18 x 8 x 6 ins., firmly set 12 ins. in the ground, mkd. WC¼ on W. face, with mound of stone to the W., from which the remains of the orig. bearing trees

An oak, 17 ins. diam., bears S. 23° E., 101 lks. dist., mkd. with an overgrown blaze.

A cut-off oak stump, 12 ins. diam., bears N. 89½° W., 45 lks. dist., no mks.

At the cor. point

Set the iron post, 20 ins. in the ground, brass cap mkd.

T9N R14E
 ¼
 W|C
 S5↓S4
 1969

Remonumentation, T. 9 N., R. 14 E., Arizona

CHAINS

from which

An alligator juniper, 7 ins. diam., bears N. 55°
W., 68 lks. dist., mkd. T9N R14E WC $\frac{1}{4}$ S5 BT.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 75 lks. N. of Chamberlain Trail graded road
bearing E. and W.

Remonumentation, T. 10 N., R. 22 E., Arizona

CHAINS

Township 10 North, Range 22 East, G&SR M., Arizona

The north boundary was surveyed in 1882 by O. D. Wheeler, the east and west boundaries and subdivisional lines were surveyed in 1883 by O. D. Wheeler, Homestead Entry 647 in section 29 was surveyed in 1926 by T. F. Myers and the east boundary was resurveyed in 1935 by Theo Vander Meer.

Remonumentation, T. 10 N., R. 22 E., Arizona

The cor. of Tps. 10 and 11 N., Rs. 22 and 23 E., monumented by a malpais stone, 18 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. with 6 notches on the 4 faces, with mound of stone to the S.

At the cor. point

Set the iron post, 18 ins. in the ground, mound of stone to top, brass cap mkd.

T11N
R22E R23E
S36|S31
S 1|S 6
T10N
1969

from which

A forked juniper, 8 ins. diam., bears S. 2½° E., 270 lks. dist., mkd. on main trunk T10N R23E S6 BT.

No other bearing trees available.

Rebuild mound of stone S. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 2 lks. N. of a fence bearing E. and W.

The ¼ sec. cor. of secs. 25 and 30, T. 10 N., Rs. 21 and 22 E., monumented by a sandstone, 16 x 10 x 6 ins., firmly set 6 ins. in the ground, in a collar of stone, from which the remains of the orig. bearing trees

A cut-off pine stump, with a pine log, 18 ins. diam., alongside, bears S. 60° E., 49 lks. dist., stump mkd. BT and log mkd. ¼ S.
(Note: record bearing S. 6° E.).

A white oak, 11 ins. diam., bears S. 50° W., 60 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T10N
R21E R22E
¼
S25|S30
1969

from which

Remonumentation, T. 10 N., R. 22 E., Arizona

CHAINS

A juniper, 9 ins. diam., bears S. 71° E., 16 lks. dist., mkd. T10N R22E S30 BT.

A juniper, 8 ins. diam., bears N. 62° W., 33 lks. dist., mkd. T10N R21E S25 BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is in level area in dense oak, juniper and pine timber.

The $\frac{1}{4}$ sec. cor. of secs. 13 and 24, monumented by a basalt stone, 32 x 14 x 9 ins., loosely set in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone to the S., from which the remains of the orig. bearing trees

A yellow pine, 24 ins. diam., bears N. 12° E., 116 lks. dist., mkd. with an overgrown blaze. (Note: record bearing N. 2° E.).

A dead yellow pine, 35 ins. diam., bears S. 73° E., 110 lks. dist., mkd. $\frac{1}{4}$ S.

At the cor. point

Set the iron post, 18 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R22E

$\frac{1}{4}$ $\frac{S13}{S24}$
1969

from which

A yellow pine, 8 ins. diam., bears S. 34° E., 83 lks. dist., mkd. $\frac{1}{4}$ S24 BT.

A yellow pine, 6 ins. diam., bears N. 50° W., 130 lks. dist., mkd. $\frac{1}{4}$ S13 BT.

Raise a mound of stone N. of the iron post.

Bury orig. cor. stone alongside the iron post.

Cor. is in moderate juniper and pine timber, 5 lks. S. of a bladed area.

The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented by a basalt stone, 22 x 13 x 8 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, in a scattered mound of stone.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T10N R22E

$\frac{1}{4}$ S27|S26
1969

Raise a mound of stone W. of the iron post.

Bury orig. cor. stone alongside the iron post.

Cor. is 2 lks. W. of a fence bearing N. and S.

Remonumentation, T. 10 N., R. 22 E., Arizona

CHAINS

The cor. of secs. 22, 23, 26 and 27, monumented by a basalt stone, 30 x 14 x 10 ins., firmly set 10 ins. in the ground, mkd. with 2 notches on the S. face and 2 notches on the E. face, from which the orig. bearing trees

A pine, 18 ins. diam., bears N. 81° E., 81 lks. dist., mkd. with an overgrown blaze.

A juniper, 35 ins. diam., bears S. 16° W., 140 lks. dist., mkd. S27.

A juniper, 32 ins. diam., bears N. 24° W., 137 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 10 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R22E
S22|S23
S27|S26
 1969

No new bearing trees available.

Bury orig. cor. stone alongside the iron post.

Cor. is 10 lks. W. of a fence cor., from which fences bear E. and S. for 32 lks., then S. and W.

The ¼ sec. cor. of secs. 23 and 26, monumented by a basalt stone, 16 x 8 x 6 ins., firmly set 8 ins. in the ground, mkd. ¼ on N. face, with mound of stone to the NE.

At the cor. point

Set the iron post, 14 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R22E
 ¼ S23
 S26
 1969

No bearing trees available.

Raise a mound of stone N. of the iron post.

Bury orig. cor. stone alongside the iron post.

Cor. is under a fence bearing E. and W.

The cor. of secs. 14, 15, 22 and 23, monumented by a basalt stone, 24 x 12 x 7 ins., set 18 ins. in the ground, in a scattered mound of stone, mkd. with 3 notches on S. face and 2 notches on E. face.

At the cor. point

Set the iron post, 15 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R27E
S15|S14
S22|S23
 1969

Remonumentation, T. 10 N., R. 22 E., Arizona

CHAINS

No bearing trees available.

Raise a mound of stone W. of the iron post.

Bury orig. cor. stone alongside the iron post.

Cor. is 26 lks. W. of a fence cor., from which fences bearing S. and NW. for 58 lks. dist., thence S. and W.

The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented by a basalt stone, 18 x 10 x 7 ins.; loosely set 2 ins. in the ground, in a scattered mound of stone, mkd. $\frac{1}{4}$ on N. face, from which the remains of the orig. bearing trees

A juniper stump, 7 ins. diam., bears N. 16° E., 136 lks. dist., no mks.

A juniper stump, 22 ins. diam., bears N. 85° W., 226 lks. dist., mkd. BT.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R22E
 $\frac{1}{4}$ $\frac{S14}{S23}$
 1969

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 5 lks. N. of a fence bearing E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented by a basalt stone, 18 x 12 x 10 ins., firmly set in the ground, in a collar of stone, mkd. $\frac{1}{4}$ on N. face.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T10N R22E
 $\frac{1}{4}$ $\frac{S27}{S34}$
 1969

No bearing trees available.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is in moderate scrub cedar, 12 lks. S. of a fence bearing E. and W.

Remonumentation, T. 10 N., R. 22 E., Arizona

CHAINS

The cor. of secs. 15, 16, 21 and 22, monumented by a basalt stone, 30 x 16 x 5 ins., set 6 ins. in the ground, mkd. with 3 notches on S. face and 3 notches on E. face, with rebar alongside, and with mound of stone to the N., from which the remains of the orig. bearing trees

A stump hole, with an uprooted juniper tree, 15 ins. diam., alongside, bears S. 32° E., 158 lks. dist.; mkd. T10N R22E S22.

A juniper, 36 ins. diam., bears N. 88° W., 132 lks. dist., mkd. T10N R22E S.

At the cor. point

Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.

T10N	R22E
<u>S16</u>	<u>S15</u>
S21	S22
1969	

No new bearing trees available.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone and the rebar alongside the iron post.

Cor. is in a railed area, 57 lks. E. of a fence cor., from which fences bear S., W. and NE. for 1 lk., thence E.

The ¼ sec. cor. of secs. 15 and 22, monumented by a basalt stone, 19 x 12 x 9 ins., firmly set 10 ins. in the ground, mkd. ¼ on N. face.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T10N	R22E
¼	<u>S15</u>
	S22
1969	

from which

A local corner, a rebar, 5/8 ins. diam., firmly set in the ground, bears S. 49° W., 8.2 lks. dist.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 21 lks. S. of a fence bearing E. and W.

Remonumentation, T. 10 N., R. 22 E., Arizona

CHAINS

The cor. of secs. 29, 30, 31 and 32, monumented by a sandstone, 25' x 18' x 17 ins., set 19 ins. in the ground, mkd. with 1 notch on S. face and 5 notches on E. face, with mound of stone N., and with a rock in place NE. of the cor., with 8 x 8 x 6 ins. above ground, mkd. 1 ES 647, from which the remains of the original bearing trees

No evidence found of a cedar, 14 ins. diam., bearing N. 38° E., 55 lks. dist., as called for in record.

No evidence found of a yellow pine, 16 ins. diam., bearing S. 40° E., 54 lks. dist., as called for in record.

A pine, 20 ins. diam., bears N. 50° W., 34 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 20 ins. in the ground, brass cap mkd.

T10N R22E
 S30 | S29
 S31 | S32
 1969

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is 110 lks. S. of a power line.

The ¼ sec. cor. of secs. 29 and 30, monumented by a sandstone, 30 x 14 x 7 ins., firmly set 18 ins. in the ground mkd. ¼ on W. face, with a sandstone in place E. of the cor. 10 x 8 x 4 ins. above ground, mkd. 2HES 647 on E. face, from which the remains of the orig. bearing trees

A yellow pine, 22 ins. diam., bears S. 27° E., 40 lks. dist., mkd. ¼ S.
 (Note: record dist. 42 lks.).

A stump hole, bears S. 63° W., 80 lks. dist.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T10N R22E
 ¼
 S30 | S29
 1969

from which

A yellow pine, 6 ins. diam., bears N. 48° W., 108 lks. dist., mkd. ¼ S30 BT.

Bury orig. cor. stone alongside the iron post.

Remonumentation, T. 10 N., R. 22 E., Arizona

CHAINS

The cor. of secs. 19, 20, 29 and 30, monumented by a local survey cor., a pipe, 1 in. diam., buried 3 ins. under ground, in a graded road, verified by record course and dist. from the remains of the orig. bearing trees

A yellow pine, 18 ins. diam., bears N. 18° E., 86 lks. dist., mkd. with faint scribe mks.

A yellow pine, 24 ins. diam., bears S. 54° E., 88 lks. dist., mkd. with an overgrown blaze.

A rotted pine stump, bears SW. 173 lks. dist., mkd. BT. (record).

A yellow pine, 18 ins. diam., bears N. 54° W., 124 lks. dist., mkd. T10N R22E S19.

At the cor. point

Set the iron post, 10 ins. below surface of road, brass cap mkd.

T10N R22E

S19	S20
S30	S29

 1969

The orig. cor., a sandstone, 24 x 11 x 10 ins., mkd. 2 on S. face and with 5 notches on E. face, was found lying on top of the ground nearby.

Bury orig. cor. stone and local pipe cor. alongside the iron post.

Cor. is in a graded county road, 25 lks. N. of a fence bearing W. and S. for 18 lks. dist., thence bearing S. and E.

The ¼ sec. cor. of secs. 19 and 30, monumented by a sandstone, 14 x 10 x 6 ins., set 4 ins. in the ground, mkd. ¼ on N. face, in a collar of stone, from which the remains of the orig. bearing trees

An oak, 10 ins. diam., bears S. 46° W., 47 lks. dist., mkd. with a blaze.
 (Note: record dist. 49 lks.).

No evidence found of a pine, bearing N. 62° W., 53 lks. dist., as called for in record.

At the cor. point

Set the iron post, 20 ins. in the ground, brass cap mkd.

T10N R22E

¼ S19
¼ S30

 1969

from which

A yellow pine, 7 ins. diam., bears S. 54° W., 37 lks. dist., mkd. ¼ S30 BT.

A juniper, 18 ins. diam., bears S. 48½° E., 109 lks. dist., mkd. ¼ S30 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 2 lks. S. of a fence bearing E. and W.

CERTIFICATE OF SURVEY

(I) ~~(We)~~ John H. Witmer, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day
 of July, 1969, (I) ~~(We)~~ have remonumented a portion of the cadastral
 survey corners in Township 8 North, Range 23 East, Township 9 North, Range
 14 East and Township 10 North, Range 22 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

October 1, 1969
 (Date) 
 (Cadastral Surveyor)


 (Date) _____
 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date FEB 18 1970

BUREAU OF LAND MANAGEMENT
 Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral
 survey corners in Township 8 North, Range 23 East, Township 9 North,
 Range 14 East and Township 10 North, Range 22 East, All of the Gila and
 Salt River Meridian, Arizona,
 executed by John H. Witmer, Cadastral Surveyor,
 having been critically examined and found correct, are hereby approved.

JUN 2 1971
 (Date) 
 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

 (Date) _____
 (Chief, Division of Cadastral Survey)