

BOOK 4897

Form 4-679
(January 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 11 NORTH, RANGE 13 EAST

TOWNSHIP 12 NORTH, RANGE 8 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Howard H. Thomas, Cadastral Surveyor

Under special instructions dated April 5, 19 68, which provided for the surveys included under Group Number 499, approved April 5, 1968, and assignment instructions dated April 5, 19 68.

Survey commenced April 23, 19 68

Survey completed June 28, 19 68

BOOK 4897
INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION CORNER MONUMENTS

Tp. 11 N. R. 13 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	17 3	16	15	14	13
19 3	20 3	21	22	23	24
30	29 2	28	27	26	25
31	32	33	34	35	36

Tp. 12 N. R. 8 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. _____ R. _____ Mer. _____

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 11 North, Range 13 East
 Township 12 North, Range 8 East
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 5, 1968 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination used was 14° East.

Township 11 North, Range 13 East, G&SR M., Arizona

The subdivisional lines were surveyed in 1905 by J. B. Wright.

Re monumentation, T. 11 N., R. 13 E., G&SR M., Arizona

The cor. of secs. 29, 30, 31 and 32, monumented by a sandstone, 24 x 10 x 10 ins., firmly set 12 ins. in the ground, in a scattered mound of stone, mkd. with 5 notches on E. face and 1 notch on S. face, from which the orig. bearing trees

A dead pine stump, 36 ins. diam., bears N. 70½° E., 85 lks. dist.

A pine, 24 ins. diam., bears S. 73½° E., 25 lks. dist., mkd. N. R13E S32 BT.

A pine, 24 ins. diam., bears S. 47½° W., 31 lks. dist., mkd. with a blaze, partly overgrown, with parts of scribe mks. visible.

A pine, 26 ins. diam., bears N. 43° W., 62 lks. dist., mkd. T11N R13E S30 BT.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R13E	
S30	S29
S31	S32
1968	

Bury the orig. cor. stone alongside the iron post.

Cor. is about 8 chs. SW. of the Boy Scout Ranch and 4 chs. N. of Williamson Creek.

Remonumentation, T. 11 N., R. 13 E.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented by a sandstone, 23 x 14 x 6 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone to the W. From the cor., the orig. bearing trees

A dead pine snag, 24 ins. diam., bears N. $58\frac{1}{2}^\circ$ E., 53 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

A pine, 33 ins. diam., bears S. 61° W., 77 lks. dist., mkd. $\frac{1}{4}$ S 30

At the cor. point

Set the iron post, 10 ins. in the ground, mound of stone to top, brass cap mkd.

T11N R13E
 $\frac{1}{4}$
 S30|S29
 1968

from which

A pine, 14 ins. diam., bears S. 31° E., 9 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 40 lks. S. of a track road, bearing E. and W.

The sec. cor. of secs. 19, 20, 29 and 30, was re-established by record course and distance from the orig. bearing trees

A walnut, 27 ins. diam., bears N. 82° E., 88 lks. dist., mkd. R13E S20 BT.

A dead oak, 24 ins. diam., bears S. 27° E., 97 lks. dist., mkd. with a blaze and faint scribe mks.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T11N R13E
 S19|S20
 S30|S29
 1968

from which

A pine, 18 ins. diam., bears S. $22\frac{1}{2}^\circ$ E., 82 lks. dist., mkd. T11N R13E S29 BT.

Deposit broken glass in the hole around the iron post.

Cor. is on the SE. edge of a small field, about 50 lks. N. of a creek, draining westerly.

Cor. set by permission of interested party.

Remonumentation, T. 11 N., R. 13 E.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented by a sandstone, 17 x 10 x 6 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone to the N. From the cor., the remains of an original bearing tree

A dead pine stump, 24 ins. diam., bears N. 75° W., 123 lks. dist., mkd. $\frac{1}{4}$ S19 BT. (Note: record dist. 118 lks.).

At the cor. point

Set the iron post, 17 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R13E
 $\frac{1}{4}$ $\frac{S19}{S30}$
 1968

from which

A pine, 9 ins. diam., bears N. 3° W., 23 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

A pine, 8 ins. diam., bears N. 76° E., 7 lks. dist., mkd. S19 BT.

Rebuild the orig. mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 80 lks. S. of a power line bearing E. and W.

The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented by a sandstone, 24 x 10 x 8 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone to the W. From the cor., the orig. bearing trees

An oak, 12 ins. diam., bears S. 58 $\frac{1}{2}$ ° E., 23 lks. dist., mkd. with an overgrown blaze.

A cedar, 33 ins. diam., bears N. 69 $\frac{1}{2}$ ° W., 53 lks. dist., mkd. $\frac{1}{4}$ S19 BT. (Note: record tree a pine).

At the cor. point

Set the iron post, 21 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R13E
 $\frac{1}{4}$
 S19 | S20
 1968

Rebuild the orig. mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 17, 18, 19 and 20, monumented by a sandstone, 21 x 13 x 9 ins., firmly set 12 ins. in the ground, mkd. with 5 notches on E. face and 3 notches on S. face, with a mound of stone to the W. From the cor., the orig. bearing trees

Remonumentation, T. 12 N., R. 8 E.

CHAINS

An oak, 14 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., 11 lks. dist., mkd. with an overgrown blaze.

A stump hole, bears S. 57° E., 30 lks. dist.

A pine, 18 ins. diam., bears S. 48° W., 49 lks. dist., mkd. T11N R13E S19.

A dead pine, 12 ins. diam., bears N. $26\frac{1}{4}^{\circ}$ W., 19 lks. dist., mkd. T11N R13E S18 BT.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R13E
 $\frac{S18}{S19} | \frac{S17}{S20}$
 1968

Rebuild the orig. mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 1 ch. N. of a ravine, draining SE.

Township 12 North, Range 8 East, G&SR M., Arizona

The east boundary and the subdivisional lines were surveyed in 1905 by J. B. Wright.

Remonumentation, T. 12 N., R. 8 E., G&SR M., Arizona

The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, T. 12 N., Rs. 8 and 9 E., monumented by a sandstone, 17 x 10 x 5 ins., firmly set 11 ins. in the ground, mkd. with X on top and $\frac{1}{4}$ on W. face, from which the remains of an orig. bearing tree

A stump hole, with a fallen oak snag, 15 ins. diam., alongside, bears S. $38\frac{1}{2}^{\circ}$ W., 64 lks. dist.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T12N
 R8E R9E
 $\frac{1}{4}$
 $S36 | S31$
 1968

from which

A pine, 14 ins. diam., bears N. 61° E., 10 lks. dist., mkd. S31 BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is at a fence cor., from which fences bear N., S. and W.

Remonumentation, T. 12 N., R. 8 E.


CHAINS

The witness cor. of secs. 25, 30, 31 and 36, T. 12 N., Rs. 8 and 9 E., monumented by a sandstone, 22 x 12 x 8 ins. firmly set 12 ins. in the ground, mkd. with WC on top, 5 notches on N. face and 1 notch on S. face, with mound of stone to the W. From the cor., an orig. bearing tree

An oak, 12 ins. diam., bears N. 12°20' E., 43 lks. dist., mkd. with a blaze and faint scribe mks.

At the cor. point

Set the iron post, 15 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 14 ins. diam., bears S. 42° E., 13 lks. dist., mkd. T12N R9E S31 BT.

Bury the orig. cor. stone alongside the iron post.


Cor. is under a fence bearing N. and S., 50 lks. S. of a gulch, draining SW.

The 1/4 sec. cor. of secs. 25 and 30, T. 12 N., Rs. 8 and 9 E., reestablished by record course and distance from the orig. bearing tree

An oak, 14 ins. diam., bears S. 57° E., 137 lks. dist., mkd. with a blaze and faint scribe mks.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.



from which

A water pipe, 2 ins. diam., projecting 1 ft. above ground, set in cement, with a metal tag at the top, mkd. L.S., bears S. 57° E., 2 lks. dist.

A fence cor., from which fences bear N., E. and W., bears North, 1 lk. dist.

The cor. of secs. 19, 24, 25 and 30, T. 12 N., Rs. 8 and 9 E., monumented by a sandstone, 25 x 10 x 10 ins., firmly set 18 ins. in the ground, mkd. with an X on top, 4 notches on the N. face and 2 notches on the S. face, with a water pipe, 1 in. diam., set in the ground alongside, and a mound of stone to the W. From the cor., the remaining orig. bearing trees

Remonumentation, T. 12 N., R. 8 E.

CHAINS

An oak, 18 ins. diam., bears N. 80° E., 22 lks. dist., mkd. with faint scribe mks. (Note: record bearing N. 74° E.).

An oak, 10 ins. diam., bears S. 29° E., 97 lks. dist., mkd. with faint scribe mks.

A pine, 18 ins. diam., bears S. 75° W., 9 lks. dist., mkd. 12N R8E S25 BT. (Note: record bearing S. 71½° W.).

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T12N
R8E R9E
S24|S19
S25|S30
1968

Rebuild the orig. mound of stone W. of the iron post.

Bury orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 19 and 24, T. 12 N., Rs. 8 and 9 E., monumented by a sandstone, 22 x 12 x 10 ins., firmly set 14 ins. in the ground, mkd. ¼ on W. face, with a mound of stone to the W.

At the cor. point

Set the iron post, 18 ins. in the ground, brass cap mkd.

T12N
R8E R9E
¼
S24|S19
1968

from which

A cedar, 7 ins. diam., bears N. 46° W., 23 lks. dist., mkd. T12N R8E ¼ S24 BT.

Rebuild the orig. mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is on a steep S. slope, under a fence bearing N. and S., about 2½ chs. N. of a gulch, draining SE.

The cor. of secs. 25, 26, 35 and 36, monumented by a sandstone, 21 x 12 x 7 ins., firmly set 12 ins. in the ground, in a scattered mound of stone, mkd. with 1 notch on E. face and 1 notch on S. face, from which the remaining orig. bearing trees

An oak, 20 ins. diam., bears S. 89° E., 84 lks. dist., mkd. with a blaze, partly overgrown, and faint scribe mks.

An oak, 30 ins. diam., bears N. 2° W., 37 lks. dist., mkd. with an overgrown blaze. (Note: record dist. 27 lks.).

Remonumentation, T. 12 N., R. 8 E.

CHAINS

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T12N R8E
 S26 | S25
 S35 | S36
 1968

Bury the orig. cor. stone alongside the iron post.

Cor. is at the bottom edge of a steep W. slope on the N. side of a gully, draining SE., about 1 ch. E. of a wash, 15 lks. wide, 3 ft. deep, with small open field to the W.

The cor. of secs. 22, 23, 26 and 27, monumented by a sandstone, 19 x 10 x 6 ins., firmly set 7 ins. in the ground, mkd. with 2 notches on E. face and 2 notches on S. face, with mound of stone to the W. From the cor., the orig. bearing trees

An oak, 24 ins. diam., bears N. 30° E., 24 lks. dist., mkd. with an overgrown blaze. (Note: record bearing and dist., N. 24° E., 22 lks.).

A juniper, 24 ins. diam., bears S. 42° E., 31 lks. dist., mkd. T12N R8E S26 BT. (Note: record bearing S. 45° E.).

A pine, 12 ins. diam., bears S. 30° W., 27 lks. dist., mkd. T12N R8E S27 BT. (Note: record bearing and dist., S. 35° W., 29 lks.).

A stump hole, with a fallen dead oak, 12 ins. diam., alongside, bears N. 18½° E., 94 lks. dist., mkd. dimly 12 N R. (Note: record dist. 92 lks.).

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T12N R8E
 S22 | S23
 S27 | S26
 1968

Rebuild the orig. mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 1½ chs. E. of a ravine, draining northerly.

The cor. of secs. 21, 22, 27 and 28, monumented by a sandstone, 27 x 18 x 10 ins., firmly set 17 ins. in the ground, mkd. with 3 notches on E. face and 2 notches on S. face, with a mound of stone to the W.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

Remonumentation, T. 12 N., R. 8 E.

CHAINS

T12N R8E
 $\frac{S21}{S28} | \frac{S22}{S27}$
 1968

from which

A pine, 8 ins. diam., bears S. 36° E., 32 lks. dist., mkd. T12N R8E S27 BT.

No evidence found of orig. bearing trees.

Bury the orig. cor. stone alongside the iron post.

Cor. is at the bottom of a steep N. slope.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented by a sandstone, 27 x 12 x 8 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone to the N.

At the cor. point

Set the iron post, 20 ins. in the ground, mound of stone to top, brass cap mkd.

T12N R8E
 $\frac{1}{4} \frac{S22}{S27}$
 1968

from which

A pine, 9 ins. diam., bears S. 22° E., 26 lks. dist., mkd. T12N R8E S27 BT.

A pine, 6 ins. diam., bears S. 31° W., 13.5 lks. dist., mkd. X BT.

No evidence found of orig. bearing trees.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 3 chs. E. of a ravine, draining NW., and 3 lks. N. of a fence bearing E. and W.

BOOK 4897

Form 9180-8
(August 1967)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
James E. Muth	Engineering Aid
(U. S. Forest Service employee)	

10

CERTIFICATE OF SURVEY

I, Howard H. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of April, 1968, I have remonumented a portion of the cadastral survey corners in Township 11 North, Range 13 East, and Township 12 North, Range 8 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 10, 1969
(Date)

Howard H. Thomas
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JUN 17 1969

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 11 North, Range 13 East, and Township 12 North, Range 8 East, of the Gila and Salt River Meridian, Arizona,

executed by Howard H. Thomas, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 21 1971
(Date)

Clark I. Lumm
(Chief, Division of ~~Engineering~~
Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Engineering)~~