

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of a

PORTION of the SOUTH and WEST BOUNDARIES

and the

COMPLETION SURVEY

of the

SUBDIVISIONAL LINES,

TOWNSHIP 27 NORTH, RANGE 21 WEST

and the

RETRACEMENT OF THE BOUNDARIES

of

MINERAL SURVEY NO. 1103

MARIPOSA and LITTLE DAISY LODES

TOWNSHIPS 26 and 27 NORTH, RANGE 21 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Gary T. Oviatt

Cadastral Surveyor

Under special instructions dated July 11, 19 68, which provided for the surveys  
included under Group Number 488, approved July 11, 1968,  
and assignment instructions dated September 12, 19 68.

Survey commenced September 23, 19 68

Survey completed October 25, 19 68

1A

BOOK 4898

INDEX DIAGRAM

Township 27 North, Range 21 West,

7 6 34	35 5 34	27 4 27	21 3 21	15 2 14	8 1
6 7 33	33 8 32	26 9 26	20 10 20	13 11 13	12
5 18 31	31 17 30	25 16 24	19 15 19	12 14 11	13
4 19 29	30 20 29	24 21 23	18 22 18	11 23 10	24
2 30	28 29	22 28 22	17 27 16	10 26 9	25
31	32	33 1	16 34	8 35	36

Retracement of M.S. No. 1103 -- Page 36

Township 27 North, Range 21 West  
Gila and Salt River Meridian, Arizona

CHAINS

The south five miles of the east boundary and the east four miles of the south boundary were surveyed in 1915 by H. G. Bardsley. A portion of the subdivisional lines were surveyed in 1915 by Bardsley and Durnford. The north one mile of the east boundary, the west two miles of the south boundary, the west and north boundaries and a portion of the subdivisional lines were surveyed in 1955 by D. E. Harding.

The following notes are those of a dependent resurvey of a portion of the south and west boundaries and the completion survey of the subdivisional lines, Township 27 North, Range 21 West and a retracement of the boundaries of Mineral Survey No. 1103, Mariposa and Little Daisy lodes, Tps. 26 and 27 North, Range 21 West, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the Specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 11, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township as determined by traverse from USC&GS Triangulation Station POPE, located in the southeast portion of section 3, is: Latitude 35°40'37" North and Longitude 114°28'06" West.

The mean magnetic declination was found to be: 15½° East.

Dependent Resurvey, Portion of the South Boundary  
Township 27 North, Range 21 West

Reestablishment of the Survey executed by  
H. G. Bardsley in 1915

Beginning at the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented by an iron post 3 in. diam., firmly set in a mound of stone, brass cap mkd.

T27N R21W  
S33 | S34  
S 4 | S 3  
T26N  
1915

N. 89°58' W., bet. secs. 4 and 33.

Over mountainous land; asc. SE. slope.

7.30 Top of ridge, bears N. and S. 20° W.; desc. SW. slope.

20.82 Intersect line 6-7, Mineral Survey No. 1103, Little Daisy lode, at a point from which Cor. No. 7 bears S. 2°40' E., 1.08 chs. dist., hereinafter described. Cor. No. 6 bears N. 2°40' W., 6.067 chs. dist., hereinafter described.

Dep. Res., Portion South Boundary, T. 27 N., R. 21 W.

CHAINS

- 31.00 Graded road on a curve, bears N. 10° E. and S. 25° E.; enter moderate rolling land.
- 40.10 The ½ sec. cor. of secs. 4 and 33, monumented by an iron post 1 in. diam., firmly set in a mound of stone, brass cap mkd.

½  
S33  
 S 4  
 1915

from which

Cor. No. 1, Mineral Survey No. 1103 Mariposa lode, bears S. 12°28'30" E., 4.528 chs. dist., hereinafter described.

---

S. 89°46' W., beginning new measurement.

Over rolling land; asc. E. slope.

- 10.10 Top of spur, slopes N. 10° W.; desc. W. slope.
- 19.60 Draw, drains N. 20° W.
- 21.98 Intersect line 2-3, Mineral Survey No. 1103 Mariposa lode, at a point from which Cor. No. 2 bears S. 5°12' E., 6.248 chs. dist., hereinafter described. Cor. No. 3 bears N. 5°12' W., 2.85 chs. dist., hereinafter described.
- 24.30 Graded road, bears N. 30° E. and S. 30° W.
- 39.91 The cor. of secs. 4, 5, 32 and 33, monumented by an iron post 3 ins. diam., projecting 20 ins. above ground, set in a collar of stone, brass cap mkd.

T27N R21W  
S32 | S33  
 S 5 | S 4  
 T26N  
 1915

from which

Cor. No. 3, mineral Survey No. 1103 Mariposa lode, bears N. 80°42' E., 17.92 chs. dist.

Land, mountainous to rolling.  
 Soil, rocky and sandy loam.  
 No timber; Undergrowth, creosote bush and cacti.

---

Dependent Resurvey, Portion of the West Boundary  
 Township 27 North, Range 21 West

---

Reestablishment of the Survey executed by  
 D. E. Harding in 1955

---

This line was fully retraced and found defective. In the following resurvey, to facilitate establishment of the subdivisional lines, new corners are set at regular

Dep. Res., Portion West Boundary, T. 27 N., R. 21 W.

CHAINS	
	<p>intervals of 40.00 chains in latitudinal dist. from the cor. of sections 25, 30, 31 and 36 to the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 12. The original corners are remarked to function as angle points only.</p> <p>From the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post <math>2\frac{1}{2}</math> ins. diam., projecting 6 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R22W R21W <u>S25   S30</u> <u>S36   S31</u> 1955</p> <p>N. <math>1^{\circ}31'</math> W., bet. secs. 25 and 30.</p> <p>Over rolling land, through moderate undergrowth.</p>
5.30	Wash, 20 lks. wide, 1 ft. deep, drains SW.
25.00	Wash, 20 lks. wide, 1 ft. deep, drains SW.
31.70	Top of ridge, bears E. and W.
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 30.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T27N R22W R21W $\frac{1}{4}$ <u>S25   S30</u> 1968
40.60	Raise a mound of stone W. of the corner.
	The original $\frac{1}{4}$ sec. cor. of secs. 25 and 30, monumented by an iron post 1 in. diam., projecting 18 ins. above the ground, mound of stone W., brass cap mkd. $\frac{1}{4}$ S25 S30 1955. This monument now functions as an angle point only, brass cap remarked:
	S25   S30 A P 1968 1955
	-----
	N. $1^{\circ}30'$ E., beginning new measurement.
	Over rolling land, through moderate undergrowth.
3.00	Wash, 50 lks. wide, 1 ft. deep, drains SW.
28.00	Spur, slopes N. $80^{\circ}$ E.
39.42	Point for the cor. of secs. 19, 24, 25 and 30.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	T27N R22W R21W <u>S24   S19</u> <u>S25   S30</u> 1968

Dep. Res., Portion West Boundary, T. 27 N., R. 21 W.

CHAINS	
40.03	<p>The cor. is located on a spur sloping E.                      N. 1°30' E., bet. secs. 19 and 24, continuing measurement.</p> <p>The original cor. of secs. 19, 24, 25 and 30, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd. T27N R21W R22W S19 S24 S25 S30 1955. This monument now functions as an angle point only, brass cap remarked:</p> <p style="text-align: center;">T27N                      R22W R21W                      S24   S19                      A P                      1968                      1955</p> <p>Land, rolling.                      Soil, rocky and sandy clay loam.                      No timber; Undergrowth, creosote bush and cacti.</p>
7.40	<p>N. 0°04' W., bet. secs. 19 and 24; beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 100 lks. wide, 2 ft. deep, drains S. 20° E.</p>
13.70	<p>Draw, drains S. 60° W.</p>
25.50	<p>Spur, slopes W.</p>
39.39	<p>Point for the ¼ sec. cor. of secs. 19 and 24.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T27N                      R22W R21W                      ¼                      S24   S19                      1968</p>
39.99	<p>The original ¼ sec. cor. of secs. 19 and 24, monumented by an iron post 1 in. diam., firmly set in a mound of stone, brass cap mkd. ¼ S19 S24 1955. This monument now functions as an angle point only, brass cap remarked:</p> <p style="text-align: center;">A P                      S24   S19                      1968                      1955</p>
10.90	<p>N. 0°04' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 30 lks. wide, 1 ft. deep, drains S. 50° W.; asc. S. slope.</p>
39.40	<p>Point for the cor. of secs. 13, 18, 19 and 24.</p>

Dep. Res., Portion West Boundary, T: 27 N., R. 21 W.

CHAINS		
39.95	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T27N R22W R21W S13   S18 S24   S19 1968</p> <p>N. 0°04' E., bet. secs. 13 and 18, continuing measurement.</p> <p>The original cor. of secs. 13, 18, 19 and 24, monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, brass cap mkd. T27N R21W R22W S13 S18 S19 S24 1955; mound of stone W. This monument now functions as an angle point only, brass cap remarked:</p> <p style="text-align: center;">T27N R22W R21W A P S13   S18 1968 1955</p> <p>Land, rolling. Soil, rocky and sandy clay loam. No timber; undergrowth, creosote bush and cacti and grass</p>	
18.60	<p>N. 0°13' W., bet. secs. 13 and 18, beginning new measurement.</p> <p>Over mountainous land, through moderate undergrowth.</p> <p>Spur, slopes SE.</p>	
36.20	<p>Top of ridge, bears N. 25° E. and SW.; desc. N. slope.</p>	
39.45	<p>Point for the ¼ sec. cor. of secs. 13 and 18.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T27N R22W R21W ¼ S13   S18 1968</p>	
39.91	<p>The original ¼ sec. cor. of secs. 13 and 18, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, 24 ins. high, brass cap mkd. ¼ S13 S18 1955. This monument now functions as an angle point only, brass cap remarked:</p> <p style="text-align: center;">A P S13   S18 1968 1955</p>	
13.00	<p>N. 0°03' E., beginning new measurement.</p> <p>Over mountainous land, through moderate undergrowth.</p> <p>Wash in bottom of El Dorado Canyon, 40 lks. wide, 2 ft. deep, drains S. 80° W.; graded road, bears same as wash;</p>	

Dep. Res., Portion West Boundary, T. 27 N., R. 21 W.

CHAINS	
	asc. over broken S. slope.
36.60	Draw, drains SW.
39.54	Point for the cor. of secs. 7, 12, 13 and 18.  Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.  <div style="text-align: center;">                     T27N                      R22W R21W                      S12   S 7                      S13   S18                      1968                 </div>
	from which  U.S. M. M. No. 2695, bears N. 45°06' E., 7.50 chs. dist., monumented by a granite stone, 18 x 18 x 8 ins. above the ground, mkd. X on top and USMM No. 2695 on E. face, mound of stone W.  N. 0°03' E., bet. secs. 7 and 12, continuing measurement.
39.95	The original cor. of secs. 7, 12, 13 and 18, monumented by an iron post 2½ ins. diam., projecting 12 ins. above the ground, brass cap mkd. T27N R21W R22W S7 S12 S13 S18 1955, with a mound of stone W. This monument now functions as an angle point only, brass cap remarked:  <div style="text-align: center;">                     T27N                      R22W R21W                      A P                      S12   S 7                      1968                      1955                 </div>
	Land, mountainous. Soil, rocky and sandy clay loam. No timber; undergrowth, creosote bush and cacti.
	N. 1°34' W., bet. secs. 7 and 12, beginning new measurement.  Over mountainous land, through moderate undergrowth.
25.00	Spur, slopes W.; desc. N. slope.
39.60	Point for the ¼ sec. cor. of secs. 7 and 12.  Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.  <div style="text-align: center;">                     T27N                      R22W R21W                      ¼                      S12   S 7                      1968                 </div>
40.11	The original ¼ sec. cor. of secs. 7 and 12, monumented by an iron post 2½ ins. diam., projecting 10 ins. above the ground, brass cap mkd. ¼ S7 S12 1955, mound of stone W. This monument now functions as an angle point only, brass cap remarked:

Dep. Res., Portion West Boundary, T. 27 N., R. 21 W.

CHAINS	
	A P S12   S 7 1968 1955 <hr/>
	N. 1°26' E., beginning new measurement. Over mountainous land, through moderate undergrowth.
1.00	Wash, 20 lks. wide, 1 ft. deep, drains S. 60° W.; asc. broken S. slope.
11.00	Top of ridge, bears E. and W.; desc. N. slope.
33.30	Wash, 10 lks. wide, 1 ft. deep, drains W.; asc. S. slope.
39.62	The cor. of secs. 1, 6, 7 and 12, monumented by an iron post 2½ ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.
	T27N R22W R21W S 1   S 6 S12   S 7 1955
	Land, mountainous. Soil, rocky clay and sandy loam. No timber; Undergrowth, creosote bush, cacti and bunch grass.
	N. 0°13' W., bet. secs. 1 and 6.
4.80	Top of ridge, divide between Detrital Valley and Colorado River, bears S. 80° E. and N. 80° W.; desc. N. slope.
39.92	The ¼ sec. cor. of secs. 1 and 6, monumented by an iron post 2½ ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.
	¼ S 1   S 6 1955 <hr/>
	N. 0°07' W., beginning new measurement. Over rolling land, through moderate undergrowth.
39.96	The cor. of Tps. 27 and 28 N., Rs. 21 and 22 W., monumented by an iron post 2½ ins. diam., firmly set in a collar of stone, brass cap mkd.
	T28N R22W R21W S36   S31 S 1   S 6 T27N 1955

Dep. Res., Portion West Boundary, T. 27 N., R. 21 W.

CHAINS	
	<p>Land, mountainous to moderate rolling. Soil, rocky and sandy loam. No timber; Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>Completion Survey of the Subdivisional Lines Township 27 North, Range 21 West</p>
	<p>From the cor. of secs. 1, 2, 11 and 12, monumented by an iron post 2 ins. diam., projecting 20 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W S 2   S 1 S11   S12 1915</p> <p>N. 0°01' E., bet. secs. 1 and 2.</p> <p>Over nearly level land, through moderate undergrowth.</p>
40.00	<p>Point for the ½ sec. cor. of secs. 1 and 2.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W ½ S 2   S 1 1968</p> <p>Set a wooden post 4 x 4 ins. square, 4 ft. long, alongside the iron post.</p>
55.80	<p>Graded road, bears E. and W.</p>
69.00	<p>Enter Detrital Wash area, bears S. 5° E. and N. 5° W.; drains N. 5° W.</p>
79.87	<p>True point for the cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., from which the witness cor., bears S. 89°56' W., 1.00 ch. dist., monumented by an iron post 2½ ins. diam., projecting 4 ins. above ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W S35   S36 W S 2   S 1 C T27N 1955</p> <p>The cor. is located on the W. bank of Detrital Wash.</p> <p>Land, nearly level. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>the Tp., monumented by an iron post 3 ins. diam., projecting 18 ins. above the ground, with a small mound of earth W. and remains of pits to the NE., SE., and SW., brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W  <math>\frac{S34}{S3}</math>   <math>\frac{S35}{S2}</math>                      T26N                      1915</p>
	<p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
2.90	Wash, 10 lks. wide, 1 ft. deep, drains NE.
30.00	Track road, bears E. and W.
37.80	Wash, 20 lks. wide, 1 ft. deep, drains E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math>  <math>\frac{S34}{S34}</math>   <math>\frac{S35}{S35}</math>                      1968</p>
	Raise a mound of stone W. of the corner.
58.40	Track road, bears NE. and SW.
66.80	Graded road, bears N. 70° E. and S. 70° W.
78.80	Graded road, bears S. 40° E. and N. 40° W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T27N R21W  <math>\frac{S27}{S34}</math>   <math>\frac{S26}{S35}</math>                      1968</p>
	Raise a mound of stone W. of the corner.
	<p>Land, gently rolling.                      Soil, sandy and gravelly clay loam.                      No timber; Undergrowth, creosote bush and cacti.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36, monumented by an iron post 2 ins. diam., projecting 20 ins. above the ground, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W  <math>\frac{S26}{S35}</math>   <math>\frac{S25}{S36}</math>                      1915</p>
	<p>N. 89°56' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through moderate undergrowth.</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35. Set the iron post 22 ins. in the ground, brass cap mkd.  T27N R21W $\frac{1}{4}$ $\frac{S26}{S35}$ 1968  Deposit glass at the base of the iron post.
56.80	Graded road, bears N. 60° E. and S. 60° W.
64.10	Track road, bears S. 30° E. and N. 30° W.
80.00	The cor. of secs. 26, 27, 34 and 35.  Land, gently rolling. Soil, sandy and gravelly loam. No timber; Undergrowth, creosote bush and cacti.
<hr/>	
	N. 0°01' W., bet. secs. 26 and 27.  Over gently rolling land, through moderate undergrowth.
17.80	Track road, bears SE. and NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27. Set the iron post 22 ins. in the ground, brass cap mkd.  T27N R21W $\frac{1}{4}$ $\frac{S27}{S26}$ 1968  Deposit glass at the base of the iron post.
58.00	Wash, 80 lks. wide, 2 ft. deep, drains E.
71.10	Graded road, bears N. 30° E. and S. 30° W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27. Set the iron post 20 ins. in the ground in a collar of stones, brass cap mkd.  T27N R21W $\frac{S22}{S27}$ $\frac{S23}{S26}$ 1968  Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti and grass.
<hr/>	
	From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., projecting 18 ins. above the ground, brass cap mkd.  T27N R21W $\frac{S23}{S26}$ $\frac{S24}{S25}$ 1915

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
39.94	<p>S. 89°51' W., bet. secs. 23 and 26.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 23 and 26.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W ¼ <u>S23</u> S26 1968</p>
	<p>Set a mesquite post 2½ ins. diam., 3½ ft. long, alongside the iron post.</p>
74.70	<p>Graded road, bears N. 30° E. and S. 30° W.</p>
79.88	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
40.00	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 22 and 23.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W ¼ <u>S22</u>   <u>S23</u> 1968</p>
	<p>Set a wooden post 2 x 2 ins. square, 6 ft. long, alongside the iron post.</p>
80.00	<p>Point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W <u>S15</u>   <u>S14</u> <u>S22</u>   <u>S23</u> 1968</p>
	<p>Set a wooden post 4 x 4 ins. square, 4 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24, monumented by an iron post 2 ins. diam., projecting 16 ins. above the ground, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W <u>S14</u>   <u>S13</u> <u>S23</u>   <u>S24</u> 1915</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>S. 89°47' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>26.60 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.</p> <p>39.89 Point for the ¼ sec. cor. of secs. 14 and 23.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R21W</p> <p>¼ <u>S14</u></p> <p>S23</p> <p>1968</p> </div> <p>Set a wooden post 2 x 4 ins. square, 4½ ft. long, alongside the iron post.</p> <p>79.78 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, gently rolling. Soil, gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<hr/> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>12.00 Wash, 50 lks. wide, 2 ft. deep, drains N. 80° E.</p> <p>38.80 Wash, 20 lks. wide, 2 ft. deep, drains N. 55° E.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 14 and 15.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R21W</p> <p>¼</p> <p>S15   S14</p> <p>1968</p> </div> <p>Set a wooden post 2 x 4 ins. square, 3½ ft. long, alongside the iron post.</p> <p>51.00 Wash, 30 lks. wide, 1 ft. deep, drains N. 70° E.</p> <p>57.50 Track road, bears S. 35° E. and N. 35° W.</p> <p>64.00 Track road, bears S. 70° E. and N. 70° W.</p> <p>77.10 Track road, bears N. 80° E. and S. 80° W.</p> <p>80.00 Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T27N R21W</p> <p><u>S10</u>   <u>S11</u></p> <p><u>S15</u>   <u>S14</u></p> <p>1968</p> </div> <p>Set a wooden post 2 x 3 ins. square, 7 ft. long, alongside the iron post.</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>Land, nearly level. Soil, gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14, monumented by an iron post 2 ins. diam., projecting 16 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W S11 S12 S14 S13 1915</p> <p>S. 89°44' W., bet. secs. 11 and 14.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>2.80 Wash, 20 lks. wide, 2 ft. deep, drains N. 60° E.</p> <p>27.00 Telephone line, bears S. 23°47' E. and N. 23°47' W.</p> <p>27.06 Right-of-way fence, bears S. 23°47' E. and N. 23°47' W.</p> <p>30.35 U.S. Highway No. 93, bears S. 23°47' E. and N. 23°47' W.</p> <p>33.64 Right-of-way fence, parallels Highway.</p> <p>35.10 Power line, bears S. 23°37' E. and N. 23°37' W.</p> <p>39.82 Point for the ¼ sec. cor. of secs. 11 and 14.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W ¼ S11 S14 1968</p> <p>Set a wooden post 2 x 2 ins. square, 5 ft. long, alongside the iron post.</p> <p>68.40 Wash, 20 lks. wide, 1 ft. deep, drains N. 60° E.</p> <p>74.10 Track road, bears NE. and SW.</p> <p>79.64 The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, nearly level. Soil, gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Ascend S. slope.</p> <p>7.00 Low ridge, bears E. and W.; desc. N. slope.</p> <p>23.00 Bottom of desc.; asc. S. slope.</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
37.40	Spur, slopes NW.; desc. N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.  Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.  <div style="text-align: center;">                     T27N R21W  <math>\frac{1}{4}</math>                      S10 S11                      1968                 </div>
	Set a wooden post 2 x 4 ins. square, 3 ft. long, alongside the iron post.  Enter nearly level land, bears E. and W.
40.90	Wash, 10 lks. wide, 1 ft. deep, drains E.
79.50	Wash, 30 lks. wide, 1 ft. deep, drains E.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.  Set the iron post 22 ins. in the ground, brass cap mkd.  <div style="text-align: center;">                     T27N R21W  <u>S 3   S 2</u>                      S10   S11                      1968                 </div>
	from which  <div style="text-align: center;">                     Triangulation Station POPE, bears N. 18°11' W.,                      20.23 chs. dist., monumented by a standard disk,                      3 ins. diam., set in concrete in a drill hole, mkd.                      POPE 1950.                 </div>
	Set a wooden post 4 x 4 ins. square, 4 ft. long, alongside the iron post.  Land, rolling to nearly level. Soil, rocky and sandy clay loam. No timber; Undergrowth, creosote bush and cacti.
	From the cor. of secs. 1, 2, 11 and 12.  S. 89°40' W., bet. secs. 2 and 11.  Over nearly level land, through moderate undergrowth.
9.70	Wash, 20 lks. wide, 2 ft. deep, drains NE.
39.75	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.  Set the iron post 22 ins. in the ground, brass cap mkd.  <div style="text-align: center;">                     T27N R21W  <math>\frac{1}{4}</math> <u>S 2</u>                      S11                      1968                 </div>
	Set a metal pipe, 2 ins. diam., 6 ft. long, alongside the iron post.

## Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
60.70	Wash, 20 lks. wide, 2 ft. deep, drains N. 60° E.
62.10	Telephone line, bears S. 23°47' E. and N. 23°47' W.
62.13	Right-of-way fence, bears S. 23°47' E. and N. 25°30' W.
65.37	U.S. Highway No. 93, bears S. 23°47' E. and N. 23°47' W.
68.75	Right-of-way fence, bears S. 23°47' E. and N. 23°37' W.
69.90	Power line, bears S. 23°37' E. and N. 23°29' W.
79.50	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, nearly level. Soil, sandy and rocky clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	N. 0°17' W., bet. secs. 2 and 3.
	Over nearly level land, through moderate undergrowth.
14.00	Graded road, bears N. 70° E. and S. 70° W.
17.40	Wash, 50 lks. wide, 1 ft. deep, drains E.
22.40	Power line, bears S. 23°29' E. and N. 23°29' W.
24.94	Right-of-way fence, bears S. 23°37' E. and N. 23°47' W.
32.52	U.S. Highway No. 93, bears S. 23°47' E. and N. 23°47' W.
36.14	Right-of-way fence, bears S. 25°30' E. and N. 23°47' W.
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 3.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W <math>\frac{1}{4}</math> S 3   S 2 1968</p>
	Set a wooden post 4 x 4 ins. square, 4 ft. long, alongside the iron post.
	The cor. is located under a telephone line, parallels Highway.
67.40	Wash, 20 lks. wide, 2 ft. deep, drains NE.
80.18	<p>The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., monumented by an iron post 2<math>\frac{1}{2}</math> ins. diam., firmly set in a mound of stone, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W S34   S35 S 3   S 2 T27N 1955</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>Land, nearly level. Soil, rocky and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp. N. 0°02' W., bet. secs. 33 and 34. Over mountainous land, through moderate undergrowth. Ascend steep S. slope.</p>
0.70	Top of ridge, bears NE. and SW.; desc. N. slope.
17.00	Spur, slopes N. 40° E.
25.00	Bottom of desc.; thence across level land.
31.40	Graded road, bears N. 65° E. and S. 65° W.
40.00	Point for the 1/2 sec. cor. of secs. 33 and 34. Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T27N R21W 1/2 S33 S34 1968</p>
	Set a wooden post 4 x 4 ins. square, 5 ft. long, alongside the iron post and raise a mound of stone W. of the corner.
51.70	Wash, 40 lks. wide, 2 ft. deep, drains S. 70° E.; asc. SE. slope of high rocky ridge.
63.00	Low saddle, bears E. and W.
80.00	Point for the cor. of secs. 27, 28, 33 and 34. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T27N R21W S28 S27 S33 S34 1968</p>
	The cor. is located on a spur sloping E.
	Land, mountainous. Soil, rocky and gravelly clay loam. No timber; Undergrowth, creosote bush and cacti.
	<p>From the cor. of secs. 26, 27, 34 and 35. S. 89°50' W., bet. secs. 27 and 34. Over gently rolling land, through moderate undergrowth.</p>
1.10	Graded road, bears S. 40° E. and N. 40° W.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
9.80	Wash, 5 lks. wide, 1 ft. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T27N R21W $\frac{1}{4}$ $\frac{S27}{S34}$ 1968
	Raise a mound of stone N. of the corner.
56.00	Base of mountain, bears S. 25° E. and N. 25° W.; asc. steep E. slope.
80.00	The cor. of secs. 27, 28, 33 and 34.
	Land, nearly level to mountainous. Soil, gravelly and rocky loam. No timber; Undergrowth, creosote bush and cacti.
	N. 0°02' W., bet. secs. 27 and 28.
	Over mountainous land.
12.80	Saddle, bears E. and W.; desc. NE. slope.
31.10	Wash, 70 lks. wide, 2 ft. deep, drains E.; asc. SE. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.
	T27N R21W $\frac{1}{4}$ S28   S27 1968
45.00	Spur, slopes SE.; desc. NE. slope.
59.50	Leave mountainous land, bears S. 25° E. and N. 25° W.; enter gently rolling land, covered with moderate undergrowth.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.
	T27N R21W $\frac{S21}{S28}$   $\frac{S22}{S27}$ 1968
	Land, mountainous to gently rolling. Soil, rocky and gravelly loam. No timber; Undergrowth, creosote bush and cacti.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°50' W., bet. secs. 22 and 27.</p> <p>Over nearly level land, through moderate undergrowth.</p>
39.98	<p>Point for the ¼ sec. cor. of secs. 22 and 27.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math> <math>\frac{S22}{S27}</math>                      1968</p>
	<p>Raise a mound of stone N. of the corner.</p>
55.80	<p>Track road, bears SE. and NW.</p>
65.90	<p>Graded road, bears S. 40° E. and N. 40° W., 7.00 chs., thence N. 50° W.</p>
79.96	<p>The cor. of secs. 21, 22, 27 and 28.</p>
	<p>Land, nearly level.                      Soil, gravelly clay loam.                      No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°02' W., bet. secs. 21 and 22.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
12.40	<p>Graded road, bears S. 50° E. and N. 50° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 21 and 22.</p>
	<p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math> S21   S22                      1968</p>
54.30	<p>Wash, 100 lks. wide, 2 ft. deep, drains N. 80° E.</p>
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p>
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math> S16   S15                      S21   S22                      1968</p>
	<p>Land, gently rolling.                      Soil, gravelly clay loam.                      No timber; Undergrowth, creosote bush, cacti and grass.</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°48' W., bet. secs. 15 and 22.</p> <p>Over nearly level land, through moderate undergrowth.</p>
36.60	Wash, 20 lks. wide, 2 ft. deep, drains NE.
39.97	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math> <math>\frac{S15}{S22}</math>                      1968</p>
	<p>Set a wooden post 2 x 2 ins. square, 5 ft. long, alongside the iron post.</p>
43.60	Wash, 30 lks. wide, 2 ft. deep, drains N. 60° E.
77.80	Wash, 10 lks. wide, 1 ft. deep, drains SE.
79.94	The cor. of secs. 15, 16, 21 and 22.
	<p>Land, nearly level.</p> <p>Soil, gravelly and sandy loam.</p> <p>No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land, through moderate undergrowth.</p>
0.90	Ravine, 4 ft. deep, 15 lks. wide, drains E.
10.60	Wash, 40 lks. wide, 2 ft. deep, drains E.; asc. S. slope.
22.60	Saddle, bears NE. and SW.; desc. N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16.
	<p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math>                      S16 S15                      1968</p>
59.50	Spur, slopes W.; continue descent.
79.10	Track road, bears N. 25° E. and SW.
80.00	Point for the cor. of secs. 9, 10, 15 and 16.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W                      S 9 S10                      S16 S15                      1968</p>
	<p>Raise a mound of stone W. of the corner.</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>Land, rolling. Soil, rocky and gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15. S. 89°46' W., bet. secs. 10 and 15. Over rolling land, through moderate undergrowth.</p>
10.70	Track road, bears N. and S.
37.60	Track road, bears S. 65° E. and N. 65° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.  Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T27N R21W <math>\frac{1}{4}</math> <math>\frac{S10}{S15}</math> 1968</p>
74.90	Track road, bears N. and S.
79.60	Track road, bears N. 25° E. and S. 25° W.
80.00	The cor. of secs. 9, 10, 15 and 16.  Land, rolling. Soil, rocky and gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.
	<hr/> <p>N. 0°02' W., bet. secs. 9 and 10. Over rolling land, through moderate undergrowth. Ascend S. slope.</p>
29.90	Spur, slopes NW.; desc. N. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.  Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
	<p>T27N R21W <math>\frac{1}{4}</math> S 9   S10 1968</p>
66.00	Wash, 30 lks. wide, 1 ft. deep, drains NE.
71.00	Track road, bears N. 10° E. and S. 30° W.
80.00	Point for the cor. of secs. 3, 4, 9 and 10.  Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T27N R21W S 4   S 3 S 9   S10 1968</p>

## Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 89°46' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through moderate undergrowth.</p>
36.50	Wash, 20 lks. wide, 2 ft. deep, drains NE.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T27N R21W $\frac{1}{4}$ $\frac{S 3}{S10}$ 1968
	Set a wooden post 4 x 4 ins. square, 4 ft. long, alongside the iron post.
78.70	Track road, bears N. and S.
80.00	The cor. of secs. 3, 4, 9 and 10.
	<p>Land, rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>N. 0°17' W., bet. secs. 3 and 4.</p> <p>Over rolling land, through moderate undergrowth.</p>
1.90	Track road, bears SE. and NW.
3.30	Wash, 100 lks. wide, 1 ft. deep, drains E.
3.90	Track road, bears E. and W.
5.50	Graded road, bears N. 80° E. and S. 80° W.
15.10	Wash, 25 lks. wide, 1 ft. deep, drains NE.; asc. rocky S. slope.
20.60	Top of rocky knoll; desc. N. slope.
37.50	Wash, 120 lks. wide, 1 ft. deep, drains NW.; asc. S. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
	Set the iron post over an X chiseled in solid rock, mound of stone to top, brass cap mkd.
	T27N R21W $\frac{1}{4}$ S 4   S 3 1968

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
43.90	Top of rock out-cropping, slopes W.; desc. N. slope.
80.36	The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 10 ins. above the ground, brass cap mkd.
	<p style="text-align: center;">T28N R21W  <u>S33 S34</u>  S 4 S 3  T27N  1955</p>
	<p>Land, rolling.  Soil, gravelly and rocky loam.  No timber; Undergrowth, creosote bush, cacti and grass.</p>
<hr/>	
	From the cor. of secs. 27, 28, 33 and 34.
	N. 89°59' W., bet. secs. 28 and 33.
	Over mountainous land.
4.40	Top of ridge, bears S. 25° E. and N. 25° W.; desc. SW. slope.
23.40	Wash, 30 lks. wide, 1 ft. deep, drains SE.; asc. gentle E. slope.
40.04	Point for the ¼ sec. cor. of secs. 28 and 33.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T27N R21W  ¼ <u>S28</u>  S33  1968</p>
56.30	Spur, slopes S. 25° E.
66.50	Ravine, drains SE.
72.00	Ridge, divide between Detrital Valley and Colorado River, bears N. 30° E. and S. 30° W.; desc. W. slope.
80.08	The cor. of secs. 28, 29, 32 and 33, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.
	<p style="text-align: center;">T27N R21W  <u>S29 S28</u>  S32 S33  1955</p>
	<p>Land, mountainous.  Soil, rocky loam.  No timber; Undergrowth, creosote bush and cacti.</p>
<hr/>	
	N. 0°03' W., bet. secs. 28 and 29.
	Over mountainous land, through moderate undergrowth.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
8.10	Ravine, drains W.
15.60	Spur, slopes NW.
20.40	Ravine, drains NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
	Set the iron post 8 ins. in the ground over a X chiseled on solid rock, mound of stone to top, brass cap mkd.
	T27N R21W $\frac{1}{4}$ S29 S28 1968
52.00	Wash, 10 lks. wide, 3 ft. deep, drains NW.
60.00	Leave mountainous land; enter rolling land, bears E. and W.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T27N R21W S20 S21 S29 S28 1968
	Set a wooden post 4 x 4 ins. square, 4 ft. long, alongside the iron post.
	Land, mountainous to rolling. Soil, rocky and gravelly loam. No timber; Undergrowth, creosote and cacti.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 89°58' W., bet. secs. 21 and 28.
	Over rolling land, through moderate undergrowth.
15.00	Ravine, drains NE.
17.50	Base of mountain, bears S. 25° E. and N. 25° W.; asc. NE. slope.
32.80	Spur, slopes N.; desc. NW. slope.
40.03	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T27N R21W $\frac{1}{4}$ $\frac{S21}{S28}$ 1968
49.90	Track road at base of mountain, bears N. and S.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
71.50	Track road, bears SE. and NW.
77.30	Wash, 20 lks. wide, 6 ins. deep, drains N.
80.06	The cor. of secs. 20, 21, 28 and 29.
	Land, mountainous and rolling. Soil, rocky and gravelly loam. No timber; Undergrowth, creosote bush and cacti.
	N. 0°03' W., bet. secs. 20 and 21.
	Over gently rolling land, through moderate undergrowth.
11.00	Graded road, bears N. 50° E. and S. 50° W.
33.60	Wash, 20 lks. wide, 1 ft. deep, drains E.
40.00	Point for the ¼ sec. cor. of secs. 20 and 21.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	T27N R21W ¼ S20 S21 1968
44.00	Wash, 20 lks. wide, 1 ft. deep, drains SE.
54.30	Draw, drains E.
68.00	Track road, bears S. 80° E. and N. 80° W.
80.00	Point for the cor. of secs. 16, 17, 20 and 21.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T27N R21W S17 S16 S20 S21 1968
	Raise a mound of stone W. of the corner.
	Land, rolling. Soil, gravelly and sandy loam. No timber; Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 15, 16, 21 and 22.
	N. 89°59' W., bet. secs. 16 and 21.
	Over rolling land, through moderate undergrowth.
9.10	Wash, 30 lks. wide, 1 ft. deep, drains S. 10° E.
30.10	Spur, slopes S. 30° E.
40.02	Point for the ¼ sec. cor. of secs. 16 and 21.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math> <math>\frac{S16}{S21}</math>                      1968</p>
77.20	Wash, 20 lks. wide, 1 ft. deep, drains S. 25° E.
77.50	Graded road, bears S. 25° E. and N. 25° W.
80.04	The cor. of secs. 16, 17, 20 and 21.
	<p>Land, rolling.                      Soil, gravelly and sandy loam.                      No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°03' W., bet. secs. 16 and 17.</p> <p>Over rolling land, through moderate undergrowth.</p>
5.40	Graded road, bears S. 25° E. and N. 25° W.
8.20	Wash, 100 lks. wide, 3 ft. deep, drains E.
16.40	Track road, bears N. 30° E. and S. 30° W.
18.50	Wash, 50 lks. wide, 2 ft. deep, drains SW.
27.20	Wash, 15 lks. wide, 1 ft. deep, drains SW.
38.30	Ravine, drains SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W  <math>\frac{1}{2}</math>                      S17   S16                      1968</p>
	Raise a mound of stone W. of the corner.
41.40	Base of mountain, bears E. and W.; asc. steep S. slope.
54.00	Spur, slopes SW.
59.80	Track road, bears N. 80° E. and S. 80° W., along a spur, sloping S. 80° W.; desc. NW. slope.
67.00	Ravine, drains W.
80.00	Point for the cor. of secs. 8, 9, 16 and 17.
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T27N R21W                      S 8   S 9                      S17   S16                      1968</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
29.50	Land, rolling to mountainous. Soil, gravelly and rocky loam. No timber; Undergrowth, creosote bush and cacti.
31.50	From the cor. of secs. 9, 10, 15 and 16. N. 89°59' W., bet. secs. 9 and 16. Over rolling land, through moderate undergrowth.
40.03	Track road, bears N. and S. Wash, 30 lks. wide, 1 ft. deep, drains N. 15° E. Point for the ¼ sec. cor. of secs. 9 and 16. Set the iron post 22 ins. in the ground, brass cap mkd.
60.40	<div style="text-align: center;">                         T27N R21W                          ¼ <math>\frac{S\ 9}{S16}</math>                          1968                     </div> Raise a mound of stone N. of the corner. Ascend steep E. slope.
69.00	Spur, slopes NE. Draw, drains N.
72.50	High spur, sloping N. 10° E.; desc. NW. slope.
80.06	The cor. of secs. 8, 9, 16 and 17. Land, rolling to mountainous. Soil, gravelly and rocky loam. No timber; Undergrowth, creosote bush and cacti.
11.10	N. 0°03' W., bet. secs. 8 and 9. Over mountainous land. Wash, 140 lks. wide, 3 ft. deep, drains N. 80° E.
36.40	Ravine, drains NE.
40.00	Point for the ¼ sec. cor. of secs. 8 and 9. Set the iron post 20 ins. in the ground, brass cap mkd.
	<div style="text-align: center;">                         T27N R21W                          ¼                          S 8   S 9                          1968                     </div> from which Cor. No. 4, Mineral Survey No. 2694 Chicago lode, bears S. 22°57' W., 8.98 chs. dist., monumented by a malpais stone, 7 x 10 x 12 ins. above the ground,

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	<p>mkd. 4 2694 C and + on top, from which a bearing object, a rock in place, bears S. 64°35' E., 11 lks. dist., mkd. BR 4 2694 +.</p>
	<p>Raise a mound of stone W. of the corner.</p>
59.90	<p>Wash, 10 lks. wide, 2 ft. deep, drains E.; enter rolling land, bears SE. and NW.</p>
71.10	<p>Graded road, bears E. and W.</p>
80.00	<p>Point for the cor. of secs. 4, 5, 8 and 9.</p>
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W  <math>\frac{S\ 5}{S\ 8}   \frac{S\ 4}{S\ 9}</math>                      1968</p>
	<p>Land, mountainous to rolling.                      Soil, rocky and gravelly loam.                      No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p>
	<p>N. 89°58' W., bet. secs. 4 and 9.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
14.90	<p>Wash, 10 lks. wide, 1 ft. deep, drains N. 50° E.</p>
16.10	<p>Graded road, bears N. 50° E. and S. 50° W.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 9.</p>
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T27N R21W  <math>\frac{1}{4} \frac{S\ 4}{S\ 9}</math>                      1968</p>
80.00	<p>The cor. of secs. 4, 5, 8 and 9.</p>
	<p>Land, rolling.                      Soil, gravelly and sandy clay loam.                      No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°15' W., bet. secs. 4 and 5.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
18.20	<p>Rocky outcrop, slopes SW.</p>

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

<p>CHAINS</p> <p>27.20</p> <p>40.00</p> <p>80.14</p>	<p>Saddle of a ridge, bears NE. and SW.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 5.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T27N R21W <math>\frac{1}{4}</math> S 5   S 4 1968</p> <p>The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented by an iron post <math>2\frac{1}{2}</math> ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R21W <u>S32   S33</u> S 5   S 4 T27N 1955</p> <p>Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, monumented by an iron post <math>2\frac{1}{2}</math> ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T27N R21W <u>S30   S29</u> S31   S32 1955</p> <p>N. <math>0^{\circ}03'</math> W., bet. secs. 29 and 30.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>24.00 Graded road, bears N. <math>50^{\circ}</math> E. and S. <math>50^{\circ}</math> W.</p> <p>39.00 Track road, bears N. <math>80^{\circ}</math> E. and S. <math>80^{\circ}</math> W.</p> <p>40.00 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 29 and 30.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T27N R21W <math>\frac{1}{4}</math> S30   S29 1968</p> <p>Raise a mound of stone W. of the corner.</p> <p>Ascend SW. slope of mountain.</p> <p>74.50 Rocky spur, slopes S. <math>75^{\circ}</math> W.; desc. steep N. slope.</p> <p>79.20 Wash, 20 lks. wide, 1 ft. deep, drains S. <math>75^{\circ}</math> W.; asc. steep S. slope.</p>
--	---

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T27N R21W  <math>\frac{S19}{S30}   \frac{S20}{S29}</math>                      1968</p> <p>Land, rolling to mountainous.                      Soil, gravelly and rocky clay loam.                      No timber; Undergrowth, creosote bush and cacti.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>S. 89°47' W., bet. secs. 20 and 29.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
14.30	<p>Graded road, bears N. 50° E. and S. 50° W., 6.00 chs., thence S. 20° W.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 20 and 29.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T27N R21W  <math>\frac{1}{4} \frac{S20}{S29}</math>                      1968</p>
51.00	<p>Asc. E. slope of mountain, bears S. 40° E. and N. 40° W.</p>
66.00	<p>Ridge, bears S. 40° E. and N. 40° W.; desc. steep W. slope.</p>
77.00	<p>Wash, 20 lks. wide, 1 ft. deep, drains S. 75° W.; asc. SE. slope.</p>
80.00	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, rolling.                      Soil, rocky and gravelly loam.                      No timber; Undergrowth, creosote bush and cacti.</p>
	<p>N. 89°58' W., bet. secs. 19 and 30.</p>
	<p>Over mountainous land, through moderate undergrowth.</p>
23.20	<p>Base of mountain, bears S. 40° E. and N. 40° W.; thence enter rolling land.</p>
40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 30.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T27N R21W  <math>\frac{1}{4} \frac{S19}{S30}</math>                      1968</p>

Completion Survey of Subdivisional Lines, T. 27 N., R 21 W.

CHAINS	
45.80	Wash, 30 lks. wide, 1 ft. deep, drains S.
74.60	Wash, 100 lks. wide, 1 ft. deep, drains S. 20° E.; asc. E. slope.
78.80	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp.
	Land, mountainous to rolling. Soil, rocky and gravelly clay loam. No timber; Undergrowth, creosote bush and cacti.
From the cor. of secs. 19, 20, 29 and 30.	
N 0°03' W., bet. secs. 19 and 20.	
Over mountainous land; by triangulation.	
Asc. steep S. slope.	
15.40	Top of mountain, bears S. 40° E. and N. 40° W.; end of triangulation; thence along mountain top.
30.00	Descend NE. slope.
40.00	Point for the ¼ sec. cor. of secs. 19 and 20.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.
T27N R21W ¼ S19 S20 1968	
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 24 ins. in the ground, brass cap mkd.
T27N R21W S18 S17 S19 S20 1968	
	Set a wooden post 4 x 4 ins. square, 6½ ft. long, alongside the iron post.
	Land, mountainous. Soil, rocky and clay loam. No timber; Undergrowth, creosote bush and cacti.
From the cor. of secs. 16, 17, 20 and 21.	
S. 89°45' W. bet. secs. 17 and 20.	
Over rolling land, through moderate undergrowth.	
7.50	Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.
40.00	Point for the ¼ sec. cor. of secs. 17 and 20.
	Set the iron post 20 ins. in the ground, brass cap mkd.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	T27N R21W $\frac{1}{4}$ $\frac{S17}{S20}$ 1968
	Raise a mound of stone N. of the corner.
44.70	Track road, bears S. 65° E. and N. 50° W.
80.00	The cor. of secs. 17, 18, 19 and 20.
	Land, rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti and grass.
	N. 89°56' W., bet. secs. 18 and 19.  Over rolling land, through moderate undergrowth.
15.00	Ascend E. slope of mountain, bears S. 30° E. and N. 30° W.
25.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 15° E.
33.20	Top of ridge; divide bet. Detrital Valley and Colorado River, bears S. 30° E. and N. 30° W.; desc. W. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.
	Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.
	T27N R21W $\frac{1}{4}$ $\frac{S18}{S19}$ 1968
	Located on a steep W. slope.
49.30	Draw, drains NW.
55.60	Wash, 70 lks. wide, 2 ft. deep, drains S. 35° W.; asc. gentle E. slope.
75.30	Draw, drains S. 25° W.
78.67	The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.
	Land, rolling to mountainous. Soil, rocky clay loam. No timber; Undergrowth, creosote bush and cacti.
	From the cor. of secs. 17, 18, 19 and 20.  N. 0°03' W., bet. secs. 17 and 18.  Over rolling land, through moderate undergrowth.
7.80	Track road, bears E. and W.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
18.70	Track road, bears SE. and NW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18. Set the iron post 22 ins. in the ground, brass cap mkd.  T27N R21W $\frac{1}{4}$ S18   S17 1968  Raise a mound of stone W. of the corner.
44.90	Wash, 10 lks. wide, 1 ft. deep, drains NE.
80.00	Point for the cor. of secs. 7, 8, 17 and 18. Set the iron post 22 ins. in the ground, brass cap mkd.  T27N R21W S 7   S 8 S18   S17 1968  from which  A windmill, bears N. 46°59' E., 31.32 chs. dist.  Raise a mound of stone W. of the corner.  Land, rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 8, 9, 16 and 17. S. 89°44' W., bet. secs. 8 and 17. Over mountainous land, through moderate undergrowth. Descend steep W. slope.
14.50	Draw, drains N. 10° W.; asc. E. slope.
29.60	Ridge, bears N. 20° E. and S. 20° W.; desc. W. slope.
31.00	Track road, bears NE. and SW.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17. Set the iron post 20 ins. in the ground, brass cap mkd.  T27N R21W $\frac{1}{4}$ S 8 S17 1968  from which  Cor. No. 1, Mineral Survey No. 2696, Waldorf Astoria lode, bears N. 61°08' W., 10.10 chs. dist., monumented by a malpais stone, 6 x 12 x 10 ins. above the ground, mound of stone alongside, mkd. + 1 2696 W A on N. face.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
	Raise a mound of stone N. of the corner.
62.00	Graded road, bears S. 25° E. and N. 25° W.
71.30	Ridge, bears N. 10° E. and S. 10° W.
80.00	The cor. of secs. 7, 8, 17 and 18.
	Land, mountainous to rolling. Soil, gravelly and rocky loam. No timber; Undergrowth, creosote bush, cacti and grass.
	N. 89°54' W., bet. secs. 7 and 18.
	Over rolling land, through moderate undergrowth.
8.50	Graded road, bears N. 30° E. and S. 30° W.
40.00	Point for the ¼ sec. cor. of secs. 7 and 18.
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T27N R21W ¼ <math>\frac{S\ 7}{S18}</math> 1968</p>
51.70	Leave rolling land, bears N. and S.; enter mountainous land; asc. E. slope.
63.40	Draw, drains S.
68.30	Ridge, bears N. and S.; desc. W. slope.
78.66	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.
	Land, rolling to mountainous. Soil, gravelly and rocky loam. No timber; Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°03' W., bet. secs. 7 and 8.
	Over rolling land, through moderate undergrowth.
8.50	Graded road, bears N. 50° E. and S. 50° W.
9.90	Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.
35.80	Track road, bears E. and W.
40.00	Point for the ¼ sec. cor. of secs. 7 and 8.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS		
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math>            S 7   S 8            1968</p>	
49.30	<p>Wash, 10 lks. wide, 1 ft. deep, drains N. 70° E.</p>	
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T27N R21W            S 6   S 5            S 7   S 8            1968</p>	
	<p>Set a wooden post 4 x 4 ins. square, 4 ft. long, alongside the iron post.</p>	
	<p>Land, rolling.            Soil, gravelly and sandy loam.            No timber; Undergrowth, creosote bush, cacti and grass.</p>	
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>	
	<p>S. 89°43' W., bet. secs. 5 and 8.</p>	
	<p>Over rolling land, through moderate undergrowth.</p>	
40.01	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 8.</p>	
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>	
	<p style="text-align: center;">T27N R21W  <math>\frac{1}{4}</math> S 5            S 8            1968</p>	
51.80	<p>Wash, 20 lks. wide, 2 ft. deep, drains N.</p>	
62.70	<p>Graded road, bears N. 10° E. and S. 10° W.</p>	
77.40	<p>Graded road, bears S. 80° E. and N. 80° W.</p>	
80.02	<p>The cor. of secs. 5, 6, 7 and 8.</p>	
	<p>Land, rolling.            Soil, gravelly and sandy loam.            No timber; Undergrowth, creosote bush, cacti and grass.</p>	
	<p>N. 89°50' W., bet. secs. 6 and 7.</p>	
	<p>Over rolling land, through moderate undergrowth.</p>	

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS	
24.90	Wash, 10 lks. wide, 1 ft. deep, drains N.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T27N R21W $\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$ 1968
	Raise a mound of stone N. of the corner.
57.00	Wash, 20 lks. wide, 1 ft. deep, drains NE.; asc. E. slope of ridge, bears SE. and NW.
72.80	Top of ridge, divide between Detrital Valley and Colorado River, bears SE. and NW.; desc. SW. slope.
78.66	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.
	T27N R22W R21W $\frac{S\ 1\   S\ 6}{S\ 12\   S\ 7}$ 1955
	Land, rolling. Soil, gravelly and sandy loam. No timber; Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 5, 6, 7 and 8.
	N. $0^{\circ}14'$ W., bet. secs. 5 and 6.
	Over rolling land, through moderate undergrowth.
0.70	Graded road, bears S. $75^{\circ}$ E. and N. $75^{\circ}$ W.
38.10	Wash, 10 lks. wide, 1 ft. deep, drains N. $30^{\circ}$ E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T27N R21W $\frac{1}{4}$ $S\ 6\   S\ 5$ 1968
	Raise a mound of stone W. of the corner.
54.50	Wash, 20 lks. wide, 2 ft. deep, drains N. $60^{\circ}$ E.
80.40	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 9 ins. above the ground, brass cap mkd.

Completion Survey of Subdivisional Lines, T. 27 N., R. 21 W.

CHAINS

T28N R21W  

S31	S32
S 6	S 5

T27N  
1955

Land, rolling.  
Soil, gravelly and sandy loam.  
No timber; Undergrowth, creosote bush, cacti and grass.

Retracement of the Boundaries of Mineral Survey No. 1103  
Mariposa and Little Daisy Lodes

Retracing the Survey executed  
by O. F. Kuencer in 1893

Beginning at Cor. No. 1, M.S. 1103 Mariposa lode, monumented by a wooden post, 4 x 4 ins. square, 30 ins. above the ground, mks. visible but not legible, from which a granite stone in place, 3 x 3 x 1 ft., bears N. 62°02' W., 57 lks. dist., mkd. 1 1103 + BR.; from which

The 1/2 sec. cor. of secs. 4 and 33, bears N. 12°28'30" W., 4.528 chs. dist., hereinbefore described.

Thence S. 85°02' W., along line 1-2 of Mariposa lode.

Over rolling and mountainous land.

22.47 Cor. No. 2 of Mariposa lode, monumented by a wooden post 4 x 4 ins. square, 30 ins. above the ground, mkd. 2 1103 on S. side and MPA on N. side, from which a granite stone in place, 3 x 4 x 1 ft., bears N. 71°51' E., 93.9 lks. dist., mkd. + 2 1103 BR.

Thence N. 5°12' W.

6.248 Intersect line bet. secs. 4 and 33 on the S. bdy. of T. 27 N., R. 21 W., at a point from which the cor. of secs. 4, 5, 32 and 33 bears S. 89°46' W., 17.93 chs. dist.

9.098 Cor. No. 3 of Mariposa lode, as determined from a bearing rock. A granite stone in place, 3 x 3 x 1 ft., bears N. 0°14' E., 15.8 lks. dist., mkd. BR 3 1103. This cor. position conforms to another tie made in 1915 from the cor. of secs. 4, 5, 32 and 33 on S. bdy. of T. 27 N., R. 21 W.

Thence N. 85°09' E.

22.59 Cor. No. 4 of Mariposa lode on line 8-5, M.S. 1103, Little Daisy lode, monumented by a wooden post 4 x 4 ins. square, 40 ins. long, lying loose on the ground, mkd. 4 1103 MPA, from which a granite stone in place 18 x 18 x 6 ins. above the ground, bears N. 82°02' W., 67.8 lks. dist., mkd. + 4 1103 BR.; and from which

Retracement of the Boundaries of Mineral Survey No. 1103  
Mariposa and Little Daisy Lodes

CHAINS	
	<p>Cor. No. 8, M. S. 1103, Little Daisy lode, bears S. 3°42' E., 7.035 chs. dist.</p> <p>Thence N. 7°17' W., along line 8-5 of Little Daisy lode.</p>
1.918	<p>Cor. No. 5 of Little Daisy lode, monumented by a wooden post 4 x 4 ins. square, 40 ins. long, loosely set, mkd. LD on one side and 5 1103 on one side, from which a rock in place, bears S. 37°02' W., 1.894 chs. dist., mkd. X.</p> <p>Thence S. 88°36' E.</p>
10.10	<p>Graded road, bears N. 10° E. and S. 10° W.</p>
18.995	<p>Cor. No. 6 of Little Daisy lode, monumented by a wooden post, 4 x 4 ins. square, 30 ins. long, firmly set in a mound of stone, mkd. 6 1103 on S. face and LD on N. face. Unable to find record bearing rock.</p> <p>Thence S. 2°40' E.</p>
6.067	<p>Intersect line bet. secs. 4 and 33 on the S. bdy. of T. 27 N., R. 21 W., at a point from which the ¼ sec. cor. of secs. 4 and 33, bears N. 89°58' W., 19.28 chs. dist.</p>
7.147	<p>Cor. No. 7 of Little Daisy lode, monumented by a mound of stone with a wooden post 4 x 4 ins. square, 40 ins. long, lying alongside, mkd. LD on one face, from which a rock in place, bears N. 26°06' E., 40.9 lks. dist., mkd. + BR 7 1103.</p> <p>Thence S. 85°55' W.</p>
9.30	<p>Graded road, bears S. 25° E. and N. 25° W.</p>
18.638	<p>Cor. No. 8 of Little Daisy lode, on line 1-4, M. S. 1103, Mariposa lode, monumented by the remains of an old wooden post, 4 x 4 ins. square, mks. visible but not legible, from which a rock in place, 30 x 24 x 12 ins., bears N. 16°16' E., 2.214 chs. dist., mkd. 1103 + 8.</p> <p>Thence S. 7°09' E.</p>
2.025	<p>Cor. No. 1, M. S. 1103 Mariposa lode, and place of beginning.</p>
<p>General Description</p>	
<p>The elevation in Township 27 North, Range 21 West, ranges from 2,350 to 3,700 ft. above sea level, being at its lowest point in section 31 and at the highest point in the northwest portion of section 16. The land in the east half is gently rolling to nearly level and the west half is rolling and mountainous. The soil is rocky and gravelly to sandy clay loam. The vegetation consists of creosote bush, cacti and grass.</p> <p>U. S. Highway No. 93 enters the area surveyed in this township at the east boundary of section 14, traverses</p>	

## General Description

CHAINS

northwesterly and leaves at the north boundary of section 3. There are numerous graded and track roads throughout the township.

The primary interest in the township is mining and grazing.

The most important developments in mining are Mineral Survey Claims Nos. 1103 and 2694. Numerous other mining claims are located in the west portion of the township. There is no recent activity in mining.

There was evidence of Mountain Sheep on the west slopes of the range of mountains over-looking the Colorado River.

The direction of the drainage varies throughout the area surveyed in this township.



CERTIFICATE OF SURVEY

(I) ~~(We)~~ Gary T. Oviatt, HEREBY  
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day  
 of July, 19 68, (I) ~~(We)~~ have dependently resurveyed portions of the  
 south and west boundaries and completed the survey of the subdivisional lines,  
 Township 27 North, Range 21 West, and retraced the boundaries of Mineral Survey  
 No. 1103, Mariposa and Little Daisy lodes, Tps. 26 and 27 N., R. 21 W.,

of the Gila and Salt River Meridian, in the State of Arizona, which  
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)  
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-  
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in  
 specific manner described in the foregoing field notes.

January 30, 1970  
 (Date)

*Gary T. Oviatt*  
 (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
 Date JUL 10 1970

BUREAU OF LAND MANAGEMENT  
 Washington, D.C.

The foregoing field notes of the dependent resurvey of portions of the south and  
 west boundaries and the completion survey of the subdivisional lines,  
 Township 27 North, Range 21 West, and retracement of the boundaries of  
 Mineral Survey No. 1103, Mariposa and Little Daisy lodes, Tps. 26 and 27 N.,  
 R. 21 W., of the Gila and Salt River Meridian, Arizona,  
 executed by Gary T. Oviatt

having been critically examined and found correct, are hereby approved.

JUN 21 1971  
 (Date)

*Clark F. Humm*  
 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above described surveys in~~  
 , is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-628