

1A

BOOK 4900
INDEX DIAGRAM

Township $\frac{1}{2}$ 28 North $\frac{1}{2}$ $\frac{1}{2}$ $\frac{1}{2}$, Range $\frac{1}{2}$ 21 West

31	30	20	15		
6	29 5	19 4	8	2	1
29	28	19	14		
7	27 8	18 9	10	14 11	6 12
27	26		13	13	5
18	25 17	16	15	12 14	5 13
25	24		11	11	4
19	24 20	17 21	22	10 23	4 24
23	23	17	10	9	3
30	22 29	16 28	27	9 26	3 25
22	21	16	8	7	2
31	20 32	15 33	34	6 35	1 36

Township 28 North, Range 21 West
Gila and Salt River Meridian, Arizona

CHAINS

The north boundary, (Seventh Standard Parallel North), was surveyed in 1930 by D. R. Averill. The south, east and west boundaries and a portion of the subdivisional lines were surveyed in 1955 by D. E. Harding.

The following notes are those of a completion survey of the subdivisional lines of Township 28 North, Range 21 West.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 11, 1968.


Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 ins. long, 2½ ins. in diameter flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township as determined by traverse from USC&GS Triangulation Station POPE, located in section 3, T. 27 N., R. 21 W. is: Latitude 35°45'50.6" North and Longitude 114°28'06.0" West.

The mean magnetic declination was found to be: 15½° East.

Completion Survey of the Subdivisional Lines
Township 28 North, Range 21 West

From true point for the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., from which the witness cor., bears S. 89°56' W., 1.00 ch. dist., monumented by an iron post 2½ ins. diam., projecting 4 ins. above the ground, brass cap mkd.



from the true point

USC&GS Triangulation Station POPE, bears S. 54° 34'45" W., 105.48 chs. dist., monumented by a standard disk, 3 ins. diam., set in concrete in a drill hole, mkd. POPE 1950.

N. 0°01' W., bet. secs. 35 and 36.

Over nearly level land, in Detrital Wash area.

- 31.60 Main channel of Detrital Wash, 60 lks. wide, 2 ft. deep, drains N. 20° W.
- 32.50 Leave Detrital Wash area, bears S. 20° E. and N. 20° W.
- 40.00 Point for the ½ sec. cor. of secs. 35 and 36.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS		
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4}$ S35 S36 1968</p>	
	<p>Set a wooden post, 2 x 3 ins. squared, 3 ft. long, alongside the iron post.</p>	
76.50	<p>Wash, 60 lks. wide, 1 ft. deep, drains S. 75° W.</p>	
80.00	<p>Point for the cor. of secs. 25, 26, 35 and 36.</p>	
	<p>Set the iron post 26 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W S26 S25 S35 S36 1968</p>	
	<p>Raise a mound of stone W. of the corner.</p> <p>Land, nearly level. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>	
	<hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R21W R20W S25 S30 S36 S31 1955</p>	
	<p>S. 89°59' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	
1.20	<p>Wash, 30 lks. wide, 2 ft. deep, drains N. 75° W.</p>	
15.70	<p>Wash, 30 lks. wide, 1 ft. deep, drains S. 75° W.</p>	
37.20	<p>Graded road, bears S. 10° E. and N. 10° W.</p>	
39.96	<p>Point for the ¼ sec. cor. of secs. 25 and 36.</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4}$ S25 S36 1968</p>	
	<p>Raise a mound of stone N. of the corner.</p>	
79.92	<p>The cor. of secs. 25, 26, 35 and 36.</p>	

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>Land, gently rolling. Soil, rocky and sandy clay loam. Timber, scattered Joshua trees Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°01' W., bet. secs. 25 and 26</p> <p>Over gently rolling land, through moderate undergrowth.</p>
16.00	Wash, 20 lks. wide, 1 ft. deep, drains W.
40.00	Point for the ¼ sec. cor. of secs. 25 and 26.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p>T28N R21W ¼ S26 S25 1968</p>
	Raise a mound of stone W. of the corner.
52.50	Graded road, bears S. 60° E. and N. 60° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T28N R21W S23 S24 S26 S25 1968</p>
	Raise a mound of stone W. of the corner.
	<p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, mound of stone W., brass cap mkd.</p>
	<p>T28N R21W R20W S24 S19 S25 S30 1955</p>
	N. 89°56' W., bet. secs. 24 and 25.
	Over gently rolling land, through moderate undergrowth.
39.97	Point for the ¼ sec. cor. of secs. 24 and 25.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p>T28N R21W ¼ S24 S25 1968</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	Raise a mound of stone N. of the corner.
57.20	Graded road, bears S. 15° E. and N. 15° W.
79.94	The cor. of secs. 23, 24, 25 and 26.
	Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
	N. 0°01' W., bet. secs. 23 and 24.
	Over gently rolling land, through moderate undergrowth.
36.00	Track road, bears S. 70° E. and N. 70° W.
40.00	Point for the ¼ sec. cor. of secs. 23 and 24, falls in a wash, 20 lks. wide, 1 ft. deep, drains W., impractical to monument.
40.20	Point selected for the witness ¼ sec. cor. of secs. 23 and 24.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	T28N R21W ½ W C S23 S24 ↓ 1968
59.90	Track road, bears E. and W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T28N R21W S14 S13 S23 S24 1968
	Raise a mound of stone W. of the corner.
	Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, mound of stone E., brass cap mkd.
	T28N R21W R20W S13 S18 S24 S19 1955

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>N. 89°54' W., bet. secs. 13 and 24.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
39.96	<p>Point for the ¼ sec. cor. of secs. 13 and 24.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W $\frac{1}{4}$ $\frac{S13}{S24}$ 1968</p>
	<p>Raise a mound of stone N. of the corner.</p>
79.70	<p>Graded road, bears S. 15° E. and N. 15° W.</p>
79.92	<p>The cor. of secs. 13, 14, 23 and 24.</p>
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
0.80	<p>Graded road, bears S. 15° E. and N. 15° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 13 and 14.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W $\frac{1}{4}$ S14 S13 1968</p>
	<p>Raise a mound of stone W. of the corner.</p>
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W $\frac{1}{4}$ S11 S12 S14 S13 1968</p>
	<p>Raise a mound of stone W. of the corner.</p>
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, mound of stone W., brass cap mkd.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS		
39.97	<p style="text-align: center;">T28N R21W R20W <u>S12 S 7</u> <u>S13 S18</u> 1955</p> <p>N. 89°50' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 12 and 13.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>	
79.94	<p style="text-align: center;">T28N R21W ¼ <u>S12</u> <u>S13</u> 1968</p> <p>Raise a mound of stone N. of the corner.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>	
39.83	<p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 11 and 12.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
79.66	<p style="text-align: center;">T28N R21W ¼ <u>S11 S12</u> 1968</p> <p>Raise a mound of stone W. of the corner.</p> <p>The cor. of secs. 1, 2, 11 and 12, monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R21W <u>S 2 S 1</u> <u>S11 S12</u> 1955</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>	
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam.,</p>	

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{S34}{S3} \frac{S35}{S2}$ 1955</p> <p>from which</p> <p style="text-align: center;">Triangulation Station POPE, bears S. 5°32'30" W., 61.24 chs. dist., previously described.</p> <p>N. 0°01' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
15.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° E.
36.20	Wash, 10 lks. wide, 2 ft. deep, drains N 60° E.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	<p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4}$ $\frac{S34}{S3} \frac{S35}{S2}$ 1968</p>
73.40	Wash, 20 lks. wide, 2 ft. deep, drains NE.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{S27}{S34} \frac{S26}{S35}$ 1968</p> <p>Set a wooden post, 2 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°53' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
16.00	Enter Detrital Wash area, bears S. 15° E. and N. 15° W.
24.50	Main channel of Detrital Wash, 90 lks. wide, 2 ft. deep, drains N.
37.50	Leave Detrital Wash area, bears S. 15° E. and N. 15° W.

Completion Survey, Subdivisional Lines, T 28 N., R. 21 W.

CHAINS	
39.95	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4} \frac{S26}{S35}$ 1968</p> <p>Set a wooden post, $3\frac{1}{2}$ ins. diam., $3\frac{1}{2}$ ft. long, alongside the iron post.</p>
53.10	Track road, bears N. 30° E. and S. 30° W.
79.90	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
S. 89°54' W., bet. secs. 27 and 34.	
Over gently rolling land, through moderate undergrowth.	
15.50	Wash, 30 lks. wide, 2 ft. deep, drains NE.
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4} \frac{S27}{S34}$ 1968</p> <p>Raise a mound of stone N. of the corner.</p>
52.69	Telephone line, bears S. 23°42' E. and N. 23°42' W.
54.40	Right-of-way fence, bears S. 23°42' E. and N. 23°42' W.
56.00	U.S. Highway No. 93 and 466, bears S. 23°42' E. and N. 23°42' W.
56.90	Wash, 20 lks. wide, 1 ft. deep, drains NE.
57.70	Right-of-way fence, bears S. 23°42' E. and N. 23°42' W.
60.10	Power line, bears S. 23°42' E. and N. 23°42' W.
62.50	Enter mountainous land, bears SE. and NW.; asc. E. slope
80.08	<p>True point for the cor. of secs. 27, 28, 33 and 34, from which the witness cor. bears N. 0°02' W., 1.00 ch. dist. monumented by an iron post $2\frac{1}{2}$ ins. diam., set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{S28}{S33} \frac{S27}{S34}$ W C 1955</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>Land, gently rolling to mountainous. Soil, gravelly, sandy and rocky loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
40.00	<p>From the cor. of secs. 26, 27, 34 and 35. N. 0°01' W., bet. secs. 26 and 27. Over rolling land, through moderate undergrowth. Point for the ¼ sec. cor. of secs. 26 and 27. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W ¼ S27 S26 1968</p>
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27. Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W S22 S23 S27 S26 1968</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26. S. 89°52' W., bet. secs. 23 and 26. Over gently rolling land, through moderate undergrowth.</p>
39.96	<p>Point for the ¼ sec. cor. of secs. 23 and 26. Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W ¼ S23 S26 1968</p>
46.90	<p>Set a wooden post, 3 ins. diam., 3½ ft. long, alongside the iron post.</p>
56.70	<p>Enter Detrital Wash area, bears S. 20° E. and N. 20° W.</p>
72.10	<p>Track road crosses wash area, bears S. 70° E. and N. 70° W.</p>
	<p>Leave Detrital Wash area, bears S. 20° E. and N. 20° W.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
79.92	The cor. of secs. 22, 23, 26 and 27. Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
	S. 89°52' W., bet. secs. 22 and 27. Over nearly level land, through moderate undergrowth.
26.80	Wash, 20 lks. wide, 1 ft. deep, drains N. 30° E.
40.06	Point for the ¼ sec. cor. of secs. 22 and 27. Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd. <div style="text-align: center;"> T28N R21W ¼ <u> S22</u> S27 1968 </div>
80.12	The cor. of secs. 21, 22, 27 and 28, monumented by an iron post 2½ ins. diam., projecting 4 ins. above the ground, mound of stone W., brass cap mkd. <div style="text-align: center;"> T28N R21W <u>S21 S22</u> <u>S28 S27</u> 1955 </div> Land, nearly level. Soil, gravelly, rocky loam. No timber; Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 22, 23, 26 and 27. N. 0°01' W., bet. secs. 22 and 23. Over nearly level land, through moderate undergrowth.
4.50	Graded road, bears S. 70° E. and N. 70° W.
24.00	Enter Detrital Wash area, bears S. 13° E. and N. 13° W.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T28N R21W ¼ <u>S22 S23</u> 1968 </div> Set a wooden post, 4 x 4 ins. square, 3 ft. long, alongside the iron post. The cor. is located in the wash area.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
52.30	Main channel of Detrital Wash, 30 lks. wide, 3 ft. deep, drains N. 13° W.
63.10	Wash, 20 lks. wide, 3 ft. deep, drains N. 25° W.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T28N R21W S15 S14 S22 S23 1968
	Raise a mound of stone W. of the corner.
	Land, nearly level. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 13, 14, 23 and 24.
	S. 89°51' W., bet. secs. 14 and 23.
	Over nearly level land, through moderate undergrowth.
39.96	Point for the ¼ sec. cor. of secs. 14 and 23.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T28N R21W ¼ ——— S14 S23 1968
	Set a wooden post, 2 ins. diam., 3½ ft. long, alongside the iron post.
75.40	Enter Detrital Wash area, bears S. 10° E. and N. 10° W.
79.92	The cor. of secs. 14, 15, 22 and 23.
	Land, nearly level. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
	S. 89°48' W., bet. secs. 15 and 22.
	Over level land, through Detrital Wash area, bears S. 10° E. and N. 10° W.
13.10	Leave Detrital Wash area, bears S. 10° E. and N. 10° W.; enter gently rolling land.
26.50	Track road, bears NE. and SW.
40.09	Point for the ¼ sec. cor. of secs. 15 and 22.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{2}$ $\frac{S15}{S22}$ 1968</p> <p>Raise a mound of stone N. of the corner.</p>	
80.18	<p>The cor. of secs. 15, 16, 21 and 22, monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 5 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{S16}{S21} \frac{S15}{S22}$ 1955</p> <p>Land, nearly level to gently rolling. Soil, gravelly and rocky loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>	
40.00	<p>From the cor. of secs. 14, 15, 22 and 23. N. $0^{\circ}01'$ W., bet. secs. 14 and 15.</p> <p>Over nearly level land, through Detrital Wash area.</p> <p>Point for the $\frac{1}{2}$ sec. cor. of secs. 14 and 15.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{2}$ $\frac{S15}{S14} \frac{S14}{S14}$ 1968</p> <p>Set a wooden post, 3 ins. diam., $3\frac{1}{2}$ ft. long, alongside the iron post.</p> <p>The cor. is located on the E. edge of Detrital Wash.</p>	
49.00	<p>Leave Detrital Wash area, bears S. 10° E. and N. 10° W.; enter moderate undergrowth.</p>	
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{S10}{S15} \frac{S11}{S14}$ 1968</p> <p>Set a wooden post, 2 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass last half.</p>	

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°53' W., bet. secs. 11 and 14.</p> <p>Over nearly level land, through moderate undergrowth.</p>
22.40	Graded road, bears S. 25° E. and N. 25° W.
39.96	Point for the ¼ sec. cor. of secs. 11 and 14.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T28N R21W</p> <p>¼ $\frac{S11}{S14}$</p> <p>1968</p>
	Raise a mound of stone N. of the corner.
79.92	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, nearly level.</p> <p>Soil, gravelly and sandy clay loam.</p> <p>Timber, scattered Joshua trees.</p> <p>Undergrowth, creosote bush, cacti and grass.</p>
	<p>S. 89°43' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
6.80	Enter Detrital Wash area, bears S. 5° E. and N. 5° W.
7.30	Main channel of wash, 100 lks. wide, 2 ft. deep, drains N.
18.40	Leave Detrital Wash area, bears N. and S.
40.11	Point for the ¼ sec. cor. of secs. 10 and 15.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T28N R21W</p> <p>¼ $\frac{S10}{S15}$</p> <p>1968</p>
	Raise a mound of stone N. of the corner.
58.80	Track road, bears NE. and SW.
80.22	The cor. of secs. 9, 10, 15 and 16, monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd.
	<p>T28N</p> <p>R21W</p> <p>S 9 S10</p> <p>S16 S15</p> <p>1955</p>
	<p>Land, gently rolling.</p> <p>Soil, gravelly and rocky clay loam.</p> <p>No timber; Undergrowth, creosote bush, cacti and grass.</p>

Completion Survey, Subdivisional Lines, T. 28 N , R. 21 W.

CHAINS	
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 0°03' W., bet. secs. 10 and 11.</p> <p>Over nearly level land, through moderate undergrowth.</p>
39.83	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4}$ S10 S11 1968</p> <p>Set a wooden post, 2 x 3 ins. squared, 3$\frac{1}{2}$ ft. long, alongside the iron post.</p>
49.15	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 80° W.</p>
79.66	<p>The cor. of secs. 2, 3, 10 and 11, monumented by an iron post 2$\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W S 3 S 2 S10 S11 1955</p> <p>Land, nearly level land. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>S. 89°56' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
17.60	<p>Enter Detrital Wash area, bears N. and S.</p>
23.00	<p>Leave Detrital Wash area, bears S. 5° E. and N. 5° W.</p>
40.10	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4}$ $\frac{S 3}{S10}$ 1968</p> <p>Raise a mound of stone N. of the corner.</p> <p>The cor. is located approximately 8.00 chs. S. of a power line bearing N. 89° E and S. 89° W.</p>
80.20	<p>The cor. of secs. 3, 4, 9 and 10, monumented by an iron post 2$\frac{1}{2}$ ins. diam., projecting 6 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W S 4 S 3 S 9 S10 1955</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS

Land, gently rolling.
Soil, gravelly and sandy clay loam.
No timber; Undergrowth, creosote bush, cacti and grass.

The point for the $\frac{1}{4}$ sec. cor. of sec. 3 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 20 ins. in the ground, brass cap mkd.

$\frac{1}{4}$ S3
T28N R21W
1968

from which

The Standard cor. of secs. 34 and 35, T. 29 N., R. 21 W., bears East, 11 lks. dist., monumented by an iron post 2 ins. diam., projecting 15 ins. above the ground, brass cap mkd. SC T29N R21W S34 S35 1930.

Set a wooden post, 2 ins. diam., 3 ft. long, alongside the iron post.

From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.

T28N R21W
S32 | S33
S 5 | S 4
T27N
1955

N. $0^{\circ}03'$ W., bet. secs. 32 and 33.

Over rolling land, through moderate undergrowth.

31.40 Wash, 20 lks. wide, 1 ft. deep, drains NE.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33.

Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.

T28N R21W
 $\frac{1}{4}$
S32 | S33
1968

66.30 Wash, 15 lks. wide, 2 ft. deep, drains NW., 200 lks. dist., thence N.

80.00 Point for the cor. of secs. 28, 29, 32 and 33.

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.

T28N R21W
S29 | S28
S32 | S33
1968

Land, rolling.
Soil, gravelly and sandy clay loam.
No timber; Undergrowth, creosote bush, cacti and grass.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>From true point for the cor. of secs. 27, 28, 33 and 34. S. 89°53' W., bet. secs. 28 and 33.</p> <p>Over mountainous land.</p> <p>Ascend steep E. slope by triangulation.</p>
25.00	Top of mountain, bears SE. and NW.; desc. SW. slope.
38.00	Large draw, drains SE.; asc. steep E. slope.
39.95	Point for the ¼ sec. cor. of secs. 28 and 33.
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T28N R21W ¼ $\frac{S28}{S33}$ 1968</p>
	Continue by triangulation.
48.40	Top of mountain, bears SE. and NW.; desc. W. slope.
69.50	Base of mountain, bears SE. and NW.; enter rolling land.
79.90	The cor. of secs. 28, 29, 32 and 33 and end of triangulation.
	<p>Land, mountainous. Soil, rocky and gravelly loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°03' W., bet. secs. 28 and 29.</p> <p>Over rolling land, through moderate undergrowth.</p>
3.00	Wash, 50 lks. wide, 3 ft. deep, drains W., 400 lks. dist. thence N.
24.70	Wash, 50 lks. wide, 2 ft. deep, drains W.; asc. S. slope.
30.10	Head of a draw, drains W.
33.80	Spur, slopes S. 80° W.; desc. N. slope.
37.60	Head of a draw, drains SW.; asc. S. slope.
40.00	Point for the ¼ sec. cor. of secs. 28 and 29.
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T28N R21W ¼ $\frac{S29}{S28}$ 1968</p>
43.30	Rocky ridge, bears E. and SW.; desc. N. slope.
48.60	Draw, drains W.; heads 200 lks. E.; asc. S. slope.
53.00	Ridge, bears S. 70° E. and N. 70° W.; desc. N. slope.
66.80	Wash, 40 lks. wide, 2 ft. deep, drains NW.; enter gently rolling land.
80.00	Point for the cor. of secs. 20, 21, 28 and 29.
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	<p>T28N R21W $\frac{S20}{S29} \frac{S21}{S28}$ 1968</p> <p>Land, rolling to gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p>
	<p>S. 89°51' W., bet. secs. 21 and 28.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
23.10	<p>Telephone line, bears S. 35°58' E. and N. 35°58' W.</p>
25.10	<p>Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.</p>
26.95	<p>U.S. Highway No. 93 and 466, bears S. 35°58' E. and N. 35°58' W.</p>
28.85	<p>Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.</p>
34.15	<p>Power line, bears S. 35°58' E. and N. 35°58' W.</p>
35.10	<p>Wash, 30 lks. wide, 2 ft. deep, drains N. 50° E.</p>
39.89	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 21 and 28.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p>T28N R21W $\frac{1}{2} \frac{S21}{S28}$ 1968</p>
	<p>Raise a mound of stone N. of the corner.</p>
46.20	<p>Base of ridge, bears N. and S.; enter rolling land, asc. E. slope.</p>
55.50	<p>Top of ridge, bears N. and S.; desc. W. slope.</p>
60.50	<p>Base of ridge, bears N. and S.; enter gently rolling land.</p>
79.78	<p>The cor. of secs. 20, 21, 28 and 29.</p>
	<p>Land, gently rolling to rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°11' W., bet. secs. 20 and 21.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
40.02	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 20 and 21.</p>
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p>T28N R21W $\frac{1}{2} \frac{S20}{S21}$ 1968</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
42.00	Enter wash area, 2 ft. deep, drains NE.
50.00	Leave wash area, drains NE.
63.00	Power line, bears S. 35°58' E. and N. 35°58' W.
67.60	Graded road, bears S. 35°58' E. and N. 35°58' W.
70.10	Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.
72.70	U.S. Highway No. 93 and 466, bears S. 35°58' E. and N. 35°58' W.
75.40	Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.
76.50	Wash, 30 lks. wide, 1 ft. deep, drains N. 10° E.
78.00	Telephone line, bears S. 35°58' E. and N. 35°58' W.
80.04	The cor. of secs. 16, 17, 20 and 21, monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd.
	<p style="text-align: center;">T28N R21W $\frac{S17}{S20} \frac{S16}{S21}$ 1955</p>
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17, monumented by an iron post 2½ ins. diam., projecting 4 ins. above the ground, mound of stone W., brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W $\frac{S8}{S17} \frac{S9}{S16}$ 1955</p>
	<p>N. 0°03' W., bet. secs. 8 and 9.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
39.60	Wash, 20 lks. wide, 2 ft. deep, drains N. 80° E.
40.00	Point for the ¼ sec. cor. of secs. 8 and 9.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W ¼ $S8 S9$ 1968</p>
	<p>Raise a mound of stone W. of the corner.</p>
62.80	Temple Bar road (paved), bears N. 20° E. and S. 25° W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\begin{array}{r l} S & 5 \\ S & 8 \end{array} \begin{array}{l} S & 4 \\ S & 9 \end{array}$ 1968</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
<p>39.94</p>	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°52' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4} \begin{array}{r} S & 4 \\ S & 9 \end{array}$ 1968</p> <p>Set a wooden post, 2 ins. diam., 3½ ft. long, alongside the iron post.</p>
<p>73.10</p>	<p>Temple Bar road (paved), bears N. 20° E. and S. 20° W.</p>
<p>79.88</p>	<p>The cor. of secs. 4, 5, 8 and 9.</p>
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>5.70 Graded road, bears E. and W.</p> <p>6.90 High tension power line, bears N. 89° E. and S. 89° W.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4} \begin{array}{r} S & 5 \\ S & 4 \end{array}$ 1968</p> <p>Set a wooden post, 3 ins. diam., 3½ ft. long, alongside the iron post.</p> <p>45.60 Wash, 25 lks. wide, 2 ft. deep, drains N. 85° E.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS

80.90

Intersect the S. bdy. of T. 29 N., R. 21 W., (Seventh Standard Parallel North).

Point for the closing cor. of secs. 4 and 5.

Set the iron post 20 ins. in the ground, brass cap mkd.

T29N
S33
S 5 | S 4
T28N R21W
C C
1968

from which

The Standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 29 N., R. 21 W., bears East, 8 lks. dist., monumented by an iron post 1 in. diam., projecting 9 ins. above the ground, mound of stone N., brass cap mkd. S C $\frac{1}{4}$ S 33 1930.

Raise a mound of stone S. of the corner.

Land, gently rolling.

Soil, gravelly and sandy clay loam.

No timber; Undergrowth, creosote bush, cacti and grass.

The point for the $\frac{1}{4}$ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing corners.

Set the iron post 20 ins. in the ground, brass cap mkd.

$\frac{1}{4}$ S 4
T28N R21W
1968

from which

The Standard cor. of secs. 33 and 34, T. 29 N., R. 21 W., bears East, 15 lks. dist., monumented by an iron post 2 ins. diam., projecting 15 ins. above the ground, brass cap mkd. SC T29N R21W S33 S34 1930.

Set a wooden post, 2 ins. diam., 3 ft. long, alongside the iron post.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.

T28N R21W
S31 | S32
S 6 | S 5
T27N
1955

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	N. 0°03' W., bet. secs. 31 and 32. Over rolling land, through moderate undergrowth.
40.00	Point for the ¼ sec. cor. of secs. 31 and 32. Set the iron post 22 ins. in the ground, brass cap mkd. T28N R21W ¼ S31 S32 1968
65.80	Raise a mound of stone W. of the corner. Wash, 20 lks. wide, 2 ft. deep, drains N. 75° E.
80.00	Point for the cor. of secs. 29, 30, 31 and 32. Set the iron post 20 ins. in the ground, brass cap mkd. T28N R21W S30 S29 S31 S32 1968
	Raise a mound of stone W. of the corner. Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 28, 29, 32 and 33. S. 89°54' W., bet. secs. 29 and 32. Over rolling land, through moderate undergrowth.
5.00	Wash, 20 lks. wide, 1 ft. deep, drains N.
35.60	Graded road, bears N. 10° E. and S. 10° W.
37.50	Wash, 20 lks. wide, 1 ft. deep, drains N. 10° W.
39.70	Wash, 10 lks. wide, 1 ft. deep, drains N.
40.00	Point for the ¼ sec. cor. of secs. 29 and 32. Set the iron post 20 ins. in the ground, brass cap mkd. T28N R21W ¼ — S29 S32 1968
	Raise a mound of stone N. of the corner.
71.70	Wash, 30 lks. wide, 1 ft. deep, drains N. 10° E.
80.00	The cor. of secs. 29, 30, 31 and 32. Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>S. 89°50' W., bet. secs. 30 and 31.</p> <p>Over rolling land, through moderate undergrowth.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 30 and 31.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T28N R21W} \\ \frac{1}{4} \frac{\text{S30}}{\text{S31}} \\ 1968 \end{array}$ <p>Raise a mound of stone N. of the corner.</p>
61.90	<p>Graded road, bears S. 20° E. and N. 20° W.</p>
62.50	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 10° W.</p>
78.60	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, brass cap mkd.</p> $\begin{array}{r} \text{T28N} \\ \text{R22W R21W} \\ \text{S25 S30} \\ \text{S36 S31} \\ 1955 \end{array}$ <p>Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through moderate undergrowth.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 29 and 30.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> $\begin{array}{r} \text{T28N R21W} \\ \frac{1}{4} \frac{\text{S30 S29}}{} \\ 1968 \end{array}$
80.00	<p>Point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T28N R21W} \\ \text{S19 S20} \\ \text{S30 S29} \\ 1968 \end{array}$ <p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS

From the cor. of secs. 20, 21, 28 and 29.

S. 89°58' W., bet. secs. 20 and 29.

Over rolling land, through moderate undergrowth.

21.70 Low ridge, bears N. and S.

27.10 Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.

29.70 Wash, 20 lks. wide, 2 ft. deep, drains N. 10° W.

35.00 Graded road, bears N. and S.

35.90 Wash, 20 lks. wide, 2 ft. deep, drains N. 30° E.

39.20 Track road, bears N. and S.

39.98 Point for the 1/4 sec. cor. of secs. 20 and 29.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T28N R21W
1/4 $\frac{S20}{S29}$
1968

79.96 The cor. of secs. 19, 20, 29 and 30.

Land, rolling.

Soil, gravelly and sandy clay loam.

No timber; Undergrowth, creosote bush, cacti and grass.

S. 89°45' W., bet. secs. 19 and 30.

Over rolling land, through moderate undergrowth.

30.10 Wash, 20 lks. wide, 1 ft. deep, drains N. 30° E.

40.00 Point for the 1/4 sec. cor. of secs. 19 and 30.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T28N R21W
1/4 $\frac{S19}{S30}$
1968

78.66 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post 2 1/2 ins. diam., projecting 12 ins. above the ground, mound of stone W., brass cap mkd.

T28N
R22W R21W
S24 | S19
S25 | S30
1955

Land, rolling.

Soil, gravelly and sandy clay loam.

No timber; Undergrowth, creosote bush, cacti and grass.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°03' W., bet. secs. 19 and 20.
	Over rolling land, through moderate undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T28N R21W $\frac{1}{4}$ S19 S20 1968</p>
	Raise a mound of stone W. of the corner.
50.20	Wash, 20 lks. wide, 1 ft. deep, drains NE.
77.90	Track road, bears N. 60° E. and S. 60° W.
80.00	Point for the cor. of secs. 17, 18, 19 and 20.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T28N R21W S18 S17 S19 S20 1968</p>
	Raise a mound of stone W. of the corner.
	Land, rolling.
	Soil, gravelly and sandy clay loam.
	No timber; Undergrowth, creosote bush, cacti and grass.
	<hr/>
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°55' W., bet. secs. 17 and 20.
	Over rolling land, through moderate undergrowth.
1.10	Telephone line, bears S. 35°58' E. and N. 35°58' W.
3.00	Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.
4.90	U.S. Highway No. 93 and 466, bears S. 35°58' E. and N. 35°58' W.
6.80	Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.
11.00	Graded road, bears N. 10° E. and S. 10° W.
12.10	Power line, bears S. 35°58' E. and N. 35°58' W.
29.80	Wash, 25 lks. wide, 1 ft. deep, drains NE.
39.83	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T28N R21W $\frac{1}{4}$ — S17 S20 1968</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS

Raise a mound of stone N. of the corner.

42.80 Track road, bears S. 10° E. and N 10° W.

45.70 Wash, 20 lks. wide, 2 ft. deep, drains NE.

58.60 Wash, 20 lks. wide, 2 ft. deep, drains NE.

77.20 Track road, bears NE. and S. 60° W.

79.66 The cor. of secs. 7, 8, 17 and 18.

Land, rolling.
Soil, gravelly and sandy clay loam.
No timber; Undergrowth, creosote bush, cacti and grass.

S. 89°40' W., bet. secs. 18 and 19.

Over rolling land, through moderate undergrowth.

40.00 Point for the ¼ sec. cor. of secs. 18 and 19.

Set the iron post 24 ins. in the ground, brass cap mkd.

T28N R21W
 $\frac{1}{4}$ $\frac{S18}{S19}$
 1968

Raise a mound of stone N. of the corner.

65.50 Ascend steep E. slope of a mountain, bears N. and S.

78.67 The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post 2½ ins. in the ground, mound of stone W., brass cap mkd.

T28N
 R22W R21W
 $\frac{S13}{S24} | \frac{S18}{S19}$
 1955

from which

USC&GS Triangulation Station LARSON, monumented by a standard bronze disk, set in a drill hole in a boulder, mkd. LARSON 1934, bears N. 39°31'34" W., 24.77 chs. dist.

The cor. is located on a steep E. slope.

Land, rolling to mountainous.
Soil, rocky and gravelly loam.
No timber; Undergrowth, creosote bush, cacti and grass.

From the cor. of secs. 17, 18, 19 and 20.

N. 0°03' W., bet. secs. 17 and 18.

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
40.00	<p>Over rolling land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W $\frac{1}{4}$ S18 S17 1968</p>
80.00	<p>Point for the cor. of secs. 7, 8, 17 and 18.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W S 7 S 8 S18 S17 1968</p>
	<p>Set a wooden post, 4 x 4 ins. square, 6 ft. long, alongside the iron post.</p> <p>Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°57' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
39.80	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R21W $\frac{1}{4}$ $\frac{S 8}{S17}$ 1968</p>
42.00	<p>Raise a mound of stone N. of the corner.</p> <p>Temple Bar road (paved), bears N. 40° E. and S. 40° W.</p>
48.00	<p>Track road, bears N. and S.</p>
59.20	<p>Telephone line, bears S. 35°58' E. and N. 35°58' W.</p>
61.20	<p>Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.</p>
62.70	<p>U.S. Highway No. 93 and 466, bears S. 35°58' E. and N. 35°58' W.</p>
64.50	<p>Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.</p>
66.90	<p>Graded road, bears S. 36° E and N. 36° W.</p>
70.30	<p>Power line, bears S. 35°58' E. and N. 35°58' W.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
79.60	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
<hr/>	
<p>S. 89°40' W., bet. secs. 7 and 18.</p>	
<p>Over rolling land, through moderate undergrowth.</p>	
38.70	<p>Wash, 20 lks. wide, 2 ft. deep, drains NE.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 18.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
<p style="text-align: center;">T28N R21W 1/4 $\frac{S\ 7}{S18}$ 1968</p>	
<p>Set a wooden post, 2 ins. diam., 4 ft. long, alongside the iron post.</p>	
78.69	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by an iron post 2 1/2 ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.</p>
<p style="text-align: center;">T28N R22W R21W $\frac{S12\ S\ 7}{S13\ S18}$ 1955</p>	
<p>Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>	
<hr/>	
<p>From the cor. of secs. 7, 8, 17 and 18.</p>	
<p>N. 0°03' W., bet. secs. 7 and 8.</p>	
<p>Over rolling land, through moderate undergrowth.</p>	
12.90	<p>Power line, bears S. 35°58' E. and N. 35°58' W.</p>
20.15	<p>Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.</p>
22.80	<p>U.S. Highway No. 93 and 466, bears S. 35°58' E. and N. 35°58' W.</p>
25.35	<p>Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.</p>
27.90	<p>Telephone line, bears S. 35°58' E. and N. 35°58' W.</p>
39.80	<p>Point selected for the witness 1/4 sec. cor. of secs. 7 and 8.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4}$ S 7 \uparrow S 8 W C 1968</p>
40.00	<p>True point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, falls in a wash, 10 lks. wide, 1 ft. deep, drains N. 60° E., this point impracticable to monument.</p>
43.90	<p>Wash, 30 lks. wide, 2 ft. deep, drains NE.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{S 6 S 5}{S 7 S 8}$ 1968</p> <p>Set a wooden post, 4 x 6 ins. squared, 3 ft. long, alongside the iron post.</p> <p>Land, rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89°59' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
30.10	<p>Wash, 30 lks. wide, 2 ft. deep, drains N. 40° E.</p>
39.78	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4} \frac{S 5}{S 8}$ 1968</p> <p>Set a wooden post, 2 ins. diam., 3½ ft. long, alongside the iron post.</p>
51.50	<p>Track road, bears S. 5° E. and N. 5° W.</p>
79.56	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
	<p>S. 89°40' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
32.30	Track road, bears NE. and SW.
35.00	Telephone line, bears S. 30° E. and N. 30° W.
39.70	Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.
40.00	Point for the ¼ sec. cor. of secs. 6 and 7.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R21W $\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$ 1968</p> <p>from which</p> <p style="text-align: center;">USC&GS Triangulation Station BUILDER, monumented by a brass tablet, 3 ins. diam., set in a drill hole in top of a 9 x 10 in. boulder, projecting 6 ins. above the ground, mkd. BUILDER 1935, bears S. 32°36' E., 8.72 chs. dist.</p> <p>Set a wooden post, 2 ins. diam., 3½ ft. long, alongside the iron post.</p>
41.60	U.S. Highway No. 93 and 466, bears S. 35°58' E. and N. 35°58' W.
43.50	Right-of-way fence, bears S. 35°58' E. and N. 35°58' W.
60.70	Power line, bears S. 45° E. and N. 45° W.
75.20	Graded road, bears N. 60° E. and S. 60° W.
78.72	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., pro- jecting 6 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R22W R21W $\frac{S\ 1\ \ S\ 6}{S12\ \ S\ 7}$ 1955</p> <p>The cor. is located on a E. slope.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over gently rolling land, through moderate undergrowth.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS	
5.10	Graded road, bears E. and W.
5.70	Transmission power line, bears N. 89° E. and S. 89° W.
31.00	Track road, bears NE. and SW.
40.00	Point for the ½ sec. cor. of secs. 5 and 6. Set the iron post 24 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T28N R21W ½ S 6 S 5 1968 </div> Set a wooden post, 4 x 6 ins. squared, 3 ft. long, alongside the iron post.
48.60	Track road, bears NE. and SW.
77.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 75° E.
80.90	Intersect the S. bdy. of T. 29 N., R. 21 W., (Seventh Standard Parallel North). Point for the closing cor. of secs. 5 and 6. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T29N S32 <hr style="width: 50px; margin: 0 auto;"/> S 6 S 5 C C T 28N R21W 1968 </div> from which The Standard ½ sec. cor. of Sec. 32, T. 29N., R. 21 W., bears West 37 lks. dist., monumented by an iron post 1 in. diam., projecting 6 ins. above the ground, mound of stone N., mkd. SC ½ S32 1930. Raise a mound of stone S. of the corner. Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti and grass.
	<hr style="width: 80%; margin: 10px auto;"/> The point for the ½ sec. cor. of sec. 5 is on the N. bdy. at mid-point bet. the closing corners. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> ½ S 5 T28N R21W 1968 </div> from which The Standard cor. of secs. 32 and 33, T. 29 N.,

Completion Survey, Subdivisional Lines, T. 28 N., R. 21 W.

CHAINS

R. 21 W., bears West, 15 lks. dist., monumented by an iron post 2 ins. diam., projecting 6 ins. above the ground, mound of stone N., brass cap mkd. SC T29N R21W S32 S33 1930.

Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.

The point for the $\frac{1}{4}$ sec. cor. of sec. 6 is on the N. bdy., 40.00 chs. in westing from the closing cor. of secs. 5 and 6.

Set the iron post 22 ins. in the ground, brass cap mkd.

$\frac{1}{4}$ S 6
T28N R21W
1968

from which

The Standard cor. of secs. 31 and 32, T. 29 N., R. 21 W., bears West, 37 lks. dist., monumented by an iron post 2 ins. diam., projecting 8 ins. above the ground, mound of stone N., brass cap mkd. SC T29N R21W S31 S32 1930.

Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.

General Description

The elevation in Township 28 North, Range 21 West, ranges from 2,000 ft. to 3,200 ft. above sea level, being at its highest point in the center of section 28. The land ranges from nearly level in the north and east portions to broken in the southwest portion. The soil is sandy and gravelly loam throughout most of the township with the exception of the southwest portion which is rocky. There is no timber in the township with the exception of scattered Joshua trees in the east portion. The undergrowth consists of creosote bush, cacti and a good amount of grass.

Highway No. 93 and 466 enters the township at the south boundary of section 34, traverses northwesterly and leaves at the west boundary of section 6. There are numerous graded and track roads throughout the township. Detrital Wash enters the township at the corner of section 1, 2, 35 and 36, drains northerly and leaves at the north boundary of section 3.

The primary use of the land is for grazing. Water is trucked in for the cattle.

CERTIFICATE OF SURVEY

I, Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11 day of July, 1968, I have completed the survey of the subdivisional lines of Township 28 North, Range 21 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 6, 1970
(Date)

Gary T. Oviatt
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JUL 10 1970

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the completion survey of the subdivisional lines of Township 28 North, Range 21 West, of the Gila and Salt River Meridian, Arizona,

executed by Gary T. Oviatt, having been critically examined and found correct, are hereby approved.

JUN 21 1971
(Date)

Clark L. Lumm
(Chief, Division of Engineering)
Cadastral Survey

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.~~

~~_____
(Date)~~

~~_____
(Chief, Division of Engineering)~~