

BOOK 4903

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

RETRACEMENT

of a

PORTION

of the

NORTH BOUNDARY (SECOND STANDARD PARALLEL SOUTH)

DEPENDENT RESURVEY

of the

EAST AND SOUTH BOUNDARIES

and

SUBDIVISIONAL LINES

SURVEY

of

SUBDIVISIONS in SECTIONS 1, 10, 15 and 31,

TOWNSHIP 11 SOUTH, RANGE 30 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Gary T. Oviatt

Cadastral Surveyor

Under special instructions dated November 20, 19 68, which provided for the surveys included under Group Number 465, approved November 21, 1968, and assignment instructions dated November 21, 19 68.

Survey commenced January 16, 19 69

Survey completed March 13, 19 69

119

BOOK 4903

INDEX DIAGRAM

Township 11 South, Range 30 East

6 5 4 4 3 2

		54	46	37	27
6	5	53 4	45 3	35 2	26 1 12
64	63	52	44	35	25
7	62 8	52 9	43 10	34 11	24 12 11
61	61	51	42	33	24
18	60 17	50 16	41 15	32 14	23 13 10
59	59	50	40	31	22
19	58 20	49 21	40 22	30 23	21 24 9
57	57	48	39	30	21
30	56 29	48 28	38 27	29 26	20 25 8
55	55	47	38	28	19
31	54 32	46 33	37 34	28 35	18 36 6

18 17 16 16 15 14

Subdivision Sec. 1 ---- Page 64
 " Sec. 10 --- Page 65
 " Sec. 15 --- Page 67
 " Sec. 31 --- Page 70

Township 11 South, Range 30 East
Gila and Salt River Meridian, Arizona

CHAINS

The north boundary (the Second Standard Parallel South) was surveyed in 1882 by T. F. White. The south, east and west boundaries were surveyed in 1884 by L. Wolfley. The subdivisional lines were surveyed in 1885 by J. C. Smith. The east boundary was resurveyed in 1916 by A. B. Rich and original corners altered to function for T. 11 S., R. 30 E., only. The north boundary (the Second Standard Parallel South through Range 30 East) was resurveyed in 1920 by Veal Siebecker and original standard corners were altered to function as angle points. A portion of the north boundary (the Second Standard Parallel South in Range 29 East) was resurveyed in 1936 by H. M. Muscott. The west boundary was resurveyed in 1952 by C. E. Bilbray.

The following notes are those of a retracement of a portion of the north boundary (Second Standard Parallel South); a dependent resurvey of the east and south boundaries and subdivisional lines designed to restore the corners in their true original location according to the best available evidence, and a survey of subdivisions in sections 1, 10, 15 and 31, Township 11 South, Range 30 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the Specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated November 20, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 32°25'29" North and Longitude 109°13'38" West, as determined by a traverse made to U.S.F.S. triangulation station ORANGE BUTTE, located in section 1, T. 12 S., R. 30 E.

The mean magnetic declination was found to be: 13° East.

Retracement, Portion South Boundary
(Second Standard Parallel South)
T. 10 S., R. 30 E., G&SRM, Arizona

Retracement of the Survey executed
by Veal Siebecker in 1920

Beginning at the standard ¼ sec. cor. of sec. 36, T. 10 S., R. 30 E., monumented by an iron post 1 in. diam., set in a mound of stone, brass cap mkd.

¼ S C
S36
1920

from which

An angle point, bears N. 89°52' E., 63 lks. dist.,

Retracement, Portion of South Boundary, T. 10 S., R. 30 E.
(Second Standard Parallel South)

CHAINS	
	<p>monumented by a basalt stone, 7 x 7 ins., projecting 7 ins. above the ground, mkd. AP on N. face, mound of stone N.</p> <p>S. 89°52' W., along the S. bdy. of sec. 36.</p> <p>Descend SW. slope of a rocky ridge, bears N. and S.</p>
22.40	Bottom of descent, bears N. and S.; enter nearly level land.
39.32	<p>Angle point, monumented by a basalt stone, 8 x 7 ins., projecting 15 ins. above the ground, mkd. AP on N. face, mound of stone N.</p> <p>S. 89°56' W., continuing measurement.</p>
39.99	The standard cor. of secs. 35 and 36, monumented by an iron post 2 ins. diam., projecting 14 ins. above the ground, brass cap mkd.
	<p>T10S R30E S35 S36 S C 1920</p>
	<p>Land, mountainous to nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>
	<p>S. 89°56' W., along the S. bdy. of sec. 35.</p> <p>Over nearly level land, through moderate undergrowth.</p>
29.30	Jeep road, bears SE. and NW.
39.38	<p>Angle point, monumented by a basalt stone, 7 x 4 ins., projecting 9 ins. above the ground, mkd. AP on S. face, mound of stone N.</p> <p>S. 89°50' W., continuing measurement.</p>
39.90	Fence cor.; fences bear S. 2° E. and W.
40.19	The standard ¼ sec. cor. of sec. 35, monumented by an iron post 1 in. diam., projecting 20 ins. above the ground, brass cap mkd.
	<p>¼ S35 S C 1920</p>
	<p>S. 89°50' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
39.33	<p>Angle point, monumented by a basalt stone, 8 x 4 ins., projecting 8 ins. above the ground, mkd. AP on N. face, mound of stone N.</p> <p>N. 89°58' W., continuing measurement.</p>

Retracement, Portion of South Boundary, T. 10 S., R. 30 E.
(Second Standard Parallel South)

CHAINS		
39.84	<p>The standard cor. of secs. 34 and 35, monumented by an iron post 2 ins. diam., projecting 18 ins. above the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S C T10S R30E <u>S34 S35</u> 1920</p> <p>Land, nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>	
	<p>N. 89°58' W., along the S. bdy. of sec. 34.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
39.61	<p>Angle point, monumented by a basalt stone, 7 x 4 ins., projecting 8 ins. above the ground, mkd. AP on S. face, mound of stone N.</p> <p>N. 89°55' W., continuing measurement.</p>	
40.17	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 34, monumented by an iron post 1 in. diam., projecting 15 ins. above the ground in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ <u>S34</u> SC 1920</p> <p>N. 89°55' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
9.30	<p>Track road, bears NE. and SW.</p>	
12.45	<p>Fence cor.; fences bear N. 3° E. and E.</p>	
21.80	<p>Base of mountain, bears N. and S.; asc. steep E. slope.</p>	
39.43	<p>Angle point, monumented by a basalt stone, 10 x 7 ins., projecting 15 ins. above the ground, mkd. SC on N. face and AP on S. face, mound of stone N.</p> <p>This cor. is located on a SE. slope.</p> <p>N. 89°51' W., continuing measurement.</p>	
39.89	<p>The standard cor. of secs. 33 and 34, monumented by an iron post 2 ins. diam., projecting 24 ins. above the ground in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T10S R30E <u>S33 S34</u> S C 1920</p>	

Retracement, Portion of South Boundary, T. 10 S., R. 30 E.
(Second Standard Parallel South)

CHAINS	
	<p>Land, mountainous. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>N. 89°51' W., along the S. bdy. of sec. 33.</p> <p>Over mountainous land.</p>
0.70	Top of mountain, bears N. and S.; desc. W. slope.
19.00	Base of mountain, bears N. and S.; thence over rolling land, through moderate undergrowth.
39.98	<p>Angle point, monumented by an iron post 1 in. diam., projecting 15 ins. above the ground, mound of stone N., brass cap mkd. AP 1920.</p> <p>West, continuing measurement.</p>
40.07	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented by an iron post 1 in. diam., projecting 12 ins. above the ground, mound of stone N., brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \frac{1}{4} \text{ S C} \\ \hline \text{S33} \\ \hline 1920 \end{array}$ </div> <hr style="width: 20%; margin: auto;"/> <p>West, beginning new measurement.</p>
1.80	Wash, 10 lks. wide, 2 ft. deep, drains S.
16.40	Wash, 20 lks. wide, 2 ft. deep, drains irregularly S.
39.33	<p>Angle point, monumented by an iron post 2 ins. diam., projecting 8 ins. above the ground, brass cap mkd. AP 1920.</p> <p>N. 84°28' W., continuing measurement.</p>
39.98	<p>The standard cor. of secs. 32 and 33, monumented by an iron post 2 ins. diam., projecting 15 ins. above the ground, brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{r} \text{S C} \\ \text{T10S R30E} \\ \hline \text{S32 S33} \\ \hline 1920 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 15° W., 7 lks. dist.; fences bear North and S. 89°30' W.</p> <p>Land, mountainous to rolling. Soil, rocky and sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>S. 89°21' W., along the S. bdy. of sec. 32.</p>

Retracement, Portion of South Boundary, T. 10 S., R. 30 E.
(Second Standard Parallel South)

CHAINS	
	Over rolling land, through moderate undergrowth.
2.80	Wash, 30 lks. wide, 2 ft. deep, drains S. 20° W.
34.30	Wash, 20 lks. wide, 1 ft. deep, drains S.
39.54	Angle point, monumented by an iron post 1 in. diam., projecting 8 ins. above the ground, brass cap mkd.
	$\frac{1}{4} \text{ AP}$ $\frac{\text{S32}}{1920}$
	from which
	A fence cor., bears NW., 10 lks. dist.; fences bear N. 89°30' E. and S. 1°15' W.
	N. 89°21' W., continuing measurement.
39.61	Fence, bears N. 1°15' E. and S. 1°15' W.
40.01	The standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented by an iron post 1 in. diam., projecting 4 ins. above the ground, brass cap mkd.
	$\frac{1}{4}$ $\frac{\text{S32}}{\text{S C}}$ 1920
	<hr style="width: 20%; margin: auto;"/>
	N. 89°21' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
36.50	Wash, 30 lks. wide, 2 ft. deep, drains S. 35° W.
39.43	Angle point, monumented by an iron post 2 ins. diam., projecting 2 ins. above the ground, mkd. AP 1920.
	N. 89°58' W., continuing measurement.
40.13	The standard cor. of secs. 31 and 32, monumented by an iron post 2 ins. diam., projecting 15 ins. above the ground, brass cap mkd.
	S C T10S R30E $\frac{\text{S31} \text{S32}}{1920}$
	Land, rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	<hr style="width: 50%; margin: auto;"/>
	N. 89°58' W., along the S. bdy. of sec. 31.
	Over rolling land, through moderate undergrowth.

Retracement, Portion of South Boundary, T. 10 S., R. 30 E.
(Second Standard Parallel South)

CHAINS

- 19.30 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 39.64 Angle point, monumented by an iron post 1 in. diam., projecting 2 ins. above the ground, mkd. AP 1920.
- N. 89°52' W., continuing measurement.
- 39.98 The standard $\frac{1}{4}$ sec. cor. of sec. 31, monumented by an iron post 1 in. diam., projecting 6 ins. above the ground, brass cap mkd.

$$\begin{array}{r} \text{S C} \\ \frac{1}{4} \text{ S31} \\ \hline 1920 \end{array}$$

N. 89°52' W., beginning new measurement.

Over rolling land, through moderate undergrowth.

- 39.53 The standard cor. of Tp. 10 S., Rs. 29 and 30 E., monumented by an iron post 3 ins. diam., projecting 9 ins. above the ground, and with a wooden post, 4 x 4 ins. square, 4 $\frac{1}{2}$ ft. long, lying alongside, brass cap mkd.

$$\begin{array}{r} \text{S C} \\ \text{T10S} \\ \text{R29E R30E} \\ \text{S36|S31} \\ \text{T11S R30E} \\ \text{S 6} \\ 1920 \end{array}$$

from which

The remains of orig. bearing tree, a mesquite, bears N. 59 $\frac{1}{2}$ ° E., 8 lks. dist., with a limb lying on the ground with scribe mks. visible but not legible.

Remains of a cat claw, bears N. 25 $\frac{1}{2}$ ° W., 36 lks. dist., no visible mks.

Reset the wooden post 4 x 4 ins. square, 4 $\frac{1}{2}$ ft. long, 2 lks. N. of the iron post.

Land, rolling.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

Dep. Res., East Boundary, T. 11 S., R. 30 E.

Reestablishment of the Survey executed
by A. B. Rich in 1916

The cor. of Tps. 11 and 12 S., R. 30 E. only, monumented by a granite stone, 19 x 16 x 8 ins., set 6 ins. in the

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS																						
	<p>ground, mkd. with 6 notches on S. and W. edges, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T11S</td><td></td></tr> <tr><td>R30E</td><td>R31E</td></tr> <tr><td>S36</td><td>S 6</td></tr> <tr><td><u>S 1</u></td><td></td></tr> <tr><td>T12S</td><td></td></tr> <tr><td>1969</td><td></td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">U.S.F.S. Triangulation Station ORANGE BUTTE, bears S. 43°47' W., 86.42 chs. dist., monumented by a brass tablet, 3 ins. diam., set in a drill hole in a rock in place, mkd. ORANGE BUTTE 19.</p> <p>Bury the orig. cor. alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>N. 0°20' E., along the E. bdy. of sec. 36.</p> <p>Over mountainous land; asc. SE. slope.</p>	T11S		R30E	R31E	S36	S 6	<u>S 1</u>		T12S		1969										
T11S																						
R30E	R31E																					
S36	S 6																					
<u>S 1</u>																						
T12S																						
1969																						
8.79	<p>The closing cor. of Tps. 11 and 12 S., R. 31 E., monumented by an iron post 3 ins. diam., projecting 14 ins. above the ground, set in a mound of stone, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T11S</td><td></td></tr> <tr><td>T11S</td><td>R31E</td><td></td></tr> <tr><td>S36</td><td>S31</td><td>C</td></tr> <tr><td></td><td><u>S 6</u></td><td>C</td></tr> <tr><td>R30E</td><td>T12S</td><td></td></tr> <tr><td></td><td>R31E</td><td></td></tr> <tr><td></td><td>1916</td><td></td></tr> </table> </div>		T11S		T11S	R31E		S36	S31	C		<u>S 6</u>	C	R30E	T12S			R31E			1916	
	T11S																					
T11S	R31E																					
S36	S31	C																				
	<u>S 6</u>	C																				
R30E	T12S																					
	R31E																					
	1916																					
15.00	Rocky spur, slopes SE.; desc. NE. slope.																					
23.80	Gulch, drains SE.; asc. SE. slope.																					
26.00	Spur, slopes SE.; desc. NE. slope.																					
29.30	Gulch, drains SE.; asc. SE. slope.																					
42.31	<p>The ¼ sec. cor. of sec. 36 only, monumented by a granite stone, 14 x 14 x 9 ins., set 4 ins. in the ground, mkd. ¼ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 4 ins. in the ground, over an X chiseled in solid rock, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T11S</td><td></td></tr> <tr><td>R30E</td><td>R31E</td><td></td></tr> <tr><td></td><td>¼</td><td></td></tr> <tr><td>S36</td><td></td><td></td></tr> <tr><td></td><td>1969</td><td></td></tr> </table> </div>		T11S		R30E	R31E			¼		S36				1969							
	T11S																					
R30E	R31E																					
	¼																					
S36																						
	1969																					

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS	
	<p>Deposit the orig. cor. stone in the mound around the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p> <p>Over mountainous land.</p>
1.80	Rocky spur, slopes SE.; desc. NE. slope.
39.71	<p>The cor. of secs. 25 and 36 only, monumented by a granite stone, 16 x 14 x 9 ins., set 11 ins. in the ground, mkd. with 5 notches on N. and 1 notch on S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11S R30E R31E S25 S31 S36 1969</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, mountainous. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p> <hr style="width: 80%; margin: 10px auto;"/>
	<p>N. 0°24' W., along the E. bdy. of sec. 25.</p> <p>Over mountainous land.</p>
6.93	<p>The closing cor. of secs. 30 and 31, monumented by an iron post 2 ins. diam., projecting 12 ins. above the ground, mound of stone E., brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11S T11S S25 S30 C S31 C R30E R31E 1916</p> </div>
7.40	Wash at base of mountain, 10 lks. wide, 2 ft. deep, drains NW.; thence over gently rolling land.
16.80	Track road, bears S. 75° E. and N. 75° W.
24.20	Wash, 30 lks. wide, 2 ft. deep, drains N. 60° W.
28.20	Wash, 50 lks. wide, 3 ft. deep, drains N. 60° W.
34.80	Track road, bears S. 60° E. and N. 60° W.
39.80	Wash, 30 lks. wide, 4 ft. deep, drains W.

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS	
40.38	<p>The $\frac{1}{4}$ sec. cor. of sec. 25 only, monumented by a basalt stone, 18 x 12 x 10 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E R31E $\frac{1}{4}$ S25 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p>
14.40	<p>Wash, 20 lks. wide, 2 ft. deep, drains S. 70° W.</p>
40.17	<p>The cor. of secs. 24 and 25 only, monumented by a basalt stone, 23 x 9 x 6 ins., set 14 ins. in the ground, mkd. with 4 notches on N. and 2 notches on S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E R31E S24 S30 S25 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
0.30	<p>N. 0°07' E., along the E. bdy. of sec. 24.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains W.</p>
6.32	<p>The closing cor. of secs. 19 and 30, monumented by an iron post 2 ins. diam., projecting 12 ins. above the ground, mound of stone E., brass cap mkd.</p> <p style="text-align: center;">T11S R30E R31E S24 S19 CC S30 1916</p>

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS	
40.24	<p>The ¼ sec. cor. of sec. 24 only, monumented by a basalt stone, 15 x 8 x 5 ins., set 10 ins. in the ground, mkd. ¼ on W. face, mound of stone W.</p>
	<p>At the corner point</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E R31E ¼ S24 1969</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Raise a mound of stone W. of the corner.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 0°18' W., beginning new measurement.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
3.50	<p>Track road, bears N. 60° E. and S. 60° W.</p>
20.80	<p>Wash, 10 lks. wide, 3 ft. deep, drains W.</p>
40.22	<p>The cor. of secs. 13 and 24 only, monumented by a basalt stone, 12 x 8 x 7 ins., set 6 ins. in the ground, mkd. with 3 notches on N. and S. faces, mound of stone W.</p>
	<p>At the corner point</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E R31E S13 S19 S24 1969</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Raise a mound of stone W. of the corner.</p>
	<p>Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<hr/> <p>N. 0°01' W., along the E. bdy. of sec. 13.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
5.94	<p>The closing cor. of secs. 18 and 19, monumented by an iron post 2 ins. diam., projecting 14 ins. above the ground, mound of stone E., brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E R31E S13 S18 C C S19 1916</p>

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS	
13.30	Wash, 20 lks. wide, 4 ft. deep, drains W.
22.20	Wash, 30 lks. wide, 5 ft. deep, drains W.
39.80	Wash, 20 lks. wide, 2 ft. deep, drains W.
40.06	The 1/4 sec. cor. of sec. 13 only, monumented by an iron post, 1 in. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd. 1/4 S13 1916.
<hr/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	
6.90	Track road, bears N. 60° E. and S. 60° W.
40.05	The cor. of secs. 12 and 13 only, monumented by a basalt stone, 11 x 7 x 4 ins., set 4 ins. in the ground, mkd. with 2 notches on N. and 4 notches on S. faces, mound of stone W.
<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
<p>T11S R30E R31E S12 S18 S13 1969</p>	
<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote, cacti, cat claw and grass.</p>	
<hr/> <p>N. 0°06' W., along the E. bdy. of sec. 12.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
5.88	The closing cor. of secs. 7 and 18, monumented by an iron post 2 ins. diam., projecting 14 ins. above the ground, mound of stone E., brass cap mkd.
<p>T11S R30E R31E S12 S 7 C S18 C 1916</p>	
25.80	Track road, bears SE. and NW.
29.50	Wash, 20 lks. wide, 4 ft. deep, drains N. 75° W.
40.17	The 1/4 sec. cor. of sec. 12 only, monumented by a basalt stone, 16 x 8 x 4 ins., set 5 ins. in the ground, mkd. 1/2 on W. face, mound of stone W.

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS		
40.05	<p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11S R30E R31E 1/4 S12 1969</p> <p>Deposit the orig. cor. stone alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 0°14' E., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>The cor. of secs. 1 and 12 only, monumented by a basalt stone, 16 x 10 x 10 ins., set 6 ins. in the ground, mkd. with 1 notch on N. and 5 notches on S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11S R30E R31E S 1 S 7 S12 1969</p> <p>Deposit the orig. cor. stone in the mound around the iron post.</p> <p>Land, nearly level to rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	
2.80	<p>N. 0°19' E., along the E. bdy. of sec. 1.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Spur, slopes W.</p>	
5.70	<p>The closing cor. of secs. 6 and 7., monumented by an iron post 2 ins. diam., projecting 14 ins. above the ground, mound of stone E., brass cap mkd.</p> <p style="text-align: center;">T11S R30E R31E S 1 S 6 C S 7 S 7 C 1916</p>	
35.50	<p>Track road, bears N. 70° E. and S. 70° W.</p>	
40.03	<p>The 1/2 sec. cor. of sec. 1 only, monumented by a basalt stone, 19 x 10 x 6 ins., set 12 ins. in the ground, mkd. 1/2 on W. face, mound of stone W.</p>	

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T11S
R30E R31E
1/4 |
S 1 |
1969

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the corner.

N. 0°55' W., beginning new measurement.

Over rolling land, through moderate undergrowth.

9.50 Wash, in Sands Draw, 200 lks. wide, with 4 ft. banks, drains N. 80° W.

19.50 Ascend SW. slope of mountain, bearing N. and S.

20.21 Point for the N 1/16 sec. cor. of sec. 1 only, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S
R30E R31E
N 1 |
16 |
S 1 |
1969

Raise a mound of stone W. of the corner.

22.30 Fence, bears E. and W.

41.94 Intersect the Second Standard Parallel South.

The closing cor. of Tp. 11 S., Rs. 30 and 31 E., monumented by a basalt stone, 13 x 12 x 7 ins., set 6 ins. in the ground, mkd. with 6 notches on E., S. and W. faces and CC on S. face.

At the corner point

Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.

T10S
S36

S 1 | S 6
C C
R30E R31E
T11S
1969

from which

The standard 1/4 sec. cor. of sec. 36, T. 10 S., R. 30 E., bears S. 89°52' W., 6 lks. dist., hereinbefore described.

Dep. Res., East Boundary, T. 11 S., R. 30 E.

CHAINS		
	<p>An angle point, bears N. 89°52' E., 57 lks. dist., hereinbefore described.</p> <p>Deposit the orig. cor. in the mound around the iron post.</p> <p>Raise a mound of stone S. of the corner.</p> <p>Land, rolling to mountainous. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	
	<p>Dependent Resurvey, South Boundary Township 11 South, Range 30 East.</p>	
	<p>Reestablishment of the Survey executed by L. Wolfley in 1884</p> <hr/> <p>From the cor. of Tps. 11 and 12 S., R. 30 E. only, on E. bdy. of Tp.</p> <p>N. 89°02' W., bet. secs. 1 and 36.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>39.98 The ½ sec. cor. of secs. 1 and 36, monumented by a volcanic rock, 10 x 8 x 8 ins., set 4 ins. in the ground, mkd. ½ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ½ <u>S36</u> S 1 T12S 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p> <hr/> <p>N. 89°45' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>19.30 Wash, 100 lks. wide, 6 ft. banks, drains NW.</p> <p>40.20 The cor. of secs. 1, 2, 35 and 36, monumented by a volcanic rock, 14 x 7 x 7 ins., set 3 ins. in the ground, mkd. with 1 notch on E. and 5 notches on W. faces, mound of stone W.</p> <p>At the corner point</p>	

Dep. Res., South Boundary, T. 11 S., R. 30 E.

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{S35}{S2} \frac{S36}{S1}$ T12S 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw, mesquite and grass.</p>
	<p>N. 89°29' W., bet. secs. 2 and 35.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Ascend NE. slope of a spur, sloping N.</p>
20.00	<p>Top of spur, slopes N.; desc. NW. slope.</p>
40.97	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, monumented by an unmkd. volcanic rock, 20 x 6 x 4 ins., set 10 ins. in the ground with mound of stone N.</p>
	<p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4} \frac{S35}{S2}$ T12S 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p>
	<p>N. 89°20' W., beginning new measurement.</p> <p>Descend W. slope.</p>
5.20	<p>Bottom of slope; thence over nearly level land.</p>
40.16	<p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{S34}{S3} \frac{S35}{S2}$ T12S 1969</p>

Dep. Res., South Boundary, T. 11 S., R. 30 E.

CHAINS	
40.16	<p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling to nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw, mesquite and grass.</p> <hr/> <p>N. 89°20' W., bet. secs. 3 and 34.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The ½ sec. cor. of secs. 3 and 34, monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, mound of stone N., brass cap mkd.</p> $\frac{1}{2} \frac{S34}{S 3}$ <p style="text-align: center;">1952</p> <hr/> <p>N. 89°07' W., beginning new measurement.</p> <p>Over nearly level land.</p>
29.50	Wash, 20 lks. wide, 3 ft. deep, drains NW.
36.40	Center of a catch pond, 2.50 chs. long, 1.80 chs. wide.
37.30	Center of a dyke, 2.50 chs. long, bears NE. and SW.
40.08	<p>The cor. of secs. 3, 4, 33 and 34, monumented by a volcanic rock, 12 x 5 x 4 ins., loosely set in a mound of stone, dimly mkd. with 3 notches on one side, and with a wooden post 4 x 4 ins. square, 3 ft. long, alongside.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p> $\begin{array}{r} T11S R30E \\ \hline S33 S34 \\ S 4 S 3 \\ \hline T12S \\ 1969 \end{array}$
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Reset the wooden post alongside the corner.</p> <p>Land, level. Soil, rocky clay loam No timber; Undergrowth, creosote bush, cacti, cat claw, mesquite and grass.</p>
	<hr/> <p>N. 89°16' W., bet. secs. 4 and 33.</p> <p>Over level land, through moderate undergrowth.</p>

Dep. Res., South Boundary, T. 11 S., R. 30 E.

CHAINS

- 12.40 Track road, bears S. 60° E. and N. 60° W.
- 39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
- Set the iron post 24 ins. in the ground, brass cap mkd.
- $$\begin{array}{r} T11S R30E \\ \frac{1}{4} \frac{S33}{S 4} \\ T12S \\ 1969 \end{array}$$
- Set a wooden post 2 x 4 ins. squared, 4 ft. long, alongside the iron post.
- 79.97 Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.
- Set the iron post 24 ins. in the ground, brass cap mkd.
- $$\begin{array}{r} T11S R30E \\ \frac{S32}{S 5} | \frac{S33}{S 4} \\ T12S \\ 1969 \end{array}$$
- Set a wooden post 4 x 6 ins. squared, 4 ft. long, alongside the iron post.
- Land, level to gently rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw, mesquite and grass.
-
- N. 89°16' W., bet. secs. 5 and 32.
- Over gently rolling land, through moderate undergrowth.
- 39.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
- Set the iron post 24 ins. in the ground, brass cap mkd.
- $$\begin{array}{r} T11S R30E \\ \frac{1}{4} \frac{S32}{S 5} \\ T12S \\ 1969 \end{array}$$
- Set a wooden post 2 x 4 ins. squared, 3 ft. long, alongside the iron post.
- 79.97 Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
- Set the iron post 24 ins. in the ground, brass cap mkd.
- $$\begin{array}{r} T11S R30E \\ \frac{S31}{S 6} | \frac{S32}{S 5} \\ T12S \\ 1969 \end{array}$$

Dep. Res., South Boundary, T. 11 S., R. 30 E.

CHAINS

Set a wooden post 4 x 4 ins. square, 5 ft. long, alongside the iron post.

Land, gently rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw, mesquite and grass.

N. 89°16' W., bet. secs. 6 and 31.

Over gently rolling land, through moderate undergrowth.

32.10 Fence, bears N. and S.

39.99 Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 22 ins. in the ground, brass cap mkd.

T11S R30E

$\frac{1}{4}$ $\frac{S31}{S 6}$

T12S
1969

Set a 1 x 6 in. board, 4 ft. long, alongside the iron post.

76.30 Track road, bears N. and S.

76.60 Fence, bears N. and S.

77.39 The cor. of Tps. 11 and 12 S., Rs. 29 and 30 E., monumented by an iron post 2 $\frac{1}{2}$ ins. diam., projecting 4 ins. above the ground, with a wooden post 4 x 4 ins. square alongside, brass cap mkd.

T11S
R29E R30E
 $\frac{S36}{S 1} | \frac{S31}{S 6}$
T12S
1952

Land, gently rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw, mesquite and grass.

Dependent Resurvey, Subdivisional Lines
Township 11 South, Range 30 East

Reestablishment of the Survey executed
by J. C. Smith in 1885

During this resurvey of the subdivisional lines, in certain areas, two monuments were found which referred

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>to the same corner. Only one survey is of record. Corners accepted are harmoniously related to other corners set by Smith in 1885. The origin of the second set of corner monuments is not known.</p>
	<p>From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp.</p>
	<p>N. 2°07' W., bet. secs. 35 and 36.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
18.70	<p>Wash, 50 lks. wide, 4 ft. banks, drains N. 30° W.</p>
40.52	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E $\frac{1}{2}$ S35 S36 1969</p>
	<p>Set a wooden post 2 x 4 ins. squared, 5 ft. long, alongside the iron post.</p>
52.40	<p>Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.</p>
81.04	<p>The cor. of secs. 25, 26, 35 and 36, monumented by a malpais stone, 19 x 10 x 5 ins., lying loose on the ground, mkd. with 1 notch on each of two faces.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E S26 S25 S35 S36 1969</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Raise a mound of stone W. of the corner.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, sandy clay loam.</p>
	<p>No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp.</p>
	<p>S. 89°55' W., bet. secs. 25 and 36.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
4.20	<p>Spur, slopes N.; desc. W. slope.</p>
15.00	<p>Bottom of descent, bears N. and S.; thence over gently rolling land.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

<p>CHAINS 41.20</p>	<p>Wash, 5 lks. wide, 1 ft. deep, drains NW.</p>						
<p>41.70</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R30E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">$\frac{1}{4}$</td> <td style="padding-left: 5px;">S25</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">S36</td> </tr> </table> <p>1969</p> </div> <p>Raise a mound of stone N. of the corner.</p>	$\frac{1}{4}$	S25		S36		
$\frac{1}{4}$	S25						
	S36						
<p>83.40</p>	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling to gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>N. 2°21' E., bet. secs. 25 and 26.</p> <p>Over gently rolling land, through moderate undergrowth.</p>						
<p>5.20</p>	<p>Wash, 20 lks. wide, 2 ft. deep, drains SW.</p>						
<p>17.50</p>	<p>Track road, bears N. 80° E. and S. 80° W.</p>						
<p>29.80</p>	<p>Ascend SW. slope of a round knoll.</p>						
<p>40.71</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R30E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">$\frac{1}{4}$</td> <td style="padding-left: 5px;">S26</td> <td style="padding-left: 5px;">S25</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;"></td> <td style="padding-left: 5px;"></td> </tr> </table> <p>1969</p> </div> <p>Raise a mound of stone W. of the corner.</p>	$\frac{1}{4}$	S26	S25			
$\frac{1}{4}$	S26	S25					
<p>44.20</p>	<p>Spur, slopes NW.; desc. NW. slope.</p>						
<p>54.00</p>	<p>Bottom of descent; continue over gently rolling land.</p>						
<p>81.43</p>	<p>The cor. of secs. 23, 24, 25 and 26, monumented by a malpais stone, 13 x 9 x 7 ins., loosely set in a mound of stone, mkd. with 2 notches on one face and 1 notch on another face.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R30E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S23</td> <td style="padding-left: 5px;">S24</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S26</td> <td style="padding-left: 5px;">S25</td> </tr> </table> <p>1969</p> </div>	S23	S24	S26	S25		
S23	S24						
S26	S25						

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cat claw, cacti and grass.</p>
	<p>From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp.</p> <p>N. 89°28' W., bet. secs. 24 and 25.</p> <p>Over nearly level land, through moderate undergrowth.</p>
39.92	<p>Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ¼ $\frac{S24}{S25}$ 1969</p>
51.60	Track road, bears SE. and NW.
54.00	Wash, 10 lks. wide, 2 ft. deep, drains NW.
65.20	Wash, 100 lks. wide, 2 ft. deep, drains N. 30° W.
79.84	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>N. 0°13' W., bet. secs. 23 and 24.</p> <p>Over nearly level land, through moderate undergrowth.</p>
9.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.
14.20	Wash, 70 lks. wide, 4 ft. deep, drains W.
18.55	Track road, bears N. 80° E. and S. 80° W.
39.21	<p>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ¼ $\frac{S23}{S24}$ 1969</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS					
	<p>from which</p> <p>A monument of unknown origin, bears N. 12°37' W., 8.51 chs. dist., a malpais stone, 16 x 9 x 7 ins., set 6 ins. in the ground, mkd. ¼ on N. face, mound of stone W.</p> <p>Raise a mound of stone W. of the corner.</p>				
49.80	Wash, 10 lks. wide, 2 ft. deep, drains W.				
75.90	Wash, 20 lks. wide, 1 ft. deep, drains W.				
78.43	<p>The cor. of secs. 13, 14, 23 and 24, monumented by a lava stone, 11 x 9 x 5 ins., set 4 ins. in the ground, mkd. with 3 notches on S. and 1 notch on E. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R30E</p> <table border="1" style="margin: auto;"> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> </table> <p>1969</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	S14	S13	S23	S24
S14	S13				
S23	S24				
	<p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp.</p> <p>S. 88°26' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through moderate undergrowth.</p>				
7.20	Spur, slopes NW.; desc. W. slope.				
18.00	Bottom of descent; enter gently rolling land, bears SE. and NW.				
39.70	<p>The ¼ sec. cor. of secs. 13 and 24, monumented by a lava stone, 14 x 10 x 6 ins., set 7 ins. in the ground, mkd. ¼ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R30E</p> <table border="1" style="margin: auto;"> <tr> <td>¼ S13</td> </tr> <tr> <td>S24</td> </tr> </table> <p>1969</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p>	¼ S13	S24		
¼ S13					
S24					

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>S. 89°42' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
16.30	Track road, bears NE. and SW.
20.60	Wash, 30 lks. wide, 2 ft. deep, drains SW.
40.29	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, rolling to gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>N. 0°13' E., bet. secs. 13 and 14.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
23.00	Wash, 10 lks. wide, 2 ft. deep, drains W.
33.10	Track road, bears NE. and SW.
41.38	The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented by a malpais stone, 16 x 6 x 5 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.
	<p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S14 S13 1969</p> <p>Deposit the orig. cor. stone alongside the iron post.</p>
	<p>N. 0°39' E., beginning new measurement.</p> <p>Over gently rolling land.</p>
9.00	Wash, 10 lks. wide, 2 ft. deep, drains NW.
18.15	Track road, bears N. 70° E. and S. 30° W.
31.50	Wash, 20 lks. wide, 3 ft. deep, drains W.
39.42	The cor. of secs. 11, 12, 13 and 14, monumented by a malpais stone, 11 x 7 x 5 ins., lying loose on the ground, mkd. with 4 notches on one face and 1 notch on another face, mound of stone W.
	<p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S11 S12 S14 S13 1969</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS		
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	
	<p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp.</p> <p>S. 89°35' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	
19.10	Wash, 10 lks. wide, 2 ft. deep, drains NW., from S. 60° E.	
39.67	Point for the ½ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{2}$ $\frac{S12}{S13}$ 1969</p>	
	<p>Raise a mound of stone N. of the corner.</p>	
46.00	Track road, bears S. 60° E and N. 60° W.	
58.70	Same road, bears N. 80° E. and S. 80° W.	
62.40	Same road, bears irregularly E.	
79.34	The cor. of secs. 11, 12, 13 and 14.	
	<p>Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti and grass.</p>	
	<p>N. 1°00' E., bet. secs. 11 and 12.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	
14.80	Wash, 20 lks. wide, 3 ft. deep, drains W.	
25.70	Wash, 30 lks. wide, 3 ft. deep, drains W.	
40.58	The ½ sec. cor. of secs. 11 and 12, monumented by a malpais stone, 10 x 7 x 4 ins., set 4 ins. in the ground, mkd. ½ on W. face, mound of stone W.	
	<p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{2}$ $\frac{S11}{S12}$ 1969</p>	

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS					
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E , beginning new measurement.</p> <p>Over nearly level land.</p> <p>22.60 Track road, bears NE. and SW.</p> <p>39.93 The cor. of secs. 1, 2, 11 and 12, monumented by a malpais stone, 13 x 8 x 6 ins., set 7 ins. in the ground, mkd. with 5 notches on S. and 1 notch on E. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11S R30E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S11</td> <td style="padding: 0 5px;">S12</td> </tr> </table> <p>1969</p> </div> <p>from which</p> <p style="margin-left: 40px;">A monument of unknown origin, bears N. 0°24' W., 9.20 chs. dist., monumented by a malpais stone, 12 x 10 x 2 ins., loosely set 2 ins. in the ground, mound of stone W.</p> <p style="margin-left: 40px;">A windmill, bears S. 60°43' E., 14.08 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling to level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	S 2	S 1	S11	S12
S 2	S 1				
S11	S12				
	<hr style="width: 50%; margin: 10px auto;"/> <p>From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp.</p> <p>N. 89°02' W., bet. secs. 1 and 12.</p> <p>Descend W. slope, through moderate undergrowth.</p> <p>18.00 Base of descent, bears N. and S.; enter nearly level land</p> <p>38.54 The ½ sec. cor. of secs. 1 and 12, monumented by a malpais stone, 13 x 8 x 4 ins., set 4 ins. in the ground, mkd. ½ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11S R30E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">½ S 1</td> <td style="padding: 0 5px;">S12</td> </tr> </table> <p>1969</p> </div>	½ S 1	S12		
½ S 1	S12				

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>from which</p> <p>A monument of unknown origin, bears North, 9.41 chs. dist., monumented by a malpais stone, 16 x 9 x 8 ins., set in a mound of stone, malpais stone mkd. $\frac{1}{2}$ on N. face.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p> <hr/> <p>S. 88°40' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>8.70 Track road, bears SE. and N. 30° W.</p> <p>13.10 Track road, bears N. 50° E. and SW.</p> <p>39.60 Track road, bears S. 50° E. and N. 50° W.</p> <p>40.15 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling to level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>N. 0°15' W., bet. secs. 1 and 2.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>0.50 Track road, bears S. 50° E. and N. 50° W.</p> <p>40.25 The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented by a malpais stone, 16 x 9 x 9 ins., set 6 ins. in the ground, mkd. $\frac{1}{2}$ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S 2 S 1 1969</p> <p>from which</p> <p>A monument of unknown origin, bears N. 0°58' W., 9.20 chs. dist., monumented by a malpais stone, 9 x 8 x 8 ins., above ground, mkd. $\frac{1}{2}$ on W. face, mound of stone W.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <hr/>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

N. 2°06' W., beginning new measurement.

Over nearly level land.

25.40 Wash, 20 lks. wide, 5 ft. banks, drains W. (Sands Draw)

38.90 Fence cor.; fences bear E. and N. 2° W.

41.87 Intersect the Second Standard Parallel South.

The closing cor. of secs. 1 and 2, monumented by a basalt stone, 13 x 10 x 7 ins., set 6 ins. in the ground, mkd. with 1 notch on E. and 5 notches on W. faces and CC on S. face, mound of stone S.

At the corner point

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T10S
S35

S 2 | S 1
T11S R30E
C C
1969

from which

The standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 10 S., R. 30 E., bears S. 89°50' W., 27 lks. dist., hereinbefore described.

An angle point, bears N. 89°50' E., 54 lks. dist., hereinbefore described.

Fence cor., bears NE., 2 lks. dist.; fences bear S. 2° E. and W.

Deposit the orig. cor. stone alongside the iron post.

Land, nearly level.

Soil, rocky clay loam.

No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

The point for the $\frac{1}{4}$ sec. cor. of sec. 1 is on the N. bdy. and at mid-point bet. the closing cors.

Set the iron post 24 ins. in the ground, brass cap mkd.

$\frac{1}{4}$ S 1
T11S R30E
1969

from which

The standard cor. of secs. 35 and 36, T. 10 N., R. 30 E., bears S. 89°56' W., 7 lks. dist., hereinbefore described.

An angle point, bears N. 89°56' E., 60 lks. dist., hereinbefore described.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	Raise a mound of stone S. of the corner.
	From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp. N. 0°58' W., bet. secs. 34 and 35. Over gently rolling land, through moderate undergrowth.
5.10	Wash, 20 lks. wide, 1 ft. deep, drains W.
23.00	Wash, 10 lks. wide, 2 ft. deep, with 5 ft. banks, drains irregularly W.
39.40	Wash, 10 lks. wide, 2 ft. deep, drains W.
40.39	Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T11S R30E $\frac{1}{4}$ S34 S35 1969 </div> from which A monument of unknown origin, bears N. 1°33' W., 8.36 chs. dist., monumented by a malpais stone, $\frac{1}{2}$ 2 x 8 x 7 ins., set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.
	Raise a mound of stone W. of the corner.
58.70	Wash, 70 lks. wide, 2 ft. deep, drains S. 80° W.
80.78	The cor. of secs. 26, 27, 34 and 35, monumented by a malpais stone, 12 x 7 x 5 ins., loosely set, mkd. with 2 notches on E. and 1 notch on S. faces. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T11S R30E S27 S26 S34 S35 1969 </div> Bury the orig. cor. stone alongside the iron post. Set a wooden post 3 ins. diam., 3 ft. long, alongside the iron post. Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	From the cor. of secs. 25, 26, 35 and 36.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
39.99	<p>N. 86°38' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented by a malpais stone, 16 x 8 x 7 ins., set 4 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ $\frac{S26}{S35}$ 1969</p> <p>from which</p> <p style="padding-left: 40px;">Center of a circular catch pond, bears S. 67°13' E., 16.40 chs. dist.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p>
39.55	<p style="text-align: center;">—————</p> <p>S. 87°26' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
11.70	<p>N. 0°08' W., bet. secs. 26 and 27.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Wash, 30 lks. wide, 1 ft. deep, drains N. 75° W.</p>
40.79	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S27 S26 1969</p>
81.58	<p>Raise a mound of stone W. of the corner.</p> <p>The cor. of secs. 22, 23, 26 and 27, monumented by a malpais stone, 19 x 13 x 6 ins., firmly set in a mound of stone, mkd. with 2 notches on E. and S. faces.</p> <p>At the corner point</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{S22}{S27} \frac{S23}{S26}$ 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
42.53	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 88°32' W., bet. secs. 23 and 26.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented by a malpais stone, 13 x 8 x 4 ins., lying loose on the ground, mkd. $\frac{1}{4}$ on one face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4} \frac{S23}{S26}$ 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p>
40.49	<p>N. 87°17' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
24.80	<p>N. 1°39' E., bet. secs. 22 and 23.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains W.</p>
39.94	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S22 S23 1969</p> <p>Set a wooden post 4 ins. diam., 4 ft. long, alongside the iron post.</p> <p>56.60 Track road, bears S. 60° E. and N. 60° W.</p> <p>70.30 Wash, 40 lks. wide, 1 ft. deep, drains NW.</p> <p>79.88 The cor. of secs. 14, 15, 22 and 23, monumented by a malpais stone, 12 x 8 x 7 ins., set 12 ins. in the ground, mkd. with 2 notches on E. and 3 notches on S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S15 S14 S22 S23 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, nearly level. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<hr/> <p>From the corner of secs. 13, 14, 23 and 24.</p> <p>N. 88°18' W., bet. secs. 14 and 23.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>19.00 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.</p> <p>39.92 The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented by a lava stone, 12 x 6 x 6 ins., set 4 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S14 S23 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p> <hr/>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	N. 88°26' W., beginning new measurement. Over nearly level land.
16.90	Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W.
40.46	The cor. of secs. 14, 15, 22 and 23. Land, nearly level. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	N. 0°14' E., bet. secs. 14 and 15. Over nearly level land, through moderate undergrowth.
11.10	Track road, bears N. 40° E. and S. 40° W.
20.15	Point for the S 1/16 sec. cor. of secs. 14 and 15, at proportionate dist. Set the iron post 24 ins. in the ground, brass cap mkd. T11S R30E S 1/16 S15 S14 1969
	Raise a mound of stone W. of the corner.
20.70	Track road, bears SE. and NW.
38.70	Wash, 50 lks. wide, 2 ft. deep, drains S. 60° W.
40.30	The 1/4 sec. cor. of secs. 14 and 15, monumented by a malpais stone, 14 x 10 x 5 ins., lying loose on the ground, mkd. 1/4 on one face, mound of stone W. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd. T11S R30E 1/4 S15 S14 1969
	Bury the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the corner.
	N. 0°10' W., beginning new measurement. Over nearly level land.
14.70	Track road, bears N. 80° E. and S. 80° W.
20.00	Point for the N 1/16 sec. cor. of secs. 14 and 15, at proportionate dist.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
40.00	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E N 1/16 S15 S14 1969</p> <p>Raise a mound of stone W. of the corner.</p> <p>The cor. of secs. 10, 11, 14 and 15, monumented by a malpais stone, 9 x 7 x 6 ins., set 4 ins., in the ground, mkd. with 2 notches on E. and 4 notches on S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S10 S11 S15 S14 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, nearly level. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
21.40 25.50 27.20 35.00 39.91	<hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88°24' W., bet. secs. 11 and 14.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Wash, 20 lks. wide, 5 ft. banks, drains SW. for 2.30 chs., thence drains W.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains W.</p> <p>Leave wash, drains SW.</p> <p>Track road, bears N. 30° E. and S. 30° W.</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented by a lava stone, 10 x 8 x 6 ins., set 3 ins. in the ground, mkd. 1/4 on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E 1/4 S11 S14 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS		
41.05	<p>Raise a mound of stone N. of the corner.</p> <hr/> <p>N. 89°02' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, nearly level. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	
9.85	<p>N. 0°28' E., bet. secs. 10 and 11.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Track road, bears N. 80° E. and S. 80° W.</p>	
40.04	<p>The ½ sec. cor. of secs. 10 and 11, monumented by a malpais stone, 14 x 8 x 4 ins., lying loose on the ground, mkd. ½ on one face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ½ S10 S11 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p>	
40.16	<p>N. 0°58' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 2, 3, 10 and 11, monumented by a malpais stone, 9 x 9 x 6 ins., set 3 ins. in the ground, mkd. with 2 notches on E. and 5 notches on S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S 3 S 2 S10 S11 1969</p> <p>from which</p> <p>A monument of unknown origin, bears N. 2°49' W., 8.15 chs. dist., monumented by a malpais stone, 17 x 7 x 6 ins., lying loose on the ground, mkd. with 2 notches on one face and 5 notches on S. face.</p>	

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
40.00	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°54' W., bet. secs. 2 and 11.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The ¼ sec. cor. of secs. 2 and 11, monumented by a malpais stone, 9 x 8 x 4 ins., set 3 ins. in the ground, mkd. ¼ on N. face, mound of stone NE.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ¼ $\frac{S\ 2}{S11}$ 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p> <hr/> <p>N. 87°45' W., beginning new measurement.</p> <p>Over nearly level land.</p>
40.68	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>N. 0°59' W., bet. secs. 2 and 3.</p> <p>Over level land, through moderate undergrowth.</p>
39.99	<p>The ¼ sec. cor. of secs. 2 and 3, monumented by a malpais stone, 14 x 12 x 4 ins., lying loose on the ground, mkd. ¼ on one face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ¼ S 3 S 2 1969</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

from which

A monument of unknown origin, bears N. 1°20' W., 8.37 chs. dist., monumented by a malpais stone, 18 x 10 x 10 ins., set 3 ins. in the ground, mkd. ½ on S. face, mound of stone W.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the corner.

N. 0°43' W., beginning new measurement.

Over level land.

0.25 Track road, bears E. and W.

23.20 Enter wash area, bears E. and W. (Sands Draw)

29.70 Main channel, 60 lks. wide, 2 ft. deep, drains N. 80° W.

32.00 Leave wash area, bears E. and N. 80° W.

40.46 Intersect the Second Standard Parallel South.

The closing cor. of secs. 2 and 3, monumented by a basalt stone, 20 x 11 x 11 ins., set 6 ins. in the ground, mkd. with 2 notches on E. and 4 notches on W. faces, and CC on S. face, mound of stone S.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T10S
S 34
S 3 | S 2
T11S R30E
C C
1969

from which

The standard ¼ sec. cor. of sec. 34, T. 10 S., R. 30 E., bears N. 89°55' W., 12 lks. dist., hereinbefore described.

An angle point, bears S. 89°55' E., 44 lks. dist., hereinbefore described.

The cor. is located 3 lks. S. of an E. and W. fence.

Raise a mound of stone S. of the corner.

Land, level.

Soil, rocky clay loam.

No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 2 is on the N. bdy. at mid-point bet. the closing cors.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 2 T11S R30E 1969 </p> <p>from which</p> <p style="padding-left: 40px;">The standard cor. of secs. 34 and 35, T. 10 S., R. 30 E., bears N. $89^{\circ}58'$ W., 3 lks. dist., hereinbefore described.</p> <p style="padding-left: 40px;">An angle point, bears S. $89^{\circ}58'$ E., 48 lks. dist., hereinbefore described.</p> <p>Raise a mound of stone S. of the corner.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp.</p> <p>N. $1^{\circ}03'$ W., bet. secs. 33 and 34.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>.90 Wash, 10 lks. wide, 2 ft. deep, drains W.</p> <p>2.50 Track road, bears E. and W.</p> <p>22.70 Wash, 50 lks. wide, 2 ft. deep, drains N. 80° W.</p> <p>27.50 Wash, 60 lks. wide, 2 ft. deep, drains N. 50° W., 80 lks. dist., thence W.</p> <p>40.37 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T11S R30E $\frac{1}{4}$ S33 S34 1969 </p> <p>Raise a mound of stone W. of the corner.</p> <p>68.50 Wash, 15 lks. wide, 2 ft. deep, drains S. 70° W.</p> <p>80.75 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T11S R30E $\frac{1}{4}$ S28 S27 S33 S34 1969 </p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 87°57' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
40.55	<p>The ½ sec. cor. of secs. 27 and 34, monumented by a malpais stone, 12 x 8 x 7 ins., set 4 ins. in the ground, mkd. ½ on N. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ½ S27 S34 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p>
	<p style="text-align: center;">—————</p> <p>S. 89°33' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
39.78	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>N. 0°02' W., bet. secs. 27 and 28.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
40.37	<p>Point for the ½ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ½ S28 S27 1969</p> <p>Raise a mound of stone W. of the corner.</p>
41.60	<p>Track road, bears NE. and SW.</p>
43.60	<p>Wash, 40 lks. wide, 2 ft. deep, drains W.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS		
51.30	Wash, 10 lks. wide, 2 ft. deep, drains W.	
61.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 80° W.	
64.90	Wash, 15 lks. wide, 1 ft. deep, drains S. 70° W.	
80.74	<p>The cor. of secs. 21, 22, 27 and 28, monumented by a malpais stone, 9 x 8 x 7 ins., set 2 ins. in the ground, mkd. with 3 notches on E. and 2 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{c} \text{T11S R30E} \\ \hline \text{S21 S22} \\ \hline \text{S28 S27} \\ \hline 1969 \end{array}$ <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	
40.39	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°11' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>The ¼ sec. cor. of secs. 22 and 27, monumented by a malpais stone, 11 x 10 x 6 ins., set 4 ins. in the ground, mkd. ¼ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> $\begin{array}{c} \text{T11S R30E} \\ \hline \frac{1}{4} \frac{\text{S22}}{\text{S27}} \\ \hline 1969 \end{array}$ <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p>	
18.30	Track road, bears S. 20° E. and N. 10° W.	
39.76	The cor. of secs. 21, 22, 27 and 28.	

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS		
	<p>Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>N. 0°19' W., bet. secs. 21 and 22.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>6.20 Wash, 20 lks. wide, 2 ft. deep, drains S. 80° W.</p> <p>27.70 Wash, 30 lks. wide, 2 ft. deep, 4 ft. banks, drains S. 70° W.</p> <p>39.14 The ¼ sec. cor. of secs. 21 and 22, monumented by a lava stone, 11 x 8 x 4 ins., lying loose on the ground, mkd. ¼ on one face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ¼ S21 S22 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p> <hr/> <p>N. 2°57' E., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>40.84 Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S16 S15 S21 S22 1969</p> <p>from which</p> <p style="text-align: center;">A windmill, bears N. 22°07' E., 18.10 chs. dist.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>	

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	N. 89°45' W., bet. secs. 15 and 22.
	Over gently rolling land, through moderate undergrowth.
2.90	Wash, 15 lks. wide, 2 ft. deep, drains N. 60° W.
8.10	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
20.13	Point for the E 1/16 sec. cor. of secs. 15 and 22, at proportionate dist.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T11S R30E E 1/16 $\frac{S15}{S22}$ 1969
	Raise a mound of stone N. of the corner.
40.26	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 23 ins. in the ground, brass cap mkd.
	T11S R30E $\frac{1}{4}$ $\frac{S15}{S22}$ 1969
	Raise a mound of stone N. of the corner.
41.30	Track road, bears SE. and NW.
80.52	The cor. of secs. 15, 16, 21 and 22.
	Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	N. 0°10' W , bet. secs. 15 and 16.
	Over gently rolling land, through moderate undergrowth.
13.70	Track road, bears E. and W.
14.80	Underground water line, bears NE. and SW.
15.40	Track road, bears NE. and SW.
18.60	Wash, 50 lks. wide, 3 ft. deep, drains W.
20.30	Track road, bears E. and W.
40.79	The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented by a malpais stone, 12 x 8 x 5 ins., lying loose on the ground, mkd. $\frac{1}{4}$ on one face.
	At the corner point

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

Set the iron post 22 ins. in the ground, brass cap mkd.

T11S R30E
 $\frac{1}{2}$
 S16 | S15
 1969

from which

A windmill, bears S. 16°07' E., 25.00 chs. dist.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the corner.

N. 0°15' W., beginning new measurement.

Over gently rolling land.

2.55 Track road, bears N. 80° E. and W.

21.00 Track road, bears N. 75° E. and S. 75° W.

38.60 Wash, 10 lks. wide, 5 ft. banks, drains SW.

40.23 Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E
 S 9 | S10
 S16 | S15
 1969

Raise a mound of stone W. of the corner.

Land, gently rolling.

Soil, sandy and rocky clay loam.

No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

From the cor. of secs. 10, 11, 14 and 15.

N. 89°16' W., bet. secs. 10 and 15.

Over rolling land, through moderate undergrowth.

20.08 Point for the E 1/16 sec. cor. of secs. 10 and 15, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E
 E 1/16 $\frac{S10}{S15}$
 1969

Raise a mound of stone N. of the corner.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

- 29.20 Track road, bears N. 60° E. and S. 60° W.
- 40.16 The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented by a lava stone, 16 x 11 x 8 ins., set 4 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, mound of stone W.
- At the corner point
- Set the iron post 20 ins. in the ground, brass cap mkd.
- T11S R30E
 $\frac{1}{4}$ $\frac{S10}{S15}$
1969
- from which
- A monument of unknown origin, bears N. 0°35' E., 7.56 chs. dist., monumented by a malpais stone, 14 x 10 x 6 ins., set in a mound of stone, mkd. $\frac{1}{4}$ on one face.
- Bury the orig. cor. stone alongside the iron post.
- Raise a mound of stone N. of the corner.
-
- N. 89°14' W., beginning new measurement.
- Over gently rolling land.
- 20.35 Point for the W 1/16 sec. cor. of secs. 10 and 15, at proportionate dist.
- Set the iron post 24 ins. in the ground, brass cap mkd.
- T11S R30E
W 1/16 $\frac{S10}{S15}$
1969
- Raise a mound of stone N. of the corner.
- 27.60 Track road, bears NE. and SW.
- 38.90 Wash, 10 lks. wide, 4 ft. banks, drains SW.
- 40.70 The cor. of secs. 9, 10, 15 and 16.
- Land, gently rolling.
Soil, rocky and sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
-
- N. 0°02' W., bet. secs. 9 and 10.
- Over gently rolling land, through moderate undergrowth.
- 20.11 Point for the S 1/16 sec. cor. of secs. 9 and 10.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S 1/16 S 9 S10 1969</p>
	<p>Raise a mound of stone W. of the corner.</p>
40.22	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented by a malpais stone, 10 x 9 x 5 ins., set 3 ins. in the ground, mkd. 1/4 on W. face.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E 1/4 S 9 S10 1969</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Raise a mound of stone W. of the corner.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 0°25' W., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
37.80	<p>Dim track road, bears NE. and S. 25° W.</p>
39.92	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a malpais stone, 8 x 7 x 6 ins., set 3 ins. in the ground, mkd. with 5 notches on S. and 3 notches on E. face.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S 4 S 3 S 9 S10 1969</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Raise a mound of stone W. of the corner.</p>
	<p>Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p>
	<p>N. 89°28' W., bet. secs. 3 and 10.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
24.00	Track road, bears N. 10° E. and S.
40.75	The ¼ sec. cor. of secs. 3 and 10, monumented by a malpais stone, 12 x 8 x 6 ins., set 8 ins. in the ground, mkd. ½ on N. face, set in a mound of stone.
	At the corner point Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T11S R30E $\frac{1}{4}$ $\frac{S\ 3}{S10}$ 1969</p>
	<p>from which</p> <p style="padding-left: 40px;">A monument of unknown origin, bears N. 0°54' E., 7.57 chs. dist., monumented by a malpais stone, 24 x 18 x 18 ins. above ground, mkd. ½ on N. face, mound of stone NW.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the corner.</p>
	<hr style="width: 20%; margin: auto;"/> <p>N. 89°08' W., beginning new measurement.</p> <p>Over nearly level land.</p>
41.42	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<hr style="width: 80%; margin: auto;"/> <p>N. 0°25' E., bet. secs. 3 and 4.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
1.20	Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.
40.52	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 16 ins. in the ground, mound of stone to the top, brass cap mkd.
	<p style="text-align: center;">T11S R30E $\frac{1}{4}$ $S\ 4\ S\ 3$ 1969</p>
	The cor. is located 5 lks. N. of a wash, 10 lks. wide, 2 ft. deep, drains W.
47.20	Wash, 10 lks. wide, 2 ft. deep, drains S. 60° W.
66.50	Wash, 100 lks. wide, 2 ft. deep, drains S. 80° W.
72.80	Wash, 40 lks. wide, 6 ft. banks, drains S. 60° W.; asc. SW. slope of a hill, bears E. and W. (Sands Draw)

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

79.57

Intersect the Second Standard Parallel South.

The closing cor. of secs. 3 and 4, monumented by a malpais stone, 16 x 9 x 7 ins., set 4 ins. in the ground, mkd. with 3 notches on the E. and W. faces and CC on S. face, mound of stone S.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T10S
S 33

S 4 | S 3
T11S R30E
C C
1969

from which

The standard $\frac{1}{2}$ sec. cor. of sec. 33, T. 10 S., R. 30 E., bears East, 35 lks. dist., hereinbefore described.

An angle point, bears East 44 lks. dist., hereinbefore described.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone S. of the corner.

Land, gently rolling to rolling.
Soil, gravelly to rocky clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

The point for the $\frac{1}{2}$ sec. cor. of sec. 3 is on the N. bdy. at mid-point bet. the closing cors.

Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.

$\frac{1}{2}$ S 3

T11S R30E
1969

from which

The standard cor. of secs. 33 and 34, T. 10 S., R. 30 E., bears S. 89°51' E., 20 lks. dist., hereinbefore described.

An angle point, bears S. 89°51' E., 66 lks. dist., hereinbefore described.

From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp.

N. 0°42' W., bet. secs. 32 and 33.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

Over gently rolling land, through moderate undergrowth.

- 4.80 Track road, bears E. and W.
- 25.70 Wash, 60 lks. wide, 1 ft. deep, drains N. 80° W.
- 37.70 Wash, 20 lks. wide, 2 ft. deep, drains W.
- 40.66 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E

$\frac{1}{4}$
S32 | S33
1969

Set a wooden post, 3 ins. square, 5 ft. long, alongside the iron post.

- 79.70 Dim track road, bears NE. and SW.
- 81.32 Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E

S29 | S28
S32 | S33
1969

Set a wooden post, 2 x 2 ins. square, 5 ft. long, alongside the iron post.

Land, gently rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

From the cor. of secs. 27, 28, 33 and 34.

N. 88°50' W., bet. secs. 28 and 33.

Over gently rolling land, through moderate undergrowth.

- 39.71 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E

$\frac{1}{4}$ S28
S33
1969

Set a wooden post, 3 x 4 ins. squared, 5 ins. long, alongside the iron post.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
77.60	Dim track road, bears NE. and SW.
79.42	The cor. of secs. 28, 29, 32 and 33.
	Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	N. 0°35' W., bet. secs. 28 and 29.
	Over gently rolling land, through moderate undergrowth.
40.66	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T11S R30E $\frac{1}{4}$ S29 S28 1969
	Set a wooden post 3 x 3 ins. square, 3 ft. long, alongside the iron post.
71.80	Wash, 40 lks. wide, 2 ft. deep, drains N. 60° W.
73.20	Wash, 50 lks. wide, 5 ft. banks, drains W.
74.10	Wash, 20 lks. wide, 1 ft. deep, drains S. 70° W.
81.32	The cor. of secs. 20, 21, 28 and 29, monumented by a malpais stone, 12 x 5 x 4 ins., set 3 ins. in the ground, mkd. with 4 notches on E. and 2 notches on S. faces; with a wooden post 4 ft. above ground alongside.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T11S R30E S20 S21 S29 S28 1969
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. and reset the wooden post alongside the corner.
	Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 88°28' W., bet. secs. 21 and 28.
	Over gently rolling land, through moderate undergrowth.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
40.11	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S21 S28 1969</p> <p>Raise a mound of stone N. of the corner.</p>
56.50	<p>Wash, 30 lks. wide, 2 ft. deep with 6 ft. banks, drains S. 80° W.</p>
80.22	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>N. 1°57' E., bet. secs. 20 and 21.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
40.22	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented by a broken malpais stone, 17 x 10 x 6 ins., set 6 ins. in the ground, upper piece 8 x 7 x 6 ins., lying alongside, mkd. $\frac{1}{4}$ on one face, scattered mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S20 S21 1969</p> <p>Bury the mkd. portion alongside the iron post, deposit the remainder in a collar of stone around the iron post.</p> <p>Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p>
	<p>N. 0°18' W., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
35.50	<p>Track road, bears N. 80° E. and S. 80° W.</p>
39.90	<p>The cor. of secs. 16, 17, 20 and 21, monumented by a lava stone, 10 x 10 x 8 ins., set 4 ins. in the ground, mkd. with 4 notches on E. and 3 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S17 S16 S20 S21 1969</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a wooden post, 1½ x 3 ins. squared, 3 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 87°56' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
17.00	Underground water line, bears NE. and SW.
40.32	<p>The ¼ sec. cor. of secs. 16 and 21, monumented by a lava stone, 9 x 9 x 5 ins., lying loose on the ground, mkd. ¼ on one face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ¼ $\frac{S16}{S21}$ 1969</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a wooden post, 4 x 4 ins. square, 3½ ft. long, alongside the iron post.</p>
	<p>N. 88°48' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
11.90	Track road, on a curve, bears N. 50° E. and S. 50° W.; curving to S. 85° W.
40.60	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>N. 0°26' W., bet. secs. 16 and 17.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
11.80	Dim track road, bears S. 60° E. and N. 60° W.
33.20	Track road, bears E. and W.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S17 S16 1969</p> <p>Raise a mound of stone W. of the corner.</p>
80.08	<p>The cor. of secs. 8, 9, 16 and 17, monumented by a malpais stone, 11 x 6 x 4 ins., set 8 ins. in the ground, mkd. with 4 notches on E. and S. faces, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S 8 S 9 S17 S16 1969</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
40.59	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°03' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S 9 S16 1969</p> <p>Set a wooden post 3 ins. diam., 4 ft. long, alongside the iron post.</p>
81.18	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>N. 0°24' E., bet. secs. 8 and 9.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
36.60	<p>Wash, 10 lks. wide, 2 ft. deep, drains W.</p>
39.76	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{2}$ S 8 S 9 1969</p> <p>Raise a mound of stone W. of the corner.</p>
78.70	<p>Dim track road, bears E. and W.</p>
79.52	<p>The cor. of secs. 4, 5, 8 and 9, monumented by a malpais stone, 8 x 7 x 4 ins., mkd. with 5 notches on S. and 4 notches on E. faces, set in a mound of stone.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S 5 S 4 S 8 S 9 1969</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 0°43' E., 17 lks. dist.; fences bear N. 1°15' E. and N. 86°50' W.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°28' W., bet. secs. 4 and 9.</p> <p>Over nearly level land, through moderate undergrowth.</p>
40.14	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T11S R30E $\frac{1}{4}$ S 4 S 9 1969</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
80.28	<p>from which</p> <p>A monument of unknown origin, bears N. 0°55' W., 7.73 chs. dist., monumented by a malpais stone, 12 x 10 x 5 ins., mkd. ½ on S. face, set in a mound of stone.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, nearly level. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
0.17	<p>N. 0°43' E., bet. secs. 4 and 5.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Fence cor.; fences bear N. 1°15' E. and N. 86°50' W.; thence along W. side of fence.</p>
31.70	<p>Wash, 10 lks. wide, 2 ft. deep with 8 ft. banks, drains W.</p>
40.75	<p>Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ½ S 5 S 4 1969</p> <p>The cor. is located 35 lks. W. of a N. and S. fence.</p> <p>Raise a mound of stone W. of the corner.</p>
42.00	<p>Wash, in Sands Draw, 30 lks. wide, 5 ft. banks, drains SW.</p>
78.45	<p>Intersect the Second Standard Parallel South.</p> <p>Point for the closing cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10S S 32 ----- S 5 S 4 T11S R30E C C 1969</p> <p>from which</p> <p>The standard ¼ sec. cor. of sec. 32, T. 10 S., R. 30 E., bears S. 89°21' E., 28 lks. dist., hereinbefore described.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>An angle point, bears S. 89°21' E., 75 lks. dist., hereinbefore described.</p> <p>Set a wooden post, 4 x 4 ins. square, 4 ft. long, alongside the iron post.</p> <p>Land, rolling. Soil, rocky to sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p> <hr/> <p>Point for the ¼ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing cors.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 100px; margin: 0 auto;"/> <p>¼ S 4 T11S R30E 1969</p> </div> <p>from which</p> <p>The standard cor. of secs. 32 and 33, T. 10 S., R. 30 E., bears N. 89°21' E.; 33 lks. dist., hereinbefore described.</p> <p>Set a wooden post, 4 x 4 ins. square, 4 ft. long, alongside the iron post.</p>
<p>6.30</p> <p>15.50</p> <p>25.00</p> <p>29.00</p> <p>40.55</p>	<p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of the Tp.</p> <p>N. 0°23' W., bet. secs. 31 and 32.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Track road, bears S. 80° E. and N. 80° W.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains W.; thence over gently rolling land.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains W.</p> <p>Wash, 150 lks. wide, 2 ft. deep, drains S. 75° W.</p> <p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R30E</p> <p>¼</p> <p>S31 S32</p> <p>1969</p> </div> <p>Raise a mound of stone W. of the corner.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS 45.00	Track road, bears N. 65° E. and S. 65° W.
47.70	Wash, 50 lks. wide, 1 ft. deep, drains S. 75° W.
81.10	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T11S R30E} \\ \hline \text{S30} \text{S29} \\ \hline \text{S31} \text{S32} \\ \hline 1969 \end{array}$
	Raise a mound of stone W. of the corner.
	<p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	From the cor. of secs. 28, 29, 32 and 33.
	N. 89°26' W., bet. secs. 29 and 32.
	Over gently rolling land, through moderate undergrowth.
39.78	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T11S R30E} \\ \hline \frac{1}{4} \frac{\text{S29}}{\text{S32}} \\ \hline 1969 \end{array}$
	Set a wooden post, 5 x 5 ins. square, 5 ft. long, alongside the iron post.
79.56	The cor. of secs. 29, 30, 31 and 32.
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cat claw, cacti and grass.</p>
	N. 89°28' W., bet. secs. 30 and 31.
	Over gently rolling land, through moderate undergrowth.
5.15	Track road, bears N. 20° E. and S. 20° W.
39.77	Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T11S R30E} \\ \hline \frac{1}{4} \frac{\text{S30}}{\text{S31}} \\ \hline 1969 \end{array}$

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS		
	<p>Raise a mound of stone N. of the corner.</p>	
75.80	<p>Fence, bears N. and S.</p>	
76.56	<p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;"> T11S R29E R30E <u>S25 S30</u> <u>S36 S31</u> 1952 </p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°39' W., bet. secs. 29 and 30.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	
11.50	<p>Track road, bears N. 40° E. and S. 40° W.</p>	
40.55	<p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T11S R30E ¼ <u>S30 S29</u> 1969 </p> <p>Raise a mound of stone W. of the corner.</p>	
54.70	<p>Track road, bears N. 80° E. and S. 80° W.</p>	
58.20	<p>Wash, 30 lks. wide, 1 ft. deep, drains SW.</p>	
81.10	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a malpais stone, 14 x 8 x 7 ins., set 4 ins. in the ground, mkd. with 5 notches on E. and 2 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T11S R30E <u>S19 S20</u> <u>S30 S29</u> 1969 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p>	

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>N. 89°33' W., bet. secs. 20 and 29.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
39.81	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E $\frac{1}{2} \frac{S20}{S29}$ 1969</p>
	<p>Raise a mound of stone N. of the corner.</p>
53.50	<p>Track road, bears N. 10° E. and S. 10° W.</p>
79.62	<p>The cor. of secs. 19, 20, 29 and 30.</p>
	<p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>N. 89°05' W., bet. secs. 19 and 30.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
27.20	<p>Wash, 20 lks. wide, 1 ft. deep, drains SW.</p>
39.30	<p>The $\frac{1}{2}$ sec. cor. of secs. 19 and 30, monumented by a lava stone, 13 x 10 x 9 ins., set 6 ins. in the ground, mkd. $\frac{1}{2}$ on N. face.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E $\frac{1}{2} \frac{S19}{S30}$ 1969</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>Set a wooden post, 4 x 4 ins. square, 3 ft. long, alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>S. 89°37' W., beginning new measurement.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R 30 E.

CHAINS	
	Over gently rolling land.
35.40	Fence, bears N. and S.
36.07	The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, brass cap mkd.
	T11S R29E R30E <u>S24 S19</u> S25 S30 1952
	Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	From the cor. of secs. 19, 20, 29 and 30. N. 0°20' E., bet. secs. 19 and 20. Over gently rolling land, through moderate undergrowth.
0.90	Wash, 5 lks. wide, 2 ft. deep, drains irregularly W.
40.54	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 24 ins. in the ground, brass cap mkd.
	T11S R30E ¼ <u>S19 S20</u> 1969
	Set a wooden post 2 x 4 ins. squared, 3 ft. long, alongside the iron post.
66.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.
81.08	The cor. of secs. 17, 18, 19 and 20, monumented by a malpais stone, 15 x 8 x 7 ins., lying loose on the ground, mkd. with 5 notches on E. and 3 notches on S. faces. The stone was lying alongside a fence cor.; fences bear N. and W. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd.
	T11S R30E <u>S18 S17</u> S19 S20 1969
	Bury the orig. cor. stone alongside the iron post. The cor. is located at the fence cor.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

Land, gently rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

From the cor. of secs. 16, 17, 20 and 21.

N. 88°33' W., bet. secs. 17 and 20.

Over gently rolling land, through moderate undergrowth.

39.21 The ¼ sec. cor. of secs. 17 and 20, monumented by a lava stone, 12 x 8 x 5 ins., set 8 ins. in the ground, mkd. ¼ on N. face.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E
¼ $\frac{S17}{S20}$
1969

Bury the orig. cor. stone alongside the iron post.

Set a wooden post 3 x 5 ins. squared, 3 ft. long, alongside the iron post.

N. 89°10' W., beginning new measurement.

Over gently rolling land.

0.90 Track road, bears N. and S.

41.10 The cor. of secs. 17, 18, 19 and 20.

Land, gently rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

N. 89°52' W., bet. secs. 18 and 19.

Over gently rolling land, through moderate undergrowth.

Along the S. side of a fence bearing W.

39.38 Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E
¼ $\frac{S18}{S19}$
1969

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS		
	<p>Set a wooden post 4 x 4 ins. square, 3 ft. long, alongside the iron post.</p> <p>Continue along an E. and W. fence.</p> <p>75.60 The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground with a wooden post alongside, 4 x 4 ins. square, projecting 4½ ft. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T11S R29E R30E S13 S18 S24 S19 1952</p> <p>The cor. is located 8 lks. S. of an E. and W. fence.</p> <p>Land, gently rolling. Soil, rocky and sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>	
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°04' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Along the E. side of a fence bearing N. and S.</p> <p>25.60 Wash, 10 lks. wide, 2 ft. deep, drains S. 70° W.</p> <p>32.00 Wash, 10 lks. wide, 2 ft. deep, drains irregularly W.</p> <p>39.91 Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E ¼ S18 S17 1969</p> <p>Set a wooden post 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p> <p>The cor. is located 2 lks. E. of a N. and S. fence.</p> <p>74.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 40° W.</p> <p>79.82 The cor. of secs. 7, 8, 17 and 18, monumented by a malpais stone, 12 x 8 x 7 ins., lying loose under a N. and S. fence, mkd. with 5 notches on E. and 4 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T11S R30E S 7 S 8 S18 S17 1969</p>	

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the corner.

The cor. is located under a fence bearing N. and S.

Land, gently rolling.

Soil, sandy and rocky clay loam.

No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

From the cor. of secs. 8, 9, 16 and 17.

N. 89°00' W., bet. secs. 8 and 17.

Over gently rolling land, through moderate undergrowth.

39.88 Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E

$\frac{1}{4}$ $\frac{S 8}{S 17}$

1969

Set a wooden post 2 x 4 ins. squared, 4 ft. long, alongside the iron post.

75.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 40° W.

79.77 The cor. of secs. 7, 8, 17 and 18.

Land, gently rolling.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

N. 89°06' W., bet. secs. 7 and 18.

Over gently rolling land, through moderate undergrowth.

39.23 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E

$\frac{1}{4}$ $\frac{S 7}{S 18}$

1969

Set a wooden post 2 x 4 ins. squared, 4 ft. long, alongside the iron post.

75.31 The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, brass cap mkd.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	<p style="text-align: center;">T11S R29E R30E <u>S12 S 7</u> <u>S13 S18</u> 1952</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
40.37	<p>From the cor. of secs. 7, 8, 17 and 18. N. 0°36' E., bet. secs. 7 and 8. Over gently rolling land, through moderate undergrowth. Along a N. and S. fence. Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E $\frac{1}{4}$ <u>S 7 S 8</u> 1969</p>
58.80	<p>Set a wooden post, 3 x 3 ins. square, 3 ft. long, alongside the iron post.</p>
64.10	<p>The cor. is located 7 lks. E. of a fence bearing N. and S.</p>
68.30	<p>Wash, 10 lks. wide, 2 ft. deep, drains N. 70° W.</p>
79.90	<p>Wash, 10 lks. wide, 2 ft. deep, drains W.</p>
80.74	<p>Wash, 5 lks. wide, $\frac{1}{2}$ ft. deep, drains NW.</p>
	<p>Fence, bears N. 77°30' E., and bears S. 72°10' W., 24 lks. dist. to a cor. of fences bearing S. 0°15' W. and S. 72°10' W.</p>
	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T11S R30E <u>S 6 S 5</u> <u>S 7 S 8</u> 1969</p>
	<p>from which The proportionate point for the closing cor. of secs. 5 and 6, on the N. bdy. of the Tp., bears N. 0°07' W., 76.35 chs. dist.; not monumented.</p>

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS

From the point for the closing cor., the standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 10 S., R. 30 E., bears S. $89^{\circ}52'$ E., 74 lks. dist., hereinbefore described.

From the point for the closing cor., an angle point, bears S. $89^{\circ}52'$ E., 108 lks. dist., hereinbefore described.

This control line was fully retraced, and careful search was made for evidence of intervening corners, none of which was recovered.

Raise a mound of stone W. of the corner.

Land, gently rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

From the cor. of secs. 4, 5, 8 and 9.

N. $88^{\circ}06'$ W., bet. secs. 5 and 8.

Over gently rolling land, through moderate undergrowth.

38.60 Track road, bears S. 60° E. and N. 60° W.

39.75 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T11S R30E

$\frac{1}{4}$ $\frac{S 5}{S 8}$

1969

from which

A monument of unknown origin, bears N. $3^{\circ}04'$ W., 5.60 chs. dist., monumented by a malpais stone, 9 x 6 x 4 ins., set 3 ins. in the ground, mkd. $\frac{1}{4}$ on N. face.

The cor. is located 87 lks. S. of a fence bearing S. $86^{\circ}50'$ E. and N. $86^{\circ}50'$ W.

Raise a mound of stone N. of the corner.

51.00 Wash, 10 lks. wide, 2 ft. deep, drains NW.

70.60 Fence, bears S. $86^{\circ}50'$ E. and S. $77^{\circ}30'$ W.

79.50 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

Dep. Res., Subdivisional Lines, T. 11 S., R. 30 E.

CHAINS	
	N. 89°02' W., bet. secs. 6 and 7. Over gently rolling land, through moderate undergrowth.
0.80	Wash, 20 lks. wide, 5 ft. banks, drains S. 80° W.
12.30	Wash, 50 lks. wide, 7 ft. banks, drains NW.
13.60	Wash, 50 lks. wide, 6 ft. banks, drains SW.
23.50	Wash, 50 lks. wide, 2 ft. deep, drains NW.
39.61	Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T11S R30E ¼ $\frac{S\ 6}{S\ 7}$ 1969 </div>
	Set a wooden post 3 x 3 ins. square, 5 ft. long, alongside the iron post.
45.00	Fence, bears S. 60° E. and N. 60° W.
49.50	Track road, bears SE. and NW.
75.91	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, brass cap mkd. <div style="text-align: center;"> T11S R29E R30E S 1 S 6 S12 S 7 1952 </div>
	The cor. is located 6 lks. S. of a fence bearing E. and W. Land, gently rolling. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw, grass and scattered mesquite.
Subdivision, Section 1, T. 11 S., R. 30 E.	
	From the ¼ sec. cor. of secs. 1 and 12. N. 1°20' W., on the N. and S. center line of sec. 1.
8.90	Track road, bears N. 50° E and S. 50° W.
39.35	Point for the center ¼ sec. cor. of sec. 1, at intersection with the E. and W. center line of sec. 1. Set the iron post 24 ins. in the ground, brass cap mkd. <div style="text-align: center;"> C ¼ S 1 1969 </div>

Subdivision, Section 1, T. 11 S., R. 30 E.

CHAINS

- Raise a mound of stone W. of the corner.
- 59.75 Point for the C-N 1/16 sec. cor. of sec. 1.
Set the iron post 24 ins. in the ground, brass cap mkd.
- C
N 1/16 | S 1
C
1969
- Raise a mound of stone W. of the corner.
- 60.20 Enter wash area, bears S. 80° E. and N. 80° W. (Sands Draw)
- 60.60 Main channel, 100 lks. wide, 2 ft. deep, drains N. 80° W.
- 67.40 Leave wash area, bears S. 80° E. and N. 80° W.
- 68.00 Fence, bears S. 80° E. and N. 80° W.
- 81.24 The 1/4 sec. cor. of sec. 1, on the N. bdy. of the Tp.
Land, nearly level to gently rolling.
Soil, rocky clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
-
- From the 1/4 sec. cor. of sec. 1 only, on the E. bdy. of the Tp.
S. 89°56' W., on the E. and W. center line of sec. 1.
Over gently rolling land, through moderate undergrowth.
- 39.66 The center 1/4 sec. cor. of sec. 1.
- 79.06 The 1/4 sec. cor. of secs. 1 and 2.
Land, gently rolling.
Soil, rocky clay loam.
No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
-
- Subdivision, Section 10, T. 11 S., R. 30 E.
-
- From the 1/4 sec. cor. of secs. 10 and 15.
N. 0°18' E., on the N. and S. center line of sec. 10.
Over gently rolling land, through moderate undergrowth.
- 20.07 Point for the C-S 1/16 sec. cor. of sec. 10; not monumented.
- 36.30 Track road, bears NE. and SW.
- 40.15 Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W center line of sec. 10; not monumented.

Subdivision, Section 10, T. 11 S., R. 30 E.

CHAINS	
80.07	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <p>Land, gently rolling. Soil, rocky clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>N. $89^{\circ}07'$ W., on the E. and W. center line of sec. 10.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>36.90 Track road, bears N. 30° E. and S. 30° W.</p> <p>40.28 The point for the center $\frac{1}{4}$ sec. cor. of sec. 10.</p> <p>60.74 Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 10; not monumented.</p> <p>81.21 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; Undergrowth, creosote bush, cacti, cat claw and grass.</p>
	<p>Subdivision, SW$\frac{1}{4}$ Section 10</p>
	<hr/> <p>From the W $\frac{1}{16}$ sec. cor. of secs. 10 and 15.</p> <p>N. $0^{\circ}09'$ E., on the N. and S. center line of the SW$\frac{1}{4}$ of sec. 10.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>12.20 Track road, bears NE. and SW.</p> <p>20.08 Point for the SW $\frac{1}{16}$ sec. cor. of sec. 10, at intersection with the E. and W center line of the SW$\frac{1}{4}$ of sec. 10.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SW $\frac{1}{16}$ S 10 1969</p> <p>Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.</p> <p>40.18 The point for the C-W $\frac{1}{16}$ sec. cor. of sec. 10.</p>
	<hr/> <p>From the point for the C-S $\frac{1}{16}$ sec. cor. of sec. 10.</p> <p>N. $89^{\circ}11'$ W., on the E. and W. center line of the SW$\frac{1}{4}$ of sec. 10.</p>

Subdivision, Section 10, T. 11 S., R. 30 E.

CHAINS

Over gently rolling land, through moderate undergrowth.

15.70 Track road, bears N. 30° E and S. 30° W.

20.42 The SW 1/16 sec. cor. of sec. 10.

40.82 The S 1/16 sec. cor. of secs. 9 and 10.

Subdivision, Section 15, T. 11 S., R. 30 E.

From the 1/2 sec. cor. of secs. 15 and 22.

N. 0°06' E., on the N. and S. center line of sec. 15.

Over gently rolling land, through moderate undergrowth.


4.90 Track road, bears E. and W.

15.70 Wash, 20 lks. wide, 2 ft. deep, drains N. 80° W.

17.70 Wash, 15 lks. wide, 4 ft. banks, drains S. 80° W.

20.27 Point for the C-S 1/16 sec. cor. of sec. 15.

Set the iron post 22 ins. in the ground, brass cap mkd.



Set a wooden post, 3 ins. diam., 3 1/2 ft. long, alongside the iron post.

40.54 Point for the center 1/2 sec. cor. of sec. 15, at intersection with the E. and W. center line of sec. 15.


Set the iron post 22 ins. in the ground, brass cap mkd.



Set a wooden post, 3 ins. diam., 3 1/2 ft. long, alongside the iron post.

60.59 Point for the C-N 1/16 sec. cor. of sec. 15.

Set the iron post 24 ins. in the ground, brass cap mkd.



Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.

76.70 Track road, bears N. 70° E. and S. 70° W.

Subdivision, Section 15, T. 11 S., R. 30 E.

CHAINS

80.65 The ¼ sec. cor. of secs. 10 and 15.
 Land, gently rolling.
 Soil, sandy and rocky clay loam.
 No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

From the ¼ sec. cor. of secs. 14 and 15.
 N. 89°23' W., on the E. and W. center line of sec. 15.
 Over gently rolling land, through moderate undergrowth.

20.18 Point for the C-E 1/16 sec. cor. of sec. 15.
 Set the iron post 24 ins. in the ground, brass cap mkd.

E 1/16
 C ——— C
 S15
 1969

Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.

40.36 The center ¼ sec. cor. of sec. 15.

77.10 Track road, bears N. and S.

80.82 The ¼ sec. cor. of secs. 15 and 16.

Land, gently rolling.
 Soil, gravelly clay loam.
 No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

Subdivision, NE¼ Section 15

From the C-E 1/16 sec. cor. of sec. 15.
 N. 0°03' W., on the N. and S. center line of the NE¼ of sec. 15.
 Over gently rolling land, through moderate undergrowth.

12.90 Track road, bears irregularly E. and W.

20.03 Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the NE¼ of sec. 15.

Set the iron post 24 ins. in the ground, brass cap mkd.

NE 1/16
 S15
 1969

Subdivision, Section 15, T. 11 S., R. 30 E.

CHAINS

Set a wooden post 3 ins., diam., 3 ft. long, alongside the iron post.

40.07 The E 1/16 sec. cor. of secs. 10 and 15.

From the N 1/16 sec. cor. of secs. 14 and 15.

N. 89°20' W., on the E. and W. center line of the NE $\frac{1}{4}$ of sec. 15.

Over gently rolling land, through moderate undergrowth.

20.14 The NE 1/16 sec. cor. of sec. 15.

40.28 The C-N 1/16 sec. cor. of sec. 15.

Subdivision, SE $\frac{1}{4}$ Section 15

From the E 1/16 sec. cor. of secs. 15 and 22.

N. 0°10' E., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 15.

Over gently rolling land, through moderate undergrowth.

5.50 Wash, 20 lks. wide, 2 ft. deep, drains N. 70° W.

7.80 Wash, 20 lks. wide, 2 ft. deep, drains N. 60° W.

10.80 Track road, bears S. 70° E. and N. 70° W.

11.70 Track road, bears N. 60° E. and SW.

20.21 Point for the SE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ of sec. 15.

Set the iron post 22 ins. in the ground, brass cap mkd.

SE 1/16
S15
1969

Raise a mound of stone W. of the corner.

40.41 The C-E 1/16 sec. cor. of sec. 15.

From the S 1/16 sec. cor. of secs. 14 and 15.

N. 89°36' W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 15.

Over gently rolling land, through moderate undergrowth.

4.70 Track road, bears NE. and S. 15° W.

20.17 The SE 1/16 sec. cor. of sec. 15.

Subdivision, Section 15, T. 11 S., R. 30 E.

CHAINS	
24.00	Wash, 60 lks. wide, 1 ft. deep, drains SW.
40.32	The C-S 1/16 sec. cor. of sec. 15.
Subdivision, Section 31, T. 11 S., R. 30 E.	
	From the 1/4 sec. cor. of secs. 6 and 31, on the S. bdy. of the Tp.
	N. 0°15' W., on the N. and S. center line of sec. 31.
	Over gently rolling land, through moderate undergrowth.
5.75	Fence, bears S. 60° E. and N. 60° W.
20.10	Track road, bears S. 80° E. and N. 80° W.
23.40	Track road, bears N. 70° E. and S. 70° W.
28.30	Wash, 200 lks. wide, 4 ft. banks, drains W.
40.50	Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line of sec. 31.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	$ \begin{array}{c} C \frac{1}{4} \quad \quad S31 \\ \quad \quad \\ \quad \quad 1969 \end{array} $
	Set a wooden post 3 x 3 ins. square, 4 ft. long, alongside the iron post.
80.99	The 1/4 sec. cor. of secs. 30 and 31.
	Land, gently rolling.
	Soil, sandy clay loam.
	No timber; Undergrowth, creosote bush, cacti, cat claw and grass.
	From the 1/4 sec. cor. of secs. 31 and 32.
	N. 89°21' W., on the E. and W. center line of sec. 31.
	Over gently rolling land, through moderate undergrowth.
10.70	Wash, 20 lks. wide, 2 ft. deep, drains SW.
23.40	Track road, bears N. 10° E. and S. 10° W.
39.87	The center 1/4 sec. cor. of sec. 31.
77.02	Fence, bears N. and S.
76.96	The 1/4 sec. cor. of secs. 31 and 36, on the W. bdy. of the Tp., monumented by an iron post 2 1/2 ins. diam., lying loose on the ground. The cor. point was determined by a glass deposit located 20 ins. below the surface of the ground, and verified by retracing the line bet. secs. 31

Subdivision, Section 31, T. 11 S., R. 30 E.

CHAINS

and 36. Bearings and distances were not changed from the 1952 survey. Brass cap mkd. $\frac{1}{4}$ S31 S36 1952. I stamped 1969 above 1952, and reset the iron post 24 ins. in the ground.

Land, gently rolling.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush, cacti, cat claw and grass.

General Description

The elevation in Township 11 South, Range 30 East, ranges from 3,480 to 4,500 ft. above sea level, with the highest point being in the east portion of section 36. The land varies throughout the township from rolling to nearly level. The soil varies from rocky to sandy clay loam. The vegetation consists of creosote bush, cacti, cat claw and a fair growth of grass. There is no timber in the township.

There are numerous track and jeep roads throughout the township.

There is evidence of erosion control throughout the township. The only water sources come from two wells, one in section 12 and the other in section 15.

The general drainage is westerly. The primary use of the land is for grazing.

73

CERTIFICATE OF SURVEY

I, Gary T Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20 day of November, 19 68, I have retraced a portion of the north boundary (the Second Standard Parallel South); dependently resurveyed the east and south boundaries and subdivisional lines and surveyed subdivisions in sections 1, 10, 15 and 31, Township 11 South, Range 30 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 6, 1970 (Date) Gary T. Oviatt (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date OCT 2 1970

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the retracement of a portion of the north boundary (the Second Standard Parallel South); the dependent resurvey of the east and south boundaries and subdivisional lines, and the survey of the subdivisions in sections 1, 10, 15 and 31, Township 11 South, Range 30 East, Gila and Salt River Meridian, Arizona

executed by Gary T. Oviatt having been critically examined and found correct, are hereby approved.

SEP 16 1971 (Date) Clark F. Lamm (Chief, Division of Engineering) Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Engineering)