

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

DEPENDENT RESURVEY

of a

PORTION OF THE SUBDIVISIONAL LINES

and the

SURVEY

of

SUBDIVISIONS

in

SECTIONS 3, 4, 9 and 10

TOWNSHIP 7 NORTH, RANGE 29 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Jerrold E. Knight

Cadastral Surveyor

Under special instructions dated May 23, 19 68, which provided for the surveys
included under Group Number 483, approved May 23, 1968,
and assignment instructions dated May 23, 19 68.

Survey commenced June 25, 19 68

Survey completed July 24, 19 68

BOOK 4907

INDEX DIAGRAM

Township 7 North, Range 29 East

6	5	13 4 11	7 8 6	2 2 .	1
7	8	10 9 9	5 10 3	1 11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision	----	Sec. 3	--	Page 14
"	SW $\frac{1}{4}$	Sec. 3	--	Page 17
"		Sec. 4	--	Page 20
"	SE $\frac{1}{4}$	Sec. 4	--	Page 21
"		Sec. 9	--	Page 22
"	NE $\frac{1}{4}$	Sec. 9	--	Page 26
"	NW $\frac{1}{4}$	Sec. 9	--	Page 29
"		Sec. 10	--	Page 30
"	NW $\frac{1}{4}$	Sec. 10	--	Page 32

Township 7 North, Range 29 East
Gila and Salt River Meridian, Arizona

CHAINS

The north and east boundaries were surveyed in 1875 by C. B. Foster. The south and west boundaries and subdivisional lines were surveyed in 1883 by W. R. Fitzgerald. The east boundary was resurveyed in 1925 by Benjamin J. Kinsey. The north, south and west boundaries and the subdivisional lines were resurveyed in 1936 by R. F. Wilson.

The following notes are those of a dependent resurvey of a portion of the subdivisional lines, designed to restore the corners in their true original location according to the best available evidence, and a survey of subdivisions in sections 3, 4, 9 and 10, Township 7 North, Range 29 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated May 23, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of section 10, as calculated from the G.L.O. survey plat accepted March 17, 1938 is: Latitude, 34°00'35" North and Longitude, 109°16'14" West.

The mean magnetic declination was found to be 14° East.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 7 N., R. 29 E., G&SRM, Arizona

Reestablishment of the Survey Executed
in 1936 by R. F. Wilson

Beginning at the cor. of secs. 10, 11, 14 and 15, monumented by an iron post, 2 ins. diam., firmly set with 10 ins. projecting above the ground, brass cap mkd.

T7N R29E			
S10		S11	
S15		S14	
1936			

from which the remains of the original bearing trees:

A juniper, 23 ins. diam., bears N. 46½° E., 215 lks. dist., mkd. T7N R29E S11 BT.

A pine, 20 ins. diam., bears S. 16¾° E., 196 lks. dist., mkd. T7N R29E S14 BT.

A pine, 13 ins. diam., bears S. 15½° W., 103 lks. dist., mkd. T7N R29E S15 BT.

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	<p>A pine stump, 30 ins. diam., bears N. 7° W., 195 lks. dist., mkd. O BT.</p> <p>N. 6°49' E., bet. secs. 10 and 11.</p> <p>Over rolling land, through dense timber.</p>
20.87	A fence cor. bears West, 28 lks. dist.; fences bear S. 20° E. and West.
25.50	Rudd Creek on bend, 8 lks. wide, 4 ins. deep, course N. 40° W. from W.
31.00	Rudd Creek, 8 lks. wide, 4 ins. deep, course N. 70° E.
32.70	Track road, bears irregularly S. 65° E. and N. 65° W.; thence ascend over mountainous land.
39.11	<p>The ½ sec. cor. of secs. 10 and 11, monumented by an iron post, 1 in. diam., firmly set, collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \frac{1}{2} \\ \text{S10} \text{S11} \\ 1936 \end{array}$ </div> <p>from which the original bearing trees:</p> <p>A pine, 20 ins. diam., bears S. 65° E., 83 lks. dist., mkd. ½ S11 BT.</p> <p>A forked juniper, 12 ins. diam., bears N. 66½° W., 20 lks. dist., mkd. ¼ S10 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 6°26' E., beginning new measurement.</p> <p>Ascend over steep rocky S. slope through heavy timber.</p>
5.90	Top of rocky rim, bears irregularly E. and W.; thence over rolling land through scattered timber.
39.02	<p>The cor. of secs. 2, 3, 10 and 11, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{T7N R29E} \\ \text{S 3} \text{S 2} \\ \text{S10} \text{S11} \\ 1936 \end{array}$ </div> <p>Land, rolling and mountainous. Soil, rocky clay loam. Timber, pine and juniper. Undergrowth, scrub timber and bunch grass.</p>
	<p>N. 1°52' W., between secs. 2 and 3.</p> <p>Over mountainous land, through widely scattered timber.</p>
16.40	Enter dense timber, bears E. and W.
29.20	Fence, bears E. and W.

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
37.45	Milligan Creek, 40 lks. wide with 8 ft. banks, with a small flow of water, course E.
38.26	The $\frac{1}{2}$ sec. cor. of secs. 2 and 3, monumented by an iron post, 1 in. diam., firmly set with 4 ins. projecting above the ground, in a small collar of stone, brass cap mkd.
	$\begin{array}{c} \frac{1}{2} \\ \text{S } 3 \text{ S } 2 \\ 1936 \end{array}$
	N. $1^{\circ}48'$ W., beginning new measurement.
	Over mountainous land, through dense timber.
4.50	Track road, bears N. 30° E. and S. 40° W.
29.50	Enter scattered timber, bears E. and W.
38.50	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	$\begin{array}{c} \text{T8N R29E} \\ \text{S34 S35} \\ \text{S } 3 \text{ S } 2 \\ \text{T7N} \\ 1936 \end{array}$
	from which
	A juniper, 20 ins. diam., bears S. $29\frac{1}{2}^{\circ}$ E., 101 lks. dist., mkd. with faint scribing.
	A juniper, 40 ins. diam., bears S. 5° W., 291 lks. dist., mkd. T7N R29E S3 BT.
	Land, mountainous. Soil, rocky clay loam. Timber, pine and juniper. Undergrowth, scrub pine and bunch grass.
	From the cor. of secs. 10, 11, 14 and 15.
	N. $86^{\circ}50'$ W., bet. secs. 10 and 15.
	Over gently rolling land, through medium timber.
1.10	Fence, bears irregularly N. and S.
6.60	Benton Creek, 4 lks. wide, 3 ins. deep, course irregularly N.
9.90	Track road, bears irregularly N. and S.
11.50	Fence, bears N. 8° E. and S. 8° W.
29.40	Wash, 20 lks. wide, with 6 ft. banks, drains NE.
35.70	SE. cor. of an old log barn, bears North about 80 lks. dist.

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
36.90	Track road, bears irregularly N. and S.
44.51	The $\frac{1}{2}$ sec. cor. of secs. 10 and 15, monumented by an iron post, 1 in. diam., firmly set with 15 ins. projecting above the ground, brass cap mkd.
	$\frac{1}{2} \frac{S10}{S15}$ 1936
	from which the original bearing trees:
	A pine, 12 ins. diam., bears N. 10° E., 89 lks. dist., mkd. $\frac{1}{2}$ S10 BT.
	A pine, 20 ins. diam., bears S. $67\frac{1}{2}^{\circ}$ E., 33 lks. dist., mkd. with BT visible.
	A pine, 25 ins. diam., bears S. 19° E., 67 lks. dist., mkd. $\frac{1}{2}$ S15 BT.
	A pine, 25 ins. diam., bears S. $87\frac{1}{2}^{\circ}$ W., 101 lks. dist., mkd. $\frac{1}{2}$ S (No record of this bearing tree).
	A pine stump, 12 ins. diam., bears N. 41° W., 58 lks. dist., with no visible mks.
	Raise a mound of stone W. of the cor.
	The cor. is located under a fence bearing N. and S.
	<hr style="width: 20%; margin: auto;"/> N. $89^{\circ}22'$ W., beginning new measurement.
	Over rolling land, through medium timber.
13.90	Fence, bears N. 15° E. and S. 15° W.
30.50	Track road, bears N. 35° E. and S. 35° W.
30.90	Small wash, drains N. 35° E.
39.91	The cor. of secs. 9, 10, 15 and 16, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone to top, brass cap mkd.
	$\begin{array}{c} T7N R29E \\ \hline S 9 S10 \\ S16 S15 \\ \hline 1936 \end{array}$
	from which the original bearing trees:
	A pine, 13 ins. diam., bears N. $69\frac{3}{4}^{\circ}$ E., 69 lks. dist., mkd. T7N R29E S10 BT.
	A pine, 18 ins. diam., bears S. $33\frac{3}{4}^{\circ}$ E., 56 lks. dist., mkd. T7N R29E S15 BT.
	A pine, 20 ins. diam., bears S. $54\frac{1}{2}^{\circ}$ W., 19 lks. dist., mkd. T7N R29E S16 BT. (Record 17 lks. dist.).

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	<p>A pine, 17 ins. diam., bears N. 40° W., 48 lks. dist., mkd. T7N R29E S9 BT.</p> <p>Land, gently rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub pine and bunchgrass.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented by an iron post, 1 in. diam., firmly set with 10 ins. projecting above the ground, brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 9 S10 1936 </p> <p>Cor. is located under a fence bearing E. and W. N. 10°11' E., between secs. 9 and 10.</p> <p>Over gently rolling land, through an open field.</p>
17.90	Track road, bears S. 85° E. and N. 85° W.
19.24	Point for the N 1/16 sec. cor. of secs. 9 and 10, at proportionate distance.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T7N R29E N 1/16 S 9 S10 1968
	Raise a mound of stone W. of the cor.
23.60	Milligan Creek, 50 lks. wide, 6 ft. deep, course E.
23.89	Fence, bears irregularly E. and W.
24.05	Point for the S-N-N 1/256 sec. cor. of secs. 9 and 10, at proportionate distance.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T7N R29E S N N 1/256 S 9 S10 1968
	Raise a mound of stone W. of the cor.
28.86	Point for the N-N 1/64 sec. cor. of secs. 9 and 10, at proportionate dist.; not monumented.
30.60	Leave open field, enter medium timber, bears E. and W.
38.48	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post, 2 ins. diam., firmly set in a collar of stone, brass cap mkd.

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS

T7N R29E
 $\frac{S\ 4}{S\ 9} | \frac{S\ 3}{S10}$
 1936

from which the remains of the original bearing trees:

Center of stump hole, with an uprooted pine,
 14 ins. diam. lying alongside, bears N. $50\frac{1}{2}^\circ$ E.,
 146 lks. dist., fallen tree mkd. T7N R29E S 3 BT.

A juniper, 13 ins. diam., bears S. $84\frac{1}{2}^\circ$ E.,
 137 lks. dist., mkd. T7N R29E S10 BT.

A pine stump, 2 ft. high, with cut log lying
 alongside, bears S. $66\frac{1}{2}^\circ$ W., 235 lks. dist.,
 with stump mkd. BT and log mkd. T7N R29E S9.

A pine, 10 ins. diam., bears N. $44\frac{1}{2}^\circ$ W., 143
 lks. dist., mkd. T7N R29E S4 BT.

Land, gently rolling.
 Soil, clay loam.
 Timber, pine and juniper.
 Undergrowth, bunchgrass.

From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented by an
 iron post 1 in. diam., firmly set in a mound of stone
 to top, brass cap mkd.

$\frac{1}{4}$ $\frac{S\ 3}{S10}$
 1936

from which the remains of the original bearing trees:

A stump, with decayed tree 7 ins. diam. lying
 alongside, bears S. $8\frac{1}{2}^\circ$ E., 44 lks. dist., mkd.
 $\frac{1}{4}$ S10 BT.

A pine, 10 ins. diam., bears N. $5\frac{1}{2}^\circ$ E., 96 lks.
 dist., mkd. $\frac{1}{4}$ S3 BT.

New bearing tree:

A pine, 9 ins. diam., bears S. $66\frac{1}{2}^\circ$ W., 125
 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

N. $89^\circ 20'$ W., bet. secs. 3 and 10.

Descend over steep west slope, through dense timber.

- 9.91 Point for the E-W $\frac{1}{64}$ sec. cor. of secs. 3 and 10, at
 proportionate dist.; not monumented.
- 13.30 Fence, bears N. and S.
- 14.865 Point for the W-E-W $\frac{1}{256}$ sec. cor. of secs. 3 and 10,
 at proportionate dist.

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	<p>Set the iron post 16 ins. in the ground, collar of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7N R29E W E W 1/256 $\frac{S 3}{S10}$ 1968</p>
	<p>from which</p>
	<p>A pine, 8 ins. diam., bears N. 64½° E., 18 lks. dist., mkd. W E W 1/256 S3 BT.</p>
	<p>A pine, 13 ins. diam., bears S. 12° E., 49 lks. dist., mkd. W E W 1/256 S10 BT.</p>
	<p>Cor. falls at west edge of timber, in an open area on a steep W. slope.</p>
<p>16.60</p>	<p>Milligan Creek, 30 lks. wide, with 4 ft. banks and small flow of water, course irregularly N. 30° E.</p>
<p>19.82</p>	<p>Point for the W 1/16 sec. cor. of secs. 3 and 10, at proportionate dist.; not monumented.</p>
<p>29.70</p>	<p>Leave open area, enter medium timber, bears N. and S.</p>
<p>39.64</p>	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber and bunchgrass.</p>
	<p>N. 2°08' W., between secs. 3 and 4.</p>
	<p>Over gently rolling land, through moderate timber.</p>
<p>2.10</p>	<p>Leave moderate timber, enter open meadow, bears E. and W.</p>
<p>6.20</p>	<p>Wash, 10 lks. wide, 3 ft. deep, drains irregularly N. 70° E.</p>
<p>12.00</p>	<p>Wash, 10 lks. wide, 3 ft. deep, drains irregularly SE.</p>
<p>16.95</p>	<p>Corral fence, bears E. and W.</p>
<p>18.76</p>	<p>Point for the S 1/16 sec. cor. of secs. 3 and 4, at proportionate distance.</p>
	<p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7N R29E S 1/16 S 4 S 3 1968</p>
	<p>from which</p>

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	<p>A pine, 8 ins. diam., bears N. 13° E., 164 lks. dist., mkd. S 1/16 S3 BT.</p> <p>A pine, 8 ins. diam., bears N. 56° W., 200 lks. dist., mkd. S 1/16 S4 BT.</p>
20.20	Fence, bears E. and W., enter dense timber.
27.60	Graded road, bears S. 80° E. and N. 80° W., enter mountainous land.
37.52	The 1/2 sec. cor. of secs. 3 and 4, monumented by an iron post, 1 in. diam., firmly set in a mound of stone to top, brass cap mkd.
	$\begin{array}{c} \frac{1}{2} \\ S\ 4\ \ S\ 3 \\ \hline 1936 \end{array}$
	from which
	<p>A juniper, 32 ins. diam., bears S. 28½° E., 112 lks. dist., mkd. 1/2 S3 BT. (Record: S. 46° E., 109 lks. dist.).</p> <p>A juniper, 25 ins. diam., bears S. 82° W., 146 lks. dist., mkd. 1/2 S4 BT.</p>
	<hr/>
	N. 2°28' W., beginning new measurement.
	Over mountainous land, through dense timber.
8.50	Fence, bears E. and W.
12.70	Wash, 30 lks. wide, 4 ft. deep, drains S. 70° E.
19.90	Leave dense timber, enter scattered timber, bears E. and W.
37.58	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone to top, brass cap mkd.
	$\begin{array}{c} T8N\ R29E \\ \hline S33\ \ S34 \\ \hline S\ 4\ \ S\ 3 \\ \hline T7N \\ 1936 \end{array}$
	from which the original bearing trees:
	<p>A juniper, 12 ins. diam., bears N. 38¾° E., 189 lks. dist., mkd. BT.</p> <p>A forked juniper, 13 ins. diam., bears S. 89½° E., 370 lks. dist., mkd. T7N R29E S3 BT.</p> <p>A pine, 15 ins. diam., bears S. 60° W., 198 lks. dist., mkd. with an overgrown blaze.</p> <p>A pine, 18 ins. diam., bears N. 0°15' W., 294 lks. dist., mkd. with an overgrown blaze.</p>

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	<p>Land, mountainous and rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber and bunch grass.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16. S. 89°11' W., between secs. 9 and 16. Over rolling land, through dense timber, along the south rim of Rudd Creek.</p>
18.30	Rudd Creek, 30 lks. wide, 4 ins. deep, course NE.
26.40	Fence, bears irregularly N. 48° E. and S. 30° W.
39.74	The ¼ sec. cor. of secs. 9 and 16, monumented by an iron post, 1 in. diam., firmly set in a mound of stone to top, brass cap mkd.
	$\frac{1}{4} \begin{array}{r} S 9 \\ S 16 \\ 1936 \end{array}$
	<p>from which the remains of the original bearing trees:</p> <p>A pine, 15 ins. diam., bears North, 91 lks. dist., mkd. ¼ S9 BT.</p> <p>A pine, 15 ins. diam., bears S. 85½° E., 35 lks. dist., mkd. with cut out blaze.</p> <p>Center of stump hole, with an uprooted tree 16 ins. diam. lying alongside, bears S. 6¼° W., 96 lks. dist., no visible mks. (Record 86 lks. dist.).</p> <p>Sawed off stump, 18 ins. diam., with cut log lying alongside, bears N. 76° W., 32 lks. dist., log mkd. ¼ BT. (Record 36 lks. dist., 36 ins. diam.).</p>
	<hr style="width: 20%; margin: auto;"/>
	S. 88°43' W., beginning new measurement.
8.50	Logging road, bears irregularly N. 80° E. and N. 80° W.
39.63	The cor. of secs. 8, 9, 16 and 17, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone to top, brass cap mkd.
	$\begin{array}{r} T7N R29E \\ S 8 S 9 \\ S 17 S 16 \\ 1936 \end{array}$
	<p>from which the remains of the original bearing trees:</p> <p>A pine, 12 ins. diam., bears N. 27° E., 64 lks. dist., mkd. T7N R29E S9 BT. (Record diam. 27 ins.).</p> <p>A pine stump, 27 ins. diam., bears S. 30½° E., 73 lks. dist., mkd. T7N R29E S visible. (Record 13 lks. dist.).</p>

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	<p>A pine, 13 ins. diam., bears S. $49\frac{1}{2}^{\circ}$ W., 41 lks. dist., mkd. T7N R29E S17 BT. (Record 14 lks. dist.).</p> <p>A pine, 16 ins. diam., bears N. $41\frac{3}{4}^{\circ}$ W., 38 lks. dist., mkd. T7N R29E S8 BT.</p> <p>Land, rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber.</p>
	<p>N. $10^{\circ}41'$ E., bet. secs. 8 and 9.</p> <p>Over rolling land, through dense timber, along an east slope.</p> <p>27.80 Ascend over a steep N. slope.</p> <p>33.10 Fence, bears N. 70° E. and S. 70° W.</p> <p>34.30 Milligan Creek, 15 lks. wide, with a small flow of water, course N. 70° E.</p> <p>40.33 The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented by an iron post, 1 in. diam., firmly set in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 8 S 9 1936</p> <p>from which the original bearing trees:</p> <p>A pine, 13 ins. diam., bears S. $80\frac{3}{4}^{\circ}$ E., 85 lks. dist., mkd. $\frac{1}{4}$ S9 BT.</p> <p>A juniper, 10 ins. diam., bears N. 39° W., 46 lks. dist., mkd. $\frac{1}{4}$ S8 BT.</p> <p>An undeveloped spring with a small flow of water, bears S. $24^{\circ}30'$ W., 7.25 chs. dist.</p>
19.475	<p>N. $9^{\circ}55'$ E., beginning new measurement.</p> <p>Over mountainous land, through dense timber.</p> <p>Point for the N $1/16$ sec. cor. of secs. 8 and 9, at proportionate distance.</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7N R29E N $1/16$ S 8 S 9 1968</p> <p>from which</p> <p>A juniper, 11 ins. diam., bears N. 20° E., 76 lks. dist., mkd. N $1/16$ S9 BT.</p>

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	<p>A pine, 15 ins. diam., bears S. 86° W., 52 lks. dist., mkd. N 1/16 S8 BT.</p> <p>An undeveloped spring with a small flow of water, bears N. 20° W., 130 lks. dist.</p> <p>Raise a mound of stone West of the corner.</p> <p>21.00 Creek, 4 lks. wide, 6 ins. deep, small flow of water, course East.</p> <p>38.95 The cor. of secs. 4, 5, 8 and 9, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7N R29E S 5 S 4 S 8 S 9 1936</p> <p>from which the original bearing trees:</p> <ul style="list-style-type: none"> A pine, 11 ins. diam., bears N. 51½° E., 54 lks. dist., mkd. with cut out blaze. A pine, 16 ins. diam., bears N. 54½° E., 74 lks. dist., mkd. T7N R29E S4 BT. A pine, 17 ins. diam., bears S. 62¾° E., 56 lks. dist., mkd. T7N R29E S. A pine, 17 ins. diam., bears S. 40½° E., 41 lks. dist., mkd. with cut out blaze. A pine, 30 ins. diam., bears S. 30½° W., 34 lks. dist., mkd. T7N R29E S8 BT. (Record diam. 36 ins.). A pine, 25 ins. diam., bears N. 16¼° W., 87 lks. dist., mkd. T7N R29E S5 BT. <p>Land, mountainous. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber.</p>
<p>4.97</p>	<p>From the cor. of secs. 3, 4; 9 and 10.</p> <p>N. 89°49' W., between secs. 4 and 9.</p> <p>Over gently rolling land, through medium timber.</p> <p>Point for the E-E-E 1/256 sec. cor. of secs. 4 and 9, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7N R29E E E E 1/256 $\frac{S 4}{S 9}$ 1968</p> <p>from which</p> <p>A pine, 5 ins. diam., bears S. 30° W., 71 lks. dist., mkd. E E E 1/256 S9 BT.</p>

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
	Raise a mound of stone N. of the cor.
8.62	A fence cor., bears S., 51 lks. dist.; fences bear S. and W.
9.94	Point for the E-E 1/64 sec. cor. of secs. 4 and 9, at proportionate dist.; not monumented.
14.70	Leave timber, enter open meadow, bears N. and S.
19.88	Point for the E 1/16 sec. cor. of secs. 4 and 9, at proportionate dist. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T7N R29E E 1/16 $\frac{S\ 4}{S\ 9}$ 1968 </div>
	from which <div style="text-align: center;"> A pine, 14 ins. diam., bears S. 6½° W., 41 lks. dist., mkd. E 1/16 S9 BT. A fence cor., bears S. 17° W., 101 lks. dist.; fences bear E. and N. 5° W. </div>
	Raise a mound of stone N. of the cor.
	Enter timber, bears N. and S.
20.32	Fence, bears N. and S.
24.20	Track road, bears irregularly N. 25° E. and S. 25° W.
39.76	The ¼ sec. cor. of secs. 4 and 9, monumented by an iron post, 1 in. diam., firmly set in a mound of stone to top, brass cap mkd. <div style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$ 1936 </div>
	from which <div style="text-align: center;"> A pine, 8 ins. diam., bears N. 12° E., 27 lks. dist., mkd. ¼ S4 BT. (Record 12 ins. diam., N. 8¾° E., 34 lks. dist.). A pine, 10 ins. diam., bears S. 54° W., 35 lks. dist., mkd. ¼ S9 BT. (Record 12 ins. diam., 26 lks. dist.). </div>
	N. 88°56' W., beginning new measurement.
	Over rolling mountain land, through dense timber.
8.80	Fence, bears irregularly N. 80° E. and S. 80° W.
12.10	Fence, bears N. 5° E. and S. 5° W., about 79 lks. dist., to a cor. of fences extending N. 5° E. and N. 85° E.

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS	
15.00	Graded road, bears N. and S.
19.505	Point for the W 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7N R29E W 1/16 $\frac{S\ 4}{S\ 9}$ 1968</p>
	from which
	A pine, 18 ins. diam., bears S. 10° E., 45 lks. dist., mkd. W 1/16 S9 BT.
	A pine, 13 ins. diam., bears S. 51° W., 28 lks. dist., mkd. T7N R29E W 1/16 S9 BT.
	Raise a mound of stone W. of the cor.
	Ascend over E. slope.
39.01	The cor. of secs. 4, 5, 8 and 9.
	<p>Land, gently rolling to mountainous. Soil, clay loam. Timber, pine and juniper. Undergrowth, bunch grass and scrub timber.</p>
	N. 3°41' W., bet. secs. 4 and 5.
	Over mountainous land, through dense timber, along an E. slope; by traverse, topography as taken from 1936 survey notes.
17.50	Improved road, Springerville to Big Lake, bears NE. and SW.
20.90	Same improved road, bears NW. and SE.
29.90	Branch of Milligan Creek, with flowing stream, 3 lks. wide, 1 in. deep, course E.
35.70	Improved dirt road, bears E., and bears W. for 2 chs. to a junction with the Springerville to Big Lake road.
37.12	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented by an iron post, 1 in. diam., firmly set with 10 ins. projecting above the ground, brass cap mkd.
	<p style="text-align: center;">$\frac{1}{4}$ S 5 S 4 1936</p>
	from which the original bearing trees:
	A pine, 10 ins. diam., bears S. 81 $\frac{3}{4}$ ° E., 66 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	A pine, 8 ins. diam., bears N. 53 $\frac{1}{4}$ ° W., 62 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

Dep. Resurvey, Portion Subdivisional Lines, T. 7 N., R. 29 E.

CHAINS													
	N. 3°32' W., beginning new measurement. Over mountainous land, through dense timber.												
15.70	Improved road, Springerville to Big Lake, bears N. 20° E. and S. 20° W.												
21.00	Draw, drains W.												
23.10	Spur, slopes NW.												
29.10	Draw, drains NW.												
34.30	Wash, 6 lks. wide, 3 ft. deep, drains NW.												
36.90	The cor. of secs. 4, 5, 32 and 33, on the North bdy. of the Tp., monumented by an iron post, 2 ins. diam., firmly set in a collar of stone, brass cap mkd.												
	<table style="margin: auto;"> <tr><td>T8N</td><td>R29E</td></tr> <tr><td>S32</td><td>S33</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td colspan="2" style="text-align: center;">T7N</td></tr> <tr><td colspan="2" style="text-align: center;">1936</td></tr> </table>	T8N	R29E	S32	S33	S 5	S 4	T7N		1936			
T8N	R29E												
S32	S33												
S 5	S 4												
T7N													
1936													
	from which the original bearing trees:												
	A pine, 12 ins. diam., bears N. 60½° E., 30 lks. dist., mkd. T8N R29E S33 BT.												
	A dead pine, 12 ins. diam., bears S. 57½° E., 69 lks. dist., mkd. TV11 RXX1X E S1V BT.												
	A dead pine, 18 ins. diam., bears S. 51½° E., 67 lks. dist., mkd. T7N R29E S4 BT.												
	A pine, 16 ins. diam., bears S. 83° W., 50 lks. dist., mkd. with illegible scribing.												
	A pine, 12 ins. diam., bears N. 50° W., 30 lks. dist., mkd. T8N R29E S32 BT.												
	Land, mountainous. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber.												
	Survey, Subdivision of Sec. 3, T. 7 N., R. 29 E.												
	From the ¼ sec. cor. of secs. 3 and 10. N. 1°52' W., on the N. and S. center line of sec. 3. Desc. over steep N. slope.												
9.47	Point for the C-S-S 1/64 sec. cor. of sec. 3.; this cor. was not monumented.												
18.94	Point for the C-S 1/16 sec. cor. of sec. 3. Set the iron post 20 ins. in the ground, brass cap mkd.												
	<table style="margin: auto;"> <tr><td></td><td>C</td><td></td></tr> <tr><td>C S 1/16</td><td> </td><td>S 3</td></tr> <tr><td></td><td>C</td><td></td></tr> <tr><td colspan="3" style="text-align: center;">1968</td></tr> </table>		C		C S 1/16		S 3		C		1968		
	C												
C S 1/16		S 3											
	C												
1968													

Survey, Subdivision of Sec. 3, T. 7 N., R. 29 E.

CHAINS	
	<p>from which</p> <p>A pine, 12 ins. diam., bears S. 89$\frac{3}{4}$° E., 61 lks. dist., mkd. X BT.</p> <p>A pine, 12 ins. diam., bears S. 40° W., 34 lks. dist., mkd. C S 1/16 S3 BT.</p>
20.90	Fence, bears N. 46° E. and S. 46° W.; enter open meadow.
22.60	Milligan Creek at inlet edge of an earthen stock tank, course East.
28.41	<p>Point for the C-N-S 1/64 sec. cor. of sec. 3.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>N S 1/64 S 3</p> <p>C</p> <p>1968</p> </div> <p>from which</p> <p>South edge of a metal stock tank, bears N. 79° 49' W., 9.28 chs. dist.</p> <p>A windmill, bears N. 76°30' W., 9.22 chs. dist.</p> <p>SE. corner of an old log cabin, 20 x 20 ft., with E. side bearing N. and S., bears N. 73°22' W., 9.85 chs. dist.</p> <p>A fence cor., bears N. 23° E., 81 lks. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located in an open meadow.</p>
29.16	Fence, bears S. 85° W. and N. 85° E. to a cor. of fences extending S. 34°20' E. and S. 85° W.
31.00	Track road, bears N. 73° E. and S. 73° W.; leave open meadow, bears E. and W.; ascend over S. slope through dense timber.
31.20	Old fence, bears E. and W.
33.60	Fence, bears S. 35° E. and N. 35° W.
37.88	<p>Point for the C $\frac{1}{4}$ sec. cor. of sec. 3, at intersection with the E. and W. center line of sec. 3.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R29E</p> <p>C $\frac{1}{4}$ S3</p> <p>1968</p> </div> <p>from which</p> <p>A juniper, 6 ins. diam., bears S. 73° W., 73 lks. dist., mkd. C $\frac{1}{4}$ S3 BT.</p> <p>A pine, 5 ins. diam., bears N. 38$\frac{1}{2}$° W., 34 lks. dist., mkd. C $\frac{1}{4}$ S3 BT.</p>

Survey, Subdivision of Sec. 3, T. 7 N., R. 29 E.

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p>
56.40	<p>Fence, bears S. 10° W., and bears N. 10° E. for about 150 lks. to a cor. of fences extending S. 80° E. and S. 10° W.</p>
57.90	<p>Rim, bears E. and W.; thence over mesa.</p>
75.93	<p>The ¼ sec. cor. of secs. 3 and 34 on the N. bdy. of the Tp., monumented by an iron post 1 in. diam., firmly set in a mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;"> $\frac{1}{4} \frac{S34}{S3}$ 1936 </p>
	<p>from which the original bearing trees:</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears N. 17½° E., 72 lks. dist., mkd. BT.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears S. 18½° W., 320 lks. dist., mkd. ¼ S3 BT.</p> <p>Land, mountainous. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber and bunchgrass.</p>
	<p>From the ¼ sec. cor. of secs. 2 and 3.</p>
	<p>N. 89°57' W., on the E. and W. center line of sec. 3.</p>
	<p>Over rolling land, through dense timber.</p>
10.70	<p>Track road, bears irregularly N. 70° E. and S. 70° W.</p>
26.20	<p>Fence, bears S. 30° E. and N. 10° W.</p>
40.11	<p>The C ¼ sec. cor. of sec. 3.</p>
43.00	<p>Fence, bears S. 35° E. and N. 35° W.</p>
57.70	<p>Wash, 15 lks. wide, 2 ft. deep, drains S. 20° E. for 200 lks., thence drains S. 80° E.</p>
60.00	<p>Point for the C-W 1/16 sec. cor. of sec. 3.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;"> $W \frac{1}{16}$ $C \frac{\quad}{S3} C$ 1968 </p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 28½° W., 21 lks. dist., mkd. CW 1/16 S3 BT.</p>
	<p style="padding-left: 40px;">An alligator juniper, 30 ins. diam., bears N. 86½° W., 71 lks. dist., mkd. CW 1/16 S3 BT.</p>
	<p>Raise a mound of stone N. of the cor.</p>

Survey, Subdivision of Sec. 3, T. 7 N., R. 29 E.

CHAINS	
	<p>The cor. is located on a NE. slope and on the W. side of a draw draining SE.</p>
<p>79.89</p>	<p>The ½ sec. cor. of secs. 3 and 4.</p> <p>Land, rolling and mountainous. Soil, clay loam. Timber, cedar, pine and alligator juniper. Undergrowth, bunchgrass and scrub timber.</p> <hr/> <p style="text-align: center;">Subdivision of the SW ¼ of Sec. 3</p> <hr/> <p>From the point for the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 1°59' W., on the N. and S. center line of the SW ¼ of sec. 3.</p> <p>Over gently rolling meadow land.</p> <p>8.40 Leave meadow, enter scattered timber, bears N. 70° E. and S. 70° W.</p> <p>9.43 Point for the C-S-SW 1/64 sec. cor. of sec. 3; not monumented.</p> <p>14.00 Wash, 4 lks. wide, 3 ins. deep, small flow of water, course N. 85° E.</p> <p>15.25 Fence, bears irregularly E. and W.</p> <p>18.86 Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E. and W. center line of the SW ¼ of sec. 3.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S3 1968</p> <p>from which</p> <p style="text-align: center;">A fence cor. bears N. 14¾° W., 9 lks. dist.; fences bear N. 0°24' E. and S. 88°48' W.</p> <p>Raise a mound of stone W. of the cor.</p> <p>24.80 Track road, bears irregularly NE. and SW.</p> <p>26.40 Improved road, bears E. curving NE., and N. 65° W. for 150 lks., thence W.; ascend S. slope through dense timber.</p> <p>28.275 Point for the C-N-SW 1/64 sec. cor. of sec. 3.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C N SW 1/64 S3 1968</p>

Survey, Subdivision of Sec. 3, T. 7 N., R. 29 E.

CHAINS	
	<p>from which</p> <p>A pine, 8 ins. diam., bears S. $9\frac{1}{2}^{\circ}$ W., 66 lks. dist., mkd. C N SW $\frac{1}{64}$ S3 BT.</p> <p>An alligator juniper, 35 ins. diam., bears N. $89\frac{1}{2}^{\circ}$ W., 110 lks. dist., mkd. C N SW $\frac{1}{64}$ S3 BT.</p> <p>Raise a mound of stone W. of the cor.</p> <p>36.30 Descend over NE. slope.</p> <p>37.69 The C-W $\frac{1}{16}$ sec. cor. of sec. 3.</p>
	<p>From the C-S $\frac{1}{16}$ sec. cor. of sec. 3.</p> <p>N. $89^{\circ}40'$ W., on the E. and W. center line of the SW $\frac{1}{2}$ of sec. 3.</p> <p>Over rolling land, through dense timber.</p> <p>2.56 Fence, bears N. 55° E. and S. 55° W.</p> <p>2.68 Fence, bears S. 35° E. and N. 35° W.; leave dense timber, enter scattered timber, bears N. 55° E. and S. 55° W.</p> <p>6.20 Milligan Creek, 40 lks. wide with 8 ft. banks, small flow of water, courses N. 50° E. emptying into an earthen stock pond.</p> <p>9.935 Point for the C-E-SW $\frac{1}{64}$ sec. cor. of sec. 3.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">CE SW $\frac{1}{64}$ S3 1968</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located 53 lks. S. of a fence bearing E. and W.</p> <p>The cor. is located 50 lks. N. of a wash, 50 lks. wide, with 12 ft. banks, drains Easterly.</p> <p>11.40 Fence, bears N. 70° E. and S. 70° W.</p> <p>19.87 The SW $\frac{1}{16}$ sec. cor. of sec. 3.</p> <p>23.80 Fence, bears N. and S.</p> <p>38.20 Fence, bears N. and S.</p> <p>39.73 The S $\frac{1}{16}$ sec. cor. of secs. 3 and 4.</p>
	<p style="text-align: center;">Subdivision of the SE $\frac{1}{2}$ SW $\frac{1}{2}$ of sec. 3</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the E-W $\frac{1}{64}$ sec. cor. of secs. 3 and 10.</p> <p>N. $1^{\circ}55'$ W., on the N. and S. center line of the SE $\frac{1}{2}$ SW $\frac{1}{2}$ of sec. 3.</p>

Survey, Subdivision of Sec. 3, T. 7 N., R. 29 E.

CHAINS	
	Descend over NW. slope, through dense timber.
9.46	Point for the SE-SW 1/64 sec. cor. of sec. 3, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 3.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	SE SW 1/64 S3 1968
	from which
	A pine, 7 $\frac{1}{2}$ ins. diam., bears S. 70° W., 93 lks. dist., mkd. SE SW 1/64 S3 BT.
	No other suitable bearing trees available.
11.45	Fence, bears irregularly N. 30° E. and S. 30° W.
13.70	Milligan Creek, 40 lks. wide, with 10 ft. banks, small flowing stream, course N. 70° E.; leave dense timber, enter widely scattered timber.
18.40	Wash, 50 lks. wide, 12 ft. deep, drains E.
18.925	The C-E-SW 1/64 sec. cor. of sec. 3.

	From the point for the C-S-S 1/64 sec. cor. of sec. 3. N. 89°33' W., on the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 3.
	Over a NW. slope, through dense timber.
9.925	The SE-SW 1/64 sec. cor. of sec. 3.
11.15	Fence, bears N. 30° E. and S. 30° W.; leave dense timber, enter widely scattered timber, bears N. 30° E. and S. 30° W.
14.40	Milligan Creek, 40 lks. wide, with 10 ft. banks, a small flowing stream, course NE.
14.885	Point for the C-W-SE-SW 1/256 sec. cor. of sec. 3.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	C W SE SW 1/256 S3 1968
	Raise a mound of stone W. of the cor.
15.20	Wash, 25 lks. wide, 8 ft. deep, drains NE.
19.845	Point for the C-S-SW 1/64 sec. cor. of sec. 3.

Survey, Subdivision of Sec. 4, T. 7 N., R. 29 E.

CHAINS	Survey, Subdivision of Sec. 4, T. 7 N., R. 29 E.
	<p>From the $\frac{1}{2}$ sec. cor. of secs. 4 and 9.</p> <p>N. $2^{\circ}39'$ W., on the N. and S. center line of sec. 4.</p> <p>Over rolling land, through dense timber.</p> <p>2.10 Fence, bears N. 78° E. and S. 78° W.</p> <p>4.90 Draw, drains SW.</p> <p>11.00 Ridge, bears E. and W.; desc. N. slope.</p> <p>18.785 Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 4.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S $\frac{1}{16}$ S 4</p> <p>C</p> <p>1968</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. $55\frac{1}{2}^{\circ}$ E., 10 lks. dist., mkd. C S $\frac{1}{16}$ S4 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ W., 19 lks. dist., mkd. X BT.</p> <p>22.50 Draw, drains E.; asc. S. slope.</p> <p>25.70 Ridge, bears E. and W.; desc. N. slope.</p> <p>27.20 Wash, 6 lks. wide, 1 ft. deep, drains E.</p> <p>30.40 Graded road, bears S. $84\frac{1}{2}^{\circ}$ E. and N. $84\frac{1}{2}^{\circ}$ W.</p> <p>37.57 Point for the C $\frac{1}{4}$ sec. cor. of sec. 4, at intersection with the E. and W. center line of sec. 4.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7N R29E</p> <p>C $\frac{1}{4}$ S4</p> <p>1968</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ E., 21 lks. dist., mkd. C $\frac{1}{4}$ S4 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 48° W., 19 lks. dist., mkd. C $\frac{1}{4}$ S4 BT.</p> <p style="padding-left: 40px;">A wooden hub, bears S. $14^{\circ}02'$ E., 3.5 lks. dist.</p> <p>40.00 Leave rolling land, enter mesa, bears E. and W.</p>

Survey, Subdivision of Sec. 4, T. 7 N., R. 29 E.

CHAINS	
45.00	Leave dense timber, bears E. and W.; enter scattered timber.
74.79	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., monumented by an iron post, 1 in. diam., firmly set with 12 ins. projecting above the ground, brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ $\frac{S33}{S4}$ 1936</p> <p>There is no remaining evidence of the original bearing trees.</p> <p>Land, mountainous. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber.</p>
16.60	<p>From the $\frac{1}{4}$ sec. cor. of secs. 3 and 4. N. $89^{\circ}46'$ W., on the E. and W. center line of sec. 4. Over rolling land, through dense timber.</p>
20.065	<p>Fence, bears N. 17° E. and S. 17° W.</p> <p>Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 4.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to the top, brass cap mkd.</p> <p style="text-align: center;">E $\frac{1}{16}$ C ————— C S 4 1968</p> <p>from which</p> <p style="padding-left: 40px;">A juniper fork, 5 ins. diam., bears S. $41\frac{1}{2}^{\circ}$ W., 43 lks. dist., mkd. CE $\frac{1}{16}$ S4 BT.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 85° W., 17 lks. dist., mkd. CE $\frac{1}{16}$ S4 BT.</p>
40.13	<p>The C $\frac{1}{4}$ sec. cor. of sec. 4. Continue along a south slope.</p>
79.81	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 5.</p> <p>Land, rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, scrub timber.</p>
<p>Subdivision of the SE $\frac{1}{4}$ of sec. 4</p> <hr style="width: 20%; margin: auto;"/> <p>From the E $\frac{1}{16}$ sec. cor. of secs. 4 and 9.</p>	

Survey, Subdivision of Sec. 4, T. 7 N., R. 29 E.

CHAINS	
	N. 2°23' W., on the N. and S. center line of the SE¼ of sec. 4.
	Over gently rolling land, through med. timber.
8.20	Leave timber, enter open meadow, bears E. and W.
13.80	Draw, drains East 260 lks. dist. to an earthen diversion dam.
18.77	Point for the SE 1/16 sec. cor. of sec. 4 at the intersection with the E. and W. center line of the SE¼ of sec. 4.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	SE 1/16 S 4 1968
	from which
	The N. end of the roof of a cabin, bears S. 26°50' E., 330 lks. dist.
	A windmill, bears S. 42°20' E., 193 lks. dist.
	Raise a mound of stone W. of the cor.
20.09	Fence, bears E. and W.; leave open meadow, enter dense timber, bears E. and W.
20.60	Wash, 20 lks. wide with 5 ft. banks, course SE.
28.60	Improved road, bears S. 84° E. and N. 84° W.
31.50	Fence, bears N. and S.
37.52	The C-E 1/16 sec. cor. of sec. 4.
From the S 1/16 sec. cor. of secs. 3 and 4.	
	N. 89°45' W., on the E. and W. center line of the SE¼ of sec. 4.
	Over gently rolling land, through scattered timber.
9.00	Wash, 30 lks. wide, 3 ft. deep, drains S. 15° E.; leave timber, enter open meadow.
17.70	Track road, bears N. and S.
17.80	Old fence, bears N. and S.
19.98	The SE 1/16 sec. cor. of sec. 4.
20.35	Fence, bears N. and S.; leave open meadow, enter dense timber.
39.97	The C-S 1/16 sec. cor. of sec. 4.
Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.	
From the ¼ sec. cor. of secs. 9 and 16.	

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
	N. 10°04' E., on the N. and S. center line of sec. 9. Over rolling land, through medium timber.
3.60	Track road, bears NE. and SW.
9.80	Ridge, bears E. and W.
19.60	Track road, bears NE. and SW.; draw, drains NE.
21.00	Spur, slopes NE.
22.40	Draw, drains E.
36.10	Spur, slopes E.
38.40	Improved road, curves from East to NW.
39.06	Fence, bears S. 80° W. and bears N. 80° E., 1.7 lks. to a cor. of fences extending N. 10° E., S. 89° E. and S. 80° W.
39.16	Point for the C 1/4 sec. cor. of sec. 9, at intersection with the E. and W. center line of sec. 9. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T7N R29E C 1/4 S 9 1968 </div> from which A pine, 5 ins. diam., bears S. 75° E., 24 lks. dist., mkd. X BT. A pine, 10 ins. diam., bears S. 15° W., 63 lks. dist., mkd. C 1/4 S9 BT. A local cor., bears S. 5° W., 10 lks. dist., monumented by a stone, 10 x 10 ins., firmly set with 10 ins. projecting above the ground, mkd. HES 228 6 on the N. face, 1/4 on the S. face and an X on top. Raise a mound of stone W. of the cor. 40.80 Leave timber, enter open meadow, bears E. and W. 46.30 Milligan Creek, 15 lks. wide, 1 ft. deep, drains E. 53.56 Point for the C-N-S-N 1/256 sec. cor. of sec. 9. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> C C N S N S 9 1/256 C 1968 </div> from which A local cor., monumented by a stone, 18 x 12 ins., firmly set with 6 ins. projecting above the ground, mkd. X on top and HES 228 on the W. face, bears S. 15° W., 8 lks. dist.

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
	<p>The NW. cor. of a cabin, bears S. 5° E., 81 lks. dist.</p> <p>A water trough, with 1 in. diam. plastic pipe flowing ½ full, bears South, 10 lks. dist.</p> <p>The cor. is located 1 lk. West of a fence bearing N. 10° E. and S. 10° W.</p> <p>Raise a mound of stone W. of the cor.</p>
55.00	<p>Track road, bears irregularly W. and E. for 20 lks., thence S. for 250 lks., thence easterly.</p> <p>Leave open meadow, enter med. timber, bears E. and W.</p>
56.00	<p>Fence, bears N. 81° E. and S. 81° W., 14 lks. to a fence cor. with fences extending N. 81° E., S., W. and NW.</p>
58.36	<p>Point for the C-N 1/16 sec. cor. of sec. 9.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C</p> <p> </p> <p>C N 1/16 S 9</p> <p> </p> <p>C</p> <p>1968</p> </div> <p>from which</p> <p>A pine, 7 ins. diam., bears S. 43° E., 89 lks. dist., mkd. T7N CN 1/16 S9 BT.</p> <p>A pine, 10 ins. diam., bears N. 69° W., 60 lks. dist., mkd. CN 1/16 S9 BT.</p>
59.60	<p>Top of knoll.</p>
73.30	<p>Asc. steep S. slope.</p>
77.55	<p>The ¼ sec. cor. of secs. 4 and 9.</p> <p>Land, rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, bunchgrass and scrub timber.</p>
	<p>From the ¼ sec. cor. of secs. 9 and 10.</p> <p>N. 89°45' W., on the E. and W. center line of sec. 9.</p> <p>Over nearly level land, through open meadow, along the N. side of a fence, bearing westerly.</p>
10.40	<p>Leave open meadow, enter scattered timber, bears N. and S.</p>
19.84	<p>Point for the C-E 1/16 sec. cor. of sec. 9.</p>

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
	<p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">C E 1/16 S 9 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 80° E., 47 lks. dist., mkd. CE 1/16 S9 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 19° W., 42 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fence cor. bears S. 39° E., 37 lks. dist. with fences extending S., E. and W.</p> <p>The cor. is located 73 lks. North of a graded road bearing E. and W.</p>
21.50	Fence, bears N. 19° E. and S. 19° W.
39.68	The C ¼ sec. cor. of sec. 9.
40.30	Graded road, bears S. 18° E. and N. 18° W.
54.70	Fence, bears N. 9° E. and S. 9° W.
59.155	Point for the C-W 1/16 sec. cor. of sec. 9.
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">W 1/16</p> <p style="text-align: center;">C ————— C S 9 1968</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears S. 12° E., 67 lks. dist., mkd. CW 1/16 S9 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 56° W., 30 lks. dist., mkd. CW 1/16 S9 BT.</p> <p>The cor. is located 123 lks. North of an E-W. fence.</p>
63.80	Top of a knoll; desc. steep W. slope.
70.95	Milligan Creek, 5 lks. wide, 2 ft. deep, with a small flowing stream and with a 1½ in. plastic water line paralleling the stream, course N.
73.80	Jeep trail, bears N. and S.
78.63	The ¼ sec. cor. of secs. 8 and 9.
	<p>Land, rolling and mountainous. Soil, silt clay loam. Timber, pine and juniper. Undergrowth, bunchgrass and scrub timber.</p>

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
	<p>Subdivision of the NE$\frac{1}{4}$ of sec. 9</p> <hr/>
	<p>From the C-E 1/16 sec. cor. of sec. 9.</p> <p>N. 10°07' E., on the N. and S. center line of the NE$\frac{1}{4}$ of sec. 9.</p> <p>Over rolling land, through dense timber.</p>
1.90	Leave dense timber, enter open meadow, bears E. and W.
6.30	Track road, bears NW. and SE. for about 2.00 chs., thence curves to NE.
14.42	<p>Point for the C-N-S-NE 1/256 sec. cor. of sec. 9.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C N S NE 1/256 S 9 1968</p> <p>Raise a mound of stone W. of the cor.</p>
15.30	Milligan Creek, 70 lks. wide, 25 ft. deep, with a small flowing stream, course E.
19.225	<p>Point for the NE 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the NE$\frac{1}{4}$ of sec. 9.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 9 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 6° E., 143 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 22 ins. diam., bears N. 51° W., 117 lks. dist., mkd. NE 1/16 S9 BT.</p> <p>Raise a mound of stone W. of the cor.</p>
20.40	Wash, 20 lks. wide, 3 ft. deep, drains E.
20.60	Leave meadow, enter timber, bears E. and W.
21.20	Fence, bears E. and W.
28.84	Point for the C-N-NE 1/64 sec. cor. of sec. 9; not monumented.
29.50	Spur, slopes E.
37.50	Fence, bears E., and bears W., 20 lks. dist. to a cor. of fences extending N., S. and E.
38.455	The E 1/16 sec. cor. of sec. 4 and 9.

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
	From the N 1/16 sec. cor. of secs. 9 and 10.
	N. 89°48' W., on the E. and W. center line of the NE 1/4 of sec. 9.
	Over open meadow.
3.35	Track road bears N. for 2 chs., thence NW., and bears S. for 1 ch., thence E.
4.965	Point for the C-E-E-NE 1/256 sec. cor. of sec. 9; not monumented.
9.93	Point for the C-E-NE 1/64 sec. cor. of sec. 9; not monumented.
11.00	Track road, bears N. 35° E. and S. 70° W.
12.80	Milligan Creek, 110 lks. wide, 20 ft. deep, drains N. 35° E., for about 5.00 chs. to an earthen stock pond.
19.855	The NE 1/16 sec. cor. of sec. 9.
27.80	Fence, bears N. 77° E. and S. 77° W.; leave open meadow and enter timber.
39.71	The C N 1/16 sec. cor. of sec. 9.
Subdivision of the NE 1/4 NE 1/4 of sec. 9	
	From the point for the C-E-NE 1/64 sec. cor. of sec. 9.
	N. 10°10' E. on the N. and S. center line of the NE 1/4 NE 1/4 of sec. 9.
	Over open meadow.
0.30	Track road, bears N. 35° E. and S. 35° W.
1.60	Milligan Creek, 200 lks. wide, 15 ft. deep, at the W. edge of an earthen stock tank.
3.40	Leave open meadow, enter scattered timber.
4.81	Point for the C-S-NE-NE 1/256 sec. cor. of sec. 9; not monumented.
9.62	Point for the NE-NE 1/64 sec. cor. of sec. 9, at the intersection of the E. and W. center line of the NE 1/4 NE 1/4 of sec. 9; not monumented.
13.90	Top of ridge, bears E. and W.
18.80	Fence, bears E. and W.
19.24	Point for the E-E 1/64 sec. cor. of secs. 4 and 9.

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
	<p>From the point for the N-N 1/64 sec. cor. of secs. 9 and 10.</p> <p>N. 89°48' W., on the E. and W. center line of the NE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 9.</p> <p>Over open meadow.</p>
4.975	Point for the C-E-NE-NE 1/256 sec. cor. of sec. 9; not monumented.
6.80	Fence, bears N. and S., leave open meadow, enter timber.
9.95	Point for the NE-NE 1/64 sec. cor. of sec. 9.
19.89	Point for the C-N-NE 1/64 sec. cor. of sec. 9.
<p>Subdivision of the SE$\frac{1}{4}$NE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 9</p> <hr/>	
	<p>From the point for the C-E-E-NE 1/256 sec. cor. of sec. 9.</p> <p>N. 10°15' E. on the N. and S. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 9,</p>
2.00	Track road, bears E. and W.
2.90	Milligan Creek, 150 lks. wide, 20 ft. deep, drains N. 80° E.
3.48	Fence, bears N. 75° E., and S. 75° W. for 6 lks. to a cor. of fences extending N. and N. 75° E.
4.81	Point for the SE-NE-NE 1/256 sec. cor. of sec. 9 at the intersection of the E. and W. center line of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 9.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>SE NE NE 1/256 S 9 1968</p>
	Raise a mound of stone W. of the cor.
9.625	Point for the C-E-NE-NE 1/256 sec. cor. of sec. 9.
<hr/>	
	<p>From the S-N-N 1/256 sec. cor. of secs. 9 and 10.</p> <p>N. 89°48' W., on the E. and W. center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 9.</p>
4.97	The SE-NE-NE 1/256 sec. cor. of sec. 9.
5.40	Fence, bears N. and S.
9.945	Point for the C-S-NE-NE 1/256 sec. cor. of sec. 9.

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
	<p>Subdivision of the NW$\frac{1}{4}$ of sec. 9</p> <hr/>
	<p>From the C-W 1/16 sec. cor. of sec. 9.</p> <p>N. 9°58' E., on the N. and S. center line of the NW$\frac{1}{4}$ of sec. 9.</p> <p>Along a steep NE. slope, through dense timber.</p>
11.40	Fence, bears SE., and NW. for 20 lks., thence irregularly N. 15° W.
12.00	Milligan Creek, drains E., asc. SE. slope.
14.70	Same fence, bears irregularly S. 65° E., and N. 65° W., 200 lks. to a cor. of fences extending S. 65° E. and S. 15° E.
19.32	Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the NW $\frac{1}{4}$ of sec. 9.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 9 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 42° E., 47 lks. dist., mkd. NW 1/16 S9 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 40° E., 46 lks. dist., mkd. T7N R29E NW 1/16 S9 BT.</p> <p>Raise a mound of stone W. of the cor.</p>
21.90	Track road, in a small draw, bears E. and W.; the draw drains E.
23.80	Small spur, slopes E.
33.20	Small spur, slopes E.
38.67	The W 1/16 sec. cor. of secs. 4 and 9.
	<hr/> <p>From the C-N 1/16 sec. cor. of sec. 9.</p> <p>N. 89°20' W., on the E. and W. center line of the NW$\frac{1}{4}$ of sec. 9.</p>
9.40	Fence, bears S. 3° E. and N. 3° W.
12.30	Graded road, bears S. 45° E. and N. 20° W.
14.90	Wash, 15 lks. wide, 3 ft. deep, drains SE.
19.485	The NW 1/16 sec. cor. of sec. 9.

Survey, Subdivision of Sec. 9, T. 7 N., R. 29 E.

CHAINS	
24.53	Track road, bears N. 20° E. and S. 20° W.
38.97	The N 1/16 sec. cor. of secs. 8 and 9.
Survey, Subdivision of Sec. 10, T. 7 N., R. 29 E.	
	From the 1/4 sec. cor. of secs. 10 and 15.
	N. 10°00' E., on the N. and S. center line of sec. 10.
	Over rolling land, through medium timber.
2.90	Track road, bears N. 70° E. and S. 70° W.
6.00	Rudd Creek, 5 lks. wide, 4 ins. deep, course E.
9.83	Fence, bears E., and W.
13.80	Top of a narrow ridge, bears E. and W.
18.70	Track road, in bottom of a draw, bears E. and W.; draw drains E.
37.94	Point for the C 1/4 sec. cor. of sec. 10, at intersection with the E. and W. center line of sec. 10.
	Set the iron post 22 ins. in the ground, mound of stone to top, brass cap mkd.
	T7N R29E C 1/4 S10 1968
	from which
	A pine, 8 ins. diam., bears S. 79° E., 24.5 lks. dist., mkd. X BT.
	A pine, 10 ins. diam., bears S. 33° W., 35 lks. dist., mkd. C 1/4 S10 BT.
	A fence cor., bears N. 17° W., 104 lks. dist.; fence bears N. 10° E. and W.
40.00	Wash, 15 lks. wide, 4 ft. deep, drains W.
57.37	Point for the C-N 1/16 sec. cor. of sec. 10.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	C N 1/16 S10 C 1968
	from which
	A pine, 10 ins. diam., bears S. 4° E., 41 lks. dist., mkd. CN 1/16 S10 BT.

Survey, Subdivision of Sec. 10, T. 7 N., R. 29 E.

CHAINS	
62.23	<p>The cor. is located 40 lks. E. of a fence bearing approximately N. 10° E. and S. 10° W.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Point for the C-S-N-N 1/256 sec. cor. of sec. 10.</p> <p>Set the iron post 12 ins. in the ground to bed rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C S N N 1/256 S10 1968</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. 54° E., 6 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fence cor. bears N. 32° W., 64 lks. dist. with fences extending approximately S. 10° E. and W.</p> <p>Cor. is on a steep S. slope.</p>
67.09	<p>Point for the C-N-N 1/64 sec. cor. of sec. 10. This cor. was not monumented.</p>
76.81	<p>The 1/4 sec. cor. of secs. 3 and 10.</p>
	<p>Land, rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, bunchgrass and scrub timber.</p>
6.50	<p>Top of a vertical cliff, 70 ft. high, bears NE. and SW., thence over gently rolling land.</p>
42.51	<p>The C 1/4 sec. cor. of sec. 10.</p>
62.37	<p>Point for the C-W 1/16 sec. cor. of sec. 10.</p>
	<p>Set the iron post 16 ins. in the ground, collar of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">W 1/16</p>
	<p style="text-align: center;">C ————— C</p>
	<p style="text-align: center;">S10</p>
	<p style="text-align: center;">1968</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 15° E., 4 lks. dist., mkd. C W 1/16 S10 BT.</p>

Survey, Subdivision of Sec. 10, T. 7 N., R. 29 E.

CHAINS	
	<p>A pine, 10 ins. diam., bears S. 69½° W., 28 lks. dist., mkd. X BT.</p> <p>The cor. is located 40 lks. S. of a fence bearing E. and W.</p>
68.90	A fence cor., bears N. 30 lks. dist., with fences extending E., W. and N. 5° W.
72.00	Enter open meadow, bears N. and S.
78.00	Fence, bears E. and W.
82.23	The ¼ sec. cor. of secs. 9 and 10.
	<p>Land, gently rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, bunchgrass and scrub timber.</p>
<p>Subdivision of the NW¼ of sec. 10</p> <hr/>	
	<p>From the C-W 1/16 sec. cor. of sec. 10.</p> <p>N. 10°05' E., on the N. and S. center line of the NW¼ of sec. 10.</p> <p>Over gently rolling land, through scattered timber.</p>
0.40	Fence, bears E. and W.
4.90	Leave timber, enter open meadow, bears E. and W.
19.20	Track road, bears irregularly SE. and NW.
19.325	Point for the NW 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the NW¼ of sec. 10.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S10 1968</p>
	<p>Raise a mound of stone W. of the cor.</p>
23.70	Fence, bears E. and W.; leave open meadow and enter scattered timber.
24.16	Point for the C-S-N-NW 1/256 sec. cor. of sec. 10.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C S N NW 1/256 S10 1968</p>
	<p>Raise a mound of stone W. of the cor.</p>
28.995	Point for the C-N-NW 1/64 sec. cor. of sec. 10; not monumented.

Survey, Subdivision of Sec. 10, T. 7 N., R. 29 E.

CHAINS	
38.30	Milligan Creek, 15 lks. wide, 4 ft. deep, drains E.
38.67	Point for the W 1/16 sec. cor. of secs. 3 and 10.
<hr/>	
From the C-N 1/16 sec. cor. of sec. 10.	
N. 89°02' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 10.	
Over rolling land, through medium timber.	
0.40	Fence, bears approximately N. 10° E. and S. 10° W.
8.00	Leave timber, enter open meadow, bears N. and S.
9.913	Point for the C-E-NW 1/64 sec. cor. of sec. 10. This cor. was not monumented.
13.00	Wash, 40 lks. wide, with 3 ft. banks and a small flow of water, course N.
14.869	Point for the C-W-E-NW 1/256 sec. cor. of sec. 10; not monumented.
19.825	The NW 1/16 sec. cor. of sec. 10.
20.00	Track road, bears SE. and NW.
31.20	Fence, bears N. and S.
35.90	Track road, bears irregularly N. 50° E. and S. 70° W.
39.67	The N 1/16 sec. cor. of secs. 9 and 10.
Land, gently rolling. Soil, clay loam. Timber, pine and juniper. Undergrowth, bunchgrass and scrub timber.	
<hr/>	
Subdivision of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10	
<hr/>	
From the C-E-NW 1/64 sec. cor. of sec. 10.	
N. 10°02' E., on the N. and S. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10.	
Over gently rolling land, through medium timber, along a W. slope.	
4.845	Point for the C-S-NE-NW 1/256 sec. cor. of sec. 10; not monumented.
5.80	Fence, bears S. 85° E. and N. 85° W.
9.69	Point for the NE-NW 1/64 sec. cor. of sec. 10, at intersection with the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10; not monumented.
19.38	Point for the E-W 1/64 sec. cor. of secs. 3 and 10.
<hr/>	

Survey, Subdivision of Sec. 10, T. 7 N., R. 29 E.

CHAINS	
	<p>From the point for the C-N-N 1/64 sec. cor. of sec. 10.</p> <p>N. 89°11' W., on the E. and W. center line of the NE$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 10.</p>
9.913	Point for the NE-NW 1/64 sec. cor. of sec. 10.
14.874	Point for the C-W-NE-NW 1/256 sec. cor. of sec. 10; not monumented.
15.00	Wash, 40 lks. wide, with 3 ft. banks and a small flow of water, course N.
19.835	Point for the C-N-NW 1/64 sec. cor. of sec. 10.
	<p>From the point for the C-W-E-NW 1/256 sec. cor. of sec. 10.</p> <p>N. 10°04' E., on the N. and S. center line of the SW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 10.</p>
0.23	Fence, bears E. and W.
4.41	Fence, bears E. and W.
4.835	Point for the SW-NE-NW 1/256 sec. cor. of sec. 10, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 10.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>SW NE NW 1/256 S10 1968</p>
	Raise a mound of stone W. of the cor.
9.60	Wash, 40 lks. wide, 3 ft. banks, small flow of water, course N.
9.68	Point for the C-W-NE-NW 1/256 sec. cor. of sec. 10.
	<p>From the point for the C-S-NE-NW 1/256 sec. cor. of sec. 10.</p> <p>N. 89°08' W., on the E. and W. center line of the SW$\frac{1}{4}$NE$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 10.</p>
0.70	Fence, bears N., and bears S. for 45 lks. to a fence cor. with fences extending N. and W.
4.90	Wash, dry, 30 lks. wide, with 3 ft. banks, course N. 10° E.
4.96	The SW-NE-NW 1/256 sec. cor. of sec. 10.
9.92	Point for the C-S-N-NW 1/256 sec. cor. of sec. 10.

Survey, Subdivision of Sec. 10, T. 7 N., R. 29 E.

CHAINS	General Description
	<p>The portion of Township 7 North, Range 29 East, included in this survey, lies in the south-central part of Apache County, approximately 8 miles south of Springerville, Arizona. Private land owners have developed several springs and buildings on the patented land. Livestock grazing and timber are the principal uses of this land at the present.</p> <p>The land is mountainous, with a valley approximately one mile wide in the center of the areas surveyed and along the drainage of Milligan Creek. The valley is approximately 8400 feet above sea level. The mountains rise sharply to approximately 9,000 feet. The mountains are covered with a dense growth of pine, cedar and juniper. The soil is a clay loam in the valley and a rocky clay loam on the hillsides. Milligan Creek is fed from scattered developed and undeveloped springs and seeps. There are 2 earthen stock tanks, one located in sec. 3 and the other in sec. 9. There is a graded all weather road, providing excellent access to most of the surveyed area. There is no mining activity in the area surveyed.</p>

37

CERTIFICATE OF SURVEY

(I) (~~we~~), Jerrold E. Knight, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23 day of May, 1968, (I) (~~we~~) have made a dependent resurvey of a portion of the subdivisional lines, and a survey of subdivisions in sections 3, 4, 9, and 10, Township 7 North, Range 29 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 1, 1970 (Date) [Signature: Jerrold E. Knight] (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date JAN 22 1971 BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, and the survey of subdivisions in sections 3, 4, 9 and 10, Township 7 North, Range 29 East, Gila and Salt River Meridian, Arizona,

executed by Jerrold E. Knight having been critically examined and found correct, are hereby approved.

DEC 28 1971 (Date) [Signature: Clark F. Sumner] (Chief, Division of Cadastral Survey)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626