

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

RETRACEMENT

OF A

PORTION OF THE SOUTH BOUNDARY

DEPENDENT RESURVEY

OF

PORTION

OF THE

EAST AND NORTH BOUNDARIES

AND

SUBDIVISIONAL LINES

SURVEY

OF

SUBDIVISIONS IN SECTION 36

TOWNSHIP 9 SOUTH, RANGE 28 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Kenneth D. Herman Cadastral Surveyor

Louis D. Gilbert Cadastral Surveyor

Under special instructions dated December 13, 19 67, which provided for the surveys included under Group Number 478, approved December 14, 1967, and assignment instructions dated December 14, 19 67.

Survey commenced January 8, 19 68

Survey completed January 31, 19 68

1A

BOOK 4919 INDEX DIAGRAM

Township 9 South, Range 28 East

| | | | | | |
|-------|-------|-------|-------|-------|----|
| | 2 | 3 | 4 | 5 | 6 |
| 6 48 | 5 38 | 4 30 | 3 21 | 2 13 | 1 |
| 47 | 46 | 37 | 29 | 20 | 12 |
| 7 46 | 8 36 | 9 28 | 10 19 | 11 11 | 12 |
| 45 | 45 | 36 | 27 | 19 | |
| 18 44 | 17 35 | 16 26 | 15 18 | 14 11 | 13 |
| 43 | 43 | 34 | 26 | 17 | |
| 19 42 | 20 33 | 21 25 | 22 17 | 23 10 | 24 |
| 41 | 40 | 33 | 24 | 16 | 9 |
| 30 39 | 29 32 | 28 23 | 27 15 | 26 8 | 25 |
| 39 | 38 | 31 | 23 | 15 | 8 |
| 31 | 32 30 | 33 22 | 34 14 | 35 7 | 36 |
| | | | | | 1 |

2

Subdivisions of Section 36 - - - - - Page 48

Township 9 South, Range 28 East
Gila and Salt River Meridian, Arizona

CHAINS

The boundaries were surveyed in 1884 by L. Wolfley. The subdivisional lines were surveyed in 1885 by J. C. Smith. The west one and one-half miles of the north boundary were resurveyed and the east four and one-half miles were retraced in 1914 by W. B. Kimmel. The east boundary was resurveyed in 1921 by W. H. Thorn. The south and west boundaries were resurveyed in 1960-61 by D. Cazier.

The following field notes are those of a retracement of a portion of the south boundary; the dependent resurvey of a portion of the east and north boundaries and subdivisional lines, designed to restore the corners in their true original locations according to the best available evidence, and a survey of subdivisions in section 36, Township 9 South, Range 28 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated December 13, 1967.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township, as scaled from U.S.G.S. Quadrangle "Javelina Peak", Arizona, scale 1:24000, dated 1966, is: Latitude 32°35'59.4" North, and Longitude 109°25'30.1" West.

The mean magnetic declination was found to be 13° East.

Retracement of a Portion of the South Boundary
Township 9 South, Range 28 East

Retracement of the Survey
Executed by D. Cazier in 1961

Beginning at the ¼ sec. cor. of secs. 1 and 36 on the S. bdy. of the Tp., monumented by an iron post, 2½ in. diam., as described in the official record of the 1961 resurvey.

N. 89°15' W., bet. secs. 1 and 36.

Over gently rolling land.

7.60 Wash, 25 lks. wide, 2 ft. deep, drains SW.

38.20 Wash, 10 lks. wide, 3 ft. deep, drains SW.

40.46 The cor. of secs. 1, 2, 35 and 36, monumented by an iron post, 2½ ins. diam., as described in the official record of the 1961 resurvey.

Land, gently rolling.

Soil, rocky, sandy loam.

Timber, none.

Undergrowth, creosote bush and cacti.

S. 89°19' W., bet. secs. 2 and 35.

Over nearly level land.

Retracement Portion S. Bdy. T. 9 S., R. 28 E.

| CHAINS | | | | | | | | | | | | | | | | | | | | | |
|--|--|--|-----|--|--|--|------------------|--|--|--|------|--|--|--|------|--|--|--|------|--|--|
| 40.27 | <p>The $\frac{1}{2}$ sec. cor. of secs. 2 and 35, monumented by an iron post $2\frac{1}{2}$ ins. diam., as described in the official record of the resurvey in 1961.</p> <p>Land, nearly level. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> | | | | | | | | | | | | | | | | | | | | |
| <p>Dependent Resurvey of a Portion of the East Boundary Township 9 South, Range 28 East</p> | | | | | | | | | | | | | | | | | | | | | |
| <p>Reestablishment of the Survey Executed by W. H. Thorn in 1921</p> | | | | | | | | | | | | | | | | | | | | | |
| 20.07 | <p>From the $\frac{1}{2}$ sec. cor. of sec. 36 only, on the E. bdy. of the Tp., monumented by an iron post, 1 in. diam., as described in the official record of the resurvey in 1921.</p> <p>N. $0^{\circ}05'$ E., along the E. bdy. of sec. 36.</p> <p>Over rolling land.</p> <p>Point for the N $\frac{1}{16}$ sec. cor. of sec. 36 only, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td></td><td>T9S</td><td> </td><td></td></tr> <tr><td></td><td>N $\frac{1}{16}$</td><td> </td><td></td></tr> <tr><td></td><td>S 36</td><td> </td><td></td></tr> <tr><td></td><td>R28E</td><td> </td><td></td></tr> <tr><td></td><td>1968</td><td></td><td></td></tr> </table> </div> <p>Set a wooden post, 5 ft. long, 4 ins. squared, alongside the iron post.</p> | | T9S | | | | N $\frac{1}{16}$ | | | | S 36 | | | | R28E | | | | 1968 | | |
| | T9S | | | | | | | | | | | | | | | | | | | | |
| | N $\frac{1}{16}$ | | | | | | | | | | | | | | | | | | | | |
| | S 36 | | | | | | | | | | | | | | | | | | | | |
| | R28E | | | | | | | | | | | | | | | | | | | | |
| | 1968 | | | | | | | | | | | | | | | | | | | | |
| 21.90 | Wash, 15 lks. wide, 3 ft. deep, drains W. | | | | | | | | | | | | | | | | | | | | |
| 27.70 | Wash, 20 lks. wide, 3 ft. deep, drains SW. | | | | | | | | | | | | | | | | | | | | |
| 36.92 | The cor. of secs. 30 and 31, T. 9 S., R. 29 E., monumented by an iron post, 2 ins. diam., as described in the official record of the resurvey in 1921. | | | | | | | | | | | | | | | | | | | | |
| 37.00 | Jeep Trail, bears N. 50° E. and S. 50° W. | | | | | | | | | | | | | | | | | | | | |
| 40.14 | <p>The cor. of secs. 25 and 36 only, monumented by an iron post, 2 ins. diam., as described in the official record of the resurvey in 1921.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, scattered creosote bush and cacti.</p> | | | | | | | | | | | | | | | | | | | | |
| <p>Dependent Resurvey of a Portion of the North Boundary Township 9 South, Range 28 East</p> | | | | | | | | | | | | | | | | | | | | | |
| <p>Reestablishment of the Survey Executed by L. Wolfley in 1884 and Retraced by W. B. Kimmel in 1914</p> | | | | | | | | | | | | | | | | | | | | | |

Dep. Resurvey, Portion N. Bdy., T. 9 S., R. 28 E.

| CHAINS | | | | | | | |
|------------------|---|------------------|----------|----------|------|------|--|
| | <p>From the $\frac{1}{4}$ sec. cor. of sec. 5 only, T. 9 S., R. 28 E., monumented by an iron post, 1 in. diam., as described in the official record of the resurvey in 1914.</p> | | | | | | |
| | <p>S. $89^{\circ}56'$ E., along the N. bdy. of sec. 5.</p> | | | | | | |
| | <p>Over gently rolling land.</p> | | | | | | |
| 9.80 | <p>Track road, bears N. and S.</p> | | | | | | |
| 37.63 | <p>The closing cor. of secs. 32 and 33, T. 8 S., R. 28 E., monumented by an iron post, 2 ins. diam., as described in the official record of the resurvey in 1914.</p> | | | | | | |
| 39.95 | <p>The cor. of secs. 4 and 5, T. 9 S., R. 28 E., monumented by a granite stone, 16x14x8 ins., firmly set 6 ins. in the ground, mkd. 4 notches on E. and 2 notches on W. faces with mound of stone S.</p> | | | | | | |
| | <p>At the corner point</p> | | | | | | |
| | <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> | | | | | | |
| | <p style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">S5</td> <td style="padding: 2px;">S4</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">T9S R28E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1968</td> </tr> </table> </p> | S5 | S4 | T9S R28E | | 1968 | |
| S5 | S4 | | | | | | |
| T9S R28E | | | | | | | |
| 1968 | | | | | | | |
| | <p>Bury the orig. cor. stone alongside the iron post.</p> | | | | | | |
| | <p>Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor.</p> | | | | | | |
| | <p>Land, gently rolling.</p> | | | | | | |
| | <p>Soil, rocky, sandy loam.</p> | | | | | | |
| | <p>Timber, none.</p> | | | | | | |
| | <p>Undergrowth, creosote bush, cacti and mesquite.</p> | | | | | | |
| | <p>N. $89^{\circ}56'$ E., along the N. bdy. of sec. 4.</p> | | | | | | |
| | <p>Over gently rolling land.</p> | | | | | | |
| 35.30 | <p>Wash, 20 lks. wide, 1 ft. deep, drains NW.</p> | | | | | | |
| 40.10 | <p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, Tps. 8 and 9 S., R. 28 E., monumented by a sandstone, 18x10x4 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with a mound of stone to the N. This cor. now functions for the $\frac{1}{4}$ sec. cor. of sec. 4 only.</p> | | | | | | |
| | <p>At the corner point</p> | | | | | | |
| | <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> | | | | | | |
| | <p style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">$\frac{1}{4}$ S4</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">T9S R28E</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 2px;">1968</td> </tr> </table> </p> | $\frac{1}{4}$ S4 | T9S R28E | | 1968 | | |
| $\frac{1}{4}$ S4 | | | | | | | |
| T9S R28E | | | | | | | |
| 1968 | | | | | | | |
| | <p>Bury the orig. cor. stone alongside the iron post.</p> | | | | | | |
| | <p>Raise a mound of stone N. of the cor.</p> | | | | | | |

Dep. Resurvey, Portion N. Bdy., T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | <p>N. 83°00' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>3.60 Wash, 20 lks. wide, 1 ft. deep, drains SW.</p> <p>35.00 Same wash, 10 lks. wide, 2 ft. deep, drains N. 60° W., curving S. 80° W.</p> <p>35.14 The cor. of secs. 3 and 4, T. 9 S., R. 28 E., monumented by a boulder in place, 8x4x3 ft., mkd. with 3 notches on E. and W. faces, and X on top.</p> <p>At the corner point</p> <p>Set the iron post over the X, in a mound of stone to top, brass cap mkd.</p> <div style="text-align: center; border: 1px solid black; width: fit-content; margin: 10px auto;"> <p>S4 S3</p> <p>T9S R28E</p> <p>1968</p> </div> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| | <p>S. 88°10' E., along the N. bdy. of sec. 3.</p> <p>Over rolling land.</p> <p>2.85 The closing cor. of secs. 33 and 34, T. 8 S., R. 28 E., monumented by an iron post, 2 ins. diam., as described in the official record of the survey in 1914.</p> <p>19.30 Top of Dry Mountain, bears N. 10° E. and S. 10° W.</p> <p>20.00 Fence, bears N. 10° E. and S. 10° W.</p> <p>30.30 Spur, slopes SE.</p> <p>38.30 Draw, drains SE.</p> <p>39.91 The ½ sec. cor. of secs. 3 and 34, Tps. 8 and 9 S., R. 28 E., monumented by a malpais stone, 12x10x8 ins., firmly set 6 ins. in the ground, mkd. ½ on N. face, with mound of stone to the N. This cor. now functions for the ½ sec. cor. of sec. 3 only.</p> <p>At the cor. point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; border: 1px solid black; width: fit-content; margin: 10px auto;"> <p>½ S 3</p> <p>T9S R28E</p> <p>1968</p> </div> |
| | <p>N. 88°18' E., beginning new measurement.</p> <p>Over rolling land.</p> <p>1.70 Spur, slopes SE.</p> |

Dep. Resurvey, Portion N. Bdy., T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| 11.00 | Fence, bears S. 50° E. and N. 50° W. |
| 24.40 | Spur, slopes SE. |
| 30.40 | Draw, drains N. 20° E. |
| 35.20 | Spur, slopes N. 10° E. |
| 40.57 | The cor. of secs. 2 and 3, T. 9 S., R. 28 E., monumented by a malpais boulder lying on top of the ground, 3x3x3 ft., mkd. with 2 notches on E. and 4 notches on W. faces, and X on top, with mound of stone N. |
| | At the corner point |
| | Set the iron post 4 ins. in the ground, in a mound of stone to top, brass cap mkd. |
| | $\begin{array}{c} \hline S 3 S 2 \\ T9S R28E \\ 1968 \end{array}$ |
| | Deposit the orig. cor. stone in the mound and alongside the iron post. |
| | Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and cacti. |
| | N. 89°38' E., along the N. bdy. of sec. 2. |
| 2.66 | The closing cor. of secs. 34 and 35, T. 8 S., R. 28 E., monumented by an iron post, 2 ins. diam., as described in the official record of the survey in 1914. |
| 16.60 | Wash, 6 lks. wide, 2 ft. deep, drains N. 5° E. |
| 27.90 | Wash, 150 lks. wide, 3 ft. deep, drains N. 10° E. |
| 40.02 | The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, Tps. 8 and 9 S., R. 28 E., monumented by a malpais stone, 18x18x4 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N. This cor. now functions for the $\frac{1}{4}$ sec. cor. of sec. 2 only. |
| | At the corner point |
| | Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd. |
| | $\begin{array}{c} \hline \frac{1}{4} S 2 \\ T9S R28E \\ 1968 \end{array}$ |
| | Bury the orig. cor. stone alongside the iron post. |
| | N. 89°29' E., beginning new measurement. |
| | Over rolling land. |
| 15.40 | Jeep trail, bears SE. and NW. |
| 23.30 | Gully, 10 lks. wide, with 15 ft. walls. |

Dep. Resurvey, Portion N. Bdy., T. 9 S., R. 28 E.

| CHAINS | | |
|---|---|--|
| 40.78 | <p>The cor. of secs. 1 and 2, T. 9 S., R. 28 E., monumented by a malpais stone, 14x10x8 ins., firmly set 6 ins. in the ground, mkd. with 1 notch on E. and 5 notches on W. faces, with a mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 50px; margin: 0 auto;"/> <p>S 2 S 1 T9S R28E 1968</p> </div> <p>Bury the orig. cor. stone in the mound of stone and alongside the iron post.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> | |
| <hr/> | | |
| <p>N. 87°45' E., along the N. bdy. of sec. 1.</p> | | |
| 1.94 | <p>The closing cor. of secs. 35 and 36, T. 8 S., R. 28 E., monumented by an iron post, 2 ins. diam., as described in the official record of the survey in 1914.</p> | |
| 21.00 | <p>Spur, slopes N.</p> | |
| 36.90 | <p>Wash, 30 lks. wide, with 6 ft. banks, drains N.</p> | |
| 41.37 | <p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, Tps. 8 and 9 S., R. 28 E., monumented by a malpais stone, 22x14x10 ins., firmly set 18 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N. This cor. now functions for the $\frac{1}{4}$ sec. cor. of sec. 1 only.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <hr style="width: 50px; margin: 0 auto;"/> <p>$\frac{1}{4}$ S 1 T9S R28E 1968</p> </div> <p>Bury the orig. cor. stone in the mound of stone.</p> | |
| <hr/> | | |
| <p>N. 88°30' E., beginning new measurement.</p> | | |
| 26.00 | <p>Spur, slopes N.</p> | |
| 40.00 | <p>Wash, 20 lks. wide, 2 ft. deep, drains N. 10° E.</p> | |
| 40.53 | <p>The cor. of Tps. 8 and 9 S., R. 28 E. only, monumented by an iron post, 2 ins. diam., as described in the official record of the resurvey in 1921.</p> | |

Dep. Resurvey, Portion N. Bdy., T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>Dependent Resurvey, Portion, Subdivisional Lines, T. 9 S., R. 28 E.</p> |
| | <p>Reestablishment of the Survey Executed by John C. Smith in 1885</p> |
| | <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp. N. 0°08' E., bet. secs. 35 and 36. Over gently rolling land.</p> |
| 22.60 | Wash, 90 lks. wide, 4 ft. deep, drains SW. |
| 28.40 | Jeep Trail, bears NE. and SW. |
| 41.24 | Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd. |
| | <p>T9S R28E $\frac{1}{4}$ S 35 S 36 1968</p> |
| | Set a wooden post, 5 ft. long, 4 ins. squared, alongside the iron post. |
| 46.50 | Draw, drains W. for 150 lks.; thence SW. |
| 54.10 | Wash, 10 lks. wide, 2 ft. deep, drains W. |
| 60.70 | Wash, 15 lks. wide, 2 ft. deep, drains W. |
| 80.30 | Wash, 35 lks. wide, 2 ft. deep, drains S. 70° W. |
| 82.48 | The cor. of secs. 25, 26, 35 and 36, monumented by a malpais stone, 12x10x8 ins., firmly set in a mound of stone, mkd. 1 notch on E. and S. faces. At the corner point Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd. |
| | <p>T9S R28E S 26 S 25 S 35 S 36 1968</p> |
| | Bury the orig. cor. stone alongside the iron post. |
| | Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor. |

Dependent Resurvey, Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>From the cor. of secs. 25 and 36 only, on the E. bdy. of the Tp. N. 89°07' W., bet. secs. 25 and 36. Over gently rolling land.</p> |
| 3.50 | Wash, 70 lks. wide, 3 ft. deep, drains SW. |
| 18.82 | <p>Point for the E 1/16 sec. cor. of secs. 25 and 36, at proportionate dist. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E E 1/16 $\frac{S\ 25}{S\ 36}$ 1968</p> <p>Raise a mound of stone N. of the iron post.</p> |
| 37.64 | <p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented by a malpais stone, 18x16x5 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone to N. At the corner point Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$ 1968</p> <p>Bury the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87°25' W., beginning new measurement. Over gently rolling land.</p> |
| 20.40 | Draw, drains N. 70° W. |
| 41.00 | Wash, 20 lks. wide, 2 ft. deep, drains S. |
| 41.19 | <p>The cor. of secs. 25, 26, 35 and 36. Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>N. 1°28' W., bet. secs. 25 and 26. Over gently rolling land.</p> |
| 6.00 | Small draw, drains W. |
| 27.30 | Wash, 20 lks. wide, 2 ft. deep, drains W. |

Dependent Resurvey, Portion, Subdivisional Lines, T. 9 S., R. 28 E.

CHAINS

39.14 The 1/4 sec. cor. of secs. 25 and 26, monumented by a malpais stone, 16x12x6 ins., firmly set 6 ins. in the ground, mkd. 1/4 on W. face, with mound of stone to W.

At the corner point

Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.

T9S R28E
1/4
S 26 | S 25
1968

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

N. 0°48' W., beginning new measurement.

Over gently rolling land.

3.10 Draw, drains SW.

32.80 Wash, 40 lks. wide, 3 ft. deep, drains W.

40.54 The cor. of secs. 23, 24, 25 and 26, monumented by a malpais stone, 16x14x12 ins., firmly set 6 ins. in the ground, mkd. 1 notch on E. and 2 notches on S. faces, with mound of stone to W.

At the corner point

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T9S R28E
S 23 | S 24
S 26 | S 25
1968

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

Land, gently rolling.

Soil, rocky, sandy loam.

Timber, none.

Undergrowth, creosote bush, cacti and mesquite.

From the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented by an iron post, 2 in. diam., as described in the official record of the resurvey in 1921.

N. 88°28' W., bet. secs. 24 and 25.

Over rolling land.

39.89 Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.

Dependent Resurvey, Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | | |
|--------|--|--|
| | <p style="text-align: center;">T9S R28E $\frac{1}{4}$ $\frac{S\ 24}{S\ 25}$ 1968</p> | |
| 60.70 | Wash, 30 lks. wide, 4 ft. deep, drains SW. | |
| 79.78 | <p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | |
| | <p>N. 0°10' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p> | |
| 29.60 | Draw, drains W. | |
| 40.23 | <p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented by a malpais stone, 24x6x6 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone to W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> | |
| | <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 23 S 24 1968</p> | |
| | Bury the orig. cor. stone alongside the iron post. | |
| | Raise a mound of stone W. of the cor. | |
| | <p style="text-align: center;">_____</p> <p>N. 4°20' E., beginning new measurement.</p> <p>Over rolling land.</p> | |
| 14.40 | Spur, slopes W. | |
| 27.60 | Wash, 10 lks. wide, 2 ft. deep, drains W. | |
| 38.76 | <p>The cor. of secs. 13, 14, 23 and 24, monumented by a malpais stone, 15x12x8 ins., lying loose on ground, mkd. 1 notch and 3 notches on adjacent faces, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> | |
| | <p style="text-align: center;">T9S R28E $\frac{S\ 14}{S\ 23}$ $\frac{S\ 13}{S\ 24}$ 1968</p> | |
| | Bury the orig. cor. stone alongside the iron post. | |
| | Raise a mound of stone W. of the cor. | |
| | <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | N. 0°31' E., bet. secs. 13 and 14. Over gently rolling land. |
| 8.00 | Jeep Trail, bears E. and W. |
| 22.00 | Wash, 30 lks. wide, 3 ft. deep, drains westerly. |
| 33.50 | Wash, 5 lks. wide, 2 ft. deep, drains westerly. |
| 40.47 | The $\frac{1}{4}$ sec. cor. of secs. 13 and 14, monumented by a mal-pais stone, 16x12x8 ins., firmly set 6 ins. in the ground mkd. $\frac{1}{4}$ on W. face, with a mound of stone to W. |
| | At the corner point |
| | Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. |
| | T9S R28E $\frac{1}{4}$ S 14 S 13 1968 |
| | Bury the orig. cor. stone alongside the iron post. |
| | Raise a mound of stone W. of the cor. |
| | ————— |
| | N. 0°53' E., beginning new measurement. Over gently rolling land. |
| 5.60 | Wash, 20 lks. wide, 2 ft. deep, drains W. |
| 8.30 | Jeep Trail, bears SE. and NW.; thence irregularly N. |
| 17.50 | Wash, 15 lks. wide, 2 ft. deep, drains W. |
| 24.30 | Wash, 20 lks. wide, 2 ft. deep, drains SW. |
| 29.90 | Jeep Trail, bears N. 35° E. and S. 35° W. |
| 40.23 | The cor. of secs. 11, 12, 13 and 14, monumented by a mal-pais stone, 12x6x6 ins., firmly set 6 ins. in the ground, mkd. 1 notch on E. and 4 notches on S. faces, with mound of stone W. |
| | At the corner point |
| | Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd. |
| | T9S R28E S 11 S 12 S 14 S 13 1968 |
| | Bury the orig. cor. stone alongside the iron post. |
| | Land, gently rolling. Soil, rocky sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite. |
| | ————— |
| | N. 0°36' E., bet. secs. 11 and 12. Over rolling land. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| 3.60 | Wash, 15 lks. wide, 1 ft. deep, drains SW. |
| 28.00 | Spur, slopes E. |
| 36.70 | Jeep Trail, bears E. and W. |
| 40.31 | The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by a malpais stone, 14x12x8 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone W. |
| | At the corner point |
| | Set the iron post 20 ins. in the ground, brass cap mkd. |
| | <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 11 S 12 1968</p> |
| | Bury the orig. cor. stone alongside the iron post. |
| | Raise a mound of stone W. of the cor. |
| | <hr style="width: 20%; margin: auto;"/> <p>N. 1°38' E., beginning new measurement.</p> |
| | Over rolling land. |
| 32.50 | Fence, bears S. 85° E. and N. 85° W. |
| 38.30 | Draw, drains W. |
| 40.56 | The cor. of secs. 1, 2, 11 and 12, monumented by a malpais stone, 12x12x12 ins., firmly set 6 ins. in the ground, mkd. 1 notch on E. and 5 notches on S. faces, with a mound of stone to W. |
| | At the corner point |
| | Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. |
| | <p style="text-align: center;">T9S R28E S 2 S 1 S 11 S 12 1968</p> |
| | Bury the orig. cor. stone in the mound of stone. |
| | Land, rolling. |
| | Soil, rocky, sandy loam. |
| | Timber, none. |
| | Undergrowth, creosote bush, cacti and mesquite. |
| | From the cor. of secs. 1 and 12 only, on the E. bdy. of the Tp., monumented by an iron post, 2 ins. diam., as described in the official record of the resurvey in 1921. |
| | N. 89°51' W., bet. secs. 1 and 12. |
| | Over rolling land. |
| 5.00 | Spur, slopes irregularly N. |
| 25.90 | Wash, 10 lks. wide, 5 ft. deep, drains N. 10° W. |
| 36.40 | Wash, 10 lks. wide, 3 ft. deep, drains N. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| 36.67 | <p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented by a malpais stone, 14x12x10 ins., firmly set 6 ins. in the ground, dimly mkd. $\frac{1}{4}$ on N. face, with scattered mound of stone to N.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ $\frac{S 1}{S 12}$ 1968</p> <p>Bury the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°29' W., beginning new measurement.</p> <p>Over rolling land.</p> |
| 23.40 | <p>Spur, slopes N. 10° E.</p> |
| 36.39 | <p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>N. 0°32' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p> |
| 1.60 | <p>Wash, 10 lks. wide, 7 ft. deep, drains W.</p> |
| 40.46 | <p>The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented by a malpais stone, 16x8x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{4}$ on N. face.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 2 S 1 1968</p> <p>Bury the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 14°36' W., beginning new measurement.</p> <p>Over rolling land.</p> |
| 24.80 | <p>Wash, 10 lks. wide, 5 ft. deep drains N. 75° W.</p> |
| 39.73 | <p>The cor. of secs. 1 and 2 only, on the N. bdy. of the Tp.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., as described in the official record of the resurvey in 1961. |
|--------|---|
| | <p>N. 1°53' E., bet. secs. 34 and 35.</p> <p>Over gently rolling land.</p> |
| 16.20 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 23.70 | Jeep Trail, bears S. 80° E. and N. 80° W. |
| 36.80 | Wash, 20 lks. wide, 2 ft. deep, drains W. |
| 39.90 | <p>The ¼ sec. cor. of secs. 34 and 35, monumented by a malpais stone, 14x10x6 ins., firmly set 6 ins. in the ground, mkd. ¼ on W. face, with mound of stone to W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E ^¼ S 34 S 35 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>Over gently rolling land.</p> |
| 5.20 | Wash, 15 lks. wide, 2 ft. deep, drains W. from NE. |
| 34.30 | Wash, 110 lks. wide, 3 ft. deep, drains S. 80° W. |
| 40.25 | <p>The cor. of secs. 26, 27, 34 and 35, monumented by a malpais stone, 14x8x5 ins., firmly set 6 ins. in the ground, mkd. 2 notches on E. and 1 notch on S. faces, with mound of stone to N.</p> <p>At the corner point:</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E S 27 S 26 S 34 S 35 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a wooden post 4 ft. long, 4 ins. squared, alongside the iron post.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | From the cor. of secs. 25, 26, 35 and 36. |
| | S. 89°09' W., bet. secs. 26 and 35. |
| | Over gently rolling land. |
| 25.10 | Wash, 90 lks. wide, 3 ft. deep, drains SW. |
| 38.44 | The ¼ sec. cor. of secs. 26 and 35, monumented by a mal- |
| | pais stone, 18x14x12 ins., firmly set 6 ins. in the |
| | ground, mkd. ¼ on N. face, with mound of stone to N. |
| | At the corner point |
| | Set the iron post 16 ins. in the ground, mound of stone |
| | to top, brass cap mkd. |
| | T9S R28E |
| | ¼ $\frac{S}{S}$ $\frac{26}{35}$ |
| | 1968 |
| | Bury the orig. cor. stone alongside the iron post. |
| | Set a wooden post, 5 ft. long, 4 ins. squared, alongside |
| | the iron post. |
| | S. 89°54' W., beginning new measurement. |
| | Over gently rolling land. |
| 6.50 | Wash, 80 lks. wide, 3 ft. deep, drains SW. 50 lks., thence |
| | curves to W. |
| 18.70 | Same wash, drains S. from the E. |
| 25.90 | Small draw, drains SW. |
| 33.10 | Small draw, drains S. |
| 40.37 | The cor. of secs. 26, 27, 34 and 35. |
| | Land, gently rolling. |
| | Soil, rocky, sandy loam. |
| | Timber, none. |
| | Undergrowth, creosote bush, cacti and mesquite. |
| | N. 0°47' E., bet. secs. 26 and 27. |
| | Over gently rolling land. |
| 7.50 | Wash, 30 lks. wide, 3 ft. deep, drains W. |
| 31.20 | Wash, 20 lks. wide, 4 ft. deep, drains W. |
| 33.30 | Wash, 30 lks. wide, 4 ft. deep, drains NW. |
| 40.00 | The ¼ sec. cor. of secs. 26 and 27, monumented by a mal- |
| | pais stone, 12x10x10 ins., firmly set 6 ins. in the |
| | ground, mkd. ¼ on W. face, with mound of stone to W. |
| | At the corner point |
| | Set the iron post 20 ins. in the ground, brass cap mkd. |
| | T9S R28E |
| | S 27 S 26 |
| | 1968 |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | | | | | | |
|--------------------|--|--------------------|------|------|------|--|
| | <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr/> <p>N. 6°07' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>24.10 Wash, 20 lks. wide, 2 ft. deep, drains W.</p> <p>39.18 The cor. of secs. 22, 23, 26 and 27, monumented by a mal-pais stone, 16x12x12 ins., firmly set 8 ins. in the ground, mkd. 2 notches on E. and S. faces, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <table border="1"> <tr> <td>S 22</td> <td>S 23</td> </tr> <tr> <td>S 27</td> <td>S 26</td> </tr> </table> <p>1968</p> </div> <p>Bury the orig. cor. stone in the collar of stone.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | S 22 | S 23 | S 27 | S 26 | |
| S 22 | S 23 | | | | | |
| S 27 | S 26 | | | | | |
| | <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 87°57' W., bet. secs. 23 and 26.</p> <p>Over gently rolling land.</p> <p>20.50 Draw, drains N. 80° W. from N. 80° E.</p> <p>40.07 The $\frac{1}{4}$ sec. cor. of secs. 23 and 26, monumented by a mal-pais stone, 16x12x6 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <table border="1"> <tr> <td>$\frac{1}{4}$ S 23</td> <td></td> </tr> <tr> <td>S 26</td> <td></td> </tr> </table> <p>1968</p> </div> <p>Bury the orig. cor. stone in the mound of stone.</p> <p>Raise a mound of stone N. of the cor.</p> <hr/> <p>N. 89°52' W., beginning new measurement.</p> <p>Over rolling land.</p> | $\frac{1}{4}$ S 23 | | S 26 | | |
| $\frac{1}{4}$ S 23 | | | | | | |
| S 26 | | | | | | |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| 40.78 | <p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, gently rolling to rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>N. 1°25' E., bet. secs. 22 and 23.</p> <p>Over rolling land.</p> |
| 8.40 | <p>Wash, 10 lks. wide, 2 ft. deep, drains W.</p> |
| 20.60 | <p>Wash, 10 lks. wide, 2 ft. deep, drains W.</p> |
| 40.23 | <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> |
| | <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 22 S 23 1968</p> |
| 41.30 | <p>Wash, 10 lks. wide, 2 ft. deep, drains SW.</p> |
| 53.90 | <p>Wash, 40 lks. wide, 3 ft. deep, drains W.</p> |
| 60.10 | <p>Cove Well with Windmill, bears West, 10 lks. dist.</p> |
| 65.60 | <p>Cove Draw, 35 lks. wide, 3 ft. deep, drains S. 50° W.</p> |
| 80.46 | <p>The cor. of secs. 14, 15, 22 and 23, monumented by a malpais stone, 12x12x6 ins., firmly set 6 ins. in the ground, mkd. 2 notches on E. and 3 notches on S. faces, with mound of stone to W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E S 15 S 14 S 22 S 23 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°29' W., bet. secs. 14 and 23.</p> <p>Over rolling land.</p> |
| 41.38 | <p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 23, monumented by a malpais stone, 14x10x8 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone S.</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | At the corner point |
| | Set the iron post 22 ins. in the ground, brass cap mkd. |
| | $\begin{array}{r} T9S R28E \\ S 14 \\ \frac{1}{4} \overline{S 23} \\ 1968 \end{array}$ |
| | Bury the orig. cor. stone alongside the iron post. |
| | Raise a mound of stone N. of the cor. |
| | <hr/> S. 89°48' W., beginning new measurement. |
| | Over rolling land. |
| 2.60 | Cove Draw, 30 lks. wide, 2 ft. deep, drains S. 80° W. |
| 40.26 | The cor. of secs. 14, 15, 22 and 23. |
| | Land, rolling. |
| | Soil, rocky, sandy loam. |
| | Timber, none. |
| | Undergrowth, creosote bush, cacti and mesquite. |
| | <hr/> N. 2°36' E., bet. secs. 14 and 15. |
| | Over rolling land. |
| 7.80 | Jeep Trail, bears E. and W. |
| 35.50 | Wash, 100 lks. wide, 3 ft. deep, drains N. 85° W. |
| 40.76 | The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented by a malpais stone, 14x8x5 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone W. |
| | At the corner point |
| | Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd. |
| | $\begin{array}{r} T9S R28E \\ \frac{1}{4} \\ S 15 S 14 \\ 1968 \end{array}$ |
| | Bury the orig. cor. stone alongside the iron post. |
| | <hr/> N. 0°02' E., beginning new measurement. |
| | Over rolling land. |
| 21.70 | Wash, 30 lks. wide, 2 ft. deep, drains N. 80° W. |
| 37.30 | Wash, 15 lks. wide, 5 ft. deep, drains irregularly W. |
| 39.98 | The cor. of secs. 10, 11, 14 and 15, monumented by a malpais stone, 18x12x8 ins., firmly set 8 ins. in the ground, mkd. 2 notches on E. and 4 notches on S. faces, with mound of stone to W. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | | | | | | | | | |
|----------|---|----------|--|--------|------|------|------|------|--|
| | <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T9S R28E</td></tr> <tr><td>S 10</td><td>S 11</td></tr> <tr><td>S 15</td><td>S 14</td></tr> <tr><td colspan="2">1968</td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | T9S R28E | | S 10 | S 11 | S 15 | S 14 | 1968 | |
| T9S R28E | | | | | | | | | |
| S 10 | S 11 | | | | | | | | |
| S 15 | S 14 | | | | | | | | |
| 1968 | | | | | | | | | |
| | <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°41' W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p> <p>2.30 Wash, 10 lks. wide, 2 ft. deep, drains S.</p> <p>6.50 Wash, 5 lks. wide, 2 ft. deep, drains S. 10° E.</p> <p>17.20 Wash, 5 lks. wide, 2 ft. deep, drains SE.</p> <p>32.20 Saddle in ridge, bears N. and S.</p> <p>40.62 The ¼ sec. cor. of secs. 11 and 14, monumented by a malpais stone, 18x10x3 ins., firmly set 8 ins. in the ground, mkd. ¼ on N. face, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td colspan="2">T9S R28E</td></tr> <tr><td>¼ S 11</td><td></td></tr> <tr><td>S 14</td><td></td></tr> <tr><td colspan="2">1968</td></tr> </table> </div> <p>Bury the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°51' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>28.60 Thence along draw, draining irregularly W.</p> <p>39.60 Thence along wash to the S., 15 lks. wide, 5 ft. deep, draining irregularly W.</p> <p>40.06 The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | T9S R28E | | ¼ S 11 | | S 14 | | 1968 | |
| T9S R28E | | | | | | | | | |
| ¼ S 11 | | | | | | | | | |
| S 14 | | | | | | | | | |
| 1968 | | | | | | | | | |
| | <p>N. 2°13' E., bet. secs. 10 and 11.</p> | | | | | | | | |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | Over rolling land. |
| 6.20 | Draw, drains SW. |
| 41.06 | <p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented by a mal-pais stone, 12x10x8 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 10 S 11 1968</p> <p>Bury the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°43' E., beginning new measurement.</p> <p>Over rolling land.</p> |
| 10.70 | Draw, drains S. 80° W. from the E. |
| 39.73 | <p>The cor. of secs. 2, 3, 10 and 11, monumented by a mal-pais stone, 18x14x6 ins., firmly set 6 ins. in the ground, mkd. 2 notches on E. and 5 notches on S. faces, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 3 S 2 S 10 S 11 1968</p> <p>Bury the orig. cor. stone in the mound of stone.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°16' W., bet. secs. 2 and 11.</p> |
| 8.70 | Ravine, drains NW. |
| 26.70 | Wash, 30 lks. wide, 5 ft. deep, drains N. |
| 27.00 | Jeep Trail, bears N. and S. |
| 30.60 | Fence, bears S. 25° E. and N. 25° W. |
| 30.70 | Wash, 5 lks. wide, 2 ft. deep, drains NE. |
| 40.32 | <p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented by a mal-pais stone, 14x10x8 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N.</p> <p>At the corner point</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{2}{11}$ 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°32' W., beginning new measurement.</p> <p>Over rolling land.</p> |
| 6.60 | Spur, slopes N. |
| 21.90 | Wash, 5 lks. wide, 5 ft. deep, drains N. |
| 37.00 | Wash, 15 lks. wide, 2 ft. deep, drains N. 10° E. |
| 39.93 | The cor. of secs. 2, 3, 10 and 11. |
| | <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>N. 0°10' E., bet. secs. 2 and 3.</p> <p>Over rolling land.</p> |
| 37.80 | Jeep Trail, bears NE. and SW. |
| 39.60 | Wash, 10 lks. wide, 1 ft. deep, drains NE. |
| 39.88 | The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented by a malpais stone, 10x10x8 ins., firmly set in a mound of stone, dimly mkd. $\frac{1}{4}$ on W. face. |
| | <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{3}{2}$ 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 15°18' W., beginning new measurement.</p> <p>Over rolling land.</p> |
| 13.10 | Wash, 10 lks. wide, 2 ft. deep, drains S. 85° W. |
| 29.50 | Fence, bears S. 50° E. and N. 50° W. |
| 39.61 | The cor. of secs. 2 and 3 only, on the N. bdy of the Tp. |
| | <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., as described in the official record of the resurvey in 1961.</p> <p>N. 0°17' W., bet. secs. 33 and 34.</p> <p>Over rolling land.</p> |
| 12.10 | Wash, 10 lks. wide, 2 ft. deep, drains SW. |
| 13.20 | Jeep Trail, bears E. and W. |
| 22.40 | Wash, 15 lks. wide, 1 ft. deep, drains SW. |
| 31.60 | Wash, 5 lks. wide, 1 ft. deep, drains NW. |
| 34.20 | Wash, 5 lks. wide, 1 ft. deep, drains SW. |
| 38.91 | Wash, 15 lks. wide, 1 ft. deep, drains W. |
| 39.76 | <p>The ¼ sec. cor. of secs. 33 and 34, monumented by a malpais stone, 14x10x6 ins., firmly set 6 ins. in the ground, mkd. ¼ on W. face, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <p>¼</p> <p>S 33 S 34</p> <p>1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°09' E., beginning new measurement.</p> <p>Over gently rolling land.</p> |
| 11.50 | Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W. |
| 25.90 | Wash, 20 lks. wide, 1 ft. deep, drains W. |
| 37.10 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 40.10 | <p>The cor. of secs. 27, 28, 33 and 34, monumented by a malpais stone, 8x8x5 ins., firmly set 4 ins. in the ground, mkd. 3 notches on E. and 1 notch on S. faces, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <p>S 28 S 27</p> <p>S 33 S 34</p> <p>1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling to gently rolling.</p> <p>Soil, rocky, sandy loam.</p> <p>Timber, none.</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | Undergrowth, creosote bush, cacti and mesquite. |
| | From the cor. of secs. 26, 27, 34 and 35. S. 89°59' W., bet. secs. 27 and 34. Over gently rolling land. |
| 9.10 | Wash, 10 lks. wide, 2 ft. deep, drains N. |
| 15.40 | Wash, 20 lks. wide, 2 ft. deep, drains NW. |
| 19.50 | Wash, 20 lks. wide, 2 ft. deep, drains SW. |
| 31.80 | Wash, 30 lks. wide, 4 ft. deep, drains S. |
| 40.30 | The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented by a mal-pais stone, 13x10x5 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd. T9S R28E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{27}{34}$ 1968 Bury the orig. cor. stone alongside the iron post. Raise a mound of stone N. of the cor. <hr style="width: 20%; margin: auto;"/> S. 89°54' W., beginning new measurement. Over gently rolling land. |
| 3.60 | Wash, 20 lks. wide, 2 ft. deep, drains NW. 1.00 ch., thence curves to W. |
| 13.50 | Wash, 20 lks. wide, 4 ft. deep, drains NW. |
| 27.40 | Wash, 100 lks. wide, 3 ft. deep, drains NW. |
| 40.70 | The cor. of secs. 27, 28, 33 and 34. Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite. |
| | N. 0°56' W., bet. secs. 27 and 28. Over rolling land. |
| 4.30 | Wash, 50 lks. wide, 2 ft. deep, drains SW. |
| 10.80 | Wash, 60 lks. wide, 4 ft. deep, drains W. |
| 22.90 | Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | | | | | | | |
|---------------|---|------|------|---------------|------|------|--|
| 40.10 | <p>The $\frac{1}{4}$ sec. cor. of secs. 27 and 28, monumented by a malpais stone, 8x4x4 ins., loosely set in a mound of stone, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">$\frac{1}{4}$</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1968</td> </tr> </table> </div> <p>Bury the orig. cor. stone alongsdie the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°35' E., beginning new measurement.</p> <p>Over rolling land.</p> | S 28 | S 27 | $\frac{1}{4}$ | | 1968 | |
| S 28 | S 27 | | | | | | |
| $\frac{1}{4}$ | | | | | | | |
| 1968 | | | | | | | |
| 0.70 | Wash, 5 lks. wide, 2 ft. deep, drains N. 75° W. | | | | | | |
| 5.70 | Wash, 40 lks. wide, 2 ft. deep, drains NW. | | | | | | |
| 16.10 | Wash, 100 lks. wide, 5 ft. deep, drains W. | | | | | | |
| 35.90 | Wash, 15 lks. wide, 1 ft. deep, drains W. | | | | | | |
| 39.77 | <p>The cor. of secs. 21, 22, 27 and 28, monumented by a malpais stone, 14x9x5 ins., firmly set 6 ins. in the ground, mkd. 3 notches on E. and 2 notches on S. faces, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 21</td> <td style="padding: 0 5px;">S 22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td colspan="2" style="text-align: center; padding: 0 5px;">1968</td> </tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | S 21 | S 22 | S 28 | S 27 | 1968 | |
| S 21 | S 22 | | | | | | |
| S 28 | S 27 | | | | | | |
| 1968 | | | | | | | |
| | <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°22' W., bet. secs. 22 and 27.</p> <p>Over rolling land.</p> | | | | | | |

Dependent Resurvey
 Portion, Subdivisional Lines, T., 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| 38.76 | Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. <div style="text-align: center;"> T9S R28E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{22}{27}$ 1968 </div> |
| 68.10 | Wash, 30 lks. wide, 1 ft. deep, drains NW. |
| 77.52 | The cor. of secs. 21, 22, 27 and 28. |
| | Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite. |
| | N. 0°13' E., bet. secs. 21 and 22. |
| | Over rolling land. |
| 6.80 | Cove Draw, 100 lks. wide, 3 ft. deep, drains S. 75° W. |
| 10.00 | Track road, bears W. and bears E. 1.00 ch., thence curves to NE. |
| 40.25 | The $\frac{1}{4}$ sec. cor. of secs. 21 and 22, monumented by a malpais stone, 14x6x6 ins., lying loose on ground, mkd. $\frac{1}{4}$ on a face. At the corner point Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T9S R28E $\frac{1}{4}$ S 21 S 22 1968 </div> |
| | Bury the orig. cor. stone alongside the iron post. |
| | Raise a mound of stone W. of the cor. |
| | Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor. |
| | _____ |
| | N. 0°25' E., beginning new measurement. |
| | Over rolling land. |
| 4.90 | Wash, 25 lks. wide, 2 ft. deep, drains S. 80° W. |
| 40.17 | The cor. of secs. 15, 16, 21 and 22, monumented by a malpais stone, 8x6x5 ins., firmly set 4 ins. in the ground, mkd. 3 notches on E. and S. faces, with mound of stone W. At the corner point Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd. |

Dependent Resurvey
 Portion, Subdivisional Lines, T., 9 S., R. 28 E.

| CHAINS | | |
|--------|--|--|
| | <p style="text-align: center;">T9S R28E $\frac{S}{S} \frac{16}{21} \frac{S}{S} \frac{15}{22}$ 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | |
| | <p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 89°19' W., bet. secs. 15 and 22.</p> <p>Over rolling land.</p> | |
| 25.20 | Jeep Trail, bears N. 80° E. and S. 80° W. | |
| 40.28 | <p>The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented by a malpais stone, 15x10x3 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4} \frac{S}{S} \frac{15}{22}$ 1968</p> <p>The cor. is located 80 lks. N. of a small wash draining W.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°25' W., beginning new measurement.</p> <p>Over rolling land.</p> | |
| 9.40 | Wash, 10 lks. wide, 1 ft. deep, drains irregularly NW. | |
| 38.84 | <p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, rocky, loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | |
| | <p>N. 0°02' W., bet. secs. 15 and 16.</p> <p>Over rolling land.</p> | |
| 11.60 | Wash, 15 lks. wide, 4 ft. deep, drains W. | |
| 35.80 | Wash, 15 lks. wide, 3 ft. deep, drains W. | |
| 40.12 | The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented by a malpais stone, 9x5x4 ins., lying loose on ground, mkd. $\frac{1}{4}$ on a face, with mound of stone W. | |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 16 S 15 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' W., beginning new measurement.</p> <p>Over rolling land.</p> |
| 1.30 | Ravine, drains S. 70° W. |
| 17.00 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 26.10 | Wash, 30 lks. wide, 2 ft. deep, drains N. 80° W. |
| 32.00 | Wash, 15 lks. wide, 2 ft. deep, drains W. |
| 40.02 | <p>The cor. of secs. 9, 10, 15 and 16, monumented by a mal-pais stone, 12x8x6 ins., firmly set 6 ins. in the ground, mkd. 3 notches on E. and 4 notches on S. faces, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E S 9 S 10 S 16 S 15 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°28' W., bet. secs. 10 and 15.</p> <p>Over rolling land.</p> |
| 11.10 | Draw, drains S. 80° W. |
| 16.80 | Wash, 20 lks. wide, 3 ft. deep, drains S. |
| 19.40 | Spur, slopes SW. |
| 24.30 | Spur, slopes SW. |
| 31.40 | Wash, 20 lks. wide, 2 ft. deep, drains N. 50° W. |
| 40.45 | <p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented by a mal-pais stone, 15x12x6 ins., firmly set 6 ins. in the</p> |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ $\frac{S}{10}$ $\frac{S}{15}$ 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°50' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>11.90 Wash, 20 lks. wide, 2 ft. deep, drains N. 10° W.</p> <p>40.51 The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, rolling to gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>N. 0°11' E., bet. secs. 9 and 10.</p> <p>Over rolling land.</p> <p>11.10 Wash, 100 lks. wide, 12 ft. deep, drains W.</p> <p>23.40 Spur, slopes W.</p> <p>34.80 Wash, 150 lks. wide, 2 ft. deep, drains W.</p> <p>39.78 The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented by a malpais stone, 18x14x5 ins., lying loose on ground, mkd. $\frac{1}{4}$ on a face, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 9 S 10 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°25' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>36.80 Wash, 30 lks. wide, 2 ft. deep, drains W. from N. 10° E.</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | | | | | | | | | |
|-------------------|--|----------|--|-------------------|-----|------|------|------|--|
| 40.42 | <p>The cor. of secs. 3, 4, 9 and 10, monumented by a malpais stone, 12x7x6 ins., firmly set 4 ins. in the ground, mkd. 3 notches on E. and 5 notches on S. faces, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T9S R28E</td></tr> <tr><td>S 4</td><td>S 3</td></tr> <tr><td>S 9</td><td>S 10</td></tr> <tr><td colspan="2">1968</td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | T9S R28E | | S 4 | S 3 | S 9 | S 10 | 1968 | |
| T9S R28E | | | | | | | | | |
| S 4 | S 3 | | | | | | | | |
| S 9 | S 10 | | | | | | | | |
| 1968 | | | | | | | | | |
| | <p>From the cor. of sec. 2, 3, 10 and 11.</p> <p>N. 89°42' W., bet. secs. 3 and 10.</p> <p>Over rolling land.</p> | | | | | | | | |
| 31.30 | <p>Descend vertical rock wall, 70 ft. high, bears N. and S.</p> | | | | | | | | |
| 40.80 | <p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented by a malpais stone 16x16x6 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T9S R28E</td></tr> <tr><td>$\frac{1}{4}$ S 3</td><td></td></tr> <tr><td>S 10</td><td></td></tr> <tr><td colspan="2">1968</td></tr> </table> </div> <p>Bury the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°16' W., beginning new measurement.</p> <p>Over rolling land.</p> | T9S R28E | | $\frac{1}{4}$ S 3 | | S 10 | | 1968 | |
| T9S R28E | | | | | | | | | |
| $\frac{1}{4}$ S 3 | | | | | | | | | |
| S 10 | | | | | | | | | |
| 1968 | | | | | | | | | |
| 9.70 | <p>Wash, 20 lks. wide, 3 ft. deep, drains SW.</p> | | | | | | | | |
| 15.10 | <p>Wash, 10 lks. wide, 3 ft. deep, drains SW.</p> | | | | | | | | |
| 22.00 | <p>Wash, 10 lks. wide, 2 ft. deep, drains S.</p> | | | | | | | | |
| 39.50 | <p>Wash, 10 lks. wide, 3 ft. deep, drains SW.</p> | | | | | | | | |
| 42.40 | <p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> | | | | | | | | |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | N. 0°03' E., bet. secs. 3 and 4. Over rolling land. |
| 15.90 | Top of round knoll. |
| 38.36 | Point for the ¼ sec. cor. of secs. 3 and 4, as determined from the orig. mound of stone, falls on a steep S. slope. At the corner point Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd. |
| | T9S R28E ½ S 4 S 3 1968 |
| | from which A boulder, 5x5x4 ft. in size and conforming to the record, (with evidence of having been struck and moved by falling boulders from above), bears S., 5 lks. dist. No visible marks on the boulder. |
| | ————— |
| | N. 10°36' W., beginning new measurement. Asc. steep S. slope. |
| 1.50 | Top of mountain, bears E. and W., desc. N. slope. |
| 40.80 | Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W. |
| 40.89 | The cor. of secs. 3 and 4, T. 9 S., R. 28 E., on the N. bdy. of the Tp. Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, cacti and mesquite. |
| | From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. in diam., as described in the official record of the resurvey in 1960-61. from which A Jeep Trail, bears South, 20 lks. dist.; road bears N. 85° E. and S. 85° W. |
| | N. 0°52' W., bet. secs. 32 and 33. Over gently rolling land. |
| 4.80 | Fence, bears S. 75° E. and N. 75° W. |
| 11.30 | Wash, 6 lks. wide, 2 ft. deep, drains N. 60° W. |
| 30.70 | Wash, 15 lks. wide, 3 ft. deep, drains W. |
| 35.10 | Wash, 40 lks. wide, 4 ft. deep, drains SW. |
| 39.31 | The ¼ sec. cor. of secs. 32 and 33, monumented by a malpais stone, 10x8x6 ins., lying loose on ground, mkd. ¼ on |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>a face, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{2}$ S 32 S 33 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over gently rolling land.</p> <p>20.00 Enter nearly level land.</p> <p>26.00 Wash, 10 lks. wide, 3 ft. deep, drains W.</p> <p>30.55 Fence, bears S. 75° E. and N. 75° W.</p> <p>40.19 The cor. of secs. 28, 29, 32 and 33, monumented by a malpais stone, 10x8x6 ins., firmly set 4 ins. in the ground, mkd. 4 notches on E. and 1 notch on S. faces, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E S 29 S 28 S 32 S 33 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling to nearly level. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°27' W., bet. secs. 28 and 33.</p> <p>Over nearly level land.</p> <p>12.30 Wash, 35 lks. wide, 2 ft. deep, drains S. 85° W.</p> <p>37.00 Wash, 100 lks. wide, 2 ft. deep, drains S. 50° W.</p> <p>39.41 The $\frac{1}{2}$ sec. cor. of secs. 28 and 33, monumented by a malpais stone, 12x8x6 ins., firmly set 6 ins. in the ground, dimly mkd. $\frac{1}{4}$ on N. face, with mound of stone N.</p> <p>At the corner point</p> |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | Set the iron post 22 ins. in the ground, brass cap mkd. $\begin{array}{r} T9S R28E \\ \frac{1}{4} \frac{S 28}{S 33} \\ 1968 \end{array}$ Bury the orig. cor. stone alongside the iron post. Raise a mound of stone N. of the cor. <hr style="width: 20%; margin: auto;"/> S. 89°35' W., beginning new measurement. Over nearly level land. |
| 17.80 | Wash, 40 lks. wide, 1 ft. deep, drains S. 60° W. |
| 41.15 | The cor. of secs. 28, 29, 32 and 33. Land, nearly level. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite. |
| | N. 0°30' E., bet. secs. 28 and 29. Over nearly level land. |
| 1.20 | Wash, 5 lks. wide, 1 ft. deep, drains W. |
| 9.60 | Enter gently rolling land. |
| 32.50 | Draw, drains W. |
| 35.60 | Track road, bears N. 80° E. and S. 80° W. |
| 39.00 | Cove Draw, 3.40 chs. wide, 3 ft. deep, drains W. |
| 40.13 | Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor. This point falls in a Cove Draw and is impractical to monument. |
| 41.03 | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 28 and 29. Set the iron post 22 ins. in the ground, brass cap mkd. $\begin{array}{r} T9S R28E \\ \frac{1}{4} \\ W \quad C \\ S 29 \downarrow S 28 \\ 1968 \end{array}$ Raise a mound of stone W. of the iron post. |
| 51.60 | Wash, 5 lks. wide, 1 ft. deep, drains SW. |
| 56.90 | Wash, 10 lks. wide, 3 ft. deep, drains W. |
| 80.26 | The cor. of secs. 20, 21, 28 and 29, monumented by a malpais stone, 18x9x6 ins., firmly set 6 ins. in the ground, no mks. visible, with mound of stone W. I accept this as the orig. cor. |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T9S R28E S 20 S 21 S 29 S 28 1968 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Set a wooden post, 5 ft. long, 4 ins. squared, alongside the iron post.</p> <p>Land, nearly level to gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°39' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land.</p> |
| 13.60 | Enter Cove Draw, 50 lks. wide, 2 ft. deep, drains west-erly along line from the NE. |
| 33.10 | Track road, bears NE. and SW. |
| 39.82 | Point for the 1/2 sec. cor. of secs. 21 and 28, at propor-tionate dist.; there is no remaining evidence of the orig. cor. This point falls in a Cove Draw, 60 lks. wide, 2 ft. deep, draining S. from the E., and is im-practical to monument. |
| 40.60 | Leave wash area, thence over rolling land. |
| 40.62 | Point selected for the witness 1/2 sec. cor. of secs. 21 and 28. |
| | <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T9S R28E 1/2 WS 21 CS 28 1968 </p> <p>Raise a mound of stone N. of the iron post.</p> |
| 79.64 | <p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, gently rolling to rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| | <p>N. 0°44' W., bet. secs. 20 and 21.</p> <p>Over wash area.</p> |
| 0.30 | Wash, 25 lks. wide, 2 ft. deep, drains W. |
| 10.50 | Wash, 55 lks. wide, 3 ft. deep, drains S. 10° W. |
| 16.00 | Enter rolling land. |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|----------------------------------|---|
| 40.54 | <p>The $\frac{1}{2}$ sec. cor. of secs. 20 and 21, monumented by a malpais stone, 10x4x4 ins., lying loose on ground, mkd. $\frac{1}{2}$ on a face, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{2}$ S 20 S 21 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°07' W., beginning new measurement.</p> <p>Over rolling land.</p> |
| 38.56 | <p>The cor. of secs. 16, 17, 20 and 21, monumented by a malpais stone, 10x8x4 ins.; loosely set in a mound of stone, mkd. 4 notches on E. and 3 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E <u>S 17 S 16</u> S 20 S 21 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| 10.40 37.80 39.00 40.62 | <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 87°26' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land.</p> <p>Wash, 5 lks. wide, 2 ft. deep, drains NW.</p> <p>Wash, 5 lks. wide, 2 ft. deep, drains SW.</p> <p>Wash, 30 lks. wide, 3 ft. deep, drains S.</p> <p>The $\frac{1}{2}$ sec. cor. of secs. 16 and 21, monumented by a malpais stone, 10x7x3 ins., firmly set 4 ins. in the ground, mkd. $\frac{1}{2}$ on N. face, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

CHAINS

T9S R28E

 $\frac{1}{4}$ S 16

S 21

1968

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone N. of the cor.

N. 88°31' W., beginning new measurement.

Over gently rolling land.

35.00 Wash, 15 lks. wide, 2 ft. deep, drains N.

40.13 The cor. of secs. 16, 17, 20 and 21.

Land, gently rolling.

Soil, rocky, sandy loam.

Timber, none.

Undergrowth, creosote bush, cacti and mesquite.

N. 0°19' W., bet. secs. 16 and 17.

Over gently rolling land.

5.00 Wash area, drains SW.

29.90 Wash, 100 lks. wide, 2 ft. deep, drains W.

37.70 Wash, 5 lks. wide, 2 ft. deep, drains SW.

40.04 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented by a mal-pais stone, 10x6x4 ins., firmly set in a small mound of stone, mkd. $\frac{1}{4}$ on W. face.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T9S R28E

 $\frac{1}{4}$

S 17 | S 16

1968

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

N. 0°08' E., beginning new measurement.

Over gently rolling land.

2.50 Wash, 20 lks. wide, 3 ft. deep, drains W.

20.90 Wash, 15 lks. wide, 2 ft. deep, drains W.

28.60 Wash, 5 lks. wide, 1 ft. deep, drains NW.

39.98 The cor. of secs. 8, 9, 16 and 17, monumented by a mal-pais stone, 14x6x6 ins., firmly set 6 ins. in the ground, mkd. 4 notches on E. and S. faces, with a mound of stone W.

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T9S R28E <u>S 8 S 9</u> S 17 S 16 1968 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| 40.17 | <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°23' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land.</p> <p>The ½ sec. cor. of secs. 9 and 16, monumented by a malpais stone, 6x4x3 ins., lying loose on ground, mkd. ½ on a face, with scattered mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T9S R28E <u>S 9</u> S 16 1968 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°17' W., beginning new measurement.</p> <p>Over gently rolling land.</p> |
| 11.40 | Wash, 50 lks. wide, 2 ft. deep, drains S. 70° W. |
| 30.70 | Wash, 60 lks. wide, 3 ft. deep, drains NW. |
| 40.60 | <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| 1.20 | Wash, 35 lks. wide, 3 ft. deep, drains S. 85° W. |
| 5.60 | Wash, 60 lks. wide, 2 ft. deep, drains S. 70° W. |
| 23.80 | Wash, 20 lks. wide, 2 ft. deep, drains S. 20° W. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| 40.56 | <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 8 S 9 1968</p> <p>Raise a mound of stone W. of the cor.</p> |
| 46.00 | Wash, 80 lks. wide, 4 ft. deep, drains W. |
| 64.90 | Wash, 50 lks. wide, 2 ft. deep, drains W. |
| 68.60 | Wash, 15 lks. wide, 2 ft. deep, drains SW. |
| 78.60 | Wash, 10 lks. wide, 3 ft. deep, drains SW. |
| 81.12 | <p>The cor. of secs. 4, 5, 8 and 9, monumented by a malpais stone, 8x6x4 ins., firmly set 4 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E <u>S 5 S 4</u> S 8 S 9 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |
| 40.10 | <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°43' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented by a malpais stone, 12x7x5 ins., lying loose on ground, mkd. $\frac{1}{4}$ on a face, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ <u>S 4</u> S 9 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°42' W., beginning new measurement.</p> <p>Over gently rolling land.</p> |
| 40.28 | <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite.</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | N. 1°37' W., bet. secs. 4 and 5. Over gently rolling land. |
| 1.60 | Small draw, drains W. |
| 18.70 | Wash, 20 lks. wide, 2 ft. deep, drains NW. |
| 23.50 | Wash, 50 lks. wide, 1 ft. deep, drains N. 50° W. |
| 39.03 | Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 22 ins. in the ground, brass cap mkd. T9S R28E $\frac{1}{4}$ S 5 S 4 1968 |
| | Raise a mound of stone W. of the cor. |
| 40.00 | Wash, 10 lks. wide, 1 ft. deep, drains W. |
| 42.50 | Wash, 15 lks. wide, 1 ft. deep, drains W. |
| 46.90 | Wash, 20 lks. wide, 2 ft. deep, drains W. |
| 51.60 | Spur, slopes W. |
| 57.90 | Fence, bears S. 70° E. and N. 70° W. |
| 58.20 | Track road, bears S. 70° E. and N. 70° W. |
| 74.25 | The cor. of secs. 4 and 5, on the N. bdy. of the Tp. Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush, cacti and mesquite. |
| | From the cor. of secs. 28, 29, 32 and 33. N. 89°26' W., bet. secs. 29 and 32. Over nearly level land. |
| 23.50 | Fence, bears S. 30° E. and N. 30° W. |
| 40.30 | The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented by a malpais stone, 10x6x6 ins., loosely set 3 ins. in the ground, mkd. $\frac{1}{4}$ on N. face, with mound of stone N. At the corner point Set the iron post 22 ins. in the ground, brass cap mkd. T9S R28E $\frac{1}{4}$ S 29 S 32 1968 |
| | from which Cor. of fences, bears N. 15° W., 91 lks. dist.; fences bear NE. and S. 80° W. Bury the orig. cor. stone alongside the iron post. Raise a mound of stone N. of the cor. |
| | S. 89°46' W., beginning new measurement. Over gently rolling land. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | | | | | |
|--------|--|--------|------|------|------|
| 13.00 | Fence, bears N. 80° E. and S. 80° W. | | | | |
| 15.20 | Wash, 20 lks. wide, 1 ft. deep, drains SW. | | | | |
| 40.06 | <p>The cor. of secs. 29, 30, 31 and 32, monumented by a malpais stone, 8x4x4 ins., loosely set 3 ins. in the ground, mkd. with 5 notches on E. and 1 notch on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <table border="0"> <tr> <td>S 30</td> <td>S 29</td> </tr> <tr> <td>S 31</td> <td>S 32</td> </tr> </table> <p>1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, nearly level to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> | S 30 | S 29 | S 31 | S 32 |
| S 30 | S 29 | | | | |
| S 31 | S 32 | | | | |
| | <p>N. 89°35' W., bet. secs. 30 and 31. Over gently rolling land.</p> | | | | |
| 1.20 | Track road, bears NE. and SW. | | | | |
| 8.10 | Track road, bears N. and S. | | | | |
| 38.10 | Dim track road, bears SE. and NW. | | | | |
| 39.75 | <p>Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T9S R28E</p> <table border="0"> <tr> <td>¼ S 30</td> <td></td> </tr> <tr> <td>S 31</td> <td></td> </tr> </table> <p>1968</p> </div> <p>Raise a mound of stone N. of the iron post.</p> | ¼ S 30 | | S 31 | |
| ¼ S 30 | | | | | |
| S 31 | | | | | |
| 50.20 | Wash, 10 lks. wide, 2 ft. deep, drains NW. | | | | |
| 78.57 | <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. in diam., as described in the official record of the resurvey in 1961.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> | | | | |
| | <p>From the cor. of secs. 29, 30, 31 and 32. North, bet. secs. 29 and 30. Over rolling land.</p> | | | | |
| 1.50 | Track road, bears NE. and SW. | | | | |

Dependent Resurvey
 Portion Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| 9.10 | Wash, 15 lks. wide, 1 ft. deep, drains W. |
| 23.70 | Wash, 10 lks. wide, 2 ft. deep, drains S. 35° W. |
| 36.80 | Track road, bears S. 80° E. and N. 80° W. |
| 40.15 | The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented by a malpais stone, 6x6x4 ins., set 3 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone W. |
| | At the corner point |
| | Set the iron post 24 ins. in the ground, brass cap mkd. |
| | T9S R28E $\frac{1}{4}$ S 30 S 29 1968 |
| | Bury the orig. cor. stone alongside the iron post. |
| | Raise a mound of stone W. of the cor. |
| | N. 0°02' W., beginning new measurement. |
| | Over gently rolling land. |
| 8.00 | Wash, 20 lks. wide, 2 ft. deep, drains N. 60° W. |
| 14.60 | Cove Draw, 100 lks. wide, 4 ft. deep, drains N. 80° W. |
| 23.60 | Track road, bears NE. and SW. |
| 31.90 | Wash, 15 lks. wide, 1 ft. deep, drains W. |
| 37.30 | Wash, 100 lks. wide, 3 ft. deep, drains N. 80° W. |
| 40.22 | The cor. of secs. 19, 20, 29 and 30, monumented by an malpais stone, 8x4x4 ins., set 4 ins. in the ground, mkd. with 5 notches on E. and 2 notches on S. faces. |
| | At the corner point |
| | Set the iron post 24 ins. in the ground, brass cap mkd. |
| | T9S R28E S 19 S 20 S 30 S 29 1968 |
| | Bury the orig. cor. stone alongside the iron post. |
| | Set a wooden post, 4 ft. long, 4 ins. squared, alongside the cor. |
| | Land, gently rolling to rolling. |
| | Soil, sandy loam. |
| | Timber, none. |
| | Undergrowth, creosote bush and cacti. |
| | From the cor. of secs. 20, 21, 28 and 29. |
| | N. 89°32' W., bet. secs. 20 and 29. |
| | Over rolling land. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| 2.10 | Wash, 50 lks. wide, 1 ft. deep, drains S. |
| 4.20 | Wash, 40 lks. wide, 1 ft. deep, drains S. |
| 31.20 | Wash, 20 lks. wide, 1 ft. deep, drains S. 40° W. |
| 40.75 | The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented by a malpais stone, 10x9x5 ins., lying loose on ground, mkd. $\frac{1}{4}$ on a face, with mound of stone N. At the corner point Set the iron post, 18 ins. in the ground, collar of stone to top, brass cap mkd. <div style="text-align: center;"> T9S R28E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{20}{29}$ 1968 </div> Bury the orig. cor. stone alongside the iron post. <hr style="width: 20%; margin: auto;"/> N. 89°54' W., beginning new measurement. Over rolling land. |
| 6.80 | Wash, 10 lks. wide, 2 ft. deep, drains S. |
| 32.40 | Track road, bears SE. and NW. |
| 40.27 | The cor. of secs. 19, 20, 29 and 30. Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti. |
| | N. 89°49' W., bet. secs. 19 and 30. Over gently rolling land. |
| 13.30 | Wash, 160 lks. wide, 3 ft. deep, drains N. 80° W. |
| 29.00 | Enter wash, 100 lks. wide, 3 ft. deep, drains W. from the NE. |
| 39.10 | Intersection of wash with Cove Draw, 150 lks. wide, 3 ft. deep, drains N. 80° W. |
| 39.92 | Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor. This point falls in Cove Draw and is impractical to monument. |
| 40.92 | Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 19 and 30. Set the iron post 18 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T9S R28E $\frac{1}{4}$ $\frac{W}{C}$ $\frac{S}{S}$ $\frac{19}{30}$ 1968 </div> Set a wooden post 3 ft. long, 3 ins. squared, alongside the iron post. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| 51.60 | S. bank of Cove Draw, 4 ft. high, bears N. 80° E. and N. 50° W. |
| 78.47 | <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., as described in the official record of the resurvey in 1961.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| | <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°24' E., bet. secs. 19 and 20.</p> <p>Over gently rolling land.</p> |
| 11.40 | Track road, bears SE. and NW. |
| 38.60 | Wash, 10 lks. wide, 1 ft. deep, drains N. 85° W. |
| 39.77 | <p>Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E ¼ S 19 S 20 1968</p> |
| | Deposit glass in hole alongside the iron post. |
| 48.50 | Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W. |
| 72.20 | Top of mesa, bears E. and W. |
| 79.54 | <p>The cor. of secs. 17, 18, 19 and 20, monumented by a malpais stone, 12x5x4 ins., firmly set in mound of stone, mkd. with 5 notches on E. and 3 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E S 18 S 17 ----- S 19 S 20 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Set a wooden post, 6 ft. long, 4 ins. squared alongside the cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| | From the cor. of secs. 16, 17, 20 and 21. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | <p>N. 89°31' W., bet. secs. 17 and 20.</p> |
| | <p>Over rolling land.</p> |
| 5.60 | <p>Wash, 10 lks. wide, 1 ft. deep, drains SW.</p> |
| 36.50 | <p>Wash, 40 lks. wide, 1 ft. deep, drains SW.</p> |
| 39.86 | <p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented by a mal-pais stone, 20x15x10 ins., firmly set in a mound of stone, dimly mkd. $\frac{1}{4}$ on N. face.</p> |
| | <p>At the corner point</p> |
| | <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> |
| | <p style="text-align: center;">T9S R28E</p> |
| | <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 17}{S 20}$</p> |
| | <p style="text-align: center;">1968</p> |
| | <p>Bury the orig. cor. stone alongside the iron post.</p> |
| | <p>Raise a mound of stone N. of the cor.</p> |
| | <p style="text-align: center;">_____</p> <p>N. 89°17' W., beginning new measurement.</p> |
| | <p>Over rolling land.</p> |
| 39.97 | <p>The cor. of secs. 17, 18, 19 and 20.</p> |
| | <p>Land, rolling.</p> |
| | <p>Soil, sandy loam.</p> |
| | <p>Timber, none.</p> |
| | <p>Undergrowth, creosote bush and cacti.</p> |
| | <p>S. 87°13' W., bet. secs. 18 and 19.</p> |
| | <p>Over rolling land.</p> |
| 42.13 | <p>The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented by a mal-pais stone, 20x9x6 ins., firmly set in mound of stone, mkd. $\frac{1}{4}$ on N. face.</p> |
| | <p>At the corner point</p> |
| | <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> |
| | <p style="text-align: center;">T9S R28E</p> |
| | <p style="text-align: center;">$\frac{1}{4}$ $\frac{S 18}{S 19}$</p> |
| | <p style="text-align: center;">1968</p> |
| | <p>Bury the orig. cor. stone alongside the iron post.</p> |
| | <p>Raise a mound of stone N. of the cor.</p> |
| | <p style="text-align: center;">_____</p> <p>N. 85°32' W., beginning new measurement.</p> |
| | <p>Over gently rolling land.</p> |
| 7.10 | <p>Wash, 20 lks. wide, 2 ft. deep, drains SW.</p> |
| 20.90 | <p>Track road, bears S. 10° E. and N. 10° W.</p> |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| 37.01 | <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., as described in the official record of the resurvey in 1961.</p> <p>Land, rolling to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote and cacti.</p> |
| | <p>From the cor. of secs. 17, 18, 19 and 20. N. 0°10' E., bet. secs. 17 and 18. Over rolling land.</p> |
| 15.10 | Wash, 20 lks. wide, 1 ft. deep, drains S. 85° W. |
| 32.70 | Wash, 35 lks. wide, 2 ft. deep, drains NW. |
| 38.90 | Wash, 35 lks. wide, 2 ft. deep, drains S. 80° W. |
| 40.10 | <p>The ¼ sec. cor. of secs. 17 and 18, monumented by a malpais stone, 10x5x4 ins., set 4 ins. in the ground, mkd. ¼ on W. face.</p> |
| | At the corner point |
| | Set the iron post 22 ins. in the ground, brass cap mkd. |
| | <p style="text-align: center;">T9S R28E ¼ S 18 S 17 1968</p> |
| | Bury the orig. cor. stone alongside the iron post. |
| | Deposit glass in hole alongside the cor. |
| | N. 1°14' W., beginning new measurement. |
| | Over rolling land. |
| 7.30 | Wash, 10 lks. wide, 1 ft. deep, drains SW. |
| 20.50 | Top of mesa, bears E. and W. |
| 37.20 | Spur, slopes W. |
| 39.63 | <p>The cor. of secs. 7, 8, 17 and 18, monumented by a malpais stone, 12x6x6 ins., set 5 ins. in the ground, mkd. with 5 notches on E. and 4 notches on S. faces.</p> |
| | At the corner point |
| | Set the iron post 22 ins. in the ground, brass cap mkd. |
| | <p style="text-align: center;">T9S R28E S 7 S 8 S 18 S 17 1968</p> |
| | Bury the orig. cor. stone alongside the iron post. |
| | Raise a mound of stone W. of the cor. |
| | Set a wooden post, 5 ft. long, 4 ins. squared, alongside the cor. |

Dependent Resurvey
Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| | <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| | <p>From the cor. of secs. 8, 9, 16 and 17. N. 89°36' W., bet. secs. 8 and 17. Over gently rolling land.</p> |
| 25.10 | Wash, 20 lks. wide, 2 ft. deep, drains S. 70° W. |
| 39.10 | Wash, 20 lks. wide, 2 ft. deep, drains N. 75° W. |
| 40.19 | Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 24 ins. in the ground, brass cap mkd. |
| | <p>T9S R28E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{8}{17}$ 1968</p> |
| | Raise a mound of stone N. of the iron post. |
| 80.38 | The cor. of secs. 7, 8, 17 and 18. Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti. |
| | <p>N. 89°04' W., bet. secs. 7 and 18. Over gently rolling land.</p> |
| 34.50 | Track road, bears NE. and SW. |
| 38.20 | Jeep Trail, bears S. and N. 10° W. |
| 40.28 | Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 24 ins. in the ground, collar of stone to top, brass cap mkd. |
| | <p>T9S R28E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{7}{18}$ 1968</p> |
| 68.50 | Track road, bears SE. and NW. |
| 78.21 | The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by an iron post, 2 $\frac{1}{2}$ ins. in diam., as described in the official record of the resurvey in 1961. |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| | <p>From the cor. of secs. 7, 8, 17 and 18. N. 0°09' E., bet. secs. 7 and 8. Over gently rolling land.</p> |
| 5.70 | Wash, 100 lks. wide, 2 ft. deep, drains N. 80° W. |
| 8.80 | Wash, 60 lks. wide, 1 ft. deep, drains S. 80° W. |
| 40.20 | <p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, monumented by a malpais stone, 8x6x4 ins., set 3 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 7 S 8 1968</p> <p>Bury the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°14' E., beginning new measurement. Over gently rolling land.</p> |
| 7.60 | Wash, 20 lks. wide, 2 ft. deep, drains N. 80° W. |
| 40.30 | <p>The cor. of secs. 5, 6, 7 and 8, monumented by a malpais stone, 12x8x6 ins., set 5 ins. in the ground, mkd. with 5 notches on E. and S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E S 6 S 5 S 7 S 8 1968</p> <p>Bury the orig. cor. stone alongside the iron post. Deposit glass in hole alongside the cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| | <p>From the cor. of secs. 4, 5, 8 and 9. S. 89°48' W., bet. secs. 5 and 8. Over gently rolling land.</p> |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|--|
| 34.90 | Wash, 10 lks. wide, 2 ft. deep, drains N. 20° W. |
| 40.20 | The ¼ sec. cor. of secs. 5 and 8, monumented by a malpais stone, 10x4x3 ins., set 3 ins. in the ground, mkd. ¼ on N. face. |
| | At the corner point |
| | Set the iron post 22 ins. in the ground, brass cap mkd. |
| | T9S R28E $\frac{1}{4} \frac{S \ 5}{S \ 8}$ 1968 |
| | Bury the orig. cor. stone alongside the iron post. |
| | Raise a mound of stone N. of the cor. |
| | _____ |
| | N. 89°49' W., beginning new measurement. |
| | Over gently rolling land. |
| 16.00 | Wash, 20 lks. wide, 1 ft. deep, drains N. 30° W. |
| 40.21 | The cor. of secs. 5, 6, 7 and 8. |
| | Land, gently rolling. |
| | Soil, sandy loam. |
| | Timber, none. |
| | Undergrowth, creosote bush and cacti. |
| | N. 89°28' W., bet. secs. 6 and 7. |
| | Over gently rolling land. |
| 0.80 | Track road, bears N. 30° E. and S. 30° W. |
| 18.40 | Wash, 15 lks. wide, 3 ft. deep, drains SW. |
| 31.00 | Wash, 15 lks. wide, 2 ft. deep, drains N. 70° W. |
| 40.62 | Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor. |
| | Set the iron post 18 ins. in the ground, brass cap mkd. |
| | T9S R28E $\frac{1}{4} \frac{S \ 6}{S \ 7}$ 1968 |
| | Deposit glass in hole alongside the iron post. |
| 60.50 | Wash, 40 lks. wide, 3 ft. deep, drains N. 80° W. |
| 72.40 | Wash, 50 lks. wide, 3 ft. deep, drains S. 60° W. |
| 78.35 | The true point for the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.; witnessed, S. 0°06' W., 20 lks. dist., by an iron post, 2½ ins. in diam., as described in the official record of the resurvey in 1961. |
| | Land, gently rolling. |

Dependent Resurvey
 Portion, Subdivisional Lines, T. 9 S., R. 28 E.

| CHAINS | |
|--------|---|
| | <p>Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8. N. 0°12' W., bet. secs. 5 and 6. Over gently rolling land.</p> <p>1.40 Track road, bears N. 30° E. and S. 30° W.</p> <p>5.90 Wash, 5 lks. wide, 1 ft. deep, drains S. 35° W.</p> <p>25.70 Wash, 5 lks. wide, 2 ft. deep, drains NW.</p> <p>40.41 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented by a charred stake, 15 ins. long, 2 ins. squared, set 12 ins. in the ground, dimly mkd. $\frac{1}{4}$ on W. edge.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T9S R28E $\frac{1}{4}$ S 6 S 5 1968</p> <p>Bury the orig. cor. alongside the iron post. Deposit glass in hole alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 2°34' W., beginning new measurement. Over gently rolling land.</p> <p>0.70 Wash, 5 lks. wide, 6 ins. deep, drains NW.</p> <p>9.80 Wash, 5 lks. wide, 6 ins. deep, drains W.</p> <p>34.06 The cor. of secs. 5 and 6, on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., as described in the official record of the resurvey in 1914.</p> <p>from which</p> <p style="padding-left: 40px;">The closing cor. of secs. 31 and 32, T. 8 S., R. 28 E., bears N. 89°51' W., 2.54 chs. dist., monumented by an iron post, 2 ins. diam., as described in the official record of the survey of T. 8 S., R. 28 E. in 1914.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| | <p>Subdivision of Section 36, T. 9 S., R. 28 E.</p> |
| | <p>From the $\frac{1}{4}$ sec. cor. of secs. 1 and 36, on the S. bdy. of the Tp., hereinbefore described.</p> |

Subdivision of Section 36, T. 9 S., R. 28 E.

CHAINS

N. $0^{\circ}38'$ E., on the N. and S. centerline of sec. 36.

Over rolling land.

9.80 Wash, 15 lks. wide, 2 ft. deep, drains SW.

38.70 Wash, 25 lks. wide, 3 ft. deep, drains W.

41.09 Point for the center $\frac{1}{4}$ sec. cor. of sec. 36, at the intersection of the E. and W. centerline of sec. 36.

Set the iron post 20 ins. in the ground, brass cap mkd.

T9S R28E

C $\frac{1}{4}$ +S 36

1968

Raise a mound of stone W. of the iron post.

56.10 Wash, 15 lks. wide, 2 ft. deep, drains W., 70 lks. dist.; thence SW.

61.11 Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 36.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T9S R28E

C
N $\frac{1}{16}$ | S 36

C

1968

61.40 Jeep Trail, bears N. 80° E. and S. 80° W.

81.13 The $\frac{1}{4}$ sec. cor. of secs. 25 and 36.

Land, rolling.

Soil, sandy loam.

Timber, none.

Undergrowth, creosote bush and cacti.

From the $\frac{1}{4}$ sec. cor. of sec. 36, on the E. bdy. of the Tp.

N. $89^{\circ}00'$ W., on the E. and W. centerline of sec. 36.

Over rolling land.

18.40 Wash, 10 lks. wide, 2 ft. deep, drains S. 40° W.

19.00 Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 36.

Set the iron post 18 ins. in the ground, brass cap mkd.

T9S R28E

C $\frac{E}{1/16}$ — C

S 36

1968

Raise a mound of stone N. of the iron post.

34.10 Wash, 60 lks. wide, 2 ft. deep, drains SW.

38.00 The center $\frac{1}{4}$ sec. cor. of sec. 36.

Subdivision of Section 36, T. 9 S., R. 28 E.

| CHAINS | |
|--|---|
| 65.60 | Wash, 15 lks. wide, 3 ft. deep, drains SW. |
| 68.90 | Jeep Trail, bears NE. and SW. |
| 78.81 | <p>The $\frac{1}{4}$ sec. cor. of secs. 35 and 36.</p> <p>Land, rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote bush and cacti.</p> |
| <p>Subdivision of NE$\frac{1}{4}$ Section 36</p> <hr/> | |
| <p>From the C-E 1/16 sec. cor. of sec. 36.</p> | |
| <p>N. 0°19' E., on the N. and S. centerline of the NE$\frac{1}{4}$ sec. 36.</p> | |
| <p>Over rolling land.</p> | |
| 16.20 | Wash, 30 lks. wide, 2 ft. deep, drains SW. |
| 20.02 | <p>Point for the NE 1/16 sec. cor. of sec. 36, at the intersection with the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 36.</p> |
| <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p> | |
| <p>T9S R28E NE 1/16 S 36 1968</p> | |
| 26.20 | Jeep Trail, bears E. and W. |
| 28.50 | Wash, 10 lks. wide, 2 ft. deep, drains SW. |
| 40.06 | The E 1/16 sec. cor. of secs. 25 and 36. |
| <hr/> <p>From the N 1/16 sec. cor. of sec. 36, on the E. bdy. of the Tp.</p> | |
| <p>N. 89°03' W., on the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 36.</p> | |
| <p>Over rolling land.</p> | |
| 9.40 | Wash, 30 lks. wide, 3 ft. deep, drains SW. |
| 11.90 | Wash, 30 lks. wide, 3 ft. deep, drains SW. |
| 13.10 | Wash, 30 lks. wide, 3 ft. deep, drains SW. |
| 18.92 | The NE 1/16 sec. cor. of sec. 36. |
| 29.90 | Wash, 15 lks. wide, 2 ft. deep, drains SW. |
| 37.79 | The C-N 1/16 sec. cor. of sec. 36. |

Township 9 South, Range 28 East
Gila and Salt River Meridian, Arizona

CHAINS

GENERAL DESCRIPTION

The land within the township is mostly rolling hills with relatively low relief; however, there are a few predominate peaks in the northeastern portion. The highest elevation, about 5340 feet above sea level, is located on the east boundary of section 12 on the western slopes of Whitlock Mountain. The lowest elevation, 3206 feet above sea level, is at the northwest township corner.

The drainage of the township consists of numerous washes. General drainage is in a westerly direction, except for the northeastern portion of the township where washes drain in a northerly direction.

The soil consists mostly of sandy, clay loam. At the higher elevations the soil is interspersed with a shallow rocky loam. The vegetative cover is composed of mesquite, creosote brush, cacti and a very limited amount of grasses. The creosote brush and cacti cover most of the area, with mesquite along the drainage areas.

The main access road into the township enters on the south boundary of section 32, traverses in a northerly direction, leaving on the north boundary of section 5.

The main improvement in the township is the L. L. Ranch, located in section 31, consisting of an old ranch house, barn and watering tanks. Also, there are a few watering ponds located in section 3 and 14, and a windmill in section 22.

There is no mineral activity at the present time, and no evidence of such in the past.

CERTIFICATE OF SURVEY

We,
 Kx Kenneth D. Herman and Louis D. Gilbert , HEREBY CERTIFY upon honor that,
 Cadastral Surveyors
 in pursuance of special instructions bearing date of the 13 day of December , 19 67 ,
 we
 have made a retracement of a portion of the south boundary; a dependent
 resurvey of a portion of the east and north boundaries and subdivisional
 lines and a survey of subdivisions in section 36, Township 9 South, Range
 28 East,

of the Gila and Salt River Meridian, in the State of Arizona , which
 us our
 are represented in the foregoing field notes as having been executed by ~~me~~ and under ~~my~~ direction;
 and that said survey has been made in strict conformity with said special instructions, the Manual
 of Instructions for the Survey of the Public Lands of the United States, and in specific manner
 described in the foregoing field notes.

March 28, 1968
 (Date)
October 9, 1969
 (Date)

 (Date)

Kenneth D. Herman
 (Cadastral Surveyor)
Louis D. Gilbert
 (Cadastral Surveyor)

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date APR 2 1971

BUREAU OF LAND MANAGEMENT,
 Washington, D. C.

The foregoing field notes of the retracement of a portion of the south boundary;
 the dependent resurvey of a portion of the east and north boundaries and
 subdivisional lines and the survey of subdivisions in section 36, Township
 9 South, Range 28 East,

executed by Kenneth D. Herman and Louis D. Gilbert, Cadastral Surveyors
 having been critically examined and found correct, are hereby approved.

MAR 3 1972
 (Date)

Clark L. Humm
 (Chief, Division of Cadastral Survey)
 Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

 (Date)

 (Chief, Division of Engineering)