



# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Form 9180-29  
(March 1965)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION  
CORNER MONUMENTS

Tp. 6 N. R. 10 E. Mer. 2 G&SR 2

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Corner monument locations: (3,2), (2,2), (3,4), (4,4), (3,3), (4,3), (2,5), (3,5), (4,5), (2,6), (3,6), (4,6), (5,6), (6,6), (6,1), (6,6)

Tp. 6 N. R. 11 E. Mer. 7 G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Corner monument locations: (3,3), (3,4), (3,5), (3,6), (4,3), (4,4), (4,5), (4,6), (5,3), (5,4), (5,5), (5,6), (6,3), (6,4), (6,5), (6,6), (6,1), (6,6)

Tp. 6 N. R. 12 E. Mer. 9 G&SRM

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Corner monument locations: (8,9)

Township 6 North, Range 10 East  
 Township 6 North, Range 11 East  
 Township 6 North, Range 12 East  
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 1, 1970 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination is 14° E.

Township 6 North, Range 10 East, G&SR M., Arizona

The east and north boundaries and subdivisional lines were surveyed in 1881 by T. F. White, and the east boundary was resurveyed in 1907 by J. B. Wright.

The cor. of Tps. 5 and 6 N., Rs. 10 and 11 E., monumented by a granite stone, 18 x 12 x 6 ins., firmly set 10 ins. in the ground, mkd. 6 notches on the N., S., E. and W. faces, from which the orig. bearing trees

A mesquite, 12 ins. diam., bears S. 35 3/4° W., 23 lks. dist., mkd. with a blaze and faint illegible scribe mks.

A mesquite, 5 ins. diam., bears N. 34 3/4° W., 59 lks. dist., mkd. with a blaze and faint illegible scribe mks.

Unable to find any evidence of the other orig. bearing trees.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T6N  
 R10E R11E  
 S36 | S31  
 S 1 | S 6  
 T5N  
 1970

Bury the orig. cor. stone alongside the iron post.

## Remonumentation, T. 6 N., R. 10 E., Arizona

## CHAINS

The cor. of secs. 19, 24, 25 and 30, T. 6 N., Rs. 10 and 11 E., monumented by a local corner, a wooden post, 4 in. squared, 6 ft. long, set in the ground, verified by record course and dist. from the orig. bearing trees

A mesquite, 12 ins. diam., bears S. 15° E., 338 lks. dist., mkd. with a blaze and faint illegible scribe mks.

A mesquite, 12 ins. diam., bears N. 47° W., 397 lks. dist., mkd. with a blaze and faint illegible scribe mks.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T6N	
R10E	R11E
<u>S24</u>	<u>S19</u>
S25	S30
1970	

Raise a mound of stone W. of the iron post.

Reset the wooden post cor. alongside the iron post.

The cor. of secs. 1, 2, 35 and 36, Tps. 6 and 7 N., R. 10 E., monumented by a granite stone, 20 x 12 x 10 ins., firmly set 10 ins. in the ground, mkd. 1 notch on E. face and 5 notches on W. face, with mound of stone to the S.

At the cor. point

Set the iron post, 10 ins. in the ground, in a mound of stone, brass cap mkd.

T7N R10E	
<u>S35</u>	<u>S36</u>
S 2	S 1
T6N	
1970	

Bury the orig. cor. stone in the mound of stone alongside the iron post.

The cor. of secs. 2, 3, 34 and 35, Tps. 6 and 7 N., R. 10 E., monumented by a granite stone, 24 x 16 x 10 ins., firmly set 6 ins. in the ground, mkd. 2 notches on E. face and 4 notches on W. face, with mound of stone to the E., from which the orig. bearing trees

A mesquite, 5 ins. diam., bears N. 30° E., 25 lks. dist., no mks.

A mesquite stump, 4 ins. diam., bears S. 10° E., 20 lks. dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

## Remonumentation, T. 6 N., R. 10 E., Arizona

## CHAINS

T7N R10E  

S34	S35
S 3	S 2

 T6N  
 1970

Rebuild the mound of stone E. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{2}$  sec. cor. of secs. 13 and 24, monumented by a quartzite stone, 18 x 12 x 8 ins., firmly set 10 ins. in the ground, mkd.  $\frac{1}{2}$  on N. face.

Unable to find any evidence of the orig. bearing tree.

At the cor. point

Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.

T6N R10E  

$\frac{1}{2}$	S13
	S24

 1970

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 11, 12, 13 and 14, monumented by a local cor., an iron pipe,  $\frac{3}{4}$  in. diam., 14 ins. long, set in the ground, with tag mkd. LS 4083, verified by course and dist. from the orig. bearing tree

A mesquite stump, 6 ins. diam., bears N. 3° E., 247 lks. dist., mkd. with faint illegible scribe mks.

At the cor. point

Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.

T6N R10E  

S11	S12
S14	S13

 1970

Reset the iron pipe cor. alongside the iron post.

The  $\frac{1}{2}$  sec. cor. of secs. 12 and 13, monumented by an igneous stone, 12 x 10 x 8 ins., lying loose on the ground, mkd.  $\frac{1}{2}$  on one face, with a local cor., an iron pipe,  $\frac{3}{4}$  in. diam., 14 ins. long, with tag mkd. LS 4083, set alongside, and with a mound of stone to the N.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T6N R10E  

$\frac{1}{2}$	S12
	S13

 1970

## Remonumentation, T. 6 N., R. 10 E., Arizona

## CHAINS

Reset the local iron pipe cor. alongside the iron post.

Bury the orig. cor. stone alongside the iron post.

---

The cor. of secs. 1, 2, 11 and 12, monumented by a granite stone, 16 x 10 x 8 ins., dimly mkd. 1 notch on E. face and 5 notches on S. face, with mound of stone to the W.

Unable to find any evidence of the orig. bearing trees.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T6N R10E  
 S 2 | S 1  
 S11 | S12  
 1970

Bury the orig. cor. stone alongside the iron post.

---

The cor. of secs. 10, 11, 14 and 15, monumented by a mound of stone, with an iron pipe, 1 in. diam., set in the center of the mound of stone, from which the orig. bearing trees

A mesquite, 6 ins. diam., bears N. 48° E., 225 lks. dist., mkd. with a blaze and faint illegible scribe mks.

A mesquite, 12 ins. diam., bears N. 65° W., 120 lks. dist., mkd. with faint illegible scribe mks.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 6 ins. in the ground, over the 1 in. iron pipe for stability, in a mound of stone, brass cap mkd.

T6N R10E  
 S10 | S11  
 S15 | S14  
 1970

## Remonumentation, T. 6 N., R. 10 E., Arizona

## CHAINS

The cor. of secs. 2, 3, 10 and 11, monumented by a granite stone, 15 x 12 x 6 ins., lying loose on the ground, mkd. 2 notches on one face and 5 notches on an adjacent face, with mound of stone to the NW., from which an orig. bearing tree

A mesquite, 8 ins. diam., bears N. 71½° E., 153 lks. dist., mkd. with a blaze and faint illegible scribe mks.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T6N R10E  
 S 3 | S 2  
 S10 | S11  
 1970

Rebuild the mound of stone NW. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 9, 10, 15 and 16, monumented by a granite stone, 16 x 10 x 8 ins., set in a mound of stone, mkd. 4 notches on E. face and 4 notches on S. face.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T6N R10E  
 S 9 | S10  
 S16 | S15  
 1970

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

## Remonumentation, T. 6 N., R. 11 E., Arizona

## CHAINS

Township 6 North, Range 11 East, G&SR M., Arizona

A portion of the south boundary and a portion of the subdivisional lines were resurveyed in 1907 by J. B. Wright, who also surveyed the east boundary, a portion of the south boundary, the north boundary, and completed the survey of the subdivisional lines.

Remonumentation, T. 6 N., R. 11 E., Arizona

The cor. of secs. 1, 6, 7 and 12, T. 6 N., Rs. 11 and 12 E., monumented by a quartzite stone, 18 x 12 x 8 ins., firmly set 6 ins. in the ground, mkd. 1 notch on N. face and 5 notches on S. face, with mound of stone to the W.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T6N  
R11E R12E  
S 1 | S 6  
S 12 | S 7  
1970

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 5, 6, 31 and 32, Tps. 5 and 6 N., R. 11 E., monumented by an iron pipe, 1 in. diam., set flush in a gravelled road, verified by record course and dist. from an orig. bearing tree

A mesquite, 7 ins. diam., bears N.  $9\frac{1}{2}^{\circ}$  W., 133 lks. dist., mkd. 6N R11E S.

Unable to find any evidence of the other orig. bearing trees.

At the cor. point

Set the iron post, 6 ins. below the surface of the road, brass cap mkd.

T6N R11E  
S 31 | S 32  
S 6 | S 5  
T5N  
1970

I placed a Gala coke can on top of the brass cap, flush with the surface of the road, in order to locate cor. readily.

Cor. is in a gravelled road bearing N.  $70^{\circ}$  E. and S.  $70^{\circ}$  W. This road is seldom graded.

Reset the 1 in. iron pipe alongside the iron post.

Remonumentation, T. 6 N., R. 11 E., Arizona

CHAINS	Tps. 6 and 7 N., R. 11 E.,
	<p>The cor. of secs. 3, 4, 33 and 34, /monumented by a quartzite stone, 13 x 6 x 5 ins., set 4 ins. in the ground, mkd. 3 notches on E. face, 3 notches on W. face, and 6 notches on S. face, with mound of stone to the W., from which an orig. bearing tree</p> <p>A mesquite, 7 ins. diam., bears S. 10° E., 80 lks. dist., mkd. T6N R11E S3 BT.</p> <p>At the cor. point</p> <p>Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7N R11E S33   S34 S 4   S 3 T6N 1970</p> <p>Rebuild the mound of stone W. of the iron post.</p> <p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>The cor. of secs. 1, 2, 11 and 12, monumented by a quartzite stone, 14 x 8 x 5 ins., firmly set 6 ins. in the ground, mkd. 1 notch on E. face and 5 notches on S. face, with mound of stone to the S.</p> <p>At the cor. point</p> <p>Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T6N R11E S 2   S 1 S11   S12 1970</p> <p>Rebuild the mound of stone S. of the iron post.</p> <p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>The ¼ sec. cor. of secs. 1 and 12, monumented by a quartzite stone, 15 x 10 x 10 ins., firmly set 4 ins. in the ground, mkd. ¼ on N. face, with mound of stone to the S.</p> <p>At the cor. point</p> <p>Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T6N R11E S 1 ¼   S12 1970</p> <p>Rebuild the mound of stone S. of the iron post.</p> <p>Bury the orig. cor. stone in the mound of stone alongside the iron post.</p>

Remonumentation, T. 6 N., R. 11 E., Arizona

CHAINS

The cor. of secs. 2, 3, 10 and 11, monumented by a quartzite stone, 14 x 10 x 8 ins., set 4 ins. in the ground, mkd. 2 notches on E. face and 5 notches on S. face, with mound of stone to the W., from which the orig. bearing trees

A cedar, 45 ins. diam., bears N. 2° E., 41 lks. dist., mkd. T6N R11E S2 BT.

A dead cedar, 36 ins. diam., bears N. 67° W., 197 lks. dist., mkd. T6N R11E S3 BT.

At the cor. point

Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.

T6N R11E  
 $\frac{S\ 3}{S10} | \frac{S\ 2}{S11}$   
 1970

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 2 and 11, monumented by a mound of stone, verified by record course and dist. from an orig. bearing tree

A cedar, 24 ins. diam., bears S. 33° E., 240 lks. dist., mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set the iron post, 4 ins. in the ground, in a mound of stone, brass cap mkd.

T6N R11E  
 $\frac{1}{4} \frac{S\ 2}{S11}$   
 1970

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, monumented by a limestone, 12 x 8 x 6 ins., set 4 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, with mound of stone to the N.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T6N R11E  
 $\frac{1}{4} \frac{S\ 3}{S10}$   
 1970

Bury the orig. cor. stone alongside the iron post.

Cor. is in a four-strand barbed wire fence bearing N. and S.

## Remonumentation, T. 6 N., R. 12 E., Arizona

## CHAINS

Township 6 North, Range 12 East, G&SR M., Arizona

A portion of the subdivisional lines was surveyed in 1907 by J. B. Wright.

Remonumentation, T. 6 N., R. 12 E., Arizona

The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9, monumented by a granite stone, 11 x 6 x 4 ins., firmly set 6 ins. in the ground, mkd.  $\frac{1}{4}$  on N. face, with mound of stone to the N.

Unable to find any evidence of the orig. bearing tree.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T6N R12E

$\frac{1}{4}$

S8|S9

1970

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.



11

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Louis D. Gilbert, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of July, 1970, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 6 North, Ranges 10, 11 and 12 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 2, 1970 (Date) Louis D. Gilbert (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date NOV 16 1970

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 6 North, Ranges 10, 11 and 12 East, all of the Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 21 1973 (Date) Clark F. Murray (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626