



BOOK 4971

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1A

Form 9180-29  
(March 1965)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# INDEX TO SECTION CORNER MONUMENTS

Tp. 30 N. R. 4 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. \_\_\_\_\_ R. \_\_\_\_\_ Mer. \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. \_\_\_\_\_ R. \_\_\_\_\_ Mer. \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 30 North, Range 4 East  
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 1, 1970 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories. The mean magnetic declination is 14½° E.

Township 30 North, Range 4 East, G&SR M., Arizona

The east boundary and a portion of the subdivisional lines were surveyed in 1904 by J. F. Hesse.

Re monumentation, T. 30 N., R. 4 E., Arizona

The cor. of secs. 25, 30, 31 and 36, Tp. 30 N., Rs. 4 and 5 E., monumented by a limestone, 18 x 14 x 10 ins., firmly set 6 ins. in the ground, mkd. 5 notches on N. face and 1 notch on S. face, from which the orig. bearing trees

A pinon, 8 ins. diam., bears N. 23 3/4° E.,  
18 lks. dist., mkd. T30N R5E S30 BT.

A pinon, 8 ins. diam., bears S. 66° E.,  
34 lks. dist., mkd. T30N R5E S31 BT.

A pinon, 10 ins. diam., bears S. 10° W.,  
47 lks. dist., mkd. T30N R4E S36 BT.

A pinon, 8 ins. diam., bears N. 19° W.,  
17 lks. dist., mkd. T30N R4E S25 BT.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T30N  
R4E R5E  
S25 | S30  
S36 | S31  
1970

Bury the orig. cor. stone in the collar of stone alongside the iron post.

Remonumentation, T. 30 N., R. 4 E., Arizona

CHAINS

The cor. of secs. 19, 24, 25 and 30, T. 30 N., Rs. 4 and 5 E., monumented by a limestone, 18 x 12 x 6 ins., firmly set 12 ins. in the ground, mkd. 4 notches on N. face and 2 notches on S. face, from which the orig. bearing trees

A pine, 32 ins. diam., bears N.  $10\frac{1}{2}^{\circ}$  E.,  
220 lks. dist., mkd. with an overgrown blaze.

A pine, 16 ins. diam., bears S.  $86\frac{1}{4}^{\circ}$  E.,  
144 lks. dist., mkd. with an overgrown blaze.

A pine, 30 ins. diam., bears S.  $23^{\circ}$  W.,  
126 lks. dist., mkd. with an overgrown blaze.

A pinon, 10 ins. diam., bears N.  $36^{\circ}$  W.,  
151 lks. dist., mkd. T30N R4E S24 BT.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T30N  
R4E R5E  
S24|S19  
S25|S30  
1970

Raise a mound of stone E. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 25, 26, 35 and 36, monumented by a sandstone, 20 x 10 x 7 ins., firmly set 14 ins. in the ground, mkd. 1 notch on E. face and 1 notch on S. face, from which the orig. bearing trees

A pine, 28 ins. diam., bears N.  $16^{\circ}$  E., 194 lks.  
dist., mkd. with an overgrown blaze.

A pine, 16 ins. diam., bears S.  $16^{\circ}$  E., 167 lks.  
dist., mkd. with an overgrown blaze.

An oak, 12 ins. diam., bears S.  $46\frac{1}{4}^{\circ}$  W., 34 lks.  
dist., mkd. with an overgrown blaze.

A pine, 36 ins. diam., bears N.  $54\frac{1}{2}^{\circ}$  W., 107 lks.  
dist., mkd. T30N R4E S26 BT.

At the cor. point

Set the iron post, 16 ins. in the ground, in a mound  
of stone, brass cap mkd.

T30N R4E  
S26|S25  
S35|S36  
1970

Bury the orig. cor. stone in the mound of stone along-  
side the iron post.

Remonumentation, T. 30 N., R. 4 E., Arizona

CHAINS

The 1/4 sec. cor. of secs. 25 and 36, monumented by a sandstone, 18 x 16 x 7 ins., firmly set 12 ins. in the ground, mkd. 1/4 on N. face, from which the orig. bearing trees

A pine, 28 ins. diam., bears S. 30° E., 11 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears N. 2° W., 30 lks. dist., mkd. S25 BT.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T30N R4E  
 1/4 S25  
 S36  
 1970

Bury the orig. cor. stone alongside the iron post.

The 1/4 sec. cor. of secs. 25 and 26, monumented by a limestone, 18 x 10 x 4 ins., firmly set 12 ins. in the ground, mkd. 1/4 on W. face, from which the orig. bearing trees

A dead oak, 5 ins. diam., bears S. 39° E., 30 lks. dist., mkd. 1/4 S25 BT.

A dead oak, 5 ins. diam., bears N. 30° W., 35 lks. dist., no mks.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T30N R4E  
 1/4  
 S26|S25  
 1970

from which

A juniper, 5 ins. diam., bears N. 68° E., 40 lks. dist., mkd. T30N R4E 1/4 S25 BT.

A pine, 10 ins. diam., bears N. 54° W., 55 lks. dist., mkd. T30N R4E 1/4 S26 BT.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 23, 24, 25 and 26, monumented by a limestone, 18 x 12 x 10 ins., set 4 ins. in the ground, mkd. 1 notch on E. face and 2 notches on S. face, with mound of stone to the W., from which the orig. bearing trees

A juniper, 14 ins. diam., bears N. 57 3/4° E., 89 lks. dist., mkd. T30N R4E S24 BT.

A pine, 18 ins. diam., bears S. 0°30' E., 92 lks. dist., mkd. T30N R4E S25 BT.

Remonumentation, T. 30 N., R. 4 E., Arizona

CHAINS

A pine, 18 ins. diam., bears S. 54 3/4° W.,  
38 lks. dist., mkd. with an overgrown blaze.

A pine, 24 ins. diam., bears N. 58 1/2° W.,  
72 lks. dist., mkd. T30N R4E S23 BT.

At the cor. point

Set the iron post, 6 ins. in the ground, in a mound of  
stone, brass cap mkd.

T30N R4E  
S23|S24  
S26|S25  
1970

Bury the orig. cor. stone in the mound of stone along-  
side the iron post.

The 1/4 sec. cor. of secs. 24 and 25, monumented by a  
sandstone, 16 x 10 x 4 ins., firmly set 10 ins. in the  
ground, mkd. 1/4 on N. face, from which the orig. bearing  
trees

A pinon, 12 ins. diam., bears S. 37° E., 84 lks.  
dist., mkd. 1/4 S25 BT.

A pine, 30 ins. diam., bears N. 29 1/4° W., 224 lks.  
dist., mkd. 1/4 S24 BT.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar  
of stone, brass cap mkd.

T30N R4E  
1/4 S24  
S25  
1970

Bury the orig. cor. stone alongside the iron post.



6

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Louis D. Gilbert, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of July, 1970, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 30 North, Range 4 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 2, 1970

(Date)

*Louis D. Gilbert*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
NOV 16 1970  
Date

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 30 North, Range 4 East, of the Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 21 1973

(Date)

*Clark F. Gurnum*

(Chief, Division of Cadastral Survey)

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626