

1A

BOOK 4976

INDEX DIAGRAM

Township 7 South, Range 17 East,

7	$\frac{1}{2}$ (51) ₆ 49	51 ₅ 48	35 ₄ 34	26 ₃	2	1
6	$\frac{1}{2}$ (50) ₇ 46	47 ₈ 45	33 ₉	10	11	12
5	$\frac{1}{2}$ (47) ₁₈ 42	44 ₁₇ 41	32 ₁₆ 31	15	14	13
4	$\frac{1}{2}$ (43) ₁₉ 39	40 ₂₀ 38	30 ₂₁ 29	25 ₂₂	23	24
3	$\frac{1}{2}$ (40) ₃₀ 22	36 ₂₉ 19	28 ₂₈ 16	23 ₂₇ 13	26	25
1	$\frac{1}{2}$ (23) ₃₁ $\frac{1}{2}$ (21)	20 ₃₂ $\frac{1}{2}$ (21)	17 ₃₃ $\frac{1}{2}$ (19)	14 ₃₄ $\frac{1}{2}$ (16)	12 ₃₅	36
	8	9	10	11		

Township 7 South, Range 17 East
Gila and Salt River Meridian, Arizona

CHAINS

The south and west boundaries were surveyed in 1877 by J. L. Harris. The east and north boundaries and a portion of the subdivisional lines were surveyed and the south and west boundaries were resurveyed in 1905 by J. F. Hesse. The north 5 miles of the east boundary, a portion of the north boundary and a portion of the subdivisional lines were resurveyed, and a portion of the subdivisional lines were surveyed in 1924 by Theo. Vander Meer. A portion of the north boundary was resurveyed in 1928 by W. E. Hiester.

The following field notes are those of a dependent resurvey of the east boundary of Township 7 South, Range 16 East, the west 4 miles of the north boundary of Township 8 South, Range 17 East and a portion of the subdivisional lines of Township 7 South, Range 17 East, designed to restore the corners in their true original location according to the best available evidence.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 26, 1970. The direction of all lines were determined by solar observations and all lines refer to the true meridian.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the corner of sections 2 and 3 only, on the north boundary of Township 8 South, Range 17 East as scaled from the U.S.G.S. Quadrangle Holy Joe Peak, Arizona, scale 1:24000 is: Latitude 32°46'24.3" N. and Longitude 110°35'09.9" W.

The mean magnetic declination was found to be 14° East.

Dependent Resurvey, East Boundary
Township 7 South, Range 16 East

Reestablishment of the Survey executed
by J. F. Hesse in 1905

The cor. of Tps. 7 and 8 S., Rs. 16 and 17 E., monumented by a wooden stake, 1 x 2 x 16 ins., set in the center of a collar of stone 2 lks. N. of an E. and W. fenceline and with a long 2 x 2 in. pole lying alongside. This position is harmoniously related to existing original corners and is accepted as the best remaining evidence of the position of the original cor. There is no remaining evidence of any bearing trees.

At the corner point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T7S
R16E R17E
S36 | S31
S 1 | S 6
T8S
1970

Dependent Resurvey, East Boundary, T. 7 S., R. 16 E.

CHAINS													
	Bury the wooden stake alongside the iron post.												
	N. 0°04' W., along the E. bdy. of sec. 36.												
	Over rolling land, through scattered undergrowth.												
7.70	N. edge of mesa, bears NE. and SW., desc. steep NW. slope.												
13.50	Wash, 150 lks. wide, 8 ft. banks, drains S. 70° W.												
23.00	Spur, slopes SW.												
33.40	Wash, 10 lks. wide, 5 ft. banks, drains SW.												
37.40	Low ridge, bears irreg. E. and W.												
39.55	The ¼ sec. cor. of sec. 36 only, monumented by a malpais stone, 18x10x6 ins., firmly set 10 ins. in the ground, mkd. ¼ on W. face, mound of stone W.; not remonumented.												
	<hr/>												
	N. 0°31' W., beginning new measurement.												
	Over rolling land, through scattered undergrowth.												
3.30	Wash, 10 lks. wide, 5 ft. deep, drains W.												
4.10	Spur, slopes N. 85° W.												
7.40	Wash, 5 lks. wide, 7 ft. banks, drains W. for 2.00 chs., thence SW.												
9.30	Wash, 5 lks. wide, 4 ft. banks, drains S. 80° W.												
16.50	Jeep road, bears N. 82° E. for 2.00 chs. curving NE. and bears S. 82° W. for 1 ch. curving SW.												
24.10	Ravine, drains irreg. S. 75° W.												
28.60	Ravine, drains N. 80° W.												
29.30	Ravine, drains S. 85° W.												
31.80	Ravine, drains SW.												
39.48	The cor. of secs. 25 and 36 only, monumented by a granite stone, 24x16x10 ins., firmly set 15 ins. in the ground, mkd. with 1 notch on S. and 5 notches on N. edges, mound of stone W. There is no remaining evidence of bearing trees.												
	At the corner point												
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.												
	<table border="0"> <tr><td>T7S</td><td> </td></tr> <tr><td>R16E</td><td> </td></tr> <tr><td>S25</td><td> </td></tr> <tr><td><hr/></td><td> </td></tr> <tr><td>S36</td><td> </td></tr> <tr><td>1970</td><td></td></tr> </table>	T7S		R16E		S25		<hr/>		S36		1970	
T7S													
R16E													
S25													
<hr/>													
S36													
1970													
	Bury the orig. cor. stone alongside the iron post.												

Dependent Resurvey, East Boundary, T. 7 S., R. 16 E.

CHAINS											
	<p>Land, rolling. Soil, shallow clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote bush</p>										
	<p>N. 0°37' W., along the E. bdy. of sec. 25. Over rolling land, through scattered undergrowth.</p>										
2.16	The closing cor. of secs. 30 and 31, T. 7 S., R. 17 E., hereinafter described.										
13.40	Enter Zapata Wash area, bears E. and W.										
14.80	Main channel in Zapata Wash, 60 lks. wide, 1 ft. deep, drains S. 85° W.										
17.10	Track road, bears N. 80° E. and S. 80° W.										
18.00	Leave Zapata Wash area, bears irreg. E. and W.										
31.90	Fork of spur, slopes SW. and W.										
40.70	<p>The ¼ sec. cor. of sec. 25 only, monumented by a granite stone, 18x10x8 ins., firmly set 14 ins. in the ground, mkd. ¼ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td> </td></tr> <tr><td>R16E</td><td> </td></tr> <tr><td>¼ S25</td><td> </td></tr> <tr><td>1970</td><td></td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>	T7S		R16E		¼ S25		1970			
T7S											
R16E											
¼ S25											
1970											
	<p>N. 0°14' W., beginning new measurement. Over rolling land, through scattered undergrowth.</p>										
14.20	Gully, 30 lks. wide, 10 ft. banks, drains N. 80° W.										
37.10	Gully, 50 lks. wide, 7 ft. banks, drains S. 75° W.										
40.55	<p>The cor. of secs. 24 and 25 only, monumented by a malpais stone, 18x10x4 ins., firmly set 14 ins. in the ground, mkd. with 2 notches on S. and 4 notches on N. edges, mound of stone W. There is no remaining evidence of bearing trees.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td> </td></tr> <tr><td>R16E</td><td> </td></tr> <tr><td>S24</td><td> </td></tr> <tr><td>S25</td><td> </td></tr> <tr><td>1970</td><td></td></tr> </table> </div>	T7S		R16E		S24		S25		1970	
T7S											
R16E											
S24											
S25											
1970											

Dependent Resurvey, East Boundary, T. 7 S., R. 16 E.

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Build a mound of stone W. of the cor.</p> <p>Land, rolling.</p> <p>Soil, shallow clay loam.</p> <p>Timber, scattered palo verde; (scattered mesquite along major drainages).</p> <p>Undergrowth, scattered creosote bush.</p>
	<p>N. 0°03' E., along the E. bdy. of sec. 24.</p> <p>Over rolling land, through scattered undergrowth.</p>
1.04	Fence, bears E. and W.
1.05	The closing cor. of secs. 19 and 30, T. 7 S., R. 17 E., hereinafter described.
18.10	Small gully, 5 lks. wide, 3 ft. deep, drains W.
25.40	Low ridge, bears S. 80° E. and W.
31.70	Wash, 5 lks. wide, 2 ft. deep, drains N. 35° W.
37.10	Wash, 20 lks. wide, 1 ft. deep, drains N. 75° W.
39.10	Wash, 35 lks. wide, 2 ft. deep, drains W.
39.82	<p>The ¼ sec. cor. of sec. 24 only, monumented by a quartzite stone, 18x8x6 ins., firmly set 14 ins. in the ground, mkd. ¼ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S </p> <p>R16E </p> <p>¼ S24 </p> <p>1970</p> </div>
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
13.90	Low ridge, bears E. and W.
40.04	<p>The cor. of secs. 13 and 24 only, monumented by a granite stone, 18x12x8 ins., firmly set 12 ins. in the ground, mkd. with 3 notches on S. and 3 notches on N. edges, mound of stone W.</p> <p>At the corner point</p>

Dependent Resurvey, East Boundary, T. 7 S., R. 16 E.

CHAINS																												
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td> </td><td></td></tr> <tr><td>R16E</td><td> </td><td></td></tr> <tr><td><u>S13</u></td><td> </td><td></td></tr> <tr><td>S24</td><td> </td><td></td></tr> <tr><td>1970</td><td></td><td></td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde; (scattered mesquite along major washes). Undergrowth, scattered creosote bush and cacti.</p> <hr/> <p>N. 0°10' W., along the E. bdy. of sec. 13.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>1.26 The closing cor. of secs. 18 and 19, T. 7 S., R. 17 E., hereinafter described.</p> <p>1.28 Fence, bears E. and W.</p> <p>8.30 Wash, 10 lks. wide, 2 ft. deep, drains S. 75° W.</p> <p>19.90 Wash, 10 lks. wide, 2 ft. deep, drains W.</p> <p>32.80 Wash, 15 lks. wide, 4 ft. banks, drains S. 80° W.</p> <p>39.93 The ½ sec. cor. of sec. 13 only, monumented by a granite stone, 18x12x4 ins., firmly set 12 ins. in the ground, mkd. ½ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T7S</td><td> </td><td></td></tr> <tr><td>R16E</td><td> </td><td></td></tr> <tr><td>½ S13</td><td> </td><td></td></tr> <tr><td>1970</td><td></td><td></td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <hr/> <p>N. 0°07' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>5.60 Jeep road, on a low ridge, bears SE. and NW.</p> <p>19.40 Gully, with 10 ft. walls, drains NW.</p> <p>26.20 Wash, 30 lks. wide, 1 ft. deep, drains W. for 3.00 chs., curving to NW.</p>	T7S			R16E			<u>S13</u>			S24			1970			T7S			R16E			½ S13			1970		
T7S																												
R16E																												
<u>S13</u>																												
S24																												
1970																												
T7S																												
R16E																												
½ S13																												
1970																												

Dependent Resurvey, East Boundary, T. 7 S., R. 16 E.

CHAINS	
39.82	<p>The cor. of secs. 12 and 13 only, monumented by a malpais stone, 24x12x10 ins., firmly set 18 ins. in the ground, mkd. with 4 notches on S. and 2 notches on N. edges, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R16E <u>S12</u> S13 1970</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <p>Land, rolling. Soil, clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush.</p>
	<p>N. 0°32' W., along the E. bdy. of sec. 12.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
1.90	<p>Gully, 25 lks. wide, 6 ft. banks, drains N. 70° W. from N. 70° E.</p>
9.10	<p>Wash, 15 lks. wide, 4 ft. banks, drains S. 80° W.</p>
32.80	<p>Spur, slopes SW.</p>
37.50	<p>S. rim above Aravaipa Creek, bears N. 60° E. and S. 60° W., desc. steep NW. slope.</p>
39.80	<p>Spur, slopes NW., curving to N. 10° W.</p>
40.09	<p>Point for the ½ sec. cor. of sec. 12 only, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R16E ½ S12 1970</p> </div>
	<p>N. 0°05' W., beginning new measurement.</p>
	<p>Desc. steep NW. slope.</p>
13.20	<p>Bottom of slope, bears N. 80° E. and S. 80° W., thence over Aravaipa Creek bottom land.</p>
19.90	<p>Aravaipa Creek, 60 lks. wide, with flowing water, course N. 75° W., curving to SW.</p>

Dependent Resurvey, East Boundary, T. 7 S., R. 16 E.

CHAINS									
23.10	Fence, bears irreg. E. and W.								
29.80	Jeep road, bears irreg. E. and W.								
39.10	Abandoned fence line, with wires lying on the ground, bears irreg. E. and W.								
39.84	Point for the cor. of secs. 1 and 12 only, at proportionate dist.; there is no remaining evidence of the orig. cor. Not monumented.								
	Land, rolling to nearly level. Soil, rocky clay loam, (sandy loam in Aravaipa Creek bottom land). Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush.								
	N. 0°03' W., along the E. bdy. of sec. 1. Over Aravaipa Creek bottom land, through scattered mesquite.								
6.90	Fence, bears irreg. E. and W., asc. steep S. slope.								
11.80	S. rim of mesa, bears E. and W.								
39.90	The $\frac{1}{4}$ sec. cor. of sec. 1 only, monumented by a granite stone, 18x10x5 ins., firmly set 14 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.								
	At the corner point Set the iron post 22 ins. in the ground, brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="text-align: center;">T7S</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="text-align: center;">R16E</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="text-align: center;">$\frac{1}{4}$ S 1</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="text-align: center;">1970</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> </table>	T7S		R16E		$\frac{1}{4}$ S 1		1970	
T7S									
R16E									
$\frac{1}{4}$ S 1									
1970									
	Bury the orig. cor. stone alongside the iron post. Build a mound of stone W. of the cor.								
	N. 0°34' W., beginning new measurement. Over gently rolling land, through scattered undergrowth.								
3.50	Aravaipa Road, bears N. 78° E. and S. 78° W.								
14.00	Power line, bears S. 70°20' E. and N. 70°20' W.; track road underneath power line.								
30.40	Wash, 20 lks. wide, 1 ft. deep, drains W.								
39.84	The cor. of Tps. 6 and 7 S., R. 16 and 17 E., monumented by a granite stone, 14x12x8 ins., firmly set 7 ins. in the ground, mkd. with 6 notches on N. edge, 6 notches on E. edge, 17E on SE. face, 6 notches on S. edge, 7S on SW. face, 6 notches on W. edge and 16E on NW. face, mound of stone S.								

Dependent Resurvey, East Boundary, T. 7 S., R. 16 E.

CHAINS

At the corner point

Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.

T6S
R16E | R17E
S36 | S31
S 1 | S 6
T7S
1970

Bury the orig. cor. stone in the mound alongside the iron post.

Land, rolling to gently rolling.
Soil, rocky clay loam, (sandy loam in Aravaipa Creek bottom land).
Timber, scattered palo verde and mesquite.
Undergrowth, scattered creosote bush and cacti.

Dependent Resurvey, Portion North Boundary
Township 8 South, Range 17 East

Reestablishment of the Survey executed
by J. F. Hesse in 1905

From the cor. of Tps. 7 and 8 S., R. 16 and 17 E.

N. 89°50' E., along the N. bdy. of sec. 6.

Over rolling land, through moderate undergrowth.

- 3.00 Wash, 5 lks. wide, 1 ft. deep, drains SW.
- 4.00 Wash, 10 lks. wide, 1 ft. deep, drains SW.
- 14.80 Wash, 5 lks. wide, 1 ft. deep, drains S. 30° W.
- 35.60 Spur, slopes S. 20° W.
- 36.40 Wash, 15 lks. wide, 5 ft. banks, drains S. 10° W.
- 39.13 The ¼ sec. cor. of sec. 6 only, monumented by a granite stone, 18x12x6 ins., firmly set 15 ins. in the ground, dimly mkd. ¼ on N. face, mound of stone N.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

¼ S 6
T8S R17E
1970

Bury the orig. cor. stone alongside the iron post.

Dependent Resurvey, Portion North Boundary, T. 8 S., R. 17 E.

CHAINS	
	<p>The cor. is located 70 lks. N. of a fence bearing irreg. E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>East, beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
17.80	Track road, bears irreg. N. and S.
34.40	Wash, 10 lks. wide, 2 ft. deep, drains S. 15° W.
39.00	Same wash, 15 lks. wide, 1 ft. deep, drains N. 80° W., curving S.
40.22	<p>The cor. of secs. 5 and 6 only, monumented by a granite stone, 20x15x10 ins., firmly set 12 ins. in the ground, mkd. with 5 notches on E. and 1 notch on W. edges. There is no remaining evidence of the bearing trees.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} T7S \\ S 32 \\ \hline S6 S 5 \\ T8S R17E \\ 1970 \end{array}$ </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 5 lks. N. of a fence bearing irreg. E. and W.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>N. 89°41' E., along the N. bdy. of sec. 5.</p> <p>Over rolling land, through scattered undergrowth.</p>
0.60	Fence, bears irreg. E. and W.
27.50	Wash, 15 lks. wide, 2 ft. deep, drains SW.
39.94	<p>The 1/4 sec. cor. of sec. 5 only, monumented by a granite stone, 15x11x9 ins., firmly set 10 ins. in the ground, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{r} \frac{1}{4} S 5 \\ T8S R17E \\ 1970 \end{array}$ </div>

Dependent Resurvey, Portion North Boundary, T. 8 S., R. 17 E.

CHAINS												
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 51 lks. S. of a fence bearing irreg. E. and W.</p> <hr/> <p>N. 89°55' E., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>											
25.20	Wash, 25 lks. wide, 1 ft. deep, drains S.											
30.80	Wash, 110 lks. wide, 2 ft. deep, drains S. 10° W.											
34.39	The closing cor. of secs. 32 and 33, T. 7 S., R. 17 E., hereinafter described.											
37.70	Wash, 30 lks. wide, 1 ft. deep, drains S. 20° W.											
39.91	<p>The cor. of secs. 4 and 5 only, monumented by a granite stone, 22x10x9 ins., firmly set 17 ins. in the ground, mkd. with 4 notches on E. and 2 notches on W. edges, and with a 3/4 in. water pipe projecting 2½ ft. above the ground along the N. side of the cor. stone, mound of stone to E. and to W.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td colspan="2">T7S</td></tr> <tr><td colspan="2">S 33</td></tr> <tr><td>S 5</td><td>S 4</td></tr> <tr><td>T8S</td><td>R17E</td></tr> <tr><td colspan="2">1970</td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post. Set the water pipe alongside the iron post. Build a mound of stone S. of the cor.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>	T7S		S 33		S 5	S 4	T8S	R17E	1970		
T7S												
S 33												
S 5	S 4											
T8S	R17E											
1970												
	<p>N. 89°59' E., along the N. bdy. of sec. 4.</p> <p>Over rolling land, through scattered undergrowth.</p>											
5.60	Ravine, drains NW.											
30.90	Wash, 10 lks. wide, 2 ft. deep, drains S. 85° W.											
39.96	<p>The ¼ sec. cor. of sec. 4 only, monumented by a granite stone, 20x10x6 ins., firmly set 14 ins. in the ground, mkd. ¼ on N. face, mound of stone N.; not remonumented.</p> <p>The cor. is located 3 lks. W. of a cor. of fences extending E. and S. 75° W.</p> <hr/>											

Dependent Resurvey, Portion North Boundary, T. 8 S., R. 17 E.

CHAINS	
	S. 89°32' E., beginning new measurement.
	Over rolling land, through scattered undergrowth.
34.72	The closing cor. of secs. 33 and 34, T. 7 S., R. 17 E., hereinafter described.
39.25	The cor. of secs. 3 and 4 only, monumented by a granite stone, 10x6 ins., projecting 9 ins. above ground, mkd. with 3 notches on W. edge only. There is no remaining evidence of the bearing trees; not remonumented.
	The cor. is located 10.5 lks. S. of a fence bearing irreg. E. and W.
	Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.
	S. 89°49' E., along the N. bdy. of sec. 3.
	Over rolling land, through scattered undergrowth.
40.00	The ½ sec. cor. of sec. 3 only, monumented by a granite stone, 14x8 ins., projecting 10 ins. above ground, mkd. ½ on N. face, mound of stone S.; not remonumented.
	The cor. is located 50 lks. S. of a fence bearing irreg. E. and W.
	S. 89°45' E., beginning new measurement.
	Over rolling land, through scattered undergrowth.
4.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° W.
18.90	Wash in W. side of Dry Camp Canyon, 90 lks. wide, 2 ft. deep, drains S. 17° W.
21.00	Wash in E. side of Dry Camp Canyon, 50 lks. wide, 2 ft. deep, drains S. 15° W.
32.60	Spur, slopes SW.
35.55	Fence, bears irreg. S. and N. to a cor. of fences bearing irreg. S. and W.
35.67	The closing cor. of secs. 34 and 35, T. 7 S., R. 17 E., hereinafter described.
38.35	Wash, 5 lks. wide, 2 ft. deep, drains SW.
39.61	The cor. of secs. 2 and 3 only, monumented by a granite stone, 10x4 ins., projecting 5 ins. above ground, mkd. with 2 notches on E. and 4 notches on W. edges, mound of stone N.; not remonumented.
	Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

Dependent Resurvey, Portion Subdivisional Lines
Township 7 South, Range 17 East

Reestablishment of the Surveys executed
by J. F. Hesse in 1905
and
Theo. Vander Meer in 1924

Beginning at the cor. of secs. 26, 27, 34 and 35, monumented by a granite stone, 18x12x8 ins., firmly set, mkd. with 2 grooves on E. and 1 groove on S. faces, mound of stone W.

At the corner point

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T7S R17E	
S27	S26
S34	S35
1970	

Bury the orig. cor. stone alongside the iron post.

Rebuild the mound of stone W. of the cor.

S. 0°01' W., bet. secs. 34 and 35.

Over rolling land, through scattered undergrowth.

- 1.10 Jeep road, bears N. 85° E. and S. 85° W.
- 5.40 Wash, 20 lks. wide, 2 ft. deep, drains S. 75° W.
- 8.40 Spur, slopes S. 85° W.
- 11.80 Wash, 30 lks. wide, 1 ft. deep, drains N. 80° W.
- 16.60 Low ridge, bears S. 85° E. and N. 85° W.
- 22.30 Wash, 5 lks. wide, 1 ft. deep, drains S. 80° W.
- 23.40 Spur, slopes W.
- 25.00 Wash, 10 lks. wide, 1 ft. deep, drains W.
- 28.50 Spur, slopes N. 75° W.
- 32.00 Wash, 5 lks. wide, 2 ft. deep, drains NW.
- 34.80 Ridge, bears S. 80° E. and N. 80° W.
- 39.76 Wash, 5 lks. wide, 1 ft. deep, drains irreg. S. 55° W.
- 39.94 Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{4}$ S34 S35 1970</p>
43.40	Spur, slopes W.
59.10	Wash, 40 lks. wide, 2 ft. deep, drains S. 35° W.
63.80	Wash in Dry Camp Canyon, 30 lks. wide, 3 ft. deep, drains S. 75° W.
69.80	Spur, slopes S. 55° W.
72.20	Wash, 5 lks. wide, 1 ft. deep, drains S. 75° W.
79.70	Spur, slopes S. 85° W.
80.46	Fence cor., with fences extending irreg. S. and W.
81.46	<p>The closing cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented by a granite stone, 18x8x5 ins., firmly set 12 ins. in the ground, mkd. with 2 grooves on E. and 4 grooves on W. faces and with C C on N. face. There is no remaining evidence of the bearing trees.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E C C S34 S35 S3 T8S 1970</p> <p>from which</p> <p style="padding-left: 40px;">The cor. of secs. 2 and 3 only, on the N. bdy. of T. 8 S., R. 17 E., bears S. 89°45' E., 3.94 chs. dist., previously described.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered to moderate palo verde. Undergrowth, creosote bush and cacti.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°55' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through scattered undergrowth.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
18.70	Wash, 20 lks. wide, 1 ft. deep, drains NW. from N. 70° E.
20.90	Jeep road, bears irreg. S. 75° E. and N. 75° W.
25.10	Same road, bears NE. and SW.
27.40	Same road, bears S. 65° E. and N. 65° W.
35.70	Wash, 5 lks. wide, 1 ft. deep, drains S. 10° W.
40.20	<p>The ¼ sec. cor. of secs. 27 and 34, monumented by a granite stone, 14x10x6 ins., firmly set 11 ins. in the ground, mkd. ¼ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E ¼ $\frac{S\ 27}{S\ 34}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
29.70	Wash, 110 lks. wide, 1 ft. deep, drains S. 50° W.
40.17	<p>True point for the cor. of secs. 27, 28, 33 and 34, determined from 2 orig. witness cors., hereinafter described, falls in a wash area, 100 lks. wide, 1 ft. deep, draining S. 80° W. from S. 80° E.; not monumented.</p> <p>The true point for the cor. is located 4 lks. E. of a fence bearing N. and S.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p> <hr/> <p>From the true point for the cor. of secs. 27, 28, 33 and 34.</p> <p>South, bet. secs. 33 and 34.</p> <p>Over rolling land, through scattered undergrowth.</p>
3.20	Wash, 40 lks. wide, 1 ft. deep, drains N. 85° W.
15.40	Wash, 5 lks. wide, 1 ft. deep, drains S. 80° W.
17.50	Spur, slopes W.
20.50	Wash, 10 lks. wide, 1 ft. deep, drains N. 75° W.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
26.00	Low ridge, bears irreg. E. and W.
30.52	Fence cor., with fences extending N. and W. and an abandoned fence line extending S.
32.40	Wash, 60 lks. wide, 1 ft. deep, drains S. 80° W.
40.00	The ¼ sec. cor. of secs. 33 and 34, monumented by a granite stone, 18x8x6 ins., firmly set 16 ins. in the ground, mkd. with ¼ on W. face, mound of stone W.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T7S R17E ¼ S33 S34 1970</p>
	Bury the orig. cor. stone alongside the iron post.
	Rebuild the mound of stone W. of the cor.
	The cor. is located in an abandoned fenceline bearing N. and S.
	<hr style="width: 20%; margin: 10px auto;"/>
	S. 0°01' E., beginning new measurement.
	Over rolling land, through scattered undergrowth.
14.10	Wash, 20 lks. wide, 2 ft. deep, drains irreg. W.
33.20	Wash, 15 lks. wide, 2 ft. deep, drains N. 85° W.
41.10	The closing cor. of secs. 33 and 34, on the S. bdy. of the Tp., monumented by a granite stone, 16x12x6 ins., loosely set, mkd. with 3 grooves on W. face, no other mks. visible. There is no remaining evidence of bearing trees.
	At the corner point
	Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T7S R17E C C S33 S34 S 4 T8S 1970</p>
	from which
	The cor. of secs. 3 and 4 only, on the N. bdy. of T. 8 S., R. 17 E., bears S. 89°32' E., 4.53 chs. dist., previously described.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 1.5 lks. N. of a fence bearing irreg. E. and W.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>The point for the S. $\frac{1}{4}$ sec. cor. of sec. 34 is on the S. bdy. of the Tp. and at midpoint bet. the closing cors.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R17E $\frac{1}{4}$ S 34</p> <hr style="width: 50px; margin: auto;"/> <p>1970</p> </div> <p>from which</p> <p style="padding-left: 40px;">The N. $\frac{1}{4}$ sec. cor. of sec. 3 only, T. 8 S., R. 17 E., bears S. 89°49' E., 4.43 chs. dist., previously described.</p>
	<p>From the true point for the cor. of secs. 27, 28, 33 and 34, previously described.</p> <p>West, bet. secs. 28 and 33.</p>
0.04	<p>Fence, bears irreg. N. and S.</p> <p>Over rolling land, through scattered undergrowth.</p>
2.00	<p>A witness cor. of secs. 27, 28, 33 and 34, monumented by a granite stone, 18x12x7 ins., firmly set 12 ins. in the ground, mkd. with 3 notches on E. and 1 notch on S. edges and with W C on E. face, mound of stone W.</p> <p>At the witness cor. point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R17E S28 S27 WC $\xrightarrow{\quad}$ S33 S34</p> <hr style="width: 50px; margin: auto;"/> <p>1970</p> </div>
14.90	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <p>Wash, 60 lks. wide, 2 ft. deep, drains N. 60° W.</p>
35.30	<p>Low ridge, bears SE. and NW.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
40.16	True point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate dist., falls in small wash draining SW.; not monumented.
40.66	The witness $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented by a malpais stone, 16x14x6 ins., set 2 ins. in the ground and in a collar of stone, mkd. WC $\frac{1}{4}$ on N. face.
	At the witness cor. point
	Set the iron post 2 ins. in the ground over an X chiseled on bedrock, mound of stone to top, brass cap mkd.
	<p>T7S R17E WC $\frac{1}{4}$ $\frac{S\ 28}{S\ 33}$ → 1970</p>
	Bury the orig. cor. stone alongside the iron post.
	<hr style="width: 20%; margin: auto;"/> <p>S. 89°59' W., beginning new measurement.</p>
	Over rolling land, through scattered undergrowth.
17.50	Wash, 30 lks. wide, 1 ft. deep, drains W. from S., curving E.; thence along S. side of wash.
21.50	Same wash, drains N. 70° W., curving N.
39.66	The cor. of secs. 28, 29, 32 and 33, monumented by a sandstone, 16x12x4 ins., firmly set 11 ins. in the ground, mkd. with 1 notch on S. and 4 notches on E. edges, mound of stone W.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T7S R17E S29 S28 S32 S33 1970</p>
	Bury the orig. cor. stone alongside the iron post.
	Rebuild the mound of stone W. of the cor.
	Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.
6.80	S. 0°02' E., bet. secs. 32 and 33.
	Over rolling land, through scattered undergrowth.
	Low ridge, bears E. and W.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

- 13.00 Wash, 15 lks. wide, 2 ft. deep, drains S. 80° W.
- 28.00 Wash, 15 lks. wide, 4 ft. banks, drains irreg. W.
- 39.93 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented by a granite stone, 18x8x6 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, mound of stone W.
- At the cor. point
- Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
- T7S R17E
 $\frac{1}{4}$
 S32 | S33
 1970
- Bury the orig. cor. stone alongside the iron post.
- Build a mound of stone W. of the cor.
-
- S. 0°04' E., beginning new measurement.
- Over rolling land, through scattered undergrowth.
- 5.80 Wash, 10 lks. wide, 1 ft. deep, drains S. 70° W., curving S.
- 11.40 Wash, 10 lks. wide, 1 ft. deep, drains N. 80° W.
- 34.70 Fence, bears N. 55° E. and S. 55° W..
- 37.80 Wash, 20 lks. wide, with 6 ft. banks, drains SW.
- 40.10 Spur, slopes W.
- 40.91 The closing cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented by a granite stone, 18x10x4 ins., firmly set 12 ins. in the ground, mkd. with 4 grooves on the E. face and C C on N. face, no other mks. visible, mound of stone N.
- At the corner point
- Set the iron post 24 ins. in the ground, brass cap mkd.
- T7S R17E
 C C
 S32 | S33
 S 5
 T8S
 1970
- from which
- The cor. of secs. 4 and 5 only, on the N. bdy. of Tp. 8 S., R. 17 E., bears N. 89°55' E., 5.52 chs. dist., previously described.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

Bury the orig. cor. stone alongside the iron post.

Rebuild the mound of stone N. of the cor.

Land, rolling.

Soil, rocky clay loam.

Timber, scattered palo verde and mesquite.

Undergrowth, scattered creosote bush and cacti.

The point for the S. $\frac{1}{4}$ sec. cor. of sec. 33, is on the S. bdy. of the Tp. and at midpoint bet. the closing cors.

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R17E

$\frac{1}{4}$ S 33

1970

from which

The N. $\frac{1}{4}$ sec. cor. of sec. 4 only, on the N. bdy. of T. 8 S., R. 17 E., bears N. $89^{\circ}59'$ E., 5.38 chs. dist.

From the cor. of secs. 28, 29, 32 and 33.

N. $89^{\circ}57'$ W., bet. secs. 29 and 32.

Over rolling land, through scattered undergrowth.

1.70 Wash, 30 lks. wide, with 3 ft. banks, drains S. 5° W. from NE.

4.40 Spur, slopes S.

5.90 Same wash as above, 20 lks. wide, 2 ft. deep, drains NW., curving W.

11.90 Spur, slopes NW.

15.50 Same wash as above, 20 lks. wide, 2 ft. deep, drains SW.

40.02 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented by a granite stone, 15x12x6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on N. face. There is no remaining evidence of the bearing trees.

At the corner point

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R17E

$\frac{1}{4}$ S 29
S 32

1970

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

Bury the orig. cor. stone alongside the iron post.

N. 89°57' W., beginning new measurement.

Over rolling land, through scattered undergrowth.

26.00 Low ridge, bears N. 80° E. and S. 80° W.

40.15 The cor. of secs. 29, 30, 31 and 32, monumented by a granite stone, 15x12x10 ins., firmly set 10 ins. in the ground, mkd. with 5 notches on E. and 1 notch on S. edges, mound of stone W.

At the corner point

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T7S R17E
 S30|S29
 S31|S32
 1970

Bury the orig. cor. stone alongside the iron post.

Rebuild the mound of stone W. of the cor.

Land, rolling.

Soil, rocky clay loam.

Timber, scattered palo verde and mesquite.

Undergrowth, scattered creosote bush and cacti.

S. 0°03' W., bet. secs. 31 and 32.

Over mesa land, through scattered undergrowth.

6.90 Leave mesa, bears N. 65° E. and S. 80° W., desc. S. slope.

32.50 Wash, 50 lks. wide, 2 ft. deep, drains S. 80° W.

39.70 The witness ¼ sec. cor. of secs. 31 and 32, monumented by a granite stone, 26x12x12 ins., firmly set 14 ins. in the ground, mkd. W ¼ C on W. face, mound of stone W.

At the witness corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T7S R17E
 W C
 ¼
 S31|S32
 ↓
 1970

Bury the orig. cor. stone alongside the iron post.

Rebuild the mound of stone W. of the cor.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

S. 0°01' W., beginning new measurement.


Over rolling land, through scattered undergrowth.

0.50 True point for the ¼ sec. cor. of secs. 31 and 32 falls in a small wash draining NW.; not monumented.

40.50 Wash, 10 lks. wide, 3 ft. banks, drains S. 85° W.

41.47 Point for the closing cor. of secs. 31 and 32, on the S. bdy. of the Tp., at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.



from which

The cor. of secs. 5 and 6 only, on the N. bdy. of Tp. 8 S., R. 17 E., bears East, 5.92 chs. dist.

Land, rolling.
Soil, rocky clay loam.
Timber, scattered palo verde and mesquite.
Undergrowth, scattered creosote bush and cacti.


The point for the S. ¼ sec. cor. of sec. 32, is on the S. bdy. of the Tp. and at midpoint bet. the closing cors.; not monumented.

from which

The N. ¼ sec. cor. of sec. 5 only, T. 8 S., R. 17 E., bears N. 89°41' E., 5.735 chs. dist., previously described.

The point for the S. ¼ sec. cor. of sec. 31, is on the S. bdy. of the Tp. and at 40.00 chs. in westing from the closing cor. of secs. 31 and 32.

Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.



from which

The N. ¼ sec. cor. of sec. 6 only, T. 8 S., R. 17 E., bears N. 89°50' E., 5.70 chs. dist.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	From the cor. of secs. 29, 30, 31 and 32.
	S. 89°51' W., bet. secs. 30 and 31.
	Over rolling land, through scattered undergrowth.
13.80	Spur, slopes S. 70° W.
16.80	Wash, 5 lks. wide, 2 ft. deep, drains SW.
21.60	Spur, slopes south.
40.08	The ¼ sec. cor. of secs. 30 and 31, monumented by a malpais stone, 18x10x6 ins., firmly set 12 ins. in the ground, in a collar of stone, mkd. with ¼ on N. face, mound of stone N.
	At the cor. point
	Set the iron post 16 ins. in the ground, in a collar of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R17E $\frac{1}{4}$ $\frac{S30}{S31}$ 1970</p>
	Bury the orig. cor. stone alongside the iron post.
	Rebuild the mound of stone N. of the cor.
	<hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">S. 89°52' W., beginning new measurement.</p>
	Over rolling land, through scattered undergrowth.
10.60	Wash, 10 lks. wide, 3 ft. deep, drains S. 75° W.
33.82	The closing cor. of secs. 30 and 31 only, on the W. bdy. of the Tp., monumented by a granite stone, 18x10x5 ins., firmly set 12 ins. in the ground, mkd. with CC on E. face and 5 grooves on N. and 1 groove on S. faces, mound of stone E.
	At the cor. point
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R17E $\frac{S30}{S31}$ C 1970</p>
	from which
	<p style="text-align: center;">The cor. of secs. 25 and 36 only, T. 7 S., R. 16 E., bears S. 0°37' E., 2.16 chs. dist., previously described.</p>
	Bury the orig. cor. stone alongside the iron post.

. Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

Rebuild the mound of stone E. of the cor.

Land, rolling.

Soil, rocky clay loam.

Timber, scattered palo verde and mesquite

Undergrowth, scattered creosote bush and cacti.

The point for the W. $\frac{1}{2}$ sec. cor. of sec. 31 only, is at proportionate dist., using 40.00 chs. in southing from the point for the closing cor. of secs. 30 and 31.

Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.

T7S	
R17E	
$\frac{1}{2}$	
S31	
	1970

from which

The E. $\frac{1}{2}$ sec. cor. of sec. 36 only, on the E. bdy. of T. 7 S., R. 16 E., bears S. $0^{\circ}31'$ E., 1.61 chs. dist., previously described.

From the true point for the cor. of secs. 27, 28, 33 and 34, previously described.

N. $0^{\circ}01'$ W., along the E. bdy. of sec. 28.

Over rolling land, through scattered undergrowth.

1.18 A witness cor. of secs. 27, 28, 33 and 34, monumented by a granite stone, 16x12x6 ins., firmly set 10 ins. in the ground, mkd. with 1 notch on S. and 3 notches on E. edges, and with W C on E. face, mound of stone W.

At the witness cor. point

Set the iron post 22 ins. in the ground, brass cap mkd.

T7S	R17E
W C	
<u>S28</u>	<u>S27</u>
S33	S34
	1970

Bury the orig. cor. stone alongside the iron post.

Rebuild the mound of stone W. of the iron post.

The witness cor. is located under a fence bearing irreg. N. and S.

31.20 Wash, 40 lks. wide, 1 ft. deep, drains S. 50° W.

Dep..Res., Portion Subdivisional Lines, T..7 S., R. 17 E.

CHAINS	
39.00	Wash, 20 lks. wide, 1 ft. deep, drains W.
39.96	<p>The $\frac{1}{4}$ sec. cor. of sec. 27 only, monumented by an iron post, 1 in. diam., projecting 12 ins. above ground, mound of stone N., brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S27 1924 </div> <p>The cor. is located under a fence bearing N. and S.</p>
40.12	<p>The $\frac{1}{4}$ sec. cor. of sec. 28 only, monumented by a granite stone, 12x10x5 ins., firmly set 8 ins. in the ground, mkd. with $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> T7S R17E $\frac{1}{4}$ S28 1970 </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <p>The cor. is located under a fence bearing N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
13.70	Wash, 15 lks. wide, 1 ft. deep, drains N. 75° W.
21.40	Wash, 45 lks. wide, 2 ft. deep, drains W.
25.60	Zapata Wash, 3.00 chs. wide, 1 ft. deep, drains S. 30° W.; track road in same wash, bears N. 30° E. and S. 30° W.
39.68	<p>Fall 10.4 lks. W. of the closing cor. of secs. 22 and 27 only, monumented by an iron post 2 ins. diam., projecting 15 ins. above ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> T7S R17E S28 $\frac{S22}{S27}$ C C 1924 </div> <p>The cor. is located under a fence bearing N. and S.</p>
40.19	<p>The cor. of secs. 21 and 28 only, monumented by a granite stone, 18x10x8 ins., firmly set 12 ins. in the ground, mkd. with 2 notches on S. and 3 notches on E. edges, mound of stone W.</p> <p>At the cor. point</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;"> T7S R17E S21 S22 S28 1970 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <p>The cor. is located under a fence bearing E. and W.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
<p>17.40</p> <p>26.00</p> <p>29.00</p> <p>38.30</p> <p>39.39</p> <p>40.07</p>	<p>N. 0°04' W., along the E. bdy. of sec. 21.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>Wash, 15 lks. wide, 2 ft. deep, drains W.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains N. 85° W.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains W.</p> <p>The ¼ sec. cor. of sec. 22 only, monumented by an iron post, 1 in. diam., set in a collar of stone to top, mound of stone E., brass cap mkd.</p> <p style="text-align: center;"> ¼ S22 1924 </p> <p>The cor. is located 1.5 lks. E. of a fence bearing N. and S.</p> <p>The ¼ sec. cor. of sec. 21 only, monumented by a granite stone, 18x8x6 ins., firmly set 12 ins. in the ground, mkd. with ¼ on W. face.</p> <p>At the cor. point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;"> T7S R17E ¼ S21 1970 </p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Build a mound of stone W. of the cor.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>The cor. is located 2 lks. E. of a fence bearing N. and S.</p>
	<p>N. 0°04' W., beginning new measurement.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
8.20	<p>Wash, 10 lks. wide, 1 ft. deep, drains S. 80° W.</p>
19.80	<p>Wash, 30 lks. wide, 1 ft. deep, drains N. 75° W.</p>
23.40	<p>Wash, 50 lks. wide, 1 ft. deep, drains S. 70° W.</p>
33.00	<p>Wash, 50 lks. wide, 1 ft. deep, drains S. 60° W.</p>
39.24	<p>The closing cor. of secs. 15 and 22 only, monumented by an iron post, 2 ins. diam., projecting 12 ins. above the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T7S R17E S21 S15 C C S22 1924</p>
	<p>The cor. is located under a fence bearing N. and S.</p>
40.04	<p>The cor. of secs. 16 and 21 only, monumented by a granite stone, 24x10x10 ins., firmly set 6 ins. in the ground, mkd. with 7S on NE. and 17E on SE. faces; and with 3 notches on S. and E. edges, mound of stone W.</p>
	<p>At the cor. point</p>
	<p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R17E S16 S15 S21 1970</p>
	<p>Bury the orig. cor. stone alongside the iron post.</p>
	<p>The cor. is located at a cor. of fences extending E., S. and W.</p>
	<p>Land, rolling.</p>
	<p>Soil, rocky clay loam.</p>
	<p>Timber, scattered palo verde and mesquite.</p>
	<p>Undergrowth, scattered creosote bush and cacti.</p>
	<p>The cor. of secs. 4 and 9 only, monumented by a granite stone, 14x12 ins., firmly set with 14 ins. projecting above ground, mkd. with 3 notches on E. and 5 notches on S. edges, mound of stone SE.; not remonumented.</p>
	<p>from which</p>
	<p>The closing cor. of secs. 3 and 10 only, monumented by an iron post 2 ins. diam., projecting 10 ins. above ground, mound of stone E., bears S. 0°02' W., 99 lks. dist., brass cap mkd.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p style="text-align: center;">T7S R17E S. 9 S 3 CC S10 1924</p> <p>N. 0° 03' E., along the E. bdy. of sec. 4.</p> <p>Over rolling and mountainous land, through scattered undergrowth.</p>
19.10	Wash, 15 lks. wide, 1 ft. deep, drains N. 80° W.
26.20	Spur, slopes NW.
30.10	Wash, 110 lks. wide, 1 ft. deep, drains N. 60° W.
38.85	From this point the W., ¼ sec. cor. of sec. 3 bears West, 3.5 lks. dist., monumented by an iron post, 1 in. diam., projecting 9 ins. above ground, and in a collar of stone, brass cap mkd.
	<p> ¼ S 3 1924</p>
39.94	Point for the E. ¼ sec. cor. of sec. 4 at broken-boundary proportionate measurement; there is no remaining evidence of the orig. cor.; not monumented.
	<hr style="width: 20%; margin: 0 auto;"/>
	<p>N. 0° 06' W., beginning new measurement.</p> <p>Over mountainous land, through scattered undergrowth.</p>
6.90	Spur, slopes NW, desc. steep N. slope.
12.20	Base of steep slope, bears E. and W.; enter Aravaipa Creek bottom land.
17.90	Aravaipa Creek, 80 lks. wide, with flowing water, 2 ft. deep, course W., curving SW.
18.90	Stone and wire revetment, bears E. and W.; leave Aravaipa Creek bottom land, thence over rolling land.
22.00	Aravaipa Road, bears N. 80° E. and SW.
30.50	Power line, bears N. 30° E. and S. 30° W.
38.82	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., projecting 16 ins. above ground and in a mound of stone, brass cap mkd.
	<p>T6S R17E S33 S34 S 4 S 3 T7S 1924</p>
	<p>Land, rolling and mountainous.</p> <p>Soil, rocky clay loam, except for the Aravaipa Creek bottom land which is a sandy loam.</p> <p>Timber, scattered palo verde and mesquite.</p> <p>Undergrowth, scattered creosote bush and cacti.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	From the cor. of secs. 28, 29, 32, and 33.
	N. 0° 03' W., bet. secs. 28 and 29.
	Over rolling land, through scattered undergrowth.
2.90	Wash, 25 lks. wide, 1 ft. deep, drains SW. from E.
4.20	Spur, slopes SW.
14.80	Wash, 25 lks. wide, 1 ft. deep, drains N. 80° W.
20.30	Wash, 100 lks. wide, 1 ft. deep, drains W. for 3.00 chs., curving to S. 75° W.
26.30	Zapata Wash, 150 lks. wide, 2 ft. deep, drains S. 80° W., track road follows along wash bottom.
36.00	Track road, bears irreg. E. and W.
40.17	The ¼ sec. cor. of secs. 28 and 29, monumented by a granite stone, 16x14x6 ins., firmly set 10 ins. in the ground, mkd. with ¼ on W. face.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T7S R17E ¼ S29 S28 1970
	Bury the orig. cor. stone alongside the iron post.
	Build a mound of stone W. of the cor.

	N. 0° 03' E., beginning new measurement.
	Over rolling land, through scattered undergrowth.
7.00	Track road, bears SE. curving E. and NW. curving W.
12.00	Wash, 5 lks. wide, 1 ft. deep, drains NW. for 5.00 chs., thence irreg. W.
14.10	Jeep road, bears N. 80° E. and W., curving NW.
18.30	Wash, 15 lks. wide, with 3 ft. banks, drains SW.
36.50	Ridge, bears S. 80° E. and NW.
40.11	The cor. of secs. 20, 21, 28 and 29, monumented by a malpais stone, 18x16x6 ins., firmly set 12 ins. in the ground, mkd. with 2 notches on S. and 4 notches on E. edges.
	At the corner point
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap. mkd.
	T7S R17E S20 S21 S29 S28 1970

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS									
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located under a fence bearing E. and W. and 5 lks. S. of an unmarked mining claim cor. monument of stones.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>								
	<p>From the cor. of secs. 21 and 28 only.</p> <p>S. 89°57' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through scattered undergrowth, along a fence bearing irreg. E. and W.</p>								
32.81	<p>Fall 1 lk. N. of a granite stone, 12x7x5 ins., lying on the ground, mkd. with $\frac{1}{4}$ on a face, mound of stone N. Origin of this stone cor. unknown.</p>								
40.28	<p>True point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist. falls in a wash, 5 lks. wide, 1 ft. deep, drains S.; not monumented.</p>								
40.76	<p>The witness $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented by a granite stone, 14x10x5 ins., firmly set 7 ins. in the ground, mkd. with $\frac{1}{4}$ W C on N. face, mound of stone N.</p> <p>At the witness corner point</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R17E</p> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">W</td> <td style="padding-right: 10px;">$\frac{1}{4}$</td> <td style="text-align: center;"> $\frac{S\ 21}{S\ 28}$ </td> <td style="padding-left: 10px;">→</td> </tr> <tr> <td style="padding-right: 10px;">C</td> <td></td> <td></td> <td></td> </tr> </table> <p>1970</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 3 lks. S. of a fence bearing irreg. E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>	W	$\frac{1}{4}$	$\frac{S\ 21}{S\ 28}$	→	C			
W	$\frac{1}{4}$	$\frac{S\ 21}{S\ 28}$	→						
C									
7.30	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 20° W.</p>								
11.70	<p>Wash, 10 lks. wide, 1 ft. deep, drains irreg. N.</p>								
39.65	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>								

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS		
	N. 0°04' W., bet. secs. 20 and 21.	
	Over rolling land, through scattered undergrowth.	
20.50	Wash; 35 lks. wide, 2 ft. deep, drains irreg. W.	
31.40	Spur, slopes E.	
40.02	The ½ sec. cor. of secs. 20 and 21, monumented by a quartzite stone, 18x6x6 ins., firmly set 12 ins. in the ground, mkd. with ½ on W. face, mound of stone W.	
	At the cor. point	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	T7S R17E ½ S20 S21 1970	
	Bury the orig. cor. stone alongside the iron post.	
	Rebuild the mound of stone W.	

	N. 0°01' E., beginning new measurement.	
	Over rolling land, through scattered undergrowth.	
5.90	Wash, 50 lks. wide, 1 ft. deep, drains irreg. NW.	
12.60	Wash, 30 lks. wide, 1 ft. deep, drains irreg. W.	
13.80	Wash, 60 lks. wide, 1 ft. deep, drains W.	
20.80	Wash, 30 lks. wide, 1 ft. deep, drains S. 85° W.	
38.80	Wash, 15 lks. wide, 1 ft. deep, drains S. 80° W.	
39.47.	Fence, bears irreg. E. and W.	
40.08	The cor. of secs. 16, 17, 20 and 21, monumented by a granite stone, 18x14x8 ins. firmly set 10 ins. in the ground, mkd. with 3 notches on S. and 4 notches on E. edges, mound of stone W.	
	At the cor. point	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T7S R17E S17 S16 S20 S21 1970	
	Bury the original cor. stone alongside the iron post.	
	Rebuild the mound of stone W. of the cor.	

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p> <hr/> <p>From the cor. of secs. 16 and 21 only.</p> <p>West, bet. secs. 16 and 21.</p> <p>Over rolling land, through scattered undergrowth.</p>
12.10	Wash, 30 lks. wide, 1 ft. deep, drains N. 15° W.
28.80	Wash, 5 lks. wide, 1 ft. deep, drains irreg. NW.
35.70	Wash, 5 lks. wide, 2 ft. deep, drains N.
40.12	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 21, monumented by a malpais stone, 18x12x8 ins., firmly set 12 ins. in the ground, mkd. with $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{4}$ $\frac{S 16}{S 21}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone N. of the cor.</p> <p>The cor. is located 7 lks. S. of a fence bearing irreg. E. and W.</p> <hr/> <p>West, beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
6.20	Fence, bears irreg. E. and W., thence along N. side of the fence.
11.70	Wash, 10 lks. wide, 1 ft. deep, drains NW.
19.70	Fence, bears N. 35° W. and S. 35° E. for 9 lks. to a cor. of fences extending E., W. and N. 35° W.
29.70	Wash, 25 lks. wide, 1 ft. deep, drains irreg. SW. for 5.00 chs., thence westerly.
40.19	The cor. of secs. 16, 17, 20 and 21.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>N. 0°06' E., bet. secs. 16 and 17.</p> <p>Over rolling land, through scattered undergrowth.</p>
19.90	Cor. of fences extending N. and SE., bears E. 30 lks. dist.
23.10	Wash, 15 lks. wide, 1 ft. deep, drains N. 80° W.
24.70	Wash, 5 lks. wide, 2 ft. deep, drains S. 85° W.
40.26	<p>The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, monumented by a granite stone, 20x10x8 ins., firmly set 15 ins. in the ground, mkd. with $\frac{1}{4}$ on W. face, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{4}$ S17 S16 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located under a fence bearing irreg. N. and S.</p>
	<p>N. 0°06' E., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
5.60	Fence, bears irreg. N. and S., thence along E. side of the fence.
12.20	Wash, 60 lks. wide, 1 ft. deep, drains irreg. NW.
25.50	Wash, 15 lks. wide, 1 ft. deep, drains W.
39.98	<p>The cor. of secs. 8, 9, 16 and 17, monumented by a granite stone, 18x12x5 ins., firmly set 14 ins. in the ground; mkd. with 4 notches on S. and E. edges, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS		
	<p style="text-align: center;">T7S R17E $\frac{S\ 8}{S17} \frac{S\ 9}{S16}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located under a fence bearing irreg. N. and S.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote bush and cacti.</p>	
	<p>N. 0°03' W., bet. secs. 8 and 9.</p> <p>Over rolling land, through scattered undergrowth.</p>	
7.00	Fence, bears N. 29° W: and S. 29° E. for 6 lks., thence bears irreg. S.	
16.70	Wash, 25 lks. wide, 1 ft. deep, drains W., curving NW.	
18.50	Low ridge, bears S. 70° E. and N. 70° W.	
21.00	Wash, 15 lks. wide, 1 ft. deep, drains N. 75° W.	
25.10	Spur, slopes N. 80° W.	
28.40	Wash, 15 lks. wide, 1 ft. deep, drains W. for approx. 6.00 chs., thence NW.	
35.10	Wash, 20 lks. wide, 2 ft. deep, drains SW. for 2.00 chs., thence NW.	
40.01	<p>The $\frac{1}{2}$ sec. cor. of secs. 8 and 9, monumented by a limestone, 18x10x7 ins., firmly set 14 ins. in the ground, in a collar of stone, mkd. with $\frac{1}{2}$ on W. face.</p> <p>At the cor. point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{2}$ $\frac{S\ 8}{S17} \frac{S\ 9}{S16}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p>	
	<p>N. 0°09' W., beginning new measurement.</p>	

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS									
	Over rolling land, through scattered undergrowth.								
15.30	Fence, bears irreg. E. and W.								
15.90	Aravaipa Creek, 115 lks. wide, with flowing water 1½ ft. deep, course N. 80° W.								
17.00	Fence cor. with fences extending irreg. E., S. and N.								
19.50	Aravaipa Road, bears E., curving NE., and bears N. 80° W., curving NW.								
25.80	Power line, bears S. 86° E. and N. 86° W.								
39.99	The cor. of secs. 4, 5, 8 and 9, monumented by a limestone, 22x10x8 ins., firmly set 18 ins. in the ground, mkd. with 5 notches on S. and 4 notches on E. edges, mound of stone W.								
	At the corner point								
	Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.								
	<table style="margin: auto;"> <tr> <td colspan="2">T7S R17E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2">1970</td> </tr> </table>	T7S R17E		S 5	S 4	S 8	S 9	1970	
T7S R17E									
S 5	S 4								
S 8	S 9								
1970									
	Bury the orig. cor. stone alongside the iron post.								
	Rebuild the mound of stone W.								
	The cor. is located under a fence bearing irreg. N. and S.								
	Land, rolling.								
	Soil, rocky clay loam; sandy loam in Aravaipa Creek bottom land.								
	Timber, scattered palo verde; mesquite along Aravaipa Creek.								
	Undergrowth, scattered creosote bush and cacti.								
	From the cor. of secs. 4 and 9 only.								
	N. 89°54' W., bet. secs. 4 and 9.								
	Over rolling land, through scattered undergrowth.								
7.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° W. for 2.00 chs., thence drains N. 70° W.								
31.20	Wash, 20 lks. wide, 1 ft. deep, drains N. 15° W. for 1.50 chs., thence drains NW.								

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
39.92	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 9, monumented by a conglomerate stone, 8x6 ins., firmly set with 16 ins. projecting above ground; mkd. with $\frac{1}{4}$ on N. face, mound of stone NW.; not remonumented.</p>
	<p>N. 89°53' W., beginning new measurement.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
0.32	<p>Fence, bears S. 30° E. and N. 30° W.</p>
4.50	<p>Wash, 150 lks. wide, 1 ft. deep, drains N. 30° W.</p>
7.50	<p>Fence, bears irreg. NE. and SW.</p>
15.80	<p>East shore of small lake, bears irreg. NE. and SW.; thence by triangulation over water.</p>
23.30	<p>West shore of same lake, bears irreg. NE. and SW.; end of triangulation.</p>
26.30	<p>Aravaipa Road, bears N. 20° E. and S. 40° W.</p>
27.90	<p>Power line with access road, bears N. 26° E. and S. 26° W.</p>
30.60	<p>Jeep road, on ridge, bears N. 20° E. and S. 20° W.</p>
33.70	<p>Wash, 30 lks. wide, 1 ft. deep, drains irreg. S.</p>
34.70	<p>Spur, slopes S. 10° W.</p>
36.10	<p>Wash, 30 lks. wide, 1 ft. deep, drains SW., curving S.</p>
40.55	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde; mesquite and cottonwood along Aravaipa Creek. Undergrowth, scattered creosote bush and cacti.</p>
	<p>N. 0°07' W., bet. secs. 4 and 5.</p>
	<p>Over rolling and mountainous land, through scattered undergrowth.</p>
20.06	<p>Point for the S $\frac{1}{16}$ sec. cor. of secs. 4 and 5, at proportionate dist.</p>
	<p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p>T7S R17E S 1/16 S 5 S 4 1970</p>
	<p>The cor. is under a fence bearing N. and S.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
20.35	Wash, 15 lks. wide, 1 ft. deep, drains W.
40.12	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented by a sandstone, 18x12x4 ins., firmly set 12 ins. in the ground, mkd. with $\frac{1}{4}$ on W. face, mound of stone W.
	At the corner point
	Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R17E $\frac{1}{4}$ S 5 S 4 1970
	Bury the orig. cor. stone alongside the iron post. The cor. is located under a fence bearing irreg. S. and N. for 4 lks. to end.
	<hr style="width: 20%; margin: auto;"/> N. 0°04' W., beginning new measurement.
	Over mountainous land, through scattered undergrowth.
1.90	Ridge, bears N. 30° W. and SE., curving S. 30° W.
23.60	Same ridge; bears SE. and NW.
27.60	Wash, 15 lks. wide, 2 ft. deep, drains SE.
38.25	The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp., monumented by an iron post, 2 ins. diam., projecting 24 ins. above ground and in a mound of stone, brass cap mkd.
	T6S R17E S32 <hr style="width: 20%; margin: auto;"/> S 5 S 4 T7S R17E 1928
	from which
	The cor. of secs. 32 and 33 only, T. 6 S., R. 17 E., monumented by an iron post 2 ins. diam., projecting 22 ins. above ground and in a mound of stone, bears N. 89°59' E., 67 lks. dist.
	Land, mountainous. Soil, rocky clay loam. Timber, scattered palo verde. Undergrowth, scattered creosote bush and cacti.
	From the cor. of secs. 29, 30, 31 and 32.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	N. 0°02' W., bet. secs. 29 and 30. Over rolling land, through scattered undergrowth.
6.20	Spur, slopes S. 80° W.
9.30	Wash, 120 lks. wide, 1 ft. deep, drains W. for approx. 5.00 chs., curving NW.
12.10	Wash, 40 lks. wide, 1 ft. deep, drains W.; track road in wash, bears irreg. E. and W.
13.60	Spur, slopes W.
15.40	Wash, 30 lks. wide, 1 ft. deep, drains S. 85° W.
20.40	Spur, slopes S. 85° W.
26.50	Spur, slopes W.
32.40	Spur, slopes N. 80° W.
36.50	Wash, 15 lks. wide, 1 ft. deep, drains irreg. W.
39.93	The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented by a granite stone, 18x6x6 ins., loosely set, no marks visible, mound of stone W. At the corner point Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd. T7S R17E $\frac{1}{4}$ S30 S29 1970 Bury the orig. cor. stone alongside the iron post. <hr/> N. 0°01' E., beginning new measurement. Over rolling land, through scattered undergrowth.
0.54	Wash, 5 lks. wide, 1 ft. deep, drains SW.
6.50	Wash, 20 lks. wide, 2 ft. deep, drains N. 75° W., curving SW.
22.00	Wash, 10 lks. wide, with 3 ft. banks, drains S. 70° W., curving W.
36.10	Low ridge, bears E. and W.
40.23	The cor. of secs. 19, 20, 29 and 30, monumented by a granite stone, 28x16x8 ins. firmly set 20 ins. in the ground, mkd. with 2 notches on S. and 5 notches on E. edges, mound of stone W.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S. R17E $\frac{S19}{S30} \frac{S20}{S29}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°53' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>1.80 S. end of jeep road bearing N. 30° W., bears N. 20 lks. dist.</p> <p>18.40 Jeep road, bears S., curving SE. and bears N. 2.00 chs. to an intersection with a track road bearing irreg. E. and W.</p> <p>27.00 The W. end of a jeep road bearing E., bears N. 70 lks. dist.</p> <p>40.13 The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented by a granite stone, 18x8x5 ins., firmly set 14 ins. in the ground, mkd. with $\frac{1}{4}$ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{4} \frac{S20}{S29}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone N.</p> <p>The cor. is located under a fence bearing irreg. E. and W.</p> <hr style="width: 20%; margin: 20px auto;"/>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS																
	<p>S. 89°54' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>31.20 Gully, 8 ft. deep, drains N. 25° W.</p> <p>40.09 The cor. of secs. 19, 20, 29 and 30.</p> <p>Land; rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>															
	<p>S. 89°57' W., bet. secs. 19 and 30.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>12.10 Spur, slopes N.</p> <p>21.50 Wash, 7 lks. wide, 3 ft. banks, drains N. 20° W.</p> <p>40.08 The 1/2 sec. cor. of secs. 19 and 30, monumented by a slate stone, 36x12x4 ins., firmly set 24 ins. in the ground, mkd. with 1/2 on N. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground; brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R17E</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding-right: 10px;">1/2</td><td style="border-bottom: 1px solid black;">S19</td><td></td></tr> <tr><td></td><td>S30</td><td></td></tr> <tr><td></td><td>1970</td><td></td></tr> </table> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located under a fence bearing irreg. E. and W.</p>	1/2	S19			S30			1970							
1/2	S19															
	S30															
	1970															
	<p>N. 89°58' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>11.00 S. edge of gully, 35 lks. wide, 7 ft. walls, drains NW. from N. 60° E.</p> <p>29.40 Same gully, 50 lks. wide, 12 ft. walls, drains S. 20° W.</p> <p>34.42 Point for the closing cor. of secs. 19 and 30 on the W. bdy. of the Tp., at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">T7S</td><td></td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">R17E</td><td></td></tr> <tr><td style="padding-right: 10px;">R16E</td><td style="border-left: 1px solid black; border-bottom: 1px solid black; padding-left: 5px;">S24</td><td style="padding-left: 5px;">C</td></tr> <tr><td></td><td style="border-left: 1px solid black; padding-left: 5px;">S30</td><td style="padding-left: 5px;">C</td></tr> <tr><td></td><td></td><td>1970</td></tr> </table> </div>		T7S			R17E		R16E	S24	C		S30	C			1970
	T7S															
	R17E															
R16E	S24	C														
	S30	C														
		1970														

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

from which

The cor. of secs. 24 and 25 only, T. 7 S.,
R. 16 E., bears S. 0°03' W., 1.05 chs. dist.,
previously described.

Land, rolling.
Soil, rocky clay loam.
Timber, scattered palo verde and mesquite.
Undergrowth, scattered creosote bush and cacti.

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 30 is at mid-
point bet. the closing cors. and on the W. bdy. of the
Tp.

Set the iron post 22 ins. in the ground, in a collar of
stone, brass cap mkd.

T7S
R17E
S30 $\frac{1}{4}$
1970

from which

The E. $\frac{1}{4}$ sec. cor. of sec. 25 only, T. 7 S.,
R. 16 E., bears S. 0°14' E., 1.53 chs. dist.,
previously described.

From the cor. of secs. 19, 20, 29 and 30.

North, bet. secs. 19 and 20.

Over rolling land, through scattered undergrowth.

- 3.20 Wash, 40 lks. wide, 6 ft. banks, drains W.
- 9.40 Spur, slopes E.
- 24.00 Wash, 30 lks. wide, 1 ft. deep, drains W.; track road,
bears E. and W.
- 30.70 Wash, 35 lks. wide, 1 ft. deep, drains N. 15° W.
- 39.20 Wash, 20 lks. wide, 1 ft. deep, drains NW., curving W.
- 39.96 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, monumented by a
granite stone, 15x8x5 ins., firmly set 11 ins. in the
ground, mkd. with $\frac{1}{4}$ on W. face, mound of stone W.
- At the corner point
- Set the iron post 24 ins. in the ground, brass cap mkd.

T7S R17E
 $\frac{1}{4}$
S19 | S20
1970

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS									
	Bury the orig. cor. stone alongside the iron post.								
	Rebuild the mound of stone W.								
	<p style="text-align: center;">_____</p> N. 0°02' W., beginning new measurement.								
	Over rolling land, through scattered undergrowth.								
12.60	Ridge, bears E. and W.								
21.30	Wash, 10 lks. wide, 1 ft. deep, drains NW., curving W.								
39.12	Fence, bears irreg. E. and W.								
40.17	The cor. of secs. 17, 18, 19 and 20, monumented by a limestone, 18x8x5 ins., firmly set 13 ins. in the ground, mkd. with 3 notches on S. and 5 notches on E. edges, mound of stone W.								
	At the corner point								
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.								
	<table style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">T7S R17E</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S18</td> <td style="text-align: center;">S17</td> </tr> <tr> <td style="text-align: center; border-right: 1px solid black;">S19</td> <td style="text-align: center;">S20</td> </tr> <tr> <td colspan="2" style="text-align: center;">1970</td> </tr> </table>	T7S R17E		S18	S17	S19	S20	1970	
T7S R17E									
S18	S17								
S19	S20								
1970									
	Bury the orig. cor. stone alongside the iron post.								
	Rebuild the mound of stone W.								
	Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.								
	From the cor. of secs. 16, 17, 20 and 21.								
	S. 89°53' W., bet. secs. 17 and 20.								
	Over rolling land, through scattered undergrowth.								
2.70	Wash, 20 lks. wide, 1 ft. deep, drains NW.								
39.40	Spur, slopes NE.								
40.08	The ½ sec. cor. of secs. 17 and 20, monumented by a quartzite stone, 18x8x8 ins. firmly set 12 ins. in the ground, mkd. with ½ on N. face, mound of stone N.								
	At the corner point								

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{4} \frac{S 17}{S 20}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Rebuild the mound of stone W. of the cor.</p> <p>The cor. is located 117 lks. N. of a fence bearing irreg. E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°53' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
15.40	Gully, 60 lks. wide, with 6 ft. walls, drains N. 10° W., curving W.
29.10	Jeep road, bears N. 15° E., curving E., and bears SW., curving W.
32.10	Same jeep road, bears SE. and NW.
40.10	The cor. of secs. 17, 18, 19 and 20.
	<p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>S. 89°58' W., bet. secs. 18 and 19.</p> <p>Over rolling land, through scattered undergrowth.</p>
8.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 15° W.
19.50	Wash, 10 lks. wide, 2 ft. deep, drains N. 15° W.
32.30	Wash, 20 lks. wide, 1 ft. deep, drains S. 10° W.
40.15	<p>The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented by a granite stone, 18x12x4 ins., firmly set 12 ins. in the ground, mkd. with $\frac{1}{4}$ on N. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{4} \frac{S 18}{S 19}$ 1970</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

Bury the orig. cor. stone alongside the iron post.

Build a mound of stone N. of the cor.

S. 89°58' W., beginning new measurement.


Over rolling land, through scattered undergrowth.

17.00 Wash, 10 lks. wide, 1 ft. deep, drains S. 5° W.

34.25 The closing cor. of secs. 18 and 19, on the W. bdy. of the Tp., monumented by a quartzite stone, 14x12x11 ins., firmly set 11 ins. in the ground, mkd. with C C on E. face and with 3 grooves on N. and S. faces, mound of stone E.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.



from which

The cor. of secs. 13 and 24 only, T. 7 S., R. 16 E., bears S. 0°10' E., 1.26 chs. dist., previously described.

Bury the orig. cor. stone alongside the iron post.

The cor. is located 2 lks. S. of a fence bearing E. and W.

Land, rolling.


Soil, rocky clay loam.

Timber, scattered palo verde and mesquite.

Undergrowth, scattered creosote bush and cacti.

The point for the W. ½ sec. cor. of sec. 19 is at mid-point bet. the closing cors. and on the W. bdy. of the Tp.

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>The E. $\frac{1}{4}$ sec. cor. of sec. 24 only, T. 7 S., R. 16 E., bears S. $0^{\circ}05'$ W., 1.265 chs. dist., previously described.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. $0^{\circ}01'$ W., bet. secs. 17 and 18.</p> <p>Over rolling land, through scattered undergrowth.</p>
4.90	Jeep road, bears irreg. E. and W.
6.50	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.
13.00	Wash, 50 lks. wide, with 5 ft. banks, drains SW.
26.10	Low ridge, bears S. 70° E. and N. 70° W.
31.20	Wash, 50 lks. wide, 1 ft. deep, drains S. 60° W.
31.90	Wash, 15 lks. wide, 1 ft. deep, drains irreg. W.
40.15	<p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented by a quartzite stone, 18x12x10 ins., firmly set 10 ins. in the ground, mkd. with $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E $\frac{1}{4}$ S18 S17 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located on a N. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ}02'$ W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
0.60	Wash, 15 lks. wide, 2 ft. deep, drains irreg. W.
40.18	<p>The cor. of secs. 7, 8, 17 and 18, monumented by a sandstone, 24x13x5 ins., firmly set 12 ins. in the ground, mkd. with 4 notches on S. and 5 notches on E. edges, mound of stone W.</p> <p>At the corner point</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E S 7 S 8 S18 S17 1970</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°57' W., bet. secs. 8 and 17.</p> <p>Over rolling land, through scattered undergrowth.</p>
2.50	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° W.
7.80	Low ridge, bears S. 20° E. and N. 20° W.
19.00	Wash, 20 lks. wide, 1 ft. deep, drains N. 35° W.
33.90	Wash, 15 lks. wide, 1 ft. deep, drains irreg. N.
40.18	<p>The ½ sec. cor. of secs. 8 and 17, monumented by a granite stone, 15x15x10 ins., firmly set 12 ins. in the ground; mkd. with ½ on N. face, mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R17E ½ $\frac{S\ 8}{S17}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°58' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
3.50	Wash, 20 lks. wide, 1 ft. deep, drains N. 35° W.
33.90	Wash, 15 lks. wide, 1 ft. deep, drains N. 30° W. from S. 85° E.
36.40	Wash, 15 lks. wide, 1 ft. deep, drains N., curving NE.
40.15	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS																			
	West, bet. secs. 7 and 18.																		
	Over rolling land, through scattered undergrowth.																		
24.40	Wash, 20 lks. wide, 1 ft. deep, drains N., curving NW.																		
40.14	The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented by a sandstone, 17x10x6 ins., firmly set 9 ins. in the ground, mkd. with $\frac{1}{4}$ on N. face, mound of stone N.																		
	At the corner point																		
	Set the iron post 24 ins. in the ground, brass cap mkd.																		
	<p style="text-align: center;">T7S R17E $\frac{1}{4}$ $\frac{S 7}{S18}$.1970</p>																		
	Bury the orig. cor. stone alongside the iron post.																		
	Rebuild the mound of stone N. of the cor.																		
	<p style="text-align: center;">—————</p> N. 89°49' W., beginning new measurement.																		
	Over rolling land, through scattered undergrowth.																		
17.60	Wash, 10 lks. wide, 2 ft. deep, drains N. 80° W.																		
32.00	Gully, 50 lks. wide, with 7 ft. walls, drains irreg. W.																		
33.92	Point selected for the witness closing cor. of secs. 7 and 18.																		
	Set the iron post 24 ins. in the ground, brass cap mkd.																		
	<p style="text-align: center;"> <table border="0"> <tr><td></td><td>T7S</td><td></td></tr> <tr><td></td><td>R17E</td><td></td></tr> <tr><td>R16E</td><td>S 7</td><td>C W</td></tr> <tr><td>S12</td><td>—</td><td></td></tr> <tr><td></td><td>S18</td><td>C C</td></tr> <tr><td></td><td>1970</td><td></td></tr> </table> </p>		T7S			R17E		R16E	S 7	C W	S12	—			S18	C C		1970	
	T7S																		
	R17E																		
R16E	S 7	C W																	
S12	—																		
	S18	C C																	
	1970																		
34.42	True point for the closing cor. of secs. 7 and 18, on the W. bdy. of the Tp., at proportionate distance , falls in a gully where a monument cannot be perpetuated; there is no remaining evidence of the orig. cor.																		
	from which																		
	<p style="text-align: center;">The cor. of secs. 12 and 13 only, T. 7 S., R. 16 E., bears S. 0°32' E., 1.88 chs. dist., previously described.</p>																		
	Land, rolling.																		
	Soil, rocky clay loam.																		
	Timber, scattered palo verde and mesquite.																		
	Undergrowth, scattered creosote bush and cacti.																		

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 18 is at mid-point bet. the closing cors. and on the W. bdy. of the Tp.

Set the iron post 22 ins. in the ground, brass cap mkd.

T7S
R17E
S18 $\frac{1}{4}$
1970

from which

The E. $\frac{1}{4}$ sec. cor. of sec. 13 only, T. 7 S., R. 16 E., bears S. $0^{\circ}07'$ E., 1.515 chs. dist., previously described.

Build a mound of stone E. of the cor.

From the cor. of secs. 7, 8, 17 and 18.

N. $0^{\circ}04'$ W., bet. secs. 7 and 8.

Over rolling land, through scattered undergrowth.

10.50 Wash, 25 lks. wide, 1 ft. deep, drains N. 75° W., curving N.

11.30 Same wash, 35 lks. wide, 1 ft. deep, drains N. 75° E., curving N.

14.20 Same wash, 50 lks. wide, with 7 ft. banks, drains NW.

21.00 Wash, 15 lks. wide, 1 ft. deep, drains W.

39.55 Point for the witness $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T7S R17E
 $\frac{1}{4}$
S 7 S 8
↑
W C
1970

Build a mound of stone W. of the cor.

The cor. is located on a spur, sloping W., curving NW.

Desc. steep N. slope.

40.05 True point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist., falls on a steep rubble slope where a monument cannot be perpetuated.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
41.30	Wash, 25 lks. wide, 1 ft. deep, drains N. 15° W.
57.20	Enter Aravaipa Creek bottom land, bears NE. and SW., thence through dense mesquite.
60.075	Point for the N. 1/16 sec. cor. of secs. 7 and 8, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R17E N 1/16 S 7 S 8 1970</p>
	Set a mesquite post, 4 ins. diam., 5 ft. long, alongside the iron post.
78.50	Aravaipa Creek, 90 lks. wide, with flowing water, 1½ ft. deep, course S. 55° W.
80.10	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R17E S 6 S 5 S 7 S 8 1970</p>
	Build a mound of stone W. of the cor.
	<p>Land, rolling. Soil, rocky clay loam; sandy loam in Aravaipa Creek bottom. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	From the cor. of secs. 4, 5, 8 and 9.
	West, bet. secs. 5 and 8.
	Over rolling land, through scattered undergrowth.
4.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 65° W.
18.60	Wash, 20 lks. wide, 2 ft. deep, drains SW.
20.40	Wash, 10 lks. wide, 1 ft. deep, drains S. 10° E.
29.70	Wash, 10 lks. wide, 5 ft. banks, drains S. 5° W.
36.10	Wash, 10 lks. wide, 2 ft. deep, drains S. 10° W.
40.16	The ¼ sec. cor. of secs. 5 and 8, monumented by a granite stone, 16x14x5 ins., firmly set 10 ins. in the ground, mound of stone N.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

At the corner point

Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.

T7S R17E
 $\frac{1}{4}$ $\frac{S 5}{S 8}$
 1970

N. 89°55' W., beginning new measurement.

Over rolling land, through scattered undergrowth.

- 7.30 Spur, slopes S. 10° W.
 10.20 Aravaipa Road, bears S. 53° E. and N. 53° W.
 11.00 Power line, bears S. 53° E. and N. 53° W.
 20.07 Point for the W. 1/16 sec. cor. of secs. 5 and 8, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T7S R17E
 W 1/16 $\frac{S 5}{S 8}$
 1970

Build a mound of stone W. of the cor.

- 25.40 Aravaipa Creek, 160 lks. wide, with flowing water 1½ ft. deep, course NW., curving W.
 37.70 Aravaipa Creek, 110 lks. wide, with flowing water 1 ft. deep, course S. 65° W.
 40.14 The cor. of secs. 5, 6, 7 and 8.

Land, rolling.
 Soil, rocky clay loam.
 Timber, palo verde and mesquite.
 Undergrowth, scattered creosote bush and cacti.

S. 89°57' W., bet. secs. 6 and 7.

Over nearly level land, through scattered undergrowth.

- 14.80 Wash, 50 lks. wide, 1 ft. deep, drains SW.
 20.03 Point for the E. 1/16 sec. cor. of secs. 6 and 7, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T7S R17E
 E 1/16 $\frac{S 6}{S 7}$
 1970

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
	Build a mound of stone N. of the cor.
20.40	Track road, bears N. and S.
20.50	Fence, bears N. and S.
28.30	Fence, bears N. and S.
28.60	Jeep road, bears N. and S.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist., there is no remaining evidence of the orig. cor. Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R17E $\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$ 1970</p>
	Build a mound of stone N. of the cor.
42.40	Jeep road, bears NE. and SW.
60.10	Dyke, bears N. and S.
74.88	Point for the closing cor. of secs. 6 and 7, at proportionate dist. and on the W. bdy. of the Tp.; not monumented.
	from which
	<p style="text-align: center;">The proportionate point for the cor. of secs. 1 and 12 only, T. 7 S., R. 16 E., bears S. $0^{\circ}03'$ E., 1.98 chs. dist., previously described.</p>
	Land, nearly level.
	Soil, sandy loam.
	Timber, scattered mesquite.
	Undergrowth, scattered grass and cacti.
	The point for the W. $\frac{1}{4}$ sec. cor. of sec. 7 is at mid-point bet. the closing cors. and on the W. bdy. of the Tp.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T7S R17E S 7 $\frac{1}{4}$ 1970</p>
	from which
	<p style="text-align: center;">The E. $\frac{1}{4}$ sec. cor. of sec. 12 only, T. 7 S., R. 16 E., bears S. $0^{\circ}05'$ E., 1.805 chs. dist., previously described.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS

The point for the W. $\frac{1}{4}$ sec. cor. of sec. 6, is at proportionate dist., using 40.00 chs. in northing from the point for the closing cor. of secs. 6 and 7.

Set the iron post 24 ins. in the ground, brass cap mkd.

T7S
R17E
 $\frac{1}{4}$ S 6
1970

from which

The E. $\frac{1}{4}$ sec. cor. of sec. 1 only, on the E. bdy. of T. 7 S., R. 16 E., bears S. $0^{\circ}34'$ E., 2.12 chs. dist.

Build a mound of stone E. of the cor.

From the cor. of secs. 5, 6, 7 and 8.

N. $0^{\circ}06'$ E., bet. secs. 5 and 6.

Over nearly level land, through scattered undergrowth.

- 6.20 Wash, 200 lks. wide, 1 ft. deep, drains S. 85° W., curving S.
- 7.20 Leave Aravaipa Creek bottom land, bears N. 80° E. and S. 80° W., enter rolling land.
- 9.50 Aravaipa Road, bears N. 88° E., curving NE. and S. 88° W.
- 12.90 Power line, bears N. $70^{\circ}15'$ E. and S. $70^{\circ}15'$ W.
- 20.025 Point for the S. $\frac{1}{16}$ sec. cor. of secs. 5 and 6, at proportionate dist.

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T7S R17E
S $\frac{1}{16}$
S 6 | S 5
1970

23.90 Wash, 10 lks. wide, 1 ft. deep, drains S. 15° W.

38.30 Wash, 15 lks. wide, 1 ft. deep, drains SW.

40.05 The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented by a limestone, 18x10x6 ins., firmly set 16 ins. in the ground, mkd. with $\frac{1}{4}$ on W. face, mound of stone W.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 17 E.

CHAINS	
<p>7.50</p> <p>30.40</p> <p>38.07</p>	<p style="text-align: center;">T7S R17E $\frac{1}{2}$ S 6 S 5 1970</p> <p>Bury the orig. cor. stone alongside the iron post. The cor. is located on a steep S. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>Wash, 15 lks. wide, 2 ft. deep, drains W., curving SW.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains SW.</p> <p>The cor. of secs. 5 and 6 only on the N. bdy. of the Tp., monumented by an iron post 2 ins. diam., projecting 14 ins. above ground and in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T6S R17E <u>S31</u> S 6 S 5 T7S R17E 1928</p> <p>from which</p> <p style="padding-left: 40px;">The cor. of secs. 31 and 32 only, on the S. bdy. of Tp. 6 S., R. 17 E., monumented by an iron post 2 ins. diam., projecting 16 ins. above ground and in a collar of stone, bears N. 89°46' E., 66 lks. dist., brass cap mkd.</p> <p style="text-align: center;">T6S R17E <u>S31 S32</u> S5 T7S R17E 1928</p> <p>Land, rolling. Soil, sandy loam in Aravaipa Creek bottom; rocky clay loam in remainder. Timber, scattered palo verde and mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p style="text-align: center;">General Description</p>
	<p>The land covered by this survey in Township 7 South, Range 17 East, is mostly rolling, although there is some mountainous land in the east portion and some nearly level land along Aravaipa Creek. The elevation ranges from about 2,260 feet above sea level at the west</p>

General Description, T. 7 S., R. 17 E.

CHAINS

boundary of section 7 to about 3,300 feet near the northeast corner of section 34. Access to the area surveyed consists mostly of track roads and jeep trails, with the exception of Aravaipa Road in the extreme north portion. The soil is mostly a rocky clay loam, changing to sandy loam in the Aravaipa Creek bottom. Aravaipa Creek courses through sections 3, 4, 5, 6, 8 and 9 and has flowing water from about 1 to 1½ feet deep. The drainage in the area surveyed is mostly from east to west. The land is used mostly for grazing. There is no evidence of recent mining activity.

55

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Paul G. Bauer, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 26th day of March, 1970, (I) ~~(We)~~ have dependently resurveyed the east boundary of Township 7 South, Range 16 East, the west 4 miles of the north boundary of Township 8 South, Range 17 East, and a portion of the subdivisional lines of Township 7 South, Range 17 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 28, 1970

(Date)

Paul G. Bauer

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAR 2 1973

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of the east boundary of Township 7 South, Range 16 East, the west 4 miles of the north boundary of Township 8 South, Range 17 East, and a portion of the subdivisional lines of Township 7 South, Range 17 East, Gila and Salt River Meridian, executed by Paul G. Bauer, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

MAY 29 1973

(Date)

Clark F. Lumm

(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys ~~is~~ is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626