

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

RETRACEMENT

OF A

PORTION OF THE EAST BOUNDARY

AND THE

DEPENDENT RESURVEY

OF A

PORTION OF THE SUBDIVISIONAL LINES

FRACTIONAL TOWNSHIP 15 SOUTH, RANGE 32 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Gary T. Oviatt

Cadastral Surveyor

Under special instructions dated April 20, 1970, which provided for the surveys
included under Group Number 526, approved April 20, 1970,
and assignment instructions dated April 20, 1970.

Survey commenced May 26, 1970

Survey completed June 26, 1970

1A

BOOK 4979

INDEX DIAGRAM

Township 15 S., Range 32 E.

6	35 5	23 4	14 3	8 2	1
				□ 334	
34	33	22	13	7	
7	33 8	21 9	12 10	6 8(1/2) 11	12
				□ 335	
32	31	20	11	5	
18	30 17	18 16	11 15	4 6(1/2) 14	13
				□ 336	
30	29	18	10	3	
19	28 20	17 21	9 22	2 4(1/2) 23	24
				□ 337	
27	27	16		1	
30	26 29	15 28	27	26	25
				□ 338	
25	24				
31	24 32	15 33	34	35	36

NEW MEXICO

Fractional Township 15 South, Range 32 East
Gila and Salt River Meridian, Arizona

CHAINS

The east boundary (the Arizona-New Mexico State Line) was surveyed by Chandler Robbins in 1875. The south boundary (the 3rd Standard Parallel South), the west and north boundaries and subdivisional lines were surveyed by R. C. Powers in 1883. The south boundary was resurveyed by J. F. Hesse in 1913. The Arizona-New Mexico State Line between the 333 and 338 mile corners was resurveyed by Warner and Thomas in 1934. The north boundary was resurveyed by D. E. Harding in 1957. A portion of the south boundary, east boundary and subdivisional lines were resurveyed by L. W. Murphy in 1962. The west boundary was resurveyed by Gary T. Oviatt in 1969.

The following field notes are those of a retracement of a portion of the east boundary (the Arizona-New Mexico State Line), a dependent resurvey of a portion of the subdivisional lines of Fractional Township 15 South, Range 32 East, Gila and Salt River Meridian, Arizona, designed to restore the corners in their true original location according to the best available evidence.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated April 20, 1970. The direction of all lines were determined by solar observations and all lines refer to the true meridian.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of section 23, at the closing corner of sections 23 and 26 as calculated from the survey plat **accepted** and dated March 13, 1963 is: Latitude 32°06'14.6" North and Longitude 109°02'53" West.

The mean magnetic declination was found to be 14° East.

Retracement, Portion East Boundary
(Arizona-New Mexico State Line)
Fractional Township 15 South, Range 32 East

The east boundary (the Arizona-New Mexico State Line) from the 334 mile corner to the 337 mile corner was retraced and found essentially the same as the official record of the 1934 survey.

Retracement of the Survey executed
by L. W. Murphy in 1962

From the 337 mile corner, monumented by an iron post, 2

Ret., Portion E. Bdy. (Ariz.-New Mex. State Line)

CHAINS

ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.

M I
337
Ariz | N M
1934

S. 0°02' W., along the 338 mile.

Over rolling land, through moderate undergrowth.

18.11

The closing cor. of secs. 23 and 26, monumented by an iron post, 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.

T15S
C S23 | N M
C S26 |
R32E |
1962

from which

The 338 mile cor., bears S. 0°02' W., 62.83 chs. dist., monumented by an iron post, 2 ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.

M I
338
Ariz | N M
1934

Land, rolling.
Soil, gravelly clay loam.
No timber; undergrowth, creosote bush, cacti, cat claw and mesquite.

Dependent Resurvey, Portion Subdivisional Lines
Fractional Township 15 South, Range 32 East

Reestablishment of the Survey executed
by R. C. Powers in 1883

From the cor. of secs. 22, 23, 26 and 27, monumented by an iron post, 2½ ins. diam., firmly set in a mound of stone, located underneath a N. and S. fence, brass cap mkd.

T15S R32E
S22 | S23
S27 | S26
1962

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	N. 0°03' E., bet. secs. 22 and 23.
	Over rolling land, through moderate undergrowth, along the E. side of a fence bearing N. and S.
5.00	Wash, 70 lks. wide, 3 ft. banks, drains NW.
18.90	Wash, 40 lks. wide, 3 ft. banks, drains NW.
20.30	A fence cor. bears West, 6 lks. dist.; fences extend S. and W.
24.70	Wash, approximately 2.00 chs. wide, 1 ft. deep, drains SW.
40.14	Point for the $\frac{1}{2}$ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T15S R32E $\frac{1}{2}$ S22 S23 1970</p>
	Raise a mound of stone W. of the cor.
55.30	Wash, 180 lks. wide, 1 ft. deep, drains W.
80.28	The cor. of secs. 14, 15, 22 and 23, as determined from a wooden stake, 1 x 1 ins., projecting 3 ins. above the ground, set in a small mound of stone. This stake was originally set in a pit $5\frac{1}{2}$ ft. SE. of the cor.
	At the corner point
	Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T15S R32E <u>S15 S14</u> S22 S23 1970</p>
	The wooden stake, bears SE. $5\frac{1}{2}$ ft. dist.
	Land, rolling.
	Soil, gravelly clay loam.
	No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.
	N. 88°43' E., bet. secs. 14 and 23.
	Over rolling land, through moderate undergrowth.
27.44	Intersect the E. bdy. of the township.
	Point for the closing cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS																																		
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>T15S</td> <td> </td> <td></td> </tr> <tr> <td></td> <td>R32E</td> <td> </td> <td>New</td> </tr> <tr> <td>C</td> <td>S14</td> <td> </td> <td>Mex</td> </tr> <tr> <td>C</td> <td>S23</td> <td> </td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>1970</td> </tr> </table> <p>from which</p> <p>The 336 mile cor., bears N. 0°05' E., 17.75 chs. dist., monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>M I</td> <td></td> </tr> <tr> <td></td> <td>336</td> <td></td> </tr> <tr> <td>Ariz</td> <td> </td> <td>N M</td> </tr> <tr> <td></td> <td></td> <td>1934</td> </tr> </table> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>		T15S				R32E		New	C	S14		Mex	C	S23						1970		M I			336		Ariz		N M			1934	
	T15S																																	
	R32E		New																															
C	S14		Mex																															
C	S23																																	
			1970																															
	M I																																	
	336																																	
Ariz		N M																																
		1934																																
	<p>Point for the E ½ sec. cor. of sec. 23 is at mid-point bet. the closing cors. and on the E. bdy. of the township.</p> <p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td>T15S</td> <td> </td> <td></td> </tr> <tr> <td></td> <td>R32E</td> <td> </td> <td></td> </tr> <tr> <td></td> <td>½</td> <td> </td> <td>New</td> </tr> <tr> <td></td> <td>S23</td> <td> </td> <td>Mex</td> </tr> <tr> <td></td> <td></td> <td></td> <td>1970</td> </tr> </table> <p>from which</p> <p>The 337 mile cor., bears S. 0°05' W., 22.44 chs. dist.</p>		T15S				R32E				½		New		S23		Mex				1970													
	T15S																																	
	R32E																																	
	½		New																															
	S23		Mex																															
			1970																															
<p>36.10</p> <p>40.24</p>	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 0°18' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Wash, 60 lks. wide, 12 ft. banks, drains N. 60° W.</p> <p>Point selected for the witness ½ sec. cor. of secs. 14 and 15.</p>																																	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T15S R32E</p> <p style="text-align: center;"> $\frac{1}{4}$ S15 S14 W C 1970 </p>	
	Raise a mound of stone W. of the cor.	
41.54	True point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15, at proportionate dist., falls in a wash 250 lks. wide, 1 ft. deep draining W.; there is no remaining evidence of the original cor.; impractical to monument.	
63.90	Fence, bears E. and W.	
73.30	Wash, 130 lks. wide, 1 ft. deep, drains S. 80° W.	
82.50	Wash, 15 lks. wide, 3 ft. banks, drains irregularly W.	
83.08	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set the iron post 26 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T15S R32E</p> <p style="text-align: center;"> S10 S11 S15 S14 1970 </p>	
	Raise a mound of stone W. of the cor.	
	<p>Land, rolling.</p> <p>Soil, gravelly clay loam.</p> <p>No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
	S. 86°42' E., bet. secs. 11 and 14.	
	Over gently rolling land, through moderate undergrowth.	
16.30	Track road, bears NE. and SW.	
28.02	Intersect the E. bdy. of the township.	
	Point for the closing cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T15S </p> <p style="text-align: center;">R32E New</p> <p style="text-align: center;">C S11 Mex</p> <p style="text-align: center;">C S14 </p> <p style="text-align: center;">1970</p>	

Dependent Resurvey, Portion Subdivisional Lines
 Fractional T. 15 S., R. 32 E.

CHAINS	
	<p>from which</p> <p>The 335 mile cor., bears N. 0°05' E., 17.57 chs. dist., monumented by an iron post, 2 ins. diam., projecting 10 ins. above the ground, mound of stone N., brass cap mkd.</p> <div style="text-align: center;"> <p>M I 335 Ariz N M 1934</p> </div> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	<p>Point for the $E\frac{1}{4}$ sec. cor. of sec. 14 is at mid-point bet. the closing cors. and on the E. bdy. of the township.</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E $\frac{1}{4}$ New S14 Mex 1970</p> </div> <p>from which</p> <p>The 336 mile cor., bears S. 0°05' W., 22.68 chs. dist.</p> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 1°37' W., bet. secs. 10 and 11.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>32.70 Wash, 30 lks. wide, 5 ft. banks, drains S. 70° W.</p> <p>41.56 The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented by a granite stone, 12 x 6 x 5 ins., set 5 ins. in the ground, mkd. $\frac{1}{4}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E $\frac{1}{4}$ S10 S11 1970</p> </div>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	<p>Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>N. 0°10' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>10.00 Wash, 30 lks. wide, 4 ft. banks, drains W.</p> <p>23.20 Wash, approximately 9 chs. wide, 1 ft. deep, drains W.</p> <p>40.28 The cor. of secs. 2, 3, 10 and 11, as determined from a wooden stake, 1 x 1 ins., projecting 6 ins. above the ground, set in a mound of stone. This stake was originally set in a pit 5½ ft. SE. of the cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E S 3 S 2 S10 S11 1970</p> <p>The wooden stake bears SE., 5½ ft. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
29.48	<p>S. 84°31' E., bet. secs. 2 and 11.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Intersect the E. bdy. of the township.</p> <p>Point for the closing cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E New C S 2 Mex C S11 1970</p> <p>from which</p> <p>The 334 mile cor., bears N. 0°02' E., 17.77 chs. dist., monumented by an iron post, 2 ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	<p style="text-align: center;">M I 334 Ariz N M 1934</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p> <hr/> <p>Point for the $\frac{E}{4}$ sec. cor. of sec. 11 is at mid-point bet. the closing cors. and on the E. bdy. of the township.</p> <p>Set the iron post 22 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4}$ S11 New Mex 1970</p> <p>from which</p> <p style="padding-left: 40px;">The 335 mile cor., bears S. $0^{\circ}02'$ W., 22.73 chs. dist.</p> <p>Raise a mound of stone W. of the cor.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. $0^{\circ}35'$ W., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>5.30 Wash, 40 lks. wide, 4 ft. banks, drains W.</p> <p>18.50 Wash, 30 lks. wide, 7 ft. banks, drains SW.</p> <p>19.90 Wash, 15 lks. wide, 5 ft. banks, drains SW.</p> <p>31.00 Track road, bears SE. and NW.</p> <p>35.60 Wash, 100 lks. wide, 1 ft. deep, drains W.</p> <p>40.04 Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 2 and 3.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4}$ S 3↑ S 2 W C 1970</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	Raise a mound of stone W. of the cor.
41.00	Wash, 180 lks. wide, 1 ft. deep, drains W.
41.14	True point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate dist. falls in a wash draining W.; there is no remaining evidence of the original cor.; impractical to monument.
48.00	Wash, 10 lks. wide, 3 ft. banks, drains W.
56.60	Wash, 10 lks. wide, 3 ft. banks, drains SW.
82.21	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, brass cap mkd.
	T14S R32E S34 S35 S 3 S 2 T15S 1957
	Land, gently rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.
	From the cor. of secs. 21, 22, 27 and 28, monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 4 ins. above the ground, in a collar of stone, brass cap mkd.
	T15S R32E S21 S22 S28 S27 1962
	N. $0^{\circ}03'$ E., bet. secs. 21 and 22.
	Over gently rolling land, through moderate undergrowth.
17.40	Wash, 70 lks. wide, 4 ft. banks, drains NE.
39.64	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T15S R32E $\frac{1}{4}$ S21 S22 1970
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the iron post.
48.60	Wash, 120 lks. wide, 1 ft. deep, drains NE.

Dependent Resurvey, Portion Subdivisional Lines
 Fractional T. 15 S., R. 32 E.

CHAINS					
64.80	Wash, 40 lks. wide, 1 ft. deep, drains NE.				
75.60	Old fence line, bears irregularly E. and W.				
79.28	<p>The cor. of secs. 15, 16, 21 and 22, monumented by a granite stone, 5 x 4 x 2 ins., lying on top of a small mound of earth, mkd. with X on top, found traces of 4 pits, no trace of stake in SE. pit.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E</p> <table border="1" style="margin: auto;"> <tr> <td>S16</td> <td>S15</td> </tr> <tr> <td>S21</td> <td>S22</td> </tr> </table> <p>1970</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 4 ft. long, 2½ ins. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	S16	S15	S21	S22
S16	S15				
S21	S22				
19.60	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 87°38' W., bet. secs. 15 and 22.</p> <p>Over rolling land, through moderate undergrowth.</p>				
40.73	<p>Wash, 20 lks. wide, 10 ft. banks, drains SW.</p> <p>Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E</p> <table border="1" style="margin: auto;"> <tr> <td>¼</td> <td>S15</td> </tr> <tr> <td></td> <td>S22</td> </tr> </table> <p>1970</p> </div> <p>Raise a mound of stone N. of the cor.</p>	¼	S15		S22
¼	S15				
	S22				
41.40	Wash, 10 lks. wide, 2 ft. deep, drains SW.				
68.80	Right bank of San Simon River, bears S. 10° E. and N. 10° W.				
75.00	Left bank of San Simon River, bears S. 10° E. and N. 10° W.				
81.46	The cor. of secs. 15, 16, 21 and 22.				

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	<p>Land, rolling. Soil, gravelly and sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	<p>N. 0°49' W., bet. secs. 15 and 16. Over gently rolling land, through moderate undergrowth.</p>
16.90	Left bank of San Simon River, bears SE. and NW.
20.70	Right bank of San Simon River, bears SE. and NW.
40.53	Point for the $\frac{1}{2}$ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor. Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T15S R32E $\frac{1}{2}$ S16 S15 1970</p>
	Raise a mound of stone W. of the cor.
54.80	Wash, approximately 10.00 chs. wide, 1 ft. deep, drains W.
62.10	Fence, bears S. 89°45' E. and N. 89°45' W.
81.06	The cor. of secs. 9, 10, 15 and 16, monumented by a mound of stone and a wood flag pole, 6 ft. above the ground. This cor. has long been recognized by local ranchers and is accepted as the best remaining evidence of the original cor. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T15S R32E S 9 S10 S16 S15 1970</p>
	Reset the flag pole alongside and raise a mound of stone W. of the cor.
	<p>Land, gently rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	From the cor. of secs. 10, 11, 14 and 15.

Dependent Resurvey, Portion Subdivisional Lines
 Fractional T. 15 S., R. 32 E.

CHAINS		
	<p>N. 88°14' W., bet. secs. 10 and 15.</p>	
	<p>Over rolling land, through moderate undergrowth.</p>	
4.70	<p>Wash, 20 lks. wide, 2 ft. deep, drains irregularly W.</p>	
27.00	<p>Same wash, drains irreg. W.</p>	
30.10	<p>Same wash, drains irreg. W.</p>	
33.20	<p>Same wash, drains S. 70° W.</p>	
41.19	<p>The 1/2 sec. cor. of secs. 10 and 15, monumented by a granite stone, 9 x 5 x 4 ins., set 4 ins. in the ground, mkd. 1/2 on N. face.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T15S R32E 1/2 $\frac{S10}{S15}$ 1970</p>	
	<p>Bury the orig. cor. stone alongside the iron post.</p>	
	<p>Raise a mound of stone N. of the cor.</p>	
	<hr/> <p>N. 89°57' W., beginning new measurement.</p>	
	<p>Over rolling land, through moderate undergrowth.</p>	
40.84	<p>The cor. of secs. 9, 10, 15 and 16.</p>	
	<p>Land, rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
	<hr/> <p>N. 0°21' W., bet. secs. 9 and 10.</p>	
	<p>Over rolling land, through moderate undergrowth.</p>	
13.40	<p>Track road, bears SE. and NW.</p>	
20.305	<p>Point for the S 1/16 sec. cor. of secs. 9 and 10, at proportionate dist.</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T15S R32E S 1/16 S 9 S10 1970</p>	
	<p>Raise a mound of stone W. of the cor.</p>	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
40.61	<p>The $\frac{1}{2}$ sec. cor. of secs. 9 and 10, monumented by a limestone, 10 x 7 x 4 ins., set 2 ins. in the ground, mkd. $\frac{1}{2}$ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{2}$ S 9 S10 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°21' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>	
4.60	Track road, bears E. and W.	
20.305	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 9 and 10, at proportionate dist.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T15S R32E N $\frac{1}{16}$ S 9 S10 1970</p>	
40.61	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T15S R32E S 4 S 3 S 9 S10 1970</p> <p>Deposit glass at the base of the iron post..</p> <p>Land, rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
	From the cor. of secs. 2, .3, 10 and 11.	
	N. 89°32' W., bet. secs. 3 and 10.	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
	Over rolling land, through moderate undergrowth.	
9.00	Wash, 3.70 chs. wide, 1 ft. deep, drains NW.	
40.62	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.	
	<p style="text-align: center;">T15S R32E $\frac{1}{4}$ $\frac{S\ 3}{S10}$ 1970</p>	
	Deposit glass at the base of the iron post.	
81.24	The cor. of secs. 3, 4, 9 and 10.	
	Land, rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.	
	N. 0°19' W., bet. secs. 3 and 4.	
	Over gently rolling land, through moderate undergrowth.	
40.61	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T15S R32E $\frac{1}{4}$ S 4 S 3 1970</p>	
	Raise a mound of stone W. of the cor.	
55.80	Track road, bears NE. and SW.	
81.14	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by an iron post, 2 $\frac{1}{2}$ ins. diam., projecting 6 ins. above the ground, brass cap mkd.	
	<p style="text-align: center;">T14S R32E S33 S34 S 4 S 3 T15S 1957</p>	
	Land, gently rolling. Soil, gravelly clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T: 15 S., R. 32 E.

CHAINS	
	<p>From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 10 ins. above the ground, brass cap mkd.</p>
	<p style="text-align: center;">S C T15S R32E <u>S32 S33</u> 1913</p>
	<p>N. 0°27' E., bet. secs. 32 and 33.</p>
	<p>Over gently rolling land, through moderate undergrowth, along underground gas line bearing N. and S.</p>
41.92	<p>Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set the iron post 26 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15S R32E ¼ <u>S32 S33</u> 1970</p>
	<p>Set a mesquite post, 4½ ft. long, 2 ins. diam., alongside the iron post.</p>
	<p>The cor. is located 38 lks. E. of an underground gas line bearing N. and S.</p>
83.46	<p>Approximate dist. to offset in underground gas line; line bears W. about 38 lks., thence S. and E. about 38 lks., thence N.</p>
83.84	<p>The cor. of secs. 28, 29, 32 and 33, monumented by an iron post, 2½ ins. diam., projecting 15 ins. above the ground, set in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T15S R32E <u>S29 S28</u> <u>S32 S33</u> 1962</p>
	<p>The cor. is located in a small cleared out area and W. of gas line.</p>
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	<p>N. 1°33' W., bet. secs. 28 and 29.</p>
	<p>Over gently rolling land, through moderate undergrowth, along the west side of an underground gas line paralleling line.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
39.75	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4}$ S29 S28 1970</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located 41 lks. West of an underground gas line bearing S. 1°31' E. and N. 1°31' W.</p>	
79.50	<p>The cor. of secs. 20, 21, 28 and 29, as determined from a wooden stake, 1 x 1 ins. diam., projecting 2 ins. above the ground, with an open pipe, 1 in. diam., projecting 3 ins. above the ground alongside. This stake was originally set in a pit 5½ ft. SE. of the cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E S20 S21 S29 S28 1970</p> <p>The wooden stake and 1 in. pipe bears SE. 5½ ft. dist.</p> <p>Set a wooden post, 4 ins. square, 2½ ft. long, alongside the iron post.</p> <p>The cor. is located 44 lks. West of an underground gas line bearing S. 1°31' E. and N. 0°54' W.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
41.20	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°08' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4}$ S21 S28 1970</p>	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	Set a mesquite post, 3 ft. long, 2½ ins. diam., alongside the iron post.
47.00	Track road, bears S. 60° E. and N. 60° W.
68.00	Wash, 10 lks. wide, 1 ft. deep, drains NE.
81.96	Underground gas line, bears S. 1°31' E. and N. 0°54' W.
82.40	The cor. of secs. 20, 21, 28 and 29.
	Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth; creosote bush, cacti, mesquite and cat claw.
	N. 0°54' W., bet. secs. 20 and 21.
	Over gently rolling land, through moderate undergrowth, along gas line paralleling line:
10.60	Track road, bears S. 60° E. and N. 60° W.
39.83	Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T15S R32E ¼ S20 S21 1970</p>
	Raise a mound of stone W. of the cor.
	The cor. is located 43 lks. West of an underground gas line bearing S. 0°54' E. and N. 1°05' W.
79.66	The cor. of secs. 16, 17, 20 and 21, monumented by a granite stone, 7 x 5 x 4 ins., set 3 ins. in the ground mkd. 4 notches on E. face and 3 notches on S. face, with an open pipe, 1 in. diam., projecting 2 ins. above the ground alongside.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T15S R32E S17 S16 S20 S21 1970</p>
	Bury the orig. cor. stone and the open pipe, alongside the iron post.
	Set a wooden post, 4 ft. long, 3 ins. diam., alongside the cor.

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	<p>The cor. is located 30 lks. West of an underground gas line bearing irregularly S. 1°05' E. and N. 0°55' W.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 86°53' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
2.30	Wash, 130 lks. wide, 1 ft. deep, drains N. 10° E.
38.90	Wash, 15 lks. wide, 8 ft. banks, drains NE.
43.78	<p>The ¼ sec. cor. of secs. 16 and 21, monumented by a volcanic stone, 6 x 5 x 3 ins., set 2 ins. in the ground, mkd. ¼ on N. face, set in a small mound of stone.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E</p> <p>¼ $\frac{S16}{S21}$</p> <p>1970</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 3 ins. diam., alongside and raise a mound of stone N. of the cor.</p>
	<p>S. 88°49' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
39.72	Underground gas line, bears irregularly S. 1°05' E. and N. 0°55' W.
40.02	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	<p>N. 0°55' W., bet. secs. 16 and 17.</p> <p>Over gently rolling land, through moderate undergrowth, along gas line paralleling line.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4}$ S17 S16 1970</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor. bears N. 77°34' E., 138 lks. dist., fences extend N. and W.</p> <p>Set a mesquite post, 3 ft. long, 4 ins. diam., alongside the iron post.</p> <p>The cor. is located 40 lks. West of an underground gas line bearing irregularly S. 0°55' E. and N. 0°55' W.</p>
40.25	<p>Fence, bears E. and W.</p>
60.00	<p>A fence cor., bears East, 100 lks. dist.; fences extend E. and S.</p>
63.60	<p>Wash, 50 lks. wide, 7 ft. banks, drains NE.</p>
79.00	<p>Underground gas line, bears NW. and SE.</p>
80.00	<p>The cor. of secs. 8, 9, 16 and 17, as determined from a wooden stake, 1 x 1 ins., projecting 3 ins. above the ground, with an open pipe, 1 in. diam., projecting 3 ins. above the ground alongside. This wood stake was originally set in a pit 5$\frac{1}{2}$ ft. SE. of the cor.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T15S R32E <u>S 8 S 9</u> S17 S16 1970</p> <p>The wooden stake and open pipe bears SE. 5$\frac{1}{2}$ ft. dist.</p> <p>Set a wooden post, 3 ft. long, 3 ins. diam., alongside the iron post.</p> <p>The cor. is located 30 lks. East of an underground gas line bearing irregularly N. and S.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>

Dependent Resurvey, Portion Subdivisional Lines
 Fractional T. 15 S., R. 32 E.

CHAINS	
	<p>From the cor. of secs. 9, 10, 15 and 16. N. 89°32' W., bet. secs. 9 and 16. Over gently rolling land, through moderate undergrowth.</p>
20.96	<p>Point for the E 1/16 sec. cor. of secs. 9 and 16, at proportionate dist. Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T15S R32E E 1/16 $\frac{S\ 9}{S16}$ 1970</p>
30.80	<p>Wash, 25 lks. wide, 2 ft. deep, drains N.</p>
34.00	<p>Right bank of San Simon River, bears S. 25° E. and N. 25° W.</p>
35.50	<p>Left bank of San Simon River, bears S. 25° E. and N. 25° W.</p>
41.92	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E 1/4 $\frac{S\ 9}{S16}$ 1970</p> <p>Raise a mound of stone N. of the cor.</p>
62.18	<p>Point selected for the witness W 1/16 sec. cor. of secs. 9 and 16. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E W 1/16 $\leftarrow \frac{S\ 9\ W}{S16\ C}$ 1970</p> <p>Raise a mound of stone N. of the cor.</p>
62.40	<p>East bank of an eroded wash with 12 ft. banks, bears NE. and SW.</p>
62.88	<p>True point for the W 1/16 sec. cor. of secs. 9 and 16, at proportionate dist., falls in a wash with 12 ft. banks, drains NE.; impractical to monument.</p>
63.30	<p>West bank of an eroded wash with 12 ft. banks, bears NE. and SW.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
83.84	<p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
20.105	<p>N. 1°39' E., bet. secs. 8 and 9.</p> <p>Over gently rolling land, through moderate undergrowth, parallel to gas line bearing N. and S.</p> <p>Point for the S 1/16 sec. cor. of secs. 8 and 9, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E S 1/16 S 8 S 9 1970</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located 73 lks. East of an underground gas line bearing irregularly N. and S.</p>	
40.21	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E 1/4 S 8 S 9 1970</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located 145 lks. East of bend in the underground gas line, bears S. and irregularly NW.</p>	
44.70	<p>Wash, 130 lks. wide, 1 ft. deep, drains E.</p>	
60.315	<p>Point for the N 1/16 sec. cor. of secs. 8 and 9, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E N 1/16 S 8 S 9 1970</p> <p>Set a wooden post, 3 ft. long, 2 ins. diam., alongside the iron post.</p> <p>The cor. is located 92 lks. East of a dim track road, bearing N. and S.</p>	

Dependent Resurvey, Portion Subdivisional Lines
 Fractional T. 15 S., R. 32 E.

CHAINS	
80.42	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{S\ 5}{S\ 8} \frac{S\ 4}{S\ 9}$ 1970</p> <p>Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, mesquite and cat claw.</p>
20.285	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°53' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the E 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E E 1/16 $\frac{S\ 4}{S\ 9}$ 1970</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p>
40.57	<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4} \frac{S\ 4}{S\ 9}$ 1970</p> <p>Set a mesquite post, 3 1/2 ft. long, 5 ins. diam., alongside the iron post.</p>
60.855	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	<p style="text-align: center;">T15S R32E W 1/16 $\frac{S\ 4}{S\ 9}$ 1970</p> <p>Set a wooden post, 2 x 3 ins. squared, 3 ft. long, alongside the iron post.</p>
61.50	Right bank of San Simon River, bears SE. and NW.
64.00	Left bank of San Simon River, bears SE. and NW.
81.14	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	<hr/> <p>N. 0°10' W., bet. secs. 4 and 5.</p> <p>Over nearly level land, through moderate undergrowth.</p>
40.19	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15S R32E $\frac{1}{2}$ S 5 S 4 1970</p> <p>Set a wooden post, 4 ft. long, 4 ins. square, alongside the iron post.</p> <p>The cor. is located 190 lks. West of the left bank of San Simon River, bears S. 30° E. and irregularly N.</p>
70.00	Left bank of San Simon River, bears S. 20° E. and N. 5° W.
75.00	Right bank of San Simon River, bears S. 20° E. and NW.
80.63	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 12 ins. above the ground, brass cap mkd.</p>
	<p style="text-align: center;">T14S R32E $\frac{S32}{S\ 5} \frac{S33}{S\ 4}$ T15S 1957</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, mesquite and cat claw.</p>

Dependent Resurvey, Portion Subdivisional Lines
 Fractional T. 15 S., R. 32 E.

CHAINS		
	<p>From the Standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 5 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">S C T15S R32E <u>S31 S32</u> 1913</p> <p>The cor. is located underneath a fence, 46 lks. N. of a fence cor.; fences extend N. 0°52' E. and E.</p> <p>N. 0°52' E., bet. secs. 31 and 32.</p> <p>Over gently rolling land, along N-S fence.</p>	
41.41	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E 1/4 <u>S31 S32</u> 1970</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located underneath a N. and S. fence.</p>	
82.82	<p>The sec. cor. of secs. 29, 30, 31 and 32, monumented by a volcanic stone, 9 x 5 x 4 ins., set 2 ins. in the ground, mkd. 5 notches on E. edge and 1 notch on S. edge.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E <u>S30 S29</u> <u>S31 S32</u> 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located at a fence cor.; fences extend S. 0° 52' W., S. 89°25' W. and N. 1°35' W.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, mesquite and cat claw.</p>	
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°11' W., bet. secs. 29 and 32.</p>	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	Over gently rolling land, through moderate undergrowth.
35.00	Dim track road, bears SE. and NW.
40.04	The 1/2 sec. cor. of secs. 29 and 32, monumented by a granite stone, 9 x 7 x 5 ins., set 2 ins. in the ground, mkd. 1/2 on N. face.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T15S R32E 1/2 $\frac{S29}{S32}$ 1970</p>
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone N. of the cor.
	<hr style="width: 20%; margin: auto;"/> <p>S. 88°53' W., beginning new measurement.</p>
	Over gently rolling land, through moderate undergrowth.
40.05	The cor. of secs. 29, 30, 31 and 32.
	Land, gently rolling.
	Soil, sandy clay loam.
	No timber; undergrowth, creosote bush, mesquite and cat claw.
	<hr style="width: 20%; margin: auto;"/> <p>S. 89°25' W., bet. secs. 30 and 31.</p>
	Over gently rolling land, along E-W fence.
39.91	The 1/2 sec. cor. of secs. 30 and 31, monumented by a granite stone, 8 x 5 x 3 ins., loosely set, mkd. 1/2 on one face.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T15S R32E 1/2 $\frac{S30}{S31}$ 1970</p>
	Bury the orig. cor. stone alongside the iron post.
	Set a wooden post, 4 ins. square, 2 1/2 ft. long, alongside the cor.
	The cor. is located underneath an E. and W. fence.
	<hr style="width: 20%; margin: auto;"/>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
42.41	<p>S. 86°48' W., beginning new measurement.</p> <p>Over gently rolling land, along E-W fence.</p> <p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 4 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T15S R31E R32E <u>S25 S30</u> S36 S31 1969</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
39.97	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 1°35' W., bet. secs. 29 and 30.</p> <p>Over nearly level land, along a N-S fence.</p> <p>The ¼ sec. cor. of secs. 29 and 30, monumented by a granite stone, 6 x 5 x 4 ins., set 2 ins. in the ground, mkd. ¼ on the W. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E ¼ <u>S30 S29</u> 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located underneath a N-S fence.</p>	
39.69	<p>N. 1°06' W., beginning new measurement.</p> <p>Over nearly level land, along a N-S fence.</p> <p>The point for the cor. of secs. 19, 20, 29 and 30, as determined latitudinally by proportionate measurement, and longitudinally by a N. and S. fence; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E <u>S19 S20</u> S30 S29 1970</p>	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
	<p>Set a cedar post, 4 ft. long, 4 ins. diam., alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
39.80	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°27' W., bet. secs. 20 and 29.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, monumented by a granite stone, 7 x 5 x 3 ins., set 2 ins. in the ground, mkd. $\frac{1}{4}$ on N. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4}$ $\frac{S20}{S29}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 2 ins. diam., alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°51' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
39.94	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
40.06	<p>S. 89°21' W., bet. secs. 19 and 30.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, monumented by a granite stone, 7 x 3 x 2 ins., loosely set, mkd. $\frac{1}{4}$ on one face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4}$ $\frac{S19}{S30}$ 1970</p>	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
40.68	<p>Bury the orig. cor. stone alongside the iron post.</p> <p>Set a mesquite post, 3 ft. long, 2½ ins. diam., alongside the cor.</p> <hr/> <p>S. 88°06' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 10 ins. above the ground, with a wooden post alongside, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R31E R32E S24 S19 S25 S30 1969</p> </div> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
39.33	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 1°07' W., bet. secs. 19 and 20.</p> <p>Over nearly level land, along a N-S fence.</p> <p>Track road, bears S. 80° E. and N. 80° W., curving N. 10° W.</p>
39.69	<p>The ¼ sec. cor. of secs. 19 and 20, monumented by a volcanic stone, 7 x 5 x 4 ins., set 2 ins. in the ground, mkd. ¼ on the W. face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E ¼ S19 S20 1970</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Deposit glass at the base of the iron post.</p> <p>The cor. is located underneath a N-S fence.</p> <hr/> <p>N. 1°06' W., beginning new measurement.</p> <p>Over nearly level land, along a N-S fence.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
39.94	<p>The cor. of secs. 17, 18, 19 and 20, monumented by a volcanic stone, 10 x 6 x 4 ins., set 2 ins. in the ground, mkd. 5 notches on E. edge and 3 notches on S. edge.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{S18}{S19} \frac{S17}{S20}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 5 lks. North of a railroad tie, set in the N-S fence.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
40.09	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 88°55' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented by a granite stone, 6 x 3 x 3 ins., set 2 ins. in the ground, mkd. $\frac{1}{4}$ on N. face and a mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{4} \frac{S17}{S20}$ 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>
40.00	<p>S. 89°16' W., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
39.84	<p>S. 89°25' W., bet. secs. 18 and 19.</p> <p>Over nearly level land, through moderate undergrowth, along the North side of a dim track road paralleling line.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T15S R32E} \\ \frac{1}{4} \frac{\text{S18}}{\text{S19}} \\ 1970 \end{array}$ <p>Raise a mound of stone N. of the cor.</p> <p>The cor. is located 18 lks. North of a dim track road, bears N. 89°25' E. and S: 89°25' W.</p>	
79.05	<p>Track road, bears irregularly N. and S.</p>	
79.57	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with a wooden post and an open pipe alongside, brass cap mkd.</p> $\begin{array}{r} \text{T15S} \\ \text{R31E R32E} \\ \frac{\text{S13} \text{S18}}{\text{S24} \text{S19}} \\ 1969 \end{array}$ <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
39.96	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°57' W., bet. secs. 17 and 18.</p> <p>Over nearly level land, along a N-S fence.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented by a granite stone, 5 x 4 x 3 ins., loosely set, mkd. $\frac{1}{4}$ on one face.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T15S R32E} \\ \frac{1}{4} \\ \text{S18} \text{S17} \\ 1970 \end{array}$ <p>Bury the orig. cor. stone alongside the iron post.</p>	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS					
	<p>The cor. is located at the cor. of a fence; fences extend E., S. 0°57' E. and N. 0°27' W.</p> <p style="text-align: center;">_____</p> <p>N. 0°27' W., beginning new measurement.</p> <p>Over nearly level land, along a N-S. fence.</p>				
40.08	<p>The cor. of secs. 7, 8, 17 and 18, which is marked by a wooden stake at a cor. of fences bearing S. 0°27' E. and S. 88°58' W. This position is harmoniously related to existing original corners and has been recognized as the cor. by local land owners and is accepted as the best existing evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E</p> <table border="1" style="margin: auto;"> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> </table> <p>1970</p> </div> <p>Set the wooden stake alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	S 7	S 8	S18	S17
S 7	S 8				
S18	S17				
0.35	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°08' W., bet. secs. 8 and 17.</p> <p>Over nearly level land, through moderate undergrowth.</p>				
39.86	<p>Underground gas line, bears N. and bears SE., 100 lks., thence S. 0°55' E.</p> <p>Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T15S R32E</p> <table border="1" style="margin: auto;"> <tr> <td>¼</td> <td>S 8</td> </tr> <tr> <td></td> <td>S17</td> </tr> </table> <p>1970</p> </div> <p>Set a mesquite post, 3½ ft. long, 2 ins. diam., alongside the iron post.</p>	¼	S 8		S17
¼	S 8				
	S17				
79.50	<p>Dim track road, bears irregularly N. and S.</p>				
79.72	<p>The cor. of secs. 7, 8, 17 and 18.</p>				

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS		
	<p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>	
39.64	<p>S. 89°49' W., bet. secs. 7 and 18.</p> <p>Over nearly level land, through moderate undergrowth, along the North side of an E. and W. fence.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E 1/4 $\frac{S\ 7}{S18}$ 1970</p>	
59.46	<p>Set a wooden post, 3 1/2 ft. long, 3 x 4 ins. squared, alongside the iron post.</p> <p>The cor. is located 72 lks. North of an E. and W. fence.</p> <p>Point for the W 1/16 sec. cor. of secs. 7 and 18, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E W 1/16 $\frac{S\ 7}{S18}$ 1970</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 41°10' W., 141 lks. dist.; fences bear N. 88°58' E., S. 88°58' W. and N. 1°15' W.</p> <p>Set a wooden post, 5 ft. long, 4 x 6 ins. squared, alongside the iron post.</p>	
60.43	<p>Fence, bears S. 1°15' E. and N. 1°15' W.</p>	
78.93	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by an iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, with a wooden post alongside, brass cap mkd.</p> <p style="text-align: center;">T15S R31E R32E $\frac{S12\ S\ 7}{S13\ S18}$ 1969</p>	

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
40.56	<p>From the cor. of secs. 7, 8, 17 and 18. N. 0°36' E., bet. secs. 7 and 8. Over nearly level land, through moderate undergrowth, along a dim track road bearing irregularly N. and S. Point for the $\frac{1}{2}$ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E $\frac{1}{2}$ S 7 S 8 1970</p> <p>Set a mesquite post, 3 ft. long, 2$\frac{1}{2}$ ins. diam., alongside the iron post.</p>
81.12	<p>The cor. of secs. 5, 6, 7 and 8, monumented by a wooden stake at a fence cor.; fences extend N. and W. This has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the position of the original cor. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E S 6 S 5 S 7 S 8 1970</p> <p>from which A bend of an underground gas line, bears NE., 53 lks. dist.; gas line bears N. and N. 89°43' E. Set the wooden stake alongside the cor.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
	<p>From the cor. of secs. 4, 5, 8 and 9. S. 89°43' W., bet. secs. 5 and 8.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
20.285	<p>Over nearly level land, through moderate undergrowth.</p> <p>Point for the E 1/16 sec. cor. of secs. 5 and 8, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
21.70	<p style="text-align: center;">T15S R32E E 1/16 $\frac{S 5}{S 8}$ 1970</p> <p>Set a wooden post, 4 ft. long, 4 ins. diam., alongside the iron post.</p>
40.57	<p>Junction of track road and underground gas line; track road, bears N. 60° E., irregularly S. and S. 89°43' W., gas line bears S. and S. 89°43' W.; thence along the South side of track road and underground gas line.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
80.77	<p style="text-align: center;">T15S R32E 1/4 $\frac{S 5}{S 8}$ 1970</p> <p>Set a wooden post, 5 ft. long, 4 ins. diam., alongside the iron post.</p> <p>The cor. is located 30 lks. South of a track road and underground gas line bearing N. 89°43' E. and S. 89°43' W.</p>
81.14	<p>Bend in track road and underground gas line, bears N. and N. 89°43' E.</p>
81.14	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, cacti, mesquite and cat claw.</p>
40.24	<p>S. 89°24' W., bet. secs. 6 and 7.</p> <p>Over nearly level land, through moderate undergrowth to the south of line only, along S. side of graded road from N. bearing W. and along cultivated field North of line.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T15S R32E 1/4 $\frac{S 6}{S 7}$ 1970</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS	
	<p>Set a wooden post, 4 ft. long, 2 x 6 ins. squared, alongside the iron post and raise a mound of stone N. of the cor.</p> <p>The cor. is located 16 lks. North of an E. and W. fence and 39 lks. South of a graded road bearing E. and W.</p>
42.67	<p>Fence cor., bears South, 16 lks. dist.; fences extend E. and S.; leave field areas, bears NE. and E., enter moderate undergrowth.</p>
80.19	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with a wooden post and mound of stone alongside, brass cap mkd.</p>
	<p style="text-align: center;">T15S R31E R32E <u>S 1 S 6</u> <u>S 12 S 7</u> 1969</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, mesquite and cat claw.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°02' W., bet. secs. 5 and 6.</p> <p>Over nearly level land, along E. side of a graded road from W. bearing N., through moderate undergrowth to the east only, cultivated fields west.</p>
36.60	<p>Fence cor.; fences extend E. and S.; leave undergrowth, enter open land.</p>
38.00	<p>Graded road, bears NE., 150 lks. dist., thence N. and bears SW., curving sharply to S.</p>
40.12	<p>Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T15S R32E <u>S 6 S 5</u> 1970</p> <p>from which</p> <p>The SW. cor. of a fence surrounding a farm house, bears N. 73°25' E., 181 lks. dist.</p> <p>The end pole of a powerline, bears S. 31°27' E., 49½ lks. dist.; powerline bears N.</p> <p>Set a wooden post, 4 ft. long, 2½ ins. diam., alongside the iron post and raise a mound of stone W. of the cor.</p>

Dependent Resurvey, Portion Subdivisional Lines
Fractional T. 15 S., R. 32 E.

CHAINS					
42.90	Field dyke, bears N. and SW. on a curve.				
80.12	Graded road, bears E. and W.				
80.40	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 10 ins. above the ground, brass cap mkd.				
<p>T14S R32E <table border="1" style="margin: auto;"> <tr> <td>S31</td> <td>S32</td> </tr> <tr> <td>S 6</td> <td>S 5</td> </tr> </table> T15S 1957</p>		S31	S32	S 6	S 5
S31	S32				
S 6	S 5				
The cor. is located on a field dyke bearing N. and S.					
<p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, creosote bush, mesquite and cat claw 1st half.</p>					
<p>General Description</p>					
<p>The area surveyed in Fractional Township 15 South, Range 32 East is located approximately 20 miles Southeast of San Simon, Arizona. The average elevation is about 3,850 ft. above sea level.</p>					
<p>The land is gently rolling in the east part of the township and nearly level in the west part. The soil is gravelly and sandy clay loam which supports creosote bush, mesquite and cat claw. The only good road, a track road, enters the township at the west boundary at the corner of sections 13, 18, 19 and 24, traverses southeasterly and leaves at the closing cor. of sections 26 and 35, on the E. bdy. of Tp.</p>					
<p>The only water noticed is at San Simon Cienega Dam No. 2, which is located in section 27. Drainage is towards the San Simon River which meanders northwesterly through the east portion of the township. The land is used primarily for the grazing of livestock. No mining activity was noted during the course of the survey.</p>					

CERTIFICATE OF SURVEY

(I) ~~(WE)~~ Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of April, 19 70, (I) ~~(WE)~~ have retraced a portion of the east boundary and made a dependent resurvey of a portion of the subdivisional lines, of fractional Township 15 South, Range 32 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 13, 1970
(Date)

Gary T. Oviatt
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date APR 17 1973

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the retracement of a portion of the east boundary and a dependent resurvey of a portion of the subdivisional lines of fractional Township 15 South, Range 32 East, of the Gila and Salt River Meridian, Arizona,

executed by Gary T. Oviatt

having been critically examined and found correct, are hereby approved.

JUN 25 1973
(Date)

Clark F. Mumm
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626