

Form 9180-6  
(April 1965)  
(formerly 4-679)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 18 NORTH, RANGE 11 EAST

TOWNSHIP 20 NORTH, RANGE 7 EAST

TOWNSHIP 20 NORTH, RANGE 8 EAST

TOWNSHIP 23 NORTH, RANGE 8 EAST

TOWNSHIP 24 NORTH, RANGE 7 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Harry K. Smith, Cadastral Surveyor

Under special instructions dated April 7, 19 72, which provided for the surveys  
included under Group Number 547, approved April 7, 1972,  
and assignment instructions dated April 7, 19 72.

Survey commenced April 24, 19 72

Survey completed May 22, 19 72

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Form 9180-29  
(March 1965)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# INDEX TO SECTION CORNER MONUMENTS

Tp. 18 N. R. 11 E. Mer. G&SR

	2					
2	6	5	4	3	2	1
1	3	3				
	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	24
	30	29	28	27	26	25
	31	32	33	34	35	36

Tp. 20 N. R. 7 E. Mer. G&SR

	6	5	4	3	2	1
	7	8	9	10	11	12
	18	17	16	15	14	13
	19	20	21	22	23	5 24
	30	29	28	27	26	4 25
	31	32	33	34	35	36

Tp. 20 N. R. 8 E. Mer. G&SR

	6	5	4	3	2	1
			9	7		
	7	8	9 8	10 7	11	12
			8	6		
	18	17	16	15	14	13
	19	20	21	22	23	24
	30	29	28	27	26	25
	31	32	33	34	35	36

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# INDEX TO SECTION CORNER MONUMENTS

Tp. 23 N. R. 8 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 24 N. R. 7 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. \_\_\_\_\_ R. \_\_\_\_\_ Mer. \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 18 North, Range 11 East  
 Township 20 North, Range 7 East  
 Township 20 North, Range 8 East  
 Township 23 North, Range 8 East  
 Township 24 North, Range 7 East  
 Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on April 7, 1972 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

---

Township 18 North, Range 11 East, G&SRM., Arizona

The south boundary was surveyed in 1883 by O. D. Wheeler.

The west boundary was surveyed in 1885 by J. C. Smith.

In 1905 E. C. Dietrich surveyed the east and north boundaries and subdivisional lines and resurveyed the south and west boundaries.

In 1917 Blout-Nash resurveyed the south one-half mile of the east boundary and S. E. Blout resurveyed the balance of the east boundary.

The north boundary was resurveyed by Matthews-Strickler in 1917.

---

Re monumentation, T. 18 N., R. 11 E., Arizona  
 The magnetic declination used was 14° East.

The cor. of secs. 1, 6, 7 and 12, T. 18 N., Rs. 10 & 11 E., monumented by a malpais stone, 12x7x6 ins., firmly set in a mound of stone, mkd. with 1 notch on the N. face and 5 notches on the S. face, from which the remaining orig. bearing trees

A cedar, 12 ins. diam., bears S. 38° E., 11 lks. dist., mkd. T18N R11E S7 BT. (Record bearing and dist., S. 24° E., 8 lks.).

A cedar, 10 ins. diam., bears S. 52° W., 14 lks. dist., mkd. T18N R10E S12 BT. (Record bearing and dist., S. 66° W., 17 lks.).

A cedar, 8 ins. diam., bears N. 62° W., 18 lks. dist., mkd. T18N R10E S1 BT. (Record bearing and dist., N. 59½° W., 21 lks.).

Remonumentation, T. 18 N., R. 11 E., Arizona

CHAINS

At the cor. point

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.

T18N  
 R10E R11E  
 $\frac{S}{S12} \frac{1}{S7} \frac{S}{S6}$   
 1972

Bury the orig. cor. stone alongside the iron post.

Cor. is on a NE. slope.

The  $\frac{1}{4}$  sec. cor. of secs. 1 and 6, T. 18 N., Rs. 10 and 11 E., monumented by a malpais stone, 16x10x4 ins., firmly set 10 ins. in the ground and in a mound of stone, mkd.  $\frac{1}{4}$  on the W. face, from which the orig. bearing trees

A cedar, 8 ins. diam., bears S. 56° E., 7 lks. dist., mkd.  $\frac{1}{4}$  S6 BT. (Record bearing and dist., S. 60° E., 5 lks.).

A cedar, 4 ins. diam., bears S. 80° W., 14 lks. dist., mkd.  $\frac{1}{4}$  S1 BT. (Record bearing and dist., S. 70° W., 4 lks.).

At the cor. point

Set the iron post 22 ins. in the ground, brass cap mkd.

T18N  
 R10E R11E  
 $\frac{1}{4}$   
 $\frac{S}{S1} \frac{1}{S6}$   
 1972

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. is located on a N. slope.

The North  $\frac{1}{4}$  sec. cor. of sec. 6 only, monumented by a malpais stone, 18x10x9 ins., firmly set 10 ins. in the ground, mkd.  $\frac{1}{4}$  on the S. face, from which the orig. bearing tree

A pinyon, 10 ins. diam., bears S. 40 $\frac{3}{4}$ ° W., 138 lks. dist., mkd. with a partially healed blaze with scribe marks visible. (Record dist., 139 lks.).

At the cor. point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

$\frac{1}{4}$  S 6  
 T18N R11E  
 1972

Remonumentation, T. 18 N., R. 11 E., Arizona

CHAINS

Bury orig. cor. stone in the mound of stone alongside the iron post.

Cor. is in a fenceline, bearing E. and W., and on the W. edge of a wash, 35 lks. wide, 3 ft. deep, draining N., curving northeasterly.

The  $\frac{1}{2}$  sec. cor. of secs. 7 and 8, monumented by a limestone, 18x12x10 ins., firmly set in a mound of stone, mkd.  $\frac{1}{2}$  on the W. face, from which the orig. bearing trees

A pinyon, 10 ins. diam., bears N. 60° E., 14 lks. dist., mkd.  $\frac{1}{2}$  S8 BT.

A cedar, 24 ins. diam., bears N. 38° W., 54 lks. dist., mkd. with a blaze on a limb, 6 ins. diam., with scribe marks  $\frac{1}{2}$  S7 BT. (Record bearing, N. 28° W.).

At the cor. point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T18N R11E

$\frac{1}{2}$   
S 7 | S 8  
1972

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 5, 6, 7 and 8, monumented by a malpais stone, 16x12x5 ins., firmly set 10 ins. in the ground, mkd. with 5 notches on the E. and S. faces, from which the remaining orig. bearing trees.

A cedar, 6 ins. diam., bears N. 55° E., 5 lks. dist., mkd. T18N R11E S5 BT.

A cedar, 6 ins. diam., bears S. 62° E., 30 lks. dist., mkd. T18N R11E S8 BT. (Record dist., 29 lks.).

A cedar, 6 ins. diam., bears N. 21 $\frac{1}{2}$ ° W., 18 lks. dist., mkd. T18N R11E S6 BT.

At the cor. point

Set the iron post 22 ins. in the ground, brass cap mkd.

T18N R11E

S 6 | S 5  
S 7 | S 8  
1972

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is in a cluster of cedar trees, 110 lks. S. of a graded road, bearing SE. and NW.

## Remonumentation, T. 20 N., R. 7 E., Arizona

CHAINS

Township 20 North, Range 7 East, G&amp;SRM., Arizona

The township boundaries and subdivisional lines were surveyed in 1878 by J. L. Harris.

In 1902 Caudle & Caudle resurveyed a portion of the E. boundary.

A portion of the N. boundary was resurveyed in 1965 by L. Murphy.

Portion of the cors. on the E. and W. boundaries and a portion of the subdivisional cors. were remonumented by W. Ott in 1966 and the  $\frac{1}{4}$  cor. of secs. 7 and 12 and the cor. of secs. 1, 6, 7 & 12 on the W. bdy. were remonumented by H. Thomas in 1968.

HES 379 and HES 380 were surveyed in 1915 by R.P.A. Johnson.

HES 619 was surveyed in 1921 by T. F. Myers and amended survey was made in 1928 by C. A. Long.

---

Remonumentation, T. 20 N., R. 7 E., Arizona  
The magnetic declination used was  $14\frac{1}{2}^{\circ}$  East.

---

The  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, monumented by a limestone, 23x16x4 ins., firmly set 12 ins. in the ground, and in a mound of stone, mkd.  $\frac{1}{4}$  on the N. face, from which the orig. bearing trees (Record calls for a post).

A ponderosa pine, 27 ins. diam., bears S.  $11^{\circ}$  W., 74 lks. dist., scribe marks visible. (Record bearing and dist., S.  $60^{\circ}$  E., 52 lks.).

A ponderosa pine, 25 ins. diam., bears N.  $9^{\circ}$  W., 90 lks. dist., scribe marks visible. (Record bearing and dist., North, 46 lks.).

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T20N R7E

$\frac{1}{4}$   $\frac{S24}{S25}$   
1972

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is located in an open area on top of a spur sloping N.

---

Remonumentation, T. 20 N., R. 7 E., Arizona

CHAINS

The  $\frac{1}{2}$  sec. cor. of secs. 23 and 24, monumented by a limestone, 26x14x6 ins., firmly set in a mound of stone, mkd.  $\frac{1}{2}$  on W. face, from which the remains of the orig. bearing trees (Record calls for a post).

A pine stump, 42 ins. diam., bears East, 105 lks. dist.

At the cor. point

Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R7E  
 $\frac{1}{2}$   
 S23 | S24  
 1972

from which.

A ponderosa pine, 10 ins. diam., bears N. 43° E., 27 lks. dist., mkd. T20N R7E  $\frac{1}{2}$  S24 BT.

A ponderosa pine, 16 ins. diam., bears S. 37° W., 36.5 lks. dist., mkd. T20N R7E  $\frac{1}{2}$  S23 BT.

Bury the orig. cor. stone in the mound of stone alongside the iron post.

The cor. is 26 lks. N. of a wash, draining easterly.

The  $\frac{1}{2}$  sec. cor. of secs. 13 and 24, monumented by a limestone, 19x10x7 ins., firmly set 10 ins. in the ground and in a mound of stone, mkd.  $\frac{1}{2}$  on the N. face; found remains of the orig. cor. post underneath the cor. stone, there was no evidence of the orig. bearing trees.

At the cor. point

Set the iron post 20 ins. in the ground, brass cap mkd.

T20N R7E  
 $\frac{1}{2}$   $\frac{S13}{S24}$   
 1972

from which

A ponderosa pine, 12 ins. diam., bears S. 13° E., 36 lks. dist., mkd. T20N R7E  $\frac{1}{2}$  S24 BT.

A ponderosa pine, 12 ins. diam., bears N. 26° W., 22 lks. dist., mkd. T20N R7E  $\frac{1}{2}$  S13 BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

## Remonumentation, T. 20 N., R. 8 E., Arizona

## CHAINS

Township 20 North, Range 8 East, G&SRM., Arizona

In 1878 J. L. Harris surveyed the west boundary and in 1879 he surveyed a portion of the north boundary (the 5th Standard Parallel North), the east and south boundaries and a portion of the subdivisional lines.

In 1883 A. E. Shoemaker resurveyed the east boundary.

In 1902 Caudle & Caudle resurveyed the east two miles and surveyed the west four miles of the north boundary (the 5th Standard Parallel North), and resurveyed a portion of the west boundary and subdivisional lines and completed the survey of the subdivisions.

In 1968 M. G. Livermore resurveyed a portion of the south boundary.

Portions of the corners on the south and west boundary were remonumented by W. Ott in 1966.

HES 379, 380 and 381 were surveyed by R.P.A. Johnson in 1915.

HES 381 was remonumented by the Forest Service in 1965.

---

Remonumentation, T. 20 N., R. 8 E., Arizona  
The magnetic declination used was  $14\frac{1}{2}^{\circ}$  East.

---

The cor. of secs. 10, 11, 14 and 15, monumented by a mound of stone (no evidence found of orig. cor. post as called for in record), from which the remains of the orig. bearing trees

A cedar, 17 ins. diam., bears N.  $75^{\circ}$  E., 48 lks. dist., scribe marks visible. (Record bearing and dist., N.  $78^{\circ}$  E., 46 lks.).

A stump hole, with a fallen pine, 20 ins. diam., lying alongside, bears S.  $2^{\circ}$  E., 178 lks. dist., tree has visible scribe marks.

A dead, partially burned pine, 22 ins. diam., bears S.  $5^{\circ}$  W., 222 lks. dist., mkd. T20N R8E S15 BT.

A stump hole, with a fallen pine, 27 ins. diam., lying alongside, bears N.  $1^{\circ}$  W., 140 lks. dist., tree has visible scribe marks.

At the cor. point

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R8E  
S10 | S11  
S15 | S14  
1972

## Remonumentation, T. 20 N., R. 8 E., Arizona

## CHAINS

from which

A cedar, 18 ins. diam., bears S. 60° E., 29 lks. dist., mkd. T20N R8E S14 BT.

A cedar, 5 ins. diam., bears S. 60° W., 154 lks. dist., mkd. T20N R8E S15 BT.

A cedar, 8 ins. diam., bears N. 16° W., 108.5 lks. dist., mkd. T20N R8E S10 BT.

Raise a mound of stone W. of the iron post.

The  $\frac{1}{2}$  sec. cor. of secs. 10 and 11, monumented by a mound of stone (No evidence found of orig. cor. post as called for in record), from which the orig. bearing trees

A cedar, 26 ins. diam., bears East, 7 lks. dist., scribe marks visible. (Record dist., 4 lks.).

A cedar, 24 ins. diam., bears S. 64° W., 34 lks. dist., mkd. with a partially healed blaze, scribe marks visible. (Record bearing and dist., S. 83° W., 33 lks.).

At the cor. point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R8E

$\frac{1}{2}$   
S10 | S11  
1972

The cor. of secs. 2, 3, 10 and 11, monumented by a rotted-off post, with a mound of stone to the W., from which the orig. bearing tree.

A ponderosa pine, 24 ins. diam., bears S. 0°30' W., 156 lks. dist., mkd. TXXN RVIIIIE X. (Record bearing and dist., S. 2 $\frac{1}{2}$ ° W., 153 lks.).

At the cor. point

Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.

T20N R8E

S 3 | S 2  
S10 | S11  
1972

from which

A cedar, 8 ins. diam., bears N. 46° E., 12 lks. dist., mkd. T20N R8E S2 BT.

A ponderosa pine, 9 ins. diam., bears S. 34° E., 92 lks. dist., mkd. T20N R8E S11 BT.

Remonumentation, T. 20 N., R. 8 E., Arizona

CHAINS

Rebuild the mound of stone W. of the iron post.

Set the remains of the orig. cor. post alongside the iron post.

The cor. of secs. 9, 10, 15 and 16, monumented by a rotted-off post, with a mound of stone to the W., from which the remaining orig. bearing trees

A ponderosa pine, 28 ins. diam., bears N. 40° E., 162 lks. dist., scribe marks visible. (Record dist., 161 lks.).

A dead pine, 32 ins. diam., bears S. 53° E., 186 lks. dist., mkd. with a rotted blaze. (Record bearing, S. 41° E.).

A ponderosa pine, 26 ins. diam., bears S. 75° W., 180 lks. dist., scribe marks visible. (Record dist., 178 lks.).

At the cor. point

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T20N R8E	
S 9	S10
S16	S15
1972	

from which

A ponderosa pine, 14 ins. diam., bears S. 74° E., 38 lks. dist., mkd. T20N R8E S15 BT.

A ponderosa pine, 6 ins. diam., bears N. 59½° W., 116 lks. dist., mkd. T20N R8E S9 BT.

Set the remains of the orig. cor. post alongside the iron post.

Rebuild the mound of stone W. of the iron post.

The ¼ sec. cor. of secs. 9 and 10, monumented by the remains of a rotted post, in a mound of stone, from which the orig. bearing trees

A ponderosa pine, 24 ins. diam., bears N. 49½° E., 217 lks. dist., mkd. with a partially healed blaze, scribe marks visible. (Record bearing and dist., N. 46° E., 215 lks.).

A ponderosa pine, 25 ins. diam., bears S. 62° W., 92 lks. dist., mkd. with a partially burned blaze, no marks visible. (Record bearing and dist., S. 31° W., 90 lks.).

At the cor. point

Remonumentation, T. 20 N., R. 8 E., Arizona

CHAINS

Set the iron post 22 ins. in the ground, brass cap mkd.

T20N R8E  
 $\frac{1}{2}$   
 S 9 | S10  
 1972

Set the remains of the orig. cor. post alongside the iron post.

Raise a mound of stone W. of the iron post.

The cor. of secs. 3, 4, 9 and 10, monumented by a wooden stake, 2 ins. diam., 2 ft. long, firmly set in a mound of stone, from which the orig. bearing trees

A cedar, 22 ins. diam., bears N. 68° E., 60 lks. dist., mkd. TXXN RVIIIIE III. (Record bearing and dist., N. 78° E., 58 lks.).

A cedar, 16 ins. diam., bears S. 80½° E., 59 lks. dist., mkd. TXXN RVIIIIE X. (Record bearing, S. 87° E.).

A cedar, 28 ins. diam., bears S. 85° W., 87 lks. dist., mkd. TXXN RVIIIIE VIII. (Record bearing and dist., S. 70° W., 82 lks.).

A cedar, 16 ins. diam., bears N. 46° W., 99 lks. dist., mkd. TXXN RVIIIIE IV. (Record bearing and dist., N. 57° W., 96 lks.).

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T20N R8E  
 S 4 | S 3  
 S 9 | S10  
 1972

Raise a mound of stone W. of the iron post.

Bury the orig. wooden cor. stake alongside the iron post.

Remonumentation, T. 23 N., R. 8 E., Arizona

CHAINS

Township 23 North, Range 8 East, G&SRM., Arizona

In 1883 the south boundary was surveyed by O. D. Wheeler.

In 1894 Oury-Perkins surveyed the west boundary.

In 1902 J. A. Lamport surveyed the east and north boundaries and subdivisional lines and resurveyed the south boundary and a portion of the west boundary.

In 1966 W. Ott remonumented a portion of the corners on the south boundary and a portion of the subdivisional corners.

HES 376 was surveyed in 1917 by R.P.A. Johnson.

---

Remonumentation, T. 23 N., R. 8 E., Arizona  
The magnetic declination used was  $14\frac{1}{2}^{\circ}$  East.

---

The cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented by a malpais stone, 16x14x10 ins., firmly set 10 ins. in the ground, mkd. with 4 notches on the N. edge and 2 notches on the S. edge, from which the remains of the orig. bearing trees

A yellow pine, 22 ins. diam., bears S.  $82^{\circ}$  E., 80 lks. dist., mkd. with a partially healed blaze, scribe marks visible. (Record bearing and dist., S.  $69^{\circ}$  E., 78 lks.).

A stump hole, bears S.  $49^{\circ}$  W., 53 lks. dist.

A yellow pine, 18 ins. diam., bears N.  $6^{\circ}$  W., 73 lks. dist., mkd. with a partially healed blaze, scribe marks visible. (Record dist., 72 lks.).

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T23N	T23N
S24	R9E
S25	S19
R8E	
	1972

from which

A yellow pine, 24 ins. diam., bears S.  $54^{\circ}$  W., 78 lks. dist., mkd. T23N R8E S25 BT.

Bury the orig. cor. stone alongside the iron post.

---

## Remonumentation, T. 23 N., R. 8 E., Arizona

## CHAINS

The  $\frac{1}{2}$  sec. cor. for sec. 24 only, on the E. bdy. of the Tp., monumented by a lava stone, 17x16x12 ins., firmly set 12 ins. in the ground, mkd.  $\frac{1}{2}$  on the W. face, from which the only remaining bearing tree

A ponderosa pine, 22 ins. diam., bears S. 59° W., 79 lks. dist., mkd. with a partially healed blaze, scribe marks visible.

At the cor. point

Set the iron post 20 ins. in the ground, brass cap mkd.

	T23N	
$\frac{1}{2}$	S24	
	R8E	
	1972	

Raise a mound of stone W. of the cor.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented by a malpais stone, 18x13x12 ins., firmly set 12 ins. in the ground, mkd. with 3 notches each on the N. and S. edges with a mound of stone to the N., from which the remains of the orig. bearing trees

A yellow pine, 30 ins. diam., bears S. 37° E., 120 lks. dist., mkd. with visible scribe marks. (Record bearing and dist., S. 60°45' E., 75 lks.).

A stump hole, with an uprooted yellow pine, 20 ins. diam., lying alongside, bears S. 34 $\frac{1}{2}$ ° W., 284 lks. dist., tree mkd. T23N R8E S24 BT.

At the cor. point

Set the iron post 22 ins. in the ground, brass cap mkd.

	T23N	T23N	
	S13	R9E	
	S24	S18	
	R8E		
	1972		

from which

A ponderosa pine, 8 ins. diam., bears S. 54° W., 111 lks. dist., mkd. T23N R8E S24 BT.

A ponderosa pine, 8 ins. diam., bears N. 30° W., 47 lks. dist., mkd. T23N R8E S13 BT.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. is on an E. slope.

Remonumentation, T. 23 N., R. 8 E., Arizona

CHAINS

The cor. of secs. 23, 24, 25 and 26, monumented by a lava stone, 19x14x8 ins., firmly set 12 ins. in the ground, mkd. with one notch on the E. face and 2 notches on the S. face, with a mound of stone to the W., from which the orig. bearing trees

A dead yellow pine, 20 ins. diam., bears N.  $32\frac{1}{2}^\circ$  E., 54 lks. dist., mkd. T23N R8E S24 BT. (Record bearing, N.  $26^\circ$  E.).

A yellow pine, 27 ins. diam., bears S.  $75\frac{1}{2}^\circ$  E., 57 lks. dist., mkd. with a partially healed blaze, scribe marks visible. (Record bearing, S.  $73^\circ$  E.).

A dead yellow pine, 15 ins. diam., bears S.  $61\frac{1}{2}^\circ$  W., 68 lks. dist., mkd. T23N R8E S26 BT. (Record bearing and dist., S.  $63^\circ 30'$  W., 62 lks.).

A dead yellow pine, 16 ins. diam., bears N.  $30^\circ$  W., 62 lks. dist., mkd. T23N R8E S23 BT.

At the cor. point

Set the iron post 22 ins. in the ground, brass cap mkd.

T23N R8E	
S23	S24
S26	S25
1972	

from which

A pinyon, 8 ins. diam., bears N.  $7^\circ$  E., 13 lks. dist., mkd. T23N R8E S24 BT.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. is located on a S. slope.

The  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, monumented by a lava stone, 22x12x10 ins., firmly set 12 ins. in the ground, mkd.  $\frac{1}{4}$  on the N. face, with a mound of stone to the N., from which the orig. bearing trees

A yellow pine, 26 ins. diam., bears N.  $1^\circ$  E., 136 lks. dist., mkd. with a healed blaze. (Record dist., 140 lks.).

A yellow pine, 18 ins. diam., bears N.  $17^\circ$  W., 57 lks. dist., mkd. with a healed blaze. (Record bearing and dist., S.  $22^\circ$  W., 52 lks.).

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T23N R8E	
$\frac{1}{4}$ S24	S25
1972	

Remonumentation, T. 23 N., R. 8 E., Arizona

CHAINS

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 22, 23, 26 and 27, monumented by a lava stone, 24x8x8 ins., firmly set 16 ins. in the ground and in a mound of stone, mkd. with 2 notches each on the E. and S. faces, from which the remains of the orig. bearing trees

A yellow pine, 30 ins. diam., bears N. 43° E., 231 lks. dist.; mkd. with a healed blaze.

A stump hole, with an uprooted pine tree, 24 ins. diam., lying alongside, bears S. 54° E., 140 lks. dist., tree has visible scribe marks.

A yellow pine, 34 ins. diam.; bears S. 72½° W., 69 lks. dist., mkd. T23N R8E S27 BT. (Record dist., 70 lks.).

A yellow pine, 24 ins. diam., bears N. 22° W., 199 lks. dist., mkd. with a healed blaze.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T23N R8E  
S22 | S23  
S27 | S26  
1972

Raise a mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 22 and 23, monumented by a lava stone, 32x10x6 ins., firmly set 18 ins. in the ground, mkd. ¼ on W. face, from which the remains of the orig. bearing trees

A pine stump, 36 ins. diam., bears N. 22°13' E., 42 lks. dist., no marks visible.

A pine stump, 28 ins. diam., bears S. 51½° W., 75 lks. dist., no marks visible.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T23N R8E  
¼  
S22 | S23  
1972

from which

A ponderosa pine, 10 ins. diam., bears S. 15° E., 7 lks. dist., mkd. T23N R8E ¼ S23 BT.

Remonumentation, T. 23 N., R. 8 E., Arizona

CHAINS

A ponderosa pine, 8 ins. diam., bears N. 22° W.,  
61 lks. dist., mkd. T23N R8E ½ S22 BT.

Bury the orig. cor. stone alongside the iron post.

The cor. is on a N. slope, 2.50 chs. S. of Hwy. 545, a  
two lane black top road, bearing E. and W.

The ¼ sec. cor. of secs. 22 and 27, monumented by a  
malpais stone, 17x13x7 ins., firmly set 10 ins. in the  
ground, mkd. ¼ 22 on the N. face and 27 on the S. face,  
from which the remains of the orig. bearing trees

A stump hole, bears N. 40° E., 35 lks. dist.

A yellow pine, 30 ins. diam., bears S. 12½° E.,  
103 lks. dist., mkd. with a healed blaze.

At the cor. point

Set the iron post 22 ins. in the ground, brass cap mkd.

T23N R8E  
¼  $\frac{S22}{S27}$   
1972

from which

A ponderosa pine, 30 ins. diam., bears N. 3½° E.,  
84 lks. dist., mkd. T23N R8E ½ S22 BT.

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. is on an E. slope, 3.50 chs. W. of a track road,  
bearing S. 30° E. and N. 30° W.

The ¼ sec. cor. of secs. 21 and 22, monumented by a mal-  
pais stone, 20x12x9 ins., firmly set 16 ins. in the  
ground, mkd. ¼ S21 on the W. face and S22 on the E. face,  
with a mound of stone to the W., from which the remains  
of an orig. bearing tree

A pine stump, 10 ins. diam., bears S. 64° W.,  
12 lks. dist., no marks visible.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T23N R8E  
¼  
S21 | S22  
1972

Remonumentation, T. 23 N., R. 8 E., Arizona

CHAINS

from which

A ponderosa pine, 7 ins. diam., bears N. 29° E.,  
64 lks. dist., mkd. T23N R8E ¼ S22 BT.

A ponderosa pine, 30 ins. diam., bears S. 47° W.,  
14 lks. dist., mkd. T23N R8E ¼ S21 BT.

A steel fence post, projecting 4½ ft. above the  
ground, bears West, 9 lks. dist.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 15 and 22, monumented by a lava  
stone, 20x16x10 ins., firmly set in a mound of stone,  
mkd. ¼ on N. face, with a mound of stone to the N.

At the cor. point

Set the iron post over an "X" chiseled in solid lava rock  
mound of stone to top, brass cap mkd.

T23N R8E

¼  $\frac{S15}{S22}$

1972

Raise a large mound of stone N. of the iron post.

Deposit the orig. cor. stone in the mound of stone along-  
side the iron post.

The cor. is located in a lava bed.

The ¼ sec. cor. of secs. 32 and 33, monumented by a mal-  
pais stone, 24x14x12 ins., firmly set 12 ins. in the  
ground, mkd. ¼ on the W. face, from which the only re-  
maining orig. bearing tree

A yellow pine, 24 ins. diam., bears S. 7° E., 56  
lks. dist., mkd. ¼ S33 BT.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T23N R8E

¼  $\frac{S32}{S33}$

1972

from which

A ponderosa pine, 5 ins. diam., bears N. 41° W.,  
21 lks. dist., mkd. T23N R8E ¼ S32 BT.

Raise a mound of stone W. of the iron post.

## Remonumentation, T. 23 N., R. 8 E., Arizona

## CHAINS

Bury the orig. cor. stone alongside the iron post.

The cor. is in a fenceline, bearing irregularly N. and S. and 2.00 chs. E. of an underground telephone cable, bearing N. and S.

The  $\frac{1}{4}$  sec. cor. of secs. 28 and 33, monumented by a malpais stone, 18x10x8 ins., firmly set 8 ins. in the ground, mkd.  $\frac{1}{4}$  on the N. face, with a mound of stone to the N., there is no evidence of the orig. bearing trees.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

$$\begin{array}{r} T23N R8E \\ \frac{1}{4} \frac{S28}{S33} \\ 1972 \end{array}$$

from which

A ponderosa pine, 10 ins. diam., bears S.  $59\frac{1}{2}^{\circ}$  W., 63 lks. dist., mkd. T23N R8E  $\frac{1}{4}$  S33 BT.

A ponderosa pine, 12 ins. diam., bears N.  $5^{\circ}$  W., 91 lks. dist., mkd. T23N R8E  $\frac{1}{4}$  S28 BT.

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 28 and 29, monumented by a volcanic stone, 16x13x12 ins., firmly set 15 ins. in the ground, mkd.  $\frac{1}{4}$  on the W. face, with a mound of stone to the W., from which the remains of the orig. bearing trees

A pine stump, 18 ins. diam., bears S.  $12^{\circ}$  E., 38 lks. dist., no marks.

A ponderosa pine, 30 ins. diam., bears N.  $74^{\circ}$  W., 14 lks. dist., mkd.  $\frac{1}{4}$  S29 BT.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

$$\begin{array}{r} T23N R8E \\ \frac{1}{4} \frac{S29}{S28} \\ 1972 \end{array}$$

from which

A ponderosa pine, 8 ins. diam., bears S.  $44^{\circ}$  E., 48 lks. dist., mkd. T23N R8E  $\frac{1}{4}$  S28 BT.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. is on a NW. slope.

Remonumentation, T. 24 N., R. 7 E., Arizona

CHAINS

Township 24 North, Range 7 East, G&SRM., Arizona

The north boundary (the 6th Standard Parallel North), and the east, south and west boundaries and subdivisional lines were surveyed in 1883 by A. E. Shoemaker.

The north and the south boundaries were resurveyed in 1894 by Oury Perkins.

The east boundary was resurveyed in 1902 by J. A. Lamport.

The west boundary was resurveyed in 1944 by White and Wakeman.

Portions of the corners on the east boundary were remonumented in 1968 by H. Thomas.

Remonumentation, T. 24 N., R. 7 E., Arizona  
The magnetic declination used was  $14\frac{1}{2}^{\circ}$  East

The cor. of secs. 8, 9, 16 and 17, monumented by a lava stone, 14x10x4 ins., firmly set in a mound of stone, mkd. with 4 notches on the E. face and 4 notches on the S. face, from which the orig. bearing trees

A pinyon, 16 ins. diam., bears N.  $27^{\circ}$  E., 85 lks. dist., mkd. T24N R7E S9 BT. (Record bearing and dist., N.  $40^{\circ}$  E., 75 lks.).

A dead pine, 26 ins. diam., bears S.  $12^{\circ}$  E., 68 lks. dist., mkd. T24N R7E S16 BT. (Record bearing, S.  $20^{\circ}$  E.).

A pinyon, 14 ins. diam., bears S.  $40^{\circ}$  W., 54 lks. dist., mkd. T24N R7E S17 BT. (Record bearing, S.  $45^{\circ}$  W.).

At the cor. point

Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.

T24N R7E	
S 8	S 9
S17	S16
1972	

from which

A ponderosa pine, 7 ins. diam., bears S.  $69^{\circ}$  E., 60 lks. dist., mkd. T24N R7E S16 BT.

A ponderosa pine, 8 ins. diam., bears N.  $32^{\circ}$  W., 60 lks. dist., mkd. T24N R7E S8 BT.

Bury the orig. cor. stone in the mound of stone alongside the iron post.



CERTIFICATE OF SURVEY

(I) ~~(We)~~ Harry K. Smith, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of April, 19 72, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 18 North, Range 11 East, Township 20 North, Range 7 East, Township 20 North, Range 8 East, Township 23 North, Range 8 East and Township 24 North, Range 7 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 12, 1972  
(Date)

*Harry K. Smith*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date NOV 3 1972

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 18 North, Range 11 East, Township 20 North, Range 7 East, Township 20 North, Range 8 East, Township 23 North, Range 8 East and Township 24 North, Range 7 East, all of the Gila and Salt River Meridian, Arizona, executed by Harry K. Smith, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

OCT 29 1973  
(Date)

*Clark F. Gunn*  
(Chief, Division of Cadastral Survey)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Cadastral Survey) GPO 849-626~~