

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

Dependent Resurvey

of the

East Boundary

a

Portion of the West Boundary

a

Portion of the North Boundary

and a

Portion of the Subdivisional Lines

and

Survey

of

Subdivisions of Certain Sections

Township 14 North, Range 26 East

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Louis D. Gilbert

Cadastral Surveyor

Paul G. Bauer

Cadastral Surveyor

Under special instructions dated March 29, 19 68, which provided for the surveys

included under Group Number 481, approved April 3, 1968,

and assignment instructions dated April 5, 19 68
July 10, 19 72.

Survey commenced April 18, 19 68

Survey completed November 7, 19 72

1A

BOOK 4987

INDEX DIAGRAM

Township 14 North, Range 26 East

9					
8 6 34	34 5	31 4 30	27 3 27	21 2 21	15 1 5 15
7	8	9	26 10 25	20 11 19	14 12 5 13
18	17	16	24 15 24	18 14 18	12 13 4 12
19 33	20	21 29	23 22 23	17 23 16	11 24 3 11
6 30 32	33 29	29 28 28	22 27	16 26	10 25 2
31	32	33	34	35	36 1

- Subdivision, Sec. 4, page 35
- Subdivision, Sec. 6, page 37
- Subdivision, Sec. 10, page 40
- Subdivision, Sec. 14, page 41
- Subdivision, Sec. 22, page 43
- Subdivision, Sec. 24, page 44

12

Township 14 North, Range 26 East
Gila and Salt River Meridian, Arizona

CHAINS

The south and east boundaries were surveyed in 1875 by C. B. Foster. The south two miles of the east boundary was retraced in 1944 by Forrest and Warner. The north one mile of the east boundary was retraced by Owens, Bauer and Ott in 1963-64. The west boundary was surveyed in 1875 by C. B. Foster. The north four miles of the west boundary was retraced in 1944 by Forrest and Warner. The north boundary was surveyed in 1875 by C. B. Foster, resurveyed in 1882 by O. D. Wheeler, retraced in 1944 by Forrest and Warner and resurveyed in 1963-64 by Owens, Bauer and Ott. The subdivisional lines were surveyed in 1875 by C. B. Foster. A portion of the subdivisional lines were retraced in 1944 by Forrest and Warner.

The following field notes are those of a dependent resurvey of the east boundary, a portion of the west and north boundaries, and a portion of the subdivisional lines, designed to restore the corners in their true original locations according to the best available evidence, and a survey of subdivisions in certain sections in Township 14 North, Range 26 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 29, 1968. The direction of all lines were determined by solar observation and all lines refer to the true meridian.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of the township as determined by calculation from that given for the southeast corner of Township 15 North, Range 26 East, as shown on the plat approved August 31, 1964 is: Latitude 34°34'04.2" N. and Longitude 109°31'29.8" W.

The mean magnetic declination was found to be 14° East.

Dependent Resurvey of the East Boundary,
T. 14 N., R. 26 E., G&SRM., Arizona

Reestablishment of the Survey executed
by C. B. Foster in 1875

Beginning at the cor. of Tps. 13 and 14 N., Rs. 26 and 27 E., monumented by a volcanic stone, 24x14x12 ins., firmly set in a mound of stone, mkd. with 6 grooves on N., E., S. and W. faces .

At the corner point

Dependent Resurvey of the East Boundary,
T. 14 N., R. 26 E.

CHAINS	
	<p>Set the iron post, 20 ins. in the ground, collar of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T14N R26E R27E <u>S36 S31</u> S 1 S 6 T13N R26E R27E 1968</p> <p>Deposit the orig. cor. stone in the collar of stone alongside the cor.</p> <p>N. 4°30' W., bet. secs. 31 and 36.</p> <p>Over rolling land, through scattered juniper.</p>
1.30	Underground gas line, bears S. 60° E. and N. 60° W.
18.00	Bladed road, bears S. 60° E. and N. 60° W.
21.60	Wash, 30 lks. wide, 3 ft. deep, drains W.
41.235	Point for the ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
69.15	Fence, bears S. 50° E. and N. 50° W.
77.20	Wash, 3.00 chs. wide, with 15 ft. banks, drains E.
82.47	Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
	<p>Land, rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>
	<p>N. 4°30' W., bet. secs. 25 and 30.</p> <p>Over rolling land through scattered juniper.</p>
20.00	Track road, bears N. 25° E. and S. 25° W.
33.00	Track road, bears SE. and NW.
36.50	Wash, 10 lks. wide, 2 ft. deep, drains NW.
41.235	Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
51.60	Leave scattered cedar timber, bears irregularly E. and W.
52.40	Track road, bears NE. and SW.
57.50	Track road, bears N. 80° E. and S. 80° W.
64.15	Fence, bears East, 4.76 chs. dist. to cor. of fences bearing NE., S. and W.

Dependent Resurvey of the East Boundary,
T. 14 N., R. 26 E.

CHAINS	
65.20	Left bank, Little Colorado River, a cut bank, 8 ft. high, bears S. 70° E. and N. 70° W.
65.60	Little Colorado River, 2.60 chs. wide, 2 ft. deep, course N. 70° W.
67.80	Right bank, Little Colorado River, a cut bank, 8 ft. high, bears S. 70° E. and N. 70° W.
76.80	Track road, bears S. 80° E. and N. 80° W.
82.47	Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
	Land, rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.
	N. 4°30' W., bet. secs. 19 and 24.
	Over gently rolling land.
13.90	Old fence line, bears S. 70° E. and N. 70° W.
31.50	Enter scattered cedar timber, bears irregularly E. and W., thence over rolling land.
41.235	Point for the ½ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post, 14 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.
	<p style="text-align: center;">T14N R26E R27E ½ S24 S19 1972</p>
46.80	Leave scattered cedar timber and enter railed area, bears irregularly E. and W.
49.00	Track road, bears N. 30° E. and S. 30° W.
82.47	The cor. of secs. 13, 18, 19 and 24, marked by a cor. of fences bearing irreg. N., E. and W. There is no remaining evidence of the orig. cor. monument. This fence cor. has been used by adjacent landowners for many years and is accepted as the best remaining evidence of the orig. cor. position.
	At the cor. point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T14N R26E R27E S13 S18 S24 S19 1972</p>

Dependent Resurvey of the East Boundary,
T. 14 N., R. 26 E.

CHAINS		
	<p>Raise a mound of stone, 1½ ft. base, 1 ft. high, W. of the cor.</p> <p>Land, gently rolling to rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>	
	<p>N. 0°03' E., bet. secs. 13 and 18.</p> <p>Over rolling land, through scattered timber.</p>	
13.40	Track road, bears E. and W.; leave timber and enter clearing, bears same.	
39.72	<p>Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R26E R27E ¼ S13 S18 1972</p> </div>	
	<p>Set a wooden post, 4 ft. long, 4 ins. squared, alongside the cor.</p> <p>The cor. is located 6 lks. W. of a N-S fenceline.</p>	
43.40	Leave clearing, bears irregularly E. and W.; enter scattered juniper, bears same.	
79.44	<p>The cor. of secs. 7, 12, 13 and 18, monumented by a limestone, 16x14x8 ins., no visible marks, loosely set at a cor. of fences extending irreg. E., S. and W., no other stones in vicinity. This stone is accepted as the best remaining evidence of the orig. cor.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R26E R27E S12 S 7 S13 S18 1972</p> </div> <p>Bury the limestone along the W. side of the cor.</p> <p>Land, rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>	

Dependent Resurvey of the East Boundary,
T. 14 N., R. 26 E.

CHAINS		
	N. 1°23' E., bet. secs. 7 and 12.	
	Over rolling land, through scattered cedar.	
21.00	Track road, bears NE. and SW.	
39.94	Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 20 ins. in the ground, brass cap mkd.	
	T14N	
	R26E R27E	
	¼	
	S12 S 7	
	1968	
	Set a cedar post, 6 ft. long, 3 ins. squared, alongside the cor.	
69.00	Leave scattered timber, bears irregularly E. and W.	
79.88	The cor. of secs. 1, 6, 7 and 12 monumented by a wooden post, 18 ins. long, 3 ins. squared, firmly set 12 ins. in the ground, dimly scribed with 3 notches on S. edge; no other markings legible.	
	At the cor. point.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	T14N	
	R26E R27E	
	S 1 S 6	
	S12 S 7	
	1968	
	Bury the orig. cor. post alongside the iron post.	
	Set a wooden post, 4 ft. long, 4 ins. squared alongside the cor.	
	Land, rolling to gently rolling.	
	Soil, sandy clay loam.	
	Timber, scattered cedar.	
	Undergrowth, sagebrush and bunchgrass.	
	N. 3°55' E., bet. secs. 1 and 6.	
	Over gently rolling land.	
2.30	Track road, bears N. 70° E. and S. 70° W.	
24.90	Track road, bears S. 70° E. and N. 70° W.	
26.00	Point for the S 1/16 sec. cor. of secs. 1 and 6, at proportionate dist.	
	Set the iron post, 18 ins. in the ground, brass cap mkd.	

Dependent Resurvey of the East Boundary,
T. 14 N., R. 26 E.

CHAINS		
	<p>T14N R26E R27E S 1/16 S 1 S 6 1968</p> <p>Raise a mound of stone W. of the cor.</p>	
31.60	Fence, bears E. and W.	
40.20	Zuni River, 70 lks. wide, 3 ft. deep, course W.	
52.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 18 ins. in the ground, brass cap mkd.	
	<p>T14N R26E R27E $\frac{1}{4}$ S 1 S 6 1968</p> <p>Raise a mound of stone W. of the cor.</p>	
53.90	Fence, bears E. and W.	
57.90	Track road, bears N. 60° E. and S. 60° W.	
78.00	Point for the N 1/16 sec. cor. of secs. 1 and 6, at proportionate dist.	
	Set the iron post 18 ins. in the ground, brass cap mkd.	
	<p>T14N R26E R27E N 1/16 S 1 S 6 1968</p> <p>Raise a mound of stone, 2 ft. base, 1$\frac{1}{2}$ ft. high, W. of the cor.</p>	
104.00	The cor. of Tps. 14 and 15 N., Rs. 26 and 27 E., monumented by an iron post, 2 $\frac{1}{2}$ ins. diam., 6 ins. above ground firmly set, with mound of stone S., brass cap mkd.	
	<p>T15N R26E R27E S36 S31 S 1 S 6 R26E R27E T14N 1963</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, sagebrush.</p>	
<p>Dependent Resurvey, Portion West Boundary, T. 14 N., R. 26 E.</p>		

Dependent Resurvey, Portion West Boundary,
T. 14 N., R. 26 E.

CHAINS

Reestablishment of the Survey executed
by C. B. Foster in 1875

From the cor. of sections 25, 30, 31 and 36, on the W. bdy.
of the Tp., as determined by record course and distance
from the original bearing tree:

A cedar, 20 ins. diam., bears S. 7° E., 208 lks.
dist., mkd. T XIV N R XXVI E S XXXI.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T14N
R25E R26E
S25 | S30
S36 | S31
1968

Set a cedar post, 4 ft. long, 4 ins. squared alongside
the cor.

N. 1°18' W., bet. secs. 25 and 30.

Over rolling land, through scattered cedar timber.

- 1.83 Highway R-0-W fence, bears S. 25° E. and N. 25° W.
4.50 U.S. Highway No. 260, bears S. 25° E. and N. 25° W.
7.50 Highway R-0-W fence, bears S. 25° E. and N. 25° W.
7.60 Power line, bears S. 25° E. and N. 25° W.
8.50 Wash, 10 lks. wide, 2 ft. deep, drains N. 70° E.
13.40 Track road, bears E. and W.
39.47 The $\frac{1}{4}$ sec. cor. of secs. 25 and 30 monumented by a $\frac{1}{2}$ in.
re-bar, 2 $\frac{1}{2}$ ft. long, firmly set and substantiated by
record distance from the orig. bearing trees:

A cedar, 8 ins. diam., bears N. 70°15' E., 52
lks. dist., mkd. VIX S BT. (Record N. 5° E.)

A cedar, 10 ins. diam., bears S. 3°30' W., 118
lks. dist., mkd. VIX BT. (Record S. 21° W.)

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T14N
R25E R26E
 $\frac{1}{4}$
S25 | S30
1968

Bury the re-bar alongside the iron post.

Set a wooden post, 5 ft. long, 4 ins. squared, alongside
the cor.

N. 1°23' W., beginning new measurement.

Over rolling land, through scattered juniper.

Dependent Resurvey, Portion West Boundary,
T. 14 N., R. 26 E.

CHAINS	
39.86	<p>The cor. of secs. 19, 24, 25, and 30, monumented by an iron post, 3 ins. diam., firmly set in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">LACY C. GREER ENG. CO. R25E R26E 24 19 25 30 T14N 1964</p> <p>This cor. is used by adjacent landowners and local surveyors and is accepted as the best available evidence of the orig. cor. position; not remonumented. There is no remaining evidence of the orig. bearing tree.</p> <p>Land, rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp. This cor. position is marked by a cor. of fences bearing N., E. and W. and is used by adjacent landowners and is accepted as the best available evidence of the orig. cor. position; not monumented.</p> <p>from which</p> <p style="text-align: center;">Cor. of fences bears East, 25 lks. dist., fences bear E., S. and W.</p> <p>N. 11°21' E., bet. secs. 1 and 6.</p> <p>Over nearly level land.</p>
41.72	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p>
42.30	<p>Wash, 10 lks. wide, 2 ft. deep, drains N. 85° W.</p>
62.58	<p>Point for the N 1/16 sec. cor. of secs. 1 and 6, at proportionate dist.; not monumented.</p>
67.50	<p>Zuni River, 10 lks. wide, 2 ft. deep, course W.</p>
83.44	<p>The cor. of Tps. 14 and 15 N., Rs. 25 and 26 E., monumented by an iron post, 2½ ins. diam., 10 ins. above ground, firmly set, mound of stone S., brass cap mkd.</p> <p style="text-align: center;">T15N R25E R26E S36 S31 S 1 S 6 T14N 1963</p> <p>Land, nearly level to gently rolling. Soil, sandy clay loam. No timber, undergrowth, sagebrush and bunchgrass.</p>

Dependent Resurvey, Portion North Boundary,
T. 14 N., R. 26 E.

CHAINS

Dependent Resurvey, Portion North Boundary,
T. 14 N., R. 26 E.

Reestablishment of the Resurvey executed
by Owens, Bauer and Ott in 1963

From the cor. of secs. 5, 6, 31 and 32, on the N. bdy.
of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam.,
10 ins. above ground, firmly set, with mound of stone W.,
brass cap mkd.

T15N R26E
S31 | S32
S 6 | S 5
T14N R26E
1963

S. $83^{\circ}22'$ W., bet. secs. 6 and 31.

Over gently rolling land.

29.30

Point for the E $\frac{1}{16}$ sec. cor. of sec. 6, T. 14 N., R.
26 E. only, at proportionate dist.

Set the iron post 22 ins. in the ground, brass cap mkd.

E $\frac{1}{16}$ S 6
T14N R26E
1968.

Deposit glass in the hole alongside the iron post.

40.05

The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented by an iron
post, $2\frac{1}{2}$ ins. diam., 10 ins. above ground, in a collar
of stone, brass cap mkd.

T15N R26E
 $\frac{1}{4}$ S31
S 6
T14N R26E
1963

This cor. now functions for the $\frac{1}{4}$ sec. cor. of sec. 31,
only, T. 15 N., R. 26 E. I change the markings to read:

T15N R26E
 $\frac{1}{4}$ S31
1968
1963

58.60

Point for the $\frac{1}{4}$ sec. cor. of sec. 6, T. 14 N., R. 26 E.,
only, at proportionate dist.

Set the iron post 22 ins. in the ground, brass cap mkd.

$\frac{1}{4}$ S 6
T14N R26E
1968

Deposit glass in the hole alongside the iron post.

Dependent Resurvey, Portion North Boundary,
T. 14 N.; R. 26 E.

CHAINS	
69.70	Wash, 20 lks. wide, 4 ft. banks, drains S. 15° W.
86.90	Wash, 30 lks. wide, 4 ft. banks, drains S. 25° W.
87.90	Point for the W 1/16 sec. cor. of sec. 6, T. 14 N., R. 26 E., only, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<hr/> W 1/16 S6 T14N R26E 1968
	Deposit glass in the hole alongside the iron post.
98.20	Low spur, slopes S.
105.00	Spur, slopes irregularly S. 60° W. from the N.
115.74	The cor. of Tps. 14 and 15 N., Rs. 25 and 26 E., hereinbefore described.
	Land, gently rolling. Soil, sandy clay loam. Timber, widely scattered cedar on spur. Undergrowth, sagebrush and bunchgrass.
Dependent Resurvey, Portion Subdivisional Lines, T. 14 N., R. 26 E.	
Reestablishment of the Survey executed by C. B. Foster in 1875	
	Beginning at the ¼ sec. cor. of secs. 25 and 26, monument- ed by a lava stone, 12x6x3 ins., firmly set in a mound of stone and mkd. ¼ on W. face. The cor. is located 23 lks. E. of a cor. of fences extending N., S. and W.; not re- monumented.
	N. 3°22' E., bet. secs. 25 and 26.
	Over gently rolling land.
9.80	Bladed road, bears S. 80° E. and N. 80° W.
11.80	Track road, bears N. 80° E. and S. 80° W.
42.25	Point for the cor. of secs. 23, 24, 25 and 26, at propor- tionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
	from which
	Cor. of fences, bear N. 75°27' W., 3.60 chs. dist.; fences extend N. and easterly, traversing along the right bank of the Little Colorado River.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	<p>From the point for the cor. of secs. 19, 24, 25 and 30, on the E. Bdy of the tp.</p> <p>S. 81°08' W., bet. secs. 24 and 25.</p> <p>Over nearly level land.</p>
23.10	Little Colorado River, 1.60 chs. wide, 2 ft. deep, course N. 80° W.
43.02	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
52.80	Little Colorado River, 1.80 chs. wide, 2 ft. deep, course S. 60° W. from N. 80° E.
72.50	Little Colorado River, 1.20 chs. wide, 2 ft. deep, course NW, curving W.
86.04	<p>The point for the cor. of secs. 23, 24, 25 and 26.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, sagebrush and bunchgrass.</p>
	<p>N. 2°06' W., bet. secs. 23 and 24.</p> <p>Over rolling land.</p>
0.15	Little Colorado River, 1.70 chs. wide, 2 ft. deep, course S. 60° W. from the E.
0.45	Track road, bears irreg. E. and W.
21.10	<p>Point for the S 1/16 sec. cor. of secs. 23 and 24, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S 1/16 S23 S24 1972</p> <p>from which</p> <p style="text-align: center;">A N-S fenceline, bears West, 2.12 chs. dist.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p>
28.00	Draw, drains SE.
42.20	<p>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 7 ins. in the ground, over an X chiseled on bedrock, mound of stone, 3 ft. base to top, brass cap mkd.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
	<p style="text-align: center;">T14N R26E $\frac{1}{4}$ S23 S24 1972</p> <p>from which</p> <p style="padding-left: 40px;">A N-S fenceline bears West, 87 lks. dist.</p>	
55.20	Fence, bears N. 1°44' E. and S. 1°44' W.	
74.90	Wash, 40 lks. wide, with 10 ft. banks, drains SW.	
84.40	Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	<p>Set the iron post 6 ins. in the ground, over an X chiseled in bedrock, mound of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S14 S13 S23 S24 1972</p> <p>from which</p> <p style="padding-left: 40px;">A N-S fenceline, bears East, 1.96 chs. dist.</p> <p>Land, rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>	
	<hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>S. 82°17' W., bet. secs. 13 and 24.</p> <p>Over rolling land through scattered juniper.</p>	
41.22	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	Set the iron post 10 ins. in the ground, mound of stone, 4 ft. base to top, brass cap mkd.	
	<p style="text-align: center;">T14N R26E $\frac{1}{4}$ S13 S24 1972</p> <p>from which</p> <p style="padding-left: 40px;">An E-W fenceline, bears North, 1.48 chs. dist.</p>	
68.00	Wash, 40 lks. wide, with 8 ft. banks, drains SW.	
80.48	Fenceline, bears N. and S.	
82.44	The cor. of secs. 13, 14, 23 and 24.	
	<p>Land, rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>	
	<hr/> <p>N. 0°04' E., bet. secs. 13 and 14.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	Over rolling land, through scattered cedar.
21.09	Point for the S 1/16 sec. cor. of sec. 13 and 14, at proportionate dist.
	Set the iron post, 6 ins. in the ground, over an X chiseled on bedrock, mound of stone, 3½ ft. base to top, brass cap mkd.
	<p style="text-align: center;">T14N R26E S 1/16 S14 S13 1972</p>
	Raise a mound of stone W. of the cor.
41.50	Track road, bears irreg. E. and W.
42.18	<p>The ¼ sec. cor. of secs. 13 and 14, marked by a cor. of fences bearing irreg. N., S. and W. There is no remaining evidence of the orig. cor. monument. This cor. position was shown to me by Mr. Issacson, an adjacent landowner, and is accepted as the best remaining evidence of the orig. cor. position.</p>
	At the cor. point
	Set the iron post 14 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.
	<p style="text-align: center;">T14N R26E ¼ S14 S13 1972</p>
	N. 1°17' E., beginning new measurement.
	Over gently rolling land, along a N. and S. fenceline.
49.60	<p>The cor. of secs. 11, 12, 13 and 14, monumented by an old cedar post, 2 ft. long, pointed on one end and squared to 3½ ins. diam., on the other end, scribed S XIV RXXVI E., firmly wired to the cor. post of fences extending northerly, easterly and S. 1°17' E.</p>
	At the cor. point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T14N R26E S11 S12 S14 S13 1972</p>
	Invert and reset the scribed post alongside the cor.
	Raise a mound of stone, 1½ ft. base, 16 ins. high, W. of the cor.
	<p>Land, gently rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, scattered bunchgrass and sagebrush.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p>
	N. 87°48' W., bet. secs. 12 and 13.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	Over gently rolling land, along the N. edge of a railed area.
15.80	Track road, bears N. and S.
40.73	The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented by a limestone, 16x10x8 ins. diam. (Record type and size), lying loose on the ground in an E-W fenceline, no marks legible, no other stones near. This stone is accepted as the best available evidence of the orig. cor.
	At the cor. point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T14N R26E $\frac{1}{4}$ $\frac{S12}{S13}$ 1972
	Raise a mound of stone, $1\frac{1}{2}$ ft. base, 14 ins. high, N. of the cor.
	<hr style="width: 20%; margin: auto;"/>
	S. $89^{\circ}32'$ W., beginning new measurement.
31.60	Wash, 10 lks. wide, with 6 ft. banks, drains N. 25° E.
39.86	The cor. of secs. 11, 12, 13 and 14.
	Land, gently rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, scattered bunchgrass and sagebrush.
	N. $1^{\circ}04'$ E., bet. secs. 11 and 12.
	Over gently rolling land, through widely scattered cedar.
17.60	Fence, bears S. 30° E. and N. 30° W.
40.62	Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set the iron post, 16 ins. in the ground, mound of stone, $3\frac{1}{2}$ ft. base, to top, brass cap mkd.
	T14N R26E $\frac{1}{4}$ S11 S12 1972
60.72	Track road, bears irreg. E. and W.
63.50	Wash, 20 lks. wide, 2 ft. deep, drains NE.
81.24	Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist., there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T14N R26E S 2 S 1 S11 S12 1972
	from which

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	<p>A cor. of fences bears N. 29°56' E., 8.03 chs. dist., fences extend NE. and N: 60° W.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of the cor.</p> <p>Land, rolling to gently rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, scattered bunchgrass, moderate sagebrush.</p> <hr/> <p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 88°09' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>9.30 Track road, bears N. 70° E. and S. 70° W.</p> <p>22.00 Wash, 10 lks. wide, 2 ft. deep, drains N. 40° E.</p> <p>40.50 Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E ¼ $\frac{S 1}{S12}$ 1968</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p> <p>The cor. is located 155 lks. North of a track road bearing N. 60° E., curving SE. and S. 70° W., curving SW.</p> <p>59.00 Wash, 20 lks. wide, 3 ft. deep, drains N.</p> <p>72.50 Wash, 70 lks. wide, with 8 ft. banks, drains NE.</p> <p>81.00 The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, gently rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p> <hr/> <p>N. 7°32' E., bet. secs. 1 and 2.</p> <p>Over rolling land.</p> <p>18.80 Zuni River, 3.90 chs. wide, with 20 ft. banks, course N. 70° W.</p> <p>40.97 The ¼ sec. cor. of secs. 1 and 2, monumented by a limestone, 10x9x8 ins., lying loose on the ground, dimly mkd. ¼ on a face, with mound of stone, 2 ft. base, 1 ft. high, W., not remonumented or rehabilitated</p> <hr/> <p>N. 2°07' E., beginning new measurement.</p> <p>Over gently rolling land.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
32.70	Wash, 20 lks. wide, 3 ft. deep, drains SW.	
51.93	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. in diam., 6 ins. above ground, firmly set, with mound of stone, 2½ ft. base, 2 ft. high, W., brass cap mkd.	
	<p>T15N R26E S35 S36 S 2 S 1 T14N R26E 1963.</p>	
	<p>Land, rolling to gently rolling. Soil, sandy clay loam. Timber, widely scattered cedar in S. 10 chs. of S. ½. Undergrowth, sagebrush and bunchgrass.</p>	
	<p>From the ¼ sec. cor. of secs. 26 and 27, monumented by basalt stone, 11x6x6 ins. above ground, firmly set, dimly mkd. ¼ on W. face, in a mound of stone, 2 ft. base, 1½ ft. high; not remonumented.</p>	
	North, bet. secs. 26 and 27.	
	Over nearly level land.	
11.80	Underground telephone cable, bears E. and W.	
39.93	The cor. of secs. 22, 23, 26 and 27, marked by a cor. of fences, bearing N. 0°14' E. (abandoned), S. 87°13' E., S. 2°15' W. and N. 87°13' W. This cor. is used by adjacent landowners and is accepted as the best available evidence of the orig. cor. position; not monumented.	
	<p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, sagebrush and bunchgrass.</p>	
	From the point for the cor. of secs. 23, 24, 25 and 26.	
	S. 88°14' W., bet. secs. 23 and 26.	
	Over nearly level land.	
4.30	Track road, bears N. and S.	
42.47	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.	
	from which	
	<p>Cor. of fences, bears S. 84°10' E., 13.18 chs. dist., fences bear W. and S. 30° E., 1.59 chs. dist., thence E.</p>	
	<p>Cor. of fences, bears S. 58°21' W., 2.16 chs. dist., fences bear E., W. and NW.</p>	
62.30	Track road, bears S. 65° E. and N. 65° W.	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
84.94	<p>The cor. of secs. 22, 23, 26 and 27.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, sagebrush and bunchgrass.</p>
20.90	<p>N. 0°14' E., bet. secs. 22 and 23.</p> <p>Over nearly level land, along abandoned fenceline.</p> <p>Point for the S 1/16 sec. cor. of secs. 22 and 23, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S 1/16 S22 S23 1968</p> <p>from which</p> <p style="text-align: center;">A fence (abandoned), bears East, 39 lks. dist., fence bears N. 1°05' E. and S. 1°05' W.</p> <p>Set a wooden post, 6 ft. long, 4 ins. squared alongside the cor.</p>
41.80	<p>Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E 1/4 S22 S23 1968</p> <p>from which</p> <p style="text-align: center;">A fence, bears East, 62 lks. dist., fence bears N. 1°05' E. and S. 1°05' W.</p> <p>Set a wooden post, 5 ft. long, 3 ins. squared alongside the iron post.</p>
59.20	<p>Fence, bears W. and E., 12 lks. dist. to cor. of fences bearing N., E. and W., and an abandoned fenceline bears S. from this fence cor., fence extends E., 3.19 chs. dist., to cor. of fences bearing W. and S</p>
66.70	<p>Track road, bears E. and W.</p>
66.80	<p>Fence, bears W. and E., 12 lks. dist. to a cor. of fences bearing N., S. and E. and W.</p>
68.40	<p>Little Colorado River, 40 lks. wide, 6 ins. deep, flows W.</p>
73.70	<p>Cor. of fences, bears N., SE. and S.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
83.60	<p>The cor. of secs. 14, 15, 22 and 23, marked by a cor. of fences bearing E., S. and W. This cor. is used by adjacent landowners and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S15 S14 S22 S23 1968</p> <p>from which</p> <p style="padding-left: 40px;">Cor. of fences, bears S. 84° W., 4.94 chs. dist., fences bear irregularly E. and N. 30° W.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, sagebrush and bunchgrass.</p>	
	<hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p>	
	<p>S. 87°39' W., bet. secs. 14 and 23.</p>	
	<p>Over rolling land, through scattered cedar.</p>	
5.50	<p>Leave scattered cedar, bears N. and S.</p>	
18.00	<p>S. edge of top of rounded hill.</p>	
33.00	<p>NW. edge of top of rounded hill.</p>	
40.78	<p>Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p>	
55.40	<p>Track road, bears N. 30° E. and S. 30° W., curving NW.</p>	
58.00	<p>Enter nearly level land.</p>	
65.50	<p>Track road, bears N. and S.</p>	
81.56	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, rolling to nearly level. Soil, sandy clay loam. Timber, scattered cedar E. 10 chs. Undergrowth, sagebrush and bunchgrass.</p>	
	<hr/> <p>N. 1°39' E., bet. secs. 14 and 15.</p>	
	<p>Over rolling land.</p>	
20.02	<p>Track road, bears S. 10° E. and N. 10° W.</p>	
20.07	<p>Fence, bears N. 65°42' E. and S. 65°42' W.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
21.735	<p>Point for the S 1/16 sec. cor. of secs. 14 and 15, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S 1/16 S15 S14 1972</p> <p>Raise a mound of stone, 20 ins. base, 16 ins. high, W. of the cor.</p>
37.70	<p>Wash, 40 lks. wide, 2 ft. deep, drains SW.</p>
43.47	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 6 ins. in the ground, over an X chiseled in bedrock, mound of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T14N R26E 1/4 S15 S14 1972</p>
50.20	<p>Fence, bears irregularly SE. and NW.</p>
86.94	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S10 S11 S15 S14 1972</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of the cor.</p> <p>Land, rolling. Soil, sandy clay loam. Timber, widely scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 84°06' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through scattered cedar.</p>
10.00	<p>Asc. steep E. Slope.</p>
38.00	<p>E. rim of south mountain of Stinking Springs Mountains, bears northerly curving northwesterly and southerly, curving southwesterly.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
40.30	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, 8 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ <u>S11</u> S14 1972</p>	
56.00	<p>W. rim of south mountain of Stinking Springs Mountains, bears N. and S., thence over rolling land.</p>	
80.60	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>	
	<p>N. 0°21' E., bet. secs. 10 and 11.</p>	
	<p>Over rolling land, along a W. slope, through widely scattered cedar.</p>	
43.45	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ S10 S11 1968</p>	
	<p>Raise a mound of stone, 2 ft. base, 20 ins. high, W. of the cor.</p>	
55.00	<p>Spur of south mountain of Stinking Springs Mountains, slopes N. 20° W.</p>	
86.90	<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post over a + chiseled in solid rock, mound of stone 3 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S 3 S 2 S10 S11 1968</p>	
	<p>Land, rolling. Soil, rocky, sandy loam. Timber, widely scattered cedar. Undergrowth, sagebrush and bunchgrass.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	From the cor. of secs. 1, 2, 11 and 12.
	S. 88°06' W., bet. secs. 2 and 11.
	Over rolling land, through scattered juniper.
9.70	Track road, bears N. and S.
12.10	Fence, bears N. and S.
33.60	Wash, 20 lks. wide, with 12 ft. banks, drains N. curving to the NE.
40.60	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
81.20	The cor. of secs. 2, 3, 10 and 11. Land, rolling. Soil, rocky, sandy loam. Timber, widely scattered juniper. Undergrowth, sagebrush and bunchgrass.
	N. 5°24' E., bet. secs. 2 and 3.
	Over rolling land.
29.60	Track road, bears S. 70° E. and N. 70° W.
36.80	Zuni River, 3.60 chs. wide, with 18 ft. banks, course NW.
43.65	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
	from which
	Cor. of fences, bears S. 42°36' W., 7.44 chs. dist., fences bear SE and SW.
56.90	Wash, 40 lks. wide, with 8 ft. banks, drains S. 20° W.
87.35	The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., 24 ins. above ground, set in a mound of stone, brass cap mkd.
	<p style="text-align: center;">T15N R26E $\frac{S34}{S3} \frac{S35}{S2}$ T14N R26E 1963</p>
	Land, rolling. Soil, rocky sandy loam. Timber, widely scattered juniper in S. half. Undergrowth, sagebrush and bunchgrass.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
	<p>From the cor. of secs. 27, 28, 33 and 34, monumented by a granite stone, 10x6x6 ins., firmly set in a mound of stone, mkd. with 3 notches on E. and 1 notch on S. edges in cor. of fences bearing N. 1°08' E., N. 89°21' E. and S. 89°21' W.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T14N R26E <u>S28 S27</u> S33 S34 1968</p>	
	<p>Bury the orig. stone cor. alongside the iron post.</p>	
	<p>Raise a mound of stone W. of the cor.</p>	
	<p>N. 1°08' E., bet. secs. 27 and 28.</p>	
	<p>Over gently rolling land, along fenceline.</p>	
21.80	<p>Bladed road, bears E. and W.</p>	
41.85	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T14N R26E $\frac{1}{4}$ <u>S28 S27</u> 1968</p>	
	<p>Raise a mound of stone W. of the iron post.</p>	
	<p>Cor. is located in a fenceline bearing N. 1°08' E. and S. 1°08' W.</p>	
51.90	<p>Underground telephone cable, bears S. 80° E. and N. 80° W.</p>	
66.00	<p>Track road, bears E. and W.</p>	
83.70	<p>The cor. of secs. 21, 22, 27 and 28, marked by a cor. of fences bearing N. 1°08' E., S. 87°13' E., S. 1°08' W. and S. 88°42' W. This cor. is used by adjacent land-owners and is accepted as the best available evidence of the original cor. position.</p>	
	<p>At the corner point</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T14N R26E <u>S21 S22</u> S28 S27 1968</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay loam. Timber, widely scattered cedar. Undergrowth, sagebrush and bunchgrass</p>
	<p>From the cor. of secs. 22, 23, 26 and 27. N. 87°13' W., bet. secs. 22 and 27. Over gently rolling land, along fenceline to the S.</p>
5.80	Wash, 20 lks. wide, 2 ft. deep, drains N.
19.77	Point for the E. 1/16 sec. cor. of secs. 22 and 27 at proportionate dist.; not monumented. from which A cor. of fences, bears S. 1° W., 1.15 chs. dist., fences bear N. 7°35' E. and irregularly E. and W.
39.54	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented. from which A cor. of fences bears S. 14°13' W., 2.32 chs. dist., fences bear N. 12°39' E. and irregularly E. and W.
40.80	Track road, bears S. 10° E. and N. 10° W.
41.30	Track road, bears S. 50° E. and N. 50° W.
52.80	Track road, bears N. 30° E. and S. 30° W.
79.08	The cor. of secs. 21, 22, 27 and 28. Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, sagebrush and bunchgrass.
	<p>N. 0°45' E., bet. secs. 21 and 22. Over gently rolling land, along fenceline.</p>
13.10	Track road, bears S. 60° E. and N. 60° W.
35.66	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented. from which A cor. of fences, bears S. 5°48' E., 4.35 chs. dist., fences bear N. 1°08' E., S. 1°08' W. and N. 70° W.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
71.32	<p>The cor. of secs. 15, 16, 21 and 22, marked by a cor. of fences bearing N., E., S. (abandoned) and NW. This cor. is used by adjacent landowners and is accepted as the best available evidence of the original cor. position; not monumented.</p> <p>Land, gently rolling. Soil, sandy clay loam. No timber; undergrowth, sagebrush and bunchgrass.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 83°53' W., bet. secs. 15 and 22.</p> <p>Over nearly level land.</p>
8.20	<p>Little Colorado River, 20 lks. wide, 6 ins. deep, flows NW.</p>
9.30	<p>Dike, bears SE. and NW.</p>
9.90	<p>Fence, bears SE. and NW.</p>
11.30	<p>Track road, bears SE. and NW.</p>
39.40	<p>Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p>
78.80	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; undergrowth, sagebrush and bunchgrass.</p>
	<p>N. 0°46' E., bet. secs. 15 and 16.</p> <p>Over nearly level land.</p>
43.41	<p>Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p>
49.92	<p>Power line, bears N. 27°44' E. and S. 27°44' W.</p>
61.10	<p>Fence, bears E. and W., 2.94 chs. dist., to cor. of fences, bearing E., S. and W.</p>
66.20	<p>Little Colorado River, 20 lks. wide, 2 ft. deep, flows W.</p>
68.30	<p>Fence, bears E. and W.</p>
69.30	<p>Dike, bears E. and W.</p>
86.82	<p>Point for the cor. of secs. 9, 10, 15 and 16 at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p> <p>from which</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS

The cor. of secs. 8, 9, 16 and 17, bears S. 79°29' W., 81.13 chs. dist., marked by a cor. of fences bearing N. 2° E., E. and S. 2° W. This cor. is used by adjacent landowners and is accepted as the best available evidence of the orig. cor. position; not monumented. No evidence of the ¼ sec. cor. of secs. 9 and 16 found.

The SE. cor. of a house, measuring 40 ft. by 30 ft. and with the long side bearing N. 40° W., bears N. 64°57' E., 27.38 chs. dist.

Stinking Springs, a flowing spring enclosed in a 3 ft. square cement box, 6 ins. high, bears N. 67° 03' E., 26.39 chs. dist., and flows in a northerly direction.

Center of an irregularly equilateral triangular stock pond, with the S. side measuring approximately 9.00 chs., bears N. 5° E., 25.20 chs. dist.

Land, nearly level.

Soil, sandy loam.

No timber; undergrowth, bunchgrass and sagebrush.

From the cor. of secs. 10, 11, 14 and 15.

S. 83°59' W., bet. secs. 10 and 15.

Over rolling land, through scattered juniper.

28.10 Fence, bears irregularly N. and S.

40.10 Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post over an X chiseled on solid sandstone, mound of stone, 3½ ft. base to top, brass cap mkd.

T14N R26E

¼ S10
S15
1972

50.40 Leave rolling land and scattered cedar, bears N. and S.; thence over nearly level land.

53.20 Track road, bears S. 10° E. and N. 10° W.

53.30 Wash, 30 lks. wide, 2 ft. deep, drains SW.

56.00 Fence, bears irreg. N. and S.

60.36 Powerline bears N. 27°44' E. and S. 27°44' W.

80.20 The point for the cor. of secs. 9, 10, 15 and 16.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
	<p>Land, rolling to nearly level. Soil, rocky, sandy loam. Timber, scattered cedar. Undergrowth, bunchgrass and sagebrush.</p>	
	<p>N. 0°32' W., bet. secs. 9 and 10. Over gently rolling land.</p>	
21.705	<p>Point for the S 1/16 sec. cor. of secs. 9 and 10, at proportionate dist. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S 1/16 S 9 S10 1968</p> <p>Set a cedar post, 6 ft. long, 4 ins. diam., 20 ins. in the ground along the W. side of the cor.</p> <p>The cor. is located 40 lks. N. of an abandoned fenceline bearing S. 80°10' E. and N. 80°10' W.</p>	
35.20	Track road, bears irregularly S. 60° E. and N. 60° W.	
41.95	Fence, bears S. 10° E. and N. 10° W.	
43.41	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E 1/4 S 9 S10 1968</p> <p>Set a cedar post, 3 ft. long, 3 ins. diam., 20 ins. in the ground along the W. side of the iron post.</p>	
47.60	Track road, bears S. 10° E. and N. 10° W.	
86.82	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no evidence remaining of the orig. cor. Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S 4 S 3 S 9 S10 1968</p> <p>Deposit glass at the base of the iron post.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	<p>Land, gently rolling. Soil, clay loam. No timber; undergrowth, bunchgrass and sagebrush.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11. S. 84°02' W., bet. secs. 3 and 10. Over rolling land.</p>
40.75	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone, $3\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ $\frac{S\ 3}{S10}$ 1968</p>
69.00	Enter gently rolling land.
72.90	Track road, bears N. 20° E. and S. 20° W.
81.50	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling to gently rolling. Soil, rocky, sandy loam. Timber, scattered juniper. Undergrowth, bunchgrass and sagebrush.</p>
	<p>N. 6°01' E., bet. secs. 3 and 4. Over gently rolling land.</p>
21.82	<p>Point for the S $\frac{1}{16}$ sec. cor. of secs. 3 and 4, at proportionate dist.</p> <p>Set the iron post 23 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S $\frac{1}{16}$ S 4 S 3 1968</p> <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.</p>
22.70	Left bank of Zuni River, bears NE. and SW.
25.60	Right bank of Zuni River, bears NE. and SW.
43.64	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ S 4 S 3 1968</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
87.41	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <p>Thence over rolling land.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above ground; brass cap mkd.</p> <p style="text-align: center;">T15N R26E S33 S34 S 4 S 3 T14N R26E 1963</p> <p>Land, rolling to gently rolling. Soil, rocky, sandy loam. Timber, scattered cedar. Undergrowth, bunchgrass and sagebrush.</p>	
22.70	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°12' W., bet. secs. 28 and 33.</p> <p>Over rolling land, along fence line.</p> <p>Ridge, bears N. and S.</p>	
39.98	<p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E ¼ S28 S33 1968</p>	
79.96	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>Cor. is in a fence line, bearing N. 89°12' E. and S. 89°12' W.</p> <p>Point for the cor. of secs. 28, 29, 32 and 33 at proportionate dist. longitudinally, and latitudinally by an old fence bearing N. 89°12' E. and S. 89°12' W.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S29 S28 S32 S33 1968</p>	
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>The cor. of secs. 29, 30, 31 and 32, bears S. 82°28' W., 80.24 chs. dist., hereinafter described. This control line was fully retraced and no evidence of the intervening cor. was found.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, scattered cedar. Undergrowth, bunchgrass and sagebrush.</p>
	<p>N. 0°18' W., bet. secs. 28 and 29.</p> <p>Over gently rolling land.</p>
37.70	Bladed road, bears E. and W.
41.46	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ S29 S28 1968</p>
67.70	<p>Set a wooden post, 4 ft. long, 3 ins. squared alongside the cor.</p> <p>Underground telephone cable, bears S. 80° E. and N. 80° W.</p>
82.92	<p>The cor. of secs. 20, 21, 28 and 29, marked by a cor. of fences bearing N. 1°48' E., N. 88°42' E., S. 4°59' W. and S. 79°13' W. This cor. is used by adjacent landowners and is accepted as the best available evidence of the orig. cor. position.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E S20 S21 S29 S28 1968</p>
	<p>Set a pipe, 2 ft. long, 1 in. diam., alongside the cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 88°42' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land, along fenceline.</p>
14.80	Track road, bears S. 10° E. and N. 10° W.
41.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ $\frac{S21}{S28}$ 1968</p> <p>from which</p> <p style="padding-left: 40px;">A fence, bears North, 2 lks. dist.; fence bears N. 88°42' E. and S. 88°42' W.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, North of the cor.</p>	
47.80	Power line, bears SE. and NW.	
55.40	Telephone line, bears SE. and NW.	
81.70	Track road, bears N. and S.	
82.04	The cor. of secs. 20, 21, 28 and 29.	
	<p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.</p>	
	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 81°36' W., bet. secs. 4 and 9.</p> <p>Over nearly level land.</p>	
7.20	Track road, bears S. 10° E. and N. 10° W.	
7.70	Fence, bears S. 10° E. and N. 10° W.	
20.46	Point for the E 1/16 sec. cor. of secs. 4 and 9, at proportionate dist., not monumented.	
23.50	Left bank of Zuni River, bears N. 70° E. and S. 25° E.	
25.60	Right bank of Zuni River, bears N. 70° E. and S. 25° E.	
40.92	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ $\frac{S 4}{S 9}$ 1968</p> <p>Deposit glass at the base of the iron post.</p>	
81.84	Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS

Set the iron post 20 ins. in the ground, brass cap mkd.

T14N R26E

S 5 | S 4

S 8 | S 9

1968

from which

The cor. of secs. 8, 9, 16 and 17, bears S. 1°19' E., 89.64 chs. dist., hereinbefore described.

The cor. of secs. 5, 6, 7 and 8 bears S. 81°10' W., 81.84 chs. dist., hereinafter described.

These control lines were fully retraced and no evidence of intervening cors. was found.

Deposit glass at the base of the iron post.

Land, gently rolling.

Soil, sandy loam.

Timber, none.

Undergrowth, bunchgrass and sagebrush.

N. 6°06' E., bet. secs. 4. and 5.

Over nearly level land.

15.50 Wash, 70 lks. wide, with 6 ft. banks, drains W.

30.50 Wash, 5 lks. wide, 2 ft. deep, drains SW.

38.50 Wash, 20 lks. wide, 3 ft. deep, drains SW.

45.06 Point for the $\frac{1}{2}$ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 20 ins. in the ground, brass cap mkd.

T14N R26E

$\frac{1}{2}$
S 5 | S 4

1968

Deposit glass at the base of the iron post.

53.10 Fence, bears SE. and NW.

90.01 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 24 ins. above ground, firmly set, in a mound of stone, brass cap mkd.

T15N R26E

S32 | S33

S 5 | S 4

T14N R26E

1963

Land, nearly level.

Soil, sandy loam.

Timber, none.

Undergrowth, bunchgrass and sagebrush.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS

From the cor. of secs. 29, 30, 31 and 32, determined latitudinally by proportionate dist. and longitudinally by topography call in the old record. A wash, 60 lks. wide, with 6 ft. banks, bears East, 9.00 chs. dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T14N R26E
S30|S29
S31|S32
1968

from which

The cor. of secs. 28, 29, 32 and 33, bears N. 82°28' E., 80.24 chs. dist., hereinbefore described.

The cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., bears S. 0°44' W., 78.60 chs. dist., monumented by a basalt stone, firmly set with 9x8x5 ins. above ground, mkd. with 5 notches on the E. face and 1 notch on the W. face.

These control lines were fully retraced and no evidence of intervening cors. was found.

Set a wooden post 3 ft. long, 4. ins. squared, alongside the cor.

S. 87°49' W., bet. secs. 30 and 31.

Over rolling land.

18.00 Track road, bears N. and S.

26.10 Fence, bears N. 5° E. and S. 5° W.

29.50 Landing strip, bears N. 5° E. and S. 5° W.

31.00 Graded road, bears N. 5° E. and S. 5° W.

31.80 Fence, bears N. 5° E. and S. 5° W.

47.76 Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate dist., there is no remaining evidence of the orig. cor.

Set the iron post 18 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.

T14N R26E
¼ $\frac{S30}{S31}$
1968

89.20 Wash, 50 lks. wide, with 6 ft. banks, drains N. 40° E.

90.60 Power line, bears S. 25° E. and N. 25° W.

90.70 Highway R-0-W fence, bears S. 25° E. and N. 25° W.

92.10 U.S. Highway No. 260, bears S. 25° E. and N. 25° W.

93.40 Highway R-0-W fence, bears S. 25° E. and N. 25° W.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
95.40	<p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered to moderate cedar. Undergrowth, bunchgrass and sagebrush.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°44' E., bet. secs. 29 and 30.</p> <p>Over rolling land.</p>
39.30	<p>Point for the ¼ sec. cor. of secs. 29 and 30, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E ¼ S30 S29 1968</p>
78.60	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <p>The cor. of secs. 19, 20, 29 and 30, monumented by an iron pipe, ¾ ins. in diam., firmly set in a mound of stone, projecting 6 ins. above the ground. This cor. is used by adjacent landowners and is accepted as the best available evidence of the orig. cor. position; not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">The cor. of secs. 20, 21, 28 and 29 bears N. 79°13' E., 79.46 chs. dist., herinbefore described. No evidence of the ¼ sec. cor. of secs. 20 and 29 found.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattered to moderate cedar. Undergrowth, bunchgrass and sagebrush.</p>
	<p>S. 88°18' W., bet. secs. 19 and 30.</p> <p>Over rolling land.</p>
27.20	<p>Graded road, bears N. 5° E. and S. 5° W.</p>
47.40	<p>Wash, 120 lks. wide, with 10 ft. banks, drains N.</p>
49.48	<p>Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS		
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T14N R26E $\frac{1}{4}$ $\frac{S19}{S30}$ 1968</p>	
98.22	Set a cedar post, 4 ft. long, 3 ins. squared alongside the cor.	
	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.	
	Land, rolling. Soil, sandy loam. Timber, scattered to moderate juniper. Undergrowth, bunchgrass and sagebrush.	
	The cor. of secs. 5, 6, 7 and 8 marked by the cor. of fences, bearing N., S., E., and W. This fence cor. has been used by adjacent landowners for many years and is accepted as the best remaining evidence of the orig. cor. position; not monumented.	
	S. 89°51' W., bet. secs. 6 and 7.	
	Over nearly level land, along fence line.	
0.70	Irrigation ditch, drains S.	
39.80	Cor. of fences, bears N., approximately 20 lks. dist. to cor. of fences bearing E. and N., 30 lks. dist. to cor. of fences bearing S. and W.	
40.00	Track road, bears N. and S.	
40.20	Power line, bears N. and S.	
60.67	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.	
120.13	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.	
	Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.	
	From the cor. of secs. 5, 6, 7 and 8.	
	N. 6°48' E., bet. secs. 5 and 6.	
	Over nearly level land.	
25.10	Track road, bears E. and W.	
26.50	Left bank of the Zuni River, bears S. 70° E. and N. 70° W., curving to the N.	
31.60	Left bank of the Zuni River, bears N. 80° E. and S. 80° W., curving to the S.	
33.70	Left bank of the Zuni River, bears S. 40° E. and N. 40° W.	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 26 E.

CHAINS	
36.70	Right bank of Zuni River, bears S. 40° E. and N. 40° W.
47.75	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E $\frac{1}{4}$ S 6 S 5 1968</p> <p>Deposit glass at the base of the iron post.</p>
52.90	Wash, 20 lks. wide, 1 ft. deep, drains W.
71.63	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 5 and 6, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E N $\frac{1}{16}$ S 6 S 5 1968</p> <p>Deposit glass at the base of the iron post.</p>
95.39	<p>The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.</p>
Survey, Subdivision Section 4, T. 14 N., R. 26 E.	
22.17	<p>From the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.</p> <p>N. 6°03' E., on the N. and S. centerline of sec. 4.</p> <p>Over nearly level land.</p> <p>Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 4; not monumented.</p>
25.70	Wash, 50 lks. wide, with 6 ft. banks, drains SW.
30.00	Fence, bears S. 70° E. and N. 70° W. Also wash, 50 lks. wide, with 8 ft. banks drains SW.
44.34	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 4, at the intersection with the E. and W. centerline of sec. 4.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E C $\frac{1}{4}$ + S4 1968</p>

Survey, Subdivision Section 4, T. 14 N., R. 26 E.

CHAINS		
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p>	
88.66	<p>The ¼ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set in a mound of stone, 2½ ft. base, projecting 26 ins. above ground, brass cap mkd.</p>	
	<p style="text-align: center;">T15N R26E ¼ $\frac{S33}{S 4}$ T14N R26E 1963</p>	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.</p>	
	<hr/> <p>From the ¼ sec. cor. of secs. 3 and 4.</p>	
	<p>S. 82°33' W., on the E. and W. centerline of sec. 4.</p>	
	<p>Over nearly level land.</p>	
10.60	<p>Fence, bears S. 10° E. and N. 10° W.</p>	
11.90	<p>Track road, bears S. 10° E. and N. 10° W.</p>	
20.36	<p>Point for the C-E 1/16 sec. cor. of sec. 4. Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T14N R26E C $\frac{E 1/16}{S 4}$ C 1968</p>	
	<p>Raise a mound of stone 1½ ft. base, 1 ft. high, N. of the cor.</p>	
32.20	<p>Wash, 20 lks. wide, with 8 ft. banks, drains S. 20° W.</p>	
40.72	<p>The C ¼ sec. cor. of sec. 4.</p>	
66.20	<p>Fence, bears S. 70° E. and N. 70° W.</p>	
81.43	<p>The ¼ sec. cor. of secs. 4 and 5.</p>	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.</p>	
	<p style="text-align: center;">Subdivision, SE¼ Section 4</p> <hr/>	
	<p>From the point for the E 1/16 sec. cor. of secs. 4 and 9. N. 6°02' E., on the N. and S. centerline of the SE¼ of sec. 4.</p>	

Survey, Subdivision Section 4, T. 14 N., R. 26 E.

CHAINS	
	Over nearly level land.
1.80	Left bank of the Zuni River, bears N. 70° E. and S. 70° W.
4.10	Rightbank of the Zuni River, bears N. 70° E. and S. 70° W.
17.60	Fence, bears S. 70° E. and N. 70° W.
22.00	Point for the SE 1/16 sec. cor. of sec. 4, at the intersection with the E. and W. centerline of the SE 1/4 of sec. 4. Set the iron post 22 ins. in the ground, brass cap mkd. T14N R26E SE 1/16 S 4 1968 Raise a mound of stone, 1½ ft. base, 16 ins. high, W. of the cor.
22.06	Fence, bears E. and W.
44.00	The C-E 1/16 sec. cor. of sec. 4.
	From the S 1/16 sec. cor. of secs. 3 and 4. S. 82°05' W., on the E. and W. centerline of the SE 1/4 of sec. 4. Over nearly level land.
1.00	Left bank of the Zuni River, bears N. 30° E. and S. 30° W.
2.90	Right bank of the Zuni River, bears N. 30° E. and S. 30° W.
15.60	Track road, bears N. and S.
20.41	The SE 1/16 sec. cor. of sec. 4.
27.20	Fence, bears S. 70° E. and N. 70° W.
40.82	The point for the C-S 1/16 sec. cor. of sec. 4.
	Survey, Subdivision Section 6, T. 14 N., R. 26 E.
	From the point for the 1/4 sec. cor. of secs. 6 and 7. N. 8°51' E., on the N. and S. centerline of sec. 6. Over nearly level land.
27.20	Wash, 10 lks. wide, 3 ft. deep, drains W.
42.30	Track road, bears E. and W.
43.20	Fence, bears E. and W.

Survey, Subdivision Section 6, T. 14 N., R. 26 E.

CHAINS	
44.69	Point for the center $\frac{1}{4}$ sec. cor. of sec. 6, at intersection with the E. and W. centerline of sec. 6, not monumented.
47.40	Zuni River, 30 lks. wide, 5 ft. banks, course westerly.
66.99	Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 6. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T14N R26E C N $\frac{1}{16}$ S 6 C 1968 </div>
89.23	Deposit glass at the base of the iron post. The $\frac{1}{4}$ sec. cor. of sec. 6 only, on the N. bdy. of the Tp. Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.
3.90	From the $\frac{1}{4}$ sec. cor. of secs. 5 and 6. S. $86^{\circ}39'$ W., on the E. and W. centerline of sec. 6. Over nearly level land.
10.30	Right bank of the Zuni River, bears S. 15° E. and N. 15° W., curving sharply W.
29.50	Right bank of the Zuni River, bears S. 15° E. and N. 15° W.
29.50	Zuni River, 25 lks. wide, with 4 ft. banks, course N. 40° W.
29.77	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 6. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T14N R26E E $\frac{1}{16}$ C _____ C S 6 1968 </div>
34.80	Deposit glass at the base of the iron post.
34.80	Fence, bears SE. and NW.
38.00	Track road, bears S. 50° E. and N. 50° W.
45.00	Track road, bears irregularly N. and S.
45.10	Fence, bears NE. and SW.
46.40	Wash, 30 lks. wide, with 8 ft. banks, drains NW.
59.54	The point for the center $\frac{1}{4}$ sec. cor. of sec. 6.

Survey, Subdivision Section 6, T. 14 N., R. 26 E.

CHAINS	
65.70	Fence, bears N. 30° W. and S. 30° E. for 1.80 chs. dist. to cor. of fences bearing E. and N. 30° W.
65.80	Track road, bears S. 30° E. and N. 30° W.
89.31	Point for the C-W 1/16 sec. cor. of sec. 6; not monumented.
117.75	<p>The point for the ¼ sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp.</p> <p>Land, nearly level. Timber, none. Soil, sandy loam. Undergrowth, bunchgrass and sagebrush.</p>
Subdivision, NE¼ Section 6	
From the C-E 1/16 sec. cor. of sec. 6.	
N. 7°47' E., on the N. and S. centerline of the NE¼ of sec. 6.	
Over nearly level land.	
0.30	Zuni River, 25 lks. wide, with 4 ft. banks, course westerly from S. 40° E.
8.80	Wash, 30 lks. wide, with 4 ft. banks, drains westerly.
23.08	<p>Point for the NE 1/16 sec. cor. of sec. 6, at the intersection with the E. and W. centerline of the NE¼ of sec. 6.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
T14N R26E NE 1/16 S 6 1968	
Deposit glass at the base of the iron post.	
46.07	The E 1/16 sec. cor. of sec. 6 only, on the N. bdy. of the Tp.
From the N 1/16 sec. cor. of secs. 5 and 6.	
S. 85°01' W., on the E. and W. centerline of the NE¼ of sec. 6.	
Over nearly level land.	
29.55	The NE 1/16 sec. cor. of sec. 6.
59.09	The C-N 1/16 sec. cor. of sec. 6.
Subdivision, NW¼ Section 6	
From the point for the C-W 1/16 sec. cor. of sec. 6.	

Survey, Subdivision Section 6, T. 14 N., R. 26 E.

CHAINS	
	N. 10°04' E., on the N. and S. centerline of the NW¼ of sec. 6. Over nearly level land.
11.90	Track road, bears S. 80° E. and N. 80° W.
18.90	Fence, bears N. 75° E. and S. 75° W.
21.50	Point for the NW 1/16 sec. cor. of sec. 6, at the intersection with the E. and W. centerline of the NW¼ of sec. 6. Set the iron post 22 ins. in the ground, brass cap mkd. T14N R26E NW 1/16 S 6 1968
	Deposit glass at the base of the iron post.
33.00	Zuni River, 30 lks. wide, with 7 ft. banks, course westerly.
40.30	Wash, 20 lks. wide, with 4 ft. banks, drains SW.
42.99	The W 1/16 sec. cor. of sec. 6 only, on the N. bdy. of the Tp.
	From the C-N 1/16 sec. cor. of sec. 6. S. 85°02' W., on the E. and W. centerline of the NW¼ of sec. 6. Over nearly level land.
2.50	Zuni River, 30 lks. wide, with 4 ft. banks, course northerly.
14.90	Zuni River, 25 lks. wide, with 4 ft. banks, course southerly.
24.50	Zuni River, 30 lks. wide, with 5 ft. banks, course NW.
26.00	Fence (abandoned), bears SE. and NW.
29.53	The NW 1/16 sec. cor. of sec. 6.
41.80	Zuni River, 30 lks. wide, with 4 ft. banks, course southerly.
47.80	Zuni River, 30 lks. wide, with 4 ft. banks, course northerly.
57.66	The point for the N 1/16 sec. cor. of secs. 1 and 6 on the W. bdy. of the Tp.
	Subdivision, Section 10, T. 14 N., R. 26 E.
	From the ¼ sec. cor. of secs. 10 and 15. N. 0°05' W., on the N. and S. centerline of sec. 10.

Survey, Subdivision Section 10, T. 14 N., R. 26 E.

CHAINS	
	Over rolling land.
0.84	Fence, bears E. and W.
1.54	Wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.
14.70	Wash, 10 lks. wide, 1 ft. deep, drains SW.
21.72	Point for the C-S 1/16 sec. cor. of sec. 10. Set the iron post 12 ins. in the ground, mound of stone 3 ft. base to top, brass cap mkd. <div style="text-align: center;"> T14N R26E C S 1/16 S10 C 1972 </div>
35.00	Wash, 20 lks. wide, 1 ft. deep, drains SW.
43.44	Point for the center 1/4 sec. cor. of sec. 10, at intersection with the E. and W. centerline of sec. 10. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T14N R26E C 1/4 + S10 1968 </div>
86.88	The 1/4 sec. cor. of secs. 3 and 10. Land, rolling. Soil, rocky, sandy loam. Timber, scattered cedar. Undergrowth, bunchgrass and sagebrush.
	From the 1/4 sec. cor. of secs. 10 and 11. S. 84°03' W., on the E. and W. centerline of sec. 10. Over rolling land.
31.70	Wash, 20 lks. wide, 1 ft. deep, drains SW.
40.41	The center 1/4 sec. cor. of sec. 10.
80.70	Track road, bears N. and S.
80.85	The 1/4 sec. cor. of secs. 9 and 10. Land, rolling. Soil, rocky, sandy loam. Timber, scattered juniper. Undergrowth, bunchgrass and sagebrush.
	Subdivision, Section 14, T. 14 N., R. 26 E.

Survey, Subdivision Section 14, T. 14 N., R. 26 E.

CHAINS		
	<p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23. N. $1^{\circ}13'$ E., on the N. and S. centerline of sec. 14. Over rolling land.</p>	
13.30	Wash, 70 lks. wide, with 8 ft. banks, drains SW.	
21.415	<p>Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 14. Set an iron post 8 ins. in the ground, over an X chiseled on solid sandstone, mound of stone, 4 ft. base to top, brass cap mkd.</p>	
	<p style="text-align: center;">T14N R26E C S $\frac{1}{16}$ S14 C 1972</p>	
27.50	Track road, bears N. 55° E. and S. 55° W.	
29.40	Fence, bears irregularly NE. and SW.	
42.83	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 14, at intersection with the E. and W. centerline of sec. 14. Set the iron post 6 ins. in the ground, over an X chiseled on solid sandstone, mound of stone 4 ft. base to top, brass cap mkd.</p>	
	<p style="text-align: center;">T14N R26E C C$\frac{1}{4}$+S14 1972</p>	
45.00	Ravine, 15 lks. wide with 12 ft. banks, drains SW.	
89.35	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 14. Land, rolling. Soil, rocky, sandy loam. Timber, scattered cedar. Undergrowth, bunchgrass and sagebrush.</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. S. $88^{\circ}29'$ W., on the E. and W. centerline of sec. 14. Over rolling land.</p>	
39.90	The center $\frac{1}{4}$ sec. cor. of sec. 14.	
42.30	Wash, 15 lks. wide, with 12 ft. banks; drains SW.	
64.50	Wash, 20 lks. wide, 2 ft. deep, drains S.	
73.60	Wash, 25 lks. wide, 4 ft. banks, drains SW.	
77.01	Fence, bears irregularly N. and S.	
80.33	The $\frac{1}{4}$ sec. cor. of secs. 14 and 15.	

Survey, Subdivision Section 14, T. 14 N., R. 26 E.

CHAINS

Land, rolling.
Soil, sandy loam.
Timber, scattered cedar.
Undergrowth, bunchgrass and sagebrush.

Subdivision, Section 22, T. 14 N., R. 26 E.

From the point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.

N. $0^{\circ}28'$ E., on the N. and S. centerline of sec. 22.

Over nearly level land.

19.37 Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 22; not monumented.

38.74 Point for the center $\frac{1}{4}$ sec. cor. of sec. 22, at the intersection with the E. and W. centerline of sec. 22; not monumented.

54.30 Wash, 30 lks. wide, 3 ft. deep, drains W.

56.00 Fence, bears E. and W.

77.38 Fence, bears N. $83^{\circ}53'$ E. and S. $83^{\circ}53'$ W.

77.48 The point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22.

Land, nearly level.
Soil, sandy loam.
Timber, none.
Undergrowth, bunchgrass and sagebrush.

From the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

S. $88^{\circ}18'$ W., on the E. and W. centerline of sec. 22.

Over nearly level land.

19.67 Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 22.

Set the iron post 24 ins. in the ground, brass cap mkd.

T14N R26E
E 1/16
C _____ C
S22
1968

Set a wooden post, 7 ft. long, 4 ins. diam., alongside the cor.

39.34 The point for the center $\frac{1}{4}$ sec. cor. of sec. 22.

59.10 Fence, (abandoned), bears N. and S.

78.10 Fence, bears N. and S.

78.68 The point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.

Survey, Subdivision Section 22, T. 14 N., R. 26 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, sagebrush and bunchgrass.</p>
	<p>Subdivision, SE$\frac{1}{4}$ Section 22</p> <hr/>
	<p>From the point for the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>N. 0°19' E., on the N. and S. centerline of the SE$\frac{1}{4}$ sec. 22.</p> <p>Over nearly level land.</p>
20.13	<p>Point for the SE 1/16 sec. cor. of sec. 22, at the intersection with the E. and W. centerline of the SE$\frac{1}{4}$ of sec. 22.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R26E SE 1/16 S22 1968</p> <p>Deposit glass at the base of the iron post.</p>
20.50	Fence, bears N. 80° W. and S. 80° E., approximately 250 lks. to cor. of fences bearing N. 80° W. and S. 7°35' W.
40.27	The C-E 1/16 sec. cor. of sec. 22.
	<p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>N. 89°45' W., on the E. and W. centerline of the SE$\frac{1}{4}$ of sec. 22.</p> <p>Over nearly level land.</p>
18.00	Fence, bears N. 7°35' E. and S. 7°35' W.
19.72	The SE 1/16 sec. cor. of sec. 22.
38.30	Track road, bears N. and S.
39.43	The point for the C-S 1/16 sec. cor. of sec. 22.
	<p>Subdivision, Section 24, T. 14 N., R. 26 E.</p> <hr/>
	<p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.</p> <p>N. 3°14' W., on the N. and S. centerline of sec. 24.</p> <p>Over nearly level land.</p>
1.05	Little Colorado River, 150 lks. wide, 2 ft. deep, course W.
20.87	<p>Point for the C-S 1/16 sec. cor. of sec. 24.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>

Survey, Subdivision Section 24, T. 14 N., R. 26 E.

CHAINS

T14N R26E
 C
 S 1/16 | S24
 |
 C
 1972

Raise a mound of stone, 2 ft. base, 16 ins. high, W. of the cor.

- 21.64 Junction of track roads, bears W., 13 lks. dist., roads bear NE., SE. and SW.
- 23.50 Enter rolling land, bears N. 20° E. and S. 10° W.
- 41.74 Point for the center $\frac{1}{4}$ sec. cor. of sec. 24, at the intersection with the E. and W. centerline of sec. 24.
- Set the iron post 24 ins. in the ground, brass cap mkd.

T14N R26E
 C $\frac{1}{4}$ +S24
 1972

Set a cedar post, 5 $\frac{1}{2}$ ft. long, 3 ins. diam., 2 ft. in the ground along the W. side of the cor.

- 52.00 Wash, 10 lks. wide, 2 ft. deep, drains SE.
- 83.44 The $\frac{1}{4}$ sec. cor. of secs. 13 and 24.

Land, nearly level to rolling.
 Soil, rocky, sandy loam.
 Timber, scattered to dense cedar.
 Undergrowth, bunchgrass and sagebrush.

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.

S. 81°40' W., on the E. and W. centerline of sec. 24

Over rolling land.

- 21.60 Track road, bears N. 60° E. and S. 60° W.
- 42.11 The center $\frac{1}{4}$ sec. cor. of sec. 24.
- 54.00 Wash, 10 lks. wide, 2 ft. deep, drains SW.
- 71.00 Wash, 10 lks. wide, 3 ft. deep, drains southerly.
- 84.21 The $\frac{1}{4}$ sec. cor. of secs. 23 and 24.

Land, rolling.
 Soil, rocky sandy loam.
 Timber, scattered to dense cedar.
 Undergrowth, bunchgrass and sagebrush.

General Description

CHAINS

The area encompassed by this survey varies from nearly level land to mountainous. Elevations range from 5440 feet to 6060 feet above sea level. The soil is mostly sandy clay loam interspersed with gravelly loam in certain areas. Vegetation consists of sagebrush and bunchgrass with the higher elevations containing moderate to scattered growth of juniper timber.

The Little Colorado River, containing water in various places, enters the township on the East boundary of Section 25 and traverses in a westerly direction leaving the surveyed area on the West boundary of Section 15.

The Zuni River, containing water in various places, enters the township on the East boundary of Section 1 and traverses in a westerly direction, leaving the township on the West boundary of Section 6.

Within the area surveyed, only one ranch house was noted, that being in the southern portion of Section 10.

The primary use of this land is for the grazing of livestock.

There is no evidence of mineral activity during the past.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ira M. Thiessen	Surveying Technician
Ronald M. Williams	Surveying Aid
Martin W. Fuller	Surveying Aid
Jerrol L. Jones	Surveying Aid
Harry K. Smith	Cadastral Surveyor
Kurt Merkle	Surveying Aid
Ronald McCally	Surveying Aid
Kenneth Weir	Surveying Aid

48

CERTIFICATE OF SURVEY

(I) (We), Louis D. Gilbert and Paul G. Bauer, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of March, 1968, (We) have dependently resurveyed the East boundary, a portion of the West and North boundaries and subdivisional lines and surveyed subdivisions in certain sections in Township 14 North, Range 26 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (us) and under (my) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 27, 1970 (Date)

(Cadastral Surveyor) Louis D. Gilbert

October 1, 1973 (Date)

(Cadastral Surveyor) Paul G. Bauer

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date NOV 8 1973

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of the East boundary, a portion of the West and North boundaries and subdivisional lines and the survey of subdivisions in certain sections in Township 14 North, Range 26 East, Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert and Paul G. Bauer

having been critically examined and found correct, are hereby approved.

MAY 7 1974 (Date)

(Chief, Division of Cadastral Survey) Bernard W. Foster

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above described surveys in is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626