

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

DEPENDENT RESURVEY

of the

SOUTH BOUNDARY

and the

DEPENDENT RESURVEY

of a

PORTION OF THE EAST BOUNDARY

AND SUBDIVISIONAL LINES

and the

SURVEY

of

SUBDIVISION OF CERTAIN SECTIONS

of

TOWNSHIP 14 NORTH

RANGE 27 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer Cadastral Surveyor

Louis D. Gilbert Cadastral Surveyor

Under special instructions dated March 29, 19 68, which provided for the surveys

included under Group Number 481, approved April 3, 1968,

and assignment instructions dated April 5, 19 68.

July 10 1972

Survey commenced September 24, 19 68

Survey completed November 7, 19 72

BOOK 4988

INDEX DIAGRAM

Township 14 North, Range 27 East,

6 37	37 5 36	28 4 28	22 3 22	2	1 10
7 35	35 8 34	27 9 27	21 10 20	13 11	9 12 8
18 33	33 17 32	26 16 26	20 15 19	14	13
19	31 20 30	24 21 23	17 22 16	11 23	24
30	29	28	27 15	26	25
31 3	32 4	33 5	14 34 5	10 35 6	36 7

Subdivision of Section 4, Page 38
Subdivision of Section 6, Page 41
Subdivision of Section 20, Page 44
Subdivision of Section 22, Page 47
Subdivision of Section 34, Page 51

Township 14 North, Range 27 East
Gila and Salt River Meridian, Arizona

CHAINS

The south boundary was surveyed in 1875 by C. B. Foster and resurveyed in 1882 by A. P. Johnson. The east boundary was surveyed in 1875 by C. B. Foster; the south one mile was retraced in 1944 by Forrest and Warner. The west boundary was surveyed in 1875 by C. B. Foster; the south two miles was retraced in 1944 by Forrest and Warner and the north one mile was retraced in 1963-64 by Owens, Bauer and Ott. The north boundary was surveyed in 1875 by C. B. Foster; resurveyed in 1882 by A. P. Johnson; the west three miles was retraced in 1944 by Forrest and Warner and retraced again in 1963-64 by Owens, Bauer and Ott. The subdivisional lines were surveyed in 1875 by C. B. Foster; a portion of the subdivisional lines were retraced in 1944 by Forrest and Warner. The north boundary was resurveyed by J. E. Knight in 1968.

The following notes are those of a dependent resurvey of the south boundary and of a portion of the east boundary and subdivisional lines, designed to restore the corners in their true original location according to the best available evidence, and a survey of the subdivisions in certain sections in Township 14 North, Range 27 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated March 29, 1968. The direction of all lines were determined by solar observation and all lines refer to the true meridian.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 ins. long, 2½ ins. diameter, flanged at the base, with a brass cap riveted to the top.

The geographic position of the southeast corner of the township as determined by calculation from that given for the southeast corner of Township 15 North, Range 26 East, as shown on the plat approved August 31, 1964, is: Latitude 34°34'08.8" N. and Longitude 109°24'37.4" W.

The mean magnetic declination was found to be 14° E.

Dependent Resurvey of a Portion of the East Boundary
T. 14 N., R. 27 E., G&SRM., Arizona

Reestablishment of the Survey executed
by C. B. Foster in 1875

Beginning at the cor. of secs. 7, 12, 13 & 18, marked by a cor. of fences extending S. 1°35' E., S. 88°22' W. and N. 1°21' W. There is no remaining evidence of the orig. cor. monument. This fence cor. has long been used by adjacent land-owners and is accepted as the best remaining evidence of the orig. cor. position.

Dependent Resurvey, Portion E. Bdy., T. 14 N., R. 27 E.

CHAINS		
	<p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E R28E <u>S12 S 7</u> S13 S18. 1972</p> <p>from which</p> <p style="padding-left: 40px;">A windmill, bears N. 75°19' W., 33.71 chs. dist.</p> <p>N. 1°13' W., bet. secs. 7 and 12.</p> <p>Over gently rolling land, along a N-S fenceline.</p>	
25.60	Low ridge, bears E. and W.	
27.80	Draw, drains N. 25° E.	
39.30	<p>Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E R28E ¼ <u>S12 S 7</u> 1972</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>The cor. is located 8 lks. E. of a N-S fenceline.</p>	
78.60	<p>The cor. of secs. 1, 6, 7 and 12, marked by a cor. of fences extending N. 74° E., S. 1°05' E. and N. 88°51' W. There is no remaining evidence of the orig. cor. monument. This fence cor. has long been used by adjacent landowners and is accepted as the best remaining evidence of the orig. cor. position.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E R28E. <u>S 1 S 6</u> S12 S 7 1972.</p> <p>from which</p>	

Dependent Resurvey, Portion E. Bdy., T. 14 N., R. 27 E.

CHAINS	
	<p>A windmill, bears N. 20°44' W., 20.41 chs. dist.</p> <p>The cor. of Tps. 14 and 15 N., Rs. 27 and 28 E., bears N. 11°31' E., 101.40 chs. dist., monumented by an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, in a collar of stone, 20 ins. diam., brass cap mkd.</p> <p style="text-align: center;"> T15N R27E R28E S36 S31 S 1 S 6 T14N 1963 </p> <p>This line was fully retraced and a diligent search was made for evidence of the intervening cor. which was not recovered.</p> <p>Land, gently rolling. Soil, shallow, sandy loam. Timber, none. Undergrowth, moderate grass and sagebrush.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of the South Boundary, T. 14 N., R. 27 E., G&SRM., Arizona</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey executed by A. P. Johnson in 1882</p> <hr/> <p>From the cor. of Tps. 13 and 14 N., Rs. 26 and 27 E., monumented by an iron post, as described in the notes of the resurvey of the E. bdy., T. 14 N., R. 26 E., resurveyed concurrently under this same Group No.</p> <p>N. 89°05' E., bet. secs. 6 and 31.</p> <p>Over rolling land.</p>
8.20	Ravine, drains N.
11.30	Underground telephone cable, bears S. 60° E. and N. 60° W.
13.70	Dim track road, bears N. and S.
23.00	Spur, slopes NW.
36.50	Spur, slopes N.
40.78	The ¼ sec. cor. of secs. 6 and 31, monumented by a lava stone, 15x12x6 ins., firmly set in a mound of stone, mkd. ¼ on N. face; not remonumented.

Dependent Resurvey of the S. Bdy., T. 14 N., R. 27 E.

CHAINS		
	N. 89°05' E., beginning new measurement. Over rolling land.	
1.30	Ravine, drains N.	
6.50	Spur, slopes N.	
24.90	Wash, 10 lks. wide, 2 ft. deep, drains N.	
26.70	Bladed road, bears S. 20° E. and N. 20° W.	
34.60	Track road, bears N. 20° E. and S. 20° W.	
38.85	Fence, bears S. and N., 235 lks. dist. to cor. of fences bearing E., S. and W., approx. 400 lks. dist. to cor. of fences bearing E. and NW.	
41.21	The cor. of secs. 5, 6, 31 and 32, monumented by a limestone, 12x10x4 ins., lying loose on the ground, mkd. with 5 notches on a face and 1 notch on an adjacent face, with mound of stone W. I reset the cor. 6 ins. in the ground and rebuild the mound of stone W. Land, rolling. Soil, rocky, sandy loam. Timber, scattered juniper. Undergrowth, bunchgrass and sagebrush.	
	N. 89°16' E., bet. secs. 5 and 32. Over rolling land.	
16.00	Spur, slopes NW.	
40.30	The ½ sec. cor. of secs. 5 and 32, monumented by a lava stone, 24x16x12 ins., firmly set in a mound of stone, mkd. ½ on E. face; not remonumented.	
	N. 89°36' E., beginning new measurement. Over gently rolling land.	
27.40	Fence, bears S. 10° E. and N. 10° W.	
27.60	Track road, bears N. and S.	
40.26	Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist., from which a lava stone, 18x12x10 ins., lying loose on the ground, mkd. with X, 4 notches on a face and 2 notches on an adjacent face, bears N. 80°03' E., 2.875 chs. dist. (Record calls for a sandstone). The found position and condition of this stone is not harmoniously related to the remaining found corners along the south boundary of T. 14 N., R. 27 E., and is not accepted as the true corner position, not remonumented. Land, rolling to gently rolling. Soil, rocky, sandy loam. Timber, widely scattered juniper. Undergrowth, bunchgrass and sagebrush.	

Dependent Resurvey of the S. Bdy., T. 14 N., R. 27 E.

CHAINS	
	N. 89°36' E., bet. secs. 4 and 33. Over gently rolling land.
3.58	Fence cor., bears N., 7 lks. dist. to cor. of fences bearing N., S. 80° E. and N. 80° W.
10.30	Descend abrupt E. slope.
24.80	Ravine, drains NE.
40.26	The ¼ sec. cor. of secs. 4 and 33, monumented by a lava stone, 14x10x8 ins., firmly set in cor. of fences bearing N., S. 80° E., S. and N. 80° W., dimly mkd. ¼ on W. face; not remonumented.
	<hr/>
	N. 89°03' E., beginning new measurement. Over gently rolling land.
6.40	Bladed road, bears N. and S.
40.95	The cor. of secs. 3, 4, 33 and 34, monumented by a sandstone, 12x10x8 ins., lying loose in a scattered mound of stone, mkd. with 3 notches on a face and 3 notches on an adjacent face. I reset the cor. stone 6 ins. in the ground and raise a mound of stone W. This cor. is located in a fence, bearing N. and S. Land, gently rolling. Soil, rocky sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.
	<hr/>
	N. 89°05' E., bet. secs. 3 and 34. Over gently rolling land.
2.50	Wash, 50 lks. wide, 3 ft. deep, drains N., 10° E.
37.60	Small wash, drains N. 20° E.
40.55	The ¼ sec. cor. of secs. 3 and 34, monumented by a lava stone, 10x10x5 ins., firmly set 5 ins. in the ground, mkd. ¼ on N. face, with mound of stone N.; not remonumented. This cor. is located in a fenceline bearing N. and S.
	<hr/>
	N. 89°09' E., beginning new measurement. Over gently rolling land.
20.17	Point for the E 1/16 sec. cor. of secs. 3 and 34, at proportionate dist.

Dependent Resurvey of the S. Bdy., T. 14 N., R. 27 E.

CHAINS

Set the iron post 20 ins. in the ground, brass cap mkd.

T14N R27E
E 1/16 $\frac{S34}{S 3}$
T13N
1968

from which

A fence, bears South, 6.5 lks. dist., fence bears irregularly E. and W.

Deposit glass at the base of the iron post.

38.90 Wash, 30 lks. wide, 2 ft. deep, drains N.

40.34 The cor. of secs. 2, 3, 34 and 35, monumented by a sandstone, 12x12x5 ins., firmly set 10 ins. in the ground, mkd. with 2 notches on E. face and 4 notches on W. face.

At the cor. point

Set the iron post 20 ins. in the ground, brass cap mkd.

T14N R27E
 $\frac{S34}{S 3} | \frac{S35}{S 4}$
T13N
1968

from which

A fence, bears South, 16 lks. dist., fence bears irregularly E. and W.

Bury the orig. cor. stone alongside the iron post.

Land, gently rolling.

Soil, sandy loam.

Timber, none.

Undergrowth, bunchgrass and sagebrush.

N. 89°10' E., bet. secs. 2 and 35.

Over gently rolling land.

29.90 Track road, bears S. 80° E. and NW.

40.62 The $\frac{1}{2}$ sec. cor. of secs. 2 and 35, monumented by a sandstone, 12x6x6 ins., firmly set 4 ins. in the ground, mkd. $\frac{1}{2}$ on N. face, with mound of stone N.; not remonumented. This cor. is located 26 lks. N. of a fenceline bearing irregularly E. and W.

Dependent Resurvey of the S. Bdy., T. 14 N., R. 27 E.

CHAINS	
	N. 89°10' E., beginning new measurement.
	Over gently rolling land.
29.30	Track road, bears N. and S.
40.37	The cor. of secs. 1, 2, 35 and 36, monumented by a lava stone, 12x10x4 ins., firmly set 8 ins. in the ground, mkd. with 1 notch on E. face and 5 notches on W. face, with mound of stone W.; not remonumented. This cor. is located in a fenceline bearing N. and S., 33 lks. dist., to cor. of fences bearing N., E. and W.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, sagebrush and bunchgrass.
	N. 89°10' E., bet. secs. 1 and 36.
	Over gently rolling land.
38.30	Wash, 10 lks. wide, 3 ft. deep, drains NE.
40.66	Cor. of fences, bears S., 71 lks. dist., fences bear E., S. and W.
40.98	The $\frac{1}{2}$ sec. cor. of secs. 1 and 36, monumented by a lava stone, 12x8x6 ins., firmly set in a mound of stone, mkd. $\frac{1}{2}$ on N. face; not remonumented. This cor. is located 71 lks. N. of a fence bearing E. and W.
	N. 88°38' E., beginning new measurement.
	Over gently rolling land.
40.34	The cor. of Tps. 13 and 14 N., Rs. 27 and 28 E., monumented by an iron post, 3 ins. diam., firmly set, projecting 1 in. above ground, brass cap mkd.
	<p style="text-align: center;">T14N R27E R28E <u>S36</u> <u>S31</u> S 1 S 6 T13N 1944</p>
	The cor. is located 160 lks. N. of an E. and W. fence-line.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	Dependent Resurvey, Portion Subdivisional Lines, T. 14 N., R. 27 E.
	<p>Reestablishment of the Survey executed by C. B. Foster in 1875</p> <hr/>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 88°21' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land, along a fence.</p>
11.90	Wash, 30 lks. wide, 3 ft. deep, drains S. 50° W.
25.60	Track road and gate in E-W fence, road bears S. 10° E. and N. 10° W.
40.94	<p>Point for the $\frac{1}{2}$ sec. cor. of secs. 12 and 13, at propor- tionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 23 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E</p> <p>$\frac{1}{2}$ $\frac{S12}{S13}$</p> <p>1972</p> </div> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1 ft. high, N. of the cor.</p> <p>The cor. is located 1 lk. N. of an E-W fence.</p>
44.90	Wash, 50 lks. wide, with 5 ft. banks, drains S. 30° W.
55.60	Wash, 10 lks. wide, 1 ft. deep, drains S. 35° W., curving S.
63.80	Wash, 10 lks. wide, 2 ft. deep, drains S.
67.80	Wash, 25 lks. wide, 3 $\frac{1}{2}$ ft. deep, drains S. 50° W.
69.30	Wash, 10 lks. wide, 3 ft. deep, drains S. 30° W.
81.88	<p>The cor. of secs. 11, 12, 13 and 14, marked by a cor. of fences extending N. 88°20' E., S. 2°12' E., N. 88°20' W. and N. 2°12' W. There is no remaining evidence of the orig. cor. monument. This fence cor. has long been used by adjacent landowners and is accepted as the best remain- ing evidence of the orig. cor. position.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E</p> <p>$\frac{S11}{S14} \frac{S12}{S13}$</p> <p>1972</p> </div>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14. N., R. 27 E.

CHAINS	
	<p>Land, gently rolling. Soil, sandy clay loam. Timber, none. Undergrowth, scattered to moderate bunchgrass and sagebrush.</p>
	<p>N. 2°15' W., bet. secs. 11 and 12.</p>
	<p>Over gently rolling land.</p>
3.40	<p>Wash, 10 lks. wide, 1½ ft. deep, drains S. 30° W. from N. 5° E.</p>
23.60	<p>Track road, bears N. 75° E. and S. 75° W.</p>
39.35	<p>Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E ¼ S11 S12 1972</p> <p>Raise a mound of stone, 1½ ft. base, 1½ ft. high, W. of the cor.</p> <p>The cor. is located in a N-S fenceline.</p>
41.90	<p>Wash, 10 lks. wide, 1 ft. deep, drains NE.</p>
63.80	<p>Wash, 15 lks. wide, 3 ft. deep, drains N. 75° E.</p>
70.10	<p>Spur, slopes N. 60° E.</p>
74.35	<p>Wash, 15 lks. wide, 2 ft. deep, drains N. 55° E.</p>
78.70	<p>The cor. of secs. 1, 2, 11 and 12, marked by a cor. of fences extending N. 88°24' E. and S. 2°15' E. There is no remaining evidence of the orig. cor. monument. This fence cor. has long been used by adjacent landowners and is accepted as the best remaining evidence of the orig. cor. position.</p> <p>At the cor. point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, 1½ ft. base, 1 ft. high, brass cap mkd.</p> <p style="text-align: center;">T14N R27E S 2 S 1 S11 S12 1972</p> <p>from which</p> <p>The point for the cor. of secs. 1, 2, 35 and 36, at proportionate measurement, on the N. bdy. of the Tp., bears N. 12°57' E., 105.40 chs. dist., not monumented. This line was fully retraced and a diligent search was made for evidence of the intervening corner, which was not recovered. The north boundary, between the corner of Tps. 14 and 15 N., Rs. 27 and 28 E. and the corner of sections</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS		
	<p>2, 3, 34 and 35, Tps. 14 and 15 N., R. 27 E., was retraced and found essentially the same as that given in the field notes and on the plat of the Dependent Resurvey of the South Boundary of T. 15 N., R. 27 E. in 1968 by J. E. Knight.</p> <p>Land, gently rolling to rolling. Soil, shallow clay loam. Timber, none. Undergrowth, scattered bunchgrass and sagebrush.</p>	
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p>	
	<p>S. 88°24' W., bet. secs. 1 and 12.</p>	
	<p>Over nearly level land, along an E-W fenceline.</p>	
20.33	<p>A cor. of fences, bears North, 2½ lks. dist., fences extend N. 43° E., N. 88°26' E. and S. 88°22' W.</p>	
41.64	<p>Point for the ¼ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T14N R27E ¼ $\frac{S}{S12}$ 1972</p>	
	<p>Set a cedar post, 3 ins. diam., 6 ft. long, 3 ft. in the ground, along the N. side of the iron post.</p>	
	<p>The cor. is located 3 lks. North of a fence bearing N. 88°23' E. and S. 88°23' W.</p>	
61.50	<p>A stock pond, 3 chs. diam., bears South, 275 lks. dist.</p>	
83.28	<p>The cor. of secs. 1, 2, 11 and 12.</p>	
	<p>Land, nearly level. Soil, clay loam. Timber, none. Undergrowth, moderate sagebrush, cockleburs and shadscale, scattered bunchgrass.</p>	
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp.</p>	
	<p>N. 0°03' W., bet. secs. 34 and 35.</p>	
	<p>Over gently rolling land.</p>	
40.13	<p>The ¼ sec. cor. of secs. 34 and 35, monumented by a sandstone, 16x9x4 ins., firmly set 9 ins. in the ground, mkd. ¼ on W. face, with scattered mound of stone W. (Record calls for a 4 ft. long post, flattened, 3 ins. wide, mkd. ¼ S).</p>	
	<p>At the cor. point</p>	
	<p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p style="text-align: center;">T14N R27E</p>
	<p style="text-align: center;">$\frac{1}{4}$</p>
	<p style="text-align: center;">S34 S35</p>
	<p style="text-align: center;">1968</p>
	<p>Bury the cor. stone alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°06' W., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
15.30	<p>Track road, bears S. 70° E. and N. 70° W.</p>
20.06	<p>Point for the N 1/16 sec. cor. of secs. 34 and 35, at proportionate dist.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E</p>
	<p style="text-align: center;">N 1/16</p>
	<p style="text-align: center;">S34 S35</p>
	<p style="text-align: center;">1968</p>
	<p>Deposit glass at the base of the iron post.</p>
38.90	<p>Track road, bears S. 20° E. and N. 20° W.</p>
40.06	<p>Cor. of fences, bears E., W. and N. 0°01' W..</p>
40.12	<p>The cor. of secs. 26, 27, 34 and 35, monumented by a sandstone, 25x10x4 ins., firmly set 10 ins. in the ground, mkd. 2 notches on E. face and 1 notch on S. face, with mound of stone W. (Record calls for a post 4 ft. long, 3 ins. squared, marked and notched.)</p>
	<p>At the cor. point</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E</p>
	<p style="text-align: center;">S27 S26</p>
	<p style="text-align: center;">S34 S35</p>
	<p style="text-align: center;">1968</p>
	<p>Bury the cor. stone alongside the iron post.</p>
	<p>This cor. is located in a fence, bearing S. 0°01' E. and N. 0°01' W.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, sandy loam.</p>
	<p>Timber, none.</p>
	<p>Undergrowth, bunchgrass and sagebrush.</p>
	<hr/>
	<p>From the cor. of secs. 22, 23, 26 and 27, marked by a cor. of fences bearing N. 88°33' E., S. 3°07' E., N. 3°07' W. There is no remaining evidence of the orig. cor. monument. This fence cor. has been used for many years by adjacent land-owners and is accepted as the best remaining evidence of the orig. cor. position; not monumented.</p>
	<p>from which</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS		
	<p>The cor. of secs. 23, 24, 25 and 26, bears N. 88°24' E., 79.96 chs. dist., marked by a cor. of fences; fences extend N. 88°30' E., southerly and S. 88°24' W. This line was fully retraced and a diligent search was made for evidence of the intervening corner, which was not recovered.</p>	
	N. 2°10' W., bet. secs. 22 and 23.	
	Over gently rolling land.	
17.20	Track road, bears southerly and N. 60° W.	
18.60	Track road, bears southerly and N. 30° W.	
20.18	Point for the S 1/16 sec. cor. of secs. 22 and 23, at proportionate dist.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T14N R27E S 1/16 S22 S23 1972</p>	
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.	
30.00	Leave gently rolling land, bears irreg. E. and W., enter nearly level land, in old lake bottom.	
32.50	Little Colorado River, 30 lks. wide, 1 ft. deep, drains N. 80° W., thence over old lake bottom (Zion Reservoir).	
40.36	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate dist., there is no remaining evidence of the orig. cor. monument.	
	Set the iron post 20 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T14N R27E ¼ S22 S23 1972</p>	
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.	
	Continue over Zion Reservoir.	
80.72	Point for the cor. of secs. 14, 15, 22 and 23, determined latitudinally by stubs of fence posts and barbed wire extending N. 88°25' E., and S. 88°42' W., and longitudinally by proportionate measurement.	
	At the cor. point	
	Set the iron post 26 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">T14N R27E S15 S14 S22 S23 1972</p>	
	from which	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p>The cor. of secs. 13, 14, 23 and 24, bears N. 88° 25' E., 81.34 chs. dist., marked by a cor. of fences; fences extend N. 88°25' E., S. 1°06' E., S. 88° 25' W., and N. 1°15' W. This fence cor. has long been used by adjacent land-owners and is accepted as the best remaining evidence of the orig. cor. position. This line was fully retraced and a diligent search was made for evidence of the intervening corner, which was not recovered.</p>
	<p>Land, gently rolling to nearly level. Soil, clay loam. Timber, none. Undergrowth, scattered bunchgrass and sagebrush.</p>
	<p>At the cor. of secs. 10, 11, 14 and 15, marked by a cor. of fences bearing S. 0°01' W., S. 89°33' W. and N. 1°23' W. This fence cor. has been used for many years by adjacent land-owners and is accepted as the best remaining evidence of the orig. cor. position.</p>
	<p>Set the iron post 22 ins. in the ground, in a collar of stone to top, 2 ft. base, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E <u>S10 S11</u> <u>S15 S14</u> 1972</p>
	<p>from which</p>
	<p>The cor. of secs. 11, 12, 13 and 14, bears N. 89°40' E., 80.40 chs. dist., previously described. This line was fully retraced and a diligent search was made for evidence of the intervening cor., which was not recovered.</p>
	<p>N. 1°11' W., bet. secs. 10 and 11.</p>
	<p>Over gently rolling land.</p>
8.90	<p>Wash, 30 lks. wide, with 4 ft. banks, drains S. 30° W.</p>
16.30	<p>Track road, bears irreg. E. and W.</p>
42.90	<p>Wash, 15 lks. wide, with 3 ft. banks, drains NW.</p>
45.74	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 6 ins. in the ground, mound of stone, 3½ ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E $\frac{1}{4}$ <u>S10 S11</u> 1972</p>
	<p>The cor. is located 11 lks. E. of an irreg. N-S fence-line.</p>
52.80	<p>Draw, drains N. 70° E.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
69.40	Enter bottom land, bears E. and W.
75.20	Zuni River, dry, 50 lks. wide, 2 ft. deep, drains West.
91.48	Point for the cor. of secs. 2, 3, 10 and 11, determined longitudinally by a N-S fenceline and latitudinally by proportionate measurement. There is no remaining evidence of the orig. cor. monument. Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T14N R27E S 3 S 2 S10 S11 1972 </div> <p>from which</p> <p>The cor. of secs. 1, 2, 11 and 12, bears S. 81°05' E., 80.17 chs. dist., previously described.</p> <p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., bears N. 14°26' E., 94.19 chs. dist., monumented by an iron post, 2½ ins. diam., firmly set, projecting 14 ins. above ground, with mound of stone W., 2 ft. base, 1½ ft. high, brass cap mkd.</p> <div style="text-align: center;"> T15N R27E S34 S35 S 3 S 2 T14N 1968 </div> <p>These control lines were fully retraced and a diligent search was made for evidence of intervening corners, none of which were recovered.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, scattered bunchgrass and sagebrush.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp.</p> <p>N. 0°04' W., bet. secs. 33 and 34.</p> <p>Over gently rolling land.</p>
17.70	Wash, 25 lks. wide, 2 ft. deep, drains SW.
19.70	Top of sandstone knoll.
25.00	Same wash, drains NE.
28.30	Same wash, drains westerly.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
36.20	Same wash, drains easterly.
40.15	The ¼ sec. cor. of secs. 33 and 34, monumented by a sandstone, 20x10x10 ins., firmly set in a mound of stone, mkd. ¼ on N. face. I reset the cor. stone 10 ins. in the ground, and raise a mound of stone W. (Record calls for a volcanic stone 20x20x10 ins.)
	N. 0°07' E., beginning new measurement.
	Over gently rolling land.
28.00	Track road, bears E. and W.
39.80	Track road, bears S. 30° E. and N. 30° W.
40.04	Fence, bears E. and W.
40.10	The cor. of secs. 27, 28, 33 and 34, monumented by a lava stone, 15x11x6 ins., lying loose on the ground, mkd. with 3 notches on E. edge and 1 notch on S. edge, with mound of stone W. I reset the cor. stone 10 ins. in the ground and raise a mound of stone W. (Record calls for a volcanic stone 30x20x20)
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89°04' W., bet. secs. 27 and 34.
	Over gently rolling land, along fenceline.
0.30	Track road, bears N. and S.
20.20	Point for the E 1/16 sec. cor. of secs. 27 and 34, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T14N R27E E 1/16 <u>S27</u> S34 1968
	Deposit glass at the base of the iron post.
	This cor. falls 22 lks. N. of a fence bearing E. and W.
21.10	Track road, bears irregularly N. and S.
35.20	Wash, 15 lks. wide, 2 ft. deep, drains SW.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
40.40	<p>The ¼ sec. cor. of secs. 27 and 34, monumented by a sandstone, 14x9x4 ins., firmly set 10 ins. in the ground, mkd. ¼ on N. face. (Record calls for a post, 4 ft. long, flattened, 3 ins. wide, mkd. ¼ S.)</p> <p>At the cor. point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E ¼ S27 S34 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>The cor. is located 18 lks. S. of an E-W fenceline.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°07' W., beginning new measurement.</p> <p>Over gently rolling land, along a fenceline.</p> <p>2.60 Wash, 10 lks. wide, 3 ft. deep, drains NW.</p> <p>21.80 Track road, bears N. and S.</p> <p>22.80 Wash, 10 lks. wide, 2 ft. deep, drains N.</p> <p>33.00 Fence, bears E. and W.</p> <p>35.80 Track road, bears N. and S.</p> <p>40.33 The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27, previously described.</p> <p>S. 87°50' W., bet. secs. 22 and 27.</p> <p>Over nearly level land.</p>
15.014	<p>A malapai stone, 12x11x8 ins. in size, with a large, deep ¼ chiseled on W. face, firmly set in a small mound of stone, bears North, 46 lks. dist.; not accepted as true cor.</p>
21.26	<p>Point for the E 1/16 sec. cor. of secs. 22 and 27, at proportionate dist.; not monumented.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
42.52	<p>The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented by a sandstone, 14x7x4 ins. in size, mkd. $\frac{1}{4}$ on a face, loosely set in a mound of stone, 2 ft. base, 1 ft. high, (Record calls for a sandstone 18x10x8); not remonumented.</p>
	<p>S. 89°56' W., beginning new measurement.</p>
	<p>Over rolling land.</p>
15.40	<p>Wash, 60 lks. wide, with 5 ft. banks, drains N. 70° W.</p>
20.35	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 22 and 27, at proportionate dist.; not monumented.</p>
21.70	<p>Wash, 15 lks. wide, 1$\frac{1}{2}$ ft. deep, drains NE.</p>
32.50	<p>Track road, bears N. 52° E. and S. 52° W.</p>
40.10	<p>Track road, bears irreg. N. and S.</p>
40.46	<p>Lane fence, bears N. and S.</p>
40.60	<p>Track road, bears N. and S. curving W.</p>
40.70	<p>The cor. of secs. 21, 22, 27 and 28, marked by a sandstone, 18x10x6 ins. in size, no markings evident. The stone is located at a cor. of fences extending N. 85°31' W. and N. 0°55' W. This position is harmoniously related to existing original corners, has long been used by adjacent landowners and is accepted as the best existing evidence of the original corner; not remonumented.</p>
	<p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, scattered to moderate bunchgrass and sagebrush.</p>
	<p>N. 0°55' W., bet. secs. 21 and 22.</p>
	<p>Over gently rolling land, along fenceline.</p>
20.115	<p>Point for the S $\frac{1}{16}$ sec. cor. of secs. 21 and 22, at proportionate dist.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p>T14N R27E S $\frac{1}{16}$ S21 S22 1972</p>
	<p>Raise a mound of stone, 1$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high, W. of the cor.</p>
	<p>The cor. is located 2 lks. E. of a N-S fenceline.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
40.23	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T14N R27E $\frac{1}{4}$ S21 S22 1972
	Raise a mound of stone, 3 ft. base, 20 ins. high, W. of the cor.
	The cor. is located in a N-S fenceline.
40.38	Fence, cor., fences bear S. 88°59' E., S. 0°55' E. and N. 0°55' W.
42.90	Draw, drains NE. from source, 3.50 chs. SW.
53.10	Draw, drains NE.
59.96	A sandstone, 25x17x6 ins., marked with 3 grooves on N. and S. faces and with W C on S. face, origin unknown.
60.345	Point for the N $\frac{1}{16}$ sec. cor. of secs. 21 and 22, at proportionate dist.
	Set the iron post 14 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.
	T14N R27E N $\frac{1}{16}$ S21 S22 1972
63.50	Bluff, 35 ft. high, bears E. and W.; end of N-S fence, thence over dry Zion Reservoir lake bed.
65.70	Water course (Little Colorado River), 15 lks. wide, 2 $\frac{1}{2}$ ft. deep, drains W.
71.50	Bluff, 25 ft. high, bears E. and W., thence over gently rolling land.
80.46	The cor. of secs. 15, 16, 21 and 22, monumented by a sandstone, 24x12x4 ins. in size, conforming to the record, mkd. with 3 grooves on a face and 3 grooves on an adjacent face, found on a sandstone boulder, 4 ft. x 2 $\frac{1}{2}$ ft. x 10 ins. thick, mkd. with 3 notches on S. and N. edges.
	At the center of top of the sandstone boulder, grout a brass tablet, 3 ins. diam., and with a 3 ins. stem, flush with the surface, in a drilled hole, brass tablet mkd.
	T14N R27E $\frac{S16}{S21}$ $\frac{S15}{S22}$ 1972

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p>from which</p> <p>The N. end of Zion Reservoir dam, bears S. 37°45' W., 10.52 chs. dist.</p> <p>A windmill, bears N. 39°37' E., 48.96 chs. dist.</p> <p>Deposit the orig. cor. stone in the mound of stone, 3½ ft. base, 3½ ft. high, W. of the brass tablet.</p> <p>Land, gently rolling. Soil, clay loam. Timber, none. Undergrowth, moderate bunchgrass and sagebrush.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 88°42' W., bet. secs. 15 and 22.</p> <p>Over level bottom land, along remnants of an old partially buried fenceline.</p>
16.00	Fenceline disappears, cont. over lake bottom.
25.90	Track road, bears SE. and NW.
40.71	<p>Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist., falls in an old lake bottom (Zion Reservoir); there is no remaining evidence of the orig. cor.</p> <p>Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E ¼ <u>S15</u> S22 1972</p>
	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p>
61.06	<p>Point for the W 1/16 sec. cor. of secs. 15 and 22, at proportionate dist.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E W 1/16 <u>S15</u> S22 1972</p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p>
74.40	Leave old lake bottom, bears S. 20° E., curving W. and N. 20° W., curving E.; thence over gently rolling land.
81.41	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, level bottom land to gently rolling. Soil, clay loam. Timber, none. Undergrowth, sparse grass, assorted weeds.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	N. 1°44' E., bet. secs. 15 and 16. Over gently rolling land.
2.40	Draw, drains N. 80° E.
4.40	Spur, projects 1.00 ch. E.
7.20	Wash, 8 lks. wide, 6 ins. deep, drains E.
9.00	Track road, bears irreg. E. and W.
17.50	Wash, 10 lks. wide, 1 ft. deep, drains SE.
17.60	A lava stone, 10x8x6 ins. diam., loosely set in a small mound of stone, mkd. with 3 grooves on E. face and 3 grooves and W C on S. face, bears West, 88 lks. dist., origin unknown.
24.30	Draw, drains S. 70° E.
41.05	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
55.90	Track road, bears irreg. E. and W.
82.10	The cor. of secs. 9, 10, 15 and 16, determined longitudinally by proportionate measurement, and latitudinally by an old fence bearing E. and W. At the cor. point Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T14N R27E S 9 S10 S16 S15 1972 </div> Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor. Land, gently rolling. Soil, sandy loam. Timber, widely scattered small cedar. Undergrowth, moderate bunchgrass and sagebrush.
	From the cor. of secs. 10, 11, 14 and 15. S. 89°32' W., bet. secs. 10 and 15. Over gently rolling land, along an E-W fenceline.
18.20	Spur, projects 4 chs. S.
24.60	Wash, 10 lks. wide, 1 ft. deep, drains S.
27.00	Wash, 10 lks. wide, 1 ft. deep, drains S.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS		
39.06	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $\frac{1}{4}$ $\frac{S10}{S15}$ 1972</p> <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.</p> <p>The cor. is located in an E-W fenceline.</p>	
54.40	Track road, bears irreg. N. and S.	
78.12	<p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered small cedar. Undergrowth, moderate bunchgrass and sagebrush.</p>	
	<p>N. $3^{\circ}51'$ W., bet. secs. 9 and 10.</p> <p>Over gently rolling land.</p>	
40.355	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $\frac{1}{4}$ S 9 S10 1972</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p>	
45.65	Track road, bears S. 20° E. and N. 20° W.	
66.80	Spur, slopes SW.	
80.71	<p>The cor. of secs. 3, 4, 9 and 10, monumented by a sandstone of record size, lying loose in a mound of stone, no legible markings.</p> <p>At the cor. point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E S 4 S 3 S 9 S10 1972</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
33.00	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, moderate bunchgrass and sagebrush.</p>
41.22	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 81°57' W., bet. secs. 3 and 10.</p> <p>Over nearly level land.</p> <p>Zuni River, 90 lks. wide, 2 ft. deep, drains N. 70° W.</p> <p>Point for the ¼ sec. cor. of secs. 3 and 10 at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E ¼ S 3 S10 1972</p>
60.00	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>Spur, slopes NE.</p>
82.44	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, gently rolling. Soil, sandy to clay loam. Timber, none. Undergrowth, scattered bunchgrass and sagebrush.</p>
14.40	<p>N. 13°52' E., bet. secs. 3 and 4.</p> <p>Over rolling land.</p> <p>Leave rolling land, bears E. and W., enter bottom land.</p>
18.70	<p>Fence, bears S. 75° E. and N. 75° W.</p>
20.50	<p>Zuni River, dry, drains S. 80° W.</p>
26.685	<p>Point for the S 1/16 sec. cor. of secs. 3 and 4, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E S 1/16 S 4 S 3 1972</p>
	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
36.10	Leave bottom land, bears E. and W., asc. over rolling land.
38.80	Point on line from which a cave, 10 ft. wide, 5 ft. high, and 10 ft. deep, bears West, 7.90 chs. dist. The cave shows evidence of early day habitation by Indians. West of and adjoining the cave are numerous petroglyphs.
53.37	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T14N R27E $\frac{1}{4}$ S 4 S 3 1972
	Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.
60.00	Track road, bears N. 70° E. and S. 70° W.
106.87	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, brass cap mkd.
	T15N R27E S33 S34 S 4 S 3 T14N 1968
	A mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, is along the W. side of the iron post.
	Land, rolling. Soil, sandy clay loam. Timber, scattered salt cedar along the Zuni River. Undergrowth, scattered bunchgrass and sagebrush with cockleburs in bottom land near the Zuni River.
	From the cor. of secs. 21, 22, 27 and 28.
	S. $89^\circ 11'$ W., bet. secs. 21 and 28.
	Over rolling land.
9.30	Bladed road, bears N. and S.
35.40	Draw, drains N. 5° E.
38.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28 at proportionate dist., there is no remaining evidence of the orig. cor.; not monumented.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
39.70	Fence, bears S. 3°20' E. and N. 3°30' W., 3.02 chs. to a cor. of fences extending S. 85°31' E., S. 3°30' E. and an abandoned fenceline bearing N. 85°31' W.
44.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° E.
47.00	Evidence of a gate in an old abandoned E-W fenceline, bears S., 43 lks. dist.
47.80	Old track road, bears S. 55° E. and N. 55° W.
51.30	Draw, drains irreg. N. 20° E.
55.90	Old track road, bears N. 20° W. and S. 20° E., 66 lks. to a junction of old track roads bearing S. 35° W., N. 70° W. and N. 20° W.
57.08	Fence, bears N. 1°54' W., 451 lks. dist. to a cor. of old fences extending S. 85°31' E., S. 1°54' E. and N. 85°31' W. From this fence cor., a sandstone, 9x5x3 ins. diam., lying loose on the ground, mkd. with 2 notches on 2 sides, bears S. 12°34' W., 1.75 chs. dist.; orig. unknown.
61.80	Track road, bears S. 80° E. and N. 80° W., curving westerly.
62.60	Same road, bears N. 75° E., curving easterly and S. 75° W., curving westerly.
73.40	Same road, bears S. 60° E. curving easterly and N. 60° W., curving westerly.
74.50	Same road, bears S. 75° E., curving easterly and S. 75° W., curving westerly.
76.08	Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
	from which
	The cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., bears S. 8°10' E., 161.18 chs. dist., this control line was fully retraced and a diligent search was made for evidence of intervening corners, none of which were recovered.
	Land, gently rolling. Soil, sandy clay loam. Timber, none. Undergrowth, scattered bunchgrass, moderate sagebrush.
	N. 1°23' W., bet. secs. 20 and 21.
	Over rolling land.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
5.70	Leave rolling land, bears NE. and SW., enter bottom land.
7.90	Little Colorado River, 25 lks. wide, with 5 ft. banks, normally dry, drains SW. from N. 30° E., curving irreg. W.
15.00	Leave bottom land, asc. broken E. slope.
19.95	Point for the S 1/16 sec. cor. of secs. 20 and 21, at proportionate dist., falls on a ledgy slope where a monument cannot be perpetuated.
20.07	<p>Point selected for the witness S 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set the iron post over an X chiseled on solid rock, mound of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">W C T14N R27E S 1/16 S20 S21 1972</p> <p>The cor. is located on a steep and rocky E. slope.</p>
24.20	Rocky rim, bears N. 10° E. and S. 5° W., thence over gently rolling land.
39.90	<p>Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 26 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E ¼ S20 S21 1972</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>
79.80	<p>The cor. of secs. 16, 17, 20 and 21, marked by the point of intersection of projection of fences from N. 0°51' E. and irreg. West. This cor. point was pointed out by a local rancher as being the true cor. point.</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E S17 S16 S20 S21 1972</p> <p>The cor. is located on the NE edge of a bladed road bearing S. 55° E. and N. 55° W., for 20 lks. to a cattle guard connecting the fences bearing northerly and westerly.</p> <p>Land, rolling to gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, scattered bunchgrass and moderate sagebrush.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p>From the cor. of secs. 15, 16, 21 and 22. S. 88°38' W., bet. secs. 16 and 21. Over rolling land.</p>
4.14	Track road, bears N. 20° W. and S. 20° E., curving S.
14.10	Wash, 5 lks. wide, 1 ft. deep, drains S. 60° W.
15.50	Wash, 5 lks. wide, 1 ft. deep, drains S. 35° W.
22.20	Wash, 10 lks. wide, 1½ ft. deep, drains S.
26.90	Wash, 30 lks. wide, 1½ ft. deep, drains irregularly S.
35.60	Wash, 20 lks. wide, 2 ft. deep, drains S.
38.36	Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate dist., there is no remaining evidence of the orig. cor.; not monumented.
64.20	Track road, bears N. 15° E. and S. 15° W.
76.72	<p>The cor. of secs. 16, 17, 20 and 21.</p> <p>Land, rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, sparse bunchgrass, moderate sagebrush.</p>
	<p>N. 0°51' E., bet. secs. 16 and 17.</p> <p>Over gently rolling land, along a fenceline.</p>
41.37	Point for the ¼ sec. cor. of secs. 16 and 17 at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
82.74	<p>The cor. of secs. 8, 9, 16 and 17, monumented by an old cedar post, 24 ins. long, 2½ ins. diam., squared on one end, pointed on the other end, scribe marks visible on 4 sides but not legible. The post is located at and tied to a cor. of fences extending easterly, S. 0°51' W. and westerly, and is accepted as the best remaining evidence of the orig. cor. position. (There is no remaining evidence of the orig. bearing trees.)</p> <p>At the cor. point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E S 8 S 9 S17 S16 1972</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p>Invert and bury the orig. cor. post alongside the iron post.</p> <p>Raise a mound of stone, 1½ ft. base, 1½ ft. high, W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, scattered bunchgrass and sagebrush.</p>
<p>38.96</p> <p>39.90</p> <p>46.80</p> <p>77.92</p>	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°10' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land, along an E-W fenceline.</p> <p>Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p> <p>Track road, bears irreg. N. and S.; enter area of pottery shards and evidence of habitation of prehistoric Indians, area bears N. 70° E. and S. 60° W. Digging has been done in numerous places, some recently.</p> <p>Leave Indian Ruin area, bears N. 70° E. and S. 70° W.</p> <p>The cor. of secs. 8, 9, 16 and 17.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered scrub cedar. Undergrowth, scattered bunchgrass and moderate sagebrush.</p>
<p>46.30</p> <p>46.65</p>	<p>N. 2°30' W., bet. secs. 8 and 9.</p> <p>Over gently rolling land.</p> <p>Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E ¼ S 8 S 9 1972</p> <p>from which</p> <p style="padding-left: 40px;">A windmill, bears S. 52°21'30" E., 12.16 chs. dist.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <p>The cor. is located 35 lks. E. of a track road bearing SE. and NW.</p> <p>Track road, bears SE. and NW.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
92.60	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E S 5 S 4 S 8 S 9 1972</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, scattered bunchgrass and moderate sagebrush.</p>
	<hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p>
	<p>N. 81°56' W., bet. secs. 4 and 9.</p>
	<p>Over rolling land.</p>
5.05	<p>Track road, bears N. 65° E. and S. 65° W.</p>
21.05	<p>Draw, drains N.</p>
28.70	<p>Enter nearly level land, bears N. 15° E. and S. 15° W.</p>
33.60	<p>Enter rolling land.</p>
38.64	<p>Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate dist., there is no remaining evidence of the orig. cor.; not monumented.</p>
56.20	<p>Wash, 10 lks. wide, 1 ft. deep, drains NW.</p>
57.50	<p>Enter gently rolling land.</p>
57.96	<p>Point for the W 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.; not monumented.</p>
77.28	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, mostly rolling. Soil, sandy loam. Timber, none. Undergrowth, scattered bunchgrass and moderate sagebrush.</p>
	<hr/> <p>N. 11°46' E., bet. secs. 4 and 5.</p>
	<p>Over gently rolling land.</p>
4.00	<p>Enter nearly level land.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
17.50	Zuni River, 30 lks. wide, dry, drains westerly, curving S. from east, curving N.
20.60	Zuni River, 30 lks. wide, dry drains S. 40° E., curving westerly from N. 15° W.
23.62	Point for the S 1/16 sec. cor. of secs. 4 and 5, at proportionate dist.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T14N R27E S 1/16 S 5 S 4 1972
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
27.30	Zuni River, 30 lks. wide, dry, drains S 20° W., curving S. from NE.
36.60	Old fenceline, bears irreg. E. and W.
47.24	Point for the ¼ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T14N R27E ¼ S 5 S 4 1972
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
70.00	Leave nearly level land, bears NE. and W., enter gently rolling land.
90.66	Fence, bears S. 88°22' E. and N. 88°22' W.
94.83	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., mound of stone to top, 2½ ft. base, 2 ft. high, brass cap mkd.
	T15N R27E S32 S33 S 5 S 4 T14N 1968
	The cor. is located on the S. edge of a wash, 10 lks. wide, 1 ft. deep, drains irreg. W.
	Land, gently rolling in N. and S. portions, nearly level in middle portion. Soil, clay loam. Timber, scattered bunchgrass, moderate sagebrush.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p>From the point for the cor. of secs. 20, 21, 28 and 29. N. 88°59' W., bet. secs. 20 and 29. Over rolling land.</p>
1.40	Track road, bears irreg. N., curving E. and irreg. S.
9.50	Little Colorado River, 25 lks. wide, 2 ft. deep, drains S. 15° W.
12.40	Ridge, bears N. 5° E. and S. 5° W.
16.40	Enter bottom land, bears N. 10° E. and S. 15° W.
19.20	Point for the E 1/16 sec. cor. of secs. 20 and 29, at proportionate dist. Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T14N R27E E 1/16 $\frac{S20}{S29}$ 1972</p>
	Set a cedar post, 6 ft. long, 3½ ins. diam., 22 ins. in the ground, along N. side of the iron post.
29.20	Wash, 15 lks. wide, with 6 ft. banks, drains S. 10° E., curving W.
30.08	Wash, 15 lks. wide, with 6 ft. banks, drains S. 25° E.
35.20	Wash, 10 lks. wide, with 4 ft. banks, drains irreg. S.
36.00	Leave bottom land, bears N., curving E. and S.; asc. steep E. slope.
38.40	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 6 ins. in the ground, over an X chiseled on bedrock, mound of stone, 3 ft. base to top, brass cap mkd.
	<p>T14N R27E ¼ $\frac{S20}{S29}$ 1972</p>
	The cor. is located 89 lks. S. of an E-W fenceline and 6.92 chs. S. 84°30' E. of a fence cor., fences extend irreg. N., E. and W.
40.20	Low ridge, bears S. 30° E. and N. 30° W.
48.20	Draw, drains S. 30° W.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
66.50	Little Colorado River, 25 lks. wide, with 10 ft. banks, drains irreg. W. from SE.
76.80	Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T14N R27E $\frac{S19 S20}{S30 S29}$ 1972</p>
	from which
	<p>The proportionate point for the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., bears N. 89°04' W., 75.89 chs. dist.</p>
	<p>The cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., bears S. 6°44' E., 162.93 chs. dist., these control lines were fully retraced and a diligent search was made for evidence of intervening corners, none of which were recovered.</p>
	<p>The NW. cor. of the remains of an old stone cabin, 16x32 ft. in size, with the long sides bearing N. 25° E. and S. 25° W., bears N. 62°06' W., 10.52 chs. dist.</p>
	<p>The NW. cor. of the remains of an old stone cabin, 17x25 ft. in size, with the long sides bearing E. and W., bears N. 47°47' W., 7.92 chs. dist.</p>
	<p>The NW. cor. of the remains of an old stone cabin, 15x15 ft. in size, bears N. 47°30' W., 9.44 chs. dist.</p>
	<p>The cor. is located 20 lks. N. of the Little Colorado River, 15 lks. wide, with 12 ft. banks, drains irreg. W.</p>
	<p>Land, gently rolling to nearly level. Soil, clay loam. Timber, salt cedar along Little Colorado River, scattered cedar on high ground. Undergrowth, sparse bunchgrass, moderate sagebrush.</p>
	<p>N. 2°51' W., bet. secs. 19 and 20.</p>
	<p>Over nearly level land.</p>
19.20	Leave nearly level land, bears irreg. E. and W., thence over gently rolling land.
40.50	Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS		
	<p>Set the iron post 6 ins. in the ground, over an X chiseled in bedrock, mound of stone to top, 3 ft. base, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $\frac{1}{4}$ S19 S20 1972</p> <p>Thence over rolling SW. slope, through scattered to moderate cedar.</p> <p>81.00 Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E <u>S18 S17</u> <u>S19 S20</u> 1972</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 12 3/4° E., 31 lks. dist., mkd. S. 20 BT.</p> <p style="padding-left: 40px;">A cedar, 8 ins. diam., bears N. 65 3/4° W., 16 lks. dist., mkd. T14N R27E S18 BT.</p> <p>Land, nearly level to rolling. Soil, clay loam in bottom lands, sandy loam in high ground. Timber, scattered to moderate cedar. Undergrowth, scattered sage and moderate bunchgrass.</p>	
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 88°13' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land.</p> <p>39.43 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29 at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $\frac{1}{4}$ <u>S17</u> <u>S20</u> 1972</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>69.80 Fence, bears irreg. N. and S.</p> <p>74.00 Ridge, bears irreg. N. and S.</p> <p>78.86 The cor. of secs. 17, 18, 19 and 20.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p>Land, gently rolling to rolling. Soil, sandy loam. Timber, railed area to N. and scattered to moderate cedar to S. Undergrowth, moderate bunchgrass and sagebrush.</p>
	<p>N. 88°04' W., bet. secs. 18 and 19.</p> <p>Over rolling land.</p>
35.00	Low sandy ridge, bears NE. and SW.
39.48	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $\frac{1}{4}$ <u>S18</u> S19 1972</p>
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>The cor. is located on a NW. slope.</p>
64.80	Track road, bears irreg. N. and S.
78.37	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., set, mkd., and witnessed as described in the concurrent resurvey of the E. bdy. of T. 14 N., R. 26 E., resurveyed under this same Group No.</p> <p>Land, rolling. Soil, sandy clay loam. Timber, scattered cedar in E. portion. Undergrowth, scattered bunchgrass, moderate sagebrush.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°12' E., bet. secs. 17 and 18.</p> <p>Over gently rolling land.</p>
12.80	Fence, bears S. 22° E. and N. 22° W.
16.60	Bladed road, bears SE. and NW., thence along western edge of railed area.
40.45	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $\frac{1}{4}$ S18 S17 1972</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS					
80.90	<p>Set a cedar post, 6 ft. long, 5 ins. diam., 2 ft. in the ground along W. side of the iron post.</p> <p>The cor. of secs. 7, 8, 17 and 18, monumented by an old cedar post, 24 ins. long, 3½ ins. diam., pointed on one end, squared on the other end, scribed RXXVII E., S. XVIII, TX-- N., S. VIII, found loosely set at a cor. of fences extending N. 89°30' E., S. 1°13' W. and S. 89°30' W.</p> <p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E</p> <table border="0"> <tr> <td>S 7</td> <td>S 8</td> </tr> <tr> <td>S18</td> <td>S17</td> </tr> </table> <p>1972</p> </div> <p>from which</p> <p>A cedar, 6 ins. diam., bears S. 37° E., 49 lks. dist., mkd. T14N R27E S17 BT.</p> <p>A cedar, 6 ins. diam., bears N. 30° W., 14 lks. dist., mkd. T14N R27E S7 BT.</p> <p>Invert and bury the mkd. cedar post alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, moderate cedar to W., railed area to E. Undergrowth, scattered to moderate bunchgrass and sagebrush.</p>	S 7	S 8	S18	S17
S 7	S 8				
S18	S17				
39.87	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°36' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land, along a fenceline bearing irreg. W.</p> <p>Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R27E</p> <table border="0"> <tr> <td>¼ S 8</td> </tr> <tr> <td>S17</td> </tr> </table> <p>1972</p> </div> <p>Raise a mound of stone, 1½ ft. base, 1½ ft. high, N. of the cor.</p>	¼ S 8	S17		
¼ S 8					
S17					

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	The cor. is located 101 lks. S. of an irreg. E-W fence-line.
79.74	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling. Soil, sandy clay loam. Timber, widely scattered cedar. Undergrowth, moderate bunchgrass and sagebrush.</p>
	N. 89°11' W., bet. secs. 7 and 18.
	Over gently rolling land, through moderate cedar.
20.50	Track road, bears S. 55° E. and N. 55° W.
39.54	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, in a collar of stone, $1\frac{1}{2}$ ft. diam., brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E $\frac{1}{4}$ $\frac{S 7}{S 18}$ 1972</p>
	The cor. is located 83 $\frac{1}{2}$ lks. N. 73°17' E. of a cor. of fences extending irreg. E., S. and W.
78.58	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 14 N., R. 26 E., resurveyed under this same Group No.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, moderate cedar. Undergrowth, scattered to moderate bunchgrass, moderate sagebrush.</p>
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°37' W., bet. secs. 7 and 8.
	Over gently rolling land.
46.05	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist., there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS		
	<p style="text-align: center;">T14N R27E $\frac{1}{2}$ S 7 S 8 1972</p> <p>Raise a mound of stone, 20 ins. base, 16 ins. high, W. of the cor.</p> <p>81.80 Track road, bears N. 75° E. and S. 75° W.</p> <p>92.10 Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E S 6 S 5 S 7 S 8 1972</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears N. 14° W., 85 lks. dist., mkd. T14N R27E S6 BT.</p> <p>No other suitable trees near.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>Land, nearly level to gently rolling. Soil, shallow sandy loam. Timber, widely scattered cedar. Undergrowth, scattered bunchgrass and moderate sagebrush.</p>	
38.355	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°53' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land.</p> <p>Point for the ½ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $\frac{1}{2}$ S 5 S 8 1972</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>76.71 The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, scattered bunchgrass and sagebrush.</p>	

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS	
	<p>S. 81°40' W., bet. secs. 6 and 7. Over gently rolling land.</p>
38.72	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E $\frac{1}{4} \frac{S 6}{S 7}$ 1972</p>
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p>
68.00	<p>Track road, bears S. 10° E. and N. 14° W.</p>
76.47	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 14 N., R. 26 E., resurveyed under this same Group No.</p>
	<p>Land, gently rolling. Soil, sandy loam. Timber, widely scattered cedar. Undergrowth, moderate bunchgrass and sagebrush.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p>
	<p>N. 8°10' E., bet. secs. 5 and 6.</p>
	<p>Over gently rolling land.</p>
15.80	<p>Wash, 45 lks. wide, 3 ft. deep, drains S. 55° W.</p>
16.30	<p>Dike, parallels wash.</p>
23.27	<p>Point for the S 1/16 sec. cor. of secs. 5 and 6.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E S 1/16 S 6 S 5 1972</p>
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p>
43.00	<p>Zuni River, 30 lks. wide, with 3½ ft. banks, dry, drains N. 60° W.</p>
46.54	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6 at proportionate dist., there is no remaining evidence of the orig. cor.; not monumented.</p>
52.70	<p>Fence, bears N. 57°30' E. and S. 57°30' W.</p>
58.70	<p>Fence, bears N. 75° E. and S. 75° W.</p>
58.90	<p>Dike, parallels fence.</p>
93.67	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate measurement, on the N. bdy. of the Tp; not</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 14 N., R. 27 E.

CHAINS

monumented. The north boundary, between the corner of sections 4, 5, 32 and 33 and the $\frac{1}{4}$ section corner of section 6 and 31, Tps. 14 and 15 N., R. 27 E., was retraced and found essentially the same as that given in the field notes and on the plat of the Dependent Resurvey of the South Boundary of T. 15 N., R. 27 E. in 1968 by J. E. Knight.

from which

The cor. of secs. 4, 5, 32 and 33, Tps. 14 and 15 N., R. 27 E., bears East, 82.76 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 22 ins. above ground, set in a mound of stone, 3 ft. base to top, brass cap mkd.

T15N R27E

S32	S33
S 5	S 4

T14N

1968

The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, bears West, 41.38 chs. dist., monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, brass cap mkd.

T15N R27E

$\frac{1}{4}$ S31
S 6

T14N

1968

Mound of stone, 2 ft. base, 2 ft. high, N. of the cor.

Land, gently rolling.

Soil, clay loam.

Timber, none.

Undergrowth, scattered bunchgrass, moderate sagebrush.

Subdivision of Section 4, T. 14 N., R. 27 E.

From the point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.

N. $12^{\circ}53'30''$ E., on the N. and S. centerline of sec. 4.

Over gently rolling land.

- 2.10 Rim, bears E. and W., desc. N. slope.
- 3.90 Base of slope, bears E. and W., thence over nearly level bottom land.
- 6.50 Wash, 20 lks. wide, 2 ft. deep, drains N. 80° W.
- 9.00 Zuni River, 10 lks. wide, 1 ft. deep, drains S. 85° W., curving N.
- 20.30 Dike, bears E. curving S. and W., curving N.
- 25.195 Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 4.
Set the iron post 20 ins. in the ground, brass cap mkd.

Subdivision of Section 4, T. 14 N., R. 27 E.

CHAINS	
	<p style="text-align: center;">T14N R27E C S $\frac{1}{16}$ S 4 C 1972</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>29.46 Fence, bears S. 74°25' E. and N. 74°25' W.</p> <p>35.45 Dike, extends E. for 3½ chs. and W. for ½ ch.</p> <p>38.35 Dike, parallels dike above.</p> <p>50.39 Point for the C½ sec. cor. of sec. 4, at the intersection with the E. and W. centerline of sec. 4.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E C½ S 4 1972</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>52.80 Wash, 10 lks. wide, 1 ft. deep, drains E., curving S.</p> <p>58.00 Leave bottom land, bears SE. and NW.; enter gently rolling land.</p> <p>76.10 Leave gently rolling land, bears N. 40° E. and S. 40° W., enter bottom land.</p> <p>82.00 Leave bottom land, bears irreg. N. and S., enter gently rolling land.</p> <p>94.76 Fence, bears irreg. E. and W.</p> <p>100.79 The ¼ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 8 ins. above ground, with mound of stone N., brass cap mkd.</p> <p style="text-align: center;">T15N R27E $\frac{1}{4}$ $\frac{S33}{S 4}$ T14N 1968</p> <p>Land, nearly level to gently rolling. Soil, clay loam. Timber, none. Undergrowth, sparse bunchgrass, moderate sagebrush.</p> <hr/> <p>From the ¼ sec. cor. of secs. 3 and 4. N. 86°10'30" W., on the E. and W. centerline of sec. 4. Over rolling land.</p>

Subdivision of Section 4, T. 14 N., R. 27 E.

CHAINS	
2.38	Fence, bears irreg. N. and S.
9.30	Track road, bears irreg. NE. and SW.
11.50	Draw, drains N.
17.20	Spur, slopes NE.
22.90	Old track road, bears N. 15° E. and S. 15° W.
28.40	Wash, 10 lks. wide, 1 ft. deep, drains NW.
39.92	The C½ sec. cor. of sec. 4.
59.89	Point for the C-W 1/16 sec. cor. of sec. 4.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	<p>T14N R27E W 1 C ——— 16 ——— C S 4 1972</p>
	Raise a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.
68.26	Wash, 20 lks. wide, 2 ft. deep, drains W.
79.86	The ¼ sec. cor. of secs. 4 and 5.
	<p>Land, rolling to gently rolling. Soil, clay loam. Timber, none. Undergrowth, sparse bunchgrass and moderate sagebrush.</p>
	<p>Subdivision, SW¼, Section 4</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the W 1/16 sec. cor. of secs. 4 and 9. N. 12°20'30" E., on the N. and S. centerline of the SW¼ of sec. 4.</p>
	Over rolling land.
3.40	Draw, drains N. 25° W.
14.80	Leave rolling land, bears irreg. E. and W., enter bottom land.
24.42	Point for the SW 1/16 sec. cor. of sec. 4, at the intersection with the E. and W. centerline of the SW¼ of sec. 4.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T14N R27E SW 1/16 + S 4 1972</p>
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.

Subdivision of Section 4, T. 14 N., R. 27 E.

CHAINS																
24.70	Zuni River, 25 lks. wide, 2 ft. deep, dry, drains SW.															
32.03	Fence, bears irreg. E. and W.															
44.30	Wash, 10 lks. wide, 2 ft. deep, drains irreg. W.															
48.84	The C-W 1/16 sec. cor. of sec. 4.															
<hr/> <p>From the C-S 1/16 sec. cor. of sec. 4.</p> <p>N. 84°04' W., on the E. and W. centerline of the SW$\frac{1}{4}$ of sec. 4.</p> <p>Over nearly level land.</p>																
7.90	Zuni River, 40 lks. wide, 4 ft. deep, dry, drains N., curving W.															
12.00	Zuni River, 40 lks. wide, 4 ft. deep, dry, drains SW.															
14.60	Zuni River, drains N., curving W.															
19.615	The SW 1/16 sec. cor. of sec. 4.															
20.67	Zuni River, drains SSW.															
24.40	Zuni River, drains N. 15° E.															
28.20	Zuni River, drains SW.															
32.20	Zuni River, drains N. 25° E.															
34.60	Zuni River, drains S. 20° E.															
39.23	The S 1/16 sec. cor. of secs. 4 and 5.															
<hr/> <p style="text-align: center;">Subdivision of Section 6, T. 14 N., R. 27 E.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>N. 5°59' E., on the N. and S. centerline of sec. 6.</p> <p>Over gently rolling land,</p>																
9.90	Dike, bears E. and W.															
24.63	Point for the C-S 1/16 sec. cor. of sec. 6.															
	Set the iron post 20 ins. in the ground, in a collar of stone, 1 $\frac{1}{2}$ ft. base, brass cap mkd.															
	<p>T14N R27E</p> <table style="margin: auto;"> <tr> <td></td> <td style="text-align: center;">C</td> <td></td> </tr> <tr> <td style="text-align: center;">S</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 6</td> </tr> <tr> <td style="text-align: center;">1/16</td> <td style="text-align: center;"> </td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">C</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">1972</td> <td></td> </tr> </table>		C		S		S 6	1/16				C			1972	
	C															
S		S 6														
1/16																
	C															
	1972															
29.80	Fence, bears N. 59° E. and S. 59° W.															
34.10	Leave gently rolling land, bears NE. and SW., enter bottom land.															
44.30	Zuni River, 40 lks. wide, with 6 ft. banks, dry, drains N. 75° W., curving S.															

Subdivision of Section 6, T. 14 N., R. 27 E.

CHAINS	
46.00	Abandoned fenceline, bears E. and W.
46.85	Fence, bears irreg. E. and W.
49.26	Point for the C½ sec. cor. of sec. 6, at intersection with the E. and W. centerline of sec. 6; not monumented.
58.80	Dike, bears E. and W.
73.87	Point for the C-N 1/16 sec. cor. of sec. 6.
	Set the iron post 20 ins. in the ground, in a collar of stone, 1½ ft. base, brass cap mkd.
	<p style="text-align: center;">T14N R27E C N 1/16 S 6 C 1972</p>
91.60	Track road, bears N. 55° E. and S. 55° W.
98.78	The ¼ sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., monumented by an iron pipe, 2½ ins. diam., firmly set, projecting 8 ins. above ground, brass cap mkd.
	<p style="text-align: center;">T15N R27E ¼ S31 S 6 T14N 1968</p>
	A mound of stone, 1½ ft. base, 1 ft. high, is located N. of the cor.
	Land, gently rolling to nearly level. Soil, clay loam. Timber, none. Undergrowth, sparse bunchgrass, moderate sagebrush.
	<p>From the point for the ¼ sec. cor. of secs. 5 and 6. S. 86°10'30" W., on the E. and W. centerline of sec. 6. Over nearly level land.</p>
1.00	Zuni River, 30 lks. wide, 2 ft. deep, dry, drains irreg. W.
7.90	Fence, bears N. 59° E. and S. 59° W.
14.30	Zuni River, drains S., curving W.
19.50	Zuni River, drains W., curving S.
25.53	Fence, bears N. 36° E. and S. 36° W.
39.87	The point for the C½ sec. cor. of sec. 6.
51.75	Fence, bears S. 67° E. and N. 67° W.
54.60	Zuni River, drains NW.
59.87	Point for the C-W 1/16 sec. cor. of sec. 6.
	Set the iron post 24 ins. in the ground, brass cap mkd.

Subdivision of Section 6, T. 14 N., R. 27 E.

CHAINS

T14N R27E

W 1/16

C — S 6 — C

1972

Set a cedar post 8½ ft. long, 3 ins. diam., 24 ins. in the ground along the S. side of the iron post.

60.60 Zuni River, drains SE.

78.92 The ¼ sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 14 N., R. 26 E., resurveyed under this same Group No.

Land, nearly level.

Soil, clay loam.

Timber, none.

Undergrowth, sparse bunchgrass, moderate sagebrush.

Subdivision, NW¼, Section 6

From the C-W 1/16 sec. cor. of sec. 6.

N. 5°01' E., on the N. and S. centerline of the NW¼ of sec. 6.

Over nearly level land.

3.30 Zuni River, 30 lks. wide, 5 ft. deep, dry, drains W., curving S.

3.70 Fence, bears irreg. E. and W.

11.20 Wash, 15 lks. wide, 2 ft. deep, drains SW.

22.20 Track road, bears N. 53° E. and S. 53° W., leave level land, bears same as road.

25.32 Point for the NW 1/16 sec. cor. of sec. 6 at intersection with the E. and W. centerline of the NW¼ of sec. 6.

Set the iron post 20 ins. in the ground, brass cap mkd.

T14N R27E

NW 1/16+S 6

1972

Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.

50.78 The W 1/16 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., firmly set, projecting 6 ins. above ground, brass cap mkd.

T15N R27E

W 1/16 $\frac{S31}{S 6}$

T14N

1968

Subdivision of Section 6, T. 14 N., R. 27 E.

CHAINS

A mound of stone, 3 ft. base, 1½ ft. high, is located N. of the cor.

From the C-N 1/16 sec. cor. of sec. 6.

S. 88°20' W., on the E. and W. centerline of the NW¼ of sec. 6.

Over nearly level bottom land.

4.00 Wash, 10 lks. wide, 1 ft. deep, drains SW.

16.00 Leave bottom land, bears NE. and SW.

17.65 Track road, bears N. 40° E. and S. 40° W.

20.32 The NW 1/16 sec. cor. of sec. 6.

25.90 Recent excavation, 1 to 6 ft. deep, approx. 1 ch. wide, bears N. 60° E., 2.20 chs. and S. 60° W., 95 lks. dist.

39.77 The N 1/16 sec. cor. of secs. 1 and 6, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, mkd. and witnessed as described in the field notes of the concurrent resurvey of the E. bdy. of T. 14 N., R. 26 E., resurveyed under this same Group No.

Subdivision of Section 20, T. 14 N., R. 27 E.

From the ¼ sec. cor. of secs. 20 and 29.

N. 2°09'30" W., on the N. and S. centerline of sec. 20.

Over rolling land.

0.96 Fence, bears irreg. E. and W.

4.00 Draw, drains E. from head, 2 chs. W.

20.07 Point for the C-S 1/16 sec. cor. of sec. 20.

Set the iron post 24 ins. in the ground, brass cap mkd.

T14N R27E
C
S 1/16 | S20
|
C
1972

Raise a mound of stone, 2 ft. base, 16 ins. high, W. of the cor.

The cor. is located 60 lks. E. of a fenceline bearing N. 3°15' E. and S. 3°15' W.

26.42 Fence, bears N. 3°15' E. and S. 3°15' W.

Subdivision of Section 20, T. 14 N., R. 27 E.

CHAINS	
40.14	<p>Point for the $C\frac{1}{4}$ sec. cor. of sec. 20 at intersection with the E. and W. centerline of sec. 20.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E $C\frac{1}{4}$—S20 1972</p> <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.</p> <p>The cor. is located 129 lks. W. of a fenceline bearing N. $3^{\circ}15'$ E. and S. $3^{\circ}15'$ W.</p>
66.90	Track road, bears N. 25° E. and S. 25° W.
80.31	<p>The $\frac{1}{4}$ sec. cor. of secs. 17 and 20.</p> <p>Land, gently rolling. Soil, sandy clay loam. Timber, scattered cedar. Undergrowth, sparse bunchgrass, moderate sagebrush.</p>
0.60	<p>From the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.</p> <p>N. $88^{\circ}38'$ W., on the E. and W. centerline of sec. 20.</p> <p>Over steep and rocky E. slope.</p> <p>Rim, bears irreg. N. and S., thence over gently rolling land.</p>
19.44	<p>Point for the C-E $1/16$ sec. cor. of sec. 20</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T14N R27E E $1/16$ C—$\frac{S20}{C}$—C 1972</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of the cor.</p>
21.25	Track road, bears SE. and NW., curving northerly.
37.59	Fence, bears N. $3^{\circ}15'$ E. and S. $3^{\circ}15'$ W.
38.88	The $C\frac{1}{4}$ sec. cor. of sec. 20.
45.30	Track road, bears irreg. N. and S.
56.80	Low, flat ridge, bears N. and S.
71.00	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.
72.38	Fence, bears irreg. N. and S.

Subdivision of Section 20, T. 14 N., R. 27 E.

CHAINS

- 77.79 The $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
Land, rolling.
Soil, sandy clay loam.
Timber, scattered cedar.
Undergrowth, sparse bunchgrass and moderate sagebrush.
-
- Subdivision, SE $\frac{1}{4}$, Section 20
-
- From the E 1/16 sec. cor. of secs. 20 and 29.
N. 1°45' W., on the N. and S. centerline of the SE $\frac{1}{4}$ of sec. 20.
Over gently rolling land.
- 2.12 Fence, bears N. 87°18' E. and S. 87°18' W.
- 20.00 Point for the SE 1/16 sec. cor. of sec. 20 at intersection with the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 20
Set the iron post 24 ins. in the ground, brass cap mkd.
- T14N R27E
SE $\frac{1}{16}$ S20
16
1972
- Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 $\frac{1}{2}$ ft. high, W. of the cor.
- 38.10 Track road, bears SE. and NW.
- 40.00 The C-E 1/16 sec. cor. of sec. 20.
-
- From the S 1/16 sec. cor. of secs. 20 and 21.
N. 88°49' W., on the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 20.
Asc. steep E. slope.
- 0.50 Rim, bears irreg. N. and S., thence over gently rolling land.
- 6.90 Track road, bears N. 20° E. and S. 20° W.
- 14.60 Wash, 10 lks. wide, 2 ft. deep, drains S. from head 1 ch. N.
- 19.32 The SE 1/16 sec. cor. of sec. 20.
- 22.50 Wash, 10 lks. wide, 6 ins. deep, drains SE.
- 23.60 Wash, 10 lks. wide, 6 ins. deep, drains SE.
- 38.64 The C-S 1/16 sec. cor. of sec. 20.

Subdivision of Section 22, T. 14 N., R. 27 E.

CHAINS	
	Subdivision of Section 22, T. 14 N., R. 27 E.
	From the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.
	N. $0^{\circ}54'$ W., on the N. and S. centerline of sec. 22.
	Over rolling land.
5.00	Enter bottom land, bears SE. and NW., curving W.
15.90	Wash, 30 lks. wide, 2 ft. deep, drains E.
16.35	Dike, bears E. and W.; the center of a stock pond, 2.00 chs. X 3.00 chs. diam., bears E., 3.00 chs. dist.
17.50	Track road, bears irreg. E. and W.
20.54	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 22; not monumented.
24.00	Enter Zion Reservoir bottom, bears N. 70° E. and S. 70° W., curving N.
41.08	Point for the C $\frac{1}{2}$ sec. cor. of sec. 22, at intersection with the E. and W. centerline of sec. 22.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T14N R27E C $\frac{1}{2}$ + S22 1972
	Raise a mound of stone, $1\frac{1}{2}$ ft. base, 2 ft. high, W. of cor.
61.22	Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 22; not monumented.
81.36	The $\frac{1}{4}$ sec. cor. of secs. 15 and 22.
	Land, rolling to nearly level.
	Soil, clay loam.
	Timber, none.
	Undergrowth, no grass, heavy growth of weeds in old Reservoir bottom.
	From the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.
	S. $88^{\circ}47'$ W., on the E. and W. centerline of sec. 22.
	Over level Reservoir bottom land.
4.10	Track road, bears S. 15° E. and N. 15° W.
20.795	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 22.
	Set the iron post 20 ins. in the ground, brass cap mkd.

Subdivision of Section 22, T. 14 N., R. 27 E.

CHAINS	
	<p style="text-align: center;">T14N R27E E 1/16 C ————— C S22 1972</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p>
41.59	The C $\frac{1}{4}$ sec. cor. of sec. 22.
43.90	Leave Zion Reservoir bottom land, enter gently rolling land.
61.93	Point for the C-W 1/16 sec. cor. of sec. 22. Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T14N R27E W 1/16 C ————— C S22 1972</p> <p>Raise a mound of stone, 1$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high N. of the cor.</p>
76.40	Draw, drains NW.
77.80	Draw, drains NE.
82.27	The $\frac{1}{4}$ sec. cor. of secs. 21 and 22. Land, level bottom land E. $\frac{1}{2}$ mile, gently rolling W. $\frac{1}{2}$ mile. Soil, clay loam. Timber, none. Undergrowth, assorted weeds in bottom land, sparse bunchgrass and sagebrush in rolling land.
<p>Subdivision, SE$\frac{1}{4}$, Section 22</p> <hr/>	
	<p>From the point for the E 1/16 sec. cor. of secs. 22 and 27. N. 1°32' W., on the N. and S. centerline of SE$\frac{1}{4}$ of sec. 22. Over gently rolling land.</p>
14.70	Draw, drains NE.
20.35	Point for the SE 1/16 sec. cor. of sec. 22, at intersection with the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 22. Set the iron post 20 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T14N R27E SE 1/16 + S 22 1972</p> <p>from which</p>


Subdivision of Section 22, T. 14 N., R. 27 E.

CHAINS	
	A windmill, bears N. 34°41' E., 7.42 chs. dist.
	A windmill, bears N. 13°19' W., 7.19 chs. dist.
	Raise a mound of stone, 2 ft. base, 2 ft. high. W. of the cor.
24.95	Track road, bears S. 50° W. and N. 50° E., curving E.
27.30	Fence, bears irreg. E. and W. 22 lks. to E. edge of a circular corral, 1.15 chs. diam.
28.10	Leave rolling land, enter bottom land of Zion Reservoir, bears irreg. E., 1.00 ch., thence northerly and SW., 3.00 chs., thence southerly.
31.30	Leave bottom land of Zion Reservoir, enter gently rolling land.
34.50	Fence, bears N. 77° W. and S. 77° E., 45 lks. to a cor. of fences extending N. 77° W. and irreg. S.
35.10	Enter bottom land of Zion Reservoir, bears irreg. E. and W.
38.26	Leave bottom land, bears E. and W., enter gently rolling land.
40.70	The C-E 1/16 sec. cor. of sec. 22.
	From the S 1/16 sec. cor. of sec. 22 and 23.
	S. 88°19' W., on the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 22.
	Over nearly level land.
0.90	Track road, bears N. 30° W. and S. 30° E., curving S.
1.21	Fence, bears N. 65° W. and S. 65° E., 76 lks. to a cor. of fences extending S. 4°07' E. and N. 65° W.
7.95	Track road, bears S. 56° E. and N. 56° W.
21.04	The SE 1/16 sec. cor. of sec. 22.
26.70	Track road (old), bears NE. and SW.
26.90	Enter bottom land of Zion Reservoir, bears NE. and SW.
34.40	Wash, 25 lks. wide, 3 ft. deep, drains N.
42.07	The C-S 1/16 sec. cor. of sec. 22.
	Subdivision SW $\frac{1}{4}$ of Section 22
	From the point for the W 1/16 sec. cor. of secs. 22 and 27.

Subdivision of Section 22, T. 14 N., R. 27 E.

CHAINS	
	N. 0°55' W., along the N. and S. centerline of the SW $\frac{1}{2}$ of sec. 22.
	Over rolling land.
1.50	Wash, 20 lks. wide, 2 ft. deep, drains NE.
4.00	Track road, bears N. 60° E. and S. 60° W.
13.00	Draw, drains SE. from head 1.00 ch. NW.
16.30	Track road, bears N. 70° W. and S. 70° E., curving N.
20.315	Point for the SW 1/16 sec. cor. of sec. 22, at intersection with the E. and W. centerline of the SW $\frac{1}{2}$ of sec. 22.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T14N R27E SW 1/16 S22 1972</p>
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.
29.10	Draw, drains NE.
40.17	Fence, bears irreg. E. and W.
40.61	The C-W 1/16 sec. cor. of sec. 22.
<hr/>	
	From the point for the C-S 1/16 sec. cor. of sec. 22.
	S. 89°20'30" W., on the E. and W. centerline of the SW $\frac{1}{2}$ of sec. 22.
	Over bottom land.
8.00	Leave bottom land, bears N., curving E. and E. curving S.
19.40	Track road, bears N., curving E. and S. curving W.
20.35	The SW 1/16 sec. cor. of sec. 22.
32.20	Old track road, bears N. 60° E. and S. 60° W.
40.68	The S 1/16 sec. cor. of secs. 21 and 22.
<hr/>	
	Subdivision NW $\frac{1}{4}$, Section 22
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 22.

Subdivision of Section 22, T. 14 N., R. 27 E.

CHAINS	
	N. 0°55' W., on the N. and S. centerline of the NW¼ of sec. 22.
	Over gently rolling land.
6.10	Leave rolling land, bears SE. and NW., enter Zion Reservoir bottom land.
20.14	Point for the NW 1/16 sec. cor. of sec. 22 at intersection with the E. and W. centerline of the NW¼ of sec. 22.
	Set the iron post 18 ins. in the ground, brass cap mkd.
	<p>T14N R27E NW 1/16</p>  <p>S22 1972</p>
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.
40.28	The W 1/16 sec. cor. of secs. 15 and 22.
	From the point for the C-N 1/16 sec. cor. of sec. 22.
	S. 88°45' W., on the E. and W. centerline of the NW¼ of sec. 22.
	Over Zion Reservoir bottom land.
20.34	The NW 1/16 sec. cor. of sec. 22.
27.40	Little Colorado River, 15 lks. wide, 2 ft. deep, drains irreg. W.
36.10	Leave bottom land, bears N. and S., enter rolling land.
40.69	The N 1/16 sec. cor. of secs. 21 and 22.
Subdivision of Section 34, T. 14 N., R. 27 E.	
	From the ¼ sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp.
	N. 0°06' W., on the N. and S. centerline of sec. 34.
	Over gently rolling land.
40.11	Point for the center ¼ sec. cor. of sec. 34, at the intersection with the E. and W. centerline of sec. 34; not monumented.
49.60	Wash, 10 lks. wide, with 4 ft. banks drains westerly.

Subdivision of Section 34, T. 14 N., R. 27 E.

CHAINS	
60.15	Point for the C-N 1/16 sec. cor. of sec. 34.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T14N R27E C N 1/16 S34 C 1968
	Raise a mound of stone W. of the iron post.
62.10	Track road, bears S. 85° E. and N. 85° W.
80.19	The ¼ sec. cor. of secs. 27 and 34.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.
	From the ¼ sec. cor. of secs. 34 and 35.
	S. 89°07' W., on the E. and W. centerline of sec. 34.
	Over gently rolling land.
20.19	Point for the C-E 1/16 sec. cor. of sec. 34.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	T14N R27E E 1/16 C — S34 — C 1968
	Deposit glass at the base of the iron post.
40.38	The point for the center ¼ sec. cor. of sec. 34.
62.00	Enter valley, bears irregularly N. and S.
77.10	Wash, 5 lks. wide, 1 ft. deep, drains N.
79.30	Leave valley, bears irregularly N. and S.
80.92	The ¼ sec. cor. of secs. 33 and 34.
	Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, bunchgrass and sagebrush.
	Subdivision, NE¼, Section 34
	From the C-E 1/16 sec. cor. of sec. 34.

Subdivision of Section 34, T. 14 N., R. 27 E.

CHAINS	
	<p>N. 0°09' W., on the N. and S. centerline of the NE$\frac{1}{4}$ of sec. 34.</p>
	<p>Over gently rolling land.</p>
20.05	<p>Point for the NE 1/16 sec. cor. of sec. 34, at the intersection with the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 34.</p>
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T14N R27E NE 1/16 S34 1968</p>
	<p>Deposit glass at the base of the iron post.</p>
26.10	<p>Track road, bears S. 85° E. and N. 85° W.</p>
40.08	<p>The E 1/16 sec. cor. of secs. 27 and 34.</p>
	<p>From the N 1/16 sec. cor. of secs. 34 and 35.</p>
	<p>S. 89°04' W., on the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 34.</p>
	<p>Over gently rolling land.</p>
10.00	<p>Track road, bears S. 85° E. and N. 85° W.</p>
20.19	<p>The NE 1/16 sec. cor. of sec. 34.</p>
31.60	<p>Track road, bears N. 60° E. and S. 60° W.</p>
35.50	<p>Track road, bears S. 60° E. and N. 60° W.</p>
40.37	<p>The C-N 1/16 sec. cor. of sec. 34.</p>
<p>General Description</p>	
<p>The area encompassed by this survey varies from nearly level to rolling land. Elevations vary from 5508 feet to 5993 feet above sea level.</p>	
<p>The soil is mostly of sandy clay loam interspersed with gravelly loam in certain portions of the township. Vegetation consists of bunchgrass and sagebrush with the higher elevations containing moderate and scattered growth of juniper timber.</p>	
<p>The Little Colorado River, containing water in certain places, enters the township on the east boundary of section 25 and traverses in a westerly direction leaving the township on the west boundary of section 30. The course of the Little Colorado River through section 22</p>	

General Description, T. 14 N., R. 27 E.

CHAINS

was discernible only where it crossed the east and west boundaries and in a portion of the northwest quarter of the section. ZION Dam, located in the NE $\frac{1}{4}$ NE $\frac{1}{4}$ of section 21, has not functioned for years but at one time backed water up into portions of sections 13, 14, 15, 22, 23, 24 and 25 and creating what is now called ZION RESERVOIR.

The Zuni River, containing water in certain places, enters the township on the east boundary of section 1 and traverses in a westerly direction leaving the township on the west boundary of section 6.

The township is uninhabited. The primary use of this land is for the grazing of livestock.

There is no evidence of mineral activity within the Tp.

55

Form 9180-8
(August 1967)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ira M. Thiessen	Surveying Technician
Ronald M. Williams	Surveying Aid
Martin W. Fuller	Surveying Aid
Jerrel L. Jones	Surveying Aid
Harry K. Smith	Cadastral Surveyor
Kurt Merkle	Surveying Aid
Ronald McCally	Surveying Aid
Kenneth Weir	Surveying Aid

CERTIFICATE OF SURVEY

XX (We), Paul G. Bauer and Louis D. Gilbert, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of March, 1968, (We) have dependently resurveyed the South boundary, and a portion of the East boundary and subdivisional lines, and surveyed subdivisions of certain sections, Township 14 North, Range 27 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 1, 1973

 (Date)

Paul G. Bauer

 (Cadastral Surveyor)

September 27, 1970

 (Date)

Louis D. Gilbert

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date NOV 8 1973

BUREAU OF LAND MANAGEMENT,
 Washington, D. C.

The foregoing field notes of the dependent resurvey of the South boundary, and of a portion of the East boundary and subdivisional lines, and the survey of subdivisions of certain sections, Township 14 North, Range 27 East, Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert and Paul G. Bauer, having been critically examined and found correct, are hereby approved.

MAY 6 1974

 (Date)

Bernard W. Featiga

 (Chief, Division of Engineering) Cadastral Survey

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 14 N., R. 27 E., S&SRM., Arizona, is a true copy of the original field notes.~~

~~_____~~
 (Date)

~~_____~~
 (Chief, Division of Engineering) Cadastral Survey