

ORIGINAL

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

THE SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

OF THE TOWNSHIP

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES WITHIN SECTION 22

AND

THE METES-AND-BOUNDS SURVEY OF TRACT NO. 37

TOWNSHIP 6 NORTH, RANGE 5 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

RAY HARPIN, SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated JULY 5, 1973, approved AUGUST 6, 1973,

_____, which provided for the surveys included under U.S. Survey/Group
Number 561, and assignment instructions dated JULY 5, 1973.

Survey commenced JULY 11, 1973

Survey completed AUGUST 7, 1973

1A

BOOK 4994

INDEX DIAGRAM

Township 6 North, Range 5 East

| | | | | | |
|----|----|----------|-------|------|----|
| 6 | 5 | 4 | 3 | 2 | 1 |
| 7 | 8 | 9 | 10 | 11 | 12 |
| | | Tract 37 | 13 | | |
| 18 | 17 | 16 | 15 11 | 14 | 13 |
| | | | 10 | | |
| 19 | 20 | 21 2 | 22 9 | 23 | 24 |
| | | | 8 | | |
| 30 | 29 | 28 | 27 7 | 26 | 25 |
| | | | 6 | 6 | 4 |
| 31 | 32 | 33 | 34 5 | 35 3 | 36 |

Subdivision of section 22 pp. 15-25
 Tract No. 37 p. 26

Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the subdivisional lines of the township, the survey of a portion of the subdivision lines within section 22, and the metes-and-bounds survey of Tract No. 37, all within Township 6 North, Range 5 East of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The First Guide Meridian East (the west boundary of the township) was surveyed by Roscoe C. Ham, Deputy Surveyor, in 1910. A portion of the First Guide Meridian East (the west boundary of the township) was dependently resurveyed, and a portion of the subdivisional lines of the township, and a portion of the subdivision lines of section 28 were surveyed by Horace G. Parker, Cadastral Surveyor, in 1959, as shown upon the official plat accepted February 2, 1960. The south boundary was surveyed by Sidney E. Blout, Cadastral Engineer, in 1919, as described in the field-note record of the north boundary and shown upon the official plat of Tp. 5 N., R. 5 E., approved September 4, 1920. A portion of the First Guide Meridian East (the west boundary of the township) was dependently resurveyed; the north and east boundaries, and a portion of the subdivisional lines were surveyed by Boyd S. Owens, Cadastral Surveyor, and Gary W. Rutledge, Surveying Technician, in 1963, as shown upon the official plat accepted March 13, 1964. Exchange Surveys Nos. 658 and 659 were surveyed by C. A. Long, Regional Engineer for the U. S. Forest Service, in 1931. Both of these surveys are located within this township.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 5, 1973.

The directions of all lines of this survey were determined from the horizontal control data of U. S. Coast and Geodetic Survey Triangulation Station, Wildcat, and refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains, reduced to horizontal equivalents.

The data furnished with the special instructions give the geographic position of the southeast corner of the township as: Latitude $33^{\circ} 48.8' N.$, and Longitude $111^{\circ} 47.2' W.$ The mean magnetic declination is 14° East.

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

Reestablishment of the Survey Executed by
Boyd S. Owens, Cadastral Surveyor
Gary W. Rutledge, Surveying Technician

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>Beginning at the cor. of secs. 21, 22, 27, and 28, which is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 6 ins. above the surface of the ground, with the brass cap mkd.</p> <p style="text-align: center;">T6N R5E S21 S22 S28 S27</p> <p style="text-align: center;">1959</p> <hr/> <p>N. 0° 02' W., between secs. 21 and 22</p> <p>Ascend over rolling southwest slope.</p> |
| 17.93 | Center line of Cave Creek Road bears N. 52° 00' E., and S. 52° 00' W. |
| 20.015 | <p>The point for the south 1/16 sec. cor. of secs. 21 and 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 21 S 22</p> <p style="text-align: center;">1973</p> |
| 40.03 | <p>The 1/4 sec. cor. of secs. 21 and 22 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R5E 1/4 S 21 S 22</p> <p style="text-align: center;">1963</p> <hr/> <p>N. 0° 02' W., beginning new measurement</p> |
| 20.015 | <p>The point for the north 1/16 sec. cor. of secs. 21 and 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 21 S 22</p> <p style="text-align: center;">1973</p> |

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

CHAINS

40.03 The cor. of secs. 15, 16, 21, and 22 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 8 ins. above the surface of the ground, with the brass cap mkd.

T6N R5E
 S 16 | S 15
 S 21 | S 22

1963

Land, rolling
 Soil, sandy and decomposed granite
 Timber, scattering paloverde, mesquite, catclaw acacia;
 undergrowth, young trees, brush, ocotillo, and cacti.

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

The cor. of secs. 1, 2, 35, and 36 on the south boundary of the township is monumented with a regulation iron post, 2 ins. in diam., firmly set, projecting 14 ins. above the surface of the ground, with the brass cap mkd.

T6N
 R5E S 35 | S 36
 S 2 | S 1
 T5N

1919

this corner is located 3 lks. north of an east and west fence line.

N. 0° 01' W., between secs. 35 and 36

Over rolling east slope.

40.00 The point for the 1/4 sec. cor. of secs. 35 and 36

Set an iron post, 28 in s. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T6N R5E
 1/4
 S 35 | S 36

1973

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| 80.00 | <p>The point for the cor. of secs. 25, 26, 35, and 36</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R5E S 26 S 25 S 35 S 36</p> <p>1973</p> <p>Land, rolling Soil, sandy and decomposed granite Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.</p> </div> | |
| | <p>The cor. of secs. 25, 30, 31, and 36 on the east boundary of the township is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 10 ins. above the surface of the ground, with the brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R5E R6E S 25 S 30 S 36 S 31</p> <p>1963</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A mound of stone, 2½ ft. base, 1 ft. high, west of the corner.</p> </div> | |
| 40.04 | <p>S. 89° 51' W., between secs. 25 and 36</p> <p>Ascend over rolling east slope.</p> <p>The point for the 1/4 sec. cor. of secs. 25 and 36</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R5E 1/4 S 25 S 36</p> <p>1973</p> </div> | |
| 80.08 | <p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling Soil, sandy and decomposed granite</p> | |

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------------|---|
| | <p>Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.</p> <p>Discontinue the survey of the first range of sections at this corner.</p> |
| | <p>The cor. of secs. 2, 3, 34, and 35 on the south boundary of the township is monumented with an iron post, 2 ins. in diam., firmly set, projecting 12 ins. above the surface of the ground, with the brass cap mkd.</p> |
| | <p style="text-align: center;"> T6N $\begin{array}{c c} \text{w} & \text{S 34} \\ \text{S} & \text{S 35} \\ \hline \text{E} & \text{S 3} \\ & \text{S 2} \\ \hline & \text{T5N} \end{array}$ </p> <p style="text-align: center;">1919</p> |
| | <p>This corner is located 4 lks. north of an east and west fence line.</p> |
| | <p style="text-align: center;">N. 0° 01' W., between secs. 34 and 35</p> <p>Descend over rolling northeast slope.</p> |
| <p>40.00</p> | <p>The point for the 1/4 sec. cor. of secs. 34 and 35</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;"> T6N R5E 1/4 $\begin{array}{c c} \text{S 34} & \text{S 35} \end{array}$ </p> <p style="text-align: center;">1973</p> |
| | <p>Ascend over rolling south slope.</p> |
| <p>80.00</p> | <p>The point for the cor. of secs. 26, 27, 34, and 35</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;"> T6N R5E $\begin{array}{c c} \text{S 27} & \text{S 26} \\ \hline \text{S 34} & \text{S 35} \end{array}$ </p> <p style="text-align: center;">1973</p> |
| | <p>Land, rolling Soil, sandy and decomposed granite</p> |

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti. |
| | From the cor. of secs. 25, 26, 35, and 36 |
| | S. 89° 55' W., between secs. 26 and 35 |
| | Ascend over rolling southeast slope. |
| 39.98 | The point for the 1/4 sec. cor. of secs. 26 and 35 |
| | Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd. |
| | $\begin{array}{c} \text{T6N R5E} \\ 1/4 \frac{\text{S } 26}{\text{S } 35} \end{array}$ |
| | 1973 |
| 79.96 | The cor. of secs. 26, 27, 34, and 35. |
| | Land, rolling |
| | Soil, sandy and decomposed granite |
| | Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti. |
| | Discontinue the regular order of survey at this corner. |
| | S. 89° 55' W., between secs. 27 and 34 |
| | Descend over rolling south slope. |
| 40.03 | The point for the 1/4 sec. cor. of secs. 27 and 34 |
| | Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd. |
| | $\begin{array}{c} \text{T6N R5E} \\ 1/4 \frac{\text{S } 27}{\text{S } 34} \end{array}$ |
| | 1973 |
| | Descend over rolling southwest slope. |
| 49.92 | Electric transmission line bears N. 16° 57' E. and S. 16° 57' W. |
| 52.26 | Electric transmission line bears N. 16° 57' E. and S. 16° 57' W. |
| 80.06 | The cor. of secs. 27, 28, 33, and 34 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting |

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

CHAINS

4 ins. above the surface of the ground, with brass cap mkd.

T6N R5E
 S 28 | S 27
 S 33 | S 34

1959

substantiated by:

A mound of stone, 2½ ft. base, 1½ ft. high, west of the corner.

Land, rolling
 Soil, sandy and decomposed granite
 Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.

From the cor. of secs. 26, 27, 34, and 35

N. 0° 01' W., between secs. 26 and 27

Ascend over rolling southeast slope.

40.00 The point for the 1/4 sec. cor. of secs. 26 and 27

Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.

T6N R5E
 1/4
 S 27 | S 26

1973

from which

A mesquite tree, 10 ins. in diam., bears S. 59° 30' E., 21 lks. distance, scribed 1/4 S26 BT.

A mesquite tree, 10 ins. in diam., bears N. 25° 45' W., 83 lks. distance, scribed 1/4 S27 BT.

80.00 The point for the cor. of secs. 22, 23, 26, and 27

Set an iron post, 28 ins. long, 2½ ins. in diam., 20 ins. in the ground and in a collar of stone, with brass cap mkd.

T6N R5E
 S 22 | S 23
 S 27 | S 26

1973

Survey of a Portion of the Subdivisional Lines
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| | <p>from which</p> <p>A granite boulder, 6 ft. x 3 ft. base, 3 ft. high, chiseled BXO on the northeast face, bears S. 18° 50' W., 72 lks. distance.</p> <p>Land, rolling Soil, sandy and decomposed granite Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.</p> | |
| | <p>S. 89° 54' W., between secs. 22 and 27</p> <p>Ascend over rolling southeast slope.</p> | |
| 20.03 | <p>The point for the east 1/16 sec. cor. of secs. 22 and 27</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> | |
| | <p style="text-align: center;">E 1/16 $\frac{S\ 22}{S\ 27}$</p> <p style="text-align: center;">1973</p> | |
| 25.58 | <p>Electric transmission line bears N. 16° 57' E. and S. 16° 57' W.</p> | |
| 27.97 | <p>Electric transmission line bears N. 16° 57' E. and S. 16° 57' W.</p> | |
| 40.06 | <p>The point for the 1/4 sec. cor. of secs. 22 and 27</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> | |
| | <p style="text-align: center;">T6N R5E</p> <p style="text-align: center;">1/4 $\frac{S\ 22}{S\ 27}$</p> <p style="text-align: center;">1973</p> | |
| | <p>Descend over rolling southwest slope.</p> | |
| 60.09 | <p>The point for the west 1/16 sec. cor. of secs. 22 and 27</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> | |
| | <p style="text-align: center;">W 1/16 $\frac{S\ 22}{S\ 27}$</p> <p style="text-align: center;">1973</p> | |
| | <p>from which</p> <p>A mesquite tree, 8 ins. in diam., bears N. 57° 45' E., 57 lks. distance, scribed W 1/16 S22 BT.</p> | |

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 80.12 | <p>The cor. of secs. 21, 22, 27, and 28, heretofore described.</p> <p>Land, rolling Soil, sandy and decomposed granite Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.</p> |
| | <p>From the cor. of secs. 22, 23, 26, and 27 N. 0° 01' W., between secs. 22 and 23 Ascend over rolling southeast slope.</p> |
| 20.00 | <p>The point for the south 1/16 sec. cor. of secs. 22 and 23</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">S 1/16 S 22 S 23 1973</p> |
| | <p>Thence, along rolling east slope.</p> |
| 34.34 | <p>Center line of a road bears S. 87° 30' W. and N. 87° 30' E.</p> |
| 40.00 | <p>The point for the 1/4 sec. cor. of secs. 22 and 23</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T6N R5E 1/4 S 22 S 23 1973</p> |
| 60.00 | <p>The point for the north 1/16 sec. cor. of secs. 22 and 23</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">N 1/16 S 22 S 23 1973</p> |
| 80.00 | <p>The point for the cor. of secs. 14, 15, 22, and 23</p> |

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|---|--|
| | <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R5E $\frac{S\ 15}{S\ 22} \frac{S\ 14}{S\ 23}$</p> <p style="text-align: center;">1973</p> <p>Land, rolling Soil, sandy and decomposed granite Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.</p> | |
| | <p>S. 89° 57' W., between secs. 15 and 22</p> <p>Ascend over rolling southeast slope.</p> | |
| 1.24 | Electric transmission line bears N. 16° 55' E. and S. 16° 55' W. | |
| 3.61 | Electric transmission line bears N. 16° 55' E. and S. 16° 55' W. | |
| 20.03 | <p>The point for the east 1/16 sec. cor. of secs. 15 and 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 $\frac{S\ 15}{S\ 22}$</p> <p style="text-align: center;">1973</p> | |
| 26.15 | <p>Intersect the eastern boundary of Exchange Survey No. 659, Tract B.</p> <p>The point for the closing cor. of secs. 15 and 22</p> <p>Set a ¼-inch T-shaped steel post, 5 ft. long, 24 ins. in the ground.</p> <p>From this corner, corner No. 13 of the Exchange Survey No. 659, Tract B (hereinafter described), bears N. 28° 22' E. (record N. 28° 20' E.), 77.37 chs. distance.</p> <p>From this same corner, corner No. 14 of the Exchange Survey No. 659, Tract B, bears S. 28° 22' W., 14.96 chs. distance, and is monumented with a phylite stone, firmly set, 12 x 4 ins. base, projecting 4 ins. above the surface of the ground, mkd. 14 ES 659 on the north face.</p> <p>Thence, on a blank line across the Exchange Survey.</p> | |
| 40.06 | The point for the 1/4 sec. cor. of secs. 15 and 22 | |

Survey of a Portion of the Subdivisional Lines
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona


| CHAINS | |
|--------|--|
| | <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R5E 1/4 $\frac{S\ 15}{S\ 22}$</p> <p style="text-align: center;">1973</p> |
| 41.03 | <p>Intersect the western boundary of Exchange Survey No. 659, Tract B.</p> <p>The point for the closing cor. of secs. 15 and 22</p> <p>Set a 1¼-inch T-shaped steel post, 5 ft. long, 24 ins. in the ground.</p> <p>From this corner, corner No. 9 of the Exchange Survey No. 659, Tract B, bears N. 4° 33' E., 12.19 chs. distance, and is monumented with a phylite stone, firmly set, 7 x 4 ins. base, projecting 17 ins. above the surface of the ground, mkd. 9 ES 659 on the east face.</p> <p>From this same corner, corner No. 15 of the Exchange Survey No. 659, Tract B, bears S. 4° 33' W., 12.67 chs. distance, and is monumented with a slate stone, firmly set, 12 x 4 ins. base, projecting 10 ins. above the surface of the ground, mkd. with a cross (+) chiseled on the top and 15 ES 659 on the northeast face.</p> |
| 42.93 | Center line of Cave Creek road bears N. 1° 30' E. and S. 1° 30' W.; thence, descend over rolling west slope. |
| 47.59 | Electric transmission line bears N. 21° 25' E. and S. 21° 25' W. |
| 60.09 | <p>The point for the west 1/16 sec. cor. of secs. 15 and 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 15}{S\ 22}$</p> <p style="text-align: center;">1973</p> |
| 80.12 | <p>The cor. of secs. 15, 16, 21, and 22, heretofore described.</p> <p>Land, rolling Soil, sandy and decomposed granite Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.</p> <hr/> <p>From the cor. of secs. 14, 15, 22, and 23</p> <p>N. 0° 01' W., between secs. 14 and 15</p> <p>Ascend over rolling southeast slope.</p> |

Survey of a Portion of the Subdivisional Lines
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 4.01 | Electric transmission line bears N. 16° 55' E. and S. 16° 55' W. |
| 11.91 | Electric transmission line bears N. 16° 55' E. and S. 16° 55' W. |
| 21.00 | Low saddle, bears east and west; thence, along rolling east slope. |
| 40.00 | The point for the 1/4 sec. cor. of secs. 14 and 15 Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd. |
| | <p>T6N R5E 1/4 S 15 S 14 1973</p> |
| | Ascend over rolling southeast slope. |
| 48.35 | Intersect the eastern boundary of Exchange Survey No. 659, Tract B. The point for the closing cor. of secs. 14 and 15 Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd. |
| | <p>TR B ES 659 S 14 S 15 C C T6N R5E 1973</p> |
| | From this corner, corner No. 13 of the Exchange Survey No. 659, Tract B, bears N. 28° 22' E., 22.38 chs. distance, and is monumented with a phylite stone, firmly set, 8 x 3 ins. base, projecting 12 ins. above the surface of the ground, mkd. ES 659 13 on the south face. |
| | From this same corner, corner No. 14 of the Exchange Survey No. 659, Tract B (heretofore described), bears S. 28° 22' W., 69.95 chs. distance. |
| | Thence, on a blank line across the Exchange Survey. |
| 72.79 | Intersect the northern boundary of Exchange Survey No. 659, Tract B. The point for the closing cor. of secs. 14 and 15 Set an iron post, 28 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd. |

Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

CHAINS




From this corner, corner No. 12 of the Exchange Survey No. 659, Tract B, bears N. 65° 57' W., 6.15 chs. distance, and is monumented with a phylite stone, firmly set, 10 x 4 ins. base, projecting 7 ins. above the surface of the ground, mkd. 12 ES 659 on the south face.

From this same corner, corner No. 13 of the Exchange Survey No. 659, Tract B (heretofore described), bears S. 65° 57' E., 11.66 chs. distance.

80.00

The point for the corner of secs. 10, 11, 14, and 15

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.



1973

Land, rolling
 Soil, sandy and decomposed granite
 Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.

S. 89° 58' W., between secs. 10 and 15

Ascend over rolling east slope.

5.68


Center line of Cave Creek road bears N. 30° 47' E. and S. 30° 47' W.

7.91

Intersect the eastern boundary of Exchange Survey No. 659, Tract A.

The point for the closing cor. of secs. 10 and 15

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.



Survey of a Portion of the Subdivisional Lines
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|---|--|
| | <p>From this corner, corner No. 4 of the Exchange Survey No. 659, Tract A, bears N. 24° 06' E., 17.32 chs. distance, and is monumented with a phylite stone, firmly set, 10 x 3 ins. base, projecting 8 ins. above the surface of the ground, mkd. 4 ES 659 on the southwest face.</p> | |
| | <p>From this same corner, corner No. 5 of the Exchange Survey No. 659, Tract A, bears S. 24° 06' W., 24.63 chs. distance, and is monumented with a slate stone, firmly set, 12 x 5 ins. base, projecting 11 ins. above the surface of the ground, mkd. with a cross (+) chiseled on the top and 5 ES 659 on the northwest face.</p> | |
| | <p>Thence, on a blank line across the Exchange Survey.</p> | |
| 17.17 | <p>Electric transmission line bears N. 21° 30' E. and S. 21° 30' W.</p> | |
| 40.07 | <p>The point for the 1/4 sec. cor. of secs. 10 and 15</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> | |
| | <p style="text-align: center;">T6N R5E 1/4 $\frac{S\ 10}{S\ 15}$ 1973</p> | |
| 69.94 | <p>Intersect the western boundary of Exchange Survey No. 659, Tract A.</p> | |
| | <p>The point for the closing cor. of secs. 10 and 15</p> | |
| | <p>Set a 1¼-inch T-shaped steel post, 5 ft. long, 24 ins. in the ground.</p> | |
| | <p>This corner is designated to function for Corner No. 1, Tract No. 37.</p> | |
| | <p>From this corner, corner No. 1 of the Exchange Survey No. 659, Tract A, bears S. 25° 42' E., 23.00 chs. distance, and is monumented with a granite stone-in-place 6 x 12 ft. base, 5 ft. high, mkd. with a cross (+) chiseled on the top and 1 ES 659.</p> | |
| | <p>From this same corner, corner No. 2 of the Exchange Survey No. 659, Tract A, bears N. 25° 42' W., 27.99 chs. distance, and is monumented with a granite stone-in-place, 8 x 6 x 2 ft. above the surface of the ground, mkd. with a cross (+) chiseled on the top and 2 ES 659.</p> | |
| 80.14 | <p>The cor. of sec. 9, 10, 15, and 16 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 10 ins. above the surface of the ground, with the brass cap mkd.</p> | |
| | <p style="text-align: center;">T6N R5E $\frac{S\ 9}{S\ 16} \mid \frac{S\ 10}{S\ 15}$ 1963</p> | |

Survey of a Portion of the Subdivisional Lines
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>This corner is designated to function for Corner No. 3, Tract No. 37.</p> <p>Land, rolling Soil, sandy and decomposed granite Timber, scattering paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo, and cacti.</p> <p>Discontinue the survey of the subdivisional line at this corner.</p> |
| | <p>Survey of a Portion of the Subdivision Lines within Section 22 Township 6 North, Range 5 East Gila and Salt River Meridian, Arizona</p> |
| | <p>From the 1/4 sec. cor. of secs. 22 and 27</p> <p>N. 0° 01' 30" W., on the north and south center line of section 22.</p> |
| 20.006 | <p>The point for the C S 1/16 sec. cor. of sec. 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 22 1973</p> |
| 30.009 | <p>The point for the C N S 1/64 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with brass cap 1½ ins. in diam., mkd.</p> <p style="text-align: center;">C N S 1/64 S 22 1973</p> |
| 40.012 | <p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R5E C 1/4 S 22 1973</p> |

Survey of a Portion of the Subdivision Lines
within Section 22
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 60.017 | <p>The point for the C N 1/16 sec. cor. of sec. 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 22 1973</p> |
| 67.277 | <p>Intersect the southern boundary of Exchange Survey No. 659, Tract B</p> <p>The point for the closing corner of section 22. I did not monument this corner point.</p> <p>From this point of intersection, corner No. 14 of the Exchange Survey No. 659, Tract B, heretofore described, bears S. 86° 36' E., 6.81 chs. distance.</p> <p>From this same point of intersection, corner No. 15 of the Exchange Survey No. 659, Tract B, heretofore described, bears N. 86° 36' W., 1.98 chs. distance.</p> <p>Thence, on a blank line across the Exchange Survey.</p> |
| 70.019 | <p>The point for the C N N 1/64 sec. cor. of sec. 22. This corner point is located within the area of Exchange Survey No. 659, Tract B, and I did not monument this corner point.</p> |
| 80.022 | <p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23</p> <p>S. 89° 55' 30" W., on the east and west center line of section 22</p> |
| 10.014 | <p>The point for the C E E 1/64 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 14 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> <p style="text-align: center;">C E E 1/64 S 22 1973</p> |
| 15.021 | <p>The point for the C W E E 1/256 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with brass cap 1½ ins. in diam., mkd.</p> |


Survey of a Portion of the Subdivision Lines
within Section 22
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | C W E E 1/256 S 22 1973 |
| 20.028 | The point for the C E 1/16 sec. cor. of sec. 22 Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd. |
| | C E 1/16 S 22 1973 |
| 40.056 | Intersect the north and south center line, the center 1/4 sec. cor. of section 22 |
| 60.086 | The point for the C W 1/16 sec. cor. of sec. 22 Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd. |
| | C W 1/16 S 22 1973 |
| 80.116 | From this corner the U. S. Coast and Geodetic Survey Triangulation Station "Wildcat" bears S. 31° 12' W., 10.566 chs. distance, and is marked with a brass tablet, ¾ ins. in diam., seated on a stone-in-place (bedrock), near ground level, mkd. WILDCAT 1946. The 1/4 sec. cor. of secs. 21 and 22. |
| | From the center east 1/16 sec. cor. of secs. 22 N. 0° 01' W., on the north and south center line of the NE 1/4 of section 22 |
| 20.003 | Intersect the east and west center line of the NE 1/4, the point for the NE 1/16 sec. cor. of sec. 22 Set an iron post, 30 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd. |
| | NE 1/16 S 22 1973 |
| 30.004 | The point for the CN NE 1/64 sec. cor. of sec. 22 |

Survey of a Portion of the Subdivision Lines
 within Section 22
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| | <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with brass cap 1 1/2 ins. in diam., mkd.</p> | |
| | <p>C N NE 1/64 S 22</p> | |
| | <p>1973</p> | |
| 40.005 | <p>The east 1/16 sec. cor. of secs. 15 and 22.</p> | |
| | <p>From the north 1/16 sec. cor. of secs. 22 and 23</p> | |
| | <p>S. 89° 56' W., on the east and west center line of the NE 1/4 of section 22</p> | |
| 15.023 | <p>The point for the C W E NE 1/256 sec. cor. of sec. 22</p> | |
| | <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 15 ins. in the ground, with the brass cap 1 1/2 ins. in diam., mkd.</p> | |
| | <p>C W E NE 1/256 S 22</p> | |
| | <p>1973</p> | |
| 20.030 | <p>Intersect the north and south center line of the NE 1/4, the NE 1/16 sec. cor. of sec. 22.</p> | |
| 40.060 | <p>The C N 1/16 sec. cor. of sec. 22.</p> | |
| | <p>From the C E E 1/64 sec. cor. of sec. 22</p> | |
| | <p>N. 0° 01' W., on the north and south center line of the SE 1/4 NE 1/4 of section 22</p> | |
| 10.000 | <p>The calculated position, the point for the SE NE 1/64 sec. cor. of sec. 22</p> | |
| | <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 in s. in the ground, with a brass cap 1 1/2 ins. in diam., mkd.</p> | |
| | <p>SE NE 1/64 S 22</p> | |
| | <p>1973</p> | |



Survey of a Portion of the Subdivision Lines
 within Section 22
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>S. 89° 55' 45" W., on the east and west center line of the SE$\frac{1}{4}$NE$\frac{1}{4}$ of section 22</p> |
| 5.007 | <p>The calculated position, the point for the C W SE NE 1/256 sec. cor. of sec. 22</p> |
| | <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> |
| | <p style="text-align: center;">C W SE NE 1/256 S 22 1973</p> |
| 10.001 | <p>N. 0° 01' W., on the north and south center line of the NW$\frac{1}{4}$SE$\frac{1}{4}$NE$\frac{1}{4}$ of section 22</p> <p>The C W E NE 1/256 sec. cor. of sec. 22.</p> |
| 11.530 | <p>From the C N NE 1/64 sec. cor. of sec. 22</p> <p>S. 89° 56' 30" W., on the east and west center line of the NW$\frac{1}{4}$NE$\frac{1}{4}$ of section 22</p> <p>Intersect the eastern boundary of Exchange Survey No. 659, Tract B.</p> <p>The point for the closing corner of section 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with brass cap 1½ ins. in diam., mkd.</p> |
| |  |
| | <p>From this corner, corner No. 13 of the Exchange Survey No. 659, Tract B, (heretofore described) bears N. 28° 22' E., 88.74 chs. distance.</p> |
| | <p>From this same corner, corner No. 14 of the Exchange Survey No. 659, Tract B, (heretofore described) bears S. 28° 22' W., 3.590 chs. distance.</p> |
| 20.030 | <p>Thence, on a blank line across the Exchange Survey</p> <p>The point for the C N N 1/64 sec. cor. of sec. 22.</p> |

Survey of a Portion of the Subdivision Lines
within Section 22
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>From the C W 1/16 sec. cor. of sec. 22</p> <p>N. 0° 02' W., on the north and south center line of the NW 1/4 of section 22</p> |
| 10.006 | <p>The point for the C S NW 1/64 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 15 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> <p style="text-align: center;">C S NW 1/64 S 22 1973</p> |
| 20.012 | <p>Intersect the east and west center line of the NW 1/4, the point for the NW 1/16 sec. cor. of sec. 22</p> <p>Set an iron post, 30 ins. long, 2½ ins. in diam., 4 ins. in the ground, over a cross (+) chiseled on bedrock, and in a mound of stone, 3 ft. base, to the top, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 22 1973</p> |
| 40.028 | <p>The west 1/16 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the C N 1/16 sec. cor. of sec. 22</p> <p>S. 89° 56' W., on the east and west center line of the NW 1/4 of section 22</p> |
| 10.016 | <p>The point for the C E NW 1/64 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 15 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> <p style="text-align: center;">C E NW 1/64 S 22 1973</p> |
| 15.023 | <p>The point for the C W E NW 1/256 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 15 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> <p style="text-align: center;">C W E NW 1/256 S 22 1973</p> |

Survey of a Portion of the Subdivision Lines
within Section 22
Township 6 North, Range 5 East
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 20.030 | Intersect the north and south center line of the NW 1/4, the NW 1/16 sec. cor. of sec. 22 |
| 40.060 | The north 1/16 sec. cor. of secs. 21 and 22. |
| 1.770 | <p>From the point for the C N N 1/64 sec. cor. of sec. 22 S. 89° 56' 30" W., on the east and west center line of the NE¹/₄NW¹/₄ of section 22</p> <p>Intersect the western boundary of Exchange Survey No. 659, Tract B.</p> <p>The point for the closing corner of section 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  </div> <p>1973</p> <p>From this corner, corner No. 9 of the Exchange Survey No. 659, Tract B, (heretofore described) bears N. 4° 33' E., 22.23 chs. distance.</p> <p>From this same corner, corner No. 15 of the Exchange Survey No. 659, Tract B, (heretofore described) bears S. 4° 33' W., 2.63 chs. distance.</p> |
| 10.014 | <p>The calculated position, the point for the NE NW 1/64 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> <div style="text-align: center;">  </div> <p>1973</p> |
| 10.004 | <p>S. 0° 01' 45" E., on the north and south center line of the NE¹/₄NW¹/₄ of section 22</p> <p>The C E NW 1/64 sec. cor. of sec. 22.</p> |

Survey of a Portion of the Subdivision Lines
 within Section 22
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|---|--|
| 10.006 | <p>From the C W E NW 1/256 sec. cor. of sec. 22</p> <p>S. 0° 01' 45" E., on the north and south center line of the NW¹/₄SE¹/₄NW¹/₄ of section 22</p> <p>The calculated position, the point for the C W SE NW 1/256 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> <p style="text-align: center;">C W SE NW 1/256 S 22 1973</p> <hr style="width: 20%; margin: auto;"/> | |
| 5.007 | <p>S. 89° 55' 45" W., on the east and west center line of the SE¹/₄NW¹/₄ of section 22</p> <p>The C S NW 1/64 sec. cor. of sec. 22.</p> | |
| 20.011 | <p>From the west 1/16 sec. cor. of secs. 22 and 27</p> <p>N. 0° 02' W., on the north and south center line of the SW 1/4 of section 22</p> <p>Intersect the east and west center line of the SW 1/4, the point for the SW 1/16 sec. cor. of sec. 22</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 22 1973</p> | |
| 35.020 | <p>The point for the C N N SW 1/256 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 10 ins. long, 1/2 inch in diam., with brass cap 1½ ins. in diam., flush with the surface of the road, mkd.</p> <p style="text-align: center;">C N N SW 1/256 S 22 1973</p> <p>from which</p> | |

Survey of a Portion of the Subdivision Lines
 within Section 22
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>An iron post, 28 ins. long, 2½ ins. in diam., set 21 ins. in the ground, for a reference monument, bears N. 89° 55' E., 58 ft. distance, with brass cap mkd. RM T6N R5E S22 58 FT 1973, and an arrow pointing to the corner.</p> |
| | <p>There are no suitable accessories or locations available for other reference monuments.</p> |
| | <p>This corner is located 43 lks. distance south of the center line of Cave Creek Road, road bears N. 39° E. and S. 39° W.</p> |
| 40.023 | <p>The C W 1/16 sec. cor. of sec. 22.</p> |
| | <p>From the C S 1/16 sec. cor. of sec. 22</p> |
| | <p>S. 89° 55' W., on the east and west center line of the SW 1/4 of section 22</p> |
| 20.030 | <p>Intersect the north and south center line of the SW 1/4, the SW 1/16 sec. cor. of sec. 22.</p> |
| 40.060 | <p>The south 1/16 sec. cor. of secs. 21 and 22.</p> |
| | <p>From the C N S 1/64 sec. cor. of secs. 22</p> |
| | <p>S. 89° 55' W., on the east and west center line of the NE¼SW¼ of section 22</p> |
| 10.014 | <p>The calculated position, the point for the NE SW 1/64 sec. cor. of sec. 22</p> |
| | <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with the brass cap 1½ ins. in diam., mkd.</p> |
| | <p style="text-align: center;">NE SW 1/64 S 22</p> |
| | <p style="text-align: center;">1973</p> |
| | <p>from which</p> |
| | <p>The southeast corner of a concrete building 24 ft. x 75 ft. (longside bears N. 38° 30' W.) bears N. 18° 16' W., 123 lks. distance.</p> |
| | <p>N. 0° 01' 45" W., on the north and south center line of the NE¼SW¼ of section 22</p> |

Survey of a Portion of the Subdivision Lines
 within Section 22
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| 5.002 | <p>The calculated position, the point for the C N NE SW 1/256 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with the brass cap 1 1/2 ins. in diam., mkd.</p> <p style="text-align: center;">C N NE SW 1/256 S 22 1973</p> <hr style="width: 20%; margin: auto;"/> | |
| 10.014 | <p>S. 89° 55' 15" W., on the east and west center line of the NW 1/4 NE 1/4 SW 1/4 of section 22</p> <p>The C N N SW 1/256 sec. cor. of sec. 22.</p> | |
| 20.003 | <p>From the east 1/16 sec. cor. of secs. 22 and 27</p> <p>N. 0° 01' W., on the north and south center line of the SE 1/4 of section 22</p> <p>Intersect the east and west center line of the SE 1/4, the point for the SE 1/16 sec. cor. of sec. 22</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 22 1973</p> | |
| 30.005 | <p>The point for the C N SE 1/64 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 18 ins. in the ground, with the brass cap 1 1/2 ins. in diam., mkd.</p> <p style="text-align: center;">C N SE 1/64 S 22 1973</p> | |
| 40.006 | <p>The C E 1/16 sec. cor. of sec. 22.</p> | |

Survey of a Portion of the Subdivision Lines
 within Section 22
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|-----------------------------|--|
| <p>20.030</p> <p>40.060</p> | <p>From the south 1/16 sec. cor. of secs. 22 and 23</p> <p>S. 89° 55' W., on the east and west center line of the SE 1/4 of section 22</p> <p>Intersect the north and south center line of the SE 1/4, the SE 1/16 sec. cor. of sec. 22</p> <p>The C S 1/16 sec. cor. of sec. 22.</p> |
| <p>5.007</p> | <p>From the C N SE 1/64 sec. cor. of sec. 22</p> <p>N. 89° 55' E., on the east and west center line of the NE 1/4 SE 1/4 of section 22</p> <p>The calculated position, the point for the C W NE SE 1/256 sec. cor. of sec. 22</p> <p>Set a copper-coated steel stake, 24 ins. long, 1/2 inch in diam., 15 ins. in the ground, with brass cap 1 1/2 ins. in diam., mkd.</p> <p style="text-align: center;">C W NE SE 1/256 S 22</p> <p style="text-align: center;">1973</p> |
| <p>10.001</p> | <p>N. 0° 01' W., on the north and south center line of the NW 1/4 NE 1/4 SE 1/4 of section 22</p> <p>The C W E E 1/256 sec. cor. of sec. 22.</p> |
| <p>20.030</p> | <p>From the C N SE 1/64 sec. cor. of sec. 22</p> <p>S. 89° 55' W., on the east and west center line of the NW 1/4 SE 1/4 of section 22</p> <p>The C N S 1/64 sec. cor. of sec. 22.</p> |


The Metes-and-Bounds Survey of Tract No. 37
 Township 6 North, Range 5 East
 Gila and Salt River Meridian, Arizona

CHAINS

The closing corner of secs. 10 and 15 (the western boundary) on line 1-2, Exchange Survey No. 659, Tract A, heretofore described, is designated to function for Corner No. 1, Tract No. 37.

N. 25° 42' W., on line 1-2 of Tract 37, along line 1-2 (the western boundary) of Exchange Survey No. 659, Tract A

23.54 The closing corner of secs. 9 and 10 which is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 8 ins. above the surface of the ground, with the brass cap mkd.



This closing corner is designated to function for Corner No. 2, Tract No. 37.

S. 0° 02' E., on line 2-3, along the east boundary of section 9

21.22 The cor. of secs. 9, 10, 15, and 16, heretofore described. This corner is designated to function for Corner No. 3, Tract No. 37.

N. 89° 58' E., on line 3-1 along the north boundary of section 15

10.20 Corner No. 1, the place of beginning.

GENERAL DESCRIPTION

The area of this survey is located within the Tonto National Forest and varies from rough and broken to rolling land. The elevation ranges from 2640 ft. above sea level along the east boundary of section 36 to 3600 ft. above sea level near the northwest corner of section 15. The soil is sandy and decomposed granite. The land within this survey is located in the Camp Creek drainage. Timber, paloverde, mesquite, catclaw acacia; undergrowth, young trees, brush, ocotillo and cacti.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Ray Harpin, Supervisory Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of July, 1973, (I) ~~(We)~~ have dependently resurveyed a portion of the subdivisional lines and surveyed a portion of the subdivisional lines of the township; surveyed a portion of the subdivision lines within section 22; and the metes-and-bounds survey of Tract No. 37, Township 6 North, Range 5 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 22, 1974
 (Date) Ray Harpin, Supervisory (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

SUBMITTED FOR APPROVAL

Date MAR 15 1974
 The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines, the survey of a portion of the subdivisional lines of the township, the survey of a portion of the subdivision lines within section 22, and the metes-and-bounds survey of Tract No. 37 executed by Ray Harpin, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

NOV 20 1974
 (Date) Bernard W. Fisher
 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626