

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

DEPENDENT RESURVEY

of a

PORTION of the SOUTH BOUNDARY

and the

COMPLETION SURVEY

of the

SUBDIVISIONAL LINES

TOWNSHIP 40 NORTH, RANGE 1 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer Cadastral Surveyor

Under special instructions dated June 22, 19 71, which provided for the surveys
included under Group Number 536, approved June 22, 1971,
and assignment instructions dated July 19, 19 71.

Survey commenced August 3, 19 71

Survey completed August 30, 19 71

1A

BOOK 4997

INDEX DIAGRAM

Township 40 North, Range 1 West,

44	44	33	25	24	13
6	43 5	32 4	8	23 2	11 1
42	41	31	22	22	10
7	41 8	30 9	10	21 11	10 12
40	39		20	20	9
18	39 17	16	15	19 14	8 13
38	37		18	18	8
19	37 20	21	29 22	17 23	7 24
36	35	28	28	16	6
30	34 29	28	27 27	15 26	5 25
33		26	26	14	5
31	32	33	25 34	13 35	3 36
		2	1		

Township 40 North, Range 1 West
Gila and Salt River Meridian, Arizona

CHAINS

The north boundary (the Tenth Standard Parallel North), was surveyed in 1911 by Andrew Nelson. The east boundary (the Gila and Salt River Meridian) was surveyed in 1914 by Jos. C. Thoma. The south boundary was surveyed in 1916 by Thomas B. Matthews and William L. Nash. The west boundary and a portion of the subdivisional lines were surveyed in 1954 by Donald E. Harding.

The following notes are those of a dependent resurvey of a portion of the south boundary designed to restore the corners in their true original location based on the best available evidence and a completion survey of the subdivisional lines of Township 40 North, Range 1 West.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions 1947, and the Special Instructions dated June 22, 1971.

The directions of all lines were determined by solar observations and all lines refer to the true meridian. Only the true line bearings and horizontal distances for the surveyed lines are given in these notes.

The geographic position of the southeast corner of the township as determined by scaling from U.S.G.S. quadrangle, Shinarump SE., Arizona, scale 1:24000, dated 1957 is: Latitude $36^{\circ}48'59''$ North and Longitude $112^{\circ}20'28''$ West.

The mean magnetic declination was found to be: 15° East.

Dependent Resurvey, Portion of the South Boundary
Township 40 North, Range 1 West

Reestablishment of the Survey executed by
Thomas B. Matthews and William L. Nash in 1916

In order to complete the subdivisional lines of T. 40 N., R. 1 W., it was necessary to resurvey a portion of the South Boundary of the township to reestablish certain corners which had been disturbed during timber railing operations.

Beginning at the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., projecting 16 ins. above the ground, in a collar of stone, 2 ft. base, 1 ft. high, brass cap mkd.

T40N
S34|S35 R1W
S 3|S 2
T39N
1916

The cor. is located $1\frac{1}{2}$ lks. S. of a cor. of fences extending N. $89^{\circ}53'$ E. and N. $76^{\circ}50'$ W.

S. $89^{\circ}53'$ W., bet. secs. 3 and 34.

Dep. Res., Portion South Boundary, T. 40 N., R. 1 W.

CHAINS		
40.00	<p>Over gently rolling land, through scattered timber and dense undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, at proportionate dist.</p> <p>The original cor., an iron post, 36 ins. long, 1 ins. diam., flanged at the base and with a brass cap riveted to the top was found lying loose on the ground. Reset the original cor. 20 ins. in the ground, with a collar of stone to the top, add date on brass cap to read:</p> $\begin{array}{r} \frac{1}{4} \text{ S34} \\ \text{S } 3 \\ 1971 \\ 1916 \end{array}$ <p>from which the original bearing trees (not previously recorded.)</p> <p>A pinyon pine, 10 ins. diam., bears N. $55\frac{1}{4}^\circ$ E., 146 lks. dist., mkd. $\frac{1}{4}$ S34 BT.,</p> <p>A cedar, 14 ins. diam., bears S. $36\frac{1}{4}^\circ$ W., 158 lks. dist., mkd. $\frac{1}{4}$ S3 BT.,</p>	
48.90	<p>Track road, bears S. 40° E., curving E. and N. 40° W., curving W.</p>	
80.00	<p>Point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist.</p> <p>The original cor., an iron post, 3 ft. long, 2 ins. diam., flanged at the base and with a brass cap riveted to the top, was found lying loose on the ground. Reset the original cor. 14 ins. in the ground, mound of stone to the top, add date on brass cap to read:</p> $\begin{array}{r} \text{T40N} \\ \text{S33} \text{S34} \\ \text{S } 4 \text{S } 3 \text{ R1W} \\ \text{T39N} \\ 1971 \\ 1916 \end{array}$ <p>Land, gently rolling. Soil, shallow and rocky. Timber, scattered pinyon and cedar. Undergrowth, dense sagebrush.</p>	
40.00	<p>S. $89^\circ 53'$ W., bet. secs. 4 and 33.</p> <p>Over gently rolling land, through dense undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 33, monumented by an iron post, 1 ins. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the cor., brass cap mkd.</p>	

Dep, Res., Portion South Boundary, T. 40 N., R. 1 W.

CHAINS

$\frac{1}{2}$
S33
 S 4
 1916

Land, gently rolling.
 Soil, shallow and rocky.
 Timber, none.
 Undergrowth, dense sagebrush.

Completion Survey of the Subdivisional Lines
 Township 40 North, Range 1 West

From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented by an iron post, 2 ins. diam., projecting 14 ins. above the ground, brass cap mkd.

T40N
S35 | S36 R1W
 S 2 | S 1
 T39N
 1916

from which the original bearing trees

A pinyon pine, 13 ins. diam., with a partially healed blaze, mkd. T40N R1W S36 BT, bears N. 23 $\frac{1}{2}$ ° E., 271 lks. dist.

A pinyon pine, 13 ins. diam., with a partially healed blaze, mkd. T39N R1W S1 BT., bears S. 21 $\frac{1}{2}$ ° E., 220 lks. dist. (Record S. 21° E.)

A cedar, 12 ins. diam., with a partially healed blaze, mkd. T39N R1W S2 BT., bears S. 6 $\frac{3}{4}$ ° W., 96 lks. dist. (Record S. 7 $\frac{3}{4}$ ° W.)

A pinyon pine, 14 ins. diam., with a partially healed blaze, mkd. T40N R1W S35 BT., bears N. 66 $\frac{1}{2}$ ° W., 178 lks. dist. (Record N. 65 $\frac{1}{2}$ ° W.)

The cor. is located in a corner of fences extending E., S. and W.

N. 0°01' W., bet. secs. 35 and 36.

Over gently rolling land, through moderate timber and scattered undergrowth.

19.50 Low rim, bears S. 30° E. and N. 30° W.

30.80 Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.

37.60 Spur, slopes N. 45° W.

40.00 Point for the $\frac{1}{2}$ sec. cor. of secs. 35 and 36.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground and in a collar of stone, $1\frac{1}{2}$ ft. base to top, brass cap mkd.

T40N R1W

$$\begin{array}{c} \frac{1}{2} \\ \hline \text{S35} | \text{S36} \\ 1971 \end{array}$$

from which

A pinyon pine, 14 ins. diam., bears N. $41\frac{1}{2}^\circ$ E., 77 lks. dist., mkd. $\frac{1}{2}$ S36 BT.

A pinyon pine, 10 ins. diam., bears S. $89\frac{1}{4}^\circ$ W., 34.5 lks. dist., mkd. $\frac{1}{2}$ S35 BT.

A catch pond, 2.00 chs. diam., bears N. $47^\circ 08'$ W., 12.94 chs. dist.

50.90 Track road, bears S. 60° E. and N. 60° W.

55.00 Track road, bears N. 56° E., curving N. and S. 56° W.

56.00 Wash, 15 lks. wide, 1 ft. deep, drains N. 80° W., curving S.

62.60 Track road, bears S. 20° E. and N. 20° W.

65.00 Track road, bears E., 35 lks. dist., curving S. 30° E. and W., 35 lks. dist., curving N. 30° W.

80.00 Point for the cor. of secs. 25, 26, 35 and 36.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone, 2 ft. base to top, brass cap mkd.

T40N R1W

$$\begin{array}{c} \text{S26} | \text{S25} \\ \hline \text{S35} | \text{S36} \\ 1971 \end{array}$$

from which

A pinyon pine, 8 ins. diam., bears N. 5° E., 71.5 lks. dist., mkd. T40N R1W S25 BT.

A pinyon pine, 6 ins. diam., bears S. $20\frac{3}{4}^\circ$ E., 79.5 lks. dist., mkd. T40N R1W S36 BT.

A pinyon pine, 10 ins. diam., bears S. $35\frac{1}{2}^\circ$ W., 91 lks. dist., mkd. T40N R1W S35 BT.

A pinyon pine, 9 ins. diam., bears N. 41° W., 118.5 lks. dist., mkd. T40N R1W S26 BT.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.

Land, gently rolling to rolling.

Soil, shallow and rocky.

Timber, moderate cedar and pinyon pine.

Undergrowth, scattered cacti and sagebrush.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

From the true point for the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., from which the witness cor. bears South, 20 lks. dist., monumented by an iron post, 3 ins. diam., projecting 11 ins. above the ground and in a mound of stone, 2 ft. base to top, brass cap mkd.

T40N
R1W|R1E
S25|S30
W|C
S36|S31
W C
1914

The cor. is located in a fenceline, bearing N. and S. S. 89°46' W., bet. secs. 25 and 36.

Over rolling land, through scattered timber and undergrowth.

- 5.80 Wash, 5 lks. wide, 1½ ft. deep, drains N. 55° W. from E.
- 20.30 Track road, bears N. 15° E. and S. 15° W.
- 33.20 Draw, drains N. 45° W.
- 39.98 Point for the ¼ sec. cor. of secs. 25 and 36.
- Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.

T40N R1W
¼ S25
S36
1971

- 79.96 The cor. of secs. 25, 26, 35 and 36.

Land, rolling.
Soil, shallow and rocky.
Timber, scattered cedar.
Undergrowth, sagebrush and cacti.

N. 0°01' W., bet. secs. 25 and 26.

Over rolling land, through moderate undergrowth.

- 40.00 Point for the ¼ sec. cor. of secs. 25 and 26.
- Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T40N R1W
¼
S26|S25
1971

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p>
42.00	Wash, 15 lks. wide, 6 ins. deep, drains N. 70° W.
64.80	Wash, 5 lks. wide, 6 ins. deep, drains N. 50° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.</p>
	<p>T40N R1W S23 S24 S26 S25 1971</p>
	<p>from which</p> <p>A pinyon pine, 4 ins. diam., bears S. 46° E., 75.3 lks. dist., mkd. BT at the base and X at breat height.</p> <p>A cedar, 15 ins. diam., bears S. 5° W., 159 lks. dist., mkd. T40N R1W S26 BT.</p> <p>A cedar, 9 ins. diam., bears N. 50 3/4° W., 42 lks. dist., mkd. T40N R1W S23 BT.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, scattered cedar and pinyon pine. Undergrowth, sagebrush and cacti.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 7 ins. above the ground and in a collar of stone, 2 ft. base to top, brass cap mkd.</p>
	<p>T40N R1W R1E S24 S19 S25 S30 1914</p>
	<p>The cor. is located near the top of the E. rim of a small canyon, bearing S. 20° E. and N. 20° W.</p> <p>S. 89°43' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through dense undergrowth.</p>
1.70	Wash, in bottom of small canyon, 20 lks. wide, 8 ins. deep, drains N. 20° W.
5.30	West rim of same canyon, bears S. 20° E. and N. 20° W.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
13.50	Fenceline, bears S. $26\frac{1}{2}^{\circ}$ E. and N. $26\frac{1}{2}^{\circ}$ W.
39.17	Track road, bears S. 50° E. and N. 50° W.
40.02	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 11 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, brass cap mkd. T40N R1W $\frac{1}{4}$ $\frac{S24}{S25}$ 1971
76.60	Gully, 15 lks. wide, with 6 ft. walls, drains N. 30° W.
80.04	The cor. of secs. 23, 24, 25 and 26. Land, rolling. Soil, shallow and rocky. Timber, scattered cedar and pinyon pine. Undergrowth, sagebrush and scattered cacti. <hr/> N. $0^{\circ}01'$ W., bet. secs. 23 and 24. Over rolling land, through dense undergrowth.
6.80	Gully 17 lks. wide, with 5 ft. banks, drains N. 40° W.
15.80	Wash, 30 lks. wide, 6 ins. deep, drains N. 80° W.
23.90	Wash, 10 lks. wide, 4 ins. deep, drains N. 70° W.
27.60	Track road, bears S. 80° E. and N. 80° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd. T40N R1W $\frac{1}{4}$ S23 S24 1971
45.40	Track road, bears S. 30° E. and N. 30° W.
71.80	Wildcat Canyon, drains N. 50° W. from East.
80.00	Point for the cor. of secs. 13, 14, 23 and 24. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd. T40N R1W $\frac{1}{4}$ S14 S13 S23 S24 1971 The cor. is located on the SW. slope of Wildcat Canyon. Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, sagebrush and scattered cacti.

Completion Survey, Subdivisional Lines T. 40 N., R. 1 W.

CHAINS	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., firmly set, projecting 20 ins. above the ground and in a mound of stone, 3 ft. base and with a scattered mound of stone W., brass cap mkd.</p>
	<p style="text-align: center;">T40N R1W R1E S13 S18 S24 S19 1914</p>
	<p>The corner is located in a fenceline bearing N. and S. S. 89°42' W., bet. secs. 13 and 24.</p>
	<p>Over gently rolling land, through dense undergrowth.</p>
39.90	<p>Track road, bears S. 40° E. and N. 40° W.</p>
40.02	<p>Point for the ¼ sec. cor. of secs. 13 and 24.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T40N R1W ¼ S13 S24 1971</p>
	<p>Raise a mound of stone N. of the corner.</p>
68.00	<p>Wash, 10 lks. wide, 3 ft. deep, drains S. 20° W.</p>
80.04	<p>The cor. of secs. 13, 14, 23 and 24.</p>
	<p>Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, sagebrush and scattered cacti.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p>
	<p>Over rolling land, through dense undergrowth.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 13 and 14.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T40N R1W ¼ S14 S13 1971</p>
61.00	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 80° W., curving SW.</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
66.20	Track road, bears East and West.
80.00	<p>Point for the cor. of secs. 11, 12, 13 and 14.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, with a mound of stone, 3½ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W S11 S12 S14 S13 .1971</p> <p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, sagebrush and scattered cacti.</p>
	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 22 ins. above the ground and in a mound of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N . R1W R1E. S12 S 7 S13 S18 1914</p>
	<p>S. 89°40' W., bet. secs. 12 and 13.</p> <p>Over rolling land, through moderate timber and dense undergrowth.</p>
6.00	Enter moderate pine and cedar timber, bearing SE. and NW.
11.20	Wash, 15 lks. wide, 1½ ft. deep, drains N. 20° W.
17.60	Enter open land, bears S. 20° E. and N. 30° W.
40.04	<p>Point for the ¼ sec. cor. of secs. 12 and 13.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W ¼ S12 S13 1971</p>
80.08	<p>The corner of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, pinyon pine and cedar in the E. ¼ mile. Undergrowth, sagebrush and scattered cacti.</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	<p>N. 0°01' W., bet. secs. 11 and 12.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
3.00	<p>Wash, 5 lks. wide, 6 ins. deep, drains N. 70° W.</p>
31.20	<p>Wash, 10 lks. wide, 6 ins. deep, drains N. 40° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.</p>
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T40N R1W</p>
	<p style="text-align: center;">$\frac{1}{4}$</p>
	<p style="text-align: center;">S11 S12</p>
	<p style="text-align: center;">1971</p>
51.30	<p>Wash, 10 lks. wide, 1 ft. deep, in small canyon, drains N. 70° W.</p>
69.60	<p>Wash, 10 lks. wide, 6 ins. deep, drains N. 70° W.</p>
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p>
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T40N R1W</p>
	<p style="text-align: center;">S 2 S 1</p>
	<p style="text-align: center;">S11 S12</p>
	<p style="text-align: center;">1971</p>
	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p>
	<p>Land, rolling.</p>
	<p>Soil, shallow and rocky.</p>
	<p>Timber, none.</p>
	<p>Undergrowth, moderate sagebrush and scattered cacti.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., monumented by an iron post, 3 ins. diam., projecting 7 ins. above ground, brass cap mkd.</p>
	<p style="text-align: center;">T40N</p>
	<p style="text-align: center;">R1W R1E</p>
	<p style="text-align: center;">S 1 S 6</p>
	<p style="text-align: center;">S12 S 7</p>
	<p style="text-align: center;">1914</p>
	<p>The cor. is located in a corner of fences extending N., E. and S.</p>
	<p>S. 89°40' W., bet. secs. 1 and 12.</p>
	<p>Over gently rolling land, through moderate sagebrush.</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
29.60	Telephone line, bears S. 40° E. and N. 40° W.
32.00	Track road, bears S. 70° E. and N. 70° W.
35.69	Right-of-way fenceline, bears S. 48°48' E. and N. 48°48' W.
40.06	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, is on the N. edge of U.S. Alt. Highway 89, bearing S. 48°48' E. and N. 48°48' W.
	At the cor. point
	Set a railroad spike flush with the pavement, with the head of the spike mkd.
	T40N R1W $\frac{1}{4}$ $\frac{S1}{S12}$ 1971
	from which
	<p>An iron post, set 3 ins. in the ground and in a mound of stone, 4 ft. base to the top, for a reference monument, bears N. 45° E., 285.4 lks. dist., with brass cap mkd. T40N R1W S1 RM 188.4 ft. 1971 and an arrow pointing to the cor.</p>
	<p>An iron post, set 4 ins. in the ground and in a mound of stone, 4 ft. base to top, for a reference monument, bears S. 45° W., 318.3 lks. dist., with brass cap mkd. T40N R1W S12 RM 210.1 ft. 1971 and an arrow pointing to the cor.</p>
	<p>The R.M.'s are located in right-of-way fencelines paralleling U.S. Alt. Highway 89, with one R.M. on each side of the road.</p>
40.47	The center line of U.S. Alt. Highway 89, bears S. 48°48' E. and N. 48°48' W.
45.24	Right-of-way fenceline, bears S. 48°48' E. and N. 48°48' W.
62.20	Track road, bears N. 20° E. and S. 20° W.
80.12	The cor. of secs. 1, 2, 11 and 12.
	<p>Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, sagebrush and cacti.</p>
	N. 0°01' W., bet. secs. 1 and 2.
	Over gently rolling land, through dense undergrowth.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
21.12	Right-of-way fenceline, bears S. 65° E. and N. 65° W.
21.30	Track road, bears S. 65° E. and N. 65° W.
24.58	The center line of U.S. Alt. Highway 89, bears S. 61°23' E. and N. 61°23' W.
28.04	Right-of-way fenceline, bears S. 65° E. and N. 65° W.
40.00	<p>Point for the 1/4 sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p>
<p>T40N R1W 1/4 S2 S1 1971</p>	
56.00	Telephone line, bears S. 42°08' E. and N. 42°08' W.
77.20	Track road, bears S. 30° E. and N. 30° W.
80.62	Intersect the S. bdy. of T. 41 N., R. 1 W. (Tenth Standard Parallel North).
<p>Point for the closing cor. of secs. 1 and 2.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.</p>	
<p>T41N S35 S2 S1 C C T40N R1W 1971</p>	
<p>from which</p> <p>The Standard Corner of secs. 35 and 36, T. 41 N., R. 1 W., bears East 2 lks. dist., monumented by an iron post, 3 ins. diam., projecting 16 ins. above the ground, brass cap mkd.</p>	
<p>T41N R1W S35 S36 1911</p>	
<p>The Standard Corner is located 15 lks. W. of a corner of fences extending E. and N. 20 1/2° W.</p> <p>Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, sagebrush and cacti.</p>	

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

Point for the $\frac{1}{4}$ sec. cor. of sec. 1 is on the N. bdy. at mid-point bet. the closing corner of secs. 1 and 2 and the cor. of Tps. 40 and 41 N., Rs. 1 E. and 1 W.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 5 ins. in the ground over an X chiseled in bedrock, mound of stone, 4 ft. base to top, brass cap mkd.

$\frac{1}{4}$ S 1
T40N R1W
1971

from which

The Standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 41 N., R. 1 W., bears East 1 lk. dist., monumented by an iron post, 1 in. diam., projecting 18 ins. above the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.

$\frac{1}{4}$ S36
1911

Both $\frac{1}{4}$ sec. cors. are located in a fenceline, bearing E. and W.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., hereinbefore described.

N. $0^{\circ}01'$ W., bet. secs. 34 and 35.

Over rolling land, through moderate undergrowth.

7.60 Wash, 10 lks. wide, 4 ins. deep, drains N. 50° W.

14.00 Enter pinyon pine and cedar timber, bears S. 30° E. and N. 30° W.

27.30 Wash, 8 lks. wide, 6 ins. deep, drains N. 60° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W
 $\frac{1}{4}$
S34|S35
1971

from which

A pinyon pine, 6 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ E., 31.5 lks. dist., mkd. T40N R1W $\frac{1}{4}$ S35 BT.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

A pinyon pine, 7 ins. diam., bears S. 40° W., 64.5 lks. dist., mkd. T40N R1W ¼ S34 BT.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the corner.

56.60 Track road, bears S. 70° E. and N. 70° W.

79.40 South rim of canyon, bears SE. and NW.

80.00 Point for the cor. of secs. 26, 27, 34 and 35.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W
 S27|S26
 S34|S35
 1971

from which

A pinyon pine, 8 ins. diam., bears N. 30¾° E., 24 lks. dist., mkd. T40N R1W S26 BT.

A pinyon pine, 4 ins. diam., bears S. 45½° E., 64 lks. dist., mkd. with an X at breast height and BT at the base of the tree.

A pinyon pine, 8 ins. diam., bears S. 34¾° W., 61 lks. dist., mkd. T40N R1W S34 BT.

A cedar, 5 ins. diam., bears N. 22° W., 65 lks. dist., mkd. T40N R1W S27 BT.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

The cor. is located on a NE. slope.

Land, rolling.

Soil, shallow and rocky.

Timber, moderate pinyon pine and cedar in the N. 66.00 chains.

Undergrowth, moderate sagebrush and cacti.

From the cor. of secs. 25, 26, 35 and 36.

S. 89°51' W., bet. secs. 26 and 35.

Over rolling land, through moderate timber and scattered undergrowth.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
27.60	Track road, bears S. 40° E. and N. 40° W.
40.00	Point for the ¼ sec. cor. of secs. 26 and 35.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	T40N R1W ¼ $\frac{S26}{S35}$ 1971
	from which
	A pinyon pine, 12 ins. diam., bears N. 65° E., 69.5 lks. dist., mkd. T40N R1W ¼ S26 BT.
	A pinyon pine, 9 ins. diam., bears S. 67° W., 9 lks. dist., mkd. T40N R1W¼S35 BT.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.
41.40	Wash, 20 lks. wide, 4 ins. deep, drains S. 30° W.
76.10	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
80.00	The cor. of secs. 26, 27, 34 and 35.
	Land, rolling. Soil, shallow and rocky. Timber, moderate pinyon pine and cedar. Undergrowth, scattered sagebrush.
	N. 0°01' W., bet. secs. 26 and 27.
	Over rolling land, through moderate timber and undergrowth
10.00	Enter open land, bears S. 30° E. and N. 30° W.
11.80	Wash in a small canyon, 20 lks. wide, 1½ ft. deep, drains NW.
15.50	Wash, 10 lks. wide, 8 ins. deep, drains NW.
23.90	N. rim of canyon, bears SE. and NW. Enter gently rolling land.
31.20	Track road, bears S. 60° E. and N. 60° W.
40.00	Point for the ¼ sec. cor. of secs. 26 and 27.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with a collar of stone to top, 2½ ft. base, brass cap mkd.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	<p style="text-align: center;">T40N R1W $\frac{1}{4}$ S27 S26 1971</p> <p>Raise a mound of stone 2½ ft. base, 2 ft. high, W. of the cor.</p>
60.50	Track road, bears E. and W.
71.30	Wash, 5 lks. wide, 1 ft. deep, drains S. 80° W.
80.00	Point for the cor. of secs. 22, 23, 26 and 27.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, with a mound of stone, 3 ft. base to the top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W S22 S23 S27 S26 1971</p> <p>Land, rolling to gently rolling. Soil, shallow and rocky. Timber, moderate pinyon pine and cedar in the S. 10.00 chs. Undergrowth, sagebrush and scattered cacti.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°51' W., bet. secs. 23 and 26.</p> <p>Over rolling land, through moderate undergrowth.</p>
15.60	E. rim of a canyon, bears S. 20° E. and N. 20° W.
20.10	Floor of canyon, drains N. 20° W.
26.50	W. rim of same canyon, bears S. 50° E. and N. 50° W. Enter gently rolling land.
34.10	E. rim of canyon, bears N. and S.
36.30	Wash in bottom of canyon, 10 lks. wide, 1 ft. deep, drains N.
39.00	W. rim of same canyon, bears N. and S.
39.98	Point for the ¼ sec. cor. of secs. 23 and 26.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, with a mound of stone 2½ ft. base to the top, brass cap mkd.</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

T40N R1W

 $\frac{1}{4}$ S23

S26

1971

67.10 Track road, bears S. 30° E. and N. 30° W.

79.96 The cor. of secs. 22, 23, 26 and 27.

Land, rolling to gently rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, moderate sagebrush and scattered cacti.

N. 0°01' W., bet. secs. 22 and 23.

Over rolling land, through moderate undergrowth.

30.50 Wash, in the bottom of canyon, 5 lks. wide, 6 ins. deep, drains S. 70° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.

T40N R1W

 $\frac{1}{4}$

S22|S23

1971

43.20 Track road, bears S. 70° E. and N. 70° W.

46.20 Gully, 10 lks. wide, with 5 ft. walls, drains S. 60° W.

51.50 Track road, bears N. 70° E. and S. 70° W.

80.00 Point for the cor. of secs. 14, 15, 22 and 23.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

T40N R1W

S15|S14

S22|S23

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, moderate sagebrush and scattered cacti.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°52' W., bet. secs. 14 and 23.</p> <p>Over rolling land, through moderate undergrowth.</p>
1.20	E. rim of Wildcat Canyon, bears S. 50° E. and N. 50° W.
7.90	Wash in Wildcat Canyon, 30 lks. wide, 1 ft. deep, drains N. 50° W.
15.30	W. rim of Wildcat Canyon, bears S. 50° E. and N. 50° W.
31.60	Track road, bears S. 50° E. and N. 50° W.
39.99	Point for the ¼ sec. cor. of secs. 14 and 23.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R1W ¼ $\frac{S14}{S23}$ 1971</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
47.90	Track road, in a curve, bears N. 60° E. and S. 30° W.
55.70	Small canyon, drains N. 50° W.
69.20	Wash, 10 lks. wide, 8 ins. deep, drains N. 30° W.
79.98	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.</p>
	<p>S. 89°54' W., bet. secs. 15 and 22.</p> <p>Over gently rolling land, through dense undergrowth.</p>
21.80	Track road, bears S. 20° E. and N. 20° W.
24.80	Draw, drains N., curving NW.
40.09	Point for the ¼ sec. cor. of secs. 15 and 22.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with a collar of stone, to top, 2½ ft. base, brass cap mkd.</p> <p style="text-align: center;">T40N R1W ¼ $\frac{S15}{S22}$ 1971</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p>
42.70	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° W.
69.30	Track road, bears S. 50° E. and N. 50° W., 60 lks. dist., thence W.
80.10	Track road, in a curve, bears N. 40° E., curving E. and S., 40° W., curving S.
80.18	The cor. of secs. 15, 16, 21 and 22, monumented by an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with a collar of stone, 2½ ft. base to top, brass cap mkd.
	<p>T40N R1W S16 S15 S21 S22 1954</p>
	<p>Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 0°01' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through moderate undergrowth.</p>
9.30	Wash, 10 lks. wide, 6 ins. deep, drains S. 80° W.
21.60	Small canyon, drains N. 70° W.
38.70	S. rim of Wildcat Canyon, bears E. and W.
40.00	Point for the ¼ sec. cor. of secs. 14 and 15.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in the ground, over an X chiseled in bedrock with a mound of stone, 3½ ft. base to top, brass cap mkd.</p>
	<p>T40N R1W ¼ S15 S14 1971</p>
	<p>The cor. is located on a small shelf, N. of the S. rim of Wildcat Canyon.</p>
43.50	Wash, in Wildcat Canyon, 30 lks. wide, 3 ft. deep, drains S. 70° W.
48.80	N. rim of Wildcat Canyon, bears S. 70° E. and N. 70° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone to top, brass cap mkd.</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	<p style="text-align: center;">T40N R1W $\frac{S10}{S15} \frac{S11}{S14}$ 1971</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°48' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
36.80	Track road, bears N. 20° E. and S. 20° W.
39.95	Point for the ¼ sec. cor. of secs. 11 and 14.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T40N R1W $\frac{S11}{\frac{1}{4} S14}$ 1971</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
62.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 40° W.
79.90	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.</p> <hr/> <p>West, bet. secs. 10 and 15.</p> <p>Over rolling land, through dense undergrowth.</p>
5.00	Wash, 15 lks. wide, 3 ft. deep, drains S. 50° W.
20.00	Track road, bears N. 40° E. and S. 40° W., 10 lks. dist., thence W.
28.10	Track road, bears S. 80° E. and N. 80° W.
36.00	North rim of Wildcat Canyon, bears S. 80° E. and N. 80° W.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
40.07	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, with a mound of stone, $2\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{1}{4}$ $\frac{S10}{S15}$ 1971</p> <p>The cor. is located on a steep S. slope.</p>
55.40	Wash in the bottom of Wildcat Canyon, 30 lks. wide, 3 ft. deep, drains N. 40° W.
68.00	W. rim of Wildcat Canyon, bears N. 5° W. and S. 5° E., curving S. 65° E.
80.14	<p>The cor. of secs. 9, 10, 15 and 16, monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor., brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{S 9 S10}{S16 S15}$ 1954</p> <p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. $0^\circ 01'$ W., bet. secs. 10 and 11.</p> <p>Over rolling land, through moderate undergrowth.</p>
6.40	Wash, 20 lks. wide, 1 ft. deep, drains S. 50° W.
38.90	Wash, 7 lks. wide, $1\frac{1}{2}$ ft. deep, drains S. 60° W.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 7 ins. in the ground, with a mound of stone, $3\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{1}{4}$ $\frac{S10 S11}{S16 S15}$ 1971</p>
70.40	Track road, bears S. 30° E. and N. 30° W.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.

T40N R1W
 $\frac{S\ 3}{S10} | \frac{S\ 2}{S11}$
 1971

from which

A catch pond, 2.00 chs. diam., bears N. 32° E., 30.50 chs. dist.

A catch pond, 3.00 chs. diam., bears N. 58°35' E., 28.20 chs. dist.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, moderate sagebrush and scattered cacti.

From the cor. of secs. 1, 2, 11 and 12.

S. 89°45' W., bet. secs. 2 and 11.

Over gently rolling land, through moderate undergrowth.

24.50 Wash, 7 lks. wide, 8 ins. deep, drains N. 20° W.

39.93 Point for the ¼ sec. cor. of secs. 2 and 11.

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, with a mound of stone, 3 ft. base to top, brass cap mkd.

T40N R1W
 $\frac{S\ 2}{\frac{1}{4} S11}$
 1971

49.20 Gully, 25 lks. wide, with 5 ft. walls, drains N. 30° W.

58.00 Track road, bears S. 30° E. and N. 30° W.

79.86 The cor. of secs. 2, 3, 10 and 11.

Land, gently rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, moderate sagebrush and scattered cacti.

S. 89°59' W., bet. secs. 3 and 10.

Over rolling land, through dense undergrowth.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

10.10 Track road, bears S. 60° E. and N. 60° W.

40.11 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 2 ins. in the ground over an X chiseled in bedrock, with a mound of stone, $3\frac{1}{2}$ ft. base to top, brass cap mkd.

T40N R1W

S 3

$\frac{1}{4}$ S10

1971

80.22 The cor. of secs. 3, 4, 9 and 10, monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 16 ins. above the ground in a mound of stone, $2\frac{1}{2}$ ft. base to top, brass cap mkd.

T40N R1W

S 4 | S 3

S 9 | S10

1954

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush and scattered cacti.

From the cor. of secs. 2, 3, 10 and 11.

N. 0°01' W., bet. secs. 2 and 3.

Over gently rolling land, through moderate undergrowth.

30.50 Gully, 20 lks. wide, with 6 ft. walls, drains S. 80° W.

31.00 Gully, 10 lks. wide, 3 ft. deep, drains S. 40° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, with a mound of stone, $3\frac{1}{2}$ ft. base to top, brass cap mkd.

T40N R1W

$\frac{1}{4}$

S 3 | S 2

1971

61.60 Wash, 20 lks. wide, 1 ft. deep, drains N. 50° W., curving W.

64.93 Right-of-way fence, bears S. 60° E. and N. 60° W., 30 lks. dist., thence N.

68.40 Center line of U.S. Alt Highway 89, bears S. 61°25' E. and N. 61°25' W.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

- 70.03 Right-of-way fence, bears N. 80° E., 50 lks. dist., thence South and S. 80° W., 50 lks. dist., thence N.
- 70.20 Wash, 7 lks. wide, 1 ft. deep, drains S. 80° W.
- 80.92 Intersect the S. bdy. of T. 41 N., R. 1 W., (Tenth Standard Parallel North).

Point for the closing cor. of secs. 2 and 3.

Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground, with a mound of stone, 2½ ft. base to top, brass cap mkd.

T41N
S35
S3|S2
C C
T40N R1W
1971

from which

The Standard cor. of secs. 34 and 35, T. 41 N., R. 1 W., bears West, 26 lks. dist., monumented by an iron post, 3 ins. diam., firmly set, projecting 14 ins. above the ground, brass cap mkd.

T41N R1W
S34|S35
1911

Land, gently rolling.
Soil, shallow and rocky.
Timber, none.
Undergrowth, moderate sagebrush and scattered cacti.

Point for the ¼ sec. cor. of sec. 2 is on the N. bdy. at mid-point bet. the closing cors.

Set the iron post, 24 ins. in the ground, brass cap mkd.

¼ S 2
T40N R1W
1971

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

from which

The standard ¼ sec. cor. of sec. 35, T. 41 N., R. 1 W., bears West, 12 lks. dist., monumented by an iron post, 1 in. diam., firmly set, projecting 12 ins. above the ground, and in a collar of stone, 2 ft. base to top, brass cap mkd.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

$$\frac{1}{4} S 35$$

 1911

The $\frac{1}{4}$ sec. cor. of sec. 35 is located in a fenceline bearing NE. and SW.

Point for the $\frac{1}{4}$ sec. cor. of sec. 3 is on the N. bdy. at mid-point bet. the closing cors.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.

$$\frac{1}{4} S3$$

 T40N R1W
 1971

from which

The standard $\frac{1}{4}$ sec. cor. of sec. 34, bears West, 16 lks. dist., monumented by an iron post, 1 in. diam., firmly set, projecting 13 ins. above ground, with pits 5 ft. E. and W. of the cor., brass cap mkd.

$$\frac{1}{4}$$

 S34
 1911

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., hereinbefore described.

N. $0^{\circ}02'$ W., bet. secs. 33 and 34.

Over rolling land, through dense undergrowth.

18.80 Fenceline, bears S. $76^{\circ}50'$ E. and N. $76^{\circ}50'$ W.

27.00 Track road, bears W. and E., curving South.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, with a mound of stone, $2\frac{1}{2}$ ft. base to top, brass cap mkd.

 T40N R1W

$$\frac{1}{4}$$

 S33|S34
 1971

48.00 Wash, 8 lks. wide, 1 ft. deep, drains N. 80° W.

68.00 Wash, 15 lks. wide, 1 ft. deep, drains W.

80.00 Point for the cor. of secs. 27, 28, 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS		
	<p style="text-align: center;">T40N R1W $\frac{S28}{S33} \frac{S27}{S34}$ 1971</p> <p>from which</p> <p>A pinyon pine, 9 ins. diam., bears N. 71° E., 131 lks. dist., mkd. T40N R1W S27 BT.</p> <p>A cedar, 10 ins. diam., bears N. 17° W., 49.5 lks. dist., mkd. T40N R1W S28 BT.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, scattered cedar and pinyon. Undergrowth, dense sagebrush and scattered cacti.</p>	
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°52' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through moderate timber and undergrowth.</p>	
40.01	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{1}{4} \frac{S27}{S34}$ 1971</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>	
62.20	<p>Track road, bears S. 70° E. and N. 70° W.</p>	
80.02	<p>The cor. of secs. 27, 28, 33 and 34.</p> <p>Land, gently rolling. Soil, shallow and rocky. Timber, moderate pinyon and cedar. Undergrowth, scattered to moderate sagebrush and scattered cacti.</p>	
	<p>S. 89°57' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land, through scattered timber and moderate undergrowth.</p>	
12.20	<p>Wash, 8 lks. wide, 6 ins. deep, drains S. 40° W.</p>	
40.09	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33.</p>	

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W

¼ $\frac{S28}{S33}$

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.

48.80 Wash, 10 lks. wide, with 5 ft. banks, drains N. 70° W.

60.00 Same wash, 10 lks. wide, 1 ft. deep, drains S. 70° W.

74.20 Same wash, 10 lks. wide, 1½ ft. deep, drains N. 50° W.

80.18 The cor. of secs. 28, 29, 32 and 33, monumented by an iron post, 2½ ins. diam., firmly set, projecting 18 ins. above the ground, with a mound of stone, 2 ft. base to top, brass cap mkd.

T40N R1W

$\frac{S29|S28}{S32|S33}$

1954

Land, gently rolling.

Soil, shallow and rocky.

Timber, scattered cedar and pinyon in the E. ½ mile.

Undergrowth, moderate to dense sagebrush and scattered cacti with sparse grass in major wash areas.

From the cor. of secs. 27, 28, 33 and 34.

N. 0°02' W., bet. secs. 27 and 28.

Over rolling land, through moderate timber and undergrowth.

8.60 Track road, bears S. 60° E. and N. 60° W.

20.50 Wash, 30 lks. wide, 1 ft. deep, drains N. 60° W.

40.00 Point for the ¼ sec. cor. of secs. 27 and 28.

Set an iron post, 30 ins. long, 2½ ins. diam., 19 ins. in the ground with a collar of stone, 2 ft. base to top, brass cap mkd.

T40N R1W

¼ $\frac{S28|S27}{S32|S33}$

1971

Raise a mound of stone 2½ ft. base, 2 ft. high, W. of the cor.

42.00 Wash, 15 lks. wide, 1 ft. deep, drains N. 45° W.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
55.60	Track road, bears E. and W.
62.50	Enter open land, bears S. 60° E. and N. 60° W.
73.10	Wash, 10 lks. wide, 1½ ft. deep, drains N. 50° W.
80.00	Point for the cor. of secs. 21, 22, 27 and 28.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.
	$\begin{array}{r} \text{T40N R1W} \\ \text{S21 S22} \\ \text{S28 S27} \\ 1971 \end{array}$
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
	<p>Land, rolling. Soil, shallow and rocky. Timber, patches of pinyon and cedar in the S. ¾ mile. Undergrowth, dense sagebrush and scattered cacti.</p>
	From the cor. of secs. 22, 23, 26 and 27.
	S. 89°52' W., bet. secs. 22 and 27.
	Over rolling land, through dense undergrowth.
27.30	Wash, 25 lks. wide, 8 ins. deep, drains N. 30° W.
40.03	Point for the ¼ sec. cor. of secs. 22 and 27.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.
	$\begin{array}{r} \text{T40N R1W} \\ \frac{1}{4} \frac{\text{S22}}{\text{S27}} \\ 1971 \end{array}$
59.00	Track road, bears S. 70° E. and N. 70° W.
80.06	The cor. of secs. 21, 22, 27 and 28.
	<p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>
	S. 89°59' W., bet. secs. 21 and 28.
	Over rolling land.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
4.60	Track road, bears N. 20° E., 30 lks. dist., to a fork in the road, with roads projecting N. 20° E., S. 20° W. and West.
35.10	Wash, 8 lks. wide, 2 ft. deep, drains N. 20° W.
40.12	Point for the ¼ sec. cor. of secs. 21 and 28.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.
	T40N R1W ¼ $\frac{S21}{S28}$ 1971
	from which
	A catch pond, 3.00 chs. diam., bears S. 26°10' W., 28.60 chs. dist.
50.10	Track road, bears N. 20° E. and S. 20° W.
62.20	Same track road, bears S. 60° E. and N. 60° W.
74.70	Wash, 12 lks. wide, 3 ft. deep, drains N. 10° W.
80.24	The cor. of secs. 20, 21, 28 and 29, monumented by an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with a collar of stone, 2 ft. base to the top, brass cap mkd.
	T40N R1W S20 S21 S29 S28 1954
	Land, gently rolling to rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.
	From the cor. of secs. 21, 22, 27 and 28.
	N. 0°06' W., bet. secs. 21 and 22.
	Over rolling land, through dense undergrowth.
4.90	Track road, bears N. 60° E., curving E. and S. 60° W., curving S. 30° W.
40.05	Point for the ¼ sec. cor. of secs. 21 and 22.
	Set an iron post, 30 ins. long, 2½ ins. diam., 3 ins. in the ground over an X chiseled in solid rock, mound of stone, 3½ ft. base to top, brass cap mkd.
	T40N R1W ¼ $\frac{S21 S22}{S22}$ 1971

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
56.10	Wash, 15 lks. wide, 2 ft. deep, drains S. 30° W.
80.03	Track road, bears N. 40° E., curving E. and S. 40° W., curving S.
80.10	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>
<p>From the cor. of secs. 8, 9, 16 and 17, monumented by an iron post, 2½ ins. diam., projecting 18 ins. above the ground, with a mound of stone, 2 ft. base to top, and a steel fence post, with a stock driving sign attached to it, set alongside the cor., brass cap mkd.</p>	
<p style="text-align: center;">T40N R1W S 8 S 9 S17 S16 1954</p>	
<p>N. 0°02' W., bet. secs. 8 and 9.</p>	
<p>Over gently rolling land, through dense undergrowth.</p>	
13.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 70° W., 30 lks. dist., thence NW.
40.00	<p>Point for the ¼ sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.</p>
<p style="text-align: center;">T40N R1W ¼ S 8 S 9 1971</p>	
43.20	Track road, bears N. 50° E. and S. 50° W.
76.00	Wash in bottom of Wildcat Canyon, 35 lks. wide, 8 ins. deep, drains N. 40° W., curving W.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

79.40 Wash, 10 lks. wide, 6 ins. deep, drains N. 70° W.

80.00 Point for the cor. of secs. 4, 5, 8 and 9.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, brass cap mkd.

T40N R1W
 $\frac{S\ 5}{S\ 8} | \frac{S\ 4}{S\ 9}$
 1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush and scattered cacti.

From the cor. of secs. 3, 4, 9 and 10, hereinbefore described.

S. 89° 49' W., bet. secs. 4 and 9.

Over gently rolling land, through dense undergrowth.

4.90 Wash, 10 lks. wide, 4 ins. deep, drains N. 10° W.

6.20 Track road, bears N. 40° E. and S. 40° W.

37.10 Wash, 20 lks. wide, 1½ ft. deep, drains N. 40° W.

39.91 Point for the ¼ sec. cor. of secs. 4 and 9.

Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.

T40N R1W
 $\frac{1}{4} \frac{S\ 4}{S\ 9}$
 1971

58.70 Track road, bears N. 20° E. and S. 20° W.

63.80 Track road, bears S. 30° E. and N. 30° W.

79.82 The cor. of secs. 4, 5, 8 and 9.

Land, gently rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	N. 0°02' W., bet. secs. 4 and 5.
	Over rolling land, through moderate undergrowth.
32.00	Track road, bears S. 30° E. and N. 30° W., 30 lks. dist., thence S.
34.60	Wash, 10 lks. wide, 8 ins. deep, drains N. 50° E., curving N.
37.20	Wash, 15 lks. wide, 1 ft. deep, drains N. 40° W.
40.00	Point for the ¼ sec. cor. of secs. 4 and 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	T40N R1W ¼ S 5 S 4 1971
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
80.90	Wash, 10 lks. wide, 4 ins. deep, drains S. 80° E.
81.03	Intersect the S. bdy. of T. 41 N., R. 1 W., (Tenth Standard Parallel North).
	Point for the closing cor. of secs. 4 and 5.
	Set an iron post, 30 ins. long, 2½ ins. diam., over an X chiseled in solid bedrock, in a mound of stone, 4 ft. base to top, brass cap mkd.
	T41N S33 S 5 S 4 C C T40N R1W 1971
	from which
	The Standard cor. of secs. 32 and 33, T. 41 N., R. 1 W., bears West, 38 lks. dist., monumented by an iron post, 3 ins. diam., firmly set on solid rock with a mound of stone, 3½ ft. base to top, mound of stone, 2½ ft. base, 2 ft. high, N. of the cor., brass cap mkd.
	T41N R1W S32 S33 1911
	Land, rolling.
	Soil, shallow and rocky.
	Timber, none.
	Undergrowth, moderate sagebrush and scattered cacti.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

The point for the $\frac{1}{4}$ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing cors.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, mound of stone, $3\frac{1}{2}$ ft. base to top, brass cap mkd.

$\frac{1}{4}$ S 4
T40N R1W
1971

from which

The Standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 41 N., R. 1 W., bears West, 22 lks. dist., monumented by an iron post, 1 in. diam., firmly set, projecting 20 ins. above the ground, with a mound of stone, 2 ft. base to top, mound of stone, N. of the cor., 2 ft. base, 2 ft. high, brass cap mkd.

$\frac{1}{4}$ S33
1911

From the cor. of secs. 29, 30, 31 and 32, monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 18 ins. above the ground, with a mound of stone, 2 ft. base to top, brass cap mkd.

T40N R1W
S30 | S29
S31 | S32
1954

S. $89^{\circ}51'$ W., bet. secs. 30 and 31.

Over gently rolling land, through moderate undergrowth.

18.80 Wash, 10 lks. wide, 6 ins. deep, drains N. 40° W.

29.80 Power transmission line, bears S. $27^{\circ}18'$ E. and N. $27^{\circ}18'$ W.

38.25 Track road, bears S. 30° E. and N. 30° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.

T40N R1W
 $\frac{1}{4}$ S30
S31
1971

from which

A cor. of fences, bears S. $56^{\circ}15'$ W., 2.03 lks. dist. with fences extending S. $48\frac{1}{4}^{\circ}$ E., and N. $88^{\circ}10'$ W., 4.00 chs. dist., thence irreg. W.,

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of the cor.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
65.90	Wash, 10 lks. wide, 1 ft. deep, drains N. 25° E.
78.86	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., projecting 10 ins. above the ground, mound of stone, 2 ft. base, 1 ft. high, W. of the cor., brass cap mkd.
	T40N R2W R1W S25 S30 S36 S31 1954
	The cor. is located approximately 10 lks. N. of a fence-line bearing irregularly E. and W.
	Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.
	From the cor. of secs. 29, 30, 31 and 32.
	N. 0°03' W., bet. secs. 29 and 30.
	Over rolling land, through dense undergrowth.
3.40	Track road, bears S. 10° E. and N. 10° W.
22.50	Draw, drains S. 60° W.
24.90	Ryan Road, bears S. 22°47' E. and N. 22°47' W.
37.00	Track road, bears N. 70° E. and S. 70° W.
39.44	Track road, bears E. and W.
40.00	Point for the ¼ sec. cor. of secs. 29 and 30.
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.
	T40N R1W ¼ S30 S29 1971
43.00	Abandoned Ryan Road, bears S. 54°36' E. and N. 54°36' W.
55.00	Track road, bears S. 35° E. and N. 35° W.
70.40	Track road, bears irregularly SE. and NW.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.

T40N R1W
 $\frac{S19}{S30} | \frac{S20}{S29}$
 1971

from which

A U.S. Army Corps. of Engineers survey marker, a concrete post, 6 ins. square, with U.S. imprinted on all four sides and a brass tablet on top, projecting 4 ins. above the ground, bears N. $64^{\circ}41'$ W., 13.5 lks. dist.; brass tablet mkd.; Corps. of Engineers - U.S. Army Jacob Lake Rec. Cen L.A. Dist. 1966.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush and scattered cacti.

From the cor. of secs. 20, 21, 28 and 29.

S. $89^{\circ}52'$ W., bet. secs. 20 and 29.

Over gently rolling land, through dense undergrowth.

- 11.40 Track road, bears N. and S.
 21.60 Bladed road, bears S. 45° E., curving E. and N. 45° W.
 22.20 Track road, bears S. 10° E. and N. 10° W.
 26.90 Track road, bears irregularly E. and W.
 32.30 Track road, bears E. and W.
 40.02 Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., over an X chiseled in solid rock, with a mound of stone, 4 ft. base to top, brass cap mkd.

T40N R1W
 $\frac{1}{4} \frac{S20}{S29}$
 1971

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
42.90	Track road, bears S. 80° E. and N. 80° W.
50.10	Track road, bears N. and S.
64.00	Wash, 15 lks. wide, 1 ft. deep, drains NW.
80.04	The cor. of secs. 19, 20, 29 and 30. Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.
	S. 89°49' W., bet. secs. 19 and 30. Over gently rolling land, through dense undergrowth.
10.00	Track road, bears irregularly E. and W.
21.90	Abandoned Ryan Road, bears S. 30° E. and N. 30° W.
27.40	Ryan Road, bears S. 30°47' E. and N. 30°47' W.
40.00	Point for the ¼ sec. cor. of secs. 19 and 30. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, with a mound of stone, 2½ ft. base to top, brass cap mkd. T40N R1W ¼ $\frac{S19}{S30}$ 1971
48.00	Wash, 5 lks. wide, 2 ft. deep, drains N. 35° W.
48.40	Wash, 8 lks. wide, 2½ ft. deep, drains N. 20° W.
65.40	Track road, bears N. 80° E. and S. 80° W.
71.00	Power transmission line, bears S. 27°18' E. and N. 27°18' W.
78.79	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 18 ins. above the ground, mound of stone, 2 ft. base to top, brass cap mkd. T40N R2W R1W S24 S19 S25 S30 1954 Mound of stone, 2½ ft. base, 2 ft. high, W. of the cor. Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

From the cor. of secs. 19, 20, 29 and 30.

N. 0°03' W., bet. secs. 19 and 20.

Over rolling land, through dense undergrowth.

13.00 Wash, 15 lks. wide, 1 ft. deep, drains N. 70° W.

25.00 Track road, bears S. 60° E. and N. 60° W.

25.90 Bladed road, bears S. 70° E. and N. 70° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W

$\frac{1}{4}$

S19|S20

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

80.00 Point for the cor. of secs. 17, 18, 19 and 20.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W

S18|S17

S19|S20

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush and scattered cacti.

From the cor. of secs. 16, 17, 20 and 21, monumented by an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, 2½ ft. base to top, brass cap mkd.

T40N R1W

S17|S16

S20|S21

1954

Mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

S. 89°48' W., bet. secs. 17 and 20.

Over rolling land, through dense undergrowth.

12.00 Track road, bears S. 70° E. and N. 70° W.

37.30 Wash, 10 lks. wide, 1 ft. deep, drains N. 35° W.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
40.05	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, with a mound of stone, 3 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{1}{4}$ $\frac{S17}{S20}$ 1971</p>
61.80	<p>Wash, 25 lks. wide, 2 ft. deep, drains N. 20° W.</p>
80.10	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>
<p>S. 89°53' W., bet. secs. 18 and 19.</p>	
<p>Over rolling land, through dense undergrowth.</p>	
34.00	<p>Wash, 7 lks. wide, 6 ins. deep, drains N. 10° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{1}{4}$ $\frac{S18}{S19}$ 1971</p>
43.20	<p>Wash, 7 lks. wide, 1 ft. deep, drains N. 30° E.</p>
61.30	<p>Abandoned Ryan Road, bears S. 31° E. and N. 31° W.</p>
75.00	<p>Ryan Road, bears S. 30°47' E. and N. 30°47' W.</p>
77.30	<p>Track road, bears N. 60° E. and S. 60° W.</p>
78.79	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., brass cap mkd.</p> <p style="text-align: center;">T40N R2W R1W $\frac{S13}{S24}$ $\frac{S18}{S19}$ 1954</p>
<p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>	

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

From the cor. of secs. 17, 18, 19 and 20.

N. 0°03' W., bet. secs. 17 and 18.

Over rolling land, through dense undergrowth.

23.20 Wash, 30 lks. wide, 1 ft. deep, drains N. 60° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W

$\frac{1}{4}$

S18|S17

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

47.80 Track road, bears S. 70° E. and N. 70° W.

77.50 Wash, 15 lks. wide, 1 ft. deep, drains West.

80.00 Point for the cor. of secs. 7, 8, 17 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, with a mound of stone, 4 ft. base to top, brass cap mkd.

T40N R1W

S 7|S 8

S18|S17

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush and scattered cacti.

From the cor. of secs. 8, 9, 16 and 17, previously described.

S. 89°51' W., bet. secs. 8 and 17.

Over rolling land, through dense undergrowth.

35.80 Wash, 8 lks. wide, 2 ft. deep, drains N. 60° W.

40.08 Point for the $\frac{1}{4}$ sec. cor. of sec. 8 and 17.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
	<p style="text-align: center;">T40N R1W $\frac{1}{4} \frac{S 8}{S17}$ 1971</p>
80.16	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>
4.00	<p>S. 89°55' W., bet. secs. 7 and 18.</p> <p>Over rolling land, through dense undergrowth.</p> <p>Wash, 15 lks. wide, 1 ft. deep, drains NW.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 7 and 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T40N R1W $\frac{1}{4} \frac{S 7}{S18}$ 1971</p>
55.30	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p> <p>Track road, bears S. 50° E. and N. 50° W.</p>
78.73	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor., brass cap mkd.</p>
	<p style="text-align: center;">T40N R2W R1W $\frac{S12}{S13} \frac{S 7}{S18}$ 1954</p>
	<p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

From the cor. of secs. 7, 8, 17 and 18.

N. 0°03' W., bet. secs. 7 and 8.

Over rolling land, through dense undergrowth.

25.50 Wash, 170 lks. wide, 3 ft. deep, drains S. 60° W., curving NW.

32.00 Track road, bears N. 70° E. and S. 70° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W

$\frac{1}{4}$

S 7 | S 8

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

72.70 Wash, 15 lks. wide, 1½ ft. deep, drains N. 60° W.

79.60 Wash, 15 lks. wide, 1 ft. deep, drains N. 50° W.

80.00 Point for the cor. of secs. 5, 6, 7 and 8.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W

S 6 | S 5

S 7 | S 8

1971

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush and scattered cacti.

From the cor. of secs. 4, 5, 8 and 9.

S. 89°49' W., bet. secs. 5 and 8.

Over rolling land, through dense undergrowth

2.80 Wildcat Canyon, 25 lks. wide, with 4 ft. banks, drains N. 50° W.

7.70 Wildcat Canyon, 30 lks. wide, with 4 ft. banks, drains S. 80° W.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS	
40.10	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground over an X chiseled in solid rock, with a mound of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{1}{4}$ $\frac{S 5}{S 8}$ 1971</p>
42.90	Wildcat Canyon, 25 lks. wide, 3 ft. deep, drains N. 60° W.
79.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
80.20	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, dense sagebrush and scattered cacti.</p>
	S. $89^\circ 57'$ W., bet. secs. 6 and 7.
	Over rolling land, through dense undergrowth.
0.45	Wash, 15 lks. wide, drains W. from SE.
2.20	Wash, 20 lks. wide, $1\frac{1}{2}$ ft. deep, drains N.
8.80	Draw, drains N. 30° E.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R1W $\frac{1}{4}$ $\frac{S 6}{S 7}$ 1971</p>
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of the cor.
55.10	Wash, 20 lks. wide, 8 ins. deep, drains N. 30° E.
75.20	Track road, bears S. 80° E. and N. 80° W.
78.69	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor., brass cap mkd.</p>

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

T40N
R2W R1W
S 1 | S 6
S 12 | S 7
1954

Land, rolling.
Soil, shallow and rocky.
Timber, none.
Undergrowth, dense sagebrush and scattered cacti.

From the cor. of secs. 5, 6, 7 and 8.

N. 0°03' W., bet. secs. 5 and 6.

Over rolling land, through dense undergrowth.

1.00 Wash, 20 lks. wide, 1 ft. deep, drains N. 10° W.

4.70 Wash, 10 lks. wide, 6 ins. deep, drains W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T40N R1W
 $\frac{1}{4}$
S 6 | S 5
1971

Raise a mound of stone 2½ ft. base, 2 ft. high, W. of the cor.

46.90 Wash in bottom of Wildcat Canyon, 90 lks. wide, with 4 ft. banks, drains N. 50° W.

81.18 Intersect the S. bdy. of T. 41 N., R. 1 W., (Tenth Standard Parallel North).

Point for the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T41N
S32
S 6 | S 5
C C
T40N R1W
1971

from which

The Standard cor. of secs. 31 and 32, T. 41 N., R. 1 W., bears West, 24 lks. dist., monumented by an iron post, 3 ins. diam., firmly set, projecting 13 ins. above the ground, with a wooden post, 5 ins. diam., 6 ft. long, set alongside, brass cap mkd.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

T41N R1W
S31|S32
 1911

Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the closing cor.

Land, rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, dense sagebrush and scattered cacti.

The point for the ¼ sec. cor. of sec. 5 is on the N. bdy. at mid-point bet. the closing cors.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, with a mound of stone, 2½ ft. base to top, brass cap mkd.

¼ S 5
 T40N R1W
 1971

from which

The Standard ¼ sec. cor. of sec. 32, T. 41 N., R. 1 W., bears West, 31 lks. dist., monumented by an iron post, 1 ins. diam., firmly set, projecting 12 ins. above the ground, with a collar of stone, 2 ft. base to top, and a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor., brass cap mkd.

¼ S32
 1911

Both cors. are located in an abandoned E. and W. fence-line.

The point for the ¼ sec. cor. of sec. 6 is on the N. bdy. 40.00 chs. in westing from the closing cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

¼ S 6
 T40N R1W
 1971

from which

The Standard ¼ sec. cor. of sec. 31, T. 41 N., R. 1 W., bears West, 24 lks. dist., monumented by an iron post, 1 ins. diam., firmly set, projecting 14 ins. above the ground, with a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor., brass cap mkd.

Completion Survey, Subdivisional Lines, T. 40 N., R. 1 W.

CHAINS

$\frac{1}{4}$ S31
1911

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the cor.

General Description

The elevation in Township 40 North, Range 1 West, ranges from 4,800 ft. to 5,880 ft. above sea level, being at its lowest point in section 6 and at the highest point in section 36. The land varies from gently rolling to rolling throughout the township. The drainage is generally northwesterly. The soil is sandy clay and rocky. Pinyon pine and cedar timber exist in the southern part of the township, with a small amount in sections 12 and 13. The undergrowth consists of sagebrush and cacti, with sparse grass along the major washes in the southwest quarter of the township.

U. S. Alt. Highway No. 89 enters the township at the east boundary of section 12, traverses northwesterly and leaves at the north boundary of section 3. Ryan Road enters the township at the west boundary of section 18, traverses southeasterly and leaves at the south boundary of section 32. There are numerous track roads throughout the township. Wildcat Canyon enters the township at the east boundary of section 24, drains northwesterly and leaves at the west boundary of section 6.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, , HEREBY
CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day
of June , 1971 , (I) ~~(We)~~ have dependently resurveyed a portion of
the south boundary and completed the survey of the subdivisional lines,
Township 40 North, Range 1 West,

of the Gila and Salt River Meridian, in the State of Arizona , which
are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
specific manner described in the foregoing field notes.

April 2, 1974

(Date) (Cadastral Surveyor)
Paul G. Bauer

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date APR 15 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary
and the completion survey of the subdivisional lines of Township 40 North,
Range 1 West, of the Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer,
having been critically examined and found correct, are hereby approved.

MAR 14 1975

(Date) *Roger T. Barron*
Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626