

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

of a

PORTION of the EAST BOUNDARY

and

SUBDIVISIONAL LINES

and a

SURVEY

of

SUBDIVISIONS in SECTIONS 24 and 25

TOWNSHIP 7 NORTH, RANGE 29 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer

Cadastral Surveyor

Harry K. Smith

Cadastral Surveyor

Under special instructions dated July 6, 19 72, which provided for the surveys included under Group Number 550, approved July 6, 1972, and assignment instructions dated July 6, 19 72.

Survey commenced August 10, 19 72

Survey completed August 18, 19 72

1A

BOOK 5000

INDEX DIAGRAM

Township 7 North, Range 29 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13 7
19	20	21	22	23 6	24
30	29	28	27	26 3	25
31	32	33	34	35	36

1

Subdivision, section 24, pages 8-11.
Subdivision, section 25, pages 12-15.

Township 7 North, Range 29 East
Gila and Salt River Meridian, Arizona

CHAINS

The east and north boundaries were surveyed in 1875 by C. B. Foster. The south boundary, west boundary and subdivisional lines were surveyed and the north boundary retraced in 1883 by W. R. Fitzgerald. The east boundary was resurveyed in 1925 by Benjamin J. Kinsey. The south boundary, west boundary, north boundary and subdivisional lines were resurveyed in 1936 by Roger F. Wilson. Sections 3, 4, 9 and 10 were resurveyed and subdivided in 1968 by Jerrold E. Knight.

The following field notes are those of a dependent resurvey of a portion of the east boundary and subdivisional lines, and a survey of subdivisions in sections 24 and 25, Township 7 North, Range 29 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 6, 1972.

The direction of all lines were determined by solar observation and all lines refer to the true meridian. Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes.

The geographic position of the southeast corner of section 25, as scaled from a U.S.G.S. advance sheet, NUTRIOSO 1 NW., ARIZONA, scale 1:24000, is: Latitude 33°57'55" N. and Longitude 109°13'43" W.

The mean magnetic declination was found to be 13½° East.

Dependent Resurvey of a Portion of the East Boundary
T. 7 N., R. 29 E., G&SRM., Arizona

Reestablishment of the Survey Executed by C. B. Foster, Deputy Surveyor, in 1875, the Retracement Executed by W. R. Fitzgerald, Deputy Surveyor in 1883 and the Resurvey Executed by Benjamin J. Kinsey in 1925

Beginning at the ½ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp., monumented by an iron post, 1 in. diam., projecting 18 ins. above ground, set in a collar of stone, 2 ft. base, 1 ft. high, brass cap mkd.

½
S24 | S19
1925

from which

A juniper, 48 ins. diam., bears S. 38° E., 1072 lks. dist., marked with an overgrown blaze.

Dependent Resurvey, Portion of the E. Boundary
T. 7 N., R. 29 E.

CHAINS	
	<p>A pine, 12 ins. diam., bears N. 51° W., 583 lks. dist., marked $\frac{1}{2}$ S19 BT.</p>
	<p>The cor. is located in a N-S fenceline.</p>
	<p>N. 0°32' W., bet. secs. 19 and 24.</p>
	<p>Over rolling land, desc. N. slope through scattered undergrowth and timber,</p>
<p>15.40</p>	<p>Track road, bears N. 70° E. and S. 50° W., thence over gently rolling land.</p>
<p>20.18</p>	<p>Point for the N 1/16 sec. cor. of secs. 19 and 24, at proportionate dist.</p>
	<p>Set an iron post 30 inches long, 2½ inches diam., 24 inches in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7N R29E R30E N 1/16 S24 S19 1972</p>
	<p>from which</p>
	<p>A ponderosa pine, .8 ins. diam., bears S. 14¾° E., 113 lks. dist., marked N 1/16 S19 BT.</p>
	<p>A ponderosa pine, 5 ins. diam., bears S. 8° W., 72 lks. dist., marked N 1/16 S24 BT.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the iron post.</p>
	<p>The corner is located in a N-S fenceline and near the SE. edge of Riggs Creek Reservoir (this reservoir is approx. 12 chs. in diam.)</p>
<p>38.80</p>	<p>Fence, bears S. and N., curving easterly..</p>
<p>40.36</p>	<p>The cor. of secs. 13, 18, 19 and 24, monumented by an iron post, 2 ins. diam., projecting 24 ins. above ground set in a mound of stone to top, 2 ft. base, brass cap mkd.</p>
	<p style="text-align: center;">T7N R29E R30E S13 S18 S24 S19 1925</p>
	<p>from which</p>
	<p>A ponderosa pine, 14 ins. diam., bears N. 26½° E., 234 lks. dist., marked with an overgrown blaze.</p>
	<p>A snag, 20 ins. diam., 10 ft. high, bears S. 18° E., 487 lks. dist., marked T7N R30E S19 BT.</p>

Dependent Resurvey, Portion of the E. Boundary
T. 7 N., R. 29 E.

CHAINS

The roothole of a dead and down pine, 20 ins. diam., bears S. $16\frac{1}{2}^{\circ}$ W., 56 lks. dist., marks illegible.

A stump, 6 ins. diam., 30 ins. high, bears S. $18\frac{3}{4}^{\circ}$ W., 20 lks. dist., marked with Roman numerals but not legible.

A ponderosa pine, 20 ins. diam., bears N. $84^{\circ}10'$ W., 31 lks. dist., marked T7N R29E S13 BT.

A ponderosa pine, 24 ins. diam., bears N. $19^{\circ}50'$ W., 26 lks. dist., marked with an overgrown blaze.

Land, rolling to gently rolling.

Soil, rocky clay loam.

Timber, patches of pine timber, scattered juniper and pinyon pine.

Undergrowth, scattered sagebrush, grass and cacti.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 7 N., R. 29 E., G&SRM., Arizona

Reestablishment of the Survey Executed by W. R. Fitzgerald, Deputy Surveyor in 1883 and Resurveyed by Roger F. Wilson in 1936

Beginning at the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented by an iron post, 1 in. diam., projecting 12 ins. above ground, brass cap mkd.

$\frac{1}{4}$
S26 | S25
1936

from which

A ponderosa pine, 11 ins. diam., bears N. 47° E., 21 lks. dist., marked with an overgrown blaze.

A ponderosa pine, 28 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ E., 26 lks. dist., marked with an overgrown blaze.

A ponderosa pine, 14 ins. diam., bears S. 52° W., 66 lks. dist., marked $\frac{1}{4}$ S26 BT. (Record, 54 lks.)

N. $0^{\circ}09'$ E., bet. secs. 25 and 26.

Over rolling land, through dense timber and scattered undergrowth.

13.30 Leave timber, bears NE. and SW., enter open grass land.

15.60 Track road, bears N. 40° E. and S. 40° W.

19.65 Riggs Creek, 5 lks. wide, with stream of running water 2 ins. deep, course irreg. NE.

19.84 Point for the N $\frac{1}{16}$ sec. cor. of secs. 25 and 26, at proportionate dist.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 7 N., R. 29 E.

CHAINS

Set an iron post, 30 inches long, 2½ inches diam., 12 ins. in the ground, in a mound of stone to top, 2½ ft. base, brass cap mkd.

T7N R29E
N 1/16
S26|S25
1972

from which

A willow, 6 ins. diam., bears N. 48½° E., 53½ lks. dist., marked N 1/16 S25 BT.

A ponderosa pine, 10 ins. diam., bears N. 7° W., 54 lks. dist., marked N 1/16 S26 BT.

20.63 Fence, bears N. 83°10' E. and S. 83°10' W.

25.00 Remains of an old log cabin, approx. 18 x 24 ft. in size.

34.60 Track road, bears N. 30° E. and S. 30° W.

35.30 Leave open land, bears E. and W., enter timber.

39.68 The cor. of secs. 23, 24, 25 and 26, monumented by an iron post, 2 ins. diam., projecting 12 ins. above ground, mound of stone to S., 2 ft. base, 1 ft. high, brass cap mkd.

T7N R29E
S23|S24
S26|S25
1936

from which

A ponderosa pine, 14 ins. diam., bears N. 38½° E., 107 lks. dist., marked T7N R29E S24 BT.

A ponderosa pine, 14 ins. diam., broken off 6 ft. above ground, bears S. 16½° E., 46 lks. dist., marked T7N R29E S25 BT.

A ponderosa pine, 24 ins. diam., broken off 8 ft. above ground, bears S. 9° E., 59 lks. dist., marked T7N R29E S25 BT.

A ponderosa pine, 24 ins. diam., broken off 7 ft. above ground, bears S. 71½° W., 93½ lks. dist., marked T7N R29E S26 BT.

Land, gently rolling.
Soil, rocky clay loam.
Timber, yellow pine, scattered juniper.
Undergrowth, moderate grass.

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 7 N., R. 29 E.

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 24 and 25, monumented by an iron post 1 in. diam., projecting 12 ins. above ground, in a collar of stone, 2 ft. base, 6 ins. high, brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S24</u> <u>S25</u> 1936</p> <p>N. 89°17' W., bet. secs. 24 and 25.</p> <p>Over nearly level land, through grassland and scattered pine.</p>
0.89	Fence, bears N. 2 1/2° E. and S. 2 1/2° W.
10.40	Leave open land, bears NE. and SW., enter rolling timbered land.
18.50	Leave timber, bears NE. and SW., enter meadow with tall grass.
19.70	Point for the W 1/16 sec. cor. of secs. 24 and 25, at proportionate dist.
	<p>Set an iron post 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd.</p> <p style="text-align: center;">T7N R29E <u>S24</u> W 1/16 <u>S25</u> 1972</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 58 1/4° W., 77 lks. dist., marked W 1/16 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 25 1/4° W., 112 lks. dist., marked W 1/16 S24 BT.</p>
20.46	Track road, bears N 10° E. and S. 10° W.
21.10	Riggs Creek, 5 lks. wide, with running water 1 ft. deep, course N. 20° E.
33.50	Track road, bears N. 28° E. and S. 28° W.
33.60	Leave open land, bears N. 28° E. and S. 28° W., enter timber land.
39.40	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, nearly level to rolling. Soil, clay loam. Timber, moderate pine timber with considerable open grassland. Undergrowth, moderate grass.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 7 N., R. 29 E.

CHAINS	
	N. 0°08' W., bet. secs. 23 and 24.
	Over gently rolling land, through dense timber.
20.26	Point for the S 1/16 sec. cor. of secs. 23 and 24, at proportionate dist.
	Set an iron post 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, in a collar of stone to top, 2 ft. base, brass cap mkd.
	<p style="text-align: center;">T7N R29E S 1/16 S23 S24 1972</p>
	from which
	A ponderosa pine, 10 ins. diam., bears N. 9° E., 35 1/2 lks. dist., marked S 1/16 S24 BT.
	A ponderosa pine, 5 ins. diam., bears S. 62 1/2° W., 21 lks. dist., marked S 1/16 S23 BT.
27.50	Draw, drains NE.
40.52	The 1/4 sec. cor. of secs. 23 and 24, monumented by an iron post 1 in. diam., projecting 8 ins. above ground and set in a collar of stone to top, 2 ft. base, brass cap mkd.
	<p style="text-align: center;">1/4 S23 S24 1936</p>
	from which
	A ponderosa pine, 16 ins. diam., bears N. 65° E., 77 lks. dist., marked with an overgrown blaze.
	A ponderosa pine, 12 ins. diam., bears S. 83 1/4° W., 25 lks. dist., marked with an overgrown blaze
	N. 0°02' E., beginning new measurement.
0.08	Fence, bears N. 7° E. and S. 7° W.
20.19	Point for the N 1/16 sec. cor. of secs. 23 and 24, at proportionate dist.
	Set an iron post 30 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in a collar of stone to top, 20 ins. base, brass cap mkd.
	<p style="text-align: center;">T7N R29E N 1/16 S23 S24 1972</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 7 N., R. 29 E.

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears N. 24° E., 73 lks. dist., marked N 1/16 S24 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears N. 53° W., 74 lks. dist., marked N 1/16 S23 BT.</p>
40.38	<p>The cor. of secs. 13, 14, 23 and 24, monumented by an iron post, 2 ins. diam., projecting 18 ins. above ground, and in a mound of stone to top, 2 ft. base, brass cap mkd.</p> <p style="text-align: center;">T7N R29E S14 S13 S23 S24 1936</p>
	<p>from which</p> <p>A ponderosa pine, 12 ins. diam., broken off 1 ft. above ground, bears N. 43 1/4° E., 169 lks. dist., marked T7N R29E S13 BT.</p> <p>A cedar, 8 ins. diam., bears S. 45 3/4° E., 111 lks. dist., marked T7N R29E S24 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S. 76 1/2° W., 115 lks. dist., marked T7N R29E S23 BT.</p> <p>An alligator juniper, 30 ins. diam., bears N. 42 1/2° W., 128 lks. dist., marked with an overgrown blaze.</p> <p>An alligator juniper, 10 ins. diam., bears N. 38 1/2° W., 59 lks. dist., marked T7N R29E S14 BT.</p> <p>Land, gently rolling. Soil, clay loam. Timber, ponderosa pine, scattered alligator juniper and oak. Undergrowth, scattered to moderate grass.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp.</p> <p>N. 89°05' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land, through scattered timber.</p>
4.60	<p>Riggs Creek, 20 lks. wide, with stream of running water 4 lks. wide, 1 ft. deep, course N. 42° E.</p>
23.66	<p>Fence, bears S. 2°45' E. and N. 2°45' W.</p>
36.00	<p>Leave scattered timber, bears S. 30° E. and N. 10° W., enter dense timber.</p>
39.45	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented by an iron post 1 ins. diam., projecting 10 ins. above ground, mound of stone N., 2 1/2 ft. base, 2 ft. high, brass cap mkd.</p>

Dependent Resurvey, Portion of the Subdivisional Lines,
T. 7 N., R. 29 E.

CHAINS	
	<p style="text-align: center;">1/4 $\frac{S13}{S24}$ 1936</p> <p>N. 89°09' W., beginning new measurement.</p> <p>Leave timber, bears NE. and SW., enter meadow.</p>
7.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 48° E.
13.10	Leave meadow, bears irreg. N. and S., enter timberland.
26.83	Fence, bears S. 0°10' E. and N. 0°10' W.
39.54	The cor. of secs. 13, 14, 23 and 24.
	<p>Land, gently rolling. Soil, clay loam. Timber, scattered to moderate pine. Undergrowth, moderate grass.</p>
	Survey, Subdivision, Sec. 24, T. 7 N., R. 29 E.
	<p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°10' E., along the N. and S. centerline of sec. 24.</p> <p>Over gently rolling land, through scattered timber.</p>
20.20	<p>Point for the C-S 1/16 sec. cor. of sec. 24.</p> <p>Set an iron post 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, brass cap mkd.</p>
	<p>T7N R29E C S 1/16 S24 C 1972</p>
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears S. 33 1/2° E., 58 lks. dist., marked C-S 1/16 S24 BT.</p> <p>A ponderosa pine, 5 ins. diam., bears S. 21° W., 6 lks. dist., marked C-S 1/16 S24 BT.</p>
	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the iron post.</p> <p>The cor. is located 2 lks. W. of a N-S fenceline.</p>
24.55	Fence cor., fences bear northeasterly and southerly.

Subdivision, Sec. 24, T. 7 N., R. 29 E.

CHAINS	
25.05	Track road, bears irreg. NE. and SW.; leave timber area, bears NE. and SW., enter open grassland.
29.13	Riggs Creek, 4 lks. wide, with 2 inches running water, course N. 55° E.
40.40	Point for the C ¼ sec. cor. of sec. 24 at intersection with the E. and W. centerline of sec. 24. Set an iron post 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd. <div style="text-align: center;"> T7N R29E C C ¼ S24 C 1972 </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 23 ins. diam., bears N. 44½° E., 135 lks. dist., marked C ¼ S24 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 52° E., 115 lks. dist., marked C ¼ S24 BT.</p>
42.70	Track road, bears irreg. NE. and SW.
59.20	Fence, bears S. 87°20' E. and N. 87°20' W.
60.595	Point for the C-N 1/16 sec. cor. of sec. 24. Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to top, 20 in. base, brass cap mkd. <div style="text-align: center;"> T7N R29E C N 1/16 S24 C 1972 </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 88 ¾° E., 17 lks. dist., marked CN 1/16 S24 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 52° E., 115 lks. dist., marked CN 1/16 S24 BT.</p> <p>Enter sparse pine and cedar timber.</p>
80.79	The ¼ sec. cor. of secs. 13 and 24. Land, gently rolling. Soil, clay loam. Timber, some pine and cedar, mostly in extreme south and north portions. Undergrowth, moderate grass.

Subdivision, Sec. 24, T. 7 N., R. 29 E.

CHAINS

From the $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the E. bdy. of the Tp.

N. $89^{\circ}01'$ W., along the E. and W. centerline of sec. 24.

Over rolling land, through moderate timber.

12.20 Begin desc. over steep NW. slope.

18.50 Fence, bears N. 52° E. and S. 52° W.

24.80 Track road, bears irreg. NE. and SW., leave timber, parallels road, enter grassland.

26.95 Wash, 25 lks. wide, 1 ft. deep, drains N. 50° W.

30.05 Riggs Creek, with cut banks 8 ft. high and 40 lks. wide, at top, and with running water, 4 lks. wide, 2 ins. deep, course N. 42° E.

39.95 The C $\frac{1}{4}$ sec. cor. of sec. 24.

42.80 Track road, bears irreg. NE. and SW., enter scattered pine timber.

59.765 Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 24.

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, brass cap mkd.

$$\begin{array}{c} \text{T7N R29E} \\ \text{C} \frac{\text{W } 1/16}{\text{S24}} \text{C} \\ 1972 \end{array}$$

from which

A ponderosa pine, 5 ins. diam., bears S. 61° E., 55 lks. dist., marked CW $\frac{1}{16}$ S24 BT.

A ponderosa pine, 8 ins. diam., bears S. 26° W., 88 lks. dist., marked CW $\frac{1}{16}$ S24 BT.

Raise a mound of stone, 2 ft. base, 2 ft. high, N. of the iron post.

65.30 Enter moderate stand of small ponderosa pines, bears irreg. N. and S.

79.58 The $\frac{1}{4}$ sec. cor. of secs. 23 and 24.

Land, rolling to gently rolling.

Soil, clay loam.

Timber, scattered to moderate ponderosa pine in east and west portions.

Undergrowth, moderate grass.

Subdivision, SW $\frac{1}{4}$ Section 24

From the W $\frac{1}{16}$ sec. cor. of secs. 24 and 25.

N. $0^{\circ}02'30''$ E., on the N. and S. centerline of the SW $\frac{1}{4}$ of sec. 24.

Subdivision, Sec. 24, T. 7 N., R. 29 E.

CHAINS	
	Over gently rolling land, through moderate pine timber.
4.00	Track road, bears N. 50° E. and S. 50° W.
7.60	Riggs Creek, with 20 ft. banks, 40 lks. wide, and with running water 4 lks. wide, 2½ ins. deep, course N. 55° E.
8.80	Leave timber area, bears irreg. NE. and SW., enter meadow land with scattered small pines.
20.21	Point for the SW 1/16 sec. cor. of sec. 24 at intersection with the E. and W. centerline of the SW¼ of sec. 24. Set an iron post 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone to top, 2 ft. base, brass cap mkd. T7N R29E SW 1/16+S24 1972 from which A ponderosa pine, 7 ins. diam., bears N. 88° W., 188 lks. dist., marked SW 1/16 S24 BT. A ponderosa pine, 7 ins. diam., bears N. 21½° W., 147 lks. dist., marked SW 1/16 S24 BT. Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the iron post.
22.60	Leave meadow-land, bears irreg. NE. and SW., enter moderate pine timber.
40.43	The C-W 1/16 sec. cor. of sec. 24. <hr/> From the C-S 1/16 sec. cor. of sec. 24. N. 89°06'30" W., along the E. and W. centerline of the SW¼ of sec. 24. Over gently rolling land, through moderate pine timber.
0.32	Fence, bears N. and S.
3.20	Leave timber, bears irreg. NE. and SW., enter meadow-land.
3.70	Track road, bears NE. and irreg. SW.
6.00	Riggs Creek, with 10 ft. banks, 30 lks. wide, and with running water 4 lks. wide, 2 ins. deep, course N. 15° E.
19.75	The SW 1/16 sec. cor. of sec. 24.
21.70	Leave meadow-land, bears NE. and SW., enter moderate pine timber.
39.50	The S 1/16 sec. cor. of secs. 23 and 24. <hr/>

Subdivision, Sec. 25, T. 7 N., R. 29 E.

CHAINS

Survey, Subdivision, Sec. 25, T. 7 N., R. 29 E.

From the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented by an iron post, 1 in. diam., projecting 12 ins. above ground, firmly set in a collar of stone to top, 2 ft. base, brass cap mkd.

$\frac{1}{4}$ S25
 $\frac{1}{4}$ S36
1936

from which

A pinyon pine, 10 ins. diam., bears S. 38° E., $74\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S36 BT. (Record, 88 lks.)

A pinyon pine, 14 ins. diam., bears N. 45° W., 45 lks. dist., marked $\frac{1}{4}$ S25 BT. (Record, 33 lks.)

N. $0^\circ 07' 30''$ W., along the N. and S. centerline of sec. 25.

Over steep S. slope through moderate to dense timber.

8.70 Rim, bears irreg. E. and W., thence over gently rolling mesa.

39.69 Point for the C $\frac{1}{4}$ sec. cor. of sec. 25 at intersection with the E. and W. centerline of sec. 25.

Set an iron post 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd.

T7N R29E
C $\frac{1}{4}$
+
S25
1972

from which

A ponderosa pine, 8 ins. diam., bears S. $82\frac{1}{2}^\circ$ E., 51 lks. dist., marked C $\frac{1}{4}$ S25 BT.

A ponderosa pine, 10 ins. diam., bears S. 32° W., $71\frac{1}{2}$ lks. dist., marked C $\frac{1}{4}$ S25 BT.

40.84 Wash, 10 lks. wide, 1 ft. deep, drains N. 80° E., asc. steep SE. slope.

59.575 Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 25.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd.

T7N R29E
C
N $\frac{1}{16}$ | S25
|
C
1972

Subdivision, Sec. 25, T. 7 N., R. 29 E.

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 15 ins. diam., bears N. 78° E., 52 lks. dist., marked CN 1/16 S25 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 50° W., 36 lks. dist., marked CN 1/16 S25 BT.</p>
61.00	Abandoned track road, bears N. 50° E., curving S., and S. 50° W., curving S.
61.20	Abandoned fenceline, bears S. 52½° E. and N. 52½° W.
62.50	Track road, bears N. 70° E., curving S. and S. 70° W., curving S.; enter nearly level land through scattered ponderosa pine and cedar.
79.46	<p>The ¼ sec. cor. of secs. 24 and 25.</p> <p>Land, steep to nearly level. Soil, rocky clay loam. Timber, scattered to moderate ponderosa pine, scattered cedar and alligator juniper. Undergrowth, moderate grass, scattered sagebrush.</p> <hr/> <p>From the ¼ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented by an iron post, 1 in. diam., projecting 12 ins. above ground and with mound of stone W., 2 ft. base, 18 ins. high, brass cap mkd.</p> <p style="text-align: center;">¼ S25 S30 1925</p> <p>The cor. is located 2 lks. W. of a N-S fenceline.</p> <p>N. 89°08'30" W., along the E. and W. centerline of sec. 25.</p> <p>Over gently rolling land, through scattered cedar.</p>
16.57	Abandoned fenceline, bears S. 33°40' E. and N. 33°40' W.
19.90	Spur, slopes N., desc. gently NW slope.
22.90	Enter moderate pine timber, bears irreg. N. and S.
32.90	Begin desc. over steep W. slope.
35.90	Small draw, drains N. 30° W.
39.61	The C ¼ sec. cor. of sec. 25.
40.70	Wash, 10 lks. wide, 1 ft. deep, drains NE., asc. steep SE. slope.
47.40	Top of ascent, bears NE. and SW., thence over gently rolling land.
59.355	Point for the C-W 1/16 sec. cor. of sec. 25.

Subdivision, Sec. 25, T. 7 N., R. 29 E.

CHAINS	
	<p>Set an iron post 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7N R29E C-W 1/16 S25 1972</p>
	<p>from which</p>
	<p>A ponderosa pine, 10 ins. diam., bears S. 89¼° W., 128 lks. dist., marked CW 1/16 S25 BT.</p>
	<p>A cedar, 5 ins. diam., bears N. 26¼° W., 54½ lks. dist., marked CW 1/16 S25 BT.</p>
66.80	<p>Track road, bears S. 10° W. and N. 20° E., curving E.</p>
72.20	<p>Track road, bears N. 50° E. and S. 50° W.</p>
78.90	<p>Draw, drains NE.</p>
79.10	<p>The ¼ sec. cor. of secs. 25 and 26.</p>
	<p>Land, rolling. Soil, rocky clay loam. Timber, moderate ponderosa pine, scattered cedar. Undergrowth, moderate grass.</p>
	<p style="text-align: center;">Subdivision, NW¼ Section 25</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the C-W 1/16 sec. cor. of sec. 25.</p>
	<p>North along the N. and S. centerline of the NW¼ of sec. 25.</p>
	<p>Over gently rolling grassland and through scattered ponderosa pine and cedar.</p>
12.00	<p>Track road, bears N. 23° E., curving E. and S. 25° W.</p>
15.90	<p>Track road, bears S. 80° E., curving NE. and N. 80° W.</p>
19.86	<p>Point for the NW 1/16 sec. cor. of sec. 25 at intersection with the E. and W. centerline of the NW¼ of sec. 25.</p>
	<p>Set an iron post 30 ins. long, 2½ ins. diam., 22 ins. in the ground, collar of stone to top, 1½ ft. base, brass cap mkd.</p>
	<p style="text-align: center;">T7N R29E NW 1/16 + S25 1972</p>
	<p>from which</p>
	<p>A ponderosa pine, 11 ins. diam., bears S. 52½° E., 92 lks. dist., marked NW 1/16 S25 BT.</p>

Subdivision, Sec. 25, T. 7 N., R. 29 E.

CHAINS	
	A ponderosa pine, 12 ins. diam., bears S. 83° W., 67 lks. dist., marked NW 1/16 S25 BT.
22.40	Fence, bears N. 86°45' E. and S. 86°45' W.
30.30	Rim of mesa, bears irreg. E. and W., desc. steep N. slope through dense ponderosa and scattered oak and white fir.
39.71	The W 1/16 sec. cor. of secs. 24 and 25.
From the C-N 1/16 sec. cor. of sec. 25.	
N. 89°14' W., along the E. and W. centerline of the NW ¼ of sec. 25.	
Over gently rolling land.	
4.00	Track road, bears N. 55° E. and S. 55° W.
19.76	The NW 1/16 sec. cor. of sec. 25.
32.60	Wash, 5 lks. wide, ½ ft. deep, drains N. 10° W.
33.60	Leave timber, bears irreg. N. and S.
35.40	Track road, bears N. 35° E. and S. 35° W.
39.20	Riggs Creek, 25 lks. wide, 1 ft. deep, with running water 5 lks. wide and 2 ins. deep, course N. 28° E.
39.49	The N 1/16 sec. cor. of secs. 25 and 26.
General Description	
<p>The area covered in this survey is largely mesa land. The elevation ranges from about 7900 ft. to 8300 ft. above sea level. Riggs Creek enters section 25 near the ¼ section corner of sections 25 and 26 and leaves near the northeast corner of section 24. There is a considerable amount of Ponderosa pine in the area surveyed. The primary use of the land is grazing. Several track roads traverse sections 24 and 25. Riggs Creek Reservoir, approximately 12 chains diameter is located in the northeast portion of section 24.</p> <p>There are no signs of present habitation or of mining in the area surveyed.</p>	

17

CERTIFICATE OF SURVEY

~~(X)~~(We), Paul G. Bauer and Harry K. Smith, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of July, 1972, ~~(X)~~(We) have dependently resurveyed a portion of the east boundary and subdivisional lines and surveyed subdivisions in Sections 24 and 25, Township 7 North, Range 29 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~(me)~~, (us) and under ~~(my)~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

January 12, 1973

(Date)

Paul G. Bauer

(Cadastral Surveyor)

January 12, 1973

(Date)

Harry K. Smith

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date MAY 30 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the east boundary and subdivisional lines, and the survey of subdivisions in Sections 24 and 25, Township 7 North, Range 29 East of the Gila and Salt River Meridian, Arizona, executed by Paul G. Bauer and Harry K. Smith, having been critically examined and found correct, are hereby approved.

MAR 27 1975

(Date)

Bernard W. [Signature]

(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey)