

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

1A

INDEX TO SECTION  
CORNER MONUMENTS

Tp. 28N R. 6E Mer. G&SRM., Ariz.

2 6	2 1	5	4	3	2	1
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Tp. 29N R. 5E Mer. G&SRM., Ariz.

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	4

Tp. 29N R. 6E Mer. G&SRM., Ariz.

6	5	4	3	2	1	
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	4

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

18

# INDEX TO SECTION CORNER MONUMENTS

Tp. 29N R. 1E Mer. G&SRM., Ariz.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Diagram showing corner monument locations with dots and numbers:

- Section 23: 10, 11, 9
- Section 24: 7
- Section 25: 8, 8, 6, 6
- Section 26: 8, 8, 6, 6
- Section 27: 10, 9
- Section 34: 9
- Section 35: 7
- Section 36: 6, 6
- Section 34-35 boundary: 5

Tp. \_\_\_\_\_ R. \_\_\_\_\_ Mer. \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. \_\_\_\_\_ R. \_\_\_\_\_ Mer. \_\_\_\_\_

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36



Township 28 North, Range 6 East, G&SRM., Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners in Township 28 North, Range 6 East, Township 29 North, Range 5 East, Township 29 North, Range 6 East and Township 29 North, Range 1 East, G&SRM., Arizona. The remonumentation is by agreement with the U.S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The remonumentation was executed in accordance with the Manual of Surveying Instructions, 1947, and the Special Instructions for Group 559, Arizona, dated May 29, 1973. The approval of the Special Instructions on May 29, 1973, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541 dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination was  $14\frac{1}{2}^{\circ}$  East.

---

Township 28 North, Range 6 East, G&SRM., Arizona  
The west 2 tiers of sections were surveyed in 1900 by L. Wolfly.

---

Remonumentation, Subdivision, T. 28 N.,  
R. 6 E., G&SRM., Arizona

---

The cor. of secs. 5, 6, 7 and 8, reestablished by record course and distance from the orig. bearing trees

A pinyon pine, 12 ins. diam., bears N.  $53\frac{1}{4}^{\circ}$  E.,  
67 lks. dist., mkd. T28N R6E S5 BT.

A pinyon pine, 12 ins. diam., bears S.  $36^{\circ}$  E.,  
74 lks. dist., mkd. T28N R6E S8 BT.

The root hole of a pinyon pine, 16 ins. diam., dead  
and down, bears S.  $38\frac{1}{2}^{\circ}$  W., 18 lks. dist.; the tree  
is mkd. T28N R6E S7 BT.

A pinyon pine, 8 ins. diam., bears N.  $5\frac{3}{4}^{\circ}$  W., 29  
lks. dist., mkd. T28N R6E S6 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged  
at the base and with a brass cap riveted to the top,  
18 ins. in the ground, mound of stone to top,  $3\frac{1}{2}$  ft.  
base, brass cap mkd.

T28N R6E  
S6 | S5  
S7 | S8  
1973

from which

Remonumentation, T. 28 N., R. 6 E., G&SRM., Arizona

CHAINS

A pinyon pine, 12 ins. diam., bears S. 37° W.,  
92 lks. dist., mkd. T28N R6E S7 BT.

The ¼ sec. cor. of secs. 6 and 7, monumented by a pine  
post, 18 ins. long, 2½ ins. diam., loosely set, no visi-  
ble marks, from which the orig. bearing tree

A ponderosa pine, 30 ins. diam., bears S. 18¾° E.,  
77 lks. dist., mkd. ¼ S 7 BT., visible through a  
partly overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged  
at the base and with a brass cap riveted to the top, 18  
ins. in the ground, mound of stone to top, 3 ft. base,  
brass cap mkd.

T28N R6E  
¼  $\frac{S6}{S7}$   
1973

Deposit the orig. pine post in the mound alongside the  
iron post.

The ¼ sec. cor. of secs. 5 and 6, monumented by a red  
sandstone, 24x15x8 ins., fallen over, mkd. ¼ S on N.  
face, from which the orig. bearing trees

A pinyon pine, 12 ins. diam., bears N. 44½° E.,  
34 lks. dist., mkd. ¼ S 5 BT.

A pinyon pine, 14 ins. diam., bears N. 60° W.,  
13 lks. dist., mkd. ¼ S 6 BT.

At the cor. point

Set the iron post, 30 ins. long, 2½ ins. diam., flanged  
at the base and with a brass cap riveted to the top, 12  
ins. in the ground, mound of stone to top, 3 ft. base,  
brass cap mkd.

T28N R6E  
¼  $\frac{S6}{S5}$   
1973

Deposit the orig. cor. stone in the mound alongside the  
iron post.

Township 29 North, Range 5 East, G&SRM., Arizona

The south boundary, (the 7th Standard Parallel North)  
was surveyed in 1899 by W. O. Secor.

Remonumentation, S. Bdy., T. 29 N., R. 5 E.,  
G&SRM., Arizona

## Remonumentation, T. 29 N., R. 5 E., G&amp;SRM., Arizona

## CHAINS

The standard  $\frac{1}{4}$  sec. cor. of sec. 32, monumented by a limestone, 18x12x12 ins., firmly set, mkd. SC  $\frac{1}{4}$  S on N. face, from which the orig. bearing trees

A juniper, 36 ins. diam., bears N. 75° E., 31 lks. dist., mkd. SC  $\frac{1}{4}$  S 32 BT.

A ponderosa pine, 30 ins. diam., bears N. 12° W. (Record N. 54° W.) 124 lks. dist., mkd. SC  $\frac{1}{4}$  S 32 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, collar of stone to top, 2 ft. base, brass cap mkd.

SC  
T29N R5E  
 $\frac{1}{4}$  S32.  
1973

Bury the orig. cor. stone alongside the iron post.

The standard  $\frac{1}{4}$  sec. cor. of sec. 34, monumented by a limestone, 22x9x4 ins., marks visible, but not legible, from which the orig. bearing trees

A ponderosa pine, 24 ins. diam., bears N. 50° E., 33 lks. dist., mkd. SC  $\frac{1}{4}$  S 34 BT.

A ponderosa pine, 24 ins. diam., bears N. 61° W., 75 lks. dist., marks visible, but not legible.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, collar of stone to top, 2 ft. base, brass cap mkd.

SC  
T29N R5E  
 $\frac{1}{4}$  S34  
1973

Bury the orig. cor. stone alongside the iron post.

The standard cor. of secs. 34 and 35, monumented by a limestone, 20x13x3 ins., firmly set, mkd. SC on N. face, 2 grooves on E. and 4 grooves on W. faces, from which the orig. bearing trees

A pinyon pine, 13 ins. diam., bears N. 26° E., 72 lks. dist., mkd. T29N R5E S35 SC BT.

A pinyon pine, 10 ins. diam., bears N. 45° W., 42 lks. dist., mkd. T29N R5E S34 SC BT.

At the cor. point

Remonumentation, T. 29 N., R. 5 E., G&SRM., Arizona

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd.

SC  
T29N R5E  
S34|S35  
1973.

Deposit the orig. cor. stone in the mound alongside the iron post.

The standard Tp. cor. of Tps. 29 N., Rs. 5 and 6 E., monumented by a limestone 24x18x4 ins., firmly set, mkd. SC and 6 grooves on N. face, 6 notches on E. and W. edges, from which the orig. bearing trees

A pinyon pine, 10 ins. diam., bears N. 51° E., 40 lks. dist., mkd. T29N R6E S31 SC BT.

A juniper, 18 ins. diam., bears N. 65° W., 141 lks. dist., mkd. T29N R5E S36 SC.BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 8 ins. in the ground, mound of stone to top, 2½ ft. base, brass cap mkd.

SC  
T29N  
R5E R6E  
S36|S31  
1973

Deposit the orig. cor. stone in the mound alongside the iron post.

Township 29 North, Range 6 East, G&SRM., Arizona

The south boundary (the 7th Standard Parallel North) was surveyed in 1899 by W. O. Secor.

Remonumentation, S. Bdy., T. 29 N., R. 6 E., G&SRM., Arizona

The standard ¼ sec. cor. of sec. 31, monumented by a sandstone, 19x12x8 ins., firmly set, mkd. SC ¼ S 31 on N. face, from which the remains of the orig. bearing trees

A juniper, 12 ins. diam., dead and standing, bears N. 58° E., 23 lks. dist., mkd. SC ¼ S 31 BT. (Record N. 60° 20' E., 22 lks.)

A pinyon pine, 12 ins. diam., bears N. 40° W., 26 lks. dist., mkd. SC ¼ S 31 BT. (Record N. 42° W.)

Remonumentation, T. 29 N., R. 6 E., G&SRM., Arizona

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 6 ins. in the ground, mound of stone to top, 3½ ft. base, brass cap mkd.

SC  
T29N R6E  
¼ S31  
1973

from which

A pinyon pine, 10 ins. diam., bears N. 52½° E., 38½ lks. dist., mkd. SC ¼ S 31 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

Township 29 North, Range 1 East, G&SRM., Arizona

The south boundary (the 7th Standard Parallel North) was surveyed in 1899 by W. O. Secor. The east boundary and subdivisional lines were surveyed in 1901 by F. B. Jacobs. The south 2 miles of the east boundary and the line between secs. 26 and 35 were resurveyed in 1901 by F. B. Jacobs.

Remonumentation, S. Bdy., T. 29 N., R. 1 E.,  
G&SRM., Arizona

The standard cor. of secs. 34 and 35, monumented by a limestone, 24x10x8 ins., loosely set in an old mound of stone, mkd. with 2 grooves on E. and 4 grooves on W. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 24 ins. in the ground, collar of stone to top, 3 ft. base, brass cap mkd.

T29N R1E  
S|C  
S34|S35  
1973

Bury the orig. cor. stone alongside the iron post.

The cor. is located 171 lks. E. of a bend in a fence line, with fences extending N. 80° E., and W.

Remonumentation, E. Bdy., T. 29 N., R. 1 E.,  
G&SRM., Arizona

Remonumentation, T. 29 N., R. 1 E., G&SRM., Arizona

CHAINS

The cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented by a limestone, 30x14x6 ins., firmly set, mkd. with 1 groove on S. and 5 grooves on N. faces, from which the orig. bearing trees

A juniper, 12 ins. diam., bears N.  $41\frac{1}{2}^{\circ}$  E., 88 lks. dist., mkd. T XXIXN R1E SXXX BT. (Record 91 lks.)

A juniper, 12 ins. diam., bears S.  $58^{\circ}$  E., 17 lks. dist., mkd. TXXIXN R1E SXXX 1 BT.

A juniper, 18 ins. diam., bears S.  $67\frac{1}{4}^{\circ}$  W., 62 lks. dist., mkd. TXXIXN R1E SXXXVI BT. (Record 60 lks.)

A juniper, 24 ins. diam., bears N.  $66\frac{1}{2}^{\circ}$  W., 48 lks. dist., mkd. T29N R1E S25 BT. (Record 50 lks.)

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 24 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T29N
R1E R2E
S25   S30
S36   S31
1973

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 30 on the E. bdy. of the Tp., monumented by a limestone, 24x12x3 ins., firmly set, mkd.  $\frac{1}{4}$  on W. face, from which the remains of the orig. bearing trees

A juniper stump, 12 ins. diam., bears S.  $28\frac{3}{4}^{\circ}$  E., 111 lks. dist. (Record 102 lks.)

The root hole of a pinyon pine, 16 ins. diam., dead and down, bears S.  $35\frac{1}{4}^{\circ}$  W., 103 lks. dist., with portions of scribe marks visible on the tree.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, collar of stone to top,  $2\frac{1}{2}$  ft. base, brass cap mkd.

T29N
R1E R2E
$\frac{1}{4}$
S25   S30
1973

Bury the orig. cor. stone alongside the iron post.

## Remonumentation, T. 29 N., R. 1 E., G&amp;SRM., Arizona

## CHAINS

The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented by a limestone 20x12x6 ins., firmly set, mkd. with 4 grooves on N. and 2 grooves on S. faces, (an old mound of stone, 3 ft. diam., bears W., 3 lks. dist.,) from which the orig. bearing trees

A pinyon pine, 12 ins. diam., bears N. 36° E., 180 lks. dist., partly overgrown blaze, marks visible, not legible.

A juniper, 8 ins. diam., bears S. 71½° E., 68 lks. dist., (Record 168 lks.) mkd. T XXIXN R1E SXXX BT.

A juniper, 16 ins. diam., bears S. 70° W., 132 lks. dist., mkd. TXXIXN RIE SXXV BT.

A pinyon pine, 16 ins. diam., bears N. 86° W., 125 lks. dist., mkd. TXXIXN RIE SXXIV BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 12 ins. in the ground, mound of stone to top, 3½ ft. base, brass cap mkd.

T29N  
R1E R2E  
S24 | S19  
S25 | S30  
1973

Bury the orig. cor. stone alongside the iron post.

Remonumentation, Subdivision, T. 29 N.,  
R. 1 E., G&SRM., Arizona

The ¼ sec. cor. of secs. 35 and 36, monumented by a limestone, 20x15x8 ins., firmly set, mkd. ¼ on W. face, from which the remains of the orig. bearing trees

A juniper, 10 ins. diam., bears S. 33° E., 157 lks. dist., mkd. with an overgrown blaze (Record S. 46½° E.)

A pinyon pine, 12 ins. diam., bears S. 70° W., 94 lks. dist., mkd. with an overgrown blaze (Record S. 18¾° W.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, collar of stone to top, 2 ft. base, brass cap mkd.

T29N R1E  
¼  
S35 | S36  
1973

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 29 N., R. 1 E., G&SRM., Arizona

CHAINS

The cor. of secs. 25, 26, 35 and 36, monumented by a limestone, 28x8x4 ins., firmly set, mkd. with 1 groove on E. and 1 groove on S. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 18 ins. in the ground, collar of stone to top, 2 ft. base, brass cap mkd.

T29N R1E  
 $\frac{S26}{S35} | \frac{S25}{S36}$   
 1973

Invert and partially bury the orig. cor. stone alongside the iron post.

The cor. is located 6 lks. W. of a cor. of fences bearing E. and S.

The ¼ sec. cor. of secs. 25 and 36, monumented by a limestone, 20x8x8 ins., firmly set, mkd. ¼ on S. face, from which the remains of the orig. bearing trees

A juniper, 18 ins. diam., bears N. 86° E., 65 lks. dist., marks visible, not legible, partly overgrown. (Record S. 85½° W., 71 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 16 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T29N R1E  
 $\frac{1}{4} \frac{S25}{S36}$   
 1973

Bury the orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 25 and 26, monumented by a limestone, 30x18x6 ins., mkd. ¼ on W. face, loosely set in an old mound of stone, 2½ ft. base, 1 ft. high.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 6 ins. in the ground to bedrock, mound of stone to top, 4 ft. base, brass cap mkd.

T29N R1E  
 $\frac{1}{4}$   
 $\frac{S26}{S25}$   
 1973

Deposit the orig. cor. stone alongside the iron post.

## Remonumentation, T. 29.N., R. 1 E., G&amp;SRM., Arizona

## CHAINS

The cor. of secs. 23, 24, 25 and 26, monumented by a limestone, 30x10x8 ins., firmly set, mkd. with 2 grooves on E. and 1 legible groove on S. faces, from which the orig. bearing trees

A juniper, 12 ins. diam., bears N. 22½° E., 202 lks. dist., mkd. T29N R1E S23 BT. (should have been mkd. S 24.)

A pinyon pine, 16 ins. diam., bears S. 38½° W., 242 lks. dist., mkd. TXXIXN RIE SXXVI BT.

A pinyon pine, 16 ins. diam., bears N. 73½° W., 81 lks. dist., mkd. TXXIXN RIE S23 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 16 ins. in the ground, mound of stone to top, 3½ ft. base, brass cap mkd.

T29N R1E
S23   S24
S26   S25
1973

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 34 and 35, monumented by a limestone, 20x12x3 ins., firmly set, mkd. ¼ S. on W. face, with an old mound of stone, 2 ft. base, W. of the cor.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T29N R1E
¼
S34   S35
1973

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 26, 27, 34 and 35, monumented by a limestone, 20x7x5 ins., firmly set, mkd. with 1 groove on S. and 2 grooves on E. faces, from which the remains of the orig. bearing trees

A juniper, 18 ins. diam., bears S. 63° E., 234 lks. dist., marks visible, not legible, partially overgrown.

A juniper stump, burned out face, bears S. 37½° W., 206 lks. dist. (Record S. 39½° W., 204 lks.)

A juniper, 24 ins. diam., bears N. 33° W., 125 lks. dist., mkd. TXXIXN RIE SXXVII BT.

Remonumentation, T. 29. N., R. 1 E., G&SRM., Arizona

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 18 ins. in the ground, collar of stone, 1½ ft. base, 6 ins. high, brass cap mkd.

T29N R1E  
 S27|S26  
 S34|S35  
 1973

from which

A juniper, 8 ins. diam., bears S. 67½° W., 68 lks. dist., mkd. T29N R1E S34 BT.

Bury the orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 26 and 27, monumented by a limestone, 16x16x4 ins., (loosely set in an old mound of stone, 2½ ft. base,) mkd. ¼ on W. face, from which the remains of the orig. bearing trees

A juniper, 18 ins. diam., bears S. 64½° E., 35 lks. dist., no marks visible.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 4 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T29N R1E  
 ¼  
 S27|S26  
 1973

from which

A juniper, 8 ins. diam., bears S. 52½° W., 207 lks. dist., mkd. ¼ S 27 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The cor. of secs. 22, 23, 26 and 27, monumented by a limestone, 24x18x12 ins., firmly set, mkd. with 2 grooves on E. and S. faces, (an old mound of stone, 2½ ft. base, bears W., 6 lks. dist.) from which the orig. bearing tree

A juniper, 18 ins. diam., bears N. 45° W., 212 lks. dist., mkd. TXXIXN RIE SXXII BT. (Record N. ¾° W.)

At the cor. point

Remonumentation, T. 29 N., R. 1 E., G&SRM., Arizona

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 14 ins. in the ground, mound of stone to top, 2½ ft. base, brass cap mkd.

T29N R1E  
 $\frac{S22}{S27} | \frac{S23}{S26}$   
 1973

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 23 and 26, monumented by a sandstone, 20x10x8 ins., firmly set, mkd. ¼ on N. face (an old mound of stone, 2½ ft. base, bears N., 4 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, brass cap mkd.

T29N R1E  
 $\frac{1}{4} \frac{S23}{S26}$   
 1973

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.

The cor. is located 119 lks. W. of an old road bearing SE and NW.

Remonumentation, T. 29 N., R. 1 E., G&SRM., Arizona

CHAINS



CERTIFICATE OF SURVEY

(I) ~~We~~, Paul G. Bauer, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29 day

of May, 1973, (I) ~~We~~ have remonumented a portion of the cadastral survey corners in Township 28 North, Range 6 East and Township 29 North, Ranges 5, 6 and 1 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 16, 1973

(Date)

*Paul G. Bauer*

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date AUG 27 1973

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 28 North, Range 6 East and Township 29 North, Ranges 5, 6 and 1 East, all of the Gila and Salt River Meridian, Arizona.

executed by Paul G. Bauer, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

NOV 26 1975

(Date)

*J. J. [Signature]*

Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626

Form 9180-6  
(April 1974)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 28 North, Range 6 East

Township 29 North, Range 5 East

Township 29 North, Range 6 East

Township 29 North, Range 1 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer

Cadastral Surveyor

Under special instructions dated May 29, 19 73, approved May 29, 1973,

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 559, and assignment instructions dated May 29, 19 73.

Survey commenced June 4, 19 73

Survey completed June 14, 19 73

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36