

.1.A

Dependent Resurvey of T. 14 N., R. 2 W.,  
Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes describe the dependent resurvey of the boundaries of Section 9, the survey of subdivisions of Section 9, and the survey of Lot No. 2 of Section 9 of Township 14 North, Range 2 West, Gila and Salt River Meridian, Arizona.

The boundaries of the township and a portion of the subdivisional lines, including Section 9, were surveyed by Solomon W. Foster, Deputy Surveyor, in 1871.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 578, Arizona, dated August 27, 1975.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian.

The geographic position of the southeast corner of Section 9, as scaled from the U.S. Geological Survey quadrangle map Prescott, Arizona, is as follows:

Latitude 34°36.0' N.      Longitude 112°27.8' W.

The mean magnetic declination is 15°00' E.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 2 W., Gila and Salt River Meridian, Arizona (Restoring the 1871 survey by Solomon W. Foster)

Beginning at the cor. of secs. 9, 10, 15 and 16, monumented with a re-bar, 1 in. diam., projecting 1 in. above ground. This position is harmoniously related to identified original cor., has been used by local surveyors and is accepted as the best available evidence of the original cor. position, not remonumented.

Cor. is located 10 lks. E of a power line, bears N and S and 6.20 chs. N of Willow Creek, 100 lks. wide, with 4 ft. banks, drains S. 70° E.

From this point the  $\frac{1}{4}$  sec. cor. of secs. 15 and 16, bears S. 0°14' E., 40.01 chs. dist., monumented with a re-bar,  $\frac{3}{4}$  in. diam., projecting 2 ins. above ground. This position was pointed out by a knowledgeable private surveyor in the Prescott, Arizona area.

N. 0°16' W., bet. secs. 9 and 10.

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS	
	<p>Over nearly level open pasture land.</p> <p>Along the east side of a fence and along a power line, both bear N and S.</p>
10.05	Point for the S-S 1/64 sec. cor. of secs. 9 and 10, not monumented.
15.075	<p>Point for the N-S-S 1/256 sec. cor. of secs. 9 and 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R2W N-S-S 1/256 S 9   S10 1975</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p>
20.10	<p>Point for the S 1/16 sec. cor. of secs. 9 and 10, identical with Cor. No. 4, Lot 2 of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R2W S 1/16 Cor. 4 <u>Lot 2</u>   S10 S 9   1975</p> <p>from which</p> <p>The SE cor. of a concrete block barn, 60 x 35 ft., bears N. 50°20' W., 147 lks. dist.; long side bears N. 82° E. and S. 82° W.</p> <p>The SE cor. of a trailer house, 24 x 8 ft., bears N. 54°45' W., 110 lks. dist.; long side bears S. 2° E. and N. 2° W.</p> <p>The SE cor. of a metal building, 33 x 22 ft., bears N. 31°14' W., 248 lks. dist.; long side bears East and West.</p> <p>A gas pump, bears N. 12°06' W., 71 lks. dist.</p>
20.70	Fence line, bears E and W, 6 lks. dist. to fence cor.; fences extend N, E and S.
24.40	Point for Cor. No. 1, Lot 2 of sec. 9.

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 14 N., R. 2 W., G&SRM, Arizona

## CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T14N R2W

Cor. 1	S10
Lot 2	
S 9	
	1975

from which

A fence cor., bears S. 55° W., 9 lks. dist.;  
fences extend S and N. 55° W., 91 lks. dist.  
to a fence projecting N.

40.20 The ¼ sec. cor. of secs. 9 and 10, monumented with a re-bar, 20 ins. long, 1 in. diam., projecting 2 ins. above ground. This position is harmoniously related to identified original cors., has been used by local surveyors and is accepted as the best available evidence of the original cor. position.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T14N R2W

S 9	S10
	1975

from which

An alligator juniper, 24 ins. diam., bears  
East, 147.5 lks. dist., mkd. ¼ S10 BT.

An alligator juniper, 9 ins. diam., bears  
S. 31° W., 277 lks. dist., mkd. ¼ S9 BT.

A concrete monument, 1 ft. square, projecting  
6 ins. above ground, bears N. 9°57' W.,  
421 lks. dist., mkd. USMR. A thorough investi-  
gation of all available records failed to  
disclose the origin of this monument.

Raise a mound of stone, 2 ft. base, 6 ins. high, W of the  
cor.

Reset the re-bar alongside the iron post.

Cor. is under a power line, bears N and S.

N. 0°14' E., beginning new measurement.

Over rolling land, through medium undergrowth and scat-  
tering timber.

Along a power line, bearing N and S.

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS	
4.20	Fence, bears E and W, 94 lks. dist., thence S.
12.80	Bladed access road, bears N. 13° E. and S. 13° W.
18.20	Power line, bears SE and NW.
19.30	Bladed access road, bears SE and NW.
20.60	Power line, bears S. 40° E. and N. 40° W.
39.76	Bladed access road, bears NW and SE, curving southerly.
39.86	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a rebar, 1 in. diam., buried 3 ins. under ground. This position is harmoniously related to identified original cors., has been used by local surveyors and is accepted as the best available evidence of the original cor. position.</p> <p>The corner point is in the middle of a wash, 20 lks. wide, 2 feet deep, draining N. 80° E., and impractical to remonument. From the cor. position</p> <p style="padding-left: 40px;">A pinyon, 15 ins. diam., bears N. 58°15' E., 158 lks. dist., mkd. T14N R2W S3 BT.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45° W., 60.6 lks. dist., with brass cap mkd. T14N R2W S9 RM 40 ft. 1975, and an arrow pointing to the cor.</p> <p>Land, S½ nearly level to gently rolling; N½, rolling. Soil, clay loam and slightly rocky. Timber, scattering juniper, pinyon pine and ash. Undergrowth, oak and cacti.</p>
	From the cor. of secs. 9, 10, 15 and 16.
	N. 89°51' W., bet. secs. 9 and 16.
	Over nearly level land, through scattering timber.
.10	Power line, bears N and S.
.12	Fence, bears N and S.
.30	Graded gravel road, bears N and S.
.55	Fence, bears N and S.
10.10	Point for the E-E 1/64 sec. cor. of secs. 9 and 16, not monumented.
20.20	Point for the E 1/16 sec. cor. of secs. 9 and 16, not monumented.
39.84	Fence, bears N and S.

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS	
40.40	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 16, monumented with a rebar, <math>\frac{3}{8}</math> in. diam., projecting 1 in. above ground. This position is harmoniously related to identified original cors., has been used by private surveyors and is accepted as the best available evidence of the original cor. position, not remonumented.</p>
	<p>S. <math>89^{\circ}39'</math> W., beginning new measurement.</p>
1.50	<p>Underground gas line, bears S. <math>17^{\circ}40'</math> E. and N. <math>17^{\circ}40'</math> W.</p>
20.02	<p>Point for the W <math>\frac{1}{16}</math> sec. cor. of secs. 9 and 16, is occupied by a steel, hollow fence post, <math>3\frac{1}{2}</math> ins. diam., <math>4\frac{1}{2}</math> ft. above ground, at a fence cor.; fences extend N and S. <math>8^{\circ}</math> E. This position is impractical to monument. From this point</p>
	<p>An iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 20 ins. in the ground, for a reference monument, bears N. <math>89^{\circ}45'</math> W., 154.1 lks. dist., with brass cap mkd. T14N R2W W <math>\frac{1}{16}</math> S9 RM 101.8 ft. 1975, and an arrow pointing to the cor.</p>
	<p>An iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., set 22 ins. in the ground, for a reference monument, bears N. <math>4^{\circ}07'</math> W., 34.7 lks. dist., with brass cap mkd. T14N R2W W <math>\frac{1}{16}</math> S9 RM 23 ft. 1975, and an arrow pointing to the cor.</p>
21.58	<p>Fence cor.; fences extend S and S. <math>89^{\circ}39'</math> W., thence along fence.</p>
40.04	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a concrete monument, 1 ft. square, mkd. USMR. A steel fence post is set in the middle of the monument and fences extend northerly, S and N. <math>89^{\circ}39'</math> E. This position is harmoniously related to identified original cors., has been used by local surveyors, and is accepted as the best available evidence of the original cor. position. This position is impractical to remonument. From this position</p>
	<p>A granite boulder, 17 x 12 x 12 ins. above ground, bears N. <math>40^{\circ}</math> E., 2.5 lks. dist., mkd. W.C. U.S.M.R. A thorough investigation of all available records failed to disclose the origin of this mkd. stone.</p>
	<p>An oak, 4 ins. diam., bears N. <math>69^{\circ}</math> E., 124 lks. dist., mkd. with an X at breast height and BT at the base.</p>
	<p>A granite boulder, 11 x 4 x 4 ft. above ground, bears N. <math>21^{\circ}</math> W., 20 lks. dist., mkd. X BO.</p>
	<p>Land, nearly level to gently rolling. Soil, clay loam and slightly rocky. Timber, juniper, pinyon pine, ash and oak. Undergrowth, oak brush and cacti with manzanita in the west 20 chs.</p>

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS		
	<p>N. 1°06' E., bet. secs. 8 and 9.</p>	
	<p>Over rolling land, through scattering timber and dense undergrowth.</p>	
	<p>Along the E side of an irregular N-S fence.</p>	
19.97	<p>Point for the S 1/16 sec. cor. of secs. 8 and 9, not monumented.</p>	
20.60	<p>Fence, bears East and West, 4 lks. dist., to a fence cor.; fences extend N, S and E.</p>	
39.94	<p>The original 1/4 sec. cor. of secs. 8 and 9, monumented with a granite stone, 18 x 14 x 15 ins., firmly set, projecting 12 ins. above ground, mkd. 1/4 on the W face.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.</p>	
	<p>T14N R2W 1/4 S 8   S 9 1975</p>	
	<p>from which</p>	
	<p>A granite stone, 12 x 18 x 3 ins. above ground, mkd. USX on top, bears S. 30°28' W., 82 lks. dist. A thorough investigation of all available records failed to disclose the origin of this mkd. stone.</p>	
	<p>Deposit the original cor. stone in the mound alongside the iron post.</p>	
	<p>Cor. is located on top of a ridge, bearing E and W, 42 lks. E of a N-S fence.</p>	
	<p>N. 0°03' W., beginning new measurement.</p>	
39.45	<p>Power line, bears E and W.</p>	
40.20	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a volcanic stone, 15 x 12 x 10 ins. buried 2 ins. underground, mkd. with 4 notches on the E and 5 notches on the S edges, from which the remains of the original bearing tree</p>	
	<p>A cedar stump, 34 ins. diam., projecting 2 ft. above ground, bears N. 25°30' W., 137 lks. dist., mkd. with a blaze that was made when the tree was 20 ins. diam. (Record bearing and dist. N. 40° W., 136 lks. dist.)</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS		
	<p style="text-align: center;">T14N R2W S 5   S 4 S 8   S 9 1975</p> <p>from which</p> <p style="padding-left: 40px;">A granite boulder, 2 x 1½ x 1 ft. high above ground, bears N. 58°06' E., 159 lks. dist., mkd. X BO on the SW face.</p> <p style="padding-left: 40px;">A granite boulder, 4 x 3½ x 1½ ft. high above ground, bears S. 10°30' E., 169 lks. dist., mkd. X BO on the NW face.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is at a fence cor.; fences extend northerly, westerly and southerly.</p> <p>Land, rolling. Soil, clay loam and rocky. Timber, juniper, pinyon pine and oak. Undergrowth, oak brush, manzanita and cacti.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°57' W., bet. secs. 4 and 9.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p>	
.05	Bladed access road, bears SE and NW.	
.31	Power line, bears N and S.	
23.00	Power line, bears SE and NW.	
39.82	Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T14N R2W ¼ S 4 S 9 1975</p>	
	Raise a mound of stone, 3½ ft. base, 1½ ft. high, N of the cor.	
51.00	Bladed access road, bears NE and SW, curving westerly along power line.	
65.90	Underground gas line, bears S. 17°40' E. and N. 17°40' W.	
79.64	The cor. of secs. 4, 5, 8 and 9.	

Dependent Resurvey of Portion of Subdivisional Lines,  
T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS	
	<p>Land, rolling. Soil, clay loam and rocky. Timber, juniper, pinyon pine and oak Undergrowth, oak brush, manzanita and cacti.</p> <hr/> <p style="text-align: center;">Subdivision of Sec. 9, T. 14 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 16. N. <math>0^{\circ}23'</math> E., on the N and S centerline of sec. 9. Over gently rolling land, through scattering timber and undergrowth.</p>
19.945	<p>Point for the center S <math>\frac{1}{16}</math> sec. cor. of sec. 9. Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground and in a collar of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R2W C S <math>\frac{1}{16}</math>   S 9 C 1975</p> <p>from which</p> <p style="text-align: center;">An alligator juniper, 24 ins. diam., bears N. <math>48^{\circ}30'</math> W., 316 lks. dist., mkd. C S <math>\frac{1}{16}</math> S9 BT.</p>
23.00	<p>Fence, bears W and E, 27 lks. dist., thence S; enter rolling land, bears generally E and W.</p>
39.89	<p>Point for the center <math>\frac{1}{4}</math> sec. cor. of sec. 9, at intersection with the E and W centerline of sec. 9. Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R2W C <math>\frac{1}{4}</math> S9 1975</p> <p>from which</p> <p style="text-align: center;">A pinyon pine, 6 ins. diam., bears N. <math>19^{\circ}45'</math> E., 140 lks. dist., mkd. C <math>\frac{1}{4}</math> S9 BT.</p> <p style="text-align: center;">An alligator juniper, 8 ins. diam., bears S. <math>2^{\circ}</math> E., 133 lks. dist., mkd. C <math>\frac{1}{4}</math> S9 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
79.17	<p>Power line, bears E and W.</p>
79.92	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 4 and 9.</p>

## Subdivision of Sec. 9, T. 14 N., R. 2 W., G&amp;SRM, Arizona

## CHAINS

From the  $\frac{1}{4}$  sec. cor. of secs. 9 and 10.

S.  $89^{\circ}43'$  W., on the E and W centerline of sec. 9.

Over rolling land, through scattering timber and medium to dense undergrowth.

- .92 Fence, bears N and S.
- 2.10 Bladed access road, bears irregularly N and S.
- 19.965 Point for the center E  $1/16$  sec. cor. of sec. 9; not monumented.
- 39.93 The center  $\frac{1}{4}$  sec. cor. of sec. 9.
- 54.40 Underground gas line, bears S.  $17^{\circ}40'$  E. and N.  $17^{\circ}40'$  W.
- 59.695 Point for the center W  $1/16$  sec. cor. of sec. 9; not monumented.
- 79.46 The  $\frac{1}{4}$  sec. cor. of secs. 8 and 9.

SE $\frac{1}{4}$ , Section 9

From the point for the E  $1/16$  sec. cor. of secs. 9 and 16.

N.  $0^{\circ}03'$  E., on the N and S centerline of the SE $\frac{1}{4}$  of sec. 9.

Over nearly level open pasture.

- 1.70 Fence, bears S.  $75^{\circ}$  E. and N.  $75^{\circ}$  W.
- 10.01 Point for the center S-SE  $1/64$  sec. cor. of sec. 9; not monumented.
- 20.02 Point for the SE  $1/16$  sec. cor. of sec. 9, at intersection with the E and W centerline of the SE $\frac{1}{4}$  of sec. 9.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.
- T14N R2W  
SE  $1/16$  S9  
1975
- Raise a mound of stone,  $2\frac{1}{2}$  ft. base, 1 ft. high, W of the cor.
- 23.30 Fence, bears N.  $86^{\circ}43'$  E. and S.  $86^{\circ}43'$  W.
- 40.05 The point for the center E  $1/16$  sec. cor. of sec. 9.

From the S  $1/16$  sec. cor. of secs. 9 and 10.

S.  $89^{\circ}56'$  W., on the E and W centerline of the SE $\frac{1}{4}$  of sec. 9.

Subdivision of Sec. 9, T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS	
	Over open pasture.
.04	Power line, bears N and S.
.06	Fence, bears N and S.
.25	N end of a graded gravel road, bears S and N, about 2.00 chs. dist., where it becomes a bladed access road, projecting northerly.
2.30	Enter corrals, bear N and S.
8.82	Point for Cor. No. 3, Lot 2 of sec. 9, is in a fence, bearing N and S, hereinafter described.
10.045	Point for the center E-SE 1/64 sec. cor. of sec. 9; not monumented.
20.09	The SE 1/16 sec. cor. of sec. 9.
39.37	Fence, bears N and S.
40.17	The center S 1/16 sec. cor. of sec. 9.
	From the point for the E-E 1/64 sec. cor. of secs. 9 and 16.
	N. 0°08'30" W., on the N and S centerline of the SE $\frac{1}{4}$ of the SE $\frac{1}{4}$ of sec. 9.
	Over nearly level to gently rolling pasture, through corrals.
.81	Fence, bears E and W.
4.60	Fence, bears E and W.
7.80	Fence, bears E and W.
8.40	Track road, bears E and W.
8.70	Power line and fence, bear E and W.
10.03	Point for the SE-SE 1/64 sec. cor. of sec. 9, at intersection with the E and W centerline of the SE $\frac{1}{4}$ of the SE $\frac{1}{4}$ of sec. 9; not monumented.
10.50	Fence, bears E and W.
12.80	Fence, bears E and W.
13.90	Private driveway, bears SE and NW, approximately 3.00 chs. dist. to a house.
15.045	Point for the center N-SE-SE 1/256 sec. cor. of sec. 9.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 27 ins. in the ground, with brass cap mkd.
	T14N R2W S9 C-N-SE-SE 1/256 1975

Subdivision of Sec. 9, T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS	
18.90	Fence, bears E and W.
20.06	The point for the center E-SE 1/64 sec. cor. of sec. 9.
	<hr/> From the point for the S-S 1/64 sec. cor. of secs. 9 and 10.
	N. 89°55' W., on the E and W centerline of the SE½ of the SE½ of sec. 9.
	Over nearly level open pasture, through corrals.
.10	Power line and fence, bear N and S.
.30	Graded gravel road, bears N and S.
.60	Fence, bears N and S.
8.40	Fence, bears N and S.
8.50	Private drive, bears N and S.
8.70	Fence, bears N and S.
10.07	The point for the SE-SE 1/64 sec. cor. of sec. 9.
14.00	Fence, bears N and S.
18.60	Fence, bears N and S.
20.15	The point for the center S-SE 1/64 sec. cor. of sec. 9.
	<hr/> SW½, Section 9
	<hr/> From the W 1/16 sec. cor. of secs. 9 and 16.
	N. 0°44' E., on the N and S centerline of the SW½ of sec. 9.
	Over nearly level to gently rolling open land.
	Along a N and S fence.
19.955	Point for the SW 1/16 sec. cor. of sec. 9, at intersection with the E and W centerline of the SW½ of sec. 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, and in a mound of stone, 1½ ft. base to top, with brass cap mkd.
	T14N R2W SW 1/16 S9 1975
	from which
	A concrete monument, 1 ft. square, projecting 8 ins. above ground, bears N. 17°15' W., 112 lks. dist., mkd. USMR. A thorough investigation of all available records failed to disclose the origin of this monument.

Subdivision of Sec. 9, T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS					
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.				
21.60	Fence, bears E and W, 42 lks. dist., to a fence cor.; fences extend E, southerly and W.				
39.91	The point for the center W 1/16 sec. cor. of sec. 9.				
	_____				
	From the center S 1/16 sec. cor. of sec. 9.				
	S. 89°41' W., on the E and W centerline of the SW¼ of sec. 9.				
	Over nearly level to gently rolling open pasture.				
7.95	Underground gas line, bears S. 17°40' E. and N. 17°40' W.				
19.895	The SW 1/16 sec. cor. of sec. 9.				
19.93	Fence, bears N and S.				
39.75	Fence, bears N and S.				
39.785	The point for the S 1/16 sec. cor. of secs. 8 and 9.				
<hr/> <p>Metes and Bounds Survey, Lot 2, Sec. 9, T. 14 N., R. 2 W., Gila and Salt River Meridian, Arizona</p> <hr/>					
	From Cor. No. 1 of Lot 2, located on the sec. line bet. secs. 9 and 10, heretofore described.				
	S. 86°43' W., on line 1-2, Lot 2.				
.03	Power line, bears N and S.				
.15	Fence, bears S. 55° E. and N. 55° W.				
.50	Fence cor.; fences extend S and S. 86°43' W., thence a-long fence.				
2.20	Bladed access road, bears N and S.				
5.20	Fence, extends S.				
8.83	Point for Cor. No. 2, Lot 2, sec. 9.				
	Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.				
	<p>T14N R2W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 9</td> <td style="padding-left: 5px;">Cor. 2</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">Lot 2</td> </tr> </table> <p>1975</p>	S 9	Cor. 2		Lot 2
S 9	Cor. 2				
	Lot 2				
	Cor. is located at the N edge of a fence cor.; fences extend E, S and W.				
	_____				

Metes and Bounds Survey, Lot 2, Sec. 9  
T. 14 N., R. 2 W., G&SRM, Arizona

CHAINS	
	<p>S. 0°17' E., on line 2-3, Lot 2, sec. 9.</p>
	<p>Along a N and S fence.</p>
3.81	<p>Point for Cor. No. 3, Lot 2, sec. 9, at intersection with the E and W centerline of the SE<math>\frac{1}{4}</math> of sec. 9.</p>
	<p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R2W</p>
	<p style="text-align: center;">S 9   Cor. 3</p>
	<p style="text-align: center;">  Lot 2</p>
	<p style="text-align: center;">1975</p>
	<p>Cor. is located in a N and S fence.</p>
	<p>N. 89°56' E., on line 3-4, Lot 2, sec. 9, identical with the E and W centerline of the SE<math>\frac{1}{4}</math> of sec. 9; topography is as described on the E and W centerline of the SE<math>\frac{1}{4}</math> of sec. 9.</p>
8.82	<p>Cor. No. 4, Lot 2, sec. 9, identical with the S 1/16 sec. cor. of secs. 9 and 10; heretofore described.</p>
	<p>N. 0°16' W., on line 4-1, Lot 2, sec. 9, identical with the sec. line bet. secs. 9 and 10.</p>
4.30	<p>Cor. No. 1, Lot 2, sec. 9, and place of beginning.</p>
<b>GENERAL DESCRIPTION</b>	
<p>The land encompassed in this survey is located about 4.5 miles north of Prescott, Arizona. The south <math>\frac{1}{2}</math> of section 9 is nearly level to gently rolling land and the north <math>\frac{1}{2}</math> is rolling. Elevation ranges from 5,200 feet to 5,400 feet above sea level. The drainage in the north <math>\frac{1}{2}</math> is northeasterly and the south <math>\frac{1}{2}</math> drains southeasterly into Willow Creek. The soil varies from clay loam in the southern portion to clay loam and rocky in the northern portion of the survey. There are scattering stands of timber, including juniper, pinyon pine and oak in the north and west <math>\frac{1}{2}</math> of section 9, with scattering stands of ash trees in the south <math>\frac{1}{2}</math>. The undergrowth consists of young timber, oak brush, manzanita and cacti. Most of the south <math>\frac{1}{2}</math> is open grass land.</p>	
<p>There are several houses, including a trailer park, located in the SE<math>\frac{1}{4}</math> of section 9. A graded gravel road leading to these residences enters section 9 near the southeast corner of the section.</p>	
<p>An average number of readings throughout section 9 gives a mean magnetic declination of 15° E., with no noticeable difference due to local attraction.</p>	



CERTIFICATE OF SURVEY

(I) ~~we~~ Harry K. Smith, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 27th day of August, 1975, (I) ~~we~~ have dependently resurveyed the boundaries of section 9, subdivided section 9 and surveyed Lot 2 of section 9, Township 14 North, Range 2 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~we~~ and under (my) ~~our~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 6, 1976  
(Date)

*Harry K. Smith*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date APR 12 1976

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the dependent resurvey of the boundaries of section 9, the survey of subdivisions and survey of Lot 2 of section 9, Township 14 North, Range 2 West, Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

SEP 16 1976  
(Date)

*[Signature]*  
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626

Form 9180-6  
(April 1974)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
B. L. M. AZ STATE OFFICE  
OCT 6 1976  
10:00 A.M.  
PHOENIX, ARIZONA

FIELD NOTES

of the  
Dependent Resurvey of the Boundaries,  
the  
Survey of Subdivision  
and the  
Survey of Lot 2 of Section 9,  
Township 14 North, Range 2 West

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Harry K. Smith, Cadastral Surveyor

Under special instructions dated August 27, 1975, approved August 28, 1975

, which provided for the surveys included under U.S. Survey/Group  
Number 578, and assignment instructions dated September 3, 1975.

Survey commenced September 4, 1975

Survey completed October 3, 1975

# INDEX DIAGRAM

Township 14 North, Range 2 West,

6	5	4 7	3	2	1
7	8	6 9 4	1 10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision Sec. 9 -- Page 8  
Survey lot 2 Sec. 9 - Page 12