

BOOK 5021

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION
CORNER MONUMENTS

Tp. 9 N. R. 22 E. Mer. G&SR

			1		
6	5	4	3	2	1
				2	
7	8	9	10	11	12
		4	4		2
18	17	16	15	14	13
		5			
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 9 N. R. 24 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
					6
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 9 N. R. 25 E. Mer. G&SR

6	5	4	3	2	1	
7	8	7	9	10	11	12
						7
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Township 9 North Range 22 East
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners in Township 9 North, Range 22 East, Township 9 North, Range 24 East and Township 9 North, Range 25 East, G&SRM., Arizona. The remonumentation is by agreement with the U.S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The remonumentation was executed in accordance with the Manual of Surveying Instructions, 1973, and the Special Instructions for Group 577, Arizona, dated July 29, 1975. The approval of the Special Instructions on July 31, 1975 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541 dated April 21, 1961.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Township 9 North, Range 22 East, G&SRM., Arizona

The north boundary and subdivisional lines were surveyed by O. D. Wheeler in 1883, and a portion of the subdivisional lines were resurveyed by Sidney E. Blout in 1915.

Re monumentation, N. Bdy., T. 9 N., R. 22 E.,
G&SRM., Arizona

The mean magnetic declination is 14° E.

The cor. of secs. 3, 4, 33 and 34, Tps. 9 and 10 N., R. 22 E., reestablished by record course and distance from the original bearing trees

A pine stump, 18 ins. high, 18 ins. diam., bears S. 32° E., 185 lks. dist., mkd. S BT, fallen portion of the tree is mkd. T9N R22E.

A dead pine, 22 ins. diam., bears N. 59° W., 183 lks. dist., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam. 16 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T 10 N	R 22 E
S 33	S 34
S 4	S 3
T 9 N	
1975	

from which a new bearing tree

An alligator juniper, 7 ins. diam., bears N. 11½° E., 225 lks. dist., mkd. T10N R22E S34 BT.

Remonumentation, N. Bdy., T. 9 N., R. 22 E.,
G&SRM., Arizona

CHAINS

The cor. is located 4 lks. S of an E-W fence.

Remonumentation, Subdivision, T. 9 N., R. 22 E.,
G&SRM., Arizona

The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, monumented by a lava stone, 20 x 14 x 8 ins., firmly set, projecting 12 ins. above ground, mkd. $\frac{1}{4}$ on N face with a scattered mound of stone N of the cor.

At the cor. point

Set an iron post, 28 ins. long $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 9 N R 22 E
 $\frac{1}{4}$ S 12
S 13
1975

from which a new bearing tree

An alligator juniper, 6 ins. diam., bears
N. 73° E., 23 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

Bury the original mkd. stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by a basalt stone, 12 x 10 x 6 ins., set in a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on the W face.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 9 N R 22 E
 $\frac{1}{4}$
S 11 | S 12
1975

from which new bearing trees

An alligator juniper, 18 ins. diam., bears N.
 89° E., 55 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

An alligator juniper, 8 ins. diam., bears N.
 62° W., 35 lks. dist., mkd. $\frac{1}{4}$ S11 BT.

Deposit the mkd. stone alongside the iron post.

The cor. is located 53 lks. E of a fence bearing S. 35°
E. and N. 35° W.

The cor. of secs. 2, 3, 10 and 11, reestablished by
record course and distance from the original bearing tree

Remonumentation, T. 9 N., R. 22 E., G&SRM., Arizona

CHAINS

An alligator juniper stump, bears S. 29° W.,
35 lks. dist., sawed off tree, 18 ins.
diam., alongside, mkd. N R22E S10 BT.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins.
in the ground to bedrock, in a mound of stone, 2½ ft.
base to top, with brass cap mkd.

T 9 N R 22 E

S 3	S 2
S 10	S 11
1975	

from which new bearing trees

An alligator juniper, 6 ins. diam., bears
S. 27° E., 192 lks. dist., mkd. T9N R22E
S11 BT.

An alligator juniper, 7 ins. diam., bears
S. 73½° W., 151 lks. dist., mkd. T9N
R22E S10 BT.

An alligator juniper, 8 ins. diam., bears
N. 51½° W., 141 lks. dist., mkd. T9N
R22E S3 BT.

The cor. is located N. 21½° E., 38 lks. dist. from a
fence cor. with fences extending N and E.

The ¼ sec. cor. of secs. 15 and 16, monumented by a sand-
stone, 14 x 12 x 8 ins., firmly set, projecting 8 ins.
above ground, encircled by a scattered mound of stone,
mkd. ¼ on W face, from which the original bearing trees

A pine, 16 ins. diam., bears N. 68° E., 58
lks. dist., mkd. with a healed blaze.
(Record, N. 63 ¾° E., 38 lks. dist.)

A pine, 14 ins. diam., bears N. 30½° W.,
45 lks. dist., mkd. with a healed blaze.
(Record, N. 33½° W., 45 lks. dist.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins.
in the ground, mound of stone to top, with brass cap mkd.

T 9 N R 22 E

¼	
S 16	S 15

1975

Remonumentation, T. 9 N., R. 22 E., G&SRM., Arizona

CHAINS

Deposit the mkd. stone alongside the iron post.

The cor. is located 96 lks. West of Road No. 82, bearing N. 35° E. and S. 35° W.

The cor. of secs. 9, 10, 15 and 16, reestablished by record dist. from the original bearing trees

A pine, 8 ins. diam., bears N. 63° E., 72 lks. dist., mkd. T9N R22E S10 BT. (Record, N. 61° E., 72 lks.)

A pine, 20 ins. diam., bears S. 18° E., 133 lks. dist., mkd. with partial overgrown blaze, 9N R2 S1 visible. (Record, S. 20½° E., 133 lks.)

A pine, 20 ins. diam., bears S. 14° W., 137 lks. dist., mkd. T9N R22E S16 BT. (Record, S. 11½° W., 137 lks.)

A pine, 15 ins. diam., bears N. 29½° W., 67 lks. dist., mkd. with a partially healed blaze, 9N R22E BT visible. (Record, N. 31° W., 67 lks. dist.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, mound of stone, 3 ft. base to top, with brass cap mkd.

T 9 N R 22 E

S 9	S 10
S 16	S 15
1975	

from which

A 1 in. open end pipe, bears S. 73° W., 4 lks. dist., projects 16 ins. above ground.

A fence cor. bears West, 13 lks. dist., fences extend N, S and W.

The ¼ sec. cor. of secs. 10 and 15, monumented by a basalt stone, 12 x 10 x 7 ins., set in a mound of stone, 2½ ft. base, 1 ft. high, mkd. ¼ on N face, from which the remains of an original bearing tree

A stump hole, bears N. 8½° E., 91 lks. dist., fallen pine alongside mkd. ¼ S BT. (Record, N. 18° E., 91 lks.)

At the cor. point

Remonumentation, T. 9 N., R. 22 E., G&SRM., Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, mound of stone, 3 ft. base to top, with brass cap mkd.

T 9 N R 22 E

¼ $\frac{S 10}{S 15}$
1975

from which new bearing trees

An alligator juniper, 7 ins. diam., bears N. 26½° E.
89 lks. dist., mkd. ¼ S10 BT.

An alligator juniper, 6 ins. diam., bears
S. 48½° W., 63 lks. dist., mkd. ¼ S15 BT.

Deposit the mkd. stone alongside the iron post.

The ¼ sec. cor. of secs. 16 and 21, reestablished by record course and dist., from bearing trees mkd. in 1915.

An alligator juniper, 26 ins. diam., bears
S. 32½° W., 78 lks. dist., mkd. ¼ S21 BT.

A dead alligator juniper, 14 ins. diam.,
bears N. 18° W., 23 lks. dist., mkd.
¼ S BT S16.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T 9 N R 22 E

¼ $\frac{S 16}{S 21}$
1975.

from which a new bearing tree

A pine, 14 ins. diam., bears N. 61° W.,
18 lks. dist., mkd. ¼ S16 BT.

Township 9 North, Range 24 East, G&SRM., Arizona

The subdivisional lines were surveyed in 1882 by A. P. Johnson.

Remonumentation, Subdivision, T. 9 N., R. 24 E.,
G&SRM., Arizona

The mean magnetic declination is 14° E.

Remonumentation, T. 9 N., R. 24 E., G&SRM., Arizona

CHAINS

The cor. of secs. 11, 12, 13 and 14, monumented by a mound of stone, 2 ft. base, 1½ ft. high, from which the remains of the original bearing trees

A stump hole, bears N. 80° E., 30 lks. dist., a down, badly decayed pine alongside. (Record, N. 66° E., 30 lks.)

A stump hole, bears S. 36° E., 25 lks. dist., a down pine alongside, 20 ins. diam., mkd. T9N R.

A pine snag, 12 ins. high, 26 ins. diam., bears S. 41° W., 80 lks. dist., mkd. T9N R24E S1 B. (Record, S. 41° W., 30 lks.)

A stump hole, bears N. 51° W., 45 lks. dist.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 9 N. R 24 E

S 11	S 12
S 14	S 13

1975

from which new bearing trees

A pine, 16 ins. diam., bears N. 78 3/4° E., 72 lks. dist., mkd. T9N R24E S12 BT.

A pine, 12 ins. diam., bears S. 72½° E., 12 lks. dist., mkd. T9N R24E S13 BT.

A pine, 16 ins. diam., bears S. 50½° W., 93 lks. dist., mkd. T9N R24E S14 BT.

A pine, 12 ins. diam., bears N. 11½° W., 34 lks. dist., mkd. T9N R24E S11 BT.

Township 9 North, Range 25 East, G&SRM., Arizona

The West boundary and subdivisional lines were surveyed in 1882 by A. P. Johnson.

Remonumentation, W. Bdy., T. 9 N., R. 25 E., G&SRM., Arizona

The mean magnetic declination is 14° E.

Remonumentation, T. 9 N., R. 25 E., G&SRM., Arizona

CHAINS

The cor. of secs. 7, 12, 13 and 18, Tps. 9 N., Rs. 24 and 25 E., monumented by a 1 in. open pipe, projecting 20 ins. above ground, encircled by a mound of stone, 2½ ft. base, from which the remains of the original bearing trees

A stump hole, bears N. 61° E., 30 lks. dist., a down pine alongside, 20 ins. diam., mkd. T9N R.

A pine stump, 4 ft. high, 20 ins. diam., bears S. 29½° E., 47 lks. dist., mkd. T9N R25E S18 BT. (Record, S. 28° E., 46 lks.)

A stump hole, bears S. 60° W., 106 lks. dist.

A stump hole, bears N. 60° W., 105 lks. dist., a down pine alongside, 32 ins. diam., no marks visible.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone to top, with brass cap mkd.

	T 9 N	
R 24 E		R 25 E
S 12 S		S 7
S 13		S 18
1975		

from which new bearing trees

A pine, 10 ins. diam., bears N. 4° E., 26 lks. dist., mkd. T9N R25E S7 BT.

A pine, 12 ins. diam., bears S. 44½° E., 25 lks. dist., mkd. T9N R25E S18 BT.

A pine, 10 ins. diam., bears S. 79° W., 43 lks. dist., mkd. T9N R24E S13 BT.

A pine, 12 ins. diam., bears N. 56° W., 39 lks. dist., mkd. T9N R24E S12 BT.

Deposit the 1 in. open end pipe inside the iron post.

Remonumentation, Subdivision, T. 9 N., R. 25 E.,
G&SRM., Arizona

The ¼ sec. cor. of secs. 8 and 9, monumented by a basalt stone, 15 x 10 x 7 ins., firmly set, projecting 4 ins. above ground, mkd. ¼ on W face with a mound of stone, 2½ ft. base, 2 ft. high, W of cor., from which the remains of the original bearing trees

Remonumentation, T. 9 N., R. 25 E., G&SRM., Arizona

CHAINS

A pine, 20 ins. diam., bears S. $34\frac{1}{2}^{\circ}$ E.,
84 lks. dist., mkd. with a healed blaze -
open the blaze to reveal $\frac{1}{4}$ S BT.. (Record,
S. 55° E., 87 lks.)

A pine stump, 1 ft. high, 20 ins. diam.,
bears S. 70° W., 94 lks. dist., no marks.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins.
in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with
brass cap mkd.

T 9 N R 25 E

$\frac{1}{4}$

S 8 | S 9

1975

from which a new bearing tree

A pine, 8 ins. diam., bears S. $72\frac{1}{2}^{\circ}$ W.,
37 lks. dist., mkd. $\frac{1}{4}$ S 8 BT.

Bury the mkd. stone alongside the iron post.

CERTIFICATE OF SURVEY

(I) (~~We~~), Paul L. Reeves, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of July, 1975, (I) (~~We~~) have remonumented a portion of the cadastral survey corners in Township 9 North, Range 22 East, Township 9 North, Range 24 East and Township 9 North, Range 25 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 15, 1976 (Date) Paul L. Reeves (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 9 North, Range 22 East, Township 9 North, Range 24 East and Township 9 North, Range 25 East, all of the Gila and Salt River Meridian, Arizona, executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

APR 27 1977 (Date) Bernard W. Jones (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626