

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE NORTH AND SOUTH CENTER LINE AND A PORTION OF THE

MEANDER LINES OF SECTION 19

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES

WITHIN SECTIONS 19, 34, AND 35,

THE METES-AND-BOUNDS SURVEY OF LOT 1, AND PARCELS A AND B

WITHIN SECTION 34

AND

THE SURVEY OF TRACTS 37, 38, AND 39,

TOWNSHIP 8 SOUTH, RANGE 22 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

### EXECUTED BY

RAY HARPIN

CADASTRAL SURVEYOR

Under special instructions dated JANUARY 7, 1972, approved JANUARY 20,  
1972, AND SUPPLEMENTAL SPECIAL INSTRUCTIONS, DATED APRIL 10, 1972

U.S. Survey/Group, which provided for the surveys included under  
Number 543, and assignment instructions dated JANUARY 7, 1972.

Survey commenced MAY 14, 1972

Survey completed MAY 24, 1977

1A

BOOK 5074

INDEX DIAGRAM

Township 8 South, Range 22 West

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19 8	7 5	20	21	22	23
24	23	22	21	20	19
30	29	28	27	26	25
31	32	33	34 3	35 4	36 1

Meanders within Section 19 . . . . . p. 10

Survey of a portion of the subdivision lines

- Section 19. . . . . p. 10
- Section 34. . . . . p. 12
- Section 35. . . . . p. 20

Survey of Lot No. 1, Section 34 . . . . . p. 14

Survey of Parcel A, Section 34 . . . . . p. 15

Survey of Parcel B, Section 34 . . . . . p. 19

Survey of Tract 37 . . . . . p. 24

Survey of Tract 38 . . . . . p. 25

Survey of Tract 39 . . . . . p. 27

Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary of the township, a portion of the subdivisional lines, and the north and south center line and a portion of the meander lines of section 19; the survey of a portion of the subdivision lines within sections 19, 34, and 35; the metes-and-bounds survey of lot 1, and Parcels A and B within section 34; the survey of Tracts 37, 38, and 39, Township 8 South, Range 22 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The exterior boundaries and subdivisional lines of this township were originally surveyed by Theodore F. White, U. S. Deputy Surveyor, in 1874, as shown upon the official plat examined and approved May 18, 1874. The south and west boundaries, and a portion of the east and north boundaries, and a portion of the subdivisional lines were resurveyed by Robert C. Yundt, Cadastral Surveyor, in 1960 and 1961, as shown upon the official plat accepted August 28, 1961.

The dependent resurveys and surveys were executed in accordance with the specifications as set forth in the Manuals of Surveying Instructions, 1947 and 1973 Editions, and the Special Instructions dated January 7, 1972, and Supplemental Special Instructions dated April 10, 1972.

The direction of all lines of these surveys were determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains.

The geographic position of the corner of sections 1, 2, 35, and 36, on the south boundary of the township, determined by scaling from a U. S. Geological Survey Quadrangle Map, 7½ minute series "Fortuna, Arizona, 1965", is as follows: Latitude 32° 41.1' N., and Longitude 114° 28.7' W. The mean magnetic declination is 14° East.

---

Dependent Resurvey of a Portion of the South Boundary  
Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

---

Restoring the Survey Executed by Robert C. Yundt  
Cadastral Surveyor, in 1960 and 1961

---

Beginning at the corner of secs. 1, 2, 35, and 36, on the south boundary of the township, which is monumented with an iron post, 2½ ins. in diam., with brass cap 18 ins. below the surface of the ground, mkd.

Dependent Resurvey of a Portion of the South Boundary  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS

S C  
 T8S R22W  
 $\frac{S\ 35}{S\ 2} | \frac{S\ 36}{S\ 1}$   
 T9S

1960

substantiated by:

A railroad track rail, firmly set, projecting 15 ins. above the surface of the ground, bears S. 44° 12' W., 47.50 ft. distant, mkd. RP 47.50' TO SEC. COR.

A railroad track rail, firmly set, projecting 15 ins. above the surface of the ground, bears N. 45° 55' W., 47.50 ft. distant, mkd. RP 47.50' TO SEC. COR.

---

S. 89° 26' W., between Tps. 8 and 9 S., through R. 22 W., and between secs. 2 and 35.

Over nearly level land.

20.165 The point for the east 1/16 sec. cor. of secs. 2 and 35.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.

E 1/16  $\frac{S\ 35}{S\ 2}$

1973

There are no suitable accessories nor locations available for reference monuments.

40.33 The 1/4 sec. cor. of secs. 2 and 35 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 3 ins. above the surface of the ground, mkd.

S C  
 T8S R22W  
 $\frac{1/4}{S\ 35}$   
 $\frac{S\ 2}{S\ 2}$

T9S

1960

---

S. 89° 27' W., beginning new measurement

20.16 The point for the west 1/16 sec. cor. of secs. 2 and 35.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.

Dependent Resurvey of a Portion of the South Boundary  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS

W 1/16  $\frac{S\ 35}{S\ 2}$

1973

There are no suitable accessories nor locations available for reference monuments.

40.32 The cor. of secs. 2, 3, 34, and 35 is monumented with an iron post, 2½ ins. in diam., with brass cap 6 ins. below the surface of a roadway, mkd.

S C  
 T8S R22W  
 $\frac{S\ 34\ | S\ 35}{S\ 3\ | S\ 2}$   
 T9S

1960

S. 89° 43' W., between secs. 3 and 34.

Over nearly level land.

20.03 The point for the east 1/16 sec. cor. of secs. 2 and 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.

E 1/16  $\frac{S\ 34}{S\ 3}$

1973

40.06 The 1/4 sec. cor. of secs. 3 and 34 is monumented with an iron post, 2½ ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.

S C  
 T8S R22W  
 1/4  $\frac{S\ 34}{S\ 3}$   
 T9S

1960

Discontinue the dependent resurvey of the township line at this corner.

Dependent Resurvey of a Portion of the Subdivisional Lines  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the corner of secs. 1, 2, 35, and 36 on the south boundary of the township, heretofore described.</p>
	<p>N. 0° 24' W., between secs. 35 and 36</p>
19.985	<p>The point for the south 1/16 sec. cor. of secs. 35 and 36. I did not monument this corner point.</p>
39.97	<p>The 1/4 sec. cor. of secs. 35 and 36 is marked with an iron pipe, 36 ins. long, 1-inch in diam., with brass cap 6 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">BUREAU OF RECLAMATION              1/4              S 35   S 36              1941</p>
	<p>substantiated by:              A cross (+) chiseled on a concrete cylinder, 5 ft. in diam., bears S. 79° 30' E., 39 ft. distant, mkd.              + RP 39'</p>
	<p>At the corner point              Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">T8S R22W              1/4              S 35   S 36              1973</p>
	<p>Deposit the corner marker alongside the iron post.              Discontinue the regular order of survey at this corner.</p>
	<p>From the cor. of secs. 2, 3, 34, and 35 on the south boundary of the township, heretofore described.</p>
	<p>N. 0° 10' W., between secs. 34 and 35.</p>
	<p>Over nearly level land.</p>
20.055	<p>The point for the south 1/16 sec. cor. of secs. 34 and 35. I did not monument this corner point.</p>
39.07	<p>The point for Corner No. 4, lot 1, section 34.</p>
	<p>Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., 26 ins. in the ground, with brass cap, 1½ inch in diam., mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
40.11	<p style="text-align: center;">                     S 34   S 35                      LOT 1                        COR 4    <hr style="width: 10%; margin: 0 auto;"/>                     1973                 </p> <p>The 1/4 sec. cor. of secs. 34 and 35 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">                     T8S R22W                      1/4                      S 34   S 35  <hr style="width: 10%; margin: 0 auto;"/>                     1960                 </p> <p>Discontinue the regular order of survey at this corner.</p>
19.995  31.015	<p>The cor. of secs. 19, 20, 29, and 30 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">                     BUREAU OF RECLAMATION                      T8S R22W                      S 19   S 20                      S 30   S 29  <hr style="width: 10%; margin: 0 auto;"/>                     1941                 </p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Robert C. Yundt in 1960.</p> <p style="text-align: center;">                     S. 89° 18' W., between secs. 19 and 30                      Over nearly level land.                 </p> <p>The point for the east 1/16 sec. cor. of secs. 19 and 30. I did not monument this corner point.</p> <p>The point for Angle Point No. 4, Tract 37</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">                     T8S R22W                      TR 37 \ S 19                      AP 4 \  <hr style="width: 10%; margin: 0 auto;"/>                     S 30                      1973                 </p>

Dependent Resurvey of a Portion of the Subdivisional Lines  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
35.12	<p>The point for Angle Point No. 3, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R22W                  \ TR 37                  S 19 \ AP 3                  S 30</p> <p>1973</p> </div>
39.99	<p>The point for the 1/4 sec. cor. of secs. 19 and 30 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 20 ins. below the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>T8S R22W                  1/4 S 19                  S 30</p> <p>1973</p> </div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. in diam., set 25 ins. in the ground, for a reference monument, bears N. 42° 15' E., 41.8 ft. distant, with brass cap mkd. RM T8S R22W S19 41.8 FT 1973, and an arrow pointing to the corner.</p> <p>An iron post, 28 ins. long, 2½ ins. in diam., set 21 ins. in the ground, for a reference monument, bears S. 88° 30' E., 31.8 ft. distant, with brass cap mkd. RM T8S R22W S30 31.8 FT 1973, and an arrow pointing to the corner.</p>
59.985	<p>The point for the west 1/16 sec. cor. of secs. 19 and 30 is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.</p>
79.92	<p>The cor. of secs. 19, 24, 25, and 30 on the west boundary of the township, which is monumented with an iron post, 2½ ins. in diam., with brass cap flush with the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S                  R23W R22W                  S 24   S 19                  S 25   S 30</p> <p>1960</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 19, 20, 29, and 30, heretofore described.</p> <p>N. 0° 24' W., between secs. 19 and 20.</p> <p>Over nearly level land.</p>
19.86	The point for the south 1/16 sec. cor. of secs. 19 and 20 I did not monument this corner.
39.72	The 1/4 sec. cor. of secs. 19 and 20 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.
	<p>T8S R22W                  1/4                  S 19   S 20                    1960</p> <hr/>
	N. 0° 24' W., beginning new measurement.
7.03	The witness point of secs. 19 and 20 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.
	<p>T8S R22W                  W   P                  S 19   S 20                    1960</p>
7.98	The left bank of the Colorado River, course S. 56° 26' W.; the point for the meander corner on the east boundary of section 19, which is determined at record course and record distant. I did not monument this corner point.
25.50	The right bank of the Colorado River, the meander corner on the east boundary of section 19, which is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.
	<p>T8S R22W                  S 19                    MC                    1960</p> <hr/>

Dependent Resurvey of a Portion of the Subdivisional Lines  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS

N. 0° 24' W., beginning new measurement.

14.22 The cor. of secs. 17, 18, 19, and 20 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION  
 T8S R22W  
 S 18|S 17  
 S 19|S 20

1957

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Robert C. Yundt in 1960.

Discontinue the dependent resurvey of the subdivisional lines at this corner.


Dependent Resurvey of the North and South Center Line  
 of Section 19  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

From the 1/4 sec. cor. of secs. 19 and 30, heretofore described.

N. 0° 12' W., on the north and south center line of sec. 19.

11.465 The point for Angle Point No. 2, Tract 37.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.



1973

Continue on the north and south center line of sec. 19, and on line 2 - 1, Tract 37.

19.92 The point for the center-south 1/16 sec. cor. of sec. 19.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

Dependent Resurvey of the North and South Center Line  
of Section 19  
Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">C S 1/16 S 19 1973</p>	
21.115	<p>The point for Angle Point No. 1, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R22W</p> </div> <p style="text-align: center;">1973</p>	
21.81	<p>Continue on the north and south center line of sec. 19.</p> <p>The point for the Special Meander Corner of sec. 19 for the left bank of the Colorado River, which is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S M C</p> <p>T8S R22W</p> </div> <p style="text-align: center;">1973</p>	
39.84	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 19. This corner point is located within the bed of the Colorado River. I did not monument this corner point.</p>	
42.20	<p>The point for the Special Meander Corner of sec. 19 for the right bank of the Colorado River, which is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.</p>	
79.70	<p>The 1/4 sec. cor. of secs. 18 and 19 is monumented with an iron post, 2½ ins. diam., with brass cap 15 ins. below the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>T8S R22W</p> <p>1/4 <math>\frac{S\ 18}{S\ 19}</math></p> <p>1960</p> </div> <p>from which</p>	

Dependent Resurvey of the North and South Center Line  
of Section 19  
Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins. long, 2½ ins. in diam., set 25 ins. in the ground, for a reference monument, bears S. 45° 00' E., 108.6 ft. distant, with brass cap mkd. RM T8S R22W S19 108.6 FT 1973, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2½ ins. in diam., set 25 ins. in the ground, for a reference monument, bears S. 32° 30' W., 105.9 ft. distant, with brass cap mkd. RM T8S R22W S19 105.9 FT 1973, and an arrow pointing to the corner.

Dependent Resurvey of the Left Bank of the  
Colorado River, Through the East Half of Section 19  
Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

From the point for the meander corner of sec. 19 (only), heretofore described and the left bank of the Colorado River.

S. 56° 26' W.

- 14.62 Intersect the east and west center line, the point for the Special Meander Corner of sec. 19. I did not monument this corner point.
- 23.81 Intersect the north and south center line of the southeast quarter, the point for the Special Meander Corner of sec. 19. I did not monument this corner point.
- 47.68 Intersect the north and south center line, the Special Meander Corner of sec. 19, heretofore described.

Discontinue the dependent resurvey of the township at this corner.

Survey of a Portion of the Subdivision Lines  
Within Sections 19, 34, and 35  
Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

Thence, in section 19.

From the 1/4 sec. cor. of secs. 19 and 20, heretofore described.

S. 89° 30' W., on the east and west center line of sec. 19.

Over nearly level land.

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
12.24	Intersect the reestablished meander line of the left bank of the Colorado River; the point for the Special Meander Corner of sec. 19, heretofore described.
19.925	The point for the center-east 1/16 sec. cor. of sec. 19. I did not monument this corner point.
39.85	Intersect the north and south center line, the point for the center 1/4 sec. cor. of sec. 19, heretofore described.
79.67	<p>Intersect the west boundary of the township, the true point for the 1/4 sec. cor. of secs. 19 and 24.</p> <p>From this true corner point the witness 1/4 sec. cor. of secs. 19 and 24 bears N. 0° 03' W., 6.985 chs. distant, and is marked with an iron pipe, 3 ins. in diam., set in a concrete cone, 6 ins. in diam., with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} 1/4 \\ S\ 24 \mid S\ 19 \\ \downarrow \\ W\ C \end{array}</math> </div> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Robert C. Yundt in 1960.</p> <p>From this same true corner point the meander corner of secs. 19 and 24, on the left bank of the Colorado River bears S. 0° 03' E., 17.695 chs. distant, and is monumented with a regulation iron post, 2½ ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} MC \\ \diagup \quad \diagdown \\ S\ 24 \mid S\ 19 \\ R23W \mid R22W \\ T8S \\ 1960 \end{array}</math> </div>
	From the point for the east 1/16 sec. cor. of secs. 19 and 30, heretofore described.
	N. 0° 18' W., on the north and south center line of the southeast quarter of sec. 19.
19.89	Intersect the east and west center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 19. I did not monument this corner point.
34.76	Intersect the reestablished meander line of the left bank of the Colorado River, the point for the Special Meander Corner of sec. 19, heretofore described.
39.78	Intersect the east and west center line, the point for the center-east 1/16 sec. cor. of sec. 19, heretofore described.

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS


From the point for the south 1/16 sec. cor. of secs. 19 and 20, heretofore described.

S. 89° 24' W., on the east and west center line of the southeast quarter of sec. 19.

19.96 Intersect the north and south center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 19, heretofore described.

39.41 Intersect line 4 - 1, Tract 37, the point for the closing corner of sec. 19.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1973

Continue on the east and west center line of the southeast quarter of sec. 19 and on a blank line across Tract 37.

39.92 Intersect the north and south center line, the center-south 1/16 sec. cor. of sec. 19, heretofore described.

Thence, in section 34.


From the 1/4 sec. cor. of secs. 3 and 34 on the south boundary of the township, heretofore described.

N. 0° 13' W., on the north and south center line of sec. 34.

20.03 The point for the center-south 1/16 sec. cor. of sec. 34. I did not monument this corner point.

32.77 The point for Corner No. 8, Parcel A of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1973


Continue on the north and south center line and on line 8 - 7, Parcel A of section 34.

34.44 The point for Corner No. 7, Parcel A and Corner No. 3, Parcel B of sec. 34.

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1973

Continue on the north and south center line and on line 3 - 2, Parcel B of section 34.

40.06

The center 1/4 sec. cor. of sec. 34 is marked with a concrete pipe, 10 ins. in diam., with the top 8 ins. below the surface of the ground, and is accepted as the position for the corner. I did not monument this corner.

This corner is designated to function for Corner No. 2, Parcel B of section 34.

Discontinue the regular order of survey at this corner.


From the 1/4 sec. cor. of secs. 34 and 35, heretofore described.

S. 89° 41' W., on the east and west center line of sec. 34.

3.14

The point for Corner No. 2, Lot 1 of section 34.

Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., 27 ins. in the ground, with brass cap 1½ inch in diam., mkd.



1973

This corner is located on the eastern right-of-way of a road.


20.055

The point for the center-east 1/16 sec. cor. of sec. 34. I did not monument this corner point.

24.315


The point for Corner No. 1, Parcel A of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1973

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
27.86	<p>Continue on the east and west center line, and on line 1 - 2, Parcel A of section 34.</p> <p>The point for Corner No. 2, Parcel A and Corner No. 1, Parcel B of section 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T8S R22W S 34</p>  <p>1977</p> </div>
40.11	<p>Continue on the east and west center line, and on line 1 - 2, Parcel B of section 34.</p> <p>The center 1/4 sec. cor. of sec. 34, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p>
20.04	<p>From the east 1/16 sec. cor. of secs. 3 and 34 on the south boundary of the township, heretofore described.</p> <p>N. 0° 11.5' W., on the north and south center line of the southeast quarter of sec. 34.</p> <p>Intersect the east and west center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 34. I did not monument this corner point.</p>
40.09	<p>Intersect the east and west center line, the point for the center-east 1/16 sec. cor. of sec. 34, heretofore described.</p>
20.04	<p>From the point for the south 1/16 sec. cor. of secs. 34 and 35, heretofore described.</p> <p>S. 89° 42' W., on the east and west center line of the southeast quarter of sec. 34.</p> <p>Intersect the north and south center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 34, heretofore described.</p>
40.08	<p>Intersect the north and south center line, the point for the center-south 1/16 sec. cor. of sec. 34, heretofore described.</p>

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The Metes-and-Bounds Survey of Lot 1, Section 34                      Township 8 South, Range 22 West                      Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>Beginning at the 1/4 sec. cor. of secs. 34 and 35, heretofore described; which is designated to function for Corner No. 1, Lot 1 of section 34.</p>
	<p>S. 89° 41' W., on line 1 - 2, Lot 1, identical with the east and west center line of section 34.</p>
3.14	<p>Corner No. 2, Lot 1 of section 34, heretofore described.</p> <hr/>
	<p>S. 33° 59' W., on line 2 - 3, Lot 1 of section 34.</p>
	<p>Along the eastern right-of-way of a road.</p>
1.26	<p>The point for Corner No. 3, Lot 1 of section 34.</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., 27 ins. in the ground, with brass cap 1½ inch in diam., mkd.</p>
	<p style="text-align: center;">S 34                      / LOT 1                      / COR 3                      _____                      1973</p> <hr/>
	<p>N. 89° 41' E., on line 3 - 4, Lot 1 of section 34. This line is surveyed parallel to line 1 - 2.</p>
3.85	<p>Corner No. 4, Lot 1 of section 34, heretofore described.</p> <hr/>
	<p>N. 0° 10' W., on line 4 - 1, Lot 1 of section 34, identical with the section line between sections 34 and 35.</p>
1.04	<p>The 1/4 sec. cor. of secs. 34 and 35, which is designated to function for Corner No. 1, Lot 1 of section 34, and the place of beginning.</p> <hr/>
	<p style="text-align: center;">Survey of Parcel A, Section 34                      Township 8 South, Range 22 West                      Gila and Salt River Meridian, Arizona</p> <hr/>

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS

MEMORANDUM

The corner position of these Parcels were determined from the recorded deed record of the acquisition by the United States Government.

---

From Corner No. 1, Parcel A, section 34, heretofore described.

S. 89° 41' W., on line 1 - 2, Parcel A, identical with the east and west center line of section 34.


3.545 Corner No. 2, Parcel A, identical with Corner No. 1, Parcel B of section 34, heretofore described.

---

S. 61° 36' W., on line 2 - 3, Parcel A, identical with line 1 - 7, Parcel B, section 34.

4.59 The point for Corner No. 3, Parcel A, identical with Corner No. 7, Parcel B of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.





---

S. 56° 35' W., on line 3 - 4, Parcel A, identical with line 7 - 6, Parcel B, section 34.

2.81 The point for Corner No. 4, Parcel A, identical with Corner No. 6, Parcel B of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.




---


S. 51° 35' W., on line 4 - 5, Parcel A, identical with line 6 - 5, Parcel B, section 34.

1.48 The point for Corner No. 5, Parcel A, identical with Corner No. 5, Parcel B of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona


CHAINS



S. 72° 19' W., on line 5 - 6, Parcel A, identical with line 5 - 4, Parcel B, section 34.

3.65 The point for Corner No. 6, Parcel A, identical with Corner No. 4, Parcel B of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



N. 86° 57' W., on line 6 - 7, Parcel A, identical with line 4 - 3, Parcel B, section 34.

1.21 Intersect the north and south center line, Corner No. 7, Parcel A, identical with Corner No. 3, Parcel B of section 34, heretofore described.

S. 0° 13' E., on line 7 - 8, Parcel A, identical with the north and south center line of section 34.

1.67 Corner No. 8, Parcel A of section 34, heretofore described.


S. 86° 31' E., on line 8 - 9, Parcel A, section 34.

1.12 The point for Corner No. 9, Parcel A of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS




Thence, on line 9 - 10, Parcel A, section 34, along the arc of a curve, curve data:

Chord bears N. 72° 45' E.  
 Chord length 4.83 chs. distant  
 Radius 6.82 chs. distant  
 Length of arc 4.94 chs. distant

At the end of the arc of the curve, the point for Corner No. 10, Parcel A of section 34.


Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



N. 52° 01' E., on line 10 - 11, Parcel A, section 34

1.48 The point for Corner No. 11, Parcel A of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



Thence, on line 11 - 12, Parcel A, section 34, along the arc of a curve, curve data:


Chord bears N. 56° 42' E.  
 Chord length 2.52 chs. distant  
 Radius 15.45 chs. distant  
 Length of arc 2.52 chs. distant

At the end of the arc of the curve, the point for Corner No. 12, Parcel A of section 34

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



7.77 N. 61° 21' E., on line 12 - 1, Parcel A, section 34  
 Intersect the east and west center line, Corner No. 1, Parcel A of section 34, and the place of beginning.

Survey of Parcel B, Section 34  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

12.25 From Corner No. 1, Parcel B, identical with Corner No. 2, Parcel A of section 34, heretofore described.

S. 89° 41' W., on line 1 - 2, Parcel B, identical with the east and west center line of section 34

12.25 The center 1/4 sec. cor. of sec. 34. This corner is designated to function for Corner No. 2, Parcel B of section 34.

S. 0° 13' E., on line 2 - 3, Parcel B, identical with the north and south center line of section 34

5.62 Corner No. 3, Parcel B, identical with Corner No. 7, Parcel A of section 34, heretofore described.

S. 86° 57' E., on line 3 - 4, Parcel B, identical with line 7 - 6, Parcel A, section 34

1.21 Corner No. 4, Parcel B, identical with Corner No. 6, Parcel A of section 34, heretofore described.

N. 72° 19' E., on line 4 - 5, Parcel B, identical with line 6 - 5, Parcel A of section 34

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona


CHAINS		
3.65	Corner No. 5, Parcel B, identical with Corner No. 5, Parcel A of section 34, heretofore described.	
	<hr/> N. 51° 35' E., on line 5 - 6, Parcel B, identical with line 5 - 4, Parcel A of section 34	
1.48	Corner No. 6, Parcel B, identical with Corner No. 4, Parcel A of section 34, heretofore described.	
	<hr/> N. 56° 35' E., on line 6 - 7, Parcel B, identical with line 4 - 3, Parcel A of section 34	
2.81	Corner No. 7, Parcel B, identical with Corner No. 3, Parcel A of section 34, heretofore described.	
	<hr/> N. 61° 36' E., on line 7 - 1, Parcel B, identical with line 3 - 2, Parcel A of section 34	
4.59	Intersect the east and west center line, Corner No. 1, Parcel B, identical with Corner No. 2, Parcel A of section 34, and the place of beginning.	
	<hr/> Thence, in section 35	
	From the 1/4 sec. cor. of secs. 2 and 35 on the south boundary of the township, heretofore described.	
	N. 0° 18.5' W., on the north and south center line of section 35.	
20.02	The point for the center-south 1/16 sec. cor. of sec. 35.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	C S 1/16	
	S 35	
	1973	
29.245	The point for Angle Point No. 8, Tract 38	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.	

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T8S R22W                  C                  TR 38                  AP 8                  S 35                  C                  1973</p>
40.04	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">T8S R22W                  C 1/4                  S 35                  1973</p> <p>from which</p> <p style="padding-left: 40px;">A water well, bears S. 47° 30' W., 83 lks. distant.</p> <p style="padding-left: 40px;">A water well, bears S. 67° 05' W., 140 lks. distant.</p>
80.10	<p>The 1/4 sec. cor. of secs. 26 and 35 is marked with an iron pipe, 2 ins. in diam., with brass cap 5 ins. below the surface of the road, and set in a capped cast iron pipe, with the top flush with the surface of the road, the brass cap mkd.</p> <p style="text-align: center;">1/4 <math>\frac{S\ 26}{S\ 35}</math></p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Robert C. Yundt in 1960.</p>
	<p>From the 1/4 sec. cor. of secs. 35 and 36, heretofore described.</p> <p>S. 89° 31' W., on the east and west center line of sec. 35.</p>
20.125	<p>The point for the center-east 1/16 sec. cor. of sec. 35. I did not monument this corner point.</p>
40.25	<p>Intersect the north and south center line, the center 1/4 sec. cor. of sec. 35, heretofore described.</p>
48.695	<p>The point for Angle Point No. 2, Tract 38</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS



60.38 The point for the center-west 1/16 sec. cor. of sec. 35. I did not monument this corner point.

80.51 The 1/4 sec. cor. of secs. 34 and 35, heretofore described.

From the west 1/16 sec. cor. of secs. 2 and 35 on the south boundary of the township, heretofore described.

N. 0° 14' W., on the north and south center line of the southwest quarter of sec. 35.

20.04 Intersect the east and west center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 35. I did not monument this corner point.

40.08 Intersect the east and west center line, the point for the center-west 1/16 sec. cor. of sec. 35, heretofore described.

From the center-south 1/16 sec. cor. of sec. 35, heretofore described.

S. 89° 29' W., on the east and west center line of the southwest quarter of sec. 35.

20.145 Intersect the north and south center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 35, heretofore described.

40.29 The point for the south 1/16 sec. cor. of secs. 34 and 35, heretofore described.

From the east 1/16 sec. cor. of secs. 2 and 35 on the south boundary of the township, heretofore described.

N. 0° 22' W., on the north and south center line of the southeast quarter of sec. 35.

12.965 The point for Angle Point No. 6, Tract 39


Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T8S R22W                      E                      TR 39                      AP 6                      S 35                      E                      1973</p>
20.005	<p>Intersect the east and west center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 11 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">SE 1/16                      S 35                      1973</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>
40.01	<p>Intersect the east and west center line, the point for the center-east 1/16 sec. cor. of sec. 35, heretofore described.</p>
	<p>From the point for the south 1/16 sec. cor. of secs. 35 and 36, heretofore described.</p> <p>S. 89° 27.5' W., on the east and west center line of the southeast quarter of sec. 35.</p>
20.145	<p>Intersect the north and south center line of the southeast quarter, the southeast 1/16 sec. cor. of sec. 35, heretofore described.</p>
29.27	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, for a witness point of section 35, with brass cap mkd.</p>
	<p style="text-align: center;">W P                      T8S R22W                      S 35                      S ————— S                      1973</p>
32.06	<p>The point for Angle Point No. 2, Tract 39</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines  
 Within Sections 19, 34, and 35  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

CHAINS



40.29 Intersect the north and south center line, the center-south 1/16 sec. cor. of sec. 35, heretofore described.

Survey of Tracts 37, 38, and 39  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

Thence with the survey of Tract 37

Beginning at Angle Point No. 1, Tract 37 (heretofore described), and is located on the north and south center line of section 19.

S. 0° 12' E., on line 1 - 2, Tract 37, identical with the north and south center line of section 19.

1.195 The center-south 1/16 sec. cor. of sec. 19, heretofore described.

9.65 Angle Point No. 2, Tract 37, heretofore described.

S. 23° 17.5' E., on line 2 - 3, Tract 37

12.415 Angle Point No. 3, Tract 37, heretofore described.



N. 89° 18' E., on line 3 - 4, Tract 37, identical with the section line between sections 19 and 30

4.105 Angle Point No. 4, Tract 37, heretofore described.

N. 23° 17.5' W., on line 4 - 1, Tract 37

21.575 Intersect the east and west center line of the southeast quarter, the closing corner of sec. 19, heretofore described.

Survey of Tracts 37, 38, and 39  
Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

CHAINS	
22.87	Intersect the north and south center line of sec. 19, Angle Point No. 1, Tract 37, and the place of beginning.
	<p>Thence, with the survey of Tract 38</p> <p>Beginning at the center 1/4 sec. cor. of sec. 35 (heretofore described), which is designated to function for Angle Point No. 1, Tract 38</p> <p>S. 89° 31' W., on line 1 - 2, Tract 38, identical with the east and west center line of sec. 35.</p>
8.445	<p>Angle Point No. 2, Tract 38, heretofore described.</p> <hr/> <p>Thence, on line 2 - 3, Tract 38, along the arc of a curve, curve data:</p> <p>Chord bears S. 30° 53' E. Chord length 3.57 chs. distant Radius 16.52 chs. distant Length of arc 3.58 chs. distant</p> <p>At the end of the arc of the curve. The point for Angle Point No. 3, Tract 38</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T8S R22W TR 38 S 35 AP 3 1973</p> </div> <hr/> <p>S. 37° 05.5' E., on line 3 - 4, Tract 38</p>
4.085	<p>The point for Angle Point No. 4, Tract 38</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T8S R22W TR 38 S 35 AP 4 1973</p> </div> <hr/>

Survey of Tracts 37, 38, and 39  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona


CHAINS

Thence, on line 4 - 5, Tract 38, along the arc of a curve, curve data:

Chord bears S. 26° 17' E.  
 Chord length 0.63-chain distant  
 Radius 1.67 chs. distant  
 Length of arc 0.63-chain distant

At the end of the arc of the curve. The point for Angle Point No. 5, Tract 38


Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



S. 15° 28' E., on line 5 - 6, Tract 38

0.45 The point for Angle Point No. 6, Tract 38

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.





Thence, on line 6 - 7, Tract 38, along the arc of a curve, curve data:

Chord bears S. 41° 04' E.  
 Chord length 3.77 chs. distant  
 Radius 4.36 chs. distant  
 Length of arc 3.90 chs. distant

At the end of the arc of the curve. The point for Angle Point No. 7, Tract 38

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

Survey of Tracts 37, 38, and 39  
Township 8 South, Range 22 West  
Gila and Salt River Meridian, Arizona

CHAINS	
	 <p>T8S R22W TR 38 AP 7 S 35 1973</p>
	<hr/> <p>S. 66° 40.5' E., on line 7 - 8, Tract 38</p>
1.45	Intersect the north and south center line of section 35, Angle Point No. 8, Tract 38, heretofore described.
	<hr/> <p>N. 0° 18.5' W., on line 8 - 1, Tract 38, identical with the north and south center line of section 35</p>
10.795	The center 1/4 sec. cor. of sec. 35, which is designated to function for Angle Point No. 1, Tract 38, and the place of beginning.
	<hr/> <p>Thence, with the survey of Tract 39</p> <p>Beginning at the southeast 1/16 sec. cor. of sec. 35, (heretofore described) which is designated to function for Angle Point No. 1, Tract 39</p> <p>S. 89° 27.5' W., on line 1 - 2, Tract 39, identical with the east and west center line of the southeast quarter of sec. 35.</p>
9.125	A witness point of section 35, heretofore described.
11.915	Angle Point No. 2, Tract 39, heretofore described.
	<hr/> <p>S. 33° 34' E., on line 2 - 3, Tract 39</p>
0.20	The point for Angle Point No. 3, Tract 39
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.
	 <p>T8S R22W TR 39 AP 3 S 35 1973</p>

Survey of Tracts 37, 38, and 39  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona


CHAINS

Thence, on line 3 - 4, Tract 39 along the arc of a curve, curve data:

Chord bears S. 48° 20' E.  
 Chord length 2.125 chs. distant  
 Radius 4.165 chs. distant  
 Length of arc 2.15 chs. distant

At the end of the arc of the curve. The point for Angle Point No. 4, Tract 39


Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



S. 63° 06' E., on line 4 - 5, Tract 39

10.66 The point for Angle Point No. 5, Tract 39

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



Thence, on line 5 - 6, Tract 39, along the arc of a curve, curve data:

Chord bears S. 55° 23.5' E.  
 Chord length 0.915-chain distant  
 Radius 3.41 chs. distant  
 Length of arc 0.92-chain distant

At the end of the arc of the curve, intersect the north and south center line of the southeast quarter of section 35. Angle Point No. 6, Tract 39, heretofore described.

Survey of Tracts 37, 38, and 39  
 Township 8 South, Range 22 West  
 Gila and Salt River Meridian, Arizona

	<p>CHAINS</p> <p>7.04</p>	<p>N. 0° 22' W., on line 6 - 1, Tract 39, identical with the north and south center line of the southeast quarter of section 35</p> <p>The southeast 1/16 sec. cor. of sec. 35, which is designated to function for Angle Point No. 1, Tract 39, and the place of beginning.</p> <hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land area within these surveys is nearly level. The soil consists of sandy clay loam, and for the most part the area is under cultivation.</p> <p>Improvements located throughout the area, are: State, county, and farm roads; numerous canals and laterals for irrigation and/or drainage purposes.</p>	
--	---------------------------	--	--

CHAINS



CERTIFICATE OF SURVEY

(I) ~~(We)~~, Ray Harpin, HEREBY  
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day  
 of January, 1972, ~~(I) (We) have~~ and Supplemental Special Instructions  
 dated 10th day of April 1972, I have dependently resurveyed a portion of  
 the south boundary of the township, a portion of the subdivisional lines,  
 and the north and south center line and a portion of the meander lines of  
 section 19, surveyed a portion of the subdivision lines within sections  
 19, 34, and 35, surveyed the metes-and-bounds survey of lot 1, and Parcels  
 A and B within section 34, and surveyed Tracts 37, 38, and 39, Township  
 8 South, Range 22 West,  
 of the Gila and Salt River Meridian, in the State of Arizona, which  
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)  
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-  
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in  
 specific manner described in the foregoing field notes.

May 28, 1978  
 \_\_\_\_\_  
 (Date)

  
 \_\_\_\_\_  
 (Cadastral Surveyor)

\_\_\_\_\_  
 (Date)

\_\_\_\_\_  
 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
 Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south bound-  
 ary of the township, a portion of the subdivisional lines, and the north  
 and south center line and a portion of the meander lines of section 19,  
 the survey of a portion of the subdivision lines within sections 19, 34,  
 and 35, the metes-and-bounds survey of lot 1, and Parcels A and B within  
 section 34, the survey of Tracts 37, 38, and 39, Township 8 South, Range  
 22 West, of the Gila and Salt River Meridian, Arizona.

executed by Ray Harpin, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

SEP 15 1978  
 \_\_\_\_\_  
 (Date)

  
 \_\_\_\_\_  
 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
 \_\_\_\_\_, is a true copy of the original field notes.

\_\_\_\_\_  
 (Date)

\_\_\_\_\_  
 (Chief, Division of Cadastral Survey) GPO 849-626