

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

SUBDIVISIONAL LINES,

TOWNSHIP 32 NORTH, RANGE 5 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

GILBERT V. OLSON

SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated MAY 23, 19 75, approved JUNE 5, 1975,

, which provided for the surveys included under ~~XXXX~~ Survey/Group

Number 576, and assignment instructions dated MAY 9, 1975.

Survey commenced JULY 10, 19 75

Survey completed JULY 30, 19 75

1A

BOOK 5078

INDEX DIAGRAM

Township 32 NORTH, Range 5 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
18 10	11 8	9 7	7 5	5 2	3 13
10 19	9 20	8 21	6 22	4 23	1 24
30	29	28	27	26	25
31	32	33	34	35	36

T. 32 N., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent re-survey of a portion of the subdivisional lines, Township 32 North, Range 5 West, Gila and Salt River Meridian, Arizona.

A portion of the east boundary was surveyed by F. B. Jacobs, in 1901. A portion of the east boundary was re-surveyed, the south boundary, portions of the west boundary and subdivisional lines were surveyed by W. H. Thorn and Heber P. Purington, in 1917.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 23, 1975, for Group No. 576, Arizona.

The directions of the lines were determined by polaris and solar observations. They refer to the true meridian.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. All corners of the original survey were located. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 13 and 24 only, on the east boundary of the township as calculated from a direct tie to U. S. Coast and Geodetic Survey triangulation station, "HAVA", located in section 1, Township 31 North, Range 5 West, is as follows:

Latitude 36° 09' 04.1" N. Longitude 112° 45' 40.5" W.

The mean magnetic declination is 14½ E.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 32 N., R. 5 W., G&SR Mer., Arizona

Restoring the survey executed by W. H. Thorn,
and Heber P. Purington, in 1917

Beginning at the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., as described in the field notes of the dependent resurvey of the W. bdy. of T. 32 N., R. 4 W., executed concurrently with this group.

S. 89° 41' W., bet. secs. 13 and 24.

Over rolling land, through dense undergrowth.

40.07

The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, with brass cap mkd.

1/4 $\frac{S\ 13}{S\ 24}$

1917

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS		
	<p>I add marks T32N R5W 1975 on the brass cap.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 36' W., beginning new measurement.</p> <p>Over rolling land.</p>	
40.19	<p>The cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T32N R5W $\frac{S\ 14}{S\ 23} \frac{S\ 13}{S\ 24}$</p> <p>1917</p> </div> <p>from which original bearing trees</p> <p style="margin-left: 40px;">A juniper, 6 ins. diam., bears N. 59° 40' E., 90 lks. dist., with scribe marks T32N R5W S13 BT visible on open blaze.</p> <p style="margin-left: 40px;">A juniper, 5 ins. diam., bears S. 64° E., 140 lks. dist., with scribe marks T32N R5W S24 BT visible on open blaze.</p> <p style="margin-left: 40px;">A juniper, 3 ins. diam., bears S. 59° 40' W., 97 lks. dist., with scribe marks T32N R5W S23 BT visible on open blaze.</p> <p style="margin-left: 40px;">A juniper, 6 ins. diam., bears N. 27° 10' W., 40 lks. dist., with scribe marks T32N R5W S14 BT visible on open blaze.</p>	
	<p>N. 0° 05' W., bet. secs. 13 and 14.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>	
32.00	<p>SE rim of Little Coyote Canyon, bears NW and E.; desc. over broken N. slope.</p>	
39.88	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 32 ins. above ground, supported with a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>1/4 $\frac{S\ 14}{S\ 13}$</p> <p>1917</p> </div> <p>I add marks T32N R5W 1975 on the brass cap.</p> <p>Cor. is located on bare spur, slopes NW.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 05' W., beginning new measurement.</p> <p>Descend over broken land into Little Coyote Canyon.</p>	

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS	
5.10	Wash in bottom of Little Coyote Canyon, drains E.; asc. over broken SE slope.
36.30	NW rim of Little Coyote Canyon, bears NE and SW; thence over rolling land.
39.95	The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">T32N R5W $\frac{S\ 11}{S\ 14} \frac{S\ 12}{S\ 13}$</p>
	<p style="text-align: center;">1917</p>
	<p>from which original bearing trees</p> <p>A juniper, 5 ins. diam., bears N. 21° 40' E., 74 lks. dist., with scribe marks T32N R5W S12 BT visible on open blaze.</p> <p>A juniper, 6 ins. diam., bears S. 70° 25' E., 71 lks. dist., with scribe marks T32N R5W S13 BT visible on open blaze.</p> <p>A juniper, 9 ins. diam., bears S. 47° 50' W., 86 lks. dist., with scribe marks T32N R5W S14 BT visible on open blaze.</p> <p>A juniper, 6 ins. diam., bears N. 64¼° W., 190 lks. dist., with scribe marks T32N R5W S11 BT visible on open blaze.</p>
	<p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., as described in the field notes of the dependent resurvey of the W. bdy. of T. 32 N., R. 4 W., executed concurrently with this group.</p>
	<p>S. 89° 35' W., bet. secs. 12 and 13.</p>
	<p>Over rolling land, through dense undergrowth.</p>
16.80	Draw, drains NW.
22.40	Draw, drains N.
27.00	Enter level land, with scattered timber, bears N. and S.
40.12	The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a collar of stone, 2½ ft. base, 1 ft. high, with brass cap mkd.
	<p style="text-align: center;">1/4 $\frac{S\ 12}{S\ 13}$</p>
	<p style="text-align: center;">1917</p>
	<p>I add marks T32N R5W 1975 on the brass cap.</p>

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS	
	<p>from which original bearing trees</p> <p>A juniper, 6 ins. diam., bears N. 49° 40' E., 78 lks. dist., with scribe marks 1/4 S12 BT visible on open blaze.</p> <p>A juniper, 7 ins. diam., bears S. 24° 40' W., 225 lks. dist., with scribe marks 1/4 S13 BT visible on open blaze.</p> <hr/> <p>S. 89° 32' W., beginning new measurement.</p> <p>Over level land, through scattered juniper and dense sage brush.</p>
6.30	E. rim of Little Coyote Canyon, bears N. and S.; desc. over steep broken W. slope.
22.30	Wash in bottom of Little Coyote Canyon, drains NNE; asc. steep broken E. slope.
40.28	The cor. of secs. 11, 12, 13 and 14.
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89° 54' W., bet. secs. 14 and 23.</p> <p>Over rolling land, through scattered timber and dense undergrowth.</p>
9.30	Draw, drains N.
25.30	Ridge, bears N. and S.
39.86	The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a collar of stone, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S \ 14 \\ S \ 23 \end{array}$ <p>1917</p>
	<p>I add marks T32N R5W 1975 on the brass cap.</p> <p>Rebuild collar of stone, 3 ft. base to cap.</p> <hr/> <p>S. 89° 30' W., beginning new measurement.</p> <p>Over broken land.</p>
5.40	Wash, drains N.
17.40	Spur, slopes SW.
23.70	Wash, drains SE.
31.00	Same wash, drains NE.
40.05	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS		
	<p style="text-align: center;">T32N R5W S 15 S 14 S 22 S 23</p> <p style="text-align: center;">1917</p> <p>from which remains of the original bearing trees</p> <p>A juniper, 9 ins. diam., bears S. 64° 20' E., 130 lks. dist., with scribe marks T32N R5W S23 BT visible on open blaze.</p> <p>A juniper, 6 ins. diam., bears S. 8° 20' W., 160 lks. dist., with scribe marks T32N R5W S22 BT visible on open blaze.</p> <p>Cor. is located at cor. of fences, extends N. and SE.</p>	
<p>33.20</p> <p>40.00</p>	<p>N. 0° 14' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through scattered timber and undergrowth, along a fence, bearing N. and S.</p> <p>Draw, drains SSE.</p> <p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a small collar of stone, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 15 S 14</p> <p style="text-align: center;">1917</p> <p>I add marks T32N R5W 1975 on the brass cap.</p> <p>Cor. is located in fence, bears N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 04' E., beginning new measurement.</p> <p>Over rolling land, along a fence bearing N. and S.</p>	
<p>6.60</p> <p>39.96</p>	<p>Limestone ledge, 5 ft. high, bears E. and W., continue over level land.</p> <p>The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R5W S 10 S 11 S 15 S 14</p> <p style="text-align: center;">1917</p> <p>Cor. is located at cor. of fences, extends S. and W.</p>	
	<p>From the cor. of secs. 11, 12, 13, and 14.</p>	

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS	
	S. 89° 52' W., bet. secs. 11 and 14.
	Over rolling land, through scattered timber and undergrowth.
8.00	Spur, slopes SE.
17.20	Draw, drains SE.
39.87	The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, supported with a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S \ 11 \\ S \ 14 \end{array}$
	1917
	I add marks T32N R5W 1975 on the brass cap.
	S. 89° 56' W., beginning new measurement.
	Over gently rolling grassland.
27.50	Wash, drains NE.
40.05	The cor. of secs. 10, 11, 14, and 15.
	From the cor. of secs. 14, 15, 22, and 23.
	S. 89° 57' W., bet. secs. 15 and 22.
	Over rolling land, through scattered timber.
15.00	Enter level grassland, bears N. and S.
39.78	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a small collar of stone, with brass cap mkd.
	$\frac{1}{4} \begin{array}{l} S \ 15 \\ S \ 22 \end{array}$
	1917
	I add marks T32N R5W 1975 on the brass cap.
	N. 89° 57' W., beginning new measurement.
	Over level grassland.
5.70	Begin ascent over rocky E. slope.
39.20	Trail road, bears NE and SW.
40.25	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS		
	<p style="text-align: center;">T32N R5W S 16 S 15 S 21 S 22</p> <p style="text-align: center;">1917</p> <p>from which the original bearing tree</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 0° 10' E., 343 lks. dist., with scribe marks T32N R5W S15 BT visible on open blaze.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>	
28.60	<p>N. 0° 02' W., bet. secs. 15 and 16.</p> <p>Over gently rolling land, through dense undergrowth.</p> <p>Trail road, bears NNW and SSE.</p>	
40.00	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, supported with a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 16 S 15</p> <p style="text-align: center;">1917</p> <p>I add marks T32N R5W 1975 on the brass cap.</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>N. 0° 13' E., beginning new measurement.</p> <p>Over gently rolling land.</p>	
15.40	<p>Trail road, bears NNE and SSW; thence along W. side of road.</p>	
40.01	<p>The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R5W S 9 S 10 S 16 S 15</p> <p style="text-align: center;">1917</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located in fence, bears E. and W.</p>	
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89° 56' W., bet. secs. 10 and 15.</p>	

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R 5 W., G&SR Mer., Arizona

CHAINS		
	<p>Over gently rolling land, through moderate undergrowth, along a fence bearing E. and W.</p>	
39.98	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, with brass cap mkd.</p>	
	<p style="text-align: center;">1/4 $\frac{S\ 10}{S\ 15}$</p>	
	<p style="text-align: center;">1917</p>	
	<p>I add marks T32N R5W 1975 on the brass cap.</p>	
	<p>Cor. is located in fence, bears E. and W.</p>	
	<p style="text-align: center;">_____</p>	
	<p>N. 89° 57' W., beginning new measurement.</p>	
	<p>Over gently rolling land.</p>	
39.81	<p>The cor. of secs. 9, 10, 15, and 16.</p>	
	<p>From the cor. of secs. 15, 16, 21, and 22.</p>	
	<p>S. 89° 50' W., bet. secs. 16 and 21.</p>	
	<p>Over gently rolling land, through moderate undergrowth.</p>	
39.92	<p>The 1/4 sec. cor. of secs. 16 and 21, monumented with an iron post, 1 in. diam., firmly set, projecting 15 ins. above ground, in a small mound of stone, with brass cap mkd.</p>	
	<p style="text-align: center;">1/4 $\frac{S\ 16}{S\ 21}$</p>	
	<p style="text-align: center;">1917</p>	
	<p>I add marks T32N R5W 1975 on the brass cap.</p>	
	<p style="text-align: center;">_____</p>	
	<p>S. 89° 31' W., beginning new measurement.</p>	
	<p>Over gently rolling land.</p>	
40.08	<p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T32N R5W $\frac{S\ 17\ S\ 16}{S\ 20\ S\ 21}$</p>	
	<p style="text-align: center;">1917</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>	
	<p>N. 0° 07' E., bet. secs. 16 and 17.</p>	
	<p>Over gently rolling land, through moderate undergrowth.</p>	

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS		
39.99	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">1/4 S 17 S 16</p> <p style="text-align: center;">1917</p> <p>I add marks T32N R5W 1975 on the brass cap.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 03' W., beginning new measurement.</p> <p>Over gently rolling land.</p>	
40.00	<p>The cor. of secs. 8, 9, 16, and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T32N R5W S 8 S 9 S 17 S 16</p> <p style="text-align: center;">1917</p> <p>Cor. is located in fence, bears E. and W.</p> <p>From this cor., the U. S. Coast and Geodetic Survey triangulation station "TENDERFOOT", bears N. 24° 18' E., 120.15 chs. dist., monumented with a brass tablet, 3 1/4 ins. diam., cemented in a drill hole, in a sandstone outcrop, with cap mkd. TENDERFOOT 1934.</p>	
	<p>From the cor. of secs. 9, 10, 15, and 16.</p> <p>S. 89° 40' W., bet. secs. 9 and 16.</p> <p>Over gently rolling land, through moderate undergrowth, along a fence, bears E. and W.</p>	
40.04	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">1/4 $\frac{S 9}{S 16}$</p> <p style="text-align: center;">1917</p> <p>I add marks T32N R5W 1975 on the brass cap.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 39' W., beginning new measurement.</p>	
11.00	<p>Wash, drains NW.</p>	
40.02	<p>The cor. of secs. 8, 9, 16, and 17.</p> <hr/> <p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 89° 51' W., bet. secs. 17 and 20.</p>	

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS	
	Over gently rolling land, through moderate undergrowth.
39.97	The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, supported with a mound of stone, 2½ ft. base, 1½ ft. high, with brass cap mkd.
	1/4 $\frac{S\ 17}{S\ 20}$
	1917
	I add marks T32N R5W 1975 on the brass cap.
	S. 89° 49' W., beginning new measurement.
	Over gently rolling land.
31.40	Wash, drains N.
32.90	Trail road, bears N. and S.
39.96	The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.
	T32N R5W $\frac{S\ 18 S\ 17}{S\ 19 S\ 20}$
	1917
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.
	S. 89° 54' W., bet. secs. 18 and 19.
	Over gently rolling land, through moderate undergrowth.
39.99	The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, in a collar of stone, with brass cap mkd.
	1/4 $\frac{S\ 18}{S\ 19}$
	1917
	I add marks T32N R5W 1975 on brass cap.
	Rebuild mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
	S. 89° 46' W., beginning new measurement.
	Over gently rolling land.
10.60	Wash, drains NE.
24.50	Enter scattered timber, bears N. and S.

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS	
37.29	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 32 N., R. 6 W., executed concurrently with this group.
	From the cor. of secs. 17, 18, 19, and 20. N. 0° 02' W., bet. secs. 17 and 18. Over gently rolling land, through moderate undergrowth.
19.80	Trail road, bears NNW and SSE.
22.00	Wash, drains NW.
39.97	The 1/4 sec. cor. of secs. 17 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, supported with a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd. 1/4 S 18 S 17 1917 I add marks T32N R5W 1975 on brass cap. N. 0° 01' W., beginning new measurement. Over gently rolling land.
4.50	Wash, drains NNE.
7.50	Trail road, bears NNE and SSW.
40.01	The cor. of secs. 7, 8, 17, and 18, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, with brass cap mkd. T32N R5W S 7 S 8 S 18 S 17 1917 Cor. is located in fence, bears E. and W.
	From the cor. of secs. 8, 9, 16, and 17. S. 89° 46' W., bet. secs. 8 and 17. Over gently rolling land, through moderate undergrowth, along a fence bearing E. and W.
35.00	Wash, drains NNW.
39.97	The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, in a collar of stone, with brass cap mkd.

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 N., R. 5 W., G&SR Mer., Arizona

CHAINS	
	<p style="text-align: center;"> $1/4 \frac{S 8}{S 17}$ 1917 </p> <p>I add marks T32N R5W 1975 on the brass cap.</p> <p>Cor. is located in fence, bears E. and W.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89° 54' W., beginning new measurement.</p> <p>Over gently rolling land, along a fence bearing E. and W.</p> <p>30.00 Trail road, bears N. and S.</p> <p>32.00 Wash, drains N.</p> <p>40.06 The cor. of secs. 7, 8, 17, and 18.</p>
	<p style="text-align: center;">General Description</p> <p>The lands included in the notes of the foregoing survey are located about 45 miles west of Grand Canyon, Arizona and about 8 miles southwest of Supai Indian Village, Arizona. The terrain is gently rolling to nearly level plateau. The area is drained by a number of tributaries of the Grand Canyon River and by Little Coyote Canyon, located in the southeast part of the township. Elevations range from 5200 feet above sea level in the bottom of Little Coyote Canyon to about 6000 feet above sea level near the corner of sections 13, 18, 19, and 24 on the west boundary of the township.</p> <p>Access into the area is limited to a few trail roads. Soil in the area is sandy loam with a few limestone outcroppings around Little Coyote Canyon.</p> <p>Timber consists of scattered juniper in the east part of the township; with undergrowth of sagebrush and native grasses.</p> <p>The area is valuable mainly for grazing. No mineral deposits were noted during the course of the survey.</p> <p>The average of a number of readings throughout the area gives a value of $14\frac{1}{2}^{\circ}$ E. for the mean magnetic declination. There was no noted difference in local attraction.</p>


CERTIFICATE OF SURVEY

(I ~~was~~), Gilbert V. Olson, _____, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23rd day
 of May, 1975, (I ~~was~~) have dependently resurveyed a portion of
 the subdivisional lines, Township 32 North, Range 5 West,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~XVS~~ and under (my)
~~own~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

March 10, 1977

 (Date)



 (Cadastral Surveyor)
 Gilbert V. Olson

 (Date)

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the subdivisional
 lines, Township 32 North, Range 5 West, Gila and Salt River Meridian, Arizona,

executed by Gilbert V. Olson, Supervisory Cadastral Surveyor,
 having been critically examined and found correct, are hereby approved.

FEB 14 1979

 (Date)



 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

 (Date)

 (Chief, Division of Cadastral Survey) GPO 849-626