

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY

A PORTION OF THE SUBDIVISIONAL LINES

AND

A PORTION OF THE SUBDIVISION LINES WITHIN SECTION 34

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES

WITHIN SECTIONS 34 AND 35

THE METES-AND-BOUNDS SURVEY OF PARCELS A AND B, SECTION 34

AND

PARCEL D, SECTION 35

AND

THE SURVEY OF TRACTS 38, 39, AND 40

TOWNSHIP 7 SOUTH, RANGE 16 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

## EXECUTED BY

DOUGLAS A. CODY

CADASTRAL SURVEYOR

RAY HARPIN

CADASTRAL SURVEYOR

Under special instructions dated OCTOBER 14, 1969, approved OCTOBER 27, 1969,  
AND THE SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED NOVEMBER 20, 1969,

APPROVED NOVEMBER 21, 1969, which provided for the surveys included under ~~XXXXXX~~ Group  
Number 517, and assignment instructions dated OCTOBER 14, 1969.

Survey commenced NOVEMBER 19, 1974

Survey completed DECEMBER 5, 1974

1A

**BOOK 5101**

**INDEX DIAGRAM**

Township 7 SOUTH, Range 16 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
				13	
31	32	33	34 9	35 7	36
		14	4	2	

Dependent Resurvey of the Subdivision of Section 34 . . . . . pp. 15  
 Subdivision of Section 34 . . . . . pp. 21  
 Subdivision of Section 35 . . . . . pp. 22  
 Metes-and-Bounds Survey of Parcel A, Section 34 . . . . . pp. 30  
 Metes-and-Bounds Survey of Parcel B, Section 34 . . . . . pp. 30  
 Metes-and-Bounds Survey of Parcel D, Section 35 . . . . . pp. 31  
 Survey of Tract 38. . . . . pp. 32  
 Survey of Tract 39. . . . . pp. 34  
 Survey of Tract 40. . . . . pp. 35

Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the south boundary of the township, a portion of the subdivisional lines, and a portion of the subdivision lines within Section 34; the survey of a portion of the subdivision lines within Sections 34 and 35, the metes-and-bounds survey of Parcels A and B, Section 34 and Parcel D, section 35, and the survey of Tracts 38, 39, and 40, Township 7 South, Range 16 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The south boundary and the subdivisional lines were surveyed by John L. Harris, U. S. Deputy Surveyor, in 1878, as shown upon the official plat approved 1st April 1878. A portion of the subdivisional lines were dependently surveyed and a portion of the subdivision lines within sections 27 and 34 were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952, as shown upon the official plat, examined and approved by the Bureau of Reclamation, Washington, D. C., July 17, 1953, and accepted by the Bureau of Land Management, Chief, Branch of Surveys (Cadastral), July 17, 1953. A portion of the subdivisional lines and subdivision lines were dependently resurveyed and a portion of the subdivision lines were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954, as shown upon the official plat, examined and approved by the Bureau of Reclamation, Washington, D. C., March 17, 1955, and was accepted by the Bureau of Land Management, Cadastral Engineering Staff Officer, March 17, 1955.

The dependent resurvey and surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973 Edition, and the Special Instructions dated October 14, 1969 and the Supplemental Special Instructions dated November 20, 1969.

The direction of all lines of these surveys was determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains and reduced to horizontal equivalents.

Prior to the restoration of any corner, all necessary lines of the original survey were retraced and a diligent search was made for any evidence of the original corner monuments and calls of the official record. Identified corners were remonumented in their original positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The data furnished with the Special Instructions give the geographic position of the corner of Sections 1, 2, 35, and 36, on the south boundary of the township, as Latitude  $32^{\circ} 46.0' N.$ , and Longitude  $113^{\circ} 52.0' W.$  The mean magnetic declination is  $14^{\circ}$  East.

Dependent Resurvey of a Portion of the South Boundary  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Restoring the Survey Executed by John L. Harris,  
 U. S. Deputy Surveyor, in 1878

---

Beginning at the corner of secs. 1, 2, 35, and 36 on the south boundary of the township, which is marked with an iron pipe, 2 ins. in. diam., with brass cap 12 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION  
 T7S R16W  
 S 35 | S 36  
 S 2 | S 1  
 T8S

1949

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

---

S. 89° 52' W., between Tps. 7 and 8 S., through R. 16 W., and between secs. 2 and 35

Over nearly level land, along an east and west road.

40.33

The 1/4 sec. cor. of secs. 2 and 35 is marked with an iron pipe, 22 ins. long, 1-inch in diam., with the top 6 ins. below the surface of the road, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.

T7S R16W  
 1/4  $\frac{S\ 35}{S\ 2}$   
 T8S

1974

Deposit the iron pipe marker alongside the iron post.

from which

An electric transmission line pole, bears N. 67° 50' E., 112 lks. distant.

There are no other suitable accessories nor locations available for reference monuments.

---

Dependent Resurvey of a Portion of the South Boundary  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>S. 89° 52' W., beginning new measurement</p>	
	20.18	<p>The point for the west 1/16 sec. cor. of secs. 2 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">W 1/16    <math>\frac{S \ 35}{S \ 2}</math></p> <p style="text-align: center;">1974</p> <p>from which</p> <p style="padding-left: 40px;">An electric transmission line pole, bears N. 56° 20' E., 77 lks. distant.</p> <p>There are no other suitable accessories nor locations available for reference monuments.</p>	
	30.27	<p>The point for the west-west 1/64 sec. cor. of secs. 2 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">S 35 W W 1/64 S 2</p> <p style="text-align: center;">1974</p> <p>from which</p> <p style="padding-left: 40px;">An electric transmission line pole, bears N. 45° 55' E., 58 lks. distant.</p> <p style="padding-left: 40px;">A U. S. Bureau of Reclamation Bench Mark bears N. 34° 15' W., 62 lks. distant, and is marked with a brass tablet seated in a concrete headwall, mkd. BM EL. 285.95.</p>	
	40.36	<p>The corner of secs. 2, 3, 34, and 35 is marked with a redwood post, 24 ins. long, 4 ins. square, with the top 6 ins. below the surface of the road,</p> <p>substantiated by:</p> <p style="padding-left: 40px;">An (capped) iron pipe, 2 ins. in diam., firmly set, projecting 2 ft. above the surface of the ground, bears S. 41° 05' W., 78 ft. distant, mkd. RP 78.</p> <p style="padding-left: 40px;">An electric transmission line pole, bears N. 46° 40' W., 37.1 ft. distant, mkd. RP 37.1.</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>	

Dependent Resurvey of a Portion of the South Boundary  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.

T7S R16  
 S 34 | S 35  
 S 3 | S 2  
 T8S

1974

Deposit the redwood post corner marker alongside the iron post.

---

Restoring the Survey Executed by Albin H. Wadin,  
 Engineer, Bureau of Reclamation, in 1954

---

S. 89° 51' W., between secs. 3 and 34

Over nearly level land, along an east and west road.

20.17 The east 1/16 sec. cor. of secs. 3 and 34 is marked with an iron pipe, 1-inch in diam., with brass cap 12 ins. below the surface of the road, mkd.

E 1/16    S 34  
           S 3

1950

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.

---

S. 89° 51' W., beginning new measurement

5.55 The point for Angle Point No. 4, Tract 40, Tp. 7 S., R. 16 W. and Angle Point No. 1, Tract 39, Tp. 8 S., R. 16 W.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.

TR 40 / T7S  
 AP 4 / R16W  
 AP 1 / S 34  
 TR 39 / S 3  
           T8S R16W

1974

from which

Dependent Resurvey of a Portion of the South Boundary  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears S. 33° 40' W., 71 lks. distant, with brass cap mkd. RM T8S R16W S3 1974, and an arrow pointing to the corner.</p> <p>An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears N. 54° 40' W., 72 lks. distant, with brass cap mkd. RM T7S R16W AP4 TR 40 1974, and an arrow pointing to the corner.</p>
8.94	<p>The point for Angle Point No. 4, Lot 12 and Angle Point No. 2, Lot 13, Tp. 7 S., R. 16 W., and Angle Point No. 2, Lot 8 and Angle Point No. 1, Lot 10, Tp. 8 S., R. 16 W., which is determined at record distance on this township line; there is no evidence of the original corner.</p>
	<p style="text-align: center;">MEMORANDUM</p> <p>The above lot corner was established by Albin H. Wadin, in 1954. The area of these lots have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots and tracts, are described in this survey.</p>
16.93	<p>The corner, Angle Point No. 4, Lot 11 and Angle Point No. 3, Lot 12, Tp. 7 S., R. 16 W., is marked with an iron pipe, 1-inch in diam., with brass cap 6 ins. below the surface of the road and marked for the above corner. I removed and destroyed the above brass cap.</p>
	<p style="text-align: center;">MEMORANDUM</p> <p>The above lot corner was established by Albin H. Wadin, in 1954. The area of these lots have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots and tracts are described in this survey.</p>
20.17	<p>The 1/4 sec. cor. of secs. 3 and 34 is marked with an iron pipe, 1-inch in diam., with brass cap 6 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;">1/4 <math>\frac{S \ 34}{S \ 3}</math></p> <p style="text-align: center;">1949</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears N. 33° 40' E., 55 lks. distant, with brass cap mkd. RM T7S R16W S34 1974, and an arrow pointing to the corner.</p>

Dependent Resurvey of a Portion of the South Boundary  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS


An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears N. 43° 00' W., 61 lks. distant, with brass cap mkd. RM T7S R16W S34 1974, and an arrow pointing to the corner.

This corner is designated to function for Angle Point No. 2, Tract 39, Tp. 8 S., R. 16 W.

S. 89° 51' W., beginning new measurement

8.80 The point for Angle Point No. 3, Tract 40, Tp. 7 S., R. 16 W.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.




from which

An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears N. 44° 05' E., 67 lks. distant, with brass cap mkd. RM T7S R16W S34 1974, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears S. 36° 40' E., 66 lks. distant, with brass cap mkd. RM T8S R16W S3 1974, and an arrow pointing to the corner.

20.17 The west 1/16 sec. cor. of secs. 3 and 34 is marked with an iron pipe, 1-inch in diam., with brass cap 4 ins. below the surface of the road, mkd.



The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.

from which

An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears N. 48° 40' E., 73 lks. distant, with brass cap mkd. RM T7S R16W S34 1974, and an arrow pointing to the corner.

Dependent Resurvey of a Portion of the South Boundary  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS

20.17

An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears S. 47° 05' E., 68 lks. distant, with brass cap mkd. RM T8S R16W S3 1974, and an arrow pointing to the corner.

S. 89° 51' W., beginning new measurement

The corner of secs. 3, 4, 33, and 34 is marked with an iron pipe, 2 ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION  
 T7S R16W  
 S 33 | S 34  
 S 4 | S 3  
 T8S

1949

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.

from which

A (capped) iron pipe, 2 ins. in diam., firmly set, projecting 2 ft. above the surface of the ground, bears S. 69° 50' E., 116 lks. distant.

Discontinue the dependent resurvey of the township line at this corner.

Dependent Resurvey of a Portion  
 of the Subdivisional Lines  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by John L. Harris,  
 U. S. Deputy Surveyor, in 1878

From the corner of secs. 1, 2, 35, and 36 on the south boundary of the township, heretofore described.


N. 0° 06' E., between secs. 35 and 36

Over nearly level land, along a north and south road.

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS		
40.47	<p>The 1/4 sec. cor. of secs. 35 and 36 is marked with a steel rod, 1/2-inch in diam., with the top flush with the surface of the road, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>A copper-coated steel stake, 30 ins. long, 1/2-inch in diam., placed and driven on top of the steel rod corner marker, with brass cap 1 1/2 ins. in diam. flush with the surface of the road, mkd.</p> <p style="text-align: center;">T7S R16W 1/4</p> <p style="text-align: center;">S 35   S 36</p> <p style="text-align: center;">1974</p> <p>from which</p> <p style="text-align: center;">An (capped) iron pipe, 2 ins. diam., firmly set, projecting 2 ft. above the surface of the ground, bears N. 39° 05' E., 128 lks. distant.</p> <p>There are no other suitable accessories nor locations available for reference monuments.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 06' E., beginning new measurement</p>	
20.24	<p>The point for the north 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., with brass cap 1 1/2 ins. in diam. flush with the surface of the road, mkd.</p> <p style="text-align: center;">N 1/16</p> <p style="text-align: center;">S 35   S 36</p> <p style="text-align: center;">1974</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>	
24.58	<p>The point for Cor. No. 5, Parcel D, sec. 35.</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., with brass cap 1 1/2 ins. in diam. flush with the surface of the road, mkd.</p> <p style="text-align: center;">PARCEL D   COR 5  </p> <p style="text-align: center;">S 35   S 36 T7S R16W</p> <p style="text-align: center;">1974</p>	

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS		
39.82	<p>The point for Corner No. 1, Parcel D, sec. 35</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., with brass cap 1½ ins. in diam., flush with the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T7S R16W S 35   S 36</p>  <p>COR 1 PARCEL D</p> <p>1974</p> </div>	
40.48	<p>The cor. of secs. 25, 26, 35, and 36 is marked with a steel rod, 1/2-inch in diam., with the top flush with the surface of the road, and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>A copper-coated steel stake, 30 ins. long, 1/2-inch in diam., placed and driven on top of the steel rod corner marker, with brass cap 1½ ins. in diam., flush with the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T7S R16W S 26   S 25 S 35   S 36</p> <p>1974</p> </div> <p>from which</p> <p>An (capped) iron pipe, 2 ins. in diam., firmly set, projecting 2 ft. above the surface of the ground, bears N. 49° 00' E., 74 lks. distant.</p> <p>There are no other suitable accessories nor locations available for reference monuments.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p style="text-align: center;">Restoring the Survey Executed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954</p> <hr/> <p>From the corner of secs. 2, 3, 34, and 35 on the south boundary of the township, heretofore described.</p> <p>N. 0° 22' E., between secs. 34 and 35</p> <p>Over nearly level land, along a north and south road.</p>	
20.08	<p>The south 1/16 sec. cor. of secs. 34 and 35 is marked with an iron pipe, 1-inch diam., with brass cap 24 ins. below the surface of the road, mkd.</p>	

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS

S 1/16

S 34 | S 35

1949

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. This iron pipe corner marker is rusted in two below the brass cap.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., over the lower portion of the above iron pipe corner marker, with brass cap 6 ins. below the surface of the road, mkd.

S 1/16

S 34 | S 35

1974

Deposit the brass cap and the upper portion of the above iron pipe corner marker alongside the iron post.

from which

An electric transmission line pole, bears N. 14° 25' W., 175 lks. distant.

There are no other suitable accessories nor locations available for reference monuments.

N. 0° 22' E., beginning new measurement

1.90 The point for Angle Point No. 5, Tract 39 and Angle Point No. 5, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.

TR 40 | TR 39  
AP 5 | AP 5  
-----  
S 34 | S 35  
T7S R16W

1974

from which

An electric transmission line pole, bears S. 64° 25' W., 49 lks. distant.

There are no other suitable accessories nor locations available for reference monuments.

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS		
20.08	<p>The 1/4 sec. cor. of secs. 34 and 35 is marked with an iron pipe, 1-inch in diam., with brass cap 12 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION 1/4 S 34   S 35 1950</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.</p> <p>There are no suitable accessories nor locations available for reference monuments.</p> <p>This corner is designated to function for Corner No. 3, Parcel B, Section 34, Angle Point No. 4, Tract 39, and Angle Point No. 1, Tract 40.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 23' E., beginning new measurement</p>	
1.84	<p>The point for Corner No. 4, Parcel A and Corner No. 1, Parcel B, Section 34, and Angle Point No. 3, Tract 39.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T7S R16W S 34   S 35 PARCEL A COR 4 COR 1   AP 3 PARCEL B   TR 39 1974</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>	
15.16	<p>Angle Point No. 5, Lot 5 and Angle Point No. 1, Lot 6, Section 34 is marked with an iron pipe, 36 ins. long, 1-inch in diam., with brass cap 12 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T7S R16W L 5   AP 5   S 35 AP 1   L 6   S 34 1954</p>	

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona


CHAINS

MEMORANDUM

The above lot corner was established by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. The area of lot 6 of section 34 having been acquired (United States ownership). The description, lot No. 6, and the corners controlling the position of this lot is voided by this survey. The area described by this survey is now designated Parcels A and B of section 34.

At the corner point, this corner is designated to function for Corner No. 1, Parcel A, section 34, and is to continue to function for Angle Point No. 5, lot 5 of section 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.



1974

Deposit the iron pipe corner marker alongside the iron post.

There are no suitable accessories nor locations available for reference monuments.

---

N. 0° 23' E., beginning new measurement

4.92 The north 1/16 sec. cor. of secs. 34 and 35 is marked with an iron pipe, 1-inch in diam., with brass cap 18 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION  
N 1/16

S 34 | S 35

1950

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.

There are no suitable accessories nor locations available for reference monuments.

---

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS						
10.98	<p>N. 0° 23' E., beginning new measurement</p> <p>Angle Point No. 5, Lot 1 and Angle Point No. 1, Lot 2, Section 34 is marked with an iron pipe, 1-inch in diam., with brass cap 18 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION T7S R16W</p> <p>1954</p> </div>					
9.09	<p>N. 0° 23' E., beginning new measurement</p> <p>The cor. of secs. 26, 27, 34, and 35 is marked with an iron pipe, 2 ins. diam., with brass cap 8 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION T7S R16W</p> <table border="1" style="margin: auto;"> <tr> <td>S 27</td> <td>S 26</td> </tr> <tr> <td>S 34</td> <td>S 35</td> </tr> </table> <p>1950</p> </div> <p>substantiated by:</p> <p>A cross (+) chiseled on concrete headwall of a lateral, bears S. 58° 35' W., 56 ft. distant, mkd. RP + 56.</p> <p>A cross (+) chiseled on concrete headwall of a lateral, bears N. 61° 15' W., 55 ft. distant, mkd. RP + 55.</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.</p> <hr/> <p style="text-align: center;">Restoring the Survey Executed by John L. Harris, U. S. Deputy Surveyor, in 1878</p> <hr/> <p>From the cor. of sec. 25, 26, 35, and 36, heretofore described.</p> <p>S. 89° 24' W., between secs. 26 and 35</p> <p>Over nearly level land.</p>	S 27	S 26	S 34	S 35	
S 27	S 26					
S 34	S 35					

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

<p>CHAINS 20.15</p>	<p>The point for the east 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 <math>\frac{S\ 26}{S\ 35}</math></p> <p style="text-align: center;">1974</p>
<p>40.30</p>	<p>The 1/4 sec. cor. of secs. 26 and 35 is marked with an iron pipe, 1-inch in diam., with brass cap 6 ins. below the surface of the roadway, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION 1/4 <math>\frac{S\ 26}{S\ 35}</math></p> <p style="text-align: center;">1949</p>
	<p>The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 24' W., beginning new measurement</p>
<p>20.00</p>	<p>The west 1/16 sec. cor. of secs. 26 and 35 is marked with an iron pipe, 1-inch in diam., with brass cap 6 ins. below the surface of the roadway, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 <math>\frac{S\ 26}{S\ 35}</math></p> <p style="text-align: center;">1950</p>
	<p>The above corner marker is accepted as the position of the corner. This corner was not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 24' W., beginning new measurement</p>
<p>20.00</p>	<p>The corner of secs. 26, 27, 34, and 35, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 3, 4, 33, and 34 on the south boundary of the township, heretofore described.</p> <p>N. 0° 24' E., between secs. 33 and 34</p> <p>Over nearly level land, along a north and south road.</p>


Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS	
20.01	<p>The point for the south 1/16 sec. cor. of secs. 33 and 34.</p> <p>Set a copper-coated steel stake, 18 ins. long, 1/2-inch in diam., with brass cap 1½ ins. in diam., flush with the surface of the road, mkd.</p> <p style="text-align: center;">S 1/16</p> <p style="text-align: center;">S 33 S 34</p> <p style="text-align: center;">1974</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>
40.02	<p>The 1/4 sec. cor. of secs. 33 and 34 is marked with a steel rod, 1/2-inch in diam., with the top flush with the surface of the road,</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A cross (+) chiseled on concrete headwall of a lateral, bears S. 63° 50' W., 38 ft. distant, mkd. RP + 38.</p> <p style="padding-left: 40px;">A cross (+) chiseled on concrete headwall of a lateral, bears N. 67° 00' W., 49 ft. distant, mkd. RP + 49.</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>A copper-coated steel stake, 18 ins. long, 1/2-inch in diam., placed and driven on top of the steel rod corner marker, with brass cap 1½ ins. in diam., flush with the surface of the road, mkd.</p> <p style="text-align: center;">BLM 1/4</p> <p style="text-align: center;">S 33 S 34</p> <p style="text-align: center;">1974</p> <p>Discontinue the dependent resurvey of the subdivisional lines at this corner.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivision Lines within Section 34 Township 7 South, Range 16 West Gila and Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">Restoring the Survey Executed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 34 on the south boundary of the township, heretofore described.</p> <p>N. 0° 24' E., on a blank line across Tract 40, the north and south center line of sec. 34</p>
7.53	<p>Intersect line 2 - 3, Tract 40. The point for the closing corner of sec. 34.</p>

Dependent Resurvey of a Portion of the  
 Subdivision Lines within Section 34  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.




1974

From this closing corner Angle Point No. 3, Tract 40, heretofore described, bears S. 49° 33.6' W., 11.64 chs. distant.

20.04

The center-south 1/16 sec. cor. of sec. 34 is marked with an iron pipe, 1-inch in diam., with brass cap 9 ins. below the surface of the ground, mkd.

BUREAU OF RECLAMATION



1950

The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. I did not remonument this corner.

---

N. 0° 23' E., beginning new measurement

20.04

The center 1/4 sec. cor. of sec. 34 is marked with an iron pipe, 1-inch in diam., with brass cap 8 ins. below the surface of the ground, mkd.

C 1/4 S 34

1950

The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1955. This iron pipe corner marker is rusted in two just below the brass cap.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., over the lower portion of the above iron pipe corner marker, with brass cap flush with the surface of the ground, mkd.

T7S R16W  
 C 1/4 S 34

1974

Dependent Resurvey of a Portion of the  
 Subdivision Lines within Section 34  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Deposit the brass cap and the upper portion of the above iron pipe corner marker alongside the iron post.

There are no suitable accessories nor locations available for reference monuments.


Discontinue the regular order of survey at this corner.

From the 1/4 sec. cor. of secs. 34 and 35, which is designated to function for Corner No. 3, Parcel B, Section 34, Angle Point No. 4, Tract 39, and Angle Point No. 1, Tract 40, heretofore described.

S. 89° 47' W., on the east and west center line of sec. 34.


2.16 The point for Corner No. 3, Parcel A, Corner No. 2, Parcel B, Section 34, and Angle Point No. 2, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.



1974

10.13 Angle Point No. 4, at 5, Angle Point No. 2, Lot 6, Angle Point No. 2, Lot 7, and Angle Point No. 1, Lot 8, and is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 30 ins. in the ground, with brass cap mkd.



1954

MEMORANDUM


The above lot corner was established by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. The area of lot No. 6 of section 34 having been acquired (United States ownership). The areas of lots 7 through 15 inclusive, and the SE¼ of the SW¼ of section 34 are vacant (United States ownership). The descriptions, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of Parcels A and B; Lots 16 through 21 inclusive, within section 34; and Tract 40 are described in this survey.

At the corner point, this corner is designated to function for Corner No. 2, Parcel A and continues as Angle Point No. 4, Lot 5, Section 34.

Dependent Resurvey of a Portion of the  
 Subdivision Lines within Section 34  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.



1974

Deposit the iron pipe corner marker alongside the iron post.

From this corner a diligent search was made for any evidence of the corner, Angle Point No. 3, Lot 7 and Angle Point No. 5, Lot 8, Section 34, and none was found.

---

S. 89° 47' W., beginning new measurement

10.03

The center-east 1/16 sec. cor. of sec. 34 is marked with an iron pipe, 1-inch in diam., with brass cap flush with the surface of the road, mkd.

S 34  
 C E 1/16

1952

MEMORANDUM

The above corner was established by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952; it was designated to function for Angle Point No. 3, Lot 3 and Angle Point No. 3, Lot 4. In the 1954 survey, this corner was designated to function for Angle Point No. 3, Lot 5, Angle Point No. 2, Lot 8, Angle Point No. 1, Lot 9, and Angle Point No. 1, Lot 10. The area of Lots 8, 9, and 10, Section 34 have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots are described in this survey.

From the above corner a diligent search was made for any evidence of the corner, Angle Point No. 2, Lot 9 and Angle Point No. 5, Lot 10, Section 34, and none was found.

---

S. 89° 44' W., beginning new measurement

20.16

The center 1/4 sec. cor. of sec. 34, heretofore described.

Discontinue the regular order of survey at this corner.

Dependent Resurvey of a Portion of the  
Subdivision Lines within Section 34  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>From the east 1/16 sec. cor. of secs. 3 and 34 on the south boundary of the township, heretofore described.</p> <p>N. 0° 23' E., on the north and south center line of the southeast quarter of sec. 34</p>	
	4.75	<p>Intersect line 4 - 5, Tract 40. The point for the closing corner of sec. 34; I did not monument this corner point.</p> <p>From this corner point Angle Point No. 4, Tract 40, heretofore described, bears S. 49° 33.6' W., 7.33 chs. distant.</p> <p>Thence, on a blank line across Tract 40</p>	
	11.10	<p>The corner, Angle Point No. 5, Lot 12, Angle Point No. 1, Lot 13, Angle Point No. 3, Lot 14, and Angle Point No. 3, Lot 15 of Section 34, and is marked with an iron pipe, 1-inch in diam., firmly set, projecting 6 ins. above the surface of the ground, with brass cap marked for the above corner. I removed and destroyed the above brass cap.</p>	
		<p>MEMORANDUM</p> <p>The above lot corner was established by Albin H. Wadin, in 1954. The area of these lots have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots and tracts are described in this survey.</p> <p>Thence, continue on a blank line across Tract 40</p>	
	20.06	<p>The southeast 1/16 sec. cor. of sec. 34 is marked with an iron pipe, 1-inch in diam., with brass cap 3 ins. below the surface of the ground, mkd.</p>	
		<p>SE 1/16 S 34  1954</p> <hr style="width: 20%; margin: auto;"/>	
		<p>N. 0° 23' E., beginning new measurement</p>	
	4.71	<p>Intersect line 2 - 3, Tract 40. The point for the closing corner of sec. 34; I did not monument this corner point.</p> <p>From this corner point Angle Point No. 2, Tract 40, heretofore described, bears N. 49° 33.6' E., 23.77 chs. distant.</p>	
	20.07	<p>The center-east 1/16 sec. cor. of sec. 34 which is designated to function for Angle Point No. 3, Lot 4 and Angle Point No. 3, Lot 5, Section 34, heretofore described.</p>	

Dependent Resurvey of a Portion of the  
Subdivision Lines within Section 34  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS	
	From the south 1/16 sec. cor. of secs. 34 and 35, heretofore described
	S. 89° 49' W., on the east and west center line of the southeast quarter of sec. 34.
2.24	Intersect line 4 - 5, Tract 40. The point for the closing corner of sec. 34; I did not monument this corner point.
	From this corner point Angle Point No. 5, Tract 40 which is identical with Angle Point No. 5, Tract 39, heretofore described, bears N. 49° 33.6' E., 2.96 lks. distant.
	Thence, on a blank line across Tract 40
17.59	The corner, Angle Point No. 4, Lot 7, Angle Point No. 4, Lot 8, Angle Point No. 1, Lot 14, and Angle Point No. 2, Lot 15 of section 34, and is marked with an iron pipe, 1-inch in diam., firmly set, projecting 6 ins. above the surface of the ground, with brass cap marked for the above corner. I removed and destroyed the above brass cap.
	MEMORANDUM
	The above lot corner was established by Albin H. Wadin, in 1954. The area of these lots have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots and tracts are described in this survey.
	Thence, continue on a blank line across Tract 40.
20.17	The southeast 1/16 sec. cor. of sec. 34, heretofore described.
	_____
	S. 89° 49' W., beginning new measurement
	Thence, continue on a blank line across Tract 40.
5.52	Intersect line 2 - 3, Tract 40. The point for the closing corner of sec. 34; I did not monument this corner point.
	From this corner point Angle Point No. 3, Tract 40, heretofore described, bears S. 49° 33.6' W., 31.00 chs. distant.
10.58	The corner, Angle Point No. 3, Lot 9, Angle Point No. 4, Lot 10, Angle Point No. 1, Lot 11, and Angle Point No. 2, Lot 12 of Section 34, and is marked with an iron pipe, 1-inch in diam., firmly set, projecting 6 ins. above the surface of the ground, with brass cap marked for the above corner. I removed and destroyed the above brass cap.

Dependent Resurvey of a Portion of the  
Subdivision Lines within Section 34  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS

## MEMORANDUM

The above lot corner was established by Albin H. Wadin, in 1954. The area of these lots have remained vacant (United States ownership). The description, lot numbers and the corners controlling the position of these lots are voided by this survey. New descriptions of lots are described in this survey.

20.17 The center-south 1/16 sec. cor. of sec. 34, heretofore described.

Discontinue the dependent resurvey of the township at this corner.

Survey of a Portion of the Subdivision Lines  
Within Sections 34 and 35  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

Thence, in section 34

From the center 1/4 sec. cor. of sec. 34, heretofore described.

S. 89° 47' W., on the east and west center line of sec. 34

20.17 The point for the center-west 1/16 sec. cor. of sec. 34. The adjacent landowner did not grant permission to monument this corner point or to establish a witness corner, thereto.

40.34 The 1/4 sec. cor. of secs. 33 and 34, heretofore described.

Discontinue the regular order of survey at this corner.

From the west 1/16 sec. cor. of secs. 3 and 34 on the south boundary of the township, heretofore described.

N. 0° 24' E., on the north and south center line of the southwest quarter of sec. 34

20.03 Intersect the east and west center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.

SW 1/16 S 34

1974

Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>There are no suitable accessories nor locations available for reference monuments.</p>
40.06	<p>Intersect the east and west center line, the point for the center-west 1/16 sec. cor. of sec. 34, heretofore described.</p>
	<hr/> <p>From the center-south 1/16 sec. cor. of sec. 34, heretofore described.</p> <p>S. 89° 49' W., on the east and west center line of the southwest quarter of sec. 34.</p>
20.17	<p>Intersect the north and south center line of the southwest quarter, the southwest 1/16 sec. cor. of sec. 34, heretofore described.</p>
40.34	<p>The south 1/16 sec. cor. of secs. 33 and 34, heretofore described.</p>
	<hr/> <p>Thence, in section 35.</p> <p>From the 1/4 sec. cor. of secs. 2 and 35 on the south boundary of the township, heretofore described.</p> <p>N. 0° 08' E., on the north and south center line of sec. 35</p>
20.155	<p>The point for the center-south 1/16 sec. cor. of sec. 35. The adjacent landowners did not grant permission to monument this corner point or to establish a witness corner, thereto.</p>
40.31	<p>The center 1/4 sec. cor. of sec. 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.</p>
	<p style="text-align: center;">BUREAU OF RECLAMATION        C-1/4-C        S 35        1950</p>
	<p>substantiated by:</p> <p style="padding-left: 40px;">A (capped) iron pipe, 2 ins. in diam., firmly set, projecting 2 ft. above the surface of the ground, bears SOUTH, 3 ft. distant, mkd. C 1/4 S35 3 NORTH.</p> <p>The above corner marker is accepted as the position for the corner. This corner was not remonumented.</p> <hr style="width: 20%; margin-left: auto; margin-right: auto;"/>


Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0° 08' E., beginning new measurement.
10.08	The point for the C-S-N 1/64 sec. cor. of sec. 35.  Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">S 35 C S N 1/64  1974</div>
12.38	Intersect line 6 - 1, Tract 38, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 35.  Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">TR 38 C CC   S 35 C T7S R16W  1974</div> <p>Thence, on a blank line across Tract 38</p>
20.16	The point for the center-north 1/16 sec. cor. of sec. 35.  Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">C N 1/16   S 35 C  1974</div> <p>This corner is designated to function for Angle Point No. 2, Tract 38 and Corner No. 3, Parcel D, Section 35.</p> <p>Thence, on a blank line across Parcel D, Section 35.</p>
29.26	Intersect line 1 - 2, Parcel D, Section 35, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 35.  Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">T7S R16W C CC   S 35 C PARCEL D  1974</div>

Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
40.32	The 1/4 sec. cor. of secs. 26 and 35, heretofore described.
	<hr/> From the 1/4 sec. cor. of secs. 35 and 36, heretofore described.
	S. 89° 38' W., on the east and west center line of sec. 35.
20.16	The point for the center-east 1/16 sec. cor. of sec. 35.
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 35 \\ 1974 \end{array}$
40.32	The center 1/4 sec. cor. of sec. 35, heretofore described.
	<hr/> S. 89° 38' W., beginning new measurement
20.09	The point for the center-west 1/16 sec. cor. of sec. 35. The adjacent landowner did not grant permission to monument this corner or to establish a witness corner, there-to.
30.135	The point for the C-W-W 1/64 sec. cor. of sec. 35.
	Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the roadway, mkd.
	$\begin{array}{c} \text{S } 35 \\ \text{C W W} \\ 1/64 \\ 1974 \end{array}$
	This corner is located on line 6 - 1, Tract 39; thence, on a blank line across Tract 39.
40.18	The 1/4 sec. cor. of secs. 34 and 35, which is designated to function for Corner No. 3, Parcel B, Section 34, Angle Point No. 4, Tract 39, and Angle Point No. 1, Tract 40, heretofore described.
	<hr/> From the center-east 1/16 sec. cor. of sec. 35
	N. 0° 07' E., on the north and south center line of the northeast quarter of sec. 35




Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
20.20	Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 35. I did not monument his corner point.
	Thence, on a blank line across Parcel E, Section 35.
20.54	Intersect line 4 - 5, Parcel D, Section 35, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 35. I did not monument this point for the closing corner.
	Thence, on a blank line across Parcel D, Section 35.
36.30	Intersect line 1 - 2, Parcel D, Section 35, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 35. I did not monument this point for the closing corner.
40.40	The east 1/16 sec. cor. of secs. 26 and 35, heretofore described.
	From the north 1/16 sec. cor. of secs. 35 and 36, heretofore described.
	S. 89° 31' W., on the east and west center line of the northeast quarter of sec. 35
20.16	Intersect the north and south center line of the northeast quarter, the northeast 1/16 sec. cor. of sec. 35, heretofore described.
21.29	Intersect the arc of a curve, the point for Corner No. 4, Parcel D, Section 35 and Angle Point No. 1, Tract 38.
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T7S R16W                  S 35                  PARCEL D                  COR 4</p>  <p style="text-align: center;">AP 1                  TR 38</p>
	1974
	Thence, continue on the east and west center line of the northeast quarter, and line 3 - 4, Parcel D, Section 35 and line 1 - 2, Tract 38. The above parcel and tract are hereinafter described.
40.31	Intersect the north and south center line, the center-north 1/16 sec. cor. of sec. 35, which is designated to function for Angle Point No 2, Tract 38 and Corner No. 3, Parcel D, Section 35, heretofore described.

Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the point for the center-west 1/16 sec. cor. of sec. 35, heretofore described.</p>
	<p>N. 0° 16' E., on the north and south center line of the northwest quarter of sec. 35</p>
<p>10.06</p>	<p>The point for the C-S-NW 1/64 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.</p>
	<p style="text-align: center;">S 35                  C S NW                  1/64                    1974</p>
	<p>There are no suitable accessories nor locations available for reference monuments..</p> <p>This corner is designated to function for Angle Point No. 5, Tract 38.</p>
<p>18.03</p>	<p>Intersect the arc of a curve, the point for Angle Point No. 4, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T7S R16W                  W                  S   35                  AP 4                  TR 38                  W                    1974</p>
<p>20.12</p>	<p>Intersect the east and west center line of the northwest quarter, the point for the northwest 1/16 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">NW 1/16 S 35                    1974</p>
<p>40.24</p>	<p>The west 1/16 sec. cor. of secs. 26 and 35, heretofore described.</p>
	<p>From the center-north 1/16 sec. cor. of sec. 35, which is designated to function for Angle Point No. 2, Tract 38 and Corner No. 3, Parcel D, Section 35, heretofore described.</p>

Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
<p>16.90</p>	<p>S. 89° 32' W., on the east and west center line of the northwest quarter of sec. 35, and line 3 - 2, Parcel D, Section 35 and line 2 - 3, Tract 38. The above parcel and tract are hereinafter described.</p> <p>Intersect the arc of a curve, the point for Corner No. 2, Parcel D, Section 35 and Angle Point No. 3, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T7S R16W S 35 PARCEL D COR 2 N ————— N AP 3 TR 38 1974</p> </div>
<p>20.05</p>	<p>Intersect the north and south center line of the northwest quarter, the northwest 1/16 sec. cor. of sec. 35, heretofore described.</p>
<p>30.075</p>	<p>The point for the C-W-NW 1/64 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>S 35 C W NW 1/64 1974</p> </div>
<p>40.10</p>	<p>The north 1/16 sec. cor. of secs. 34 and 35, heretofore described.</p> <hr/> <p>From the C-W-W 1/64 sec. cor. of sec. 35, heretofore described.</p> <p>N. 0° 19' E., on the north and south center line of the SW 1/4 of the NW 1/4 of sec. 35, and along line 6 - 1 (the eastern boundary), Tract 39.</p> <p>10.38</p> <p>Intersect the arc of a curve, the point for Angle Point No. 1, Tract 39.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T7S R16W S 35 AP 1 TR 39 1974</p> </div>

Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
20.10	Intersect the east and west center line of the northwest quarter, the C-W-NW 1/64 sec. cor. of sec. 35, heretofore described.
4.18	<p>From the C-S-N 1/64 sec. cor. of sec. 35, heretofore described.</p> <p>S. 89° 35' W., on the east and west center line of the SE 1/4 of the NW 1/4 of sec. 35</p> <p>Intersect the arc of a curve, the point for Angle Point No. 6, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R16W              TR 38              AP 6              ————              S 35</p> <p>1974</p> </div> <p>Thence, continue on the east and west center line of the SE 1/4 of the NW 1/4 of sec. 35, and on line 6 - 5 (southern boundary), Tract 38.</p>
20.07	Intersect the north and south center line of the northwest quarter, the C-S-NW 1/64 sec. cor. of sec. 35, which is designated to function for Angle Point No. 5, Tract 38, heretofore described.
20.12	<p>From the west 1/16 sec. cor. of secs. 2 and 35 on the south boundary of the township, heretofore described.</p> <p>N. 0° 15' E., on the north and south center line of the southwest quarter of sec. 35</p> <p>Intersect the east and west center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 35. The adjacent landowner did not grant permission to monument this corner point or to establish a witness corner, thereto.</p>
40.24	Intersect the east and west center line, the point for the center-west 1/16 sec. cor. of sec. 35, heretofore described.

Survey of a Portion of the Subdivision Lines  
 Within Sections 34 and 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From this point for the center-south 1/16 sec. cor. of sec. 35, heretofore described.</p> <p>S. 89° 45' W., on the east and west center line of the southwest quarter of sec. 35.</p> <p>20.13 Intersect the north and south center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 35, heretofore described.</p> <p>30.20 The point for the C-W-SW 1/64 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the road, mkd.</p> <p style="text-align: center;">S 35 C W SW 1/64  1974</p> <p>40.27 The south 1/16 sec. cor. of secs. 34 and 35, heretofore described.</p>	
	<p>From the C-W-SW 1/64 sec. cor. of sec. 35, heretofore described.</p> <p>N. 0° 19' E., on the north and south center line of the NW 1/4 of the SW 1/4 of sec. 35.</p> <p>10.48 The point for Angle Point No. 6, Tract 39.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R16W TR 39   S 35 AP 6   1974</p>	
	<p>20.10 Intersect the east and west center line, the center-west-west 1/64 sec. cor. of sec. 35, heretofore described.</p> <p>From the west-west 1/64 sec. cor. of secs. 2 and 35 on the south boundary of the township, heretofore described.</p> <p>N. 0° 19' E., on the north and south center line of the SW 1/4 of the SW 1/4 of sec. 35</p> <p>20.10 Intersect the east and west center line of the southwest quarter, the C-W-SW 1/64 sec. cor. of sec. 35, heretofore described.</p>	

The Metes-and-Bounds Survey of Parcels A and B,  
 Section 34  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Thence, with the survey of Parcel A, Section 34</p>	
	<p>Beginning at Corner No. 1, Parcel A, which is identical with Angle Point No. 5, Lot 5, Section 34, heretofore described.</p>	
	<p>S. 33° 56' W., on line 1 - 2, Parcel A, identical with line 5 - 4, Lot 5, of Section 34.</p>	
18.32	<p>Corner No. 2, Parcel A, which is identical with Angle Point No. 4, Lot 5, Section 34, heretofore described.</p>	
	<p>_____</p>	
	<p>N. 89° 47' E., on line 2 - 3, Parcel A, identical with the east and west center line of sec. 34.</p>	
7.97	<p>Corner No. 3, Parcel A, which is identical with Corner No. 2, Parcel B, Section 34, and Angle Point No. 2, Tract 40, heretofore described.</p>	
	<p>_____</p>	
	<p>N. 49° 33.6' E., on line 3 - 4, Parcel A, identical with line 2 - 1, Parcel B, Section 34.</p>	
2.86	<p>Corner No. 4, Parcel A, which is identical with Corner No. 1, Parcel B, Section 34, and Angle Point No. 3, Tract 39, heretofore described.</p>	
	<p>_____</p>	
	<p>N. 0° 23' E., on line 4 - 1, Parcel A, Section 34, identical with the section line between secs. 34 and 35.</p>	
13.32	<p>Corner No. 1, Parcel A, which is identical with Angle Point No. 5, Lot 5, Section 34, and the place of beginning.</p>	
	<p>_____</p>	
	<p>Thence, with the survey of Parcel B, Section 34</p>	
	<p>Beginning at Corner No. 1, Parcel B, which is identical with Corner No. 4, Parcel A, Section 34, and Angle Point No. 3, Tract 39, heretofore described.</p>	
	<p>S. 49° 33.6' W., on line 1 - 2, Parcel B, identical with line 4 - 3, Parcel A, Section 34</p>	
2.86	<p>Corner No. 2, Parcel B, which is identical with Corner No. 3, Parcel A, Section 34, and Angle Point No. 2, Tract 40, heretofore described.</p>	
	<p>_____</p>	

The Metes-and-Bounds Survey of Parcels A and B,  
Section 34  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>N. 89° 47' E., on line 2 - 3, Parcel B, Section 34, identical with line 2 - 1, Tract 40.</p>	
	2.16	<p>The 1/4 sec. cor. of secs. 34 and 35, which is designated to function for Corner No. 3, Parcel B, Section 34, Angle Point No. 4, Tract 39, and Angle Point No. 1, Tract 40, heretofore described.</p>	
		<p>N. 0° 23' E., on line 3 - 1, Parcel B, Section 34, identical with line 4 - 3, Tract 39, and being the section line between secs. 34 and 35.</p>	
	1.84	<p>Corner No. 1, Parcel B, which is identical with Corner No. 4, Parcel A, Section 34, and Angle Point No. 3, Tract 39, and the place of beginning.</p>	
		<p>The Metes-and-Bounds Survey of Parcel D, Section 35 Township 7 South, Range 16 West Gila and Salt River Meridian, Arizona</p>	
		<p>Beginning at Corner No. 1, Parcel D, Section 35, heretofore described.</p> <p>Thence, on line 1 - 2, Parcel D, Section 35, along the arc of a curve, curve data:</p> <p>Radius 128.79 chs. distant Length of arc 61.23 chs. distant Length of chord 60.65 chs. distant, and bears S. 70° 41' 17" W.</p> <p>At 20.51 chs. distant on the arc of the curve. Intersect the north and south center line of the northeast quarter, the point for the closing corner of sec. 35, heretofore described.</p> <p>At 41.94 chs. distant on the arc of the curve. Intersect the north and south center line, the closing corner of sec. 35, heretofore described.</p> <p>At the end of the arc of the curve. Intersect the east and west center line of the northwest quarter of sec. 35, Corner No. 2, Parcel D, Section 35, which is identical with Angle Point No. 3, Tract 38, heretofore described.</p>	
		<p>N. 89° 32' E., on line 2 - 3, Parcel D, Section 35, identical with line 3 - 2, Tract 38.</p>	

The Metes-and-Bounds Survey of Parcel D, Section 35  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS	
16.90	Intersect the north and south center line, the center-north 1/16 sec. cor. of sec. 35, which is designated to function for Corner No. 3, Parcel D, Section 35 and Angle Point No. 2, Tract 38, heretofore described.
19.02	<hr/> N. 89° 31' E., on line 3 - 4, Parcel D, Section 35, identical with line 2 - 1, Tract 38
15.24	<hr/> Intersect the arc of a curve, Corner No. 4, Parcel D, Section 35, which is identical with Angle Point No. 1, Tract 38, heretofore described.
	<hr/> Thence, on line 4 - 5, Parcel D, Section 35, along the arc of a curve, curve data:  Radius 113.64 chs. distant Length of arc 21.80 chs. distant Length of chord 21.77 chs. distant, and bears N. 78° 03' E.  At 1.18 chs. distant on the arc of the curve. Intersect the north and south center line of the northeast quarter, the point for the closing corner of sec. 35, heretofore described.  At the end of the arc of the curve, Corner No. 5, Parcel D, Section 35, heretofore described.
	<hr/> N. 0° 06' E., on line 5 - 1, Parcel D, Section 35, identical with the section line between secs. 35 and 36.
	Corner No. 1, Parcel D, Section 35, and the place of beginning
	<hr/> <p style="text-align: center;">Survey of Tracts 38, 39, and 40                      Township 7 South, Range 16 West                      Gila and Salt River Meridian, Arizona</p>
	<hr/> Thence, with the survey of Tract 38  Beginning at Angle Point No. 1, Tract 38, which is identical with Corner No. 4, Parcel D, Section 35, heretofore described.  S. 89° 31' W., on line 1 - 2, Tract 38, identical with line 4 - 3, Parcel D, Section 35.

Survey of Tracts 38, 39, and 40  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS	
19.02	Intersect the north and south center line, the center-north 1/16 sec. cor. of sec. 35, which is designated to function for Angle Point No. 2, Tract 38 and Corner No. 3, Parcel D, Section 35, heretofore described.
16.90	<p style="text-align: center;">_____</p> <p>S. 89° 32' W., on line 2 - 3, Tract 38, identical with line 3 - 2, Parcel D, Section 35</p> <p>Intersect the arc of a curve, Angle Point No. 3, Tract 38, which is identical with Corner No. 2, Parcel D, Section 35, heretofore described.</p> <p style="text-align: center;">_____</p> <p>Thence, on line 3 - 4, Tract 38, along the arc of a curve, curve data:</p> <p>Radius 128.79 chs. distant Length of arc 3.80 chs. distant Length of chord 3.80 chs. distant, and bears S. 56° 14' 25" W.</p> <p>At the end of the arc of the curve. Intersect the north and south center line of the northwest quarter of sec. 35, Angle Point No. 4, Tract 38, heretofore described.</p> <p style="text-align: center;">_____</p> <p>S. 0° 16' W., on line 4 - 5, Tract 38, identical with the north and south center line of the northwest quarter of sec. 35.</p>
7.97	<p>The C-S-NW 1/64 sec. cor. of sec. 35, which is designated to function for Angle Point No. 5, Tract 38, heretofore described.</p> <p style="text-align: center;">_____</p> <p>N. 89° 35' E., on line 5 - 6, Tract 38, identical with the east and west center line of the SE 1/4 of the NW 1/4 of sec. 35.</p>
15.89	<p>Intersect the arc of a curve, Angle Point No. 6, Tract 38, heretofore described.</p> <p style="text-align: center;">_____</p> <p>Thence, on line 6 - 1, Tract 38, along the arc of a curve, curve data:</p>

Survey of Tracts 38, 39, and 40  
 Township 7 South, Range 16 West  
 Gila and Salt River Meridian, Arizona

CHAINS

Radius 113.64 chs. distant  
 Length of arc 25.44 chs. distant  
 Length of chord 25.39 chs. distant, and bears N. 66°  
 08' E.

At 4.79 chs. distant on the arc of the curve. Intersect  
 the north and south center line, the closing corner of  
 sec. 35, heretofore described.

At the end of the arc of the curve. Angle Point No. 1,  
 Tract 38, which is identical with Corner No. 4, Parcel D,  
 Section 35, and the place of beginning.

Thence, with the Survey of Tract 39

Beginning at Angle Point No. 1, Tract 39 (heretofore  
 described), and is located on the north and south center  
 line of the SW 1/4 of the NW 1/4 of sec. 35.

Thence, on line 1 - 2, Tract 39, along the arc of a  
 curve, curve data:

Radius 128.79 chs. distant  
 Length of arc 0.39 chs. distant  
 Length of chord 0.39 chs. distant, and bears S. 49°  
 39' W.

At the end of the arc of the curve. The point for Angle  
 Point No. 2, Tract 39

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins.  
 in the ground, with brass cap mkd.

T7S R16W  
 S 35  
 /  
 AP 2  
 TR 39

1974

S. 49° 33.6' W., on line 2 - 3, Tract 39

12.87

Angle Point No. 3, Tract 39, which is identical with  
 Corner No. 4, Parcel A, and Corner No. 1, Parcel B,  
 Section 34, heretofore described.

S. 0° 23' W., on line 3 - 4, Tract 39, identical with  
 line 1 - 3, Parcel B, Section 34

Survey of Tracts 38, 39, and 40  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS		
1.84	<p>The 1/4 sec. cor. of secs. 34 and 35, which is designated to function for Angle Point No. 4, Tract 39, Angle Point No. 1, Tract 40, Corner No. 3, Parcel B, Section 34, heretofore described.</p> <hr/>	
18.18	<p>S. 0° 22' W., on line 4 - 5, Tract 39, identical with line 1 - 5, Tract 40</p> <p>Angle Point No. 5, Tract 39, which is identical with Angle Point No. 5, Tract 40, heretofore described.</p> <hr/>	
13.29	<p>N. 49° 33.6' E., on line 5 - 6, Tract 39</p> <p>Intersect the north and south center line of the NW 1/4 of the SW 1/4 of sec. 35, Angle Point No. 6, Tract 39, heretofore described.</p> <hr/>	
9.62	<p>N. 0° 19' E., on line 6 - 1, Tract 39, identical with the north and south center line of the NW 1/4 of the SW 1/4 of sec. 35.</p> <p>Intersect the east and west center line, the C-W-W 1/64 sec. cor. of sec. 35, heretofore described.</p> <p>Continue with the above course and measurement of line 6 - 1, Tract 39, which is the north and south center line of the SW 1/4 of the NW 1/4 of sec. 35.</p>	
20.00	<p>Angle Point No. 1, Tract 39, and the place of beginning.</p> <hr/>	
	<p>Thence, with the survey of Tract 40</p>	
	<p>Beginning at the 1/4 sec. cor. of secs. 34 and 35, which is designated to function for Angle Point No. 1, Tract 40, Angle Point No. 4, Tract 39, and Corner No. 3, Parcel B, Section 34, heretofore described.</p> <p>S. 89° 47' W., on line 1 - 2, Tract 40, identical with line 3 - 2, Parcel B, Section 34</p>	
2.16	<p>Angle Point No. 2, Tract 40, which is identical with Corner No. 3, Parcel A, and Corner No. 2, Parcel B, Section 34, heretofore described.</p> <hr/>	

Survey of Tracts 38, 39, and 40  
Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS	
	S. 49° 33.6' W., on line 2 - 3, Tract 40
23.77	Intersect the north and south center line of the south-east quarter, the point for the closing corner of sec. 34, heretofore described.
31.07	Intersect the east and west center line of the southeast quarter, the point for the closing corner of sec. 34, heretofore described.
50.43	Intersect the north and south center line. The closing corner of sec. 34, heretofore described.
62.07	Angle Point No. 3, Tract 40 on the south boundary of the township, heretofore described.
	_____
	N. 89° 51' E., on line 3 - 4, Tract 40, identical with the south boundary of the township.
8.80	The 1/4 sec. cor. of secs. 3 and 34 on the south boundary of the township, heretofore described.
	Continue with the above course and measurement of line 3 - 4, Tract 40, which is the south boundary of the township.
23.42	Angle Point No. 4, Tract 40, Tp. 7 S., R. 16 W., which is identical with Angle Point No. 1, Tract 39, Tp. 8 S., R. 16 W., heretofore described.
	_____
	N. 49° 33.6' E., on line 4 - 5, Tract 40
7.33	Intersect the north and south center line of the south-east quarter, the point for the closing corner of sec. 34, heretofore described.
31.03	Intersect the east and west center line of the southeast quarter, the point for the closing corner of sec. 34, heretofore described.
33.99	Angle Point No. 5, Tract 40, which is identical with Angle Point No. 5, Tract 39, heretofore described.
	_____
	N. 0° 22' E., on line 5 - 1, Tract 40, identical with line 5 - 4, Tract 39
18.18	The 1/4 sec. cor. of secs. 34 and 35, which is designated to function for Angle Point No. 1, Tract 40, Angle Point No. 4, Tract 39, and Corner No. 3, Parcel B, Section 34, and the place of beginning.

Township 7 South, Range 16 West  
Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

The land embraced by this survey is primarily nearly level to gently rolling desert land. The soil is sand to sand gravel. Timber consists of French tamarisk, mesquite, and paloverde; undergrowth, young trees, brush, and creosote brush (shrub).

The major water course is the Gila River, with numerous flood ways, which meanders in a southwesterly direction.

Irrigated farms are developed near the area of this survey, with concrete lined lateral canals. Improved roads have been constructed throughout the vicinity.

Game birds, coyote, and rodents abound throughout the area.

CHAINS



