

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

WEST AND NORTH BOUNDARIES

AND

SUBDIVISIONAL LINES,

A SURVEY OF SUBDIVISIONS IN SECTIONS 16 AND 20

AND

ADJUSTED MEANDERS AND SURVEY OF THE MEDIAL LINE OF SPEAR'S LAKE

IN SECTIONS 6 AND 7,

TOWNSHIP 17 NORTH, RANGE 21 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

PAUL L. REEVES

CADASTRAL SURVEYOR

Under special instructions dated DECEMBER 1, 19 61, approved DEC. 29, 1961,

AND SUPPLEMENT SPECIAL INSTRUCTIONS, DATED JANUARY 25, 1980 AND

APPROVED JAN. 28, 1980, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 367, and assignment instructions dated JANUARY 28, 19 80

Survey commenced FEBRUARY 4, 19 80

Survey completed MARCH 28, 19 80

INDEX DIAGRAM

Township 17 NORTH, Range 21 WEST

6	5				
4 6 18	18 5 18	4	3	2	1
4 7 16	16 8 15	12 9 11	10	11	12
1 18 14	14 17 13	11 16 10	8 15	14	13
19	13 20 9	9 21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

- Subdivision of sec. 16 p. 20
- Subdivision of sec. 20 p. 20
- Adjusted Meanders of
- Spear's Lake, secs. 6 & 7 p. 21
- Medial line of Spear's Lake p. 23

T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

The boundaries, subdivisional lines and meanders of Spear's Lake were surveyed by John J. Fisher in 1905. Robert C. Yundt and Donald A. Cannon resurveyed a portion of the subdivisional lines and surveyed accretions in 1960, 1961 and 1962.

The following field notes are those of the dependent resurvey of a portion of the west and north boundaries and subdivisional lines; a survey of subdivisions in sections 16 and 20, adjusted meanders and survey of the medial line of Spear's Lake in sections 6 and 7, Township 17 North, Range 21 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and Special Instructions for Group No. 367, Arizona, dated December 1, 1961 and Supplemental Special Instructions, dated January 25, 1980.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record.

Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast corner of section 16, as computed from a tie to triangulation station "San" located in section 27, T. 18 N., R. 22 W., is as follows:

Latitude $34^{\circ}51'07.5''$ N. Longitude $114^{\circ}30'29.5''$ W.

The mean magnetic declination is $14^{\circ}30'$ E.

Dependent Resurvey of a Portion of the West boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

(Restoring the 1905 survey by John J. Fisher)

Beginning at the cor. of secs. 13, 18, 19, and 24, monumented with an iron post, $2\frac{1}{2}$ ins. diam., 24 ins. below surface of road, in a hand hole, with brass cap mkd.

T17N
R22W R21W
S13 | S18
S24 | S19
1960

Cor. is located in the intersection of roads, paved road extends N. and W., graded gravel road extends E.

from which

Dependent Resurvey of a Portion of the West boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. $40\frac{1}{2}^\circ$ E., 85 lks. dist., mkd. T17N R21W RM S18 56.1 ft. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 63° E., 87.6 lks. dist., mkd. T17N R21W RM S19 57.8 ft. 1980 and an arrow pointing to the cor.

RM is located alongside a power pole.

N. $0^\circ 22'$ W., bet. secs. 13 and 18.

Along a paved road.

20.04 The S $1/16$ sec. cor. of secs. 13 and 18, monumented with a brass tablet, 2 ins. diam., set in concrete, 4 ins. below center of surface of paved road, in a hand hole, with top mkd.

BIA ROADS

ELEV.

•

STAT.

19

This monument was set by the Bureau of Indian Affairs and is accepted as a careful and faithful determination of the position of the corner, not remonumented.

N. $0^\circ 22'$ W., beginning new measurement.

20.04 The $1/4$ sec. cor. of secs. 13 and 18, monumented with a brass tablet, 2 ins. diam., set in concrete, 4 ins. below surface of road, in a hand hole with top mkd.

BIA ROADS

ELEV.

•

STAT.

19

This position was monumented by the Bureau of Indian Affairs, has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position, not remonumented.

Cor. is located in the center of a N. and S. paved road.

from which



An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. $48\frac{1}{4}^\circ$ E., 70.8 lks. dist., mkd. T17N R21W RM $1/4$ S18 46.7 ft. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

Dependent Resurvey of a Portion of the West boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 67 1/4° E., 56.8 lks. dist., mkd. T17N R21W RM 1/4 S18 37.5 ft. 1980 and an arrow pointing to the cor.</p> <p>RM is located alongside a power pole, lines extend E., S. and W.</p> <hr/> <p>N. 0°24' W., beginning new measurement.</p>	
20.04	<p>The N 1/16 sec. cor. of secs. 13 and 18, monumented with a brass tablet, 2 ins. diam., set in concrete, 4 ins. below surface of center of a N. and S. paved road, in a hand hole, with top mkd.</p> <p style="text-align: center;">BIA ROADS ELEV. • STAT. 19</p> <p>This monument was set by the Bureau of Indian Affairs and is accepted as a careful and faithful determination of the position of the corner, not remonumented.</p> <hr/> <p>N. 0°24' W., beginning new measurement.</p>	
20.02	<p>The cor. of secs. 7, 12, 13 and 18, monumented with a brass tablet, 2 ins. diam., set in concrete, 4 ins. below surface of road, in a hand hole, with top mkd.</p> <p style="text-align: center;">BIA ROADS ELEV. • STAT. 19</p> <p>This position was monumented by the Bureau of Indian Affairs, has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position, not remonumented.</p> <p>Cor. is located in the center of a N. and S. paved road 47 lks. S. of an intersection, State Highway No. 95, bears E. and W., graded road extends N. and paved road extends S.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 65 1/4° E., 69.4 lks. dist., mkd. T17N R21W RM S18 45.8 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 27° W., 137.3 lks. dist., mkd. T17N R22W RM S12 90.6 ft. 1980 and an arrow pointing to the cor.</p>	

Dependent Resurvey of a Portion of the West boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS	
	Set a steel fence post alongside the RM.
	N. 0°04' W., bet. secs. 7 and 12.
	Along a graded road.
29.045	Point for the meander cor. of secs. 7 and 12, on the SE side of Spear's Lake, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 6 ins. below surface of road, with aluminum cap mkd.
	 <p style="text-align: center;">M C S12 S 7 R22W R21W T17N 1980</p>
	Cor. is located in center of a N. and S. graded road.
	Thence on a blank line, continuing measurement.
80.12	The cor. of secs. 1, 6, 7, and 12, monumented with an iron pipe, 2 ins. diam., 6 ins. below surface of road, with cap attached and mkd. with a dot only. The origin of this monument is unknown, however it is accepted as a careful and faithful determination of the position of the original cor., not remonumented.
	Cor. is located in the intersection of roads extending N., S., E. and W.
	Note: This point was called for in the original 1905 survey but never monumented.
	N. 0°04' W., on a blank line.
	Along a graded road.
39.37	Point for the meander cor. of secs. 1 and 6, on the NW side of Spear's Lake, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 4 ins. below surface of road, with aluminum cap mkd.
	 <p style="text-align: center;">T17N R22W R21W S 1 S 6 M C 1980</p>
	Cor. is located in center of a N. and S. graded dirt road.
	Continue between secs. 1 and 6.
40.07	Point for the 1/4 sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 5 ins. below surface of road, with aluminum cap mkd.

Dependent Resurvey of a Portion of the West boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

T17N
R22W R21W
1/4
S 6 | S 1
1980

Cor. is located in center of a N. and S. graded dirt road.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 47° E., 57.6 lks. dist., mkd. T17N R21W RM 1/4 S6 38 ft. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. $42\frac{1}{4}^\circ$ E., 63.6 lks. dist., mkd. T17N R21W RM 1/4 S6 42 ft. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

80.14 The cor. of Tps. 17 and 18 N., Rs. 21 and 22 W., described in the field notes for T. 18 N., R. 21 W., surveyed concurrently under this group.

Dependent Resurvey of a Portion of the North boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

(Restoring the 1905 survey by John J. Fisher)

From the cor. of secs. 4, 5, 32 and 33, monumented with a lava stone 20 x 16 x 12 ins., projecting 5 ins. above the ground, mkd. with 4 grooves on the E. face and 2 grooves on the W. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T18N R21W
S32 | S33
S 5 | S 4
T17N
1980

Deposit the mkd. stone alongside the cor.

N. $89^\circ 57'$ W., bet. secs. 5 and 32.

Over rolling land, through medium creosote.

Dependent Resurvey of a Portion of the North boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS	
39.99	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R21W $\frac{1}{4} \frac{S32}{S5}$ T17N 1980</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 45 lks. N. of a track road, bears SE and NW curving W.</p>
79.98	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 3 ins. below surface of S. edge of an E. and W. track road, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T18N R21W $\frac{S31 S32}{S6 S5}$ T17N 1980</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 57½° E., 99.2 lks. dist., mkd. T17N R21W RM S5 65.5 ft. 1980 and an arrow pointing to the cor.</p> <p>RM is located alongside a power pole.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 43° W., 105.3 lks. dist., mkd. T17N R21W RM S6 69.5 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p>
39.99	<p>N. 89°57' W., bet. secs. 6 and 31.</p> <p>Along a paved road.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a reinforcement rod, 5/8 in. diam., origin unknown, flush with surface of road. This monument is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of the North boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

Drive the reinforcement rod, 7 ins. below surface of road, set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, over local cor. in a 6 in. base of concrete, with top mkd.

T18N R21W

$\frac{1}{4}$ S31

S 6

T17N

1980

Cor. is located in the center of an E. and W. paved road.
from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 44° E., 84.8 lks. dist., mkd. T17N R21W RM 1/4 S6 56 ft. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 3/4° E., 58 lks. dist., mkd. T18N R21W RM 1/4 S31 38.3 ft. 1980 and an arrow pointing to the cor.

RM is located alongside a power pole.

N. 89°53' W., beginning new measurement.

23.235 Point for the meander cor. of secs. 6 and 31, on the E. side of Spear's Lake, at proportionate dist.; there is no remaining evidence of the original cor.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a 6 in. base of concrete, 3 ins. below surface of a road, with top mkd.

T18N
MC $\frac{S31}{S 6}$ R21W
T17N
1980

Cor. is located in the center of an E. and W. paved road.

Thence on a blank line.

38.97 Point for the meander cor. of secs. 6 and 31, on the W. side of Spear's Lake, at proportionate dist.; there is no remaining evidence of the original cor.

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a 6 in. base of concrete, 3 ins. below surface of a road, with top mkd.

T18N
R21W $\frac{S31}{S 6}$ MC
T17N
1980

Dependent Resurvey of a Portion of the North boundary,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

Cor. is located in the center of an E. and W. paved road.

Continue between secs. 6 and 31.

39.98

The cor. of Tps. 17 and 18 N., Rs. 21 and 22 W.,
described in the field notes for T. 18 N., R. 21 W.,
surveyed concurrently under this group.

Dependent Resurvey of a Portion of the Subdivisional
lines, T. 17 N., R. 21 W.,
Gila and Salt River Mer., Arizona

(Restoring the 1905 survey by John J. Fisher)

From the cor. of secs. 15, 16, 21 and 22, monumented with
an iron post, $2\frac{1}{2}$ ins. diam., projecting 8 ins. above the
ground, in a mound of stone, $1\frac{1}{2}$ ft. base, to top, and a
mound of stone, 2 ft. base, 1 ft. high, W. of the cor.,
with brass cap mkd.

T17N R21W	
S16	S15
S21	S22
1960	

N. $0^{\circ}15'$ W., bet. secs. 15 and 16.

Over rolling land, through medium creosote.

40.16

The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented with a
lava stone, 18 x 16 x 10 ins., projecting 5 ins. above
the ground, mkd. $\frac{1}{4}$ on the W. face, with a mound of
stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in
the ground, in a mound of stone, 2 ft. base, to top, with
brass cap mkd.

T17N R21W	
$\frac{1}{4}$	
S16	S15
1980	

Deposit the mkd. stone alongside the cor.

Cor. is located 110 lks. E. of a N. and S. pipe line
road.

N. $0^{\circ}04'$ W., beginning new measurement.

40.14

The cor. of secs. 9, 10, 15 and 16, monumented with a
lava stone, 18 x 12 x 12 ins., projecting 6 ins. above
the ground, mkd. with 4 grooves on the S. face and 3
grooves on the E. face, with a mound of stone, $2\frac{1}{2}$ ft.
base, 6 ins. high, W. of the cor.

At the cor. point

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W S 9 S10 S16 S15 1980</p> <p>Deposit the mkd. stone alongside the cor.</p>	
	<p style="text-align: center;">(Restoring the 1960-62 resurvey by Robert C. Yundt and Donald A. Cannon.)</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W S20 S21 S29 S28 1961</p> <p>S. 89°58' W., bet. secs. 20 and 29.</p> <p>Through dense undergrowth.</p> <p>40.00 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist; the 1960 iron post was found lying on the ground in an advanced state of deterioration and was destroyed.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W 1 S20 4 S29 1980</p> <p>Cor. is located 2 lks. N. of an E. and W. fence line and 120 lks. N. of an E. and W. canal.</p> <p>70.69 The witness point of secs. 20 and 29, monumented with an iron post, 2½ ins. diam., projecting 3 ins. above the ground, in a base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W W S20 P S29 1960</p> <p>Cor. is located 2 lks. N. of an E. and W. fence line.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 0°10' E., bet. secs. 20 and 21.</p> <p>Along cultivated field on E. and dense undergrowth on W.</p>	

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
40.02	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2½ ins. diam., in a 6 in. base of concrete, surrounded with a tile, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W 1/4 S20 S21 1961</p> <p>Cor. is located in a N. and S. fence line.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°02' E., beginning new measurement.</p>	
19.95	<p>The N 1/16 sec. cor. of secs. 20 and 21, monumented with an iron pipe, 1 in. diam., projecting 6 ins. above the ground. The origin of this monument is unknown, however it is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W N 1/16 S20 S21 1980</p> <p>Deposit the pipe inside the iron post.</p> <p>Fence cor., bears N. 15° E., 7 lks. dist., fences extend S. and W.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°06' E., beginning new measurement.</p>	
19.94	<p>The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2½ ins. diam., in a 6 in. base of concrete, surrounded with a tile, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W S17 S16 S20 S21 1961</p> <p>Set a steel fence post alongside the cor.</p> <p>Fence cor., bears S. 30° W., 8 lks. dist., fences extend N. and E.</p> <hr/> <p>(Restoring the 1905 survey by John J. Fisher)</p> <hr/> <p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 89°57' W., bet. secs. 16 and 21.</p> <p>Over rolling land, through medium creosote.</p>	

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
36.20	State Highway No. 95, bears SE and NW, thence through dense undergrowth. (scaled)	
40.11	Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.	
	T17N R21W $\frac{1}{4} \frac{S16}{S21}$ 1980	
	Cor. is located in the center of an E. and W. track road and 14 lks. N. of an E. and W. fence line.	
80.22	The cor. of secs. 16, 17, 20 and 21.	
	N. 0°10' W., bet. secs. 16 and 17.	
	Over level land, through dense undergrowth.	
40.13	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.	
	T17N R21W $\frac{1}{4}$ S17 S16 1980	
	Set a steel fence post alongside the cor.	
80.26	Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.	
	T17N R21W $\frac{S 8 S 9}{S17 S16}$ 1980	
	Set a steel fence post alongside the cor.	
	From the cor. of secs. 9, 10, 15 and 16.	
	N. 89°47' W., bet. secs. 9 and 16.	
	Over rolling land, through medium creosote.	
40.01	The 1/4 sec. cor. of secs. 9 and 16, monumented with a lava stone, 16 x 8 x 7 ins., loosely set in a scattered mound of stone, mkd. 1/4 on one face.	

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>At the cor. point.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 19 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W $\frac{1}{4}$ S 9 $\frac{4}{S16}$ 1980</p> <p>Deposit the mkd. stone alongside the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>S. $89^{\circ}54'$ W., beginning new measurement.</p>	
40.25	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr style="width: 100%;"/>	
	<p>North, bet. secs. 8 and 9.</p> <p>Over rolling land, through scattered creosote.</p> <p>40.13 The $\frac{1}{4}$ sec. cor. of secs. 8 and 9, monumented with a lava stone, 18 x 10 x 6 ins., projecting 7 ins. above the ground, mkd. $\frac{1}{4}$ on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W $\frac{1}{4}$ S 8 S 9 1980</p> <p>Deposit the mkd. stone alongside the cor.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. $0^{\circ}58'$ W., beginning new measurement.</p>	
39.87	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a lava stone, 16 x 7 x 6 ins., projecting 4 ins. above the ground, mkd. with 5 grooves on the S. face and 4 grooves on the E. face, with a mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high, E. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W S 5 S 4 S 8 S 9 1980</p> <p>Deposit the mkd. stone alongside the cor.</p> <p>Rebuild the mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located 15 lks. N. of an E. and W. track road.</p> <hr/> <p>(Restoring the 1960-62 resurvey by Robert C. Yundt and Donald A. Cannon.)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20, monumented with an iron post, 2½ ins. diam., projecting 4 ins. above the ground, in a base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W 1/4 S19 S20 1960</p>	
39.97	<p>Cor. is located 3 lks. E. of a N. and S. fence line.</p> <p>N. 0°08' W., bet. secs. 19 and 20.</p> <p>Over level land, through dense undergrowth.</p> <p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2½ ins. diam., projecting 4 ins. above the ground, in a base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W S18 S17 S19 S20 1960</p>	
20.17	<p>Cor. is located at a fence cor., fences extend E. and S.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over level land, through dense undergrowth.</p> <p>Point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W E 1/16 S17 S20 1980</p>	
40.34	<p>Cor. is located in the W. edge of a N. and S. track road.</p> <p>Fence cor., bears S. 83°35' E., 24 lks. dist., fences extend N. and S. and abandoned W.</p> <p>The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., in a base of concrete, projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W 1 S17 4 S20 1961</p>	

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor. is at the end of a fence line, extending W. only.</p> <hr/> <p>S. 89°56' W., beginning new measurement.</p>
40.00	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 89°58' W., bet. secs. 18 and 19.</p> <p>Along N. side of a graded gravel road.</p>
39.99	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2½ ins. diam., 6 ins. below ground in a base of concrete, with brass cap knocked off and a 2 in. iron pipe alongside the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W $\frac{1}{4} \frac{S18}{S19}$ 1980</p> <p>Destroy the 2½ in. iron post and deposit the 2 in. iron pipe alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 35 lks. N. of an E. and W. graded gravel road.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p>
39.98	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., heretofore described.</p> <hr/> <p>(Restoring the 1905 survey by John J. Fisher)</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°13' W., bet. secs. 17 and 18.</p> <p>Along W. side of a N. and S. graded gravel road.</p>
40.00	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with the remains of an iron pipe, 2 ins. diam., origin unknown, projecting 2 ins. above the ground, with the remains of a railroad tie alongside. This monument is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
40.19	<p style="text-align: center;">T17N R21W 1/4 S18 S17 1980</p> <p>Deposit the iron pipe alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 37 lks. W. of a N. and S. graded gravel road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°18' W., beginning new measurement.</p> <p>The cor. of secs. 7, 8, 17 and 18, monumented with a squared metal post, 5 x 5 ins., origin unknown, projecting 30 ins. above the ground, with a 2 in. iron pipe inside the metal post, painted sec. 7 on the NW and NE corners, S18 on SE face. This monument is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W S 7 S 8 S18 S17 1980</p> <p>Bury the metal post horizontally alongside the cor.</p> <p>Cor. is located 44 lks. S. of State Highway No. 95 and 36 lks. W. of a graded gravel road extending S. from the highway.</p> <p>from which</p> <p style="padding-left: 40px;">A highway department brass cap, bears S. 42° W., 3.6 lks. dist., set in a 6 in. base of concrete, mkd. P&M 584M 1967.</p>	
22.70 40.22	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°58' W., bet. secs. 8 and 17.</p> <p>Along S. side of graded gravel road.</p> <p>State Highway No. 95, bears SE and W., thence along S. side. (scaled)</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W 1/4 S 8 S17 1980</p>	

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS	
80.44	<p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 50 lks. S. of State Highway No. 95 and 32 lks. E. of a graded gravel road, extending S. from the highway.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p>
40.06	<p>S. 89°58' W., bet. secs. 7 and 18.</p> <p>Along S. side of State Highway No. 95.</p> <p>The 1/4 sec. cor. of secs. 7 and 18, monumented with an iron pipe, 2 ins. diam., origin unknown, 6 ins. below surface of ground. This monument is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W $\frac{1}{4}$ S $\frac{7}{18}$ 1980</p> <p>Deposit the iron pipe alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 40 lks. S. of State Highway No. 95.</p>
40.08	<p>S. 89°57' W., beginning new measurement.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., heretofore described.</p>
40.17	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°20' W., bet. secs. 7 and 8.</p> <p>Along a graded dirt road.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. below surface of W. edge of a N. and S. graded dirt road in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T17N R21W 1/4 S 7 S 8 1980</p> <p>Set a steel fence post alongside the cor. by request of adjoining landowner.</p> <p>from which</p>

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS					
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 51½° W., 84.1 lks. dist., mkd. T17N R21W RM 1/4 S7 55.5 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 63½° W., 70.5 lks. dist., mkd. T17N R21W RM 1/4 S7 46.5 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p>				
80.34	<p>The cor. of secs. 5, 6, 7 and 8, monumented with an iron pipe, 2 ins. diam., origin unknown, 12 ins. below surface of road with cap attached and mkd. FF. This monument is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. below surface of road, in a 6 in. base of concrete, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R21W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>1980</p> </div> <p>Deposit the iron pipe alongside the cor.</p> <p>Cor. is located 30 lks. W. of a N. and S. graded dirt road, 20 lks. N. of center of an E. and W. graded dirt road extending W. from N. and S. road.</p> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 62° E., 80.9 lks. dist., mkd. T17N R21W RM S5 53.4 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 39½° W., 45.2 lks. dist., mkd. T17N R21W RM S6 29.8 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p> <p>From the cor. an iron pipe, 2 ins. diam., bears S. 58°11' E., 33 lks. dist., lying horizontally, 24 ins. below surface of road.</p>	S 6	S 5	S 7	S 8
S 6	S 5				
S 7	S 8				

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>From the cor. of secs. 4, 5, 8 and 9.</p>	
	<p>S. 89°59' W., bet. secs. 5 and 8.</p>	
	<p>Over rolling land, through medium creosote.</p>	
40.13	<p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a lava stone, 12 x 12 x 10 ins., projecting 2 ins. above the ground, mkd. 1/4 on the N. face, with scattered mound of stone N. of the cor.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p>T17N R21W $\frac{1}{4} \frac{S}{S} \frac{5}{8}$ 1980</p>	
	<p>Deposit the mkd. stone alongside the cor.</p>	
	<p>Rebuild the mound of stone, 2½ ft. base, 1 ft. high, N. of the cor.</p>	
	<p>_____</p>	
	<p>N. 89°33' W., beginning new measurement.</p>	
40.11	<p>The cor. of secs. 5, 6, 7 and 8.</p>	
	<p>S. 89°49' W., between secs. 6 and 7.</p>	
	<p>Along a graded gravel road.</p>	
40.10	<p>Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an aluminum post, 30 ins. long, ¾ in. diam., 6 ins. below surface of road, with aluminum cap mkd.</p>	
	<p>T17N R21W $\frac{1}{4} \frac{S}{S} \frac{6}{7}$ 1980</p>	
	<p>Cor. is located 15 lks. N. of center of an E. and W. graded gravel road.</p>	
	<p>from which</p>	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 50½° E., 46.7 lks. dist., mkd. T17N R21W RM 1/4 S6 30.8 ft. 1980 and an arrow pointing to the cor.</p>	
	<p>Set a steel fence post alongside the RM.</p>	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 59° W., 45.9 lks. dist., mkd. T17N R21W RM 1/4 S6 30.3 ft. 1980 and an arrow pointing to the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS												
	<p>Set a steel fence post alongside the RM.</p> <p>From the 1/4 sec. cor. an iron pipe, 2 ins. diam., bears S. 27°12' E., 11 lks. dist., lying horizontally 15 ins. below surface of road.</p> <p>65.16 Point for the meander cor. of secs. 6 and 7 on the E. side of Spear's Lake, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 6 ins. below surface of road, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>MC</p> <table style="border-collapse: collapse; margin: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">T17N</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 6</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 7</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">R21W</td><td></td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">1980</td><td></td></tr> </table> </div> <p>From this point the local cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., bears S. 89°49' W., 14.59 chs. dist., heretofore described.</p>	T17N		S 6		S 7		R21W		1980		
T17N												
S 6												
S 7												
R21W												
1980												
40.01	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°06' E., bet. secs. 5 and 6.</p> <p>Along a graded dirt road.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. below surface of road, in a 6 in. base of concrete, with brass cap mkd.</p> <div style="text-align: center;"> <p>T17N R21W</p> <p>1/4</p> <p>S 6 S 5</p> <p>1980</p> </div> <p>Cor. is located 20 lks. W. of center of N. and S. graded dirt road.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears S. 32½° W., 51.4 lks. dist., mkd. T17N R21W RM 1/4 S6 33.9 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete, for a reference monument, bears N. 38½° W., 50.9 lks. dist., mkd. T17N R21W RM 1/4 S6 33.6 ft. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p>											

Dependent Resurvey of a Portion of the Subdivisional lines,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
79.78	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of the Tp., heretofore described.	
	Subdivision of section 16, T. 17 N., R. 21 W., Gila and Salt River Meridian, Arizona	
	<p>From the 1/4 sec. cor. of secs. 16 and 21.</p> <p>N. 0°03' W., on the N. and S. center line of sec. 16.</p> <p>Over rolling land, through medium creosote.</p>	
40.14	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 16.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p>	
	T17N R21W C 1/4 S16 1980	
	<p>From this point the remains of a wooden post, 4 ins. diam., in a mound of stone, 1½ ft. base, 6 ins. high., bears N. 74°59' E., 86 lks. dist.</p>	
80.39	The 1/4 sec. cor. of secs. 9 and 16.	
	<p>From the 1/4 sec. cor. of secs. 15 and 16.</p> <p>N. 89°56' W., on the E. and W. center line of sec. 16.</p> <p>Over rolling land, through medium creosote.</p>	
40.00	The C 1/4 sec. cor. of sec. 16.	
61.30	State Highway No. 95, bears SE and NW, thence through dense undergrowth. (scaled)	
80.17	The 1/4 sec. cor. of secs. 16 and 17.	
	Subdivision of section 20, T. 17 N., R. 21 W., Gila and Salt River Meridian, Arizona	
	<p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0°07' W., on the N. and S. center line of sec. 20.</p> <p>Over river bottom land, through dense undergrowth.</p>	
39.99	Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 20, not monumented.	
59.97	Point for the C-N 1/16 sec. cor. of sec. 20, not monumented.	
79.95	The 1/4 sec. cor. of secs. 17 and 20.	
	<p>From the 1/4 sec. cor. of secs. 20 and 21.</p>	

Subdivision of Section 20, T. 17 N., R. 21 W.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>S. 89°56' W., on the E. and W. center line of sec. 20. Over river bottom land, through dense undergrowth.</p>
20.10	Point for the C-E 1/16 sec. cor. of sec. 20, not monumented.
40.20	The point for the C 1/4 sec. cor. of sec. 20.
80.19	The 1/4 sec. cor. of secs. 19 and 20.
<hr/> <p>NE 1/4, section 20</p> <hr/>	
	<p>From the point for the C-E 1/16 sec. cor. of sec. 20. N. 0°01' W., on the N. and S. center line of the NE 1/4, sec. 20. Over river bottom land, through dense undergrowth.</p>
19.96	<p>Point for the NE 1/16 sec. cor. at intersection with the E. and W. center line of the NE 1/4, sec. 20. Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p>
	<p>T17N R21W NE 1/16 S20 1980</p>
	<p>Set a steel fence post alongside the cor. Cor. is located at the W. edge of curve in track road, extending N. and E. Fence cor., bears N. 70° E., 20 lks. dist., fence extends N. and E.</p>
39.92	The E 1/16 sec. cor. of secs. 17 and 20.
	<hr/>
	<p>From the N 1/16 sec. cor. of secs. 20 and 21. S. 89°58' W., on the E. and W. center line of the NE 1/4, sec. 20. Over river bottom land, through dense undergrowth.</p>
20.13	The NE 1/16 sec. cor. of sec. 20.
40.26	The point for the C-N 1/16 sec. cor. of sec. 20.
<hr/> <p>ADJUSTED MEANDERS OF SPEAR'S LAKE, T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona</p> <hr/>	
<p>(Retracing the 1905 survey by John J. Fisher)</p> <hr/>	

ADJUSTED MEANDERS OF SPEAR'S LAKE,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

From the meander cor. of secs. 6 and 31 on the E. side of Spear's lake and on the N. bdy. of the Tp., heretofore described.

With the adjusted meanders of Spear's Lake in sec. 6.

S. 10°30' E., 3.41 chs.

S. 7°46' E., 4.92 chs.

S. 0°47' E., 2.51 chs.

S. 4°17' E., 2.01 chs.

S. 7°46' E., 3.91 chs.

S. 17°23' W., 1.31 chs.

S. 31°34' W., 1.11 chs.

S. 15°24' W., 3.52 chs.

S. 5°26' W., 1.51 chs.

S. 16°23' W., 2.51 chs.

S. 12°39' W., 4.12 chs.

S. 17°23' W., 3.62 chs.

S. 13°09' W., 5.42 chs.

S. 4°31' E., 7.02 chs.

S. 13°15' E., 6.72 chs.

S. 1°02' E., 9.54 chs.

S. 0°02' E., 14.05 chs.

S. 5°06' W., 4.10 chs.

The meander cor. of secs. 6 and 7, heretofore described.

Continue with the adjusted meanders in sec. 6.

From the meander cor. of secs. 1 and 6 on the W. bdy. of the Tp., heretofore described.

N. 48°18' E., 4.99 chs.

N. 7°15' E., 4.99 chs.

N. 17°16' E., 2.50 chs.

N. 9°30' E., 9.99 chs.

N. 8°00' E., 4.19 chs.

N. 6°01' W., 3.59 chs.

N. 22°03' W., 2.90 chs.

N. 23°03' W., 3.90 chs.

ADJUSTED MEANDERS OF SPEAR'S LAKE,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

N. 6°01' W., 2.70 chs.

N. 40°49' W., 4.74 chs.

The meander cor. of secs. 6 and 31 on the W. side of Spear's Lake and on the N. bdy. of the Tp., heretofore described.

From the meander cor. of secs. 6 and 7, on the E. side of Spear's lake, heretofore described.

With the adjusted meanders of Spear's Lake in sec. 7.

S. 7°12' W., 18.65 chs.

S. 13°54' W., 19.54 chs.

S. 24°35' W., 8.85 chs.

S. 34°17' W., 6.78 chs.

The meander cor. of secs. 7 and 12 on the W. bdy. of the Tp., heretofore described.

MEDIAL LINE OF SPEAR'S LAKE,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona


From the meander cor. of secs. 6 and 7, heretofore described.

On a line normal to the medial line, segregating sec. 6.

N. 78°31' W., 8.21 chs.

Point for Angle Point No. 1 on the medial line.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.



Set a steel fence post alongside the cor.

Thence on the medial line.

N. 11°29' E., 2.54 chs.

Point for Angle Point No. 2.

MEDIAL LINE OF SPEAR'S LAKE,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
		<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
		<p style="text-align: center;">T17N R22W R21W AP2 S 1 S 6 1980</p>
		<p>Set a steel fence post alongside the cor.</p>
<p>N. 2°49' E., 14.90 chs.</p>		<p>Point for Angle Point No. 3</p>
		<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
		<p style="text-align: center;">T17N R22W R21W AP3 S 1 S 6 1980</p>
		<p>Set a steel fence post alongside the cor.</p>
<p>N. 2°00' W., 7.79 chs.</p>		<p>Point for Angle Point No. 4.</p>
		<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
		<p style="text-align: center;">T17N R22W R21W AP4 S 1 S 6 1980</p>
		<p>Set a steel fence post alongside the cor.</p>
		<p>Deposit an aluminum can at base of cor.</p>
<p>N. 7°31' W., 6.44 chs.</p>		<p>Point for Angle Point No. 5.</p>
		<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>

MEDIAL LINE OF SPEAR'S LAKE,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>T17N R22W R21W S 1 / AP5 S 6 1980</p> <p>Set a steel fence post alongside the cor.</p> <p>N. 2°40' W., 3.26 chs.</p> <p>Point for Angle Point No. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
		<p>T17N R22W R21W S 1 / AP6 S 6 1980</p> <p>Set a steel fence post alongside the cor.</p> <p>N. 21°53' E., 0.23 chs.</p> <p>Point for Angle Point No. 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
		<p>T17N R21W AP7 S 1 / R22W S 6 1980</p> <p>Set a steel fence post alongside the cor.</p> <p>From this point on a line normal to the medial line, the meander cor. of secs. 1 and 6 on the W. bdy. of the Tp., bears N. 68°07' W., 7.16 chs. dist., heretofore de- scribed.</p> <p>N. 21°53' E., 3.82 chs.</p> <p>Point for Angle Point No. 8, not monumented.</p> <p>N. 3°02' E., 1.42 chs.</p> <p>Point for Angle Point No. 9, not monumented.</p>	

MEDIAL LINE OF SPEAR'S LAKE,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS		
N. 12°33' E., 7.74 chs.	Point for Angle Point No. 10, not monumented.	
N. 11°47' E., 8.29 chs.	Point for Angle Point No. 11, not monumented.	
N. 7°15' E., 1.54 chs.	Point for Angle Point No. 12, not monumented.	
N. 12°34' E., 5.60 chs.	Point for Angle Point No. 13, not monumented.	
N. 5°40' W., 4.72 chs.	Point for Angle Point No. 14, not monumented.	
N. 14°37' W., 6.72 chs.	Point for Angle Point No. 15, not monumented.	
N. 9°03' W., 3.60 chs.	Point for Angle Point No. 16.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.	
	<div style="border: 1px solid black; padding: 2px; display: inline-block;"> T18N R21W S31 </div> T17N R21W S 6 AP16 1980	
	Set a steel fence post alongside the cor.	
	From this point on a line normal to the medial line, the meander cor. of secs. 6 and 31 on the N. bdy. of the Tp., bears N. 80°57' E., 6.58 chs. dist., heretofore de- scribed.	
N. 34°15' W., 5.24 chs.	Point for Angle Point No. 17.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.	
	<div style="border: 1px solid black; padding: 2px; display: inline-block;"> T18N R21W S31 </div> <div style="border: 1px solid black; padding: 2px; display: inline-block; margin-left: 20px;"> AP17 T17N R21W S 6 1980 </div>	

MEDIAL LINE OF SPEAR'S LAKE,
T. 17 N., R. 21 W., Gila and Salt River Mer., Arizona

CHAINS

S. 62°35' W., 7.09 chs.	Set a steel fence post alongside the cor. End of course. The meander cor. of secs. 6 and 31 on the N. bdy. of the Tp., heretofore described.
-------------------------	---

GENERAL DESCRIPTION

The land encompassed in this survey is located approximately 3 miles east of Needles, California in the Mohave Valley. The elevation ranges from about 455 to 700 feet above sea level.

The soil consists of a sandy loam of which a small portion is under cultivation. The undeveloped areas are covered with dense brush, mesquite, salt cedar and arrowweed. The area which raises above the valley is covered with medium creosote.

Access is by way of State Highway No. 95 and a number of graded gravel and unimproved roads.

CHAINS		
--------	--	--

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of December, 1961, ~~(I) (We)~~ and supplemental special instructions, dated January 25, 1980, have dependently resurveyed a portion of the north and west boundaries and subdivisional lines, surveyed subdivisions in sections 16 and 20, and adjusted meanders and surveyed the medial line of Spear's Lake in sections 6 and 7 of Township 17 North, Range 21 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 26, 1980 (Date) Paul L. Reeves (Cadastral Surveyor)

(Date) _____
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the north and west boundaries and subdivisional lines, a survey of subdivisions in sections 16 and 20, and adjusted meanders and survey of the medial line of Spear's Lake in sections 6 and 7 of Township 17 North, Range 21 West, Gila and Salt River Meridian, Arizona.

executed by Paul L. Reeves, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

FEB 25 1981 (Date) J. Voorhees (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date) _____
(Chief, Cadastral Survey Examination and Approval Staff)