

FIELD NOTES

1

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE FORMER BOUNDARY OF

THE FORT MOHAVE INDIAN RESERVATION

IN

FRACTIONAL TOWNSHIPS 18 and 19 NORTH, RANGE 22 WEST

AND

A PORTION OF THE NORTH BDY. AND SUBDIVISIONAL LINES

AND A SURVEY OF SUBDIVISIONS IN SECTION 14

AND

ADJUSTED MEANDERS AND SURVEY OF THE MEDIAL LINE OF SPEAR'S LAKE

IN SECTION 36

TOWNSHIP 18 NORTH, RANGE 22 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

PAUL L. REEVES

CADASTRAL SURVEYOR

Under special instructions dated DECEMBER 1, 19 61, approved DEC. 29, 1961,

AND SUPPLEMENTAL SPECIAL INSTRUCTIONS, DATED JANUARY 25, 1980 AND

APPROVED JAN. 28, 1980, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 367, and assignment instructions dated JANUARY 28, 19 80.

Survey commenced FEBRUARY 4, 19 80

Survey completed MARCH 28, 19 80

INDEX DIAGRAM

Township 18 NORTH, Range 22 WEST,

6	5	4	3 6 28	29 5 2 27	15 1 14
7	8	9	10 25	26 11 24	14 12 13
18	17	16	15 22	23 14 22	12 13 12
19	20	21	22	21 23 20	11 24 10
30	29	28	27 18	19 26 17	9 25 8
31	32	33	34	15 35	7 36

Former Bdy. Ft. Mohave Indian Reservation p. 2
 Subdivision of sec. 14 p. 31
 Adjusted Meanders of Spear's Lake, sec. 36 p. 32
 Medial line of Spear's Lake p. 33



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
DENVER SERVICE CENTER
DENVER FEDERAL CENTER, BUILDING 50
DENVER, COLORADO 80225

JPK

IN REPLY REFER TO
9622.1 (D-401)
Group No. 367,
Arizona

December 10, 1981

Memorandum

To: State Director, Arizona (942)

From: Director, BLM

Subject: Marginal notation on the plat, in two sheets, T. 18 N., R. 22 W., Gila and Salt River Meridian, Arizona

ARIZONA STATE OFFICE
BUREAU OF LAND MANAGEMENT

DEC 14 1981

7:45 AM.

DENVER, ARIZONA

This is in response to a telephone call from Harry K. Smith of your office, December 10, 1981.

There is a platting error on the east boundary of lot 5, sec. 22 and an error in the marginal data as shown on the plat, sheet 1 of 2, T. 18 N., R. 22 W., G&SRM, AZ, accepted February 25, 1981.

This memo authorizes you to make the necessary corrections as marginal notations on the original and triplicate original plat on file in your office.

The correction to lot 5, sec. 22 is: "The E. bdy. of lot 5, sec. 22 is to extend northerly to intersect the new boundary of the Fort Mohave Indian Reservation."

The correction to the marginal data is to add to the statement regarding lottings and areas: "And the plat accepted July 27, 1978."

Reference must be made to this memo in regards to these changes.

The duplicate original plat on file in this office will also be noted accordingly.

Once the annotations have been added to the original plat, you are requested to send it to Denver Service Center Branch of Micrographics (D-235), for refilming.

As an enclosure we are sending xerox copies of the plat for placements of the marginal notations.

For the Director, BLM

Enclosures

James C. Gilbert
ACTING

T. 18 N., R. 22 W., Gila and Salt River Mer., Arizona

3

CHAINS

The former boundary of the Fort Mohave Indian Reservation was surveyed by Army Engineers and resurveyed by John J. Fisher in 1905 and Sidney E. Blout in 1928. In 1975, Max L. Sevy resurveyed a portion of the former boundary of the Fort Mohave Indian Reservation and surveyed a new boundary of a portion of the Fort Mohave Indian Reservation superseding portions of the boundary as defined by Sidney E. Blout in 1928. Harry K. Smith resurveyed a portion of the former Fort Mohave Indian Reservation in 1977.

The boundaries, subdivisional lines and Spear's Lake were surveyed by John J. Fisher in 1905, and a portion of the subdivisional lines was resurveyed by Harry K. Smith in 1977.

The following field notes are those of the dependent resurvey of a portion of the former boundary of the Fort Mohave Indian Reservation in fractional Townships 18 and 19 North, Range 22 West, a portion of the north boundary, and subdivisional lines, a survey of subdivisions in section 14, and adjusted meanders and survey of the medial line of Spear's Lake in section 36, Township 18 North, Range 22 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specification set forth in the Manual of Surveying Instructions, 1973 and Special Instructions for Group No. 367, dated December 1, 1961 and Supplemental Special Instructions, dated January 25, 1980.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record.

Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

Certain corners were reestablished in 1962 under this group. Field work was suspended prior to the completion of the survey, as contemplated at that time. Those corners that were recovered are incorporated into this resurvey.

The geographic position of the southeast corner of section 36, as computed from a tie to triangulation station "San" located in section 27, T. 18 N., R. 22 W., is as follows:

Latitude $34^{\circ}53'42.7''$ N. Longitude $114^{\circ}33'42.1''$ W.

The mean magnetic declination is $14^{\circ}30'$ E.

Dependent Resurvey of a Portion of the Former Bdy. of the Fort Mohave Indian Reservation in fractional Tps. 18 and 19 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

(Restoring the 1928 resurvey by Sidney E. Blout)

Beginning at the 4½ mile post, monumented with a granite stone, 22 x 10 x 10 ins., projecting 8 ins. above the ground, mkd. ½M on the N., PL on the E. and CMIR on the W., with a mound of stone, 2½ ft. base, 1 ft. high N. of the cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

		T19N
FMIR		R22W
4½M		S34
		1980

Deposit the mkd. stone alongside the cor.

Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.

Set a steel fence post alongside the cor.

S. 0°28' W., on the 5th mile of the Former bdy. of the Fort Mohave Indian Reservation.

2.20 Point for the 1/4 sec. cor. of sec. 34 only, described in the field notes of T. 19 N., R. 22 W., surveyed concurrently under this group.

40.21 Point for the 5 mile post, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 48 ins. below surface of a cultivated field, with aluminum cap mkd.

		T19N
FMIR		R22W
5M		S34
		1980

S. 0°31' W., beginning new measurement on the 6th mile of the Former bdy. of the Fort Mohave Indian Reservation.

2.07 Point for the closing corner of secs. 3 and 34, Tps. 18 and 19 N., R. 22 W., hereinafter described.

7.31 Point for the East side center cor., at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, ¾ in. diam., flush with surface of dirt and gravel air strip, with aluminum cap mkd.

		T18N
FMIR		R22W
ESC		S 3
		1980

Dependent Resurvey of a Portion of the Former Bdy. of the
Fort Mohave Indian Reservation in fractional Tps. 18
and 19 N., R. 22 W., Gila and Salt River, Mer., Ariz.

5

CHAINS										
	<p>Cor. is located 15 lks. W. of the E. edge of the air strip, edge bears N. and S.</p> <p style="text-align: center;">_____</p> <p>S. 0°56' W., beginning new measurement.</p>									
32.86	<p>Point for the 5½ mile post, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., flush with surface of dirt and gravel air strip, with aluminum cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="border-left: 1px solid black;">T18N</td></tr> <tr><td>FMIR</td><td style="border-left: 1px solid black; border-right: 1px solid black;">R22W</td></tr> <tr><td>5½M</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 3</td></tr> <tr><td></td><td style="border-left: 1px solid black;">1980</td></tr> </table> </p>		T18N	FMIR	R22W	5½M	S 3		1980	
	T18N									
FMIR	R22W									
5½M	S 3									
	1980									
73.07	<p>Cor. is located 24 lks. W. of the E. edge of the air strip, edge bears N. and S.</p> <p>Point for the 6 mile post at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., flush with surface of dirt and gravel air strip, with aluminum cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="border-left: 1px solid black;">T18N</td></tr> <tr><td>FMIR</td><td style="border-left: 1px solid black; border-right: 1px solid black;">R22W</td></tr> <tr><td>6M</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S 3</td></tr> <tr><td></td><td style="border-left: 1px solid black;">1980</td></tr> </table> </p> <p>from which</p> <p style="padding-left: 40px;">An X, stamped on an air plane tie down eye-let, bears S. 32¾° W., 29.3 lks. dist.,.</p>		T18N	FMIR	R22W	6M	S 3		1980	
	T18N									
FMIR	R22W									
6M	S 3									
	1980									
75.14	<p>Cor. is located 38 lks. W. of E. edge of air strip, edge bears N. and S.</p> <p>Continue measurement on the 7th mile of the Former bdy. of the Fort Mohave Indian Reservation.</p> <p>Point for the closing cor. of secs. 3 and 10, hereinafter described.</p>									
113.16	<p>Point for the 6½ mile post, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 48 ins. below surface of cultivated field, with aluminum cap mkd.</p> <p style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="border-left: 1px solid black;">T18N</td></tr> <tr><td>FMIR</td><td style="border-left: 1px solid black; border-right: 1px solid black;">R22W</td></tr> <tr><td>6½M</td><td style="border-left: 1px solid black; border-right: 1px solid black;">S10</td></tr> <tr><td></td><td style="border-left: 1px solid black;">1980</td></tr> </table> </p>		T18N	FMIR	R22W	6½M	S10		1980	
	T18N									
FMIR	R22W									
6½M	S10									
	1980									
115.10	<p>Point for the 1/4 sec. cor. of sec. 10 only, hereinafter described.</p>									
152.95	<p>Graded gravel road, bears E. and W.</p>									
153.25	<p>Point for the 7 mile post, at proportionate dist.; there is no remaining evidence of the original cor. The cor. point falls in a flooded cultivated field, impracticable to monument.</p>									

Dependent Resurvey of a Portion of the Former Bdy. of the Fort Mohave Indian Reservation in fractional Tps. 18 and 19 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

Continue measurement on the 8th mile of the Former bdy. of the Fort Mohave Indian Reservation.

155.07 Point for the closing cor. of secs. 10 and 15, hereinafter described.

193.34 Point for the 7½ mile post, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.

T18N
FMIR | R22W
7½M | S15
1980

Cor. is located off the E. edge of a N. and S. graded dirt road, 18 lks. E. of center.

Set a steel fence post alongside the cor.

233.43 The 8 mile post, monumented by an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.

T18N
FMIR | R22W
8M | S22
1928

Cor. has a 12 ft. section of a telephone pole set alongside.

Remark the brass cap to read.

T18N
FMIR | R22W
8M | S15
1980
1928

S. 1°34' W., beginning new measurement on the 9th mile of the Former bdy. of the Fort Mohave Indian Reservation.

2.00 Point for the closing cor. of secs. 15 and 22, herinafter described.

37.76 Cor. 2 of the Former bdy. of the Fort Mohave Indian Reservation, monumented with an iron post, 2½ ins. diam., loosely set, projecting 6 ins. above a mound of earth and rock in the center of a cultivated field, with brass cap mkd.

T18N
FMIR | R22W
Cor. 2 | S22
1977
1975

Reset the iron post, 22 ins. in the ground, in a 12 in. base of concrete.

Dependent Resurvey of a Portion of the Former Bdy. of the
Fort Mohave Indian Reservation in fractional Tps. 18
and 19 N., R. 22 W., Gila and Salt River, Mer., Ariz.

7

CHAINS

Set a 12 ft. section of telephone pole in a 12 in. base
of concrete alongside the cor.

Add the marks 1980 to the brass cap.

Dependent Resurvey of a Portion of the North Boundary,
T. 18 N., R. 22 W., Gila and Salt River Meridian, Arizona

(Restoring the 1905 survey by John J. Fisher.)

From the cor. of secs. 1, 2, 35 and 36, monumented with a
1 in. diam. bolt, set flush with ground, with the origi-
nal lava stone 15 x 12 x 8 ins. lying loose alongside
local cor. in a scattered mound of stone, mkd. with 5
grooves on one side and 1 groove on another.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in
the ground, with brass cap mkd.

T19N R22W
S35 | S36
S 2 | S 1
T18N
1980

Deposit the local cor. inside the iron post.

Deposit the mkd. stone alongside the cor.

Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, W.
of the cor.

Set a steel fence post alongside the cor.

Cor. is located in an E. and W. fence line, 32 lks. W. of
a fence cor., fences extend N., E. and W.

S. 89°54' W., bet. secs. 2 and 35.

Over gently rolling land, through medium creosote.

40.08 The 1/4 sec. cor. of secs. 2 and 35 monumented with a
2 x 2 in. wooden hub with a tack in center, with a lava
stone 14 x 12 x 3 ins. lying loose alongside the local
cor., mkd. 1/4 on one side.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in
the ground, with brass cap mkd.

T19N R22W
1 | S35
4 | S 2
T18N
1980

Deposit mkd. stone and local hub alongside the cor.

Set a steel fence post alongside the cor.

Dependent Resurvey of a Portion of the North Bdy.,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

Cor. is located 3 lks. S. of an E. and W. fence line.

S. 89°55' W., beginning new measurement.

40.09

The cor. of secs. 2, 3, 34 and 35, monumented with an aluminum pipe, 3 ins. diam., 6 ins. below surface of center of Highway No. 95, in a hand hole, with cap mkd. Arizona Highway Department 19. This position is harmoniously related to other survey cors. in the area and is accepted as a careful and faithful determination of the cor. position; not remonumented.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 84 1/4° E., 42.7 lks. dist., mkd. T18N R22W RM S2 28.2 FT. 1980 and an arrow pointing to the cor.

RM is located 5 lks. S. of the W. end of a fence line, extending E. only.

An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 30° W., 78.3 lks. dist., mkd. T19N R22W RM S34 51.7 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a railroad tie which is the remains of a N. and S. fence and 5 lks. W. of a N. and S. power line.

S. 89°53' W., bet. secs. 3 and 34.

Along a graded gravel road.

40.05

Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. below surface of S. edge of road with aluminum cap mkd.

T19N R22W
1 S34
4 S 3
T18N
1980

Cor. is located 15 lks. S. of center of an E. and W. graded gravel road.

42.765

Point for the closing cor. of secs. 3 and 34, at proportionate dist., on the Former bdy. of the Fort Mohave Indian Reservation; there is no remaining evidence of the original cor.

Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. below surface of S. edge of road, with aluminum cap mkd.

Dependent Resurvey of a Portion of the North Bdy.,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

	T19N	
	R22W	
FMIR	S34	CC
	S 3	
	T18N	
	1980	

Cor. is located 18 lks. S. of center of E. and W. graded gravel road and N. end of air strip.

From this point the 5 mile post, bears N. 0°31' E., 2.07 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional lines, T. 18 N., R. 22 W., Gila & Salt River Mer., Ariz.

From the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Township, described in the field notes of the N. bdy. of T. 17 N., R. 22 W., surveyed concurrently under this group.

N. 0°01' W., bet. secs. 35 and 36.

Along graded road.

39.99 The 1/4 sec. cor. of secs. 35 and 36, monumented with an iron pipe, 1 in. diam., 18 ins. below surface of road. The origin of this monument is unknown, however it is accepted the best available evidence of the position of the original cor.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. below surface of road, with aluminum cap mkd.

	T18N	R22W
	1/4	
	S35	S36
	1980	

Deposit the iron pipe alongside the cor.

Cor. is located in the intersection of graded dirt roads, extending N., S. and W.

from which

A local cor., bears S. 38°13' W., 80.7 lks. dist., monumented with an iron pipe, 1 in. diam., projecting 3 ins. above the ground, with brass tag attached to top, mkd. LS 5576.

A local cor., bears S. 56°20' W., 81.8 lks. dist., monumented with an iron pipe, 1 in. diam., projecting 2 ins. above the ground, with brass tag attached to top, mkd. LS 5576.

N. 0°01" W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River Mer., Ariz.

CHAINS		
40.01	<p>The cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2½ ins. diam., 10 ins. below surface of the road, with brass cap mkd.</p> <p style="text-align: center;">T18N R22W <u>S26 S25</u> <u>S35 S36</u> 1962</p> <p>In 1962, a capped iron pipe, 2½ ins. diam., projecting 20 ins. above ground, was found at this position, and remonumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 40 ins. long, 8 ins. diam., set 26 ins. in the ground. The iron pipe was buried alongside the cor. The position of this cor. has long been recognized as the cor. by adjacent landowner and local surveyors, and is accepted as the cor.</p> <p>Add the marks 1980 to the brass cap.</p> <p>Cor. is located in the intersection of roads, extending N., S., E. and W.</p> <p>from which</p> <p style="padding-left: 40px;">An X on the N. end of a concrete lined ditch, bears S. 44 1/4° E., 92.1 lks. dist.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 44 1/4° W., 46.8 lks. dist., mkd. T18N R22W RM S26 30.9 FT. 1980 and an arrow pointing to the cor.</p> <p>RM is located alongside a stop sign.</p>	
40.22	<p>From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., described in the field notes as the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.</p> <p>S. 89°55' W., bet. secs. 25 and 36.</p> <p>Along graded gravel road.</p> <p>The 1/4 sec. cor. of secs. 25 and 36, monumented with an iron pipe, 1½ ins. diam., 12 ins. below surface of road. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 10 ins. below surface of road, with aluminum cap mkd.</p> <p style="text-align: center;">T18N R22W <u>1 S25</u> <u>4 S36</u> 1980</p> <p>Deposit the iron pipe alongside the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

11

CHAINS

Cor. is located in intersection of roads extending N., E. and W.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. $43\frac{1}{2}^\circ$ W., 70 lks. dist., mkd. T18N R22W RM 1/4 S36 46.2 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 23 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. $33\frac{1}{4}^\circ$ W., 88 lks. dist., mkd. T18N R22W RM 1/4 S25 58.1 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a stop sign.

S. $89^\circ 54'$ W., beginning new measurement.

40.22 The cor. of secs. 25, 26, 35 and 36.

N. $0^\circ 04'$ W., bet. secs. 25 and 26.

Along a dirt road and landing strip.

40.09 The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron pipe, 1 in. diam., 24 ins. long, 8 ins. below surface of ground. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.

T18N R22W
1/4
S26 | S25
1980

Deposit the iron pipe inside the cor.

Set a steel fence post alongside the cor.

Cor. is located 30 lks. E. of center of N. and S. graded dirt road.

N. $0^\circ 04'$ W., beginning new measurement.

40.08 The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, $2\frac{1}{2}$ ins. diam., 4 ins. below surface of the road, with brass cap mkd.

T18N R22W
S23 | S24
S26 | S25
1962

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS	
	<p>In 1962, a capped iron pipe, 2½ ins. diam., projecting 18 ins. above ground, was found at this position, and re-monumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 40 ins. long, 8 ins. diam., set 26 ins. in the ground. The iron pipe was buried alongside the cor. The monument has long been recognized as the cor. by adjacent landowners, and local surveyors, and is accepted as the best available evidence of the position of the original or.</p> <p>Add the marks 1980 to the brass cap.</p> <p>Cor. is located in the intersection of roads, graded gravel E. and W., graded dirt N. and S.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 40¾° E., 68.9 lks. dist., mkd. T18N R22W RM S24 45.5 FT. 1980 and an arrow pointing to the cor.</p> <p>RM is located alongside a power pole, lines bear E. and W.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 48° W., 76.1 lks. dist., mkd. T18N R22W RM S23 50.2 FT. 1980 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside the RM.</p> <p>RM is located under an E. and W. power line.</p>
<p>40.11</p>	<p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of Tp., described in the field notes of the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.</p> <p>N. 89°51' W., bet. secs. 24 and 25.</p> <p>Along a track road.</p> <p>The 1/4 sec. cor. of secs. 24 and 25, monumented with an iron pipe, 1½ ins. diam., 8 ins. below surface of road. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an aluminum post, 30 ins. long, ¾ in. diam., 8 ins. below surface inside the local iron pipe, with aluminum cap mkd.</p> <p style="text-align: center;">T18N R22W $\frac{1}{4}$ $\frac{S24}{S25}$ 1980</p> <p>Cor. is located at the intersection of roads, track road extend E. and graded gravel road extends S. and W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS	
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 29 1/4° E., 50.6 lks. dist., mkd. T18N R22W RM 1/4 S24 33.4 FT. 1980 and an arrow pointing to the cor.</p> <p>RM is located alongside a power pole, lines extend E., S. 30° W. and W.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 29 1/4° W., 103.9 lks. dist., mkd. T18N R22W RM 1/4 S25 68.6 FT. 1980 and an arrow pointing to the cor.</p> <p>RM is located alongside a power pole, lines extend N. 30° E., E. and W.</p> <hr/> <p>S. 89°50' W., beginning new measurement.</p>
40.14	The cor. of secs. 23, 24, 25 and 26.
	<hr/> <p>N. 0°34' W., bet. secs. 23 and 24.</p> <p>Along a graded dirt road.</p>
39.98	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron pipe, 2½ ins. diam., projecting 10 ins. above the ground, in advance stage of deterioration. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T18N R22W 1/4 S23 S24 1980</p> <p>Deposit the remains of the iron pipe alongside the cor.</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located 25 lks. W. of a N. and S. graded dirt road.</p> <hr/> <p>N. 0°12' E., beginning new measurement.</p>
40.51	The cor. of secs. 13, 14, 23 and 24, monumented with an iron pipe, 2½ ins. diam., projecting 4 ins. above the ground, with a railroad tie set alongside and a cap attached and mkd.

140

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS		
	<p style="text-align: center;">T18N R22W $\frac{14}{23} \frac{13}{24}$ Elev. 475.72</p> <p>The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor., not remonumented.</p>	
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., described in the field notes of the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.</p> <p>N. 89°55' W., bet. secs. 13 and 24.</p> <p>Along a track road.</p>	
<p>40.16</p>	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron pipe, 1 in. diam., 24 ins. long, projecting 1 in. above the ground, with a 4 x 4 in. wooden post, 16 ft. long set alongside the cor. This monument was set by Nathaniel J. Devlin, Civil Engineer No. 1855 and Land Surveyor No. 6452 in Arizona, and is accepted as a careful and faithful determination of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T18N R22W $\frac{1}{4} \frac{S13}{S24}$ 1980</p> <p>Deposit the iron pipe inside the cor.</p> <p>Reset the 4 x 4 in. wooden post in concrete alongside the cor.</p> <p>Cor. is located 25 lks. S. of an E. and W. track road.</p>	
	<p>N. 89°56' W., beginning new measurement.</p>	
<p>40.16</p>	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p>N. 0°09' W., bet. secs. 13 and 14.</p> <p>Along graded dirt road.</p> <p>40.02</p> <p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron pipe, 1 in. diam., projecting 14 ins. above the ground, with cap attached, no marks. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

T18N R22W

1/4

S14|S13

1980

Deposit the iron pipe alongside the cor.

Power pole, bears N. 18° E., 5 lks. dist., lines extend N., S. and W.

N. 0°10' W., beginning new measurement.

39.98 The cor. of secs. 11, 12, 13 and 14, monumented with an iron pipe, 2½ ins. diam., projecting 2 ins. above the ground, with a 4 x 4 in. wooden post, 16 ft. long alongside the cor., with cap attached and mkd.

T28N R22W

11|12

14|13

Elev. 476.47

The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor., not remonumented.

Reset the 4 x 4 in. wooden post in concrete alongside the cor.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., described in the field notes of the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.

S. 89°53' W., bet. secs. 12 and 13.

Along a track road.

40.12 The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron pipe, 1 in. diam., 24 ins. long, projecting 2 ins. above the ground. This monument was set by Nathaniel J. Devlin, Civil Engineer No. 1855 and Land Surveyor No. 6452 in Arizona, and is accepted as a careful and faithful determination of the position of the original cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.

T18N R22W

1 S12

4 S13

1980

Deposit the iron pipe, inside the cor.

Set a steel fence post alongside the cor.

S. 89°51' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS	
40.16	The cor. of secs. 11, 12, 13 and 14.
	N. 0°03' E., bet. secs. 11 and 12.
	Along a graded dirt road.
40.28	Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.
	T18N R22W 1/4 S11 S12 1980
	Set a steel fence post alongside the cor.
	Cor. is located in an abandoned N. and S. fence line and 20 lks. W. of center of a N. and S. graded dirt road.
80.56	The cor. of secs. 1, 2, 11 and 12, monumented with an iron pipe, 2 ins. diam., 24 ins. long, 12 ins. below surface of ground. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.
	T18N R22W S 2 S 1 S11 S12 1980
	Deposit the iron pipe inside the cor.
	Set a steel fence post alongside the cor.
	Cor. is located under an E. and W. power line, in a wash 150 lks. wide, drains southerly from NE and 100 lks. N. of a paved road, bears N. 85° E., curving E. and N. 85° W. curving W.
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., described in the field notes of the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.
	N. 89°58' W., bet. secs. 1 and 12.
	Along a paved road.
40.04	Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

17

CHAINS

Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 4 ins. below surface of paved road, with aluminum cap mkd.

T18N R22W

$\frac{1}{4}$ S 1
S12

1980

Cor. is located 10 lks. N. of center of paved road.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 42° E., 77.3 lks. dist., mkd. T18N R22W RM $\frac{1}{4}$ S12 51 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 37° W., 73 lks. dist., mkd. T18N R22W RM $\frac{1}{4}$ S12 48.2 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

80.08 The cor. of secs. 1, 2, 11 and 12.

N. $0^\circ 14'$ W., bet. secs. 1 and 2.

Over gently rolling land, through medium creosote.

40.04 The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with a lava stone 14 x 8 x 6 ins., projecting 4 ins. above the ground, in a collar of stone, mkd. $\frac{1}{4}$ on the W. face.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.

T18N R22W

$\frac{1}{4}$
S 2 S 1
1980

Deposit the mkd. stone alongside the cor.

Raise a mound of stone, $1\frac{1}{2}$ ft. base, to top, around the cor.

N. $0^\circ 15'$ W., beginning new measurement.

40.12 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., heretofore described.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., described in the field notes of the N. bdy. of T. 17 N., R. 22 W., surveyed concurrently under this group.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

N. 0°04' W., bet. secs. 34 and 35.

Along State Highway No. 95.

40.05 The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2½ ins. diam., 4 ins. below surface of State Highway No. 95, with brass cap mkd.

T18N R22W
1/4
S34|S35
1962

This point was established in 1962 by proportionate measurement, and monumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 26 ins. long, 5½ ins. diam., set flush with the road. The position of the cor. has long been recognized as the cor. by adjacent landowners and local surveyors, and is accepted as the cor.

Cor. is located 2 lks. W. of center of highway.

Add the marks 1980 to the brass cap.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 58° E., 68.9 lks. dist., mkd. T18N R22W RM 1/4 S35 45.5 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a stop sign.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 58½° E., 78 lks. dist., mkd. T18N R22W RM 1/4 S35 51.5 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a street sign.

N. 0°02' W., beginning new measurement.

40.05 The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2½ ins. diam., 3 ins. below surface of State Highway No. 95, in a hand hole, with brass cap mkd.

T18N R22W
S27|S26
S34|S35
1962

This point was established in 1962 by proportionate measurement in latitude and record measurement in longitude from the cor. of secs. 25, 26, 35 and 36, and monumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 26 ins. long, 5½ ins. diam., set flush with the road. The position of the cor. has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.

Add the marks 1980 to the brass cap.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

Add the marks 1980 to the brass cap.

Set a steel fence post alongside the cor.

Cor. is located off the S. edge of an E. and W. graded gravel road, with a steel fence post alongside.

From the cor. of secs. 26, 27, 34 and 35.

N. 0°10' W., bet. secs. 26 and 27.

Along State Highway No. 95.

40.04 The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2½ ins. diam., 6 ins. below surface of highway, with brass cap mkd.

T18N R22W
1/4
S27|S26
1962

This point was established in 1962 by proportionate measurement, and monumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 26 ins. long, 5½ ins. diam., set flush with the road. The position of the cor. has long been recognized as the cor. by adjacent landowners and local surveyors, and is accepted as the cor.

Add the marks 1980 to the brass cap.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 27° W., 83.2 lks. dist., mkd. T18N R22W RM 1/4 S27 54.9 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 25° W., 62 lks. dist., mkd. T18N R22W RM 1/4 S27 40.9 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

N. 0°09' W., beginning new measurement.

40.04 The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2½ ins. diam., 4 ins. below surface of highway, with brass cap mkd.

T18N R22W
S22|S23
S27|S26
1962

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

This point was established in 1962 by proportionate measurement, and monumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 20 ins. long, 5½ ins. diam., set flush with the road. The position of the cor. has long been recognized as the cor. by adjacent landowners and local surveyors, and is accepted as the cor.

Add the marks 1980 to the brass cap.

Cor. is located 4 lks. W. of the center of the highway.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 82½° E., 44.2 lks. dist., mkd. T18N R22W RM S23 29.2 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a stop sign and telephone pole, lines extend N. and W.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 39½° W., 86.1 lks. dist., mkd. T18N R22W RM S22 56.8 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a power pole, lines extend N., S., E. and W.

From the cor. of secs. 23, 24, 25 and 26.

S. 89°52' W., bet. secs. 23 and 26.

Along graded gravel road.

40.00 The 1/4 sec. cor. of secs. 23 and 26, monumented with the remains of an iron pipe approximately 2 ins. diam., 2½ ft. below surface of road. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. below surface of road, with aluminum cap mkd.

T18N R22W
1 S23
4 S26
1980

Deposit the remains of the iron pipe alongside the cor.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 60½° E., 119.7 lks. dist., mkd. T18N R22W RM 1/4 S23 79 FT. 1980 and an arrow pointing to the cor.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

19

CHAINS

from which

A triangulation station reference monument, bears S. $52^{\circ}09'$ W., 96.8 lks. dist., monumented with a brass tablet 3 ins. diam., set in the head wall of a concrete irrigation ditch, mkd. San 1964 No. 3 1978 and an arrow.

Triangulation station "San", bears N. $39^{\circ}16'$ W., 62.4 lks. dist., monumented with a brass tablet 3 ins. diam., in a 12 ins. base of concrete, projecting 6 ins. above the ground, mkd. San 1964 and a triangle in the center of cap. latitude is $34^{\circ}54'35.17169$ N., longitude is $114^{\circ}35'49.46728$ W.

From the cor. of secs. 25, 26, 35 and 36.

N. $89^{\circ}59'$ W., bet. secs. 26 and 35.

Along graded gravel road.

40.02 The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron pipe, 2 ins. diam., 10 ins. below surface of road, with cap attached, no marks, with another 2 in. diam., iron pipe, 24 ins. below road alongside. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. below surface of road, with aluminum cap mkd.

T18N R22W

$\frac{1}{4}$ S26
S35

1980

Deposit both iron pipes alongside the cor.

Cor. is located in the intersection of graded gravel roads extending E., S. and W.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. $44\frac{3}{4}^{\circ}$ E., 67.9 lks. dist., mkd. T18N R22W RM 1/4 S35 44.8 FT. 1980 and an arrow pointing to the cor.


RM is located 2 lks. N. of an E. and W. fence line.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. $34\frac{1}{4}^{\circ}$ W., 63.9 lks. dist., mkd. T18N R22W RM 1/4 S35 42.2 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a street sign.

N. $89^{\circ}58'$ W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS	
39.86	The cor. of secs. 26, 27, 34 and 35.
	N. 89°58' W., bet. secs. 27 and 34.
	Along graded gravel road.
40.00	Point for the 1/4 sec. cor. of secs. 27 and 34, at record
	dist. and on line with the witness point for secs. 27 and
	34. The 1/4 sec. cor. of secs. 27 and 34 was established
	in 1962 at record bearing and dist. and monumented with
	an iron post, 28 ins. long, 2½ ins. diam., encased in
	concrete, in a vitrified clay tile, 40 ins. long, 8 ins.
	diam., set 28 ins. in the ground with brass cap mkd.
	<p style="text-align: center;">T18N R22W $\frac{1}{4}$ S27 $\frac{1}{4}$ S34 1962</p>
	This corner has been graded out of position.
	Reset the iron post, 8 ins. below surface of S. edge of
	an E. and W. graded gravel road.
	Add the marks 1980 to the brass cap.
	from which
	<p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set</p>
	<p style="padding-left: 40px;">22 ins. in the ground, in a 6 in. base of concrete</p>
	<p style="padding-left: 40px;">for a reference monument, bears N. 30¾° E.,</p>
	<p style="padding-left: 40px;">66.1 lks. dist., mkd. T18N R22W RM 1/4 S27</p>
	<p style="padding-left: 40px;">43.6 FT. 1980 and an arrow pointing to the cor.</p>
	RM is located alongside a power pole, lines extend E., S.
	and W.
	<p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set</p>
	<p style="padding-left: 40px;">22 ins. in the ground, in a 6 in. base of concrete</p>
	<p style="padding-left: 40px;">for a reference monument, bears S. 31½° E.,</p>
	<p style="padding-left: 40px;">71.5 lks. dist., mkd. T18N R22W RM 1/4 S34</p>
	<p style="padding-left: 40px;">47.2 FT. 1980 and an arrow pointing to the cor.</p>
	RM is located at the N. edge of a concrete ditch, bears
	E. and W.
	From this point the witness point bet. secs. 27 and 34,
	bears N. 89°58' W., 37.44 chs. dist., monumented with an
	iron post, 2½ ins. diam., projecting 8 ins. above the
	ground in a 6 in. base of concrete surrounded with a clay
	tile, with brass cap mkd.
	<p style="text-align: center;">  </p>
	<p style="text-align: center;">1962</p>
	In 1962, this cor. was established at record bearing and
	dist. and monumented with an iron post, 28 ins. long, 2½
	ins. diam., encased in concrete, in a vitrified clay
	tile, 40 ins. long, 8 ins. diam., set 26 ins. in the
	ground.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

RM is located alongside a power pole, line bears E. and W.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 1° E., 145.3 lks. dist., mkd. T18N R22W RM 1/4 S26 95.9 FT. 1980 and an arrow pointing to the cor.

RM is located at N. end of a concrete ditch, extends south only.

S. $89^\circ 59'$ W., beginning new measurement.

40.03 The cor. of secs. 22, 23, 26 and 27.

N. $0^\circ 19'$ W., bet. secs. 22 and 23.

Along State Highway No. 95.

40.04 The $1/4$ sec. cor. of secs. 22 and 23, monumented with a $\frac{1}{2}$ in. diam., reinforcement rod, 3 ins. below the surface of the highway. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.

At the cor. point

Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 5 ins. below surface of highway, with aluminum cap mkd.

T18N R22W
1/4
S22|S23
1980

Deposit the reinforcement rod alongside the cor.

Cor. is located 5 lks. E. of center of highway.

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 55° E., 66.5 lks. dist., mkd. T18N R22W RM 1/4 S23 43.9 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. $38\frac{1}{2}^\circ$ E., 83.8 lks. dist., mkd. T18N R22W RM 1/4 S23 55.3 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

N. $0^\circ 28'$ W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

24

CHAINS

- 40.23 Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.
- Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 4 ins. below surface of highway, with aluminum cap mkd.
- T18N R22W
S15|S14
S22|S23
1980
- Cor. is located 3 lks. E. of center of highway.
- from which
- An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. $30\frac{1}{2}^{\circ}$ W., 77.3 lks. dist., mkd. T18N R22W RM S22 51 FT. 1980 and an arrow pointing to the cor.
- RM is located alongside a power pole, lines extend N., S., E. and W.
-
- From the cor. of secs. 13, 14, 23 and 24.
- S. $89^{\circ}45'$ W., bet. secs. 14 and 23.
- Along graded dirt road.
- 40.15 Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.
- T18N R22W
 $\frac{1}{4}$ S14
S23
1980
- Set a steel fence post alongside the cor.
- Cor. is located 45 lks. S. of an E. and W. graded dirt road.
- 80.30 The cor. of secs. 14, 15, 22 and 23.
-
- N. $89^{\circ}47'$ W., bet. secs. 15 and 22.
- Along a graded dirt road.
- 40.15 Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the original cor.
- Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. below surface of road, with aluminum cap mkd.
- T18N R22W
 $\frac{1}{4}$ S15
S22
1980

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

Cor. is located at the N. edge of an E. and W. graded dirt road.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 29½° W. 70.5 lks. dist., mkd. T18N R22W RM 1/4 S22 46.5 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

RM is located under an E. and W. power line.

47.045 The closing cor. of secs. 15 and 22, at intersection with the Fort Mohave Indian Reservation, monumented with an iron pipe, 2 ins. diam., 18 ins. below the ground, no marks. The origin of this monument is unknown, however it is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an aluminum post, 28 ins. long, 1 in. diam., 12 ins. below the ground, with aluminum cap mkd.

	T18N	
FMIR	S15	CC
	S22	
	R22W	
	1980	

Deposit the iron pipe alongside the cor.

Cor. is located a the E. edge of a N. and S. road, which is 37 lks. N. of intersections of graded dirt roads, extending N., E. and W., and 67 lks. N. of an E. and W. power line.

From this point the 8 mile post on the Fort Mohave Indian Reservation, bears N. 1°34' E., 2.00 chs. dist., heretofore described.

From the cor. of secs. 14, 15, 22 and 23.

N. 0°03' W., bet. secs. 14 and 15.

Along State Highway No. 95.

40.23 Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, ¾ in. diam., 6 ins. below surface of highway, with aluminum cap mkd.

	T18N R22W	
	1/4	
	S15 S14	
	1980	

Cor. is located 1 lk. E. of center of highway.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 45° E., 65.3 lks. dist., mkd. T18N R22W RM 1/4 S14 43.1 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 52½° E., 57.7 lks. dist., mkd. T18N R22W RM 1/4 S14 38.1 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

80.46 The cor. of secs. 10, 11, 14 and 15, monumented with a brass tag, 1 in. diam., tacked in center of highway, mkd RLS 5576. This monument was set by Donald C. Chambers, Land Surveyor No. 5576 in Arizona and is accepted as a careful and faithful determination of the position of the original cor.

At the cor. point

Set an aluminum post, 30 ins. long, ¾ in. diam., 5 ins. below surface of highway, with aluminum cap mkd.

T18N R22W
S10|S11
S15|S14
1980

Deposit the brass tag alongside the cor.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 65° W., 39.4 lks. dist., mkd. T18N R22W RM S10 26 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a power pole, lines extend N., E. and S.

From the cor. of secs. 11, 12, 13 and 14.

N. 89°56' W., bet. secs. 11 and 14.

Along a graded dirt road.

40.06 The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron pipe, 1 in. diam., 12 ins. below surface of road, with brass tag attached to the top mkd. RLS 5576. This monument was set by Donald C. Chambers, Land Surveyor No. 5576 in Arizona and is accepted as a careful and faithful determination of the position of the original cor.

At the cor. point

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

27

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 1 in. diam., 8 ins. below surface of road, with aluminum cap mkd.</p> <p style="text-align: center;">T18N R22W $\frac{1}{4}$ S11 S14 1980</p> <p>Deposit the iron pipe alongside the cor. from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 34° E., 27.4 lks. dist., mkd. T18N R22W RM 1/4 S11 18.1 FT. 1980 and an arrow pointing to the cor.</p> <p>RM is located alongside a power pole, lines extend E., S. and W.</p> <p>From this point an iron pipe, 2 ins. diam., 2 ins. below surface of road, bears S. 13°25' W., 9.3 lks. dist., origin unknown.</p> <p style="text-align: center;">_____</p> <p>N. 89°57' W., beginning new measurement.</p> <p>40.08 The cor. of secs. 10, 11, 14 and 15.</p>
	<p>N. 89°53' W., bet. secs. 10 and 15.</p> <p>Along a graded gravel road.</p> <p>40.12 Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an aluminum post, 28 ins. long, 1 in. diam., 10 ins. below surface of road, with aluminum cap mkd.</p> <p style="text-align: center;">T18N R22W $\frac{1}{4}$ S10 S15 1980</p> <p>Cor. is located 10 lks. N. of the center of an E. and W. graded gravel road.</p>
	<p>45.635 Intersect the Fort Mohave Indian Reservation.</p> <p>Point for the closing cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T18N S10 FMIR ——— CC S15 R22W 1980</p> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS	
	<p>From this point a local closing cor., bears N. 89°53' W., .8 of a lk. dist., monumented with an iron pipe, 2 ins. diam., projecting 2 ins. above the ground. The origin of this monument is unknown, however it is accepted as the best available evidence of the position of the original cor.</p>
	<p>From this same point the 7 mile post on the Fort Mohave Indian Reservation, bears N. 0°56' E., 1.82 chs. dist., heretofore described.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>
	<p>N. 0°05' W., bet. secs. 10 and 11.</p>
	<p>Along State Highway No. 95.</p>
<p>40.20</p>	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 5 ins. below surface of center of highway, with aluminum cap mkd.</p>
	<p style="text-align: center;">T18N R22W 1/4 S10 S11 1980</p>
	<p>from which</p>
	<p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. $21\frac{3}{4}$° E., 144.7 lks. dist., mkd. T18N R22W RM 1/4 S11 95.5 FT. 1980 and an arrow pointing to the cor.</p>
	<p>RM is located alongside an old fence cor., fences extend N. and E.</p>
	<p>Set a steel fence post alongside the RM.</p>
	<p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. $37\frac{3}{4}$° E., 62.1 lks. dist., mkd. T18N R22W 1/4 S11 41 FT. 1980 and an arrow pointing to the cor.</p>
	<p>RM is located alongside a road sign.</p>
<p>80.40</p>	<p>The cor. of secs. 2, 3, 10 and 11, monumented with a railroad spike 4 ins. below surface of highway. This monument was set by Mohave County Surveyor and is accepted as a careful and faithful determination of the position of the original cor., from which reference monuments</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

A 1½ in. diam. brass cap, bears N. 45° E.,
105 lks. dist., set in concrete, 6 in. base,
projecting 2 ins. above the ground, mkd. Mohave
Co. Hwy. RM-1 Sta. Pud 1973 and an arrow pointing
to the cor.

A 1½ in. diam., brass cap, bears S. 53¼° E.,
91.4 lks. dist., set in concrete, 6 in. base,
projecting 2 ins. above the ground, mkd. Mohave
Co. Hwy. RM-2 Sta. Pud 1973 and an arrow pointing
to the cor.

At the cor. point

Set an aluminum post, 30 ins. long, ¾ in. diam., 4 ins.
below surface of highway, with aluminum cap mkd.

T18N R22W
S 3 | S 2
S10 | S11
1980

Deposit the railroad spike alongside the cor.

Cor. is located in the intersection of roads, extending
N., S., E. and W.

Set a steel fence post alongside both reference
monuments.

From the cor. of secs. 1, 2, 11 and 12.

S. 89°57' W., bet. secs. 2 and 11.

Along a paved road.

40.17 Point for the 1/4 sec. cor. of secs. 2 and 11, at
proportionate dist.; there is no remaining evidence of
the original cor.

Set an aluminum post, 30 ins. long, ¾ in. diam., 4 ins.
below surface of S. edge of road, with aluminum cap mkd.

T18N R22W
1 | S 2
4 | S11
1980

from which

An iron post, 28 ins. long, 2½ ins. diam., set
21 ins. in the ground, in a 6 in. base of concrete
for a reference monument, bears S. 77° E.,
88 lks. dist., mkd. T18N R22W RM 1/4 S11 58.1 FT.
1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

RM is located under an E. and W. power line and 2 lks. N.
of an old E. and W. fence line.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 16° W., 21.7 lks. dist., mkd. T18N R22W RM 1/4 S11 14.3 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

RM is located under an E. and W. power line and 2 lks. N. of an old E. and W. fence line.

80.34 The cor. of secs. 2, 3, 10 and 11.

S. $89^\circ 30'$ W., bet. secs. 3 and 10.

Along a paved road.

39.97 Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, $\frac{3}{4}$ in. diam., 5 ins. below surface of road, with aluminum cap mkd.

T18N R22W
 $\frac{1}{4}$ S 3
S10
1980

Cor. is located 5 lks. N. of center of paved road, bears E. and W.

44.195 Intersect the Fort Mohave Indian Reservation.

Point for the closing cor. of secs. 3 and 10.

Set a aluminum post, 10 ins. long, $\frac{3}{4}$ in. diam., 5 ins. below surface of road, in a 6 in. base of concrete, with aluminum cap mkd.

FMIR | T18N
| S 3
| S10 CC
| R22W
| 1980

Cor. is located 2 lks. N. of center of a paved E. and W. road.

From this point a local closing cor., origin unknown, bears S. $89^\circ 30'$ W., .8 of a lk. dist., monumented with a large spike nail, flush with surface of road. The origin of this monument is unknown, however it is accepted as the best remaining evidence of the position of the original cor.

From this same point the 6 mile post on the Fort Mohave Indian Reservation, bears N. $0^\circ 56'$ E., 2.07 chs. dist., heretofore described.

The point for the 1/4 sec. cor. of sec. 10 only, is at midpoint on the W. bdy. of sec. 10.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

Set an aluminum post, 28 ins. long, 1 in. diam., 48 ins. below surface of cultivated field.

with aluminum cap mkd.

F MIR | T18N
| 1/4 S10
| R22W
| 1980

Cor. is located 30 lks. N. of an E. and W. graded gravel road.

From this point the 6½ mile post on the Fort Mohave Indian Reservation, bears N. 0°56' E., 1.94 chs. dist., heretofore described.

From the cor. of secs. 2, 3, 10 and 11.

N. 0°06' W., bet. secs. 2 and 3.

Along State Highway No. 95.

39.99 Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.

Set an aluminum post, 30 ins. long, ¾ in. diam., 5 ins. below surface of highway, with aluminum cap mkd.

T18N R22W
1/4
S 3 | S 2
1980

Cor. is located 1 lk. E. of center of highway.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears S. 48¾° W., 64.1 lks. dist., mkd. T18N R22W RM 1/4 S3 42.3 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 34° W., 83.9 lks. dist., mkd. T18N R22W RM 1/4 S3 55.4 FT. 1980 and an arrow pointing to the cor.

Set a steel fence post alongside the RM.

80.07 The cor. of secs. 2, 3, 34 and 35 on the N. bdy. of the Tp., heretofore described.

From the 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2½ ins. diam., 6 ins. below surface of the ground, in a 6 in. base of concrete surrounded with a clay tile, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS

T18N R22W
1/4
S28|S27
1962

This cor. was established in 1962 at record bearing and dist., and monumented with an iron post, 28 ins. long, 2½ ins. diam., encased in a vitrified clay tile, 40 ins. long, 8 ins. diam., set 36 ins. in the ground. The position of the cor. has long been recognized as the cor. by adjacent landowners and local surveyors, and is accepted as the cor.

Add the marks 1980 to the brass cap.

Cor. is located 1 lk. W. of a N. and S. fence line.

North, bet. secs. 27 and 28.

Along a graded dirt road.

40.00

The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2½ ins. diam., 3 ins. below surface of paved road, with brass cap mkd.

T18N R22W
S21|S22
S28|S27
1962

This cor. was established in 1962 at record distance from the 1/4 sec. cor. of secs. 22 and 27 and a projection of the E½ mile bet. secs. 22 and 27, and monumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 40 ins. long, 8 ins. diam., set 24 ins. in the ground. The position of the cor. has long been recognized as the cor. by adjacent landowners and local surveyors, and is accepted as the cor.

Add the marks 1980 to the brass cap.

Cor. is located in the center of a paved road, bears N. 80° W. and S. 80° E., curving easterly.

from which

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 9 1/4° E., 110.9 lks. dist., mkd. T18N R22W RM S22 73.2 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a power pole, lines extend S. and W.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, in a 6 in. base of concrete for a reference monument, bears N. 47½° W., 112 lks. dist., mkd. T18N R22W RM S21 73.9 FT. 1980 and an arrow pointing to the cor.

RM is located alongside a street sign.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 18 N., R. 22 W., Gila and Salt River, Mer., Ariz.

CHAINS		
40.08	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°49' W., bet. secs. 22 and 27.</p> <p>Along a graded dirt road.</p> <p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2½ ins. diam., 18 ins. below the ground, with brass cap mkd.</p> <p style="text-align: center;">T18N R22W 1/4 S22 4 S27 1962</p> <p>In 1962, a capped iron pipe, 2 ins. diam., projecting 14 ins. above the ground was found at this position and remonumented with an iron post, 28 ins. long, 2½ ins. diam., encased in concrete, in a vitrified clay tile, 40 ins. long, 8 ins. diam., set 28 ins. in the ground. The position of the cor. has long been recognized as the cor. by adjacent landowners and local surveyors, and is accepted as the cor.</p> <p>Add the marks 1980 to the brass cap.</p> <p>The cor. has 2 steel fence posts alongside with signs attached, which read, Survey Mon. Do Not Disturb.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°46' W., beginning new measurement.</p>	
39.99	<p>The cor. of secs. 21, 22, 27 and 28.</p> <hr style="width: 100%;"/> <p style="text-align: center;">Subdivision of section 14, T. 18 N., R. 22 W., Gila and Salt River Meridian, Arizona</p> <hr style="width: 100%;"/>	
40.12	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°06' W., on the N. and S. center line of sec. 14.</p> <p>Over level land, through dense salt cedar and mesquite.</p> <p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in in the ground, in a 6 in. base of concrete, with brass cap mkd.</p> <p style="text-align: center;">T18N R22W C 1/4 S14 1980</p> <p>Set a steel fence post alongside the cor.</p> <p>A power pole, bears N. 15° W., 15 lks. dist., lines extend N. and E.</p>	
80.23	<p>The 1/4 sec. cor. of secs. 11 and 14.</p> <hr style="width: 100%;"/> <p>From the 1/4 sec. cor. of secs. 13 and 14.</p>	

Subdivision of section 14, T. 18 N., R. 22 W.,
Gila and Salt River Mer., Arizona

CHAINS		
	S. 89°55' W., on the E. and W. center line of sec. 14.	
	Over level land, through dense salt cedar and mesquite.	
40.11	The C 1/4 sec. cor. of sec. 14.	
80.22	The 1/4 sec. cor. of secs. 14 and 15.	
<p>ADJUSTED MEANDERS OF SPEAR'S LAKE, T. 18 N., R. 22 W., Gila and Salt River Mer., Arizona</p>		
<p>(Retracing the 1905 survey by John J. Fisher)</p>		
<p>From the meander cor. of secs. 31 and 36 on the E. bdy. of the Tp., on the SW side of Spear's Lake, described in the field notes of the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.</p>		
<p>From this point the meander cor. of secs. 6 and 31, Tps. 17 and 18 N., R. 21 W., bears S. 32°08' E., 1.89 chs. dist., described in the field notes of the north bdy. of T. 17 N., R. 21 W., surveyed concurrently under this group.</p>		
<p>With the adjusted meanders of Spear's Lake in sec. 36.</p>		
	N. 20°19' W., 5.37 chs.	
	N. 36°25' W., 5.56 chs.	
	N. 50°15' W., 4.47 chs.	
	N. 45°43' W., 2.88 chs.	
	N. 61°19' W., 5.86 chs.	
	N. 56°48' W., 3.87 chs.	
	N. 82°12' W., 3.58 chs.	To upper end of Lake.
	N. 54°37' E., 14.42 chs.	Cross upper end of Lake. At 8.11 chs. dist., point for Angle Point No. 7 on medial line, not monumented.
	S. 52°29' E., 3.02 chs.	
	S. 52°59' E., 6.64 chs.	
	S. 45°32' E., 2.11 chs.	
	S. 49°15' E., 2.22 chs.	The meander cor. of secs. 31 and 36 on the E. bdy. of the Tp., on the NE side of Spear's Lake, described in the field notes of the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.

MEDIAL LINE OF SPEAR'S LAKE,
T. 18 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS


From the meander cor. of secs. 31 and 36 on the E. bdy. of the Tp., on the SW side of Spear's Lake, described in the field notes of the W. bdy. of T. 18 N., R. 21 W., surveyed concurrently under this group.

On a line normal to the medial line, segregating sec. 36.

N. 62°35' E., 7.24 chs.

Point for Angle Point No. 1 on the medial line.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.




Set a steel fence post alongside the cor.

Thence on the medial line

N. 27°25' W., 1.88 chs.

Point for Angle Point No. 2.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.




Set a steel fence post alongside the cor.

N. 35°57' W., 3.59 chs.

Point for Angle Point No. 3.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a 6 in. base of concrete, with brass cap mkd.



Set a steel fence post alongside the cor.

MEDIAL LINE OF SPEAR'S LAKE,
T. 18 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS

N. 41°21' W., 7.01 chs.

Point for Angle Point
No. 4.

Set an aluminum post, 30
ins. long, $\frac{3}{4}$ in. diam.,
30 ins. below surface of
cultivated field, with
aluminum cap mkd.

T18N
R22W | R21W
S36 | S31
AP4 |
1980

N. 48°12' W., 3.24 chs.

Point for Angle Point
No. 5.

Set an aluminum post, 30
ins. long, $\frac{3}{4}$ in. diam.,
30 ins. below surface of
cultivated field, with
aluminum cap mkd.

T18N
R22W | R21W
S36 | S31
AP5 |
1980

From this point on a line
normal to the medial line
the meander cor. of
secs. 31 and 36, bears
N. 41°48' E., 5.45 chs.
dist., on the E. bdy. of
the Tp., on the NE side of
Spear's Lake, described in
the field notes of the
W. bdy. of T. 18 N.,
R. 21 W., surveyed concur-
rently under this group.

N. 48°12' W., 5.20 chs.

Point for Angle Point
No. 6, not monumented.

N. 56°10' W., 10.26 chs.

At end of course, point
for Angle Point No. 7, on
upper end of Lake, not
monumented.

GENERAL DESCRIPTION

The land encompassed in this survey is located just east
of the Colorado River, in the Mohave Valley, about 4
miles north of Needles, California.

The elevation ranges from about 460 to 500 ft. above sea
level.

T. 18 N., R. 22 W., Gila and Salt River Mer., Arizona

CHAINS

The soil consists of a sandy loam of which a major portion is under cultivation or being developed for that purpose. The undeveloped areas are covered with dense brush, mesquite, salt cedar and arrowweed.

Access is by way of State Highway No. 95, which is located along the 2nd meridional line. There are a number of paved, graded gravel and unimproved roads on or close to most section lines.

CHAINS

39

(I) ~~(XX)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day and supplemental special instructions dated January 25, 1980, of December, 19 61, (I) ~~(XX)~~ have dependently resurveyed a portion of the former boundary of the Fort Mohave Indian Reservation in fractional Tps. 18 and 19 North, R. 22 W., a portion of the north boundary, a portion of the subdivisional lines, a survey of subdivisions in section 14, and a survey of adjusted meanders and medial line of Spear's Lake in section 36, Township 18 North, Range 22 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

September 26, 1980
(Date)

Paul L. Reeves
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the former boundary of the Fort Mohave Indian Reservation in fractional Tps. 18 and 19 North, R. 22 W., a portion of the north boundary, a portion of the subdivisional lines, a survey of subdivisions in section 14, and a survey of adjusted meanders and medial line in sec. 36, Township 18 North, Range 22 West, Gila and Salt River Meridian, Arizona

executed by Paul L. Reeves, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

FEB 25 1981
(Date)

J. D. Voorhies
(Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)