

ARIZONA RECTANGULAR SURVEY

Form 9600-9
(December 1979)
(formerly 9180-6)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

R 5131

BOOK 5131

FIELD NOTES

Page 1

OF

THE DEPENDENT RESURVEY

OF

A PORTION OF THE SECOND STANDARD PARALLEL NORTH

THROUGH RANGES 5 AND 6 WEST

A PORTION OF THE WEST BOUNDARY

A PORTION OF THE SUBDIVISIONAL LINES

CERTAIN BOUNDARIES OF MINERAL SURVEYS

AND

THE SURVEY OF SUBDIVISIONS IN SECS.

14, 23 AND 26

OF

TOWNSHIP 8 NORTH, RANGE 5 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

PAUL L. REEVES

CADASTRAL SURVEYOR

Under special instructions dated JANUARY 3, 1979, approved JANUARY 4, 1979,

AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED APRIL 16, 1979, APPROVED

APRIL 17, 1979, which provided for the surveys included under [redacted] Group

Number 611, and assignment instructions dated JANUARY 3, 1979.

Survey commenced MARCH 22, 1979

Survey completed MAY 11, 1979

INDEX DIAGRAM

Township 8 North, Range 5 West

	<u>6</u>	<u>5</u>	<u>3</u>	<u>3</u>	<u>2</u>	
<u>7</u>	6	35 5	32 4	8	2	16 1
	34	33	31	29	26	16
	7	8	30 9	28 10	25 11	15 12
			30	27	24	14
	18	17	16	15	14	13 13
				23 23	22	12
	19	20	21	22	21 23	11 24
					20	11
	30	29	28	27	19 26	9 25
					17	8
	31	32	33	34	35	36

Subdivisions of Sections

- sec. 14 . . . p. 36
- sec. 23 . . . p. 40
- sec. 26 . . . p. 42

Mineral Surveys

- No. 1587A, Niggerben Lode P44
- No. 1587A, Montana Lode P45&P47
- No. 1587A, Dutchman Lode P45
- No. 1587A, Frenchman Lode P47
- No. 1587A, May Lode P48
- No. 1587A, Alma Lode P49
- No. 1587A, Copperhead Lode P50
- No. 1587A, Oro Grande Lode P50&P53
- No. 1587A, Colossal Lode P51

T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

The south boundary was surveyed by Solomon W. Foreman in 1871 and resurveyed by John F. Hesse in 1909. Jerrold E. Knight resurveyed the south boundary of sections 32 and 33 in 1969. The west boundary was surveyed by Solomon W. Foreman in 1871 and resurveyed by John F. Hesse in 1909. The north bdy. (Second Standard Parallel North) was surveyed by Johnston B. McLaughlin in 1883 and resurveyed by John F. Hesse in 1909. Chas. M. Pidgeon resurveyed a portion of the north boundary in 1916. The north one half mile between secs. 7 and 12 on the east boundary of the township was surveyed by William A. Hancock in 1882. The north one half mile between secs. 7 and 12 was re-surveyed and the remainder of the east boundary was surveyed by John F. Hesse in 1909. The north 2 miles were resurveyed by Benjamin J. Kinsey in 1929. The subdivisional lines were surveyed by John F. Hesse in 1909. The boundaries of section 14 were resurveyed by Paul G. Bauer in 1970. Francis B. Jacobs executed mineral survey No. 1587A in 1901.

The following field notes are those of the dependent re-survey of a portion of the Second Standard Parallel North through Ranges 5 and 6 West, a portion of the west boundary, a portion of the subdivisional lines, certain boundaries of mineral surveys and the survey of subdivisions in secs. 14, 23, and 26, Township 8 North, Range 5 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specification set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 611, Arizona, Dated January 3, 1979, and Supplemental Special Instructions dated April 16, 1979.

The direction of lines were determined by direct solar observation and refer to the true meridian.

Prior to restoration of any corners, the lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions; lost corners were reestablished at proportionate positions based on the original record, but not until exhausting every reasonable possibility of finding direct evidence for the control of each corner. The retracement data were thoroughly verified and only the true line field notes are given herein.

The survey was done with a Zeiss SM 4 total station instrument.

The geographic position of the SE cor. of sec. 25, as scaled from the U.S. Geological Survey Quadrangle map "Wickenburg, Ariz.," prepared in 1964, is as follows:

Latitude 34°00' N. Longitude 112°43.1' W.

The mean magnetic declination is 14°30' E.

Dependent Resurvey of a Portion of the
Second Standard Parallel North through
R. 5 W., Gila and Salt River Meridian, Arizona

(Restoring the 1916 resurvey by Chas. M. Pidgeon)

4

Dependent Resurvey of a Portion of the
Second Standard Parallel North through
R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

Beginning at the standard township cor. of sec. 36 only, T. 9 N., Rs. 4 and 5 W., monumented with a malapais stone, 16 x 12 x 12 ins., projecting 8 ins. above the ground, mkd. SC, 6 grooves and 9 N on N. face and 6 grooves and 5 W on W. face.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

S C
T9N | T9N
R5W | S31
S36
R4W
1979

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

S. 89°43' W., on the S. bdy. of sec. 36.

Over mountainous land, through medium undergrowth.

2.10 True point for the closing cor. of sec. 1, T. 8 N., R. 5 W. and sec. 31, T. 9 N., R. 4 W., described in the field notes for T. 8 N., R. 4 W., executed concurrently.

40.00 The standard 1/4 sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, with brass cap mkd.

1/4 S36
S C
1916

Mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.

Remark the cap to read

S C
1/4 S36
1979
1916

N. 77°35' W., beginning new measurement.

0.38 The original standard 1/4 sec. cor. of sec. 36, (now an angle point) monumented with a malapais stone, 18 x 12 x 8 ins., projecting 6 ins. above the ground, mkd. AP on S. face, with a mound of stone, 2½ ft. base, 1 ft. high, N. of the cor.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the
Second Standard Parallel North through
R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">A P S C T9N R5W <u>S36</u> 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°49' W., beginning new measurement.</p>	
1.46	Point for the 1/4 sec. cor. of sec. 1 only, hereinafter described.	
39.62	<p>The standard cor. of secs. 35 and 36, monumented with a malapais stone, 15 x 8 x 9 ins., projecting 7 ins. above the ground, mkd. SC on N., 1 groove on E. and 5 grooves on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S C T9N R5W <u>S35 S36</u> S 1 T8N R5W 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located at a fence cor., fences extend E. and S.</p> <hr/> <p>S. 89°32' W., on the S. bdy. of sec. 35.</p> <p>Over mountainous land, through medium undergrowth.</p>	
1.895	The closing cor. of secs. 1 and 2, hereinafter described.	
40.06	<p>The standard 1/4 sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">S C 1/4 <u>S35</u> 1916</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <hr/> <p>From the standard cor. of secs. 32 and 33, monumented with a granite stone, 22 x 16 x 8 ins., projecting 8 ins. above the ground, mkd. SC on N., 3 grooves on E. and 2 grooves on the W. face.</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of the
Second Standard Parallel North through
R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

S C
T9N R5W
S32|S33
S 4
T8N R5W
1979

from which the original bearing trees

A palo verde, 6 ins. diam., bears N. 82° E.,
101 lks. dist., illegible scribe marks.

A palo verde, 6 ins. diam., bears N. 48° W.,
51 lks. dist., with a rotted out blaze,
no marks visible.

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of the cor.

N. $89^\circ 33'$ W., on the S. bdy. of sec. 32.

Over rolling land, through medium undergrowth.

1.57 The closing cor. of secs. 4 and 5, hereinafter described.

31.60 Track road, bears N. 10° E. and S. 10° W.

39.43 The original standard $1/4$ sec. cor. of sec. 32,
(now an angle point) monumented with a malapais stone,
24 x 12 x 10 ins., projecting 6 ins. above the ground, in
a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, mkd. AP on the
N. face.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

A P
S C
T9N R5W
S32
1979

Deposit the mkd. stone alongside the iron post.

Rebuild the mound of stone, $2\frac{1}{2}$ ft. base, $2\frac{1}{2}$ ft. high, N. of the cor.

N. $86^\circ 43'$ W., beginning new measurement.

0.40 The standard $1/4$ sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap mkd.

$1/4$ S32
S C
1916

Mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of the cor.

Dependent Resurvey of a Portion of the
Second Standard Parallel North through
R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Remark the cap to read</p> <div style="text-align: center;"> <p>S C 1/4 S32 1979 1916</p> <hr/> </div> <p>S. 89°44' W., beginning new measurement.</p>
1.72	Point for the 1/4 sec. cor. of sec. 5 only, hereinafter described.
39.88	<p>The standard cor. of secs. 31 and 32, monumented with a malapais stone, 16 x 12 x 12 ins., flush with the ground, mkd. SC on N., and 3 notches on the E. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C T9N R5W S31 S32 S 5 T8N R5W 1979</p> </div> <p>from which the remains of an original bearing tree</p> <p style="padding-left: 40px;">A mesquite stump, 16 ins. diam., bears N. 16 3/4° E., 130 lks. dist., no marks visible.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A mesquite, 14 ins. diam., bears N. 48½° W., 140 lks. dist., mkd. SC T9N R5W S31 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <hr/> <p style="text-align: center;">(Restoring the 1909 resurvey by John F. Hesse)</p> <p>N. 89°42' W., on the S. bdy. of sec. 31.</p> <p>Over rolling land, through medium undergrowth.</p>
1.82	True point for the closing cor. of secs. 5 and 6, hereinafter described.
40.01	<p>The standard 1/4 sec. cor. of sec. 31, monumented with a malapais stone, 15 x 14 x 5 ins., projecting 4 ins. above the ground, in a scattered mound of stone, mkd. SC 1/4 on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the
Second Standard Parallel North through
R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS	
	S C T9N R5W <u>1/4 S31</u> 1979
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.

	S. 89°54' W., beginning new measurement.
1.74	Point for the 1/4 sec. cor. of sec. 6 only, hereinafter described.
20.40	Highway No. 89, bears N. 13° E. and S. 13° W.
40.02	The standard cor. of Tps. 9 N., Rs. 5 and 6 W., monumented with a mound of stone, 2 ft. base, 1 ft. high.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	S C T9N R6W R5W <u>S36 S31</u> S 6 T8N R5W 1979
	Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.
<hr/> Dependent Resurvey of a Portion of the Second Standard Parallel North through R. 6 W., Gila and Salt River Mer., Arizona <hr/>	
	(Restoring the 1897 survey by Philip Contzen)
	From the standard cor. of Tps. 9 N., Rs. 5 and 6 W., heretofore described.
	S. 89°56' W., on the S. bdy. of sec. 36.
	Over gently rolling land, through medium undergrowth.
0.70	Fence line, bears S. 15° E. and N. 15° W.
1.87	Point for the closing cor. of Tps. 8 N., Rs. 5 and 6 W., hereinafter described.
2.30	Atchison, Topeka and Santa Fe railroad, bears S. 10° E. and N. 10° W.
40.02	Point for the standard 1/4 sec. cor. of sec. 36, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of a Portion of the Second
Standard Parallel North through R. 6 W.,
Gila and Salt River Mer., Arizona

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

S C
T9N R6W
1/4 S36
1979

Set a mesquite post, 6 ins. diam., 6 ft. long, alongside the iron post.

Cor. is located 40 lks. W. of a small wash, drains southerly.

80.04 The standard cor. of secs. 35 and 36, monumented with a sandstone, 12 x 8 x 6 ins., loosely set and mkd. SC on N., 5 grooves on W. and 1 groove on the E. face.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

S C
T9N R6W
S35 | S36
S 1
T8N R6W
1979

Set a mesquite post, 6 ins. diam., 4 ft. long, alongside the iron post.

Dependent Resurvey of a Portion of the W. Bdy.,
T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona

(Restoring the 1909 resurvey by John F. Hesse)

From the cor. of secs. 6 and 7 only, monumented with a malapais stone, 17 x 17 x 6 ins., projecting 4 ins. above the ground, mkd. with 1 groove on the N. and 5 grooves on the S. face, with a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

T8N | T8N
R6W | S 6
S12 | S 7
R5W
1979

Deposit the mkd. stone, alongside the iron post.

Rebuild the mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, E. of the cor.

Cor. is located at a fence cor., fences extend E., S. and N. 60° W.

N. $0^\circ 03'$ E., on the W. bdy. of sec. 6.

Dependent Resurvey of a Portion of the W. Bdy.,
T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona

CHAINS-

- Over gently rolling land, through medium undergrowth.
- 6.05 Point for the cor. of secs. 1 and 12 only, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
- 40.02 The 1/4 sec. cor. of sec. 6 only, monumented with a malapais stone, 18 x 14 x 12 ins., projecting 6 ins. above the ground, mkd. 1/4 on W. face.
- At the cor. point
- Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.
- T8N
R6W | R5W
| 1/4 S 6
1979
- Deposit the mkd. stone alongside the iron post.
- Raise a mound of stone, 2½ ft. base, 1½ ft. high, E. of the cor.
- Cor. is located 67 lks. E. of a track road, bears S. 35° E. and N. 35° W.
-
- N. 0°04' E., beginning new measurement.
- 32.41 Point for the closing cor. of Tps. 8 N., Rs. 5 and 6 W., on the Second Standard Parallel North, at proportionate dist.; there is no remaining evidence of the original cor.
- Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
- T9N R6W
S36
S 1 | S 6
|
C C
T8N
R6W R5W
1979
- Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor.
- Set a steel fence post alongside the iron post.
- From this point the standard cor. of Tps. 9 N., Rs. 5 and 6 W., bears N. 89°56' E., 1.87 chs. dist., heretofore described.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Ariz.

(Restoring the 1909 survey by John F. Hesse)

From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., described in the field notes for T. 8 N., R. 4 W., executed concurrently.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona

	CHAINS	
		<p>N. 89°57' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through medium undergrowth.</p>
	40.09	<p>The 1/4 sec. cor. of secs. 25 and 36, monumented with a granite stone, 14 x 12 x 7 ins., projecting 6 ins. above the ground, mkd. 1/4 on the N. face, in a mound of stone, 3 ft. base, 6 ins. high, from which original bearing trees</p> <p style="padding-left: 40px;">A palo verde, 8 ins. diam., bears N. 32° E., 65 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A mesquite snag, 8 ins. diam., bears S. 28° W., 114 lks. dist., mkd. 1/4 S36 BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W 1 S25 4 S36 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p>
	32.80	<p>N. 89°51' W., beginning new measurement.</p> <p>From this point on line, the SW cor. of corral, 160 x 80 ft., bears north, 44 lks. dist., long side bears N. and S.</p>
	40.02	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a granite stone, 24 x 10 x 8 ins., projecting 8 ins. above the ground, mkd. with 1 groove on E. and 1 groove on the S. face, with a scattered mound of stone N. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W S26 S25 S35 S36 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of the cor.</p> <p>Fence cor., bears south, 21 lks. dist., fences extend N., S. and E.</p> <p>Cor. is located 45 lks. S. of an E. and W. power and telephone line.</p>
		<p>N. 0°01' E., bet. secs. 25 and 26.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	Over rolling land, through medium undergrowth.	
20.16	Point for the S 1/16 sec. cor. of secs. 25 and 26.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T8N R5W	
	S 1/16	
	S26 S25	
	1979	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.	
	From this point an iron rod ¾ in. diam., projecting 12 ins. above the ground, bears N. 15° E., 4.8 lks. dist., origin unknown.	
	From this same point an open end pipe ¾ in. diam., projecting 4 ins. above the ground, bears south, 2.6 lks. dist., origin unknown.	
	A fence cor., bears N. 1° W., 75.5 lks. dist., fences extend S. and W.	
40.32	The 1/4 sec. cor. of secs. 25 and 26, monumented with a malapais stone, 20 x 12 x 7 ins., projecting 8 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 2½ ft. base, 1 ft. high, E. of the cor., from which the original bearing trees	
	A dead palo verde, 4 ins. diam., bears	
	S. 84° E., 100 lks. dist., illegible scribe marks.	
	A dead palo verde, 8 ins. diam., bears	
	S. 59° W., 27 lks. dist., illegible scribe marks.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.	
	T8N R5W	
	1/4	
	S26 S25	
	1979	
	Deposit the mkd. stone alongside the iron post.	
	—————	
	N. 0°01' W., beginning new measurement.	
19.99	Point for the N 1/16 sec. cor. of secs. 25 and 26.	
	Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock in a mound of stone, 4 ft. base, to top, with brass cap mkd.	
	T8N R5W	
	N 1/16	
	S26 S25	
	1979	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
39.98	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a $\frac{3}{4}$ in. open end pipe, origin unknown, projecting 12 ins. above the ground, in a mound of stone, 2 ft. base, 1 ft. high. This cor. is accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., over the open end pipe, 14 ins. in the ground, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W S23 S24 S26 S25 1979</p> <p>Cor. is located on steep S. slope and 2 chs. S. of an E. and W. ridge.</p>	
	<p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., described in the field notes for T. 8 N., R. 4 W., executed concurrently.</p> <p>West, bet. secs. 24 and 25.</p> <p>Over rolling land, through medium undergrowth.</p>	
40.15	<p>The $\frac{1}{4}$ sec. cor. of secs. 24 and 25, monumented with a malapais stone, 16 x 10 x 9 ins., projecting 4 ins. above the ground, mkd. $\frac{1}{4}$ on the N. face, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A palo verde, 7 ins. diam., bears N. 75° E., 38 lks. dist., illegible scribe marks.</p> <p style="padding-left: 40px;">The remains of a palo verde stump, bears S. $43\frac{1}{2}^\circ$ W., 40 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W $\frac{1}{4}$ S24 $\frac{1}{4}$ S25 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, N. of the cor.</p>	
39.98	<p>The cor. of secs. 23, 24, 25 and 26.</p>	
	<p>N. $0^\circ 08'$ E., bet. secs. 23 and 24.</p> <p>Over rolling land, through medium undergrowth.</p>	
39.57	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented with a granite stone, 16 x 12 x 6 ins., projecting 6 ins. above the ground, mkd. $\frac{1}{4}$ on W. face, with a mound of stone, 2 ft. base, 6 ins. high, W. of the cor., from which the original bearing trees</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS

A palo verde, 8 ins. diam., bears N. 72 1/4° E.,
104 lks. dist., illegible scribe marks.

A palo verde, 6 ins. diam., bears S. 69 1/4° W.,
140 lks. dist., illegible scribe marks.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in
the ground, with brass cap mkd.

T8N R5W
1/4
S23|S24
1979

Deposit the mkd. stone alongside the iron post.

Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W.
of the cor.

N. 0°04' E., beginning new measurement.

40.06

The cor. of secs. 13, 14, 23 and 24, monumented with an
iron post, 2 1/2 ins. diam., projecting 14 ins. above the
ground, in a mound of stone, 2 ft. base, 1 ft. high, with
brass cap mkd.

T8N R5W
S14|S13
S23|S24
1970

Cor. is at a fence cor., fences extend N., S., E., and W.
and under a power line, bears E. and W.

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy.
of the Tp., described in the field notes for T. 8 N.,
R. 4 W., executed concurrently.

N. 89°56' W., bet. secs. 13 and 24.

Over rolling land, through medium undergrowth.

19.08

Intersect line 3-4, M.S. No. 1587A, Niggerben Lode, at a
point from which Cor. No. 4 bears S. 15°26' W., 1.97 chs.
dist., hereinafter described.

21.65

Intersect line 4-1, M.S. No. 1587A, Oro Grande Lode, at a
point from which Cor. No. 4 bears N. 36°16' W., 3.89 chs.
dist., hereinafter described.

38.57

Intersect line 3-4, M.S. No. 1587A, Colossal Lode, at a
point from which Cor. No. 3 bears S. 40°36' W., 5.84
chs. dist., hereinafter described.

39.94

The 1/4 sec. cor. of secs. 13 and 24, monumented with a
granite stone, 16 x 10 x 8 ins., projecting 6 ins. above
the ground, mkd. 1/4 on the N. face, with a mound of
stone, 2 1/2 ft. base, 1 ft. high, NW of the cor.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in
the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T8N R5W $\frac{1}{4}$ S13 $\frac{4}{4}$ S24 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located under a power line, bears E. and W.</p> <p>From this point a mine shaft, bears N. 2° E., 220 lks. dist.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°50' W., beginning new measurement.</p>	
40.14	<p>The cor. of secs. 13, 14, 23 and 24.</p> <hr/> <p style="text-align: center;">(Restoring the 1970 resurvey by Paul G. Bauer)</p> <p>N. 0°07' E., bet. secs. 13 and 14.</p> <p>Over rolling land, through medium undergrowth.</p>	
20.00	<p>Point for the S 1/16 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a 5/8 in. reinforcement rod, 4 ft. long, 3 ft. in the ground, in a mound of stone, 2½ ft. base, to top, with aluminum cap attached and mkd.</p>	
	<p style="text-align: center;">T8N R5W S 1/16 S14 S13 1979</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N. 59° E., 95 lks. dist., mkd. S 1/16 S13 BT.</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears S. 83° E., 104 lks. dist., mkd. XBT.</p> <p>Cor. is located in a sandy overflow area, 70 lks. dist., from the left bank of the Hassayampa River, bears N. 10° E. and S. 10° W.</p>	
40.00	<p>True point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist. falls in a ravine, drains N. 80° W., in unsafe location, not monumented.</p>	
40.50	<p>The witness 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 2½ ins. diam., projecting 14 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T8N R5W 1/4 W C S14 S13 ↓ 1970</p> <hr style="width: 20%; margin: 10px auto;"/>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	N. 0°01' E., beginning new measurement.	
19.41	Point for the N 1/16 sec. cor. of secs. 13 and 14.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.	
	T8N R5W	
	N 1/16	
	S14 S13	
	1979	
	from which	
	A palo verde, 6 ins. diam., bears S. 40° W.,	
	33 lks. dist., bark scribed N 1/16 S14 BT.	
29.365	Point for the N-N 1/64 sec. cor. of secs. 13 and 14, not monumented.	
39.32	True point for the cor. of secs. 11, 12, 13 and 14, determined at record distances from 2 witness corners. The cor. point falls in the Hassayampa River; not monumented.	
	from which	
	A witness cor. of secs. 11, 12, 13 and 14, bears	
	N. 89°50' W., 7.00 chs. dist., hereinafter	
	described.	
	A witness cor. of secs. 11, 12, 13 and 14, bears	
	N. 0°02' E., 6.00 chs. dist., hereinafter	
	described.	
	(Restoring the 1909 survey by John F. Hesse)	
	From the cor. of secs. 7, 12, 13, and 18 on the E. bdy. of the Tp., described in the field notes for T. 8 N., R. 4 W., executed concurrently.	
	N. 89°34' W., bet. secs. 12 and 13.	
	Over mountainous land, through medium undergrowth.	
39.29	The witness 1/4 sec. cor. of secs. 12 and 13, monumented with a granite stone, 16 x 9 x 6 ins., projecting 8 ins. above the ground, mkd. W C 1/4 on the N. face, with a mound of stone, 2½ ft. base, 2½ ft. high, E. of the cor. and a mound of stone, 2½ ft. base, 2½ ft. high, N. of the cor.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 2 ft. base, to top with brass cap mkd.	
	W C	
	T8N R5W	
	1 ← S12	
	4 ← S13	
	1979	
	Deposit the mkd. stone alongside the iron post.	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS	
	N. 89°55' W., beginning new measurement.
0.20	Bluff, edge bears N. and S.
1.00	True point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist., falls in the Hassayampa River, not monumented.
40.87	True point for the cor. of secs. 11, 12, 13 and 14.
	N. 0°02' E., bet. secs. 11 and 12.
	Over rolling land through medium undergrowth.
6.00	The witness cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2½ ins. diam., projecting 12 ins. above the ground in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T8N R5W W C S11 S12 S14 S13 1970</p>
	N. 0°05' E., beginning new measurement.
33.96	The 1/4 sec. cor. of secs. 11 and 12, monumented with a malapais stone, 16 x 11 x 6 ins., projecting 2 ins. above the ground, mkd. 1/4 on W. face, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T8N R5W 1/4 S11 S12 1979</p>
	Deposit the mkd. stone alongside the iron post.
	North, beginning new measurement.
0.60	Fence line, bears S. 70° E. and N. 70° W.
40.16	The cor. of secs. 1, 2, 11 and 12, monumented with a volcanic stone, 20 x 20 x 8 ins., projecting 6 ins. above the ground, mkd. with 5 grooves on the S. and 1 groove on the E. face.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T8N R5W S 2 S 1 S11 S12 1979</p>
	Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Raise a mound of stone, 2½ ft. base, 3 ft. high, W. of the cor.</p> <p>Cor. is located at a fence cor., fences extend N. and W.</p>
<p>39.93</p>	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., described in the field notes for T. 8 N., R. 4 W., executed concurrently.</p> <p>N. 89°50' W., bet. secs. 1 and 12.</p> <p>Over rolling land, through medium undergrowth.</p> <p>The 1/4 sec. cor. of secs. 1 and 12, monumented with a malapais stone, 18 x 10 x 8 ins., projecting 7 ins. above the ground, mkd. 1/4 on the N. face, with a scattered mound of stone N.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W $\frac{1}{4}$ S 1 $\frac{1}{4}$ S12 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located 30 lks. S. of a wash, 15 lks. wide, 2 ft. deep, drains easterly from NW.</p> <p style="text-align: center;">_____</p> <p>N. 89°48' W., beginning new measurement.</p>
<p>39.96</p>	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>North, bet. secs. 1 and 2.</p> <p>Over rolling land, through medium undergrowth.</p>
<p>40.15</p>	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a malapais stone, 16 x 14 x 11 ins., projecting 6 ins. above the ground, mkd. 1/4 on the W. face, in a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A stump hole, bears N. 86 1/4° E., 45 lks. dist., a down palo verde, 8 ins. diam., alongside, mkd. 1/4 S 1 BT.</p> <p style="padding-left: 40px;">A palo verde snag, 10 ins. diam., bears N. 54° W., 47 lks. dist., rotted out blaze, no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W 1/4 S 2 S 1 1979</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1 ft. high, W. of the cor.

Cor. is located 107 lks. W. of a N. and S. fence line.

N. 0°09' E., beginning new measurement.

32.90

The closing cor. of secs. 1 and 2 on the Second Standard Parallel North, monumented with a granite stone, 20 x 14 x 10 ins., projecting 5 ins. above the ground, mkd. CC on the S., 1 groove on the E. and 5 grooves on the W. face, in a mound of stone, 3 ft. base, to top, from which the original bearing trees

A dead palo verde, 5 ins. diam., bears S. 33½° E., 120 lks. dist., no marks visible.

A palo verde, 7 ins. diam., bears S. 17½° W., 88 lks. dist., rotted out blaze, no marks visible.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T9N R5W
S35
S 2 | S 1
C C
T8N R5W
1979

Deposit the mkd. stone alongside the iron post.

From this point the standard cor. of secs. 35 and 36, T. 9 N., R. 5 W., bears N. 89°32' E., 1.895 chs. dist., heretofore described.

The point for the 1/4 sec. cor. of sec. 1 only, T. 8 N., R. 5 W., is at proportionate dist., on the N. bdy. of sec. 1.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, with brass cap mkd.

1/4 S 1
T8N R5W
1979

Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of the cor.

From this point the angle point on the S. bdy. of sec. 36, bears N. 89°49' E., 1.46 chs. dist., heretofore described.

From the cor. of secs. 25, 26, 35 and 36.

S. 89°59' W., bet. secs. 26 and 35.

Over gently rolling land, through medium undergrowth.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS	
20.04	Point for the E 1/16 sec. cor. of secs. 26 and 35, not monumented.
27.09	<p>The witness 1/4 sec. cor. of secs. 26 and 35, monumented with a granite stone, 17 x 17 x 6 ins., projecting 12 ins. above the ground, mkd. 1/4 on the N. face, with a 3/4 in. open end pipe, 18 ins. long, projecting 5 ins. above the ground alongside the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T8N R5W 1/4 ← S26 S35 1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N. 24 1/2° E., 18.5 lks. dist., mkd. XBT.</p> <p>Deposit the mkd. stone and iron pipe alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 1 1/2 ft. high, N. of the cor.</p> <p>Cor. is located 5 lks. S. of a telephone line and 30 lks. S. of a power line, both bear E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°59' W., beginning new measurement.</p>
12.99	True point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist. falls in overflow area of Hassayampa River in unsafe location, not monumented.
52.96	<p>The cor. of secs. 26, 27, 34 and 35, determined from the remains of the original bearing trees</p> <p style="padding-left: 40px;">The remains of a mesquite stump, 9 ins. diam., bears N. 52 1/2° E., 141 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A mesquite stump, 9 ins. diam., bears S. 46 1/2° E., 118 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A mesquite stump, 10 ins. diam., bears S. 48 1/2° W., 127 lks. dist., mkd. T8N R5W S34 BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R5W S27 S26 S34 S35 1979</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N. 38° E., 107 lks. dist., mkd. T8N R5W S26 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>A mesquite, 8 ins. diam., bears S. 54° W., 96.5 lks. dist., mkd. T8N R5W S34 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <p>From this point a local property cor. bears S. 88°01' W., 64 lks. dist., monumented with a bolt. This point was established by Burl A. Willmoth a Registered Highway Engineer in 1949.</p>	
40.00	<p>N. 0°01' E., bet. secs. 26 and 27.</p> <p>Over rolling land, through medium undergrowth.</p> <p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a malapais stone, 20 x 12 x 7 ins., projecting 10 ins. above the ground, mkd. 1/4 on the W. face, in a mound of stone, 2 ft. base, 1½ ft. high, from which the remains of the original bearing trees</p> <p>A palo verde snag, 8 ins. diam., bears S. 62 1/4° E., 87 lks. dist., illegible scribe marks.</p> <p>A dead palo verde, 9 ins. diam., bears S. 38½° W., 43 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W 1/4 S27 S26 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>	
39.84	<p>North, beginning new measurement.</p> <p>The cor. of secs. 22, 23, 26 and 27, monumented with a lava stone, 20 x 12 x 8 ins., projecting 5 ins. above the ground, mkd. with 2 grooves on the E. and 5 grooves on the S. face, with a ½ in. reinforcement rod, 15 ins. long, projecting 5 ins. above the ground alongside the cor., with aluminum cap attached and mkd.</p> <p style="text-align: center;">22 23 27 26 L.S. 4529</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W S22 S23 S27 S26 1979</p>	

22

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS

Deposit the mkd. stone and reinforcement rod alongside the iron post.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.

Cor. is located at a fence cor., fences extend E. and S.

From the cor. of secs. 23, 24, 25 and 26.

S. $89^{\circ}44'$ W., bet. secs. 23 and 26.

Over rolling land, through medium undergrowth.

20.00

The E $1/16$ sec. cor. of secs. 23 and 26, monumented with a steel rod, 1 in. diam., 20 ins. long, projecting 8 ins. above the ground, origin unknown. This point is harmoniously related to existing original cors., and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, over the iron rod, in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T8N R5W
E $1/16$ S23
S26
1979

S. $89^{\circ}44'$ W., beginning new measurement.

19.95

The $1/4$ sec. cor. of secs. 23 and 26, monumented with a 2 in. open end pipe, filled with concrete, projecting 2 ins. above the ground, mkd. $1/4$ S, origin unknown. This point is harmoniously related to existing original cors. and accepted as a careful and faithful perpetuation of the position of the original cor., not remonumented.

from which

A mesquite, 11 ins. diam., bears S. $19\frac{1}{2}^{\circ}$ W.,
6 lks. dist., mkd. $1/4$ S26 BT.

A mesquite, 14 ins. diam., bears N. $54\frac{1}{2}^{\circ}$ W.,
76.5 lks. dist., mkd. $1/4$ S23 BT.

Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.

Cor. is located 26 lks. E. of a track road, bears N. 17° E. and S. 17° W.

A fence cor., bears S. 80° E., 15 lks. dist., fences extend N., E., S. and W.

S. $89^{\circ}32'$ W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

	CHAINS		
	20.07	<p>The W 1/16 sec. cor. of secs. 23 and 26, monumented with a $\frac{1}{2}$ in. reinforcement rod, projecting 4 ins. above the ground, with an aluminum cap attached and mkd. property corner L.S. 4529, with a mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high, W. of the cor. This point is harmoniously related to existing original cors., and is accepted as a careful and faithful determination of the cor. position, not remonumented.</p>	
		<p>Cor. is located 1 link S. of an E. and W. fence line.</p>	
		<p>S. $89^{\circ}39'$ W., beginning new measurement.</p>	
	19.99	<p>The cor. of secs. 22, 23, 26 and 27.</p>	
		<p>N. $0^{\circ}02'$ E., bet. secs. 22 and 23.</p>	
		<p>Over rolling land through medium undergrowth.</p>	
	19.985	<p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p>	
		<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
		<p>T8N R5W</p>	
		<p>S 1/16</p>	
		<p>S22 S23</p>	
		<p>1979</p>	
		<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.</p>	
		<p>From this point a 1 in. open end pipe, projecting 10 ins. above the ground, in a mound of stone, $1\frac{1}{2}$ ft. base, 6 ins. high, bears S. $83\frac{1}{2}^{\circ}$ W., 13.6 lks. dist., origin and purpose unknown.</p>	
	39.97	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with a granite stone, 17 x 12 x 6 ins., projecting 7 ins. above the ground, mkd. 1/4 on the W. face, in a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees</p>	
		<p>A dead palo verde, 6 ins. diam., bears</p>	
		<p>S. $39\frac{1}{2}^{\circ}$ E., 18 lks. dist., no marks visible.</p>	
		<p>A dead palo verde, 10 ins. diam., bears</p>	
		<p>N. 54° W., 99 lks. dist., no marks visible.</p>	
		<p>At the cor. point</p>	
		<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
		<p>T8N R5W</p>	
		<p>1/4</p>	
		<p>S22 S23</p>	
		<p>1979</p>	
		<p>Deposit the mkd. stone alongside the iron post.</p>	
		<p>Rebuild the mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of the cor.</p>	

24

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	N. 0°06' E., beginning new measurement.	
20.00	Point for the N 1/16 sec. cor. of secs. 22 and 23, not monumented.	
40.00	True point for the cor. of secs. 14, 15, 22 and 23, determined at record distances from 2 witness corners. The cor. point falls in an insecure area on the E. bank of a wash draining SE.; not monumented.	
	from which	
	A witness cor. of secs. 14, 15, 22 and 23, bears N. 89°56' W., 80 lks. dist., hereinafter described.	
	A witness cor. of secs. 14, 15, 22 and 23, bears N. 0°47' W., 2.25 chs. dist., hereinafter described.	
	(Restoring the 1970 resurvey by Paul G. Bauer)	
	From the cor. of secs. 13, 14, 23 and 24.	
	West, bet. secs. 14 and 23.	
	Over rolling land, through medium undergrowth.	
20.00	The E 1/16 sec. cor. of secs. 14 and 23, monumented with an iron post, 2½ ins. diam., projecting 18 ins. above the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.	
	T8N R5W E 1/16 $\frac{S14}{S23}$ 1970	
	from which	
	A 1 1/4 in. open end pipe, projecting 18 ins. above the ground, bears S. 71° E., 3.9 lks. dist., (1970 record S. 38°40' E., 3.2 lks. dist.)	
	A fence cor., bears N. 55° E., 12 lks. dist., fences extend E. and N. 35° W.	
	Cor. is located 4 lks. S. of an E. and W. power line.	

	N. 89°58' W., beginning new measurement.	
20.04	True point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist. falls in the Hassayampa River in unsafe location, not monumented.	
27.04	The witness 1/4 sec. cor. of secs. 14 and 23, monumented with a granite stone, 20 x 14 x 8 ins., projecting 6 ins. above the ground, mkd. 1/4 WC on the N. face, in a mound of stone, 3 ft. base, 1 ft. high.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">W C T8N R5W $\frac{1}{4} \frac{S14}{S23} \rightarrow$ 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 1½ ft. high, N. of the cor.</p> <p>Cor. is located on W. bank of Hassayampa River.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°42' W., beginning new measurement.</p>	
12.96	<p>The W 1/16 sec. cor. of secs. 14 and 23, monumented with an iron post, 2½ ins. diam., projecting 12 ins. above the ground, in a mound of stone, 2½ ft. base, 8 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W W 1/16 $\frac{S14}{S23}$ 1970</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°46' W., beginning new measurement.</p>	
20.05	<p>True point for the cor. of secs. 14, 15, 22 and 23.</p> <hr/> <p>N. 89°56' W., bet. secs. 15 and 22.</p>	
0.80	<p>A witness cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W W C $\frac{S15 S14}{S22 S23} \rightarrow$ 1970</p> <p>Mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <p>Line bet. secs. 15 and 22, discontinued at this witness cor.</p> <hr/> <p>From the true point for the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 0°47' W., bet. secs. 14 and 15.</p>	
2.25	<p>A witness cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R4W W C $\frac{S15 S14}{S22 S23}$ 1970</p> <p>Mound of stone, 2 ft. base, 6 ins. high, W. of the cor.</p>	

CHAINS	
	<p>Line bet. secs. 14 and 15, discontinued at this witness cor.</p> <hr/> <p>From the true point for the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°50' W., bet. secs. 11 and 14.</p> <p>Over rolling land through medium undergrowth.</p>
7.00	<p>The witness cor. of secs. 11, 12, 13 and 14, monumented with a granite stone, 20 x 10 x 6 ins., projecting 6 ins. above the ground, mkd. WC on the NE. face, 4 notches on the S., and 1 notch on the E. edges, with a mound of stone, 2½ ft. base, 6 ins. high, W. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T8N R5W S11 S12 S14 S13 → 1979</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>N. 89°49' W., beginning new measurement.</p>
2.96	<p>Point for the E-E 1/64 sec. cor. of secs. 11 and 14, not monumented.</p>
7.94	<p>The W-E-E 1/256 sec. cor. of secs. 11 and 14, monumented with a 5/8 in. steel rod, 20 ins. long, projecting 5 ins. above the ground, origin unknown. This point is harmoniously related to existing original cors., and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S11 W-E-E 1/256 S14 1979</p> </div> <p>Deposit the steel rod alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <hr/> <p>S. 89°59' W., beginning new measurement.</p>
4.99	<p>Point for the E 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T8N R5W E 1/16 $\frac{S11}{S14}$ 1979</p> <p>from which</p> <p>An XBO stamped on a cattle guard, bears S. $39\frac{1}{2}^{\circ}$ E., 30.8 lks. dist.</p> <p>The north cor. of a trailer house, 38 x 10 ft., bears S. $3^{\circ}30'$ E., 116 lks. dist., long side, bears S. 22° W.</p> <p>The NE. cor. of a shed, 12 x 10 ft., bears S. $21^{\circ}14'$ W., 5.69 chs. dist., long side, bears S. 35° W.</p> <p>The E. cor. of a trailer house, 24 x 8 ft., bears S. $18^{\circ}21'$ W., 4.91 chs. dist., long side, bears S. 57° W.</p>	
24.94	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 16 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W $\frac{1}{4}$ $\frac{S11}{S14}$ 1970</p> <hr/> <p>(Restoring the 1909 survey by John F. Hesse)</p> <p>From the cor. of secs. 10, 11, 14 and 15, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 12 ins. above the ground, in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W $\frac{S10}{S15}$ $\frac{S11}{S14}$ 1970</p> <p>from which the 1909 bearing trees</p> <p>A palo verde, 7 ins. diam., bears N. $2\frac{1}{2}^{\circ}$ E., 38 lks. dist., open blaze, no marks visible.</p> <p>A dead palo verde, 8 ins. diam., bears S. $25\frac{1}{4}^{\circ}$ W., 50 lks. dist., open blaze, no marks visible.</p> <p>N. $0^{\circ}02'$ E., bet. secs. 10 and 11.</p> <p>Over rolling land, through medium undergrowth.</p>	
40.08	<p>The 1/4 sec. cor. of secs. 10 and 11, monumented with a malapais stone, 16 x 12 x 10 ins., projecting 10 ins. above the ground, mkd. 1/4 on the W. face, in a mound of stone, $2\frac{1}{2}$ ft. base, 6 ins. high, from which the original bearing trees</p> <p>A palo verde, 5 ins. diam., bears S. $88\frac{1}{2}^{\circ}$ E., 59 lks. dist., illegible scribe marks.</p> <p>A palo verde, 6 ins. diam., bears S. 58° W., 35 lks. dist., illegible scribe marks.</p>	

28

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W 1/4 S10 S11 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>North, beginning new measurement.</p> <p>40.15 The cor. of secs. 2, 3, 10 and 11, monumented with a granite stone, 18 x 12 x 10 ins., projecting 8 ins. above the ground, mkd. with 2 grooves on the E. and 5 grooves on the S. face, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A stump hole, bears N. 60° E., 131 lks. dist., a down palo verde alongside, 7 ins. diam., no marks visible.</p> <p style="padding-left: 40px;">A palo verde snag, 6 ins. diam., bears S. 23° E., 29 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A stump hole, bears S. 72° W., 133 lks. dist., a down palo verde alongside, 6 ins. diam., no marks visible.</p> <p style="padding-left: 40px;">A stump hole, bears N. 22½° W., 30 lks. dist., a down palo verde alongside, 6 ins. diam., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W S 3 S 2 S10 S11 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the cor.</p> <p>Cor. is located 3 lks. S. of an E. and W. fence line.</p>	
<p>40.15</p>	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°56' W., bet. secs. 2 and 11.</p> <p>Over rolling land, through medium undergrowth.</p> <p>The 1/4 sec. cor. of secs. 2 and 11, monumented with a granite stone, 16 x 12 x 8 ins., projecting 6 ins. above the ground, mkd. 1/4 on the N face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>T8N R5W $\frac{1}{4}$ S 2 S11 1979</p>	
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p> <p>Cor. is located 3 lks. S. of an E. and W. fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°57' W., beginning new measurement.</p>	
39.98	<p>The cor. of secs. 2, 3, 10 and 11.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°59' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through medium undergrowth.</p>	
40.05	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with a malapais stone, 15 x 14 x 6 ins., projecting 6 ins. above the ground, mkd. 1/4 on the N. face, with a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
	<p>T8N R5W $\frac{1}{4}$ S10 S15 1979</p>	
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°58' W., beginning new measurement.</p>	
40.16	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a malapais stone, 20 x 12 x 10 ins., projecting 8 ins. above the ground, mkd. with 3 notches on the E. and 4 notches on the S. edges, with a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor. and a steel fence post alongside the cor., from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A dead palo verde, 5 ins. diam., bears N. 68½° E., 54 lks. dist., blazed with no marks visible.</p> <p style="margin-left: 40px;">A dead palo verde, 6 ins. diam., bears S. 48° E., 166 lks. dist., illegible scribe marks.</p> <p style="margin-left: 40px;">A dead palo verde, 6 ins. diam., bears S. 26½° W., 33 lks. dist., illegible scribe marks.</p> <p style="margin-left: 40px;">A dead palo verde, 8 ins. diam., bears N. 26° W., 87 lks. dist., blazed with no marks visible.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W S 9 S10 S16 S15 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p>	
40.28	<p>N. 0°06' W., bet. secs. 9 and 10.</p> <p>Over rolling land, through medium undergrowth.</p> <p>The 1/4 sec. cor. of secs. 9 and 10, monumented with a malapais stone, 24 x 10 x 8 ins., projecting 10 ins. above the ground, mkd. 1/4 on the W. face in a mound of stone, 4 ft. base, 1 ft. high, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A palo verde, 6 ins. diam., bears N. 54 3/4° E., 76 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A palo verde, 5 ins. diam., bears N. 15½° W., 54 lks. dist., illegible scribe marks.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W 1/4 S 9 S10 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3½ ft. base, 2 ft. high, W. of the cor.</p> <p>From this point a bench mark, bears S. 0°19' E., 6.65 chs. dist., monumented with a 3½ in. brass tablet set in a concrete base, 4 ins. above the ground, mkd.</p> <p style="text-align: center;">Corps of Engineers - U.S. Army Red Slave Station Designation</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">Year 1962 Agency L.A. Dist. Survey Mark</p>	
39.97	<p>N. 0°02' W., beginning new measurement.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with a malapais stone, 16 x 12 x 10 ins., flush with the ground, mkd. with 5 notches on the S. and 3 notches on the E. edges, from which the original bearing trees</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS

A palo verde, 8 ins. diam., bears S. 44½° E., 70 lks. dist., illegible scribe marks.

A palo verde, 4 ins. diam., bears S. 68½° W., 65 lks. dist., with blaze, no marks visible.

A palo verde, 4 ins. diam., bears N. 68° W., 61 lks. dist., with blaze, no marks visible.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T8N R5W
S 4 | S 3
S 9 | S10
1979

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

Cor. is located in an E. and W. fence line and 13 lks. W. of a draw, 6 lks. wide, drains NW.

From the cor. of secs. 2, 3, 10 and 11.

N. 89°48' W., bet. secs. 3 and 10.

Over rolling land, through medium undergrowth.

40.29

The 1/4 sec. cor. of secs. 3 and 10, monumented with a malapais stone, 16 x 10 x 10 ins., loosely set, no marks visible, from which the remains of the original bearing trees

A palo verde, 8 ins. diam., bears S. 61° W., 127 lks. dist., partially rotted blaze, with illegible scribe marks.

A stump hole, bears N. 23 1/4° E., 196 lks. dist., a down palo verde alongside, 10 ins. diam., with illegible scribe marks.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T8N R5W
1 | S 3
4 | S10
1979

Deposit the mkd. stone alongside the iron post.

Cor. is located 24 lks. N. of an E. and W. fence line.

S. 89°58' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS									
40.01	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°44' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through medium undergrowth.</p>								
39.86	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a malapais stone, 22 x 14 x 8 ins., projecting 8 ins. above the ground, mkd. 1/4 on the N. face, with a steel fence post alongside the cor., from which the original bearing trees</p> <p style="padding-left: 40px;">A palo verde, 10 ins. diam., bears N. 80° E., 31 lks. dist., rotted blaze, no marks visible.</p> <p style="padding-left: 40px;">A palo verde, 8 ins. diam., bears S. 9½° W., 104 lks. dist., illegible scribe marks.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R5W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">1</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> </tr> <tr> <td style="padding: 0 5px;">4</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">16</td> </tr> </table> <p>1979</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°44' W., beginning new measurement.</p>	1	S	9	4	S	16		
1	S	9							
4	S	16							
39.98	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a malapais stone, 20 x 12 x 8 ins., projecting 12 ins. above the ground, mkd. with 4 notches on the S. and 4 notches on the E. edges, with a steel fence post alongside.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R5W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">8</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">9</td> </tr> <tr> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">17</td> <td style="padding: 0 5px;">S</td> <td style="padding: 0 5px;">16</td> </tr> </table> <p>1979</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.</p> <hr/> <p>N. 0°02' E., bet. secs. 8 and 9.</p> <p>Over rolling land, through medium undergrowth.</p>	S	8	S	9	S	17	S	16
S	8	S	9						
S	17	S	16						

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
40.03	<p>The 1/4 sec. cor. of secs. 8 and 9, monumented with a limestone, 20 x 12 x 8 ins., projecting 4 ins. above the ground, mkd. 1/4 on the W. face, from which an original bearing tree</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N. 77½° W., 139 lks. dist., mkd. 1/4 S.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W 1/4 S 8 S 9 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 85 lks. S. of a wash, 5 lks. wide, drains SW.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°06' W., beginning new measurement.</p>	
40.06	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a sandstone, 20 x 14 x 10 ins., projecting 12 ins. above the ground, mkd. with 5 grooves on the S. and 4 grooves on the E. face, with a scattered mound of stone, SE, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fallen palo verde, 8 ins. diam., bears N. 23½° E., 54 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A palo verde, 8 ins. diam., bears S. 54 1/4° E., 30 lks. dist., illegible scribe marks.</p> <p style="padding-left: 40px;">A palo verde, 8 ins. diam., bears S. 46 3/4° W., 132 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A palo verde, 10 ins. diam., bears N. 63° W., 196 lks. dist., with blaze, no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W S 5 S 4 S 8 S 9 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>Cor. is located in an E. and W. fence line.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>S. 89°54' W., bet. secs. 4 and 9.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land, through medium undergrowth.
39.97	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist., mkd. with a 1 in. reinforcement rod origin unknown, projecting 3 ins. above the ground, in a washed area. This position was not monumented in the original survey and is not now monumented with an official monument due to the probability of destruction.
47.96	The witness 1/4 sec. cor. of secs. 4 and 9, monumented with a malapais stone, 22 x 22 x 8 ins., projecting 6 ins. above the ground, mkd. WC 1/4 on the N. face in a mound of stone, 3 ft. base, 1 ft. high, from which the remains of an original bearing tree A palo verde, bears N. 5½° W., 26 lks. dist., no marks visible. At the cor. point Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> W C T8N R5W $\frac{1}{4} \frac{S 4}{S 9} \rightarrow$ 1979 </div> Deposit the mkd. stone alongside the iron post. Rebuild the mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor. Cor. is located 23 lks. S. of an E. and W. fence line. <hr style="width: 20%; margin: auto;"/> N. 89°25' W., beginning new measurement.
31.84	The cor. of secs. 4, 5, 8 and 9. <hr style="width: 100%; border: 0.5px solid black;"/>
	N. 0°05' E., bet. secs. 4 and 5. Over rolling land, through medium undergrowth.
40.08	The 1/4 sec. cor. of secs. 4 and 5, monumented with a malapais stone, 18 x 12 x 6 ins., projecting 4 ins. above the ground, mkd. 1/4 on the W. face, from which the remains of the original bearing trees A dead palo verde, 8 ins. diam., bears S. 52° E., 189 lks. dist., mkd. 1/4 S4 BT. A stump hole of the remains of a palo verde, bears S. 53½° W., 114 lks. dist., no marks. At the cor. point Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T8N R5W 1/4 S 5 S 4 1979 </div>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p> <hr/> <p>N. $0^{\circ}04'$ E., beginning new measurement.</p> <p>32.08 The closing cor. of secs. 4 and 5 on the Second Standard Parallel North, monumented with a malapais stone, 24 x 16 x 8 ins., projecting 7 ins. above the ground, mkd. CC on the S., 4 grooves on the E. and 2 grooves on the W. face, from which the original bearing trees</p> <p style="padding-left: 40px;">The remains of a palo verde, 6 ins. diam., bears S. 79° E., 82 lks. dist., rotted blaze, no marks visible.</p> <p style="padding-left: 40px;">A palo verde, 6 ins. diam., bears S. $19\frac{1}{2}^{\circ}$ W., 26 lks. dist., rotted blaze, no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R5W S32 <hr/>S 5 S 4 C C T8N R5W 1979</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the cor.</p> <p>From this point the standard cor. of secs. 32 and 33, bears S. $89^{\circ}33'$ E., 1.57 chs. dist., heretofore described.</p> <hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. $89^{\circ}59'$ W., bet. secs. 5 and 8.</p> <p>Over rolling land, through medium undergrowth.</p> <p>39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R5W $\frac{1}{4}$ S 5 <hr/>$\frac{1}{4}$ S 8 1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A catclaw, 11 ins. diam., bears N. $4\frac{1}{2}^{\circ}$ W., 39.5 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N. of the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS						
	<p>Cor. is located 7 lks. N. of an E. and W. fence line and 60 lks. E. of a wash 1 ch. wide, drains S. 20° E.</p>					
79.90	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a malapais stone, 16 x 10 x 8 ins., projecting 6 ins. above the ground, mkd. with 5 grooves on the S. and 5 grooves on the E. face, with a 3/8 in. reinforcement rod, 18 ins. long, alongside the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R5W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>1979</p> </div> <p>Deposit the mkd. stone and reinforcement rod, alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located in an E. and W. fence line and 30 lks. W. of a draw, 40 lks. wide, drains S. 60° E.</p>	S 6	S 5	S 7	S 8	
S 6	S 5					
S 7	S 8					
	<p>N. 89°56' W., bet. secs. 6 and 7.</p>					
	<p>Over rolling land, through medium undergrowth.</p>					
35.89	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented with a malapais stone, 18 x 15 x 8 ins., projecting 5 ins. above the ground, mkd. 1/4 on the N. face, with a mound of stone, 1 ft. base, 1 ft. high, N. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R5W</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1</td> <td style="padding: 0 5px;">S 6</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">4</td> <td style="padding: 0 5px;">S 7</td> </tr> </table> <p>1979</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located in an E. and W. fence line.</p>	1	S 6	4	S 7	
1	S 6					
4	S 7					
	<p style="text-align: center;">_____</p> <p>West, beginning new measurement.</p>					
14.80	<p>Highway No. 89, bears S. 10° E., and N. 10° W.</p>					
26.30	<p>Atchison, Topeka and Santa Fe Railroad, bears S. 10° E. and N. 10° W.</p>					

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS	
44.27	<p>The cor. of secs. 6 and 7 only, on the W. bdy. of the Tp., heretofore described.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°01' W., bet. secs. 5 and 6.</p> <p>Over rolling land, through medium undergrowth.</p>
40.05	<p>The 1/4 sec. cor. of secs. 5 and 6, monumented with a granite stone, 16 x 15 x 12 ins., projecting 3 ins. above the ground, mkd. 1/4 on the W. face, from which the original bearing trees</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears N. 31° E., 114 lks. dist., with blaze, no marks visible.</p> <p style="padding-left: 40px;">A palo verde, 8 ins. diam., bears S. 37° W., 71 lks. dist., illegible scribe marks.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W 1/4 S 6 S 5 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>North, beginning new measurement.</p>
31.56	<p>The witness closing cor. of secs. 5 and 6, monumented with a malapais stone, 24 x 11 x 8 ins., projecting 8 ins. above the ground, mkd. WC CC on the S. face, from which an original bearing tree</p> <p style="padding-left: 40px;">A mesquite, 9 ins. diam., bears S. 37° W., 140 lks. dist., mkd. 8N R5W S6 BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T9N R5W S31 S 6 S 5 ↓ T8N R5W C C 1979</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, S. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>North, beginning new measurement.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 8 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS	
0.74	<p>Intersect the Second Standard Parallel North, true point for the closing cor. of secs. 5 and 6, falls in wash, not monumented.</p> <p>From this point the standard cor. of secs. 31 and 32, bears S. 89°42' E., 1.82 chs. dist., heretofore described.</p>
	<p>The point for the 1/4 sec. cor. of sec. 5 only, T. 8 N., R. 5 W., at midpoint on the N. bdy. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <hr style="width: 10%; margin: auto;"/> 1/4 S 5 T8N R5W 1979 </p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor.</p> <p>From this point the standard 1/4 sec. cor. of sec. 32, T. 9 N., R. 5 W., bears N. 89°44' E., 1.72 chs. dist., heretofore described.</p>
	<p>The point for the 1/4 sec. cor. of sec. 6 only, T. 8 N., R. 5 W., at proportionate dist. on the N. bdy. of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> <hr style="width: 10%; margin: auto;"/> 1/4 S 6 T8N R5W 1979 </p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor.</p> <p>From this point the standard 1/4 sec. cor. of sec. 31, T. 9 N., R. 5 W., bears N. 89°54' E., 1.74 chs. dist., heretofore described.</p>
	<p>Subdivision of Sec. 14, T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona</p>
19.97	<p>From the true point for the 1/4 sec. cor. of secs. 14 and 23.</p> <p>N. 0°12' E., on the N and S. center line of sec. 14.</p> <p>Over rolling land, through medium undergrowth.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T8N R5W C S 1/16 S14 C 1979 </p>

Subdivision of Sec. 14, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>from which</p> <p>A ¾ in. open end pipe, projecting 18 ins. above the ground, bears S. 56½° W., 21.2 lks. dist.</p> <p>A ¾ in. open end pipe, projecting 3 ft. above the ground, bears N. 86° W., 14.8 lks. dist.</p>
39.94	<p>Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W C 1/4 S14 1979</p>
59.89	<p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W. of the cor.</p> <p>Point for the C-N 1/16 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W C N 1/16 S14 C 1979</p>
62.70	<p>Cor. is located 32 lks. E. of a wash, 15 lks. wide, drains southerly.</p> <p>Graded road, bears SE curving westerly and N. 65° W., curving westerly.</p>
79.84	<p>The 1/4 sec. cor. of secs. 11 and 14.</p>
20.02	<hr/> <p>From the true point for the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 89°58' W., on the E. and W. center line of sec. 14.</p> <p>Over gently rolling land, through medium undergrowth.</p> <p>The C-E 1/16 sec. cor. of sec. 14, monumented with a ½ in. open end pipe, 18 ins. long, projecting 10 ins. above the ground, origin unknown. This point is accepted as a careful and faithful determination of the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W E 1/16 C _____ C S 14 1979</p>

Subdivision of Sec. 14, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit the open end pipe alongside the iron post.</p> <p>From this point the SW cor. of a house, 26 x 24 ft., bears S. 29° E., 158 lks. dist., long side bears N. 85° E.</p> <p>From this same point a wood frame shop, 29 x 22 ft., bears S. 71° E., 96 lks. dist., long side bears S. 5° E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°55' W., beginning new measurement.</p>
0.85	Graded road, bears S. 30° E. and N. 30° W.
13.80	Fence line, bears S. 15° E. and N. 15° W.
19.98	The C 1/4 sec. cor. of sec. 14.
60.13	The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., projecting 15 ins. above the ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.
	<p>T8N R5W 1/4 S15 S14 1970</p>
	Mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
	<hr style="width: 20%; margin: 10px auto;"/> <p>NE 1/4, Section 14</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>From the C-E 1/16 sec. cor. of sec. 14.</p> <p>N. 0°09' E., on the N. and S. center line of the NE 1/4, sec. 14.</p> <p>Over rolling land, through medium undergrowth.</p>
19.92	<p>Point for the NE 1/16 sec. cor., at intersection with the E. and W. center line of the NE 1/4, sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p>T8N R5W NE 1/16 S14 1979</p>
	<p>Cor. is located 190 lks. W. of a bluff at right bank of the Hassayampa River, bears northerly and southerly.</p>
22.20	Fence line, bears N. 40° E. and S. 40° W.
29.895	<p>Point for the C-N-NE 1/64 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p>S14 C-N-NE 1/64 1979</p>

Subdivision of Sec. 14, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A mesquite, 9 ins. diam., bears S. 4° W., 87 lks. dist., mkd. C-N-NE 1/64 S14 BT.</p> <p>A steel rod, ½ in. diam., projecting 8 ins. above the ground, bears N. 1° W., 22.5 lks. dist.</p> <p>A well, bears S. 9°35' W., 6.00 chs. dist.</p>	
39.87	<p>The E 1/16 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>S. 89°59' W., on the E. and W. center line of the NE 1/4, sec. 14.</p> <p>Over rolling land, through medium undergrowth.</p>	
9.98	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 14, not mon- umented.</p>	
19.96	<p>The NE 1/16 sec. cor. of sec. 14.</p>	
39.92	<p>The C-N 1/16 sec. cor. of sec. 14.</p> <hr/> <p>NE 1/4 of the NE 1/4, Section 14</p> <hr/> <p>From the point for the C-E-NE 1/64 sec. cor. of sec. 14.</p> <p>N. 0°04' E., on the N. and S. center line of the NE 1/4, of the NE 1/4, sec. 14.</p>	
9.965	<p>Point for the NE-NE 1/64, sec. cor., at intersection with the E. and W. center line of the NE 1/4 of the NE 1/4, sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S14 NE-NE 1/64 1979</p>	
	<p>from which</p> <p>A mesquite, 8 ins. diam., bears N. 34° E., 50 lks. dist., mkd. NE-NE 1/64 S14 BT.</p> <p>From this point the NW cor. of a cabin, 18 x 14 ft., bears S. 82°15' E., 5.72 chs. dist., long side, bears S. 42° W.</p>	
19.94	<p>The point for the E-E 1/64 sec. cor. of secs. 11 and 14.</p> <hr/> <p>From the point for the N-N 1/64 sec. cor. of secs. 13 and 14.</p> <p>N. 89°57' W., on the E. and W. center line of the NE 1/4 of the NE 1/4, sec. 14.</p>	

Subdivision of Sec. 14, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
9.965	The NE-NE 1/64 sec. cor. of sec. 14.
13.70	Left bank of the Hassayampa River, course south.
14.948	Point for the C-W-NE-NE 1/256 sec. cor. of sec. 14, falls in the Hassayampa River, impractical to monument.
17.70	Right bank of the Hassayampa River.
19.93	The C-N-NE 1/64 sec. cor. of sec. 14.
<p>Subdivision of Sec. 23, T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona</p>	
	From the 1/4 sec. cor. of secs. 23 and 26.
	N. 0°01' E., on the N. and S. center line of sec. 23.
	Over gently rolling land, through medium undergrowth.
19.86	Point for the C-S 1/16 sec. cor. of sec. 23, not monumented.
39.72	Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 23, not monumented.
59.77	Point for the C-N 1/16 sec. cor. of sec. 23.
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p>T8N R5W C N 1/16 S23 C 1979</p>
	from which
	<p>A mesquite, 5 ins. diam., bears S. 65° E., 71.5 lks. dist., mkd. C-N 1/16 S23 BT.</p>
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
	Cor. is located 110 lks. E. of the left bank of the Hassayampa River, course SW.
79.82	True point for the 1/4 sec. cor. of secs. 14 and 23.
	From the 1/4 sec. cor. of secs. 23 and 24.
	S. 89°57' W., on the E. and W. center line of sec. 23.
	Over rolling land, through medium undergrowth.
20.01	Point for the C-E 1/16 sec. cor. of sec. 23.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

Subdivision of Sec. 23, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T8N R5W E 1/16 C-----C S23 1979</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the cor.</p> <p>Cor. is located in a gravel pit area.</p>
40.02	The point for the C 1/4 sec. cor. of sec. 23.
60.05	Point for the C-W 1/16 sec. cor. of sec. 23.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T8N R5W W 1/16 C-----C S23 1979</p>
80.08	The 1/4 sec. cor. of secs. 22 and 23.
	<p style="text-align: center;">SW 1/4, Section 23</p> <hr style="width: 20%; margin: auto;"/> <p>From the W 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 0°05' E., on the N. and S. center line of the SW 1/4, sec. 23.</p> <p>Over rolling land, through medium undergrowth.</p>
19.94	Point for the SW 1/16 sec. cor., at intersection with the E. and W. center line of the SW 1/4, sec. 23.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 9 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T8N R5W SW 1/16 S23 1979</p>
	<p>From this point a 1 1/4 in. open end pipe, projecting 18 ins. above the ground, bears S. 49° W., 44.5 lks. dist.</p> <p>Cor. is located 25 lks. W. of the right bank of the Hassayampa River, course S.</p>
39.86	The C-W 1/16 sec. cor. of sec. 23.
	<p style="text-align: center;">-----</p> <p>From the point for the C-S 1/16 sec. cor. of sec. 23.</p> <p>S. 89°46' W., on the E. and W. center line of the SW 1/4, sec. 23.</p> <p>Over rolling land, through medium undergrowth.</p>
20.05	The SW 1/16 sec. cor. of sec. 23.

Subdivision of Sec. 23, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.06	<p>The S 1/16 sec. cor. of secs. 22 and 23.</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">NW 1/4, Section 23</p> <hr style="width: 20%; margin: auto;"/> <p>From the C-W 1/16 sec. cor. of sec. 23.</p> <p>N. 0°08' E., on the N. and S. center line of the NW 1/4, sec. 23.</p> <p>Over rolling land, through medium undergrowth.</p>
20.03	<p>Point for the NW 1/16 sec. cor., at intersection with the E. and W. center line of NW 1/4, sec. 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W NW 1/16 S23 1979</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of the cor.</p> <p>From this point a 1 in. open end pipe, projecting 20 ins. above the ground, bears N. 82° W., 35.7 lks. dist.</p>
40.06	<p>The W 1/16 sec. cor. of secs. 14 and 23.</p> <hr style="width: 20%; margin: auto;"/> <p>From the C-N 1/16 sec. cor. of sec. 23.</p> <p>S. 89°53' W., on the E. and W. center line of the NW 1/4, sec. 23.</p> <p>Over rolling land, through medium undergrowth.</p>
20.01	<p>The NW 1/16 sec. cor. of sec. 23.</p>
40.05	<p>The point for the N 1/16 sec. cor. of secs. 22 and 23.</p>
<hr/> <p>Subdivision of Sec. 26, T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the true point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>N. 0°05' E., on the N. and S. center line of sec. 26.</p> <p>Over river bottom land, through medium undergrowth.</p>
20.08	<p>Point for the C-S 1/16 sec. cor. of sec. 26, not monumented.</p>
40.16	<p>Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 26, not monumented.</p>
60.14	<p>Point for the C-N 1/16 sec. cor. of sec. 26, not monumented.</p>
80.12	<p>The 1/4 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p>


Subdivision of Sec. 26, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S. 89°46' W., on the E. and W. center line of sec. 26. Over rolling land, through medium undergrowth.</p> <p>20.02 Point for the C-E 1/16 sec. cor. of sec. 26</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W E 1/16 C-----C S26 1979</p> <p>from which</p> <p style="text-align: center;">A mesquite, 10 ins. diam., bears S. 61° E., 78 lks. dist., mkd. C-E 1/16 S26 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.</p> <p>40.04 The point for the C 1/4 sec. cor. of sec. 26.</p> <p>80.05 The 1/4 sec. cor. of secs. 26 and 27.</p>
	<p style="text-align: center;">NE 1/4, Section 26</p> <hr style="width: 20%; margin: auto;"/> <p>From the C-E 1/16 sec. cor. of sec. 26.</p> <p>N. 0°01' W., on the N. and S. center line of the NE 1/4, sec. 26.</p> <p>Over gently rolling land, through medium undergrowth.</p> <p>19.985 Point for the NE 1/16 sec. cor., at intersection with the E. and W. center line of the NE 1/4, sec. 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R5W NE 1/16 S26 1979</p> <p>Set an angle iron, 4 ft. long alongside the iron post.</p> <p>Cor. is located 192 lks. W. of a gravel road, bears S. 25° E. curving southerly and N. 25° W.</p> <p>From this point the SE cor. of a house 25 x 35 ft., bears N. 40° E., 56 lks. dist., long side, bears west.</p> <p>From this same point the SE cor. of a stone wall around the house, bears N. 79° E., 117 lks. dist.</p> <p>39.97 The E 1/16 sec. cor. of secs. 23 and 26.</p> <hr style="width: 20%; margin: auto;"/> <p>From the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>S. 89°45' W., on the E. and W. center line of the NE 1/4, sec. 26.</p> <p>Over rolling land, through medium undergrowth.</p>



Subdivision of Sec. 26, T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS		
20.01	The NE 1/16 sec. cor. of sec. 26.	
39.99	The point for the C-N 1/16 sec. cor. of sec. 26.	
<hr/> SE 1/4, Section 26 <hr/>		
From the point for the E 1/16 sec. cor. of secs. 26 and 35.		
N. 0°03' E., on the N. and S. center line of the SE 1/4, sec. 26.		
Over rolling land, through medium undergrowth.		
20.12	Point for the SE 1/16 sec. cor., at intersection with the E. and W. center line of the SE 1/4, sec. 26.	
Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.		
T8N R5W SE 1/16 S26 1979		
Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of the cor.		
Cor. is located 3.50 chs. E. of the left bank of the Hassayampa River, course S.		
From this point a ¾ in. reinforcement rod, projecting 6 ins. above the ground, at a fence cor., bears N. 32½° E., 11 lks. dist.; fences extend N. and W.		
40.24	The C-E 1/16 sec. cor. of sec. 26.	
<hr/> From the S 1/16 sec. cor. of secs. 25 and 26.		
S. 89°52' W., on the E. and W. center line of the SE 1/4, sec. 26.		
Over rolling land, through medium undergrowth.		
20.025	The SE 1/16 sec. cor. of sec. 26.	
40.05	The point for the C-S 1/16 sec. cor. of sec. 26.	
<hr/> Dependent Resurvey of Certain Boundaries of Mineral Surveys in T. 8 N., R. 5 W., Gila and Salt River Meridian, Arizona <hr/>		
Mineral Survey No. 1587A Niggerben Lode <hr/>		
From Cor. No. 4, Mineral Survey No. 1587A, Niggerben Lode, reported in the official record as being on line 3-4, Mineral Survey No. 1587A, Copperhead Lode, monumented with a granite stone, 12 x 12 x 6 ins. loosely set in a mound of stone, 2 ft. base, 6 ins. high, mkd. N4 1587A on top.		

Dependent Resurvey of Certain Boundaries of
Mineral Surveys in T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set a 5/8 in. reinforcement rod, 4 ft. long, 24 ins. in the ground, in a mound of stone, 3 ft. base, 1½ ft. high, with aluminum cap attached and mkd.</p> <div style="text-align: center;">  <p>Cor. 4 MS 1587A Nig. S24 1979</p> </div> <p>Bury the mkd. stone in the mound of stone.</p> <p>Cor. is located 25 lks. N. of a power line, bears S. 65° E. and N. 65° W.</p> <p>N. 15°26' E., on line 3-4, Mineral Survey No. 1587A, Niggerben Lode, in sec. 24.</p>
1.97	Intersect the line bet. secs. 13 and 24, at a point from which the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., bears S. 89°56' E., 19.08 chs. dist., described in the field notes for T. 8 N., R. 4 W. executed concurrently. Thence in sec. 13.
20.99	Intersect line 4-1, Mineral Survey No. 1587A, Montana Lode, at a point from which Cor. No. 4 bears N. 54°47' W., 3.17 chs. dist., hereinafter described.
22.07	Cor. No. 3, Mineral Survey No. 1587A, Niggerben Lode, monumented with a mound of stone, 2 ft. base, 1 ft. high, no mkd. stone visible, not remonumented.
<p>Mineral Survey No. 1587A Montana Lode</p>	
	<p>From Cor. No. 1, Mineral Survey No. 1587A, Montana Lode, monumented with a granite stone, 8 x 6 ins., projecting 12 ins. above the ground, in a mound of stone, 2 ft. base, 1½ ft. high, mkd. 3M 1587A, not remonumented.</p> <p>N. 54°47' W., on line 4-1, Mineral Survey No. 1587A, Montana Lode.</p>
8.85	Intersect line 3-4, Mineral Survey No. 1587A, Niggerben Lode, at a point from which Cor. No. 3 bears N. 15°26' E., 1.08 chs. dist., heretofore described.
12.02	Cor. No. 4, Mineral Survey No. 1587A, Montana Lode, reported in the official record as being on line 1-2, Mineral Survey No. 1587A, Dutchman Lode, monumented with a granite stone, 12 x 6 ins., projecting 12 ins. above the ground, mkd. 4M 1587A on the E. face, with a mound of stone, 2½ ft. base, 1 ft. high, W. of the cor., not remonumented.
<p>Mineral Survey No. 1587A Dutchman Lode</p>	
	<p>From Cor. No. 4, Mineral Survey No. 1587A, Montana Lode, heretofore described.</p>

Dependent Resurvey of Certain Boundaries of
 Mineral Surveys in T. 8 N., R. 5 W.,
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>S. 37°30' W., on line 1-2, Mineral Survey No. 1587A, Dutchman Lode.</p>	
4.34	<p>Cor. No. 1, Mineral Survey No. 1587A, Dutchman Lode, monumented with a granite stone, 10 x 6 ins., projecting 12 ins. above the ground, mkd. 2D 1587A on the N. face, with a mound of stone, 2½ ft. base, 1 ft. high, S. of the cor., not remonumented.</p>	
	<p>Thence</p>	
	<p>N. 55°50' W., on line 4-1, Mineral Survey No. 1587A, Dutchman Lode.</p>	
8.25	<p>Cor. No. 4, Mineral Survey No. 1587A, Dutchman Lode, monumented with a granite stone, 18 x 14 x 12 ins., set 8 ins. in the ground, no marks visible, with a mound of stone, 2½ ft. base, 1½ ft. high, S. of the cor.</p>	
	<p>At the cor. point</p>	
	<p>Set a 5/8 in. reinforcement rod, 4 ft. long, 30 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with aluminum cap attached and mkd.</p>	
		
	<p>Deposit the granite stone in the mound of stone.</p>	
	<p>Cor. is located 75 lks. W. of a track road, bears S. 40° E. and N. 40° W.</p>	
	<p>Thence</p>	
	<p>N. 33°34' E., on line 3-4, Mineral Survey No. 1587A, Dutchman Lode.</p>	
22.47	<p>Cor. No. 3, Mineral Survey No. 1587A, Dutchman Lode, monumented with a slate stone, 12 x 6 ins., projecting 12 ins. above the ground, mkd. 4D 1587A on the S. face, with a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor., not remonumented.</p>	
	<p>Thence</p>	
	<p>S. 55°30' E., on line 2-3 Mineral Survey No. 1587A, Dutchman Lode.</p>	
9.06	<p>Point for Cor. No. 2, Mineral Survey No. 1587A, Dutchman Lode, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set a brass tablet, 3 1/4 ins. diam., 3½ in. stem, in a drill hole, in a conglomerate boulder, 4 x 4 x 2 ft. above the ground, mkd.</p>	
		

Dependent Resurvey of Certain Boundaries of
Mineral Surveys in T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located at the N. edge of a wash, 50 lks. wide, drains westerly.</p> <p>Thence</p> <p>S. 35°10' W., on line 1-2, Mineral Survey No. 1587A, Dutchman Lode.</p>
9.01	<p>Cor. No. 3, Mineral Survey No. 1587A, Montana Lode, reported in the official record as being on line 1-2 of Mineral Survey No. 1587A, Dutchman Lode, monumented with a granite stone, 10 x 8 ins., projecting 12 ins. above the ground, mkd. 1M 1587A on the E. face, with a mound of stone, 1½ ft. base, 1 ft. high, W. of the cor., not re-monumented.</p>
	<p style="text-align: center;">Mineral Survey No. 1587A Montana Lode</p>
12.00	<p>From Cor. No. 3, Mineral Survey No. 1587A, Montana Lode, heretofore described.</p> <p>S. 54°43' E., on line 2-3, Mineral Survey No. 1587A, Montana Lode.</p> <p>Cor. No. 2, Mineral Survey No. 1587A, Montana Lode, reported in the official record as being on line 4-5, Mineral Survey No. 1587A, Frenchman Lode, monumented with a granite stone, 18 x 10 ins., projecting 12 ins. above the ground, mkd. M2 1587A on the S. face, with a mound of stone, 3 ft. base, 1½ ft. high, N. of the cor., not re-monumented.</p>
	<p style="text-align: center;">Mineral Survey No. 1587A Frenchman Lode</p>
1.50	<p>From Cor. No. 2, Mineral Survey No. 1587A, Montana Lode, heretofore described.</p> <p>N. 37°00' E., on line 4-5 Mineral Survey No. 1587A, Frenchman Lode.</p>
	<p>Cor. No. 4, Mineral Survey No. 1587A, Frenchman Lode, monumented with a granite stone, 10 x 3 ins., projecting 12 ins. above the ground, mkd. F 1587A on the S. face, with a mound of stone, 4 ft. base, 2½ ft. high, N. of the cor., not re-monumented.</p> <p>Thence</p> <p>S. 55°58' E., on line 3-4, Mineral Survey No. 1587A, Frenchman Lode.</p>
0.865	<p>Intersect the line, bet. secs. 13 and 18, T. 8 N., Rs. 4 and 5 W., at a point from which the ¼ sec. cor. of secs. 13 and 18, bears N. 0°08' E., 18.48 chs. dist., described in the field notes for T. 8 N., R. 4 W., executed concurrently. Thence in sec. 18.</p>

Dependent Resurvey of Certain Boundaries of
Mineral Surveys in T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
9.13	<p>Cor. No. 3, Mineral Survey No. 1587A, Frenchman Lode, monumented with a granite stone, 16 x 6 ins., projecting 15 ins. above the ground, mkd. 3F 1587A on the S. face, with a mound of stone, 3 ft. base, 1½ ft. high, N. of the cor., not remonumented.</p> <p>Thence</p> <p>S. 37°43' W., on line 2-3, Mineral Survey No. 1587A, Frenchman Lode.</p>
4.43	<p>Cor. No. 4, Mineral Survey No. 1587A, May Lode, reported in the official record as being on line 2-3, Mineral Survey No. 1587A, Frenchman Lode, monumented with a mound of stone, 2½ ft. base, 2 ft. high, no marked stone found.</p> <p>At the cor. point</p> <p>Set a 5/8 in. reinforcement rod, 4 ft. long, 36 ins. in the ground, in the rebuilt mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p> <div data-bbox="747 1075 950 1276" style="text-align: center;"> </div> <hr/> <p style="text-align: center;">Mineral Survey No. 1587A May Lode</p>
	<p style="text-align: center;">Mineral Survey No. 1587A May Lode</p>
	<p>From Cor. No. 4, Mineral Survey No. 1587A, May Lode, heretofore described.</p> <p>S. 58°23' E., on line 3-4, Mineral Survey No. 1587A, May Lode.</p>
8.67	<p>Point for Cor. No. 3, Mineral Survey No. 1587A, May Lode, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a 5/8 in. reinforcement rod, 4 ft. long, 28 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p> <div data-bbox="771 1881 982 2083" style="text-align: center;"> </div>
	<p>Thence</p> <p>S. 34°41' W., on line 2-3, Mineral Survey No. 1587A, May Lode.</p>
6.94	<p>Cor. No. 2, Mineral Survey No. 1587A, May Lode, monumented with a granite stone, 12 x 6 ins., projecting 6 ins. above the ground, mkd. M2 1587A on the SW. face, with a mound of stone, 2½ ft. base, 1 ft. high, E. of the cor., not remonumented.</p>

Dependent Resurvey of Certain Boundaries of
Mineral Surveys in T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

51

CHAINS	
	<p>Thence</p> <p>S. 44°46' W., on line 1-2, Mineral Survey No. 1587A, May Lode.</p>
4.23	<p>Intersect the line bet. secs. 18 and 19, T. 8 N., R. 4 W., at a point from which the cor. of secs. 13, 18, 19 and 24, bears N. 89°52' W., 4.64 chs. dist., described in the field notes for T. 8 N., R. 4 W., executed concurrently. Thence in sec. 19.</p>
9.96	<p>Cor. No. 1, Mineral Survey No. 1587A, May Lode, identical with Cor. No. 1, Mineral Survey No. 1587A, Alma Lode, monumented with a granite stone, 12 x 6 ins., projecting 10 ins. above the ground, mkd. M1 on the N. face and Al 1587A on the S. face, with a mound of stone, 2 ft. base, 1 ft. high, E. of the cor., not remonumented.</p>
<p>Mineral Survey No. 1587A Alma Lode</p>	
	<p>From Cor. No. 1, Mineral Survey No. 1587A, Alma Lode, identical with Cor. No. 1, Mineral Survey No. 1587A, May Lode, heretofore described.</p> <p>S. 34°03' W., on line 1-2, Mineral Survey No. 1587A, Alma Lode.</p>
1.095	<p>Intersect the line bet. secs. 19 and 24, Tps. 8 N., Rs. 4 and 5 W., at a point from which the cor. of secs. 13, 18, 19 and 24, bears N. 0°04' E., 4.99 chs. dist., described in the field notes for T. 8 N., R. 4 W., executed concurrently. Thence in sec. 24.</p>
22.46	<p>Cor. No. 2, Mineral Survey No. 1587A, Alma Lode, monumented with a granite stone, 8 x 6 ins., projecting 12 ins. above the ground, mkd. 2A 1587A on the N. face, with a mound of stone, 2 ft. base, 2 ft. high, S. of the cor., not remonumented.</p> <p>Thence</p> <p>N. 55°48' W., on line 2-3, Mineral Survey No. 1587A, Alma Lode.</p>
9.04	<p>Cor. No. 3, Mineral Survey No. 1587A, Alma Lode, identical with Cor. No. 2, Mineral Survey No. 1587A, Copperhead Lode, monumented with a 3/8 in. reinforcement rod, 12 ins. long, projecting 8 ins. above the ground. This point was reestablished by D.S. O'Leary a local surveyor and accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>At the cor. point</p> <p>Set a 5/8 in. reinforcement rod, 4 ft. long, 30 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p>
	<p>Cor. 2 MS 1587A Ch. Cor. 3 MS 1587A Alma</p> <p>S24 1979</p>

Dependent Resurvey of Certain Boundaries of
Mineral Surveys in T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Bury the local cor. in the mound of stone.</p> <p>Cor. is located 87 lks. W. of a track road, bears irregularly N. and S.</p>
	<p>Mineral Survey No. 1587A Copperhead Lode</p>
	<p>From Cor. No. 2, Mineral Survey No. 1587A, Copperhead Lode, identical with Cor. No. 3, Mineral Survey No. 1587A, Alma Lode.</p> <p>N. 55°46' W., on line 2-3, Mineral Survey No. 1587A, Copperhead Lode.</p>
9.08	<p>Cor. No. 3, Mineral Survey No. 1587A, Copperhead Lode, monumented with a granite stone, 8 x 8 ins., projecting 5 ins. above the ground, mkd. 4 1587A on the N. face, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., not remonumented.</p> <p>Thence</p> <p>N. 34°39' E., on line 3-4, Mineral Survey No. 1587A, Copperhead Lode.</p>
6.15	<p>Intersect line 1-2, Mineral Survey No. 1587A, Oro Grande Lode, at a point from which Cor. No. 1 bears N. 56°04' E., 5.875 chs. dist., hereinafter described.</p>
12.35	<p>Intersect line 4-1, Mineral Survey No. 1587A, Oro Grande Lode, at a point from which Cor. No. 1 bears S. 36°16' E., 2.27 chs. dist., hereinafter described.</p>
12.90	<p>Cor. No. 4, Mineral Survey No. 1587A, Niggerben Lode, heretofore described.</p>
	<p>Mineral Survey No. 1587A Oro Grande Lode</p>
	<p>From Cor. No. 1, Mineral Survey No. 1587A, Oro Grande Lode, determined at proportionate dist.</p> <p>Set a 5/8 in. reinforcement rod, 4 ft. long, 3 ft. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.</p> <div style="text-align: center;"> <p>Cor. 1 MS 1587A O. Grande S24 1979</p> </div> <p>S. 56°04' W., on line 1-2, Mineral Survey No. 1587A, Oro Grande Lode.</p>
5.875	<p>Intersect line 3-4, Mineral Survey No. 1587A, Copperhead Lode, at a point from which Cor. No. 3 bears S. 34°39' W., 6.15 chs. dist., heretofore described.</p>

Dependent Resurvey of Certain Boundaries of
Mineral Surveys in T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
22.62	<p>Cor. No. 2, Mineral Survey No. 1587A, Oro Grande Lode, monumented with a granite stone, 12 x 6 ins., projecting 8 ins. above the ground, mkd. G2 1587A, with a mound of stone, 2 ft. base, 1 ft. high, S. of the cor., not re-monumented.</p> <p>Thence</p> <p>N. 35°56' W., on line 2-3, Mineral Survey No. 1587A, Oro Grande Lode.</p>
9.10	<p>Cor. No. 3, Mineral Survey No. 1587A, Oro Grande Lode, monumented with a granite stone, 16 x 6 ins., projecting 24 ins. above the ground, mkd. 3 1587A, with a mound of stone, 2 ft. base, 2 ft. high, alongside the cor., not remonumented.</p> <p>Thence</p> <p>N. 56°06' E., on line 3-4, Mineral Survey No. 1587A, Oro Grande Lode.</p>
4.26	<p>Intersect line 2-3, Mineral Survey No. 1587A, Colossal Lode, at a point from which Cor. No. 3 bears N. 50°27' W., 4.175 chs. dist., hereinafter described.</p>
22.57	<p>Cor. No. 4, Mineral Survey No. 1587A, Oro Grande Lode, hereinafter described.</p>
<p>Mineral Survey No. 1587A Colossal Lode</p>	
<p>From Cor. No. 2, Mineral Survey No. 1587A, Colossal Lode, monumented with a granite stone, 22 x 12 x 12 ins., set 12 ins. in the ground, mkd. C1 1587A on the W. face, with a mound of stone, 3 ft. base, 2½ ft. high, E. of the cor.</p>	
<p>At the cor. point</p>	
<p>Set a 5/8 in. reinforcement rod, 2 ft. long, 12 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with aluminum cap attached and mkd.</p>	
<p>Deposit the mkd. stone in the mound of stone.</p>	
<p>N. 50°27' W. on line 2-3, Mineral Survey No. 1587A, Colossal Lode.</p>	
4.385	<p>Intersect line 3-4, Mineral Survey No. 1587A, Oro Grande Lode, at a point from which Cor. No. 3 bears S. 56°06' W., 4.26 chs. dist., heretofore described.</p>
8.56	<p>Cor. No. 3, Mineral Survey No. 1587A, Colossal Lode, monumented with a granite stone, 10 x 6 ins., projecting 10 ins. above the ground, mkd. C4 1587A on top, with a mound of stone, 3 ft. base, 2 ft. high, W. of the cor., not re-monumented.</p>

Dependent Resurvey of Certain Boundaries of
 Mineral Surveys in T. 8 N., R. 5 W.,
 Gila and Salt River Meridian, Arizona

CHAINS

Thence


N. 40°36' E., on line 3-4, Mineral Survey No. 1587A, Colossal Lode.

5.84 Intersect the line bet. secs. 13 and 24, at a point from which the 1/4 sec. cor. of secs. 13 and 24, bears N. 89°56' W., 1.37 chs. dist., heretofore described. Thence in sec. 13.

23.03 Cor. No. 4, Mineral Survey No. 1587A, Colossal Lode, monumented with a granite stone, 24 x 12 x 10 ins., set 10 ins. in the ground, no marks visible, with a mound of stone, 2½ ft. base, 2½ ft. high, NW. of the cor.

At the cor. point

Set a 5/8 in. reinforcement rod, 4 ft. long, 36 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.



Deposit the granite stone in the mound of stone.

Thence

S. 48°27' E., on line 4-1, Mineral Survey No. 1587A, Colossal Lode.

9.16 Cor. No. 1, Mineral Survey No. 1587A, Colossal Lode, monumented with a granite stone, 6 x 3 ins., projecting 12 ins. above the ground, mkd. C2 1587A on the S. face, with a mound of stone, 2 ft. base, 1 ft. high, NE. of the cor., not remonumented.


Thence

S. 41°41' W., on line 1-2, Mineral Survey No. 1587A, Colossal Lode.

5.16 Cor. No. 4, Mineral Survey No. 1587A, Oro Grande Lode, reported in the official record as being on line 1-2, Mineral Survey No. 1587A, Colossal Lode, monumented with a granite stone, 18 x 8 x 8 ins., set 12 ins. in the ground, mkd. O4 1587A on the S. face, with a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.

At the cor. point

Set a 5/8 in. reinforcement rod, 4 ft. long, 18 ins. in the ground, in a mound of stone, 3 ft. base, to top, with aluminum cap attached and mkd.



Dependent Resurvey of Certain Boundaries of
Mineral Surveys in T. 8 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Deposit the mkd. stone in the mound of stone.</p> <hr/> <p style="text-align: center;">Mineral Survey No. 1587A Oro Grande Lode</p> <hr/> <p>From Cor. No. 4, Mineral Survey No. 1587A, Oro Grande Lode, heretofore described.</p> <p>S. 36°16' E., on line 4-1, Mineral Survey No. 1587A, Oro Grande Lode.</p>
3.89	Intersect the line bet. secs. 13 and 24, at a point from which the 1/4 sec. cor. of secs. 13 and 24, bears N. 89°56' W., 18.29 chs. dist., heretofore described.
6.81	Intersect line 3-4, Mineral Survey No. 1587A, Copperhead Lode, at a point from which Cor. No. 4, Mineral Survey No. 1587A, Niggerben Lode on this line, bears N. 34°39' E., 55 lks. dist., heretofore described.
9.08	Cor. No. 1, Mineral Survey No. 1587A, Oro Grande Lode, heretofore described.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>Section 25 of this survey is located approximately 2 miles north of Wickenburg, Arizona. The general elevation ranges from 2100 to 3200 ft. above sea level.</p> <p>The Hassayampa River flows through the SE portion of the township in a southerly direction.</p> <p>Access is by way of a number of unimproved and graded gravel roads.</p> <p>The vegetation consists of creosote, palo verde, mesquite and cacti.</p> <p>There is no evidence of any mining activity at the present time.</p>

CHAINS		

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY
 supplemental 16th
 CERTIFY upon honor that, in pursuance of/special instructions bearing date of the 3rd day
 April 1979
 of January, 19 79, (I) ~~(We)~~ have dependently resurveyed a portion of
 the Second Standard Parallel North, through Ranges 5 and 6 West, a por-
 tion of the west boundary, a portion of the subdivisional lines, certain
 boundaries of mineral surveys and the survey of subdivisions in secs. 14,
 23 and 26, Township 8 North, Range 5 West

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

June 30, 1980

 (Date) *Paul L. Reeves*

 (Cadastral Surveyor)

 (Date) _____
 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the Second
 Standard Parallel North, through Ranges 5 and 6 West, a portion of the
 west boundary, a portion of the subdivisional lines, certain boundaries
 of mineral surveys and the survey of subdivisions in secs. 14, 23 and
 26, Township 8 North, Range 5 West,

executed by Paul L. Reeves, Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.

MAY 04 1981

 (Date) *J. VanRhee*

 (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in~~
~~_____ is a true copy of the original field notes.~~

 (Date) _____
 (Chief, Cadastral Survey Examination and Approval Staff)