

INDEX DIAGRAM

Township 10 NORTH, Range 25 EAST,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	10 33 2	9 7 34	6 35	36

T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

The following field notes describe the corrective dependent resurvey of a portion of the south boundary and a portion of the subdivisional lines, Township 10 North, Range 25 East of the Gila and Salt River Meridian, Arizona.

The south boundary and the subdivisional lines were originally surveyed by A. P. Johnson, in 1882. An unrecorded survey of portions of the south boundary and subdivisional lines surrounding section 33 was performed by Michael Paige Wier, Arizona Registered Land Surveyor No. LS 7247 in July 1970. A dependent resurvey of a portion of the south boundary (north boundary, T. 9 N., R. 25 E.) and a portion of the subdivisional lines were executed by Gilbert V. Olson in 1973. Olson's field notes and plats were approved and accepted June 5, 1975. In 1979, Ronald S. Stoll, Arizona Registered Land Surveyor No. L.S. 11758, of Lowry & Associates, under contract with the U.S. Forest Service, retraced portions of the south boundary and subdivisional lines and executed a survey of the subdivision of section 33. The Stoll survey is recorded in the Apache County Courthouse, St. Johns, Arizona.

The Director, Denver Service Center, was informed by Roy T. Helmandollar of Page Land & Cattle Co., by letter dated November 8, 1976, that there were discrepancies in the descriptions of the physical character of the locations for the 1/4 sec. cor. of secs. 28 and 33, and that no survey monuments could be located. An investigation disclosed evidence that these two 1/4 section corners were erroneously reported in the 1975 record and they in fact could not be located. In 1976 Olson established new monumentation at these locations. Because of further questions concerning the 1973 resurvey, the 1973 dependent resurvey of the subdivisional lines was suspended February 9, 1977, and on March 3, 1977, supplemental special instructions were approved for a corrective dependent resurvey of the lines in question. In 1979 the Forest Service contract survey reported discrepancies in the measurements of several of the lines.

This corrective resurvey and survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated May 3, 1973, the Supplemental Special Instructions dated June 14, 1973, the Supplemental Special Instructions dated March 3, 1977, and the Supplemental Special Instructions dated July 15, 1980, for Group 558, Arizona.

The directions of the lines were determined by direct solar, stellar and Polaris observations. They refer to the true meridian. The lines were carried by conventional traverse methods and the bearings verified by additional observations at various points throughout this survey. The horizontal and vertical angles were determined by using the mean value of repetitive angles measured with a Wild T-16 theodolite. The distances were determined with a Hewlett-Packard 3805 E.D.M. and a steel tape, and reduced to the horizontal equivalents throughout this survey.

T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

Preliminary to the corrective resurvey, the lines of the official surveys were retraced and diligent search was made for all corners and other calls of the record. Certain positions could be accepted as perpetuations of the original corner locations, or acceptable determinations by local surveys. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 2, 3, 34, and 35, as scaled from U. S. Geological Survey quadrangle map "BOUNDARY BUTTE, ARIZ.," 1968, 7 1/2 minute series, is:

Latitude 34° 12.8' N., Longitude 109° 40.5' W.

The observed mean magnetic declination is 12 1/2° E.

Corrective Dependent Resurvey of a Portion of the
South Boundary
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

Restoring the survey executed by A. P. Johnson
in 1882, and correcting the resurvey by
Gilbert V. Olson in 1973

From the cor. of secs. 3, 4, 33, and 34, Tps. 9 and 10 N., R. 25 E., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground in a mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

T10N R25E
S 33 | S 34
S 4 | S 3
T9N

1973

From this point, an iron post, 2 1/2 ins. diam., bears N. 85° 35.5' E., 5.243 chs. dist., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T10N R25E
AM

1973

A large mound of stone, 4 ft. base, 2 1/2 ft. high, N. of post.

Add the marks 1980 to both caps.

Cor. falls approximately 80 lks. N. of center of power line extending E. and W.

S. 88° 52' W., bet. secs. 4 and 33.

Corrective Dependent Resurvey of a Portion of the
South Boundary
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Over nearly level open land, along N. edge of power line cut through scattered pine and juniper timber.</p> <p>19.91 The E 1/16 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, in a small mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T10N R25E E 1/16 $\frac{S\ 33}{S\ 4}$ T9N 1973</p> <p>from which the 1973 bearing trees</p> <p>A pine, 6 ins. diam., bears S. 40 1/2° E., 41 1/2 lks. dist., with overgrown blaze. (Record, S. 39 3/4° E., 42 lks.)</p> <p>A pine, 12 ins. diam., bears N. 6 1/4° W., 51 1/2 lks. dist., with partially overgrown blaze and visible scribe marks 1/16 S33 B. (Record, N. 7° W., 51 lks.)</p> <p>from which</p> <p>A steel fence post of unknown origin, bears N. 55 1/2° E., 9.6 lks. dist., projecting 22 ins. above ground, with flat metal plate 3 ins. square welded on top, in a small mound of stone.</p> <p>This cor. was accepted in the 1979 survey by Stoll, Arizona R.L.S. No. 11758, recorded in the Apache County Courthouse, St. Johns, Arizona.</p> <p>Add the marks 1980 to the cap.</p> <p>Cor. falls 45 lks. N. of fence extending E. and W.</p> <p style="text-align: center;">_____</p> <p>S. 89° 04' W., beginning new measurement.</p> <p>Along nearly level land, through scattered pinon and juniper timber, N. of fence line extending E. and W.</p>	
19.89	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 15 ins. above ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T10N R25E 1/4 $\frac{S\ 33}{S\ 4}$ T9N 1973</p> <p>from which the original bearing tree</p> <p>An oak, 28 ins. diam., bears S. 86 3/4° E., 14 1/2 lks. dist., with overgrown blaze on N. side. (Record, N. 70° E., 15 lks.) (1973 Record, EAST 15 lks.)</p>	

6

Corrective Dependent Resurvey of a Portion of the
South Boundary
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which the 1973 bearing trees</p> <p>A pine, 16 ins. diam., bears S. 11 1/4° E., 31 lks. dist., mkd. 1/4 S4 BT visible on partially overgrown blaze. (Record: S. 13 3/4° E.)</p> <p>A pine, 14 ins. diam., bears S. 58 1/2° W., 31 lks. dist., mkd. 1/4 S4 BT visible on partially overgrown blaze. (Record: S. 54 3/4° W.)</p> <p>Add the marks 1980 to the cap.</p> <p>Cor. falls 64 lks. N. of fence extending E. and W.</p> <hr/> <p>N. 88° 37' W., beginning new measurement.</p> <p>Over neary level land, through pinon, oak, and juniper timber, N. of fence line bearing E. and W.</p>
10.18	<p>Fall 1.8 lks. N. of steel fence post of unknown origin, firmly set, projecting 20 ins. above ground, with flat metal plate 3 ins. square welded on top. Post falls 1 lk. N. of fence line extending E. and W.</p>
20.08	<p>The W 1/16 sec. cor. of secs. 4 and 33, established by Ronald S. Stoll, Arizona R.L.S. No. 11758, recorded in the Apache County Courthouse, St. Johns, Arizona, and is accepted as a careful and faithful establishment of the cor. position, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a small mound of stone, 2 1/2 ft. base to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">U.S. DEPARTMENT OF AGRICULTURE UNLAWFUL TO DISTURB T10N R25E W 1/16 $\frac{S\ 33}{S\ 4}$ T9N 1979 LS11758 CADASTRAL SURVEY FOREST SERVICE</p>
	<p>from which</p> <p>A steel fence post, bears S. 39° 02' W., 14.6 lks. dist., firmly set, projecting 10 ins. above ground, with flat metal 3 ins. square welded on top. Falls in fence line extending E. and W.</p> <hr/> <p>N. 88° 37' W., beginning new measurement.</p>
10.04	<p>The point for the W-W 1/64 sec. cor. of secs. 4 and 33, established by Ronald S. Stoll, Arizona R.L.S. No. 11758, recorded in the Apache County Courthouse, St. Johns, Arizona, and is accepted as a careful and faithful establishment of the cor. position, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 20 ins. above ground, in a supporting mound of stone, 3 ft. base to top, with aluminum cap mkd.</p>

Corrective Dependent Resurvey of a Portion of the
South Boundary
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

U.S. DEPARTMENT OF AGRICULTURE
UNLAWFUL TO DISTURB

T10N R25E

W-W

1/64

S 33

S 4

T9N

1979

LS11758

CADASTRAL SURVEY
FOREST SERVICE

from which the 1979 bearing trees mkd. by Stoll

A pine, 8 ins. diam., bears S. 43° E., 60 1/2 lks. dist., freshly mkd. X BT on open blaze.

An oak, 15 ins. diam., bears N. 8° W., 61 1/2 lks. dist., freshly mkd. X BT on open blaze.

from which

A steel fence post of unknown origin, bears S. 31° W., 23.4 lks. dist., firmly set, projecting 36 ins. above ground, with flat metal plate 3 ins. square welded on top in a small mound of stone.

Cor. falls 11 lks. S. of fence line extending E. and W.

N. 88° 37' W., beginning new measurement.

3.94 From this point, an extensive search of the area for a mound of stone and rotted wooden post, as described in the official field note record of T. 9 N., R. 25 E., Gila and Salt River Meridian, revealed that all evidence has been obliterated since its report during the 1973 survey by Olson.

4.47 Prominent wash, drains N., ascend E. slope, through oak and pine timber.

10.04 The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 12 ins. above ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T10N R25E

S 32 | S 33

S 5 | S 4

T9N

1973

from which bearing trees of unknown origin

A pine, 40 ins. diam., down and dead and whose root hole, bears S. 17 1/4° W., 78 lks. dist., with knife marks T9N R25E S5 BT visible on shallow blaze.

A dead oak snag, 28 ins. diam., bears N. 55 1/2° W., 117 lks. dist., with illegible fragmentary scribe marks on partially overgrown blaze.

8

Corrective Dependent Resurvey of a Portion of the
South Boundary
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

from which the 1973 bearing trees

A pine, 6 ins. diam., bears N. 23° E., 29 1/2 lks. dist., with overgrown blaze. (Record, N. 24 3/4° E., 29 lks.)

A pine, 4 ins. diam., bears S. 11 3/4° E., 17 lks. dist., with overgrown blaze.

A pine, 4 ins. diam., bears S. 6 1/4° W., 25 lks. dist., with overgrown blaze.

A pine, 5 ins. diam., bears N. 31° W., 24 1/2 lks. dist., with overgrown blaze. (Record, N. 28 1/2° W., 24 lks.)

from which

The cor. of fences extending N. and E., bears N. 55° W., 5 lks. dist. (1973 Record, N. 45° W.)

Add the marks 1980 to the cap.

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

Restoring the survey executed by A. P. Johnson
in 1882, and correcting the resurvey by
Gilbert V. Olson in 1973

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T10N R25E
S 34 | S 35
S 3 | S 2
T9N

1973

from which the 1973 bearing tree

A pine, 10 ins. diam, bears N. 19 1/2° W., 52 lks. dist., visibly mkd. 10N R25E S34 BT on partially overgrown blaze. (Record, N. 22 1/4° W.)

from which

An iron post, 2 1/2 ins. diam., bears S. 89° 32' E., 6.205 chs. dist. firmly set, projecting 10 ins. above ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

S 35

AM

1973

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

Add the marks 1980 to both caps.

Cor. falls in fence line extending N. and S., and approximately 80 lks. N. of power line extending E. and W.

N. 2° 34' W., bet. secs. 34 and 35.

Ascend S. slope through pine and oak timber, along fence line.

- 41.11 The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T10N R25E

1/4

S 34|S 35

1973

Add the marks 1980 to the cap.

Cor. falls in fence line extending N. and S. approximately 1 ch.

N. 3° 46' W., beginning new measurement.

Over open nearly flat grass land.

- 41.235 Fence line extends E. and W.

- 41.310 The cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with mkd. stone partially buried alongside and a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W. of the post, with brass cap mkd.

T10N R25E

S 27|S 26

S 34|S 35

1973

from which the 1973 bearing tree

A juniper, 6 ins. diam, bears N. 8 3/4° W., 27 lks. dist., with visible scribe marks X BT on open blaze.

Add the marks 1980 to the cap.

Cor. falls near top of N. slope, 7 1/2 lks. N. of fence line extending E. and W.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp., hereinbefore described.

N. 3° 08' W., bet. secs. 33 and 34.

Over nearly level land, through pine, juniper and oak timber.

10

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS 12.00	Enter open cleared land, along dim remains of old fence line.
40.52	<p>The 1/4 sec. cor. of secs. 33 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with lava boulder, 26 x 24 ins. alongside to W., with brass cap mkd.</p> <p style="text-align: center;">T10N R25E 1/4 S 33 S 34</p> <p style="text-align: center;">1976</p> <p>from which</p> <p style="padding-left: 40px;">The cor. of fences extending E. and NW, bears EAST, 19.8 lks. dist.</p> <p style="padding-left: 40px;">The cor. of fences extending N. and SE, bears N. 13 1/2° W., 25.7 lks. dist.</p> <p>Add the marks 1980 to the cap.</p> <p>There is no evidence of the original cor. or of the 1973 cor. monument.</p> <p>NOTE Subsequent to the approval of the 1973 dependent resurvey on June 5, 1975, the Director, Denver Service Center, was informed by Roy T. Helman-dollar of Page Land & Cattle Co., by letter dated November 8, 1976, that field examination revealed that the description of the location of this cor. monument did not correctly describe the physical character of the location nor could any monument be located. In 1976, Olson, during an investigation, established the existing monument and described it as determined in line with fences to the N. and E. (erroneously described as at a buried mound of stone, in the 1973 record). This point is harmoniously related to identified original cors. in the area and is accepted as the best available evidence of the original cor.</p> <p>Cor. falls 6.0 lks. E. of the projection of fence to the N. and in the projection of a fence to the E.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1° 56' W., beginning new measurement.</p> <p>Over slightly rolling land following approximately along open area near fence line.</p>
40.88	<p>The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the post, with brass cap mkd.</p> <p style="text-align: center;">T10N R25E S 28 S 27 S 33 S 34</p> <p style="text-align: center;">1973</p>

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

from which a 1973 bearing tree erroneously omitted from the official record

An oak, 6 ins. diam, bears N. $28\frac{3}{4}^{\circ}$ W., 22 lks. dist., with overgrown blaze. (mkd. X BT in 1973)

NOTE There is no evidence of the remains of an old foundation or the stones and cement described in the 1973 record as bearing S. $29^{\circ} 15'$ E., 7.88 chs. dist.

Add the marks 1980 to the cap.

Cor. falls in remains of old fence extending E. and W., and 1.10 chs. W. of cor. of fences extending E. and S.

From the cor. of secs. 26, 27, 34, and 35.

S. $89^{\circ} 13'$ W., bet. secs. 27 and 34.

Through pine, juniper and oak timber, along N. slope just N. of old fence line extending E. and W.

37.81

The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above ground, alongside N. side of fence post, 10 ins. diam., and a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, N. of the iron post, with brass cap mkd.

T10N R25E

$\frac{1}{4}$ $\frac{S\ 27}{S\ 34}$

1973

from which the 1973 bearing trees

An oak, 6 ins. diam, bears S. $47\frac{1}{2}^{\circ}$ E., 15 lks. dist., mkd. X BT on partially overgrown blaze.

A pine, 8 ins. diam, bears N. 33° W., 32 lks. dist., with overgrown blaze.

from which

A limestone, 20 x 8 x 6 ins., lying loosely in an old mound of stone, and mkd. FH4 near one end and other indistinguishable chisel marks, bears N. $83^{\circ} 35'$ W., 2.264 chs. dist., (described as mkd. FH $\frac{1}{4}$ and N. $82^{\circ} 34'$ W., 2.28 chs. dist., in 1973 record and in fence extending E. and W.). This monument falls approximately 25 lks. N. of old fence extending E. and W.

Add the marks 1980 to the cap.

Cor. is located N. alongside of old fence line extending E. and W., at a point where a meandering fence joins from the S., and approximately in line with the dim remains of an old fence line extending N. from a point approximately 10 chs. N. of the cor.

S. $88^{\circ} 33'$ W., beginning new measurement.

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS	
	Continue along fence line, through scattered pine, juniper and oak timber.
40.35	The cor. of secs. 27, 28, 33, and 34.
	<hr/> <p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>N. 89° 53' W., bet. secs. 28 and 33.</p> <p>Over open gently rolling land.</p>
40.34	The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, in a mound of stone, 2 1/2 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T10N R25E 1/4 $\frac{S\ 28}{S\ 33}$ 1976</p>
	from which
	<p style="padding-left: 40px;">A brace post of an abandoned fence line, bears N. 16° 37' E., 62.3 lks. dist.</p>
	<p style="padding-left: 40px;">A brace post of an abandoned fence line, bears N. 24° 00' E., 64.7 lks. dist.</p>
	Add the marks 1980 to the cap.
	There is no other evidence of the original cor. or of the 1973 cor. monument.
	<p>NOTE Subsequent to the approval of the 1973 dependent resurvey on June 5, 1975, the Director, Denver Service Center, was informed by Roy T. Helman-dollar of Page Land & Cattle Co., by letter dated November 8, 1976, that field examination revealed that the description of the location of this cor. monument did not correctly describe the physical character of the location nor could any monument be located. In 1976, Olson during an investigation established the existing monument and described it as being previously monumented with a steel rod, of unknown origin, 5/8 in. diam., firmly set, projecting 4 ins. above ground, in a collar of stone. This point is accepted as the best available evidence of the original cor. An unrecorded plat of survey executed by Michael Paige Wier, Arizona R.L.S. No. 7247, in July 1970, indicates that he accepted, for 1/4 sec. cor., a found iron pipe with tag mkd. PE 6123, at what appears to be this location.</p>
	<hr/> <p>N. 89° 55' W., beginning new measurement.</p>
	Over open level cleared land.
40.30	The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 14 ins. above ground, in a supporting mound of stone, 3 1/2 ft. base to top, with brass cap mkd.

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 10 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

T10N R25E
S 29 | S 28
S 32 | S 33

1973

from which the 1973 bearing trees

A pine, 14 ins. diam., bears S. 36 1/4° E., 158
lks. dist., with overgrown blaze.

A pine, 10 ins. diam., bears S. 21 1/4° W., 56
lks. dist., with overgrown blaze.

A pine, 14 ins. diam., bears N. 58 1/2° W., 153
lks. dist., with overgrown blaze.

from which

A wooden post, 8 ins. diam., bears S. 26° E., 63
lks. dist., in the remains of old fence line
extending E. and W.

A pine stump, 36 ins. diam., bears S. 77° W., 25
1/2 lks. dist.

Add the marks 1980 to the cap.

Cor. falls approximately 80 lks. S. of dirt road bear-
ing E. and W.

GENERAL DESCRIPTION

The land encompassed in this corrective survey is located about 3 miles south of the small town of Vernon, Arizona, which is approximately 27 miles west of Springerville, Arizona, along U. S. Highway No. 60, and is on nearly flat foothills draining to the north through several shallow drainages. The terrain is covered by grasses and scattered to thick stands of pine, juniper and oak timber. Frequent and numerous outcrops of malpais lava rock are found throughout the area. Several of the drainages are cut 8 to 15 feet into the lava bedrock.

Access is by way of country road from Vernon and U.S. Highway No. 60, as well as numerous ranch roads and Forest Service access roads. The main county road from Vernon, called the Vernon-McNary Road runs south through the center of section 33, W. of the north and south center line.

The predominant use is cattle ranching for several ranches in the area.

CHAINS	
--------	--

CERTIFICATE OF SURVEY

(I) ~~XXX~~ Jerry L. Wahl, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day
 of May, 1973, ~~XXXXXXXXXX~~ and Supplemental Special Instructions
 dated June 14, 1973, March 3, 1977 and July 15, 1980, (I) have corrected
 the dependent resurvey of a portion of the south boundary and a portion
 of the subdivisional lines, Township 10 North, Range 25 East;

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~XXX~~ and under (my)
~~XXXX~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

May 6, 1981
 (Date)

Jerry L. Wahl
 Supervisory (Cadastral Surveyor)

 (Date)

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Denver, Colorado

The foregoing field notes of the corrective dependent resurvey of a portion of the
 south boundary and a portion of the subdivisional lines, Township 10 North,
 Range 25 East, of the Gila and Salt River Meridian, Arizona

executed by Jerry L. Wahl, Supervisory Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.

JUN 30 1981
 (Date)

Mary S. Speight
 ACTING (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

 (Date)

 (Chief, Cadastral Survey Examination and Approval Staff)