

~~BOOK 5 160~~

BOOK 5 16Z

FIELD NOTES

OF THE

SUBDIVISION OF SECTIONS 26 AND 29

TOWNSHIP 9 NORTH, RANGE 5 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

PAUL L. REEVES

CADASTRAL SURVEYOR

Under special instructions dated JANUARY 3, 19 79, approved JANUARY 4, 1979,
AND SECOND SUPPLEMENTAL SPECIAL INSTRUCTIONS, DATED DECEMBER 10, 1979 AND

APPROVED DECEMBER 11, 1979, which provided for the surveys included under ~~U.S. Survey~~/Group
Number 611, and assignment instructions dated JANUARY 3,, 19 79.

Survey commenced DECEMBER 13, 19 79

Survey completed DECEMBER 19, 19 79

INDEX DIAGRAM

Township 9 NORTH, Range 5 WEST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29 2	28	27	26 1	25
31	32	33	34	35	36

T. 9 N., R. 5 W., Gila and Salt River Mer., Arizona

CHAINS

The following field notes are those of the subdivision of sections 26 and 29, Township 9 North, Range 5 West, Gila and Salt River Meridian, Arizona.

The subdivisional lines of the township were surveyed by Charles M. Pidgeon in 1916.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated January 3, 1979 and the Second Supplemental Instructions dated December 10, 1979 for Group No. 611, Arizona.

The directions of lines were determined by direct solar observations and refer to the true meridian.

The survey was performed with a Zeiss SM 4 total station instrument.

The geographic position of the 1/4 sec. cor. of secs. 25 and 26, as scaled from U.S. Geological Survey Quadrangle Map, "Sam Powell Peak, Arizona," prepared in 1969, is as follows:

Latitude 34°05.6' N. Longitude 112°44.1' W.

The mean magnetic declination is 14°30' E.

Subdivision of Sec. 26, T. 9 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

Beginning at the 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, with brass cap mkd.

$\frac{1}{4}$ S26
S35
1916

N. 0°05' W., on the N and S center line of sec. 26.

Over rolling land, through medium creosote, palo verde, mesquite and cacti.

40.02 Point for the C 1/4 sec. cor., at intersection with the E and W center line of sec. 26.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

T9N R5W
C 1/4 S26
1979

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.

Cor. is located 50 lks. E of a wash, 50 lks. wide, 5 ft. deep, drains S. 20° W.

80.04 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., projecting 13 ins. above the ground, with brass cap mkd.

04

Subdivision of Section 26, T. 9 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS

$$\frac{1}{4} \frac{S23}{S26}$$

1916

Mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N of the cor.

From the $1/4$ sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., projecting 10 ins. above the ground, with brass cap mkd.

$$\frac{1}{4}$$

$$S26 | S25$$

1916

Mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of the cor.

S. $89^{\circ}59'$ W., on the E and W center line of sec. 26.

Over rolling land, through medium mesquite, creosote and palo verde.

- 9.20 Power line, bears N. 23° E. and S. 23° W.
- 20.30 Track road, bears N. 35° E. curving northerly and S. 35° W.
- 40.02 The C $1/4$ sec. cor. of sec. 26.
- 55.00 Track road, bears northerly and southerly.
- 80.06 The $1/4$ sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., projecting 11 ins. above the ground, with brass cap mkd.

$$\frac{1}{4}$$

$$S27 | S26$$

1916

Mound of stone, 3 ft. base $2\frac{1}{2}$ ft. high, W of the cor.

Subdivision of Section 29, T. 9 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

From the $1/4$ sec. cor. of secs. 29 and 32, monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, with brass cap mkd.

$$\frac{1}{4} \frac{S29}{S32}$$

1916

Mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, N of the cor.

N. $0^{\circ}04'$ W., on the N and S center line of sec. 29.

Over rolling land, through medium creosote, palo verde and cacti.

- 40.03 Point for the C $1/4$ sec. cor., at intersection with the E and W center line of sec. 29.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.

Subdivision of Section 29, T. 9 N., R. 5 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
80.04	<p style="text-align: center;">T9N R5W C 1/4 S29 1979</p> <p>Set a mesquite post, 4 ins. diam., 5 ft. long, alongside the cor.</p> <p>The 1/4 sec. cor. of secs. 20 and 29, monumented with an iron post, 1 in. diam., projecting 13 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S20 S29 1916</p>
40.01	<p>From the 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 1 in. diam., projecting 14 ins. above the gorund, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S29 S28 1916</p> <p>Mound of stone, 2 ft. base, 1½ ft. high, W of the cor. N. 89°57' W., on the E and W center line of sec. 29.</p> <p>Over rolling land, through medium creosote, palo verde, mesquite and cacti.</p>
80.00	<p>The C 1/4 sec. cor. of sec. 29.</p> <p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S30 S29 1916</p> <p>Mound of stone, 2 ft. base, 1½ ft. high, W of the cor.</p>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located approximately 8 miles southeast of Congress, Arizona. The general elevation ranges from about 2600 to 2800 ft. above sea level.</p> <p>Access is by way of track roads extending from Arizona State Highway No. 89.</p> <p>The vegetation consist of creosote, palo verde, mesquite and cacti.</p> <p>There is no evidence of mining activity at the present time.</p>

CHAINS		
--------	--	--

CERTIFICATE OF SURVEY

(I) ~~(XXX)~~ Paul L. Reeves, Cadastral Surveyor, HEREBY
 CERTIFY upon honor that, in pursuance of ^{second supplemental} ~~special instructions~~ bearing date of the 10th day
 of December, 1979, (I) ~~(XXX)~~ have subdivided sections 26 and 29,
 Township 9 North, Range 5 West,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~(XXX)~~ and under (my)
~~(XXX)~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

July 24, 1981

 (Date) Paul L. Reeves

 (Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the subdivision of sections 26 and 29,
Township 9 North, Range 5 West, Gila and Salt River Meridian, Arizona,

executed by Paul L. Reeves, Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.
 MAR 12 1982

 (Date) *Mary S. Spaight*

 (Date) **ACTING Chief, Cadastral Survey Examination and Approval Staff**

 (Date) (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

 (Date) _____

 (Date) (Chief, Cadastral Survey Examination and Approval Staff)